

Java Sequential SearchStreamGang

Example: Object-Oriented Implementation

Douglas C. Schmidt

d.schmidt@vanderbilt.edu

www.dre.vanderbilt.edu/~schmidt



Professor of Computer Science

**Institute for Software
Integrated Systems**


**Vanderbilt University
Nashville, Tennessee, USA**



Learning Objectives in this Lesson

- Know how to apply object-oriented features to the SearchStreamGang program

```
protected List<List<SearchResults>> processStream() {  
    List<List<SearchResults>> listOfListOfResults =  
        new ArrayList<>();  
  
    for (CharSequence inputSeq  
        : getInput())  
        listOfListOfResults  
            .add(processInput(inputSeq);  
  
    return listOfListOfResults;  
}
```




Starting SearchStreamGangTest
PARALLEL_SPLITTERATOR executed in 409 msec
COMPLETABLE_FUTURES_INPUTS executed in 426 msec
COMPLETABLE_FUTURES_PHASES executed in 427 msec
PARALLEL_STREAMS executed in 437 msec
PARALLEL_STREAM_PHASES executed in 440 msec
RXJAVA_PHASES executed in 485 msec
PARALLEL_STREAM_INPUTS executed in 802 msec
RXJAVA_INPUTS executed in 866 msec
SEQUENTIAL_LOOPS executed in 1638 msec
SEQUENTIAL_STREAM executed in 1958 msec
Ending SearchStreamGangTest

Learning Objectives in this Lesson

- Know how to apply object-oriented features to the SearchStreamGang program

```
protected List<List<SearchResults>> processStream() {  
    List<List<SearchResults>> listOfListOfResults =  
        new ArrayList<>();  
  
    for (CharSequence inputSeq  
        : getInput())  
        listOfListOfResults  
            .add(processInput(inputSeq);  
  
    return listOfListOfResults;  
}
```

LIMITED



Starting SearchStreamGangTest
PARALLEL_SPLITTERATOR executed in 409 msecs
COMPLETABLE_FUTURES_INPUTS executed in 426 msecs
COMPLETABLE_FUTURES_PHASES executed in 427 msecs
PARALLEL_STREAMS executed in 437 msecs
PARALLEL_STREAM_PHASES executed in 440 msecs
RXJAVA_PHASES executed in 485 msecs
PARALLEL_STREAM_INPUTS executed in 802 msecs
RXJAVA_INPUTS executed in 866 msecs
SEQUENTIAL_LOOPS executed in 1638 msecs
SEQUENTIAL_STREAM executed in 1958 msecs
Ending SearchStreamGangTest

Also understand the limitations with object-oriented programming..

An Object-Oriented Implementation of processStream()

Object-Oriented Implementation of `processStream()`

- `processStream()` sequentially searches for phrases in lists of input “strings”

```
protected List<List<SearchResults>> processStream() {
```

This method is not actually implemented with a stream..

```
List<List<SearchResults>> listOfListOfResults =  
    new ArrayList<>();
```

```
for (CharSequence inputSeq : getInput())  
    listOfListOfResults  
        .add(processInput(inputSeq));
```

```
return listOfListOfResults;  
}
```



See [livelessons/streamgangs/SearchWithSequentialLoops.java](https://livelessons.streamgangs.com/SearchWithSequentialLoops.java)

Object-Oriented Implementation of processStream()

- processStream() sequentially searches for phrases in lists of input “strings”

```
protected List<List<SearchResults>> processStream() {
```

Results are stored in a list of lists of search results

```
    List<List<SearchResults>> listOfListOfResults =  
        new ArrayList<>();
```

```
    for (CharSequence inputSeq : getInput())  
        listOfListOfResults  
            .add(processInput(inputSeq));
```

```
    return listOfListOfResults;
```

```
}
```

Object-Oriented Implementation of processStream()

- processStream() sequentially searches for phrases in lists of input "strings"



```
protected List<List<SearchResults>> processStream() {
```

Stores # of times a phrase appeared in an input string

```
List<List<SearchResults>> listOfListOfResults =  
    new ArrayList<>();
```

```
for (CharSequence inputSeq : getInput())  
    listOfListOfResults  
        .add(processInput(inputSeq));
```

```
return listOfListOfResults;  
}
```



See livelessons/utls/SearchResults.java

Object-Oriented Implementation of processStream()

- processStream() sequentially searches for phrases in lists of input “strings”


```
protected List<List<SearchResults>> processStream() {
```

Must remember to initialize this list or chaos & insanity will result..

```
List<List<SearchResults>> listOfListOfResults =  
    new ArrayList<>();
```

```
for (CharSequence inputSeq : getInput())  
    listOfListOfResults  
        .add(processInput(inputSeq));
```

```
return listOfListOfResults;  
}
```



Object-Oriented Implementation of processStream()


- processStream() sequentially searches for phrases in lists of input “strings”

```
protected List<List<SearchResults>> processStream() {
```

```
    List<List<SearchResults>> listOfListOfResults =  
        new ArrayList<>();
```

```
    for (CharSequence inputSeq : getInput())  
        listOfListOfResults  
            .add(processInput(inputSeq));
```

```
    return listOfListOfResults;  
}
```



*Explicitly loop thru all the
works of Shakespeare*

Object-Oriented Implementation of processStream()


- processStream() sequentially searches for phrases in lists of input "strings"

```
protected List<List<SearchResults>> processStream() {
```

```
    List<List<SearchResults>> listOfListOfResults =  
        new ArrayList<>();
```

```
    for (CharSequence inputSeq : getInput())  
        listOfListOfResults  
            .add(processInput(inputSeq));
```

```
    return listOfListOfResults;  
}
```



The `getInput()` method is defined in the `StreamGang` framework

Object-Oriented Implementation of processStream()

- processStream() sequentially searches for phrases in lists of input “strings”

```
protected List<List<SearchResults>> processStream() {
```

```
    List<List<SearchResults>> listOfListOfResults =  
        new ArrayList<>();
```

```
    for (CharSequence inputSeq : getInput())  
        listOfListOfResults  
            .add(processInput(inputSeq));
```

```
    return listOfListOfResults;  
}
```

*CharSequence optimizes
subSequence() to avoid memory
copies (cf. String substring())*

Object-Oriented Implementation of processStream()

- processStream() sequentially searches for phrases in lists of input “strings”

```
protected List<List<SearchResults>> processStream() {
```

```
    List<List<SearchResults>> listOfListOfResults =  
        new ArrayList<>();
```

```
    for (CharSequence inputSeq : getInput())  
        listOfListOfResults  
            .add(processInput(inputSeq));
```

```
    return listOfListOfResults;
```

```
}
```



Applying processInput() to each work

processInput() returns a list of SearchResults—one list for each input string

Object-Oriented Implementation of processStream()

- processStream() sequentially searches for phrases in lists of input “strings”

```
protected List<List<SearchResults>> processStream() {
```

```
    List<List<SearchResults>> listOfListOfResults =  
        new ArrayList<>();
```

```
    for (CharSequence inputSeq : getInput())  
        listOfListOfResults  
            .add(processInput(inputSeq));
```

```
    return listOfListOfResults;
```

```
}
```

Add the list of search results to the list of lists

Object-Oriented Implementation of processStream()

- processStream() sequentially searches for phrases in lists of input “strings”


```
protected List<List<SearchResults>> processStream() {
```

```
    List<List<SearchResults>> listOfListOfResults =  
        new ArrayList<>();
```

```
    for (CharSequence inputSeq : getInput())  
        listOfListOfResults  
            .add(processInput(inputSeq));
```

```
    return listOfListOfResults;
```

```
}
```



If `listOfListOfResults` isn't initialized properly chaos & insanity will result..

Object-Oriented Implementation of processStream()

- processStream() sequentially searches for phrases in lists of input “strings”

```
protected List<List<SearchResults>> processStream() {
```

```
    List<List<SearchResults>> listOfListOfResults =  
        new ArrayList<>();
```

```
    for (CharSequence inputSeq : getInput())  
        listOfListOfResults  
            .add(processInput(inputSeq));
```

```
    return listOfListOfResults;
```

```
}
```



Return the search results

Object-Oriented Implementation of processStream()

- processStream() sequentially searches for phrases in lists of input “strings”

```
protected List<List<SearchResults>> processStream() {
```

Indicates how many times a search phrase appeared in each input string

```
List<List<SearchResults>> listOfListOfResults =  
    new ArrayList<>();
```

```
for (CharSequence inputSeq : getInput())  
    listOfListOfResults  
        .add(processInput(inputSeq));
```

```
return listOfListOfResults;
```

```
}
```

Object-Oriented Implementation of processInput()

Object-Oriented Implementation of processInput()

- processInput() searches an input string for all occurrences of phrases to find

```
List<SearchResults> processInput(CharSequence inputSeq) {  
    String title = getTitle(inputSeq);  
    CharSequence input = inputSeq.  
        subSequence(title.length(), inputSeq.length());  
    List<SearchResults> listOfResults = new ArrayList<>();  
  
    for (String phrase : mPhrasesToFind) {  
  
        SearchResults res =  
            searchForPhrase(phrase, input, title);  
        if (res.size() > 0) listOfResults.add(res);  
    }  
    return listOfResults;  
}
```

Object-Oriented Implementation of processInput()

- processInput() searches an input string for all occurrences of phrases to find

```
List<SearchResults> processInput(CharSequence inputSeq) {  
    String title = getTitle(inputSeq);  
    CharSequence input = inputSeq.  
        subSequence(0, inputSeq.length());  
    List<SearchResults> listOfResults = new ArrayList<>();  
  
    for (String phrase : mPhrasesToFind) {  
  
        SearchResults res =  
            searchForPhrase(phrase, input, title);  
        if (res.size() > 0) listOfResults.add(res);  
    }  
    return listOfResults;  
}
```

*The input is a section of
a text file managed by
the test driver program*

Object-Oriented Implementation of processInput()

- processInput() searches an input string for all occurrences of phrases to find

```
List<SearchResults> processInput(CharSequence inputSeq) {  
    String title = getTitle(inputSeq);  
    CharSequence input = inputSeq.  
        subSequence(title.length(), inputSeq.length());  
    List<SearchResults> listOfResults = new ArrayList<>();  
  
    for (String phrase : mPhrasesToFind) {  
  
        SearchResults res =  
            searchForPhrase(phrase, input, title);  
        if (res.size() > 0) listOfResults.add(res);  
    }  
    return listOfResults;  
}
```

The input is split into two parts

Object-Oriented Implementation of processInput()

- processInput() searches an input string for all occurrences of phrases to find

```
List<SearchResults> processInput(CharSequence inputSeq) {  
    String title = getTitle(inputSeq);  
    CharSequence input = inputSeq.  
        subSequence(title.length(), inputSeq.length());  
    List<SearchResults> listOfResults = new ArrayList<>();  
  
    for (String phrase : mPhrasesToFind) {  
  
        SearchResults res =  
            searchForPhrase(phrase, input, title);  
        if (res.size() > 0) listOfResults.add(res);  
    }  
    return listOfResults;  
}
```

See [SearchStreamGang/src/main/java/livelessons/utils/SharedString.java](#)

Object-Oriented Implementation of processInput()

- processInput() searches an input string for all occurrences of phrases to find


```
List<SearchResults> processInput(CharSequence inputSeq) {  
    String title = getTitle(inputSeq);  
    CharSequence input = inputSeq.  
        subSequence(title.length(), inputSeq.length());  
    List<SearchResults> listOfResults = new ArrayList<>();  
  
    for (String phrase : mPhrasesToFind) {  
  
        SearchResults res =  
            searchForPhrase(phrase, input, title);  
        if (res.size() > 0) listOfResults.add(res);  
    }  
    return listOfResults;  
}
```

*Create empty list
to store results*

Object-Oriented Implementation of processInput()

- processInput() searches an input string for all occurrences of phrases to find

```
List<SearchResults> processInput(CharSequence inputSeq) {  
    String title = getTitle(inputSeq);  
    CharSequence input = inputSeq.  
        subSequence(title.length(), inputSeq.length());  
    List<SearchResults> listOfResults = new ArrayList<>();  
  
    for (String phrase : mPhrasesToFind) {  
  
        SearchResults res =  
            searchForPhrase(phrase, input, title);  
        if (res.size() > 0) listOfResults.add(res);  
    }  
    return listOfResults;  
}
```



Again, you must remember to initialize this list or chaos & insanity will result..

Object-Oriented Implementation of processInput()

- processInput() searches an input string for all occurrences of phrases to find

```
List<SearchResults> processInput(CharSequence inputSeq) {  
    String title = getTitle(inputSeq);  
    CharSequence input = inputSeq.  
        subSequence(title.length(), inputSeq.length());  
    List<SearchResults> listOfResults = new ArrayList<>();  
  
    for (String phrase : mPhrasesToFind) {  
        SearchResults res =  
            searchForPhrase(phrase, input, title);  
        if (res.size() > 0) listOfResults.add(res);  
    }  
    return listOfResults;  
}
```

Explicitly loop thru all phrases to search input

Object-Oriented Implementation of processInput()

- processInput() searches an input string for all occurrences of phrases to find

```
List<SearchResults> processInput(CharSequence inputSeq) {  
    String title = getTitle(inputSeq);  
    CharSequence input = inputSeq.  
        subSequence(title.length(), inputSeq.length());  
    List<SearchResults> listOfResults = new ArrayList<>();  
  
    for (String phrase : mPhrasesToFind) {  
        SearchResults res =  
            searchForPhrase(phrase, input, title);  
        if (res.size() > 0) listOfResults.add(res);  
    }  
    return listOfResults;  
}
```

Apply this function to all phrases in the input

Object-Oriented Implementation of processInput()

- processInput() searches an input string for all occurrences of phrases to find

```
List<SearchResults> processInput(CharSequence inputSeq) {  
    String title = getTitle(inputSeq);  
    CharSequence input = inputSeq.  
        subSequence(title.length(), inputSeq.length());  
    List<SearchResults> listOfResults = new ArrayList<>();  
  
    for (String phrase : mPhrasesToFind) {  
  
        SearchResults res =  
            searchForPhrase(phrase, input, title);  
        if (res.size() > 0) listOfResults.add(res);  
    }  
    return listOfResults;  
}
```

Explicitly check if results are non-empty

Object-Oriented Implementation of processInput()

- processInput() searches an input string for all occurrences of phrases to find

```
List<SearchResults> processInput(CharSequence inputSeq) {  
    String title = getTitle(inputSeq);  
    CharSequence input = inputSeq.  
        subSequence(title.length(), inputSeq.length());  
    List<SearchResults> listOfResults = new ArrayList<>();  
  
    for (String phrase : mPhrasesToFind) {  
  
        SearchResults res =  
            searchForPhrase(phrase, input, title);  
        if (res.size() > 0) listOfResults.add(res);  
    }  
    return listOfResults;  
}
```

*Add non-empty SearchResults
to the list of search results*

Object-Oriented Implementation of processInput()

- processInput() searches an input string for all occurrences of phrases to find

```
List<SearchResults> processInput(CharSequence inputSeq) {  
    String title = getTitle(inputSeq);  
    CharSequence input = inputSeq.  
        subSequence(title.length(), inputSeq.length());  
    List<SearchResults> listOfResults = new ArrayList<>();  
  
    for (String phrase : mPhrasesToFind) {  
  
        SearchResults res =  
            searchForPhrase(phrase, input, title);  
        if (res.size() > 0) listOfResults.add(res);  
    }  
    return listOfResults;  
}
```



There are control constructs in this code, which makes it harder to read!

Object-Oriented Implementation of processInput()

- processInput() searches an input string for all occurrences of phrases to find

```
List<SearchResults> processInput(CharSequence inputSeq) {  
    String title = getTitle(inputSeq);  
    CharSequence input = inputSeq.  
        subSequence(title.length(), inputSeq.length());  
    List<SearchResults> listOfResults = new ArrayList<>();  
  
    for (String phrase : mPhrasesToFind) {  
  
        SearchResults res =  
            searchForPhrase(phrase, input, title);  
        if (res.size() > 0) listOfResults.add(res);  
    }  
    return listOfResults;  
}
```

Return list result to processStream()

Object-Oriented Implementation of searchForPhrase()

Object-Oriented Implementation of searchForPhrase()

- searchForPhrase() uses a regex to find phrases in an input string

```
SearchResults searchForPhrase(String phr, String in, String ti){
    List<SearchResults.Result> results = new ArrayList<>();
    String regex = phr.trim()
        .replaceAll("\\s+", "\\s+")
        .replace("?", "\\?");

    Pattern pat = compile(regex, CASE_INSENSITIVE | DOTALL);
    Matcher match = pat.matcher(in);

    while (match.find()) results.add(new Result(match.start()));

    return new SearchResults(Thread.currentThread().getId(),
                               0, phr, ti, results); ...
}
```

Object-Oriented Implementation of searchForPhrase()

- searchForPhrase() uses a regex to find phrases in an input string

```
SearchResults searchForPhrase(String phr, String in, String ti){
```

```
    List<SearchResults.Result> results = new ArrayList<>();
```

```
    String regex = phr.trim()
```

```
        .replaceAll("\\s+", "\\|\\s+")
```

```
        .replace("?", "\\?");
```

Explicitly create an empty list to store search results

```
    Pattern pat = compile(regex, CASE_INSENSITIVE | DOTALL);
```

```
    Matcher match = pat.matcher(in);
```

```
    while (match.find()) results.add(new Result(match.start()));
```

```
    return new SearchResults(Thread.currentThread().getId(),  
                             0, phr, ti, results); ...
```


Object-Oriented Implementation of searchForPhrase()

- searchForPhrase() uses a regex to find phrases in an input string

```
SearchResults searchForPhrase(String phr, String in, String ti){  
    List<SearchResults.Result> results = new ArrayList<>();
```

```
    String regex = phr.trim()  
        .replaceAll("\\s+", "\\s+")  
        .replace("?", "\\?");
```

*Create regex to search for phrase
by collapsing extraneous whitespace
& quoting any/all question marks*

```
    Pattern pat = compile(regex, CASE_INSENSITIVE | DOTALL);  
    Matcher match = pat.matcher(in);
```

```
    while (match.find()) results.add(new Result(match.start()));
```

```
    return new SearchResults(Thread.currentThread().getId(),  
                             0, phr, ti, results); ...
```

Object-Oriented Implementation of searchForPhrase()

- searchForPhrase() uses a regex to find phrases in an input string

```
SearchResults searchForPhrase(String phr, String in, String ti){  
    List<SearchResults.Result> results = new ArrayList<>();  
    String regex = phr.trim()  
        .replaceAll("\\s+", "\\s+")  
        .replace("?", "\\?");
```

Compile the regex

```
    Pattern pat = compile(regex, CASE_INSENSITIVE | DOTALL);  
    Matcher match = pat.matcher(in);
```

```
    while (match.find()) results.add(new Result(match.start()));
```

```
    return new SearchResults(Thread.currentThread().getId(),  
                             0, phr, ti, results); ...
```

See docs.oracle.com/javase/8/docs/api/java/util/regex/Pattern.html

Object-Oriented Implementation of searchForPhrase()

- searchForPhrase() uses a regex to find phrases in an input string

```
SearchResults searchForPhrase(String phr, String in, String ti){
```

```
    List<SearchResults.Result> results = new ArrayList<>();
```

```
    String regex = phr.trim()
```

```
        .replaceAll("\\s+", "\\s+")
```

```
        .replace("?", "\\?");
```

```
    Pattern pat = compile(regex, CASE_INSENSITIVE | DOTALL);
```

```
    Matcher match = pat.matcher(in);
```

Create a matcher

```
    while (match.find()) results.add(new Result(match.start()));
```

```
    return new SearchResults(Thread.currentThread().getId(),  
                             0, phr, ti, results); ...
```

See docs.oracle.com/javase/8/docs/api/java/util/regex/Matcher.html

Object-Oriented Implementation of searchForPhrase()

- searchForPhrase() uses a regex to find phrases in an input string

```
SearchResults searchForPhrase(String phr, String in, String ti){  
    List<SearchResults.Result> results = new ArrayList<>();  
    String regex = phr.trim()  
        .replaceAll("\\s+", "\\s+")  
        .replace("?", "\\?");
```

```
    Pattern pat = compile(regex, CASE_INSENSITIVE | DOTALL);  
    Matcher match = pat.matcher(in);
```

Explicitly loop thru all regex matches

```
    while (match.find()) results.add(new Result(match.start()));
```

```
    return new SearchResults(Thread.currentThread().getId(),  
                             0, phr, ti, results); ...
```

Object-Oriented Implementation of searchForPhrase()

- searchForPhrase() uses a regex to find phrases in an input string

```
SearchResults searchForPhrase(String phr, String in, String ti){  
    List<SearchResults.Result> results = new ArrayList<>();  
    String regex = phr.trim()  
        .replaceAll("\\s+", "\\s+")  
        .replace("?", "\\?");
```

```
    Pattern pat = compile(regex, CASE_INSENSITIVE | DOTALL);  
    Matcher match = pat.matcher(in);
```

Explicitly add starting index of all regex matches

```
    while (match.find()) results.add(new Result(match.start()));  
  
    return new SearchResults(Thread.currentThread().getId(),  
                             0, phr, ti, results); ...
```

Object-Oriented Implementation of searchForPhrase()

- searchForPhrase() uses a regex to find phrases in an input string

```
SearchResults searchForPhrase(String phr, String in, String ti){  
    List<SearchResults.Result> results = new ArrayList<>();  
    String regex = phr.trim()  
        .replaceAll("\\s+", "\\s+")  
        .replace("?", "\\?");  
  
    Pattern pat = compile(regex, CASE_INSENSITIVE | DOTALL);  
    Matcher match = pat.matcher(in);  
  
    while (match.find()) results.add(new Result(match.start()));  
  
    return new SearchResults(Thread.currentThread().getId(),  
                                0, phr, ti, results); ...  
}
```

Return search results to processInput()

End of Java Sequential SearchStreamGang Example: Object-Oriented Implementation