

Java Streams: Overview of Aggregate Operations

Douglas C. Schmidt

d.schmidt@vanderbilt.edu

www.dre.vanderbilt.edu/~schmidt

Professor of Computer Science


**Institute for Software
Integrated Systems**

**Vanderbilt University
Nashville, Tennessee, USA**



Learning Objectives in this Part of the Lesson

- Understand the structure & functionality of stream aggregate operations



Overview of Stream Aggregate Operations

Overview of Stream Aggregate Operations

- An aggregate operation is a higher-order function that applies a "behavior" on elements in a stream



A "higher order function" is a function that is passed a function as a param



Input x

Aggregate operation (Behavior f)



Output $f(x)$

Aggregate operation (Behavior g)



Output $g(f(x))$


Aggregate operation (Behavior h)

Output $h(g(f(x)))$

See [en.wikipedia.org/wiki/Higher-order function](https://en.wikipedia.org/wiki/Higher-order_function)


Overview of Stream Aggregate Operations

- An aggregate operation is a higher-order function that applies a “behavior” on elements in a stream



Overview of Stream Aggregate Operations

- An aggregate operation is a higher-order function that applies a “behavior” on elements in a stream



Input x

Aggregate operation (Behavior f)



Output $f(x)$

Aggregate operation (Behavior g)



Output $g(f(x))$

Aggregate operation (Behavior h)

Output $h(g(f(x)))$

Overview of Stream Aggregate Operations

- There are two types of aggregate operations



Input x

Intermediate operation (Behavior f)



Output $f(x)$

Intermediate operation (Behavior g)




Output $g(f(x))$

Terminal operation (Behavior h)

Overview of Stream Aggregate Operations

- There are two types of aggregate operations
 - **Intermediate operations**
 - Process elements in their input stream & yield an output stream
 - e.g., filter(), map(), flatMap(), takeWhile(), dropWhile(), etc.



Overview of Stream Aggregate Operations

- There are two types of aggregate operations

- Intermediate operations**

- Process elements in their input stream & yield an output stream
- e.g., `filter()`, `map()`, `flatMap()`, `takeWhile()`, `dropWhile()`, etc.


```
long HamletCharacters = Stream
    .of("horatio", "laertes",
        "Hamlet", ...)
    .count();
```



Input x

OPTIONAL

Intermediate operations are optional



Terminal operation (Behavior h)

Overview of Stream Aggregate Operations

- There are two types of aggregate operations

- Intermediate operations**

- Process elements in their input stream & yield an output stream
- Intermediate operations can be further classified via several dimensions

	Run-to-completion	Short-Circuiting
Stateful	distinct(), skip(), sorted()	limit(), takeWhile(), dropWhile(), etc.
Stateless	filter(), map(), flatMap(), etc.	N/A

Overview of Stream Aggregate Operations

- There are two types of aggregate operations

- Intermediate operations**

- Process elements in their input stream & yield an output stream
- Intermediate operations can be further classified via several dimensions, e.g.
 - Stateful
 - Store info from a prior invocation for use in a future invocation



	Run-to-completion	Short-Circuiting
Stateful	distinct(), skip(), sorted()	limit(), takeWhile(), dropWhile(), etc.
Stateless	filter(), map(), flatMap(), etc.	N/A

Overview of Stream Aggregate Operations

- There are two types of aggregate operations

- Intermediate operations**

- Process elements in their input stream & yield an output stream
- Intermediate operations can be further classified via several dimensions, e.g.
 - Stateful
 - Stateless
 - Do not store info from any prior invocations



	Run-to-completion	Short-Circuiting
Stateful	distinct(), skip(), sorted()	limit(), takeWhile(), dropWhile(), etc.
Stateless	filter(), map(), flatMap(), etc.	N/A

See javapapers.com/java/java-stream-api

Overview of Stream Aggregate Operations

- There are two types of aggregate operations

- Intermediate operations**

- Process elements in their input stream & yield an output stream
- Intermediate operations can be further classified via several dimensions, e.g.
 - Stateful
 - Stateless
 - Run-to-completion
 - Process all elements in the input stream

	Run-to-completion	Short-Circuiting
Stateful	distinct(), skip(), sorted()	limit(), takeWhile(), dropWhile(), etc.
Stateless	filter(), map(), flatMap(), etc.	N/A



See en.wikipedia.org/wiki/Run_to_completion_scheduling

Overview of Stream Aggregate Operations

- There are two types of aggregate operations

- Intermediate operations**

- Process elements in their input stream & yield an output stream
- Intermediate operations can be further classified via several dimensions, e.g.
 - Stateful
 - Stateless
 - Run-to-completion
 - Short-circuiting
 - Make stream operate on a reduced size



	Run-to-completion	Short-Circuiting
Stateful	distinct(), skip(), sorted()	limit(), takeWhile(), dropWhile(), etc.
Stateless	filter(), map(), flatMap(), etc.	N/A

Overview of Stream Aggregate Operations

- There are two types of aggregate operations

- Intermediate operations**

- Terminal operations**

- Trigger intermediate operations & produce a non-stream result
 - e.g., `forEach()`, `reduce()`, `collect()`, `findAny()`, etc.



*One terminal operation
is mandatory in a stream*



Input x

Intermediate operation (Behavior f)



Output $f(x)$

Intermediate operation (Behavior g)



Output $g(f(x))$

Terminal operation (Behavior h)

Overview of Stream Aggregate Operations

- There are two types of aggregate operations

- **Intermediate operations**

- **Terminal operations**

- Trigger intermediate operations & produce a non-stream result
- Terminal operations can also be classified via several dimensions

Operation Type	Examples
Run-to-completion	reduce(), collect(), forEach(), etc.
Short-circuiting	allMatch(), anyMatch(), findAny(), findFirst(), noneMatch()

Overview of Stream Aggregate Operations

- There are two types of aggregate operations

- Intermediate operations**

- Terminal operations**

- Trigger intermediate operations & produce a non-stream result
- Terminal operations can also be classified via several dimensions, e.g.
 - Run-to-completion
 - Terminate only after processing all elements in the stream

Operation Type	Examples
Run-to-completion	<code>reduce()</code> , <code>collect()</code> , <code>forEach()</code> , etc.
Short-circuiting	<code>allMatch()</code> , <code>anyMatch()</code> , <code>findAny()</code> , <code>findFirst()</code> , <code>noneMatch()</code>



Overview of Stream Aggregate Operations

- There are two types of aggregate operations

- Intermediate operations**

- Terminal operations**

- Trigger intermediate operations & produce a non-stream result
- Terminal operations can also be classified via several dimensions, e.g.
 - Run-to-completion
 - Short-circuiting
 - May cause a stream to terminate before processing all values

Operation Type	Examples
Run-to-completion	reduce(), collect(), forEach(), etc.
Short-circuiting	allMatch(), anyMatch(), findAny(), findFirst(), noneMatch()



End of Java Streams: Overview of Aggregate Operations