

Java Streams: Terminal Operations

Douglas C. Schmidt

d.schmidt@vanderbilt.edu

www.dre.vanderbilt.edu/~schmidt

Professor of Computer Science


**Institute for Software
Integrated Systems**

**Vanderbilt University
Nashville, Tennessee, USA**




Learning Objectives in this Part of the Lesson

- Understand the structure & functionality of stream aggregate operations
 - Intermediate operations
 - Terminal operations



Learning Objectives in this Part of the Lesson


- Understand the structure & functionality of stream aggregate operations
 - Intermediate operations
 - Terminal operations




These operations also apply to both sequential & parallel streams

Learning Objectives in this Part of the Lesson

- Understand the structure & functionality of stream aggregate operations
 - Intermediate operations
 - Terminal operations



We continue to showcase the SimpleSearchStream program




Overview of Terminal Operations

Overview of Common Stream Terminal Operations

- Every stream finishes with a terminal operation that yields a non-stream result

Stream

```
.of("horatio",  
    "laertes",  
    "Hamlet", ...)  
.filter(s -> toLowerCase  
           (s.charAt(0)) == 'h')  
.map(this::capitalize)  
.sorted()  
.forEach(System.out::println);
```



Overview of Common Stream Terminal Operations

- Every stream finishes with a terminal operation that yields a non-stream result, e.g.
 - No value at all
 - e.g., `forEach()` & `forEachOrdered()`

`forEach()` only has side-effects!



Overview of Common Stream Terminal Operations

- Every stream finishes with a terminal operation that yields a non-stream result, e.g.

- No value at all

- e.g., `forEach()` & `forEachOrdered()`

Stream

```
.of("horatio",  
    "laertes",  
    "Hamlet", ...)  
.filter(s -> toLowerCase  
           (s.charAt(0)) == 'h')  
.map(this::capitalize)  
.sorted()  
.forEach  
  (System.out::println);
```

Print each character in Hamlet that starts with 'H' or 'h' in consistently capitalized & sorted order.

Overview of Common Stream Terminal Operations

- Every stream finishes with a terminal operation that yields a non-stream result, e.g.
 - No value at all
 - The result of a reduction operation
 - e.g., `collect()` & `reduce()`




See docs.oracle.com/javase/tutorial/collections/streams/reduction.html

Overview of Common Stream Terminal Operations

- Every stream finishes with a terminal operation that yields a non-stream result, e.g.
 - No value at all
 - The result of a reduction operation
 - e.g., `collect()` & `reduce()`


`collect()` & `reduce()` terminal operations work seamlessly with parallel streams.



See docs.oracle.com/javase/tutorial/collections/streams/parallelism.html

Overview of the collect() Terminal Operation

- A terminal operation also triggers all the intermediate operation processing





Overview of the collect() Terminal Operation

Overview of the collect() Terminal Operation

- Overview of the collect() terminal operation

This terminal operation uses a collector to perform a reduction on the elements of its input stream & returns the results of the reduction.





See docs.oracle.com/javase/8/docs/api/java/util/stream/Stream.html#collect

Overview of the collect() Terminal Operation

- Overview of the collect() terminal operation

Triggers intermediate operation processing.




Overview of the collect() Terminal Operation

- Overview of the collect() terminal operation

Create a list of non-empty SearchResults.

```
List<SearchResults> results =  
wordsToFind  
    .stream()  
    .map(this::searchForWord)  
    .filter(not  
        (SearchResults::isEmpty))  
    .collect(toList());
```



The list returned from collect() presents search results in "encounter order"

End of Java Streams: Terminal Operations