# Java Parallel Streams Internals: Order of Processing

Douglas C. Schmidt
<a href="mailto:d.schmidt@vanderbilt.edu">d.schmidt@vanderbilt.edu</a>
www.dre.vanderbilt.edu/~schmidt



**Professor of Computer Science** 

**Institute for Software Integrated Systems** 

Vanderbilt University Nashville, Tennessee, USA




### Learning Objectives in this Part of the Lesson

- Understand parallel stream internals, e.g.
  - Know what can change & what can't
    - Splitting, combining, & pooling mechanisms
    - Order of processing




• The *order* in which chunks in a parallel stream are processed is non-deterministic






See en.wikipedia.org/wiki/Nondeterministic\_algorithm

 The *order* in which chunks in a parallel stream are processed is non-deterministic






The ordering can exhibit different behaviors on different runs, even for the same input


- The *order* in which chunks in a parallel stream are processed is non-deterministic
  - Programmers have little/no control over how chunks are processed





- The *order* in which chunks in a parallel stream are processed is non-deterministic
  - Programmers have little/no control over how chunks are processed
  - Non-determinism enables optimizations at multiple layers!






e.g., scheduling & execution of tasks via fork-join pool, JVM, hardware cores, etc.

- The *order* in which chunks in a parallel stream are processed is non-deterministic
  - Programmers have little/no control over how chunks are processed
  - Non-determinism enables optimizations at multiple layers!

e.g., fork-join framework's support for workstealing is a non-deterministic optimization



Fork-Join Pool

See upcoming lessons on "The Java Fork-Join Framework"

# End of Java Parallel Stream Internals: Order of Processing