

Introduction to Cryptography

Manuel – Summer 2021

Notes

---

---

---

---

---

---

---

---

---

---

Table of contents

Chapter 0:	Course information .....	1	(3)
Chapter 1:	Cryptology overview .....	5	(20)
Chapter 2:	Block ciphers .....	21	(83)
Chapter 3:	Public Key Cryptography .....	34	(135)
Chapter 4:	Hash functions .....	56	(221)
Chapter 5:	Digital signatures .....	64	(254)
Chapter 6:	Secret sharing .....	72	(288)
Chapter 7:	Traitor tracing .....	77	(308)
Chapter 8:	Elliptic Curve Cryptography .....	84	(335)
Chapter 9:	Quantum Cryptography .....	91	(361)
Chapter 10:	Side channel attacks .....	98	(391)

Notes

---

---

---

---

---

---

---

---

---

---

# 0. Course information

Notes

---

---

---

---

---


---

---

---

---

---



Notes

---

---

---

---

---

---

---

---

---

---

5

Basic information

Teaching team:

- Instructor: Manuel (charlem@sjtu.edu.cn)
- Teaching assistants:
  - Hanyu (whynull@sjtu.edu.cn)
  - Yichao (wangyichao1304@sjtu.edu.cn)

Important rules:

- When contacting a TA for an important matter, cc the instructor
- Add the tag [VE475] to the subject, e.g. Subject: [VE475] Grades
- Use SJTU jBox service to share large files (> 2 MB)

Never send large files by email

Notes

---

---

---

---

---

---

---

---

---

---

6

Course schedule

Course arrangements:

- Lectures:
  - Tuesday 14:00 – 15:40
  - Thursday 14:00 – 15:40
  - Friday 12:10 – 13:50 (even weeks)
- Office hours:
  - Anytime (Piazza)
  - On appointment (Zoom)

Notes

---

---

---

---

---

---

---

---

---

---

7

Course objectives

Primary goals:

- Understand the basics of cryptology and security
- Become familiar with the most common cryptographic protocols
- Be able to relate theory and practice in cryptology

*Decide on the validity and security of given cryptographic solutions*

Notes

---

---

---

---

---

---

---

---

---

---

8

Course workflow

Learning strategy:

- Course side:
  - ① Understand the basic concepts of cryptography
  - ② Know the most common problems and their solutions
  - ③ Get an overview of many subfields of cryptography
- Personal side:
  - ① Perform extra research
  - ② Relate known strategies to new problems
  - ③ Read and write some code

Notes

---

---

---

---

---

---

---

---

---

---

9
Course outcomes

Detailed goals:

- Know the most common symmetric key cryptography protocols
- Know the most common public key cryptography protocols
- Understand the importance of true randomness in cryptography
- Understand the basics on hash functions in cryptography
- Know the various security levels and be able to derive their corresponding key length depending on the most efficient attacks available
- Know the basic algorithms to solve real life problems such as digital signatures, secret sharing, or traitor tracing
- Be able to perform basic programming in a cryptographic context, i.e. using large numbers or low level logical operations
- Get a high level overview of the various sub-fields of cryptography
- Understand the mathematics used in cryptography

Notes

---

---

---

---

---


---

---

---

---

---



Notes

---

---

---

---

---

---

---

---

---

---

11
Assignments

Homework:

- Total: 10
- Content: basic concepts, coding, mathematics

Projects:

- Total: 2
- Content: discover new areas of cryptology

Challenges:

- Total: 3
- Content: code breaking

Notes

---

---

---

---

---

---

---

---

---

---

12
Grading policy

Grade weighting:

- Homework: 15%
- Projects: 25%
- Final exam: 30%
- Midterm exam: 30%

Assignment submissions:

- Bonus: +10% for a work fully written in  $\text{\LaTeX}$ , limited to 100%
- Penalty: -10% for a work not written in a neat and legible fashion
- Late policy: -10% per day, not accepted after three days

*Grades will be curved with the median in the range  $\llbracket B, B+ \rrbracket$*

Notes

---

---

---

---

---

---

---

---

---

---

13

Honor code

General rules:

- Not allowed:
  - Reuse the code or work from other students or groups
  - Reuse the code or work from the internet
  - Share too many details on how to complete a task
- Allowed:
  - Reuse part the course or textbooks and quoting the source
  - Share ideas and understandings on the course
  - Provide hints on where or how to find information

Notes

14

Honor Code

Documents allowed during the exams:

- Part A: a mono or bilingual dictionary
- Part B:
  - The lecture slides with **notes on them** (paper or electronic)
  - A mono or bilingual dictionary

Group works:

- Every student in a group is responsible for his group's submission
- If a student breaks the Honor Code, the whole group is guilty

Notes

15

Special circumstances

Contact us as early as possible when:

- Facing special circumstances, e.g. full time work, illness
- Feeling late in the course
- Feeling to work hard without any result

Any late request will be rejected

Notes

16

Chapter organisation

```
graph TD; CI((Course information)) --- E((Evaluations)); CI --- L((Logistics)); CI --- R((Resources));
```

Notes

17

Canvas

Information and documents available on the Canvas platform:

- Course materials:
  - Syllabus
  - Lecture slides
  - Homework
  - Projects
  - Challenges
- Course information:
  - Announcements
  - Notifications
  - Grades
  - Polls

Notes

18

References

Useful places where to find information:

- Introduction to Modern Cryptography* (J. Katz and Y. Lindell)
- Cryptography, theory and practice* (D. Stinson)
- Search information online, i.e.  $\{websites \setminus \{non-English\} websites\}$

Notes

19


Key points

- Work regularly, do not wait the last minute/day
- Respect the Honor Code
- Go beyond what is taught
- Do not learn, understand
- Keep in touch with us
- Advice and suggestions are always much appreciated

Notes

# 1. Cryptology overview

Notes



Notes

---

---

---

---

---

---

---

---

Are you following the right course?

Notes

---

---

---


---

---

---

---

---



Notes

---

---

---


---

---

---

---

---



Notes

---

---

---

---

---

---

---

---

25
A brief history of cryptology – Early times

Cryptology as an old science:

- 1500 Mesopotamia: earliest known use
- 700 Greeks: military applications
- 500 Common among Hebrew scholars
- 100 Romans
- 800 Arabs: document cryptanalysis methods

Advantage was on the side of cryptanalysts

Notes

26
A brief history of cryptology – Until World War II

No major advances until World War I:

- 1914 Basic and insecure encryption methods
- 1917 Discovery of an unbreakable cipher
- 1920 Development of electromechanical devices
- 1929 First usage of mathematics
- 1939 Major breakthroughs

Advantage is still on the side of cryptanalysts

Notes

27
A brief history of cryptology – Modern times

Mathematics becomes the heart of cryptography:

- 1949 Shannon: secrecy et authenticity
- 1976 Diffie et Hellman: public key cryptography
- 1990 Internet popularize the use of cryptography
- 2017 Cryptology is everywhere

Politics try to kill cryptography and give governments the monopoly

Notes

28
Basic communication scenario

```

graph LR
    Alice[Alice] -- Plaintext --> Encrypt[Encrypt]
    Key1[Encryption key] --> Encrypt
    Encrypt -- Ciphertext --> Decrypt[Decrypt]
    Key2[Decryption key] --> Decrypt
    Decrypt -- Plaintext --> Bob[Bob]
    Eve[Eve] --> Ciphertext
  
```

Notes

29
Eve's goals

Eve has one of the following goals:

- Read a message
- Find the key
- Corrupt Alice's message
- Masquerade as Alice

Notes

30
Eve's strategy

There are the five main types of attacks:

- Eve only has a copy of the ciphertext: *ciphertext only*
- Eve has a copy of the ciphertext but also of the corresponding plaintext: *Known Plaintext Attack (KPA)*
- Eve chooses the plaintext to be encrypted: *Chosen Plaintext Attack (CPA)*
- Eve chooses the ciphertext to be decrypted: *Chosen Ciphertext Attack (CCA)*
- Eve chooses any plaintext to be encrypted or ciphertext to be decrypted: *Chosen Plaintext and Ciphertext Attack (CPCA)*

Notes

31
Eve's strategy

Notes

32
Eve's strategies

Methods to collect data:

- On fiber cables and infrastructures as the flow passes
- From the servers of service providers

Methods to retrieve encrypted data:

- Break the encryption
- Influence industrial standards
- Pressure manufacturers to make insecure devices
- Infiltrate hardware and software

Notes



33
Who is Eve and why is she evil?

Eve is anyone that might want to read or temper the data:

- Low threat: friends, family members, etc.
- High threat: governmental agencies and companies

Reasons for mass surveillance:

- Combat terrorism
- Assess foreign policies and economical stability
- Gather commercial secrets

Notes

34
Why fear Eve?

What does your phone know about you?

*“They (the NSA) can use the system to go back in time and scrutinize every decision you’ve ever made, every friend you’ve ever discussed something with, and attack you on that basis to sort of derive suspicion from an innocent life and paint anyone in the context of a wrongdoer.”*

Edward Snowden

Notes

35
Kerckhoffs’ principle

Principle (Kerckhoffs’ principle)

A cryptosystem should be secure even if everything about the system, except the key, is public knowledge.

In other words:

- Security through obscurity is not security
- Data should be encrypted using standard, publicly known algorithms
- The implementation must be accessible to all

Notes


36
Chapter organisation

```

graph TD
    A((Cryptography overview)) --- B((Classical cryptology))
    A --- C((A first glimpse at cryptology))
    A --- D((Modern cryptology))

```

Notes



Simple description:

- One of the earliest cipher
- Attributed to Julius Caesar
- Letters are shifted by a given number of places
- The shift is called the *key* of the cipher

Exercise. Recover the plaintext given the ciphertext JRRGPRUQLQJ

## Notes

### Definitions

- 1 Let  $a$  and  $b$  be two integers, with  $a \neq 0$ . We say that  $a$  divides  $b$  if there exists an integer  $k$  such that  $b = ak$ , and we denote it  $a|b$ .
- 2 Let  $a$ ,  $b$  and  $n$  be three integers with  $n \neq 0$ . We say that  $a$  is congruent to  $b$  modulo  $n$ , if  $n$  divides  $a - b$ . It is denoted  $a \equiv b \pmod{n}$

In modern cryptography:

- The plaintext is first converted into a numerical value
- If the alphabet is composed of  $n$  symbols then each one is assigned a value between 0 and  $n - 1$

## Notes

Caesar cipher in mathematical terms:

- 1 Label letters as integers from 0 to 25
- 2 Choose a key  $\kappa$  in the range 0 – 25
- 3 Encrypt using the function  $x \mapsto x + \kappa \pmod{26}$
- 4 Decrypt using the function  $x \mapsto x - \kappa \pmod{26}$
- 5 Label integers from 0 to 25 as letters

Exercise. Encrypt and decrypt “students are working hard” using Caesar cipher with the key  $\kappa = -5$

## Notes

Using the different types of attacks:

- Ciphertext only: only 26 possible keys  $\Rightarrow$  exhaustive search
- KPA: deduce the key from the plaintext/ciphertext pair
- CPA: for the plaintext “a”, the ciphertext gives  $\kappa$
- CCA: for the ciphertext “A”, the plaintext gives  $-\kappa \pmod{26}$

## Notes


In 1776 Thomas Jefferson sent a message to Benjamin Franklin:

LWNSOZBNWVWBAYBNVBSQWVUOHWDIZWRBPNBPPOUWRPAWX  
 AWPBWZWMYPOBNPBBNWJPAWWRZSLWZQJBNVIAWAPBSALIBNX  
 WABPIRYRPOIWRPQOWAIENBVBNBPUSREBNVWPAWOIHWOIQW  
 ABJPRZBNWFYAVYIBSHNPFIRWVVBPNBBSVWXYAWBNVWVAIENB  
 VESDWARUWRBPAWIRVBIBYBWZPUSREUWRZWADIREBHWIATYVB  
 FSLWAVHASUBNWXSRVWRBSHBOTESDWARWZBNPBLNWWWDWAPRJ  
 HSAUSHEDWARUWRBQWXSUVWZVWBAYXBIDWSHBNVWVWRZVIB  
 IVBNVAIENBSHBNWFWFSOWBSPOBWASABSPQSOIVNIBPRZBSIRVBI  
 BYBWRWLESDWARUWRBOPJIREIBVHSYRZPBISRSRVYXNFAIRXIFOO  
 TPRZSAEPRIKIREIBVFSWLAVIRVYXNHSAPVBSVVMJSVBOICWOJBS  
 WHHWXBBNWIAPVHBJPRZNPFFIRWW

*Your job is to decipher it*

## Notes

## Letters distribution in English



## Notes

## Decrypting the message – Monograms

For the 10 most common letters their count gives:

W	B	R	S	I	V	A	P	N	O
76	64	39	36	36	35	34	32	30	16

We can guess:

- W is probably e
- B, R, S, I, V, A, P, and N are probably t, a, o, i, n, s, h, and r
- But what is their order?

## Notes

## Decrypting the message – Digrams

## Digrams count

## Rules in English

	W	B	R	S	I	V	A	P	N
W	3	4	12	2	4	10	14	3	1
B	4	4	0	11	5	5	2	4	20
R	5	5	0	1	1	5	0	3	0
S	1	0	5	0	1	3	5	2	0
I	1	8	10	1	0	2	3	0	0
V	8	10	0	0	2	2	0	3	1
A	7	3	4	2	5	4	0	1	0
P	0	8	6	0	1	1	4	0	0
N	14	3	0	1	1	1	0	7	0

- e contacts most of other letters
- a, i, o tend to avoid each other
- 80% of the letters preceding n are vowels
- the most common digram is th
- h often appears before e, rarely after
- r pairs more with vowels and s with consonants
- rn more common than nr and to than ot

## Notes

Summarizing all the guesses and carrying on:

L	W	N	S	O	Z	B	N	W	V	W	B	A	Y
<b>W</b>	<b>E</b>	<b>h</b>	<b>O</b>	<b>I</b>	<b>S</b>	<b>Q</b>	<b>h</b>	<b>O</b>	<b>E</b>	<b>H</b>	<b>t</b>	<b>r</b>	<b>u</b>
t	h	s	t	O	<b>b</b>	e	V	W	I	f	W	D	i
Z	W	R	B	S	b	P	s	P	...		e	v	
d	E	n	t	t	n	a	t	a					

## Notes

[illegible]

The deciphered text is from the Declaration of independence:

we hold these truths to be self evident that all men are created equal that they are endowed by their creator with certain unalienable rights that among these are life liberty and the pursuit of happiness that to secure these rights governments are instituted among men deriving their just powers from the consent of the governed that whenever any form of government becomes destructive of these ends it is the right of the people to alter or to abolish it and to institute new government laying its foundation on such principles and organizing its powers in such form as to seem most likely to effect their safety and happiness

## Notes

[illegible]

a b c d e f g h i k l m n o p q r s t u x y z  
 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 10

Nulles     $\mathbb{f}\mathbb{f} \vdash \_ \mathbb{d}$                       Dowbleth     $\sigma$

and for with that if but where as of the from by  
2 3 4 4 4 3 7 11 11 8 11 10

so not when there this in wich is what say me my wyrt  
 ʒ x ʥ ʥ ʒ x ʒ ʒ ʒ ʒ ʒ

send lře receive bearer I pray you Mte your name myne

## Notes

[illegible]

### Using the One Time Pad:

- 1 Represent the message as a sequence of 0s and 1s of length  $l$
- 2 Generate a key of length  $l$  and composed of 0s and 1s
- 3 XOR the message and the key



## Breaking the One Time Pad:

- Ciphertext only: all the messages of same length have equal probability
- KPA, CPA, CCA: only reveal part of the key used during the attack

## Notes

[illegible]

A *block cipher* encrypts several letters at once:

- Changing one letter in the plaintext impacts several letters in the ciphertext
- Frequency analysis of letters and digrams cannot be applied

Hill cipher:

- Invented in 1929
- One of the first cipher to use algebraic methods
- Never been used much in practice

### Definition

The *greatest common divisor* of two integers  $a$  and  $b$ , with  $|a| + |b| \neq 0$ , is the largest positive integer dividing both  $a$  and  $b$ . It is noted  $\gcd(a, b)$ , and  $a$  and  $b$  are said to be *coprime* if  $\gcd(a, b) = 1$ .

In fact  $\gcd(a, b)$  can be expressed as a linear combination of  $a$  and  $b$  with integer coefficients.

### Lemma (Bézout's identity)

Let  $a$  and  $b$  be two integers where at least one of them is not zero, and  $d = \gcd(a, b)$ . Then there exists two integers  $s$  and  $t$ , called *Bézout coefficients*, such that  $as + bt = d$ .

Algorithm. (*Extended Euclidean Algorithm*)

**Input** :  $a, b$ , two positive integers

**Out-**  $r_1 = \gcd(a, b)$  and  $\langle s_1, t_1 \rangle$ , Bézout coefficients

**put** :

```

1  $r_0 \leftarrow b; r_1 \leftarrow a;$ 
2  $s_0 \leftarrow 0; s_1 \leftarrow 1;$ 
3  $t_0 \leftarrow 1; t_1 \leftarrow 0;$ 
4 while  $r \neq 0$  do
5    $q \leftarrow r_1 \text{ div } r_0;$ 
6    $\langle r_1, r_0 \rangle \leftarrow \langle r_0, r_1 - qr_0 \rangle;$ 
7    $\langle s_1, s_0 \rangle \leftarrow \langle s_0, s_1 - qs_0 \rangle;$ 
8    $\langle t_1, t_0 \rangle \leftarrow \langle t_0, t_1 - qt_0 \rangle;$ 
9 end while
10 return  $r_1, \langle s_1, t_1 \rangle$ 
```

### Proposition

Let  $a$  and  $n$  be two coprime integers and  $s$  and  $t$  be such that  $as + nt = 1$ . Then  $as \equiv 1 \pmod{n}$ , and  $s$  is called the *multiplicative inverse* of  $a$  modulo  $n$ . Besides  $s$  is unique.

Example. What is the multiplicative inverse of 11111 modulo 12345?

Running the extended Euclidean algorithm confirms that 11111 and 12345 are coprime and therefore 11111 is invertible modulo 12345. Moreover since

$$11111 \cdot 2471 + 12345 \cdot (-2224) = 1,$$

we conclude that  $11111 \cdot 2471 \equiv 1 \pmod{12345}$ .

**Theorem (Cramer's rule)**

Let  $A$  be an  $m \times m$  matrix, then

$$\text{Adj}(A) \cdot A = \det(A) I_m, \quad (1.1)$$

where  $\text{Adj}(A)$  denotes the adjugate of  $A$ ,  $\det(A)$  the determinant of  $A$ , and  $I_m$  the  $m \times m$  identity matrix.

From equation (1.1) we see that for  $A$  to be invertible,  $\det(A)$  must be invertible. In particular if  $A$  is defined modulo  $n$ ,  $\det(A)$  must be invertible modulo  $n$ , that is there exists  $t$  such that

$$\det(A) \cdot t \equiv 1 \pmod{n}.$$

## Notes

Example. Compute the inverse of the matrix

$$A = \begin{pmatrix} 1 & 1 & 1 \\ 1 & 2 & 3 \\ 1 & 4 & 9 \end{pmatrix} \pmod{11}.$$

Since  $\det(A) = 2$  and  $\gcd(2, 11) = 1$ ,  $A$  is invertible modulo 11 and

$$A^{-1} = \frac{1}{2} \begin{pmatrix} + \begin{vmatrix} 2 & 3 \\ 4 & 9 \end{vmatrix} - \begin{vmatrix} 1 & 1 \\ 4 & 9 \end{vmatrix} + \begin{vmatrix} 1 & 1 \\ 2 & 3 \end{vmatrix} \\ - \begin{vmatrix} 1 & 3 \\ 1 & 9 \end{vmatrix} + \begin{vmatrix} 1 & 1 \\ 1 & 9 \end{vmatrix} - \begin{vmatrix} 1 & 1 \\ 1 & 3 \end{vmatrix} \\ + \begin{vmatrix} 1 & 2 \\ 1 & 4 \end{vmatrix} - \begin{vmatrix} 1 & 1 \\ 1 & 4 \end{vmatrix} + \begin{vmatrix} 1 & 1 \\ 1 & 2 \end{vmatrix} \end{pmatrix} \pmod{11}.$$

## Notes

Then calculating all the cofactors yields

$$A^{-1} = \frac{1}{2} \begin{pmatrix} 6 & -5 & 1 \\ -6 & 8 & -2 \\ 2 & -3 & 1 \end{pmatrix} \pmod{11}.$$

In this case it is easy to see that 6 is the inverse of 2 modulo 11, such that we get

$$A^{-1} = \begin{pmatrix} 36 & -30 & 6 \\ -36 & 48 & -12 \\ 12 & -18 & 6 \end{pmatrix} \equiv \begin{pmatrix} 3 & 3 & 6 \\ 8 & 4 & 10 \\ 1 & 4 & 6 \end{pmatrix} \pmod{11}.$$

## Notes

Constructing Hill cipher:

- Key: generate a random  $n \times n$  matrix  $K$  modulo 26, such that  $\gcd(\det(K), 26) = 1$
- Encrypt:
  - Split the plaintext into blocks of size  $n$ , padding with extra letters if necessary
  - Multiply each block considered as a vector by the matrix  $K$
- Decrypt:
  - Split the ciphertext into blocks of size  $n$
  - Multiply each block considered as a vector by the matrix  $K^{-1}$

## Notes

Example. Encrypt "good morning" with the key  $K = \begin{pmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 9 & 7 & 8 \end{pmatrix}$ .

- ① Split and pad the plaintext

$$\begin{array}{cccccccccccc} g & o & o & d & m & o & r & n & i & n & g & x \\ 6 & 14 & 14 & 3 & 12 & 14 & 17 & 13 & 8 & 13 & 6 & 23 \end{array}$$

$\underbrace{\hspace{1.5cm}}_A \quad \underbrace{\hspace{1.5cm}}_B \quad \underbrace{\hspace{1.5cm}}_C \quad \underbrace{\hspace{1.5cm}}_D$

- ② Multiply each vector by  $K$

$$\begin{array}{cccccccccccc} 6 & 24 & 6 & 21 & 8 & 11 & 11 & 25 & 11 & 10 & 9 & 25 \\ G & Y & G & V & I & L & L & Z & L & K & J & Z \end{array}$$

$\underbrace{\hspace{1.5cm}}_{A'} \quad \underbrace{\hspace{1.5cm}}_{B'} \quad \underbrace{\hspace{1.5cm}}_{C'} \quad \underbrace{\hspace{1.5cm}}_{D'}$

Knowing "goodmorningx" and "GYGVILLZLKJZ" recover the key.

- ① Find  $n$ : since  $n|12$ , try some values until the right one is found  
 ② Use the three first blocks to construct the equation

$$\underbrace{\begin{pmatrix} 6 & 14 & 14 \\ 3 & 12 & 14 \\ 17 & 13 & 8 \end{pmatrix}}_A \cdot \begin{pmatrix} a & b & c \\ d & e & f \\ g & h & i \end{pmatrix} \equiv \begin{pmatrix} 6 & 24 & 6 \\ 21 & 8 & 11 \\ 11 & 25 & 11 \end{pmatrix} \pmod{26}$$

- ③ Since  $A$  is not invertible modulo 26, try with the three last blocks

$$\underbrace{\begin{pmatrix} 3 & 12 & 14 \\ 17 & 13 & 8 \\ 13 & 6 & 23 \end{pmatrix}}_A \cdot \begin{pmatrix} a & b & c \\ d & e & f \\ g & h & i \end{pmatrix} \equiv \begin{pmatrix} 21 & 8 & 11 \\ 11 & 25 & 11 \\ 10 & 9 & 25 \end{pmatrix} \pmod{26}$$

- ④ Since  $A$  is now invertible we calculate

$$K = \begin{pmatrix} a & b & c \\ d & e & f \\ g & h & i \end{pmatrix} \equiv \begin{pmatrix} 3 & 12 & 14 \\ 17 & 13 & 8 \\ 13 & 6 & 23 \end{pmatrix}^{-1} \cdot \begin{pmatrix} 21 & 8 & 11 \\ 11 & 25 & 11 \\ 10 & 9 & 25 \end{pmatrix} \pmod{26}$$

$$K = \begin{pmatrix} a & b & c \\ d & e & f \\ g & h & i \end{pmatrix} \equiv \begin{pmatrix} 11 & 18 & 4 \\ 7 & 11 & 10 \\ 1 & 22 & 11 \end{pmatrix} \cdot \begin{pmatrix} 21 & 8 & 11 \\ 11 & 25 & 11 \\ 10 & 9 & 25 \end{pmatrix} \pmod{26}$$

And the key is

$$K = \begin{pmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 9 & 7 & 8 \end{pmatrix}.$$

Remarks on Hill cipher:

- In a substitution cipher, changing one letter from the plaintext alters one letter from the ciphertext
- In Hill cipher changing one letter from the plaintext alters the whole corresponding block from the ciphertext
- Hill cipher is not vulnerable to frequency analysis attacks
- As a drawback a small error in the transmission can induce a major error in the encrypted message and the deciphered text becomes unreadable

61
The Enigma machine

Device information:

- Developed in Germany during the 1920s
- 1054560 ways to initialise the machine
- 100391791500 ways to interchange six pairs of letters
- Secretly broken in Poland in the 1930s
- Techniques extended by the British during World War II

Notes

---

---

---

---

---

---

---

---

---

---

62
Chapter organisation

Notes

---

---

---

---

---

---

---

---

---

---

63
Symmetric vs. Asymmetric

All the previous schemes are symmetric:

- The same key is used to both encrypt and decrypt
- The decryption key is easily derived from the encryption key

Limitations:

- Alice and Bob need to meet in order to exchange, generate, or share the secret keys
- Key management problem:
  - 2 users → 1 key
  - 5 users → 4 keys each, total 10 keys
  - $n$  users →  $n - 1$  keys each, total  $O(n^2)$  keys

Notes

---

---

---

---

---

---

---

---

---

---

64
Public key cryptography

Notes

---

---

---

---

---

---

---

---

---

---



65Public Key Cryptography

Notes

---

---

---

---

---

---

---

---

---

---

66Implementing public key cryptography

*Anybody can lock the padlock but only Bob can unlock it*

Mathematical problems used in Public Key Cryptography (PKC):

- Easy to generate by anybody
- Hard to solve for everybody
- Easy to solve when knowing a small secret

Common examples:

- Multiplication and factorisation
- Exponentiation and discrete logarithm problem

Notes

---

---

---

---

---

---

---

---

---

---

67Historical progression

Over time security has depended on:

- Early years: keeping the encryption method secret
- After WW I: keeping the secret key unknown
- Modern cryptography:
  - The method, the encryption key, and how to find the secret key are known
  - Security depends on the computational infeasibility of finding it

*PKC adds much flexibility at a high computational cost*

Notes

---

---

---

---

---

---

---

---

---

---

68Measuring security – Key space

Basic security feeling:

- Obvious strategy: brute force all possible keys
- Intuition: the larger the key space the harder finding the key

Example. Substitution cipher:

- Key space:  $26! \approx 4 \cdot 10^{26} \approx 2^{89}$
- Very simple to break using frequency analysis

*Brute force is to be used only if no other attack is possible*

Notes

---

---

---

---

---

---

---

---

---

---

69
Measuring security – Computational complexity

Best CPUs available in 2015:

- Regular user: 298,190 MIPS (Intel Core i7 5960x)
- Supercomputer: 10,000,000,000 MIPS (Fujitsu K – 705,024 cores)

How many such computers need to run for a year to complete a program composed of  $2^{80}$  instructions?

Notes

---

---

---

---

---

---

---

---

---

---

70
Complexity and security

*The goal is to be secure in the worst case*

In the worst case the attacker:

- Has the best computational facilities
- Uses the most efficient attack available

To be secure against such an attacker:

- Check to complexity of the best algorithm available
- Adjust the parameters of the cipher such that more than  $2^{128}$  operations are required to break the encryption

Notes

---

---

---

---

---

---

---

---

---

---

71
Complexity and security

Example. Assuming that the best attack on a mathematical problem requires  $\sqrt{n}$  operations, where  $n$  is the size of the key, what key size should be chosen to be secure?

Since secure means that the attacker has to compute at least  $2^{128}$  operations to break the encryption it suffices to calculate

$$(2^{128})^2 = 2^{256}.$$

Hence the key space should contain  $2^{256}$  elements, that is the key should be at least 256 bits long.

Notes

---

---

---

---

---

---

---

---

---

---

72
Improving security?

*Is double encryption with two different keys enhancing security?*

Improving security:

- Naive answer: for a key of length  $k$ ,  $2^{2k}$  operations are needed
- Better answer:
  - It does not change anything, e.g. Hill cipher
  - It is possible to do better than  $2^{2k}$ : meet in the middle attack

Symmetric encryption using a function  $f$  and a key  $k$ :

- Simple encryption:  $c = f_k(m)$
- Double encryption:  $c = f_{k_2}(f_{k_1}(m))$
- Decryption:  $m = f_{k_1}^{-1}(f_{k_2}^{-1}(c))$

Notes

---

---

---

---

---

---

---

---

---

---

Assuming a KPA setup:

- ① For all the keys, compute and store the ciphertexts  $c_i = f_{k_i}(m)$
- ② Compute all plaintexts  $m_i = f_{k_i}^{-1}(c)$  and find any matching  $c_i$
- ③ Recover the corresponding keys  $k_1$  and  $k_2$
- ④ Test  $k_1$  and  $k_2$  on more plaintext/ciphertext pairs

Exercise. Assuming no attack applies on an encryption scheme and a key size of 64 bits, what is its security if applying double encryption?


Main complexity classes related to cryptology:

- $\mathcal{P}$ : decision problems for which there exists a deterministic polynomial time algorithm
- $\mathcal{NP}$ : decision problems for which the answer "yes" can be verified using a deterministic polynomial time algorithm
- $\mathcal{NP}$ -complete: hardest problems in  $\mathcal{NP}$
- $\text{co-}\mathcal{NP}$ : decision problems for which the answer "no" can be verified using a deterministic polynomial time algorithm
- $\text{co-}\mathcal{NP}$ -complete: hardest problems in  $\text{co-}\mathcal{NP}$


Example. Integer factorization is in both  $\mathcal{NP}$  and  $\text{co-}\mathcal{NP}$

Let  $n$  be a large integer and  $1 < m < n$ . Does  $n$  have a factor  $p$ , with  $1 < p < m$ ?

- $\mathcal{NP}$ : with certificate " $p$  a factor of  $n$ " verify in polynomial time that  $1 < p < m$  and  $p|n$
- $\text{co-}\mathcal{NP}$ : with certificate "the list of all the prime factors of  $n$ " verify in polynomial time that:
  - They are all prime
  - Their product is  $n$
  - None of them is between 1 and  $m$



Bob knows a secret path, and wants to prove it without revealing it



Strategy:

- 1 Alice hides while Bob chooses to go Left (L) or Right (R)
- 2 Alice randomly asks Bob to exit on L or R
- 3 If Bob is on the wrong side he uses the secret path or otherwise returns
- 4 Repeat steps 1 to 3 many times

## Notes

## Definitions

- 1 Let  $G_1 = (V_1, E_1)$  and  $G_2 = (V_2, E_2)$  be two simple graphs. Then we say that  $G_1$  and  $G_2$  are *isomorphic* if there exists a bijective function  $\varphi: V_1 \rightarrow V_2$  such that the induced map
 
$$\varphi_*: E_1 \rightarrow E_2, \quad (a, b) \mapsto (\varphi(a), \varphi(b))$$
 is bijective. Such a function  $\varphi$  is called a *graph isomorphism*.
- 2 A *Hamilton circuit* in a graph  $G$  is a simple circuit that passes through every vertex of  $G$  exactly once.

## Notes

Hard problems related to graph theory:

- Graph isomorphism:
  - No known polynomial time algorithm
  - Not proven to be  $\mathcal{NP}$ -complete
  - Best known algorithm has exponential complexity
- Finding a Hamiltonian circuit:
  - Proven to be  $\mathcal{NP}$ -complete
  - Best known algorithm has exponential complexity

## Notes

Initial setup:



- A graph  $G$
- A Hamiltonian circuit in  $G$

- Bob's graph  $G$



Process:

- 1 Bob generates  $H$ , a graph isomorphic to  $G$
- 2 Bob commits  $H$
- 3 Alice randomly asks for either the isomorphism or a Hamiltonian circuit in  $H$
- 4 Bob either shows the isomorphism or translates the Hamiltonian circuit in  $G$  onto  $H$  and shows it

## Notes

81
Zero knowledge proofs

Regarding the process and setup:

- Is Bob revealing any sensitive information?
- Why does Bob need to commit  $H$ ?
- If Bob can anticipate Alice's request how can he cheat if asked for:
  - The graph isomorphism?
  - The Hamiltonian circuit?
- Explain whether randomness is important or not in the process.
- Can any of Bob and Alice cheat?
- How many times should the process be repeated for Bob to prove that he really knows a Hamiltonian circuit in  $G$ ?

Notes

82
Key points

- What is cryptology?
- Who are Alice, Bob, and Eve?
- What is Kerckhoff's principle?
- Explain the One-Time-Pad
- Explain the underlying idea of public key cryptography
- In 2021 what security level is considered safe?

Notes

2. Block ciphers

Notes

84
Chapter organisation

```

graph TD
    A((Block ciphers)) --- B((Feistel networks))
    A --- C((Randomness))
    A --- D((Advanced Encryption Standard))

```

Notes

A *block cipher* is composed of two functions, inverse of each other:


$$E : \{0, 1\}^n \times \{0, 1\}^k \rightarrow \{0, 1\}^n \quad D : \{0, 1\}^n \times \{0, 1\}^k \rightarrow \{0, 1\}^n$$

$$(P, K) \mapsto C \quad (C, K) \mapsto P$$


where  $n$  and  $k$  are the sizes of a block and the key, respectively.

Goal: given a key  $K$ , design an invertible function  $E$  whose output cannot be distinguished from a random permutation over  $\{0, 1\}^n$ .


## Notes



Limitation: what if a block is repeated several times over the message?




## Notes



Basic principle:

- Cipher Block Chaining (CBC)
- Most commonly used mode
- Uses an Initialization Vector
- Can it be parallelized?

## Notes



## Notes

89
What is randomness?

```

int getRandomNumber()
{
    return 4; // chosen by fair dice roll.
              // guaranteed to be random.
}

```

Notes

---

---

---

---

---

---

---

---

---

---

90
Randomness

**Definition** (Kolmogorov randomness)  
 Let  $x$  be a string.
 

- We say that  $x$  is *random* if and only if it is not larger than any program that can produce it in any language.
- The *entropy* of  $x$  is the minimum number of bits necessary to describe  $x$ .

Remark. A random string of length  $k$  cannot be compressed in any way, therefore it has entropy  $k$   
 Example. 3434 3434 3434 3434 3434 3434 3434 3434  
 ed71 b38f 4316 6907 a8ea 75d3 c141 735f

Notes

---

---

---

---

---

---

---

---

---

---

91
Random bits generation

Generating true randomness is not simple:
 

- Toss a coin
- Measure physical phenomena that are expected to be random
- In case of a lack of entropy the output is blocked

Example. The thermal noise from a semiconductor resistor  
 A nuclear decay radiation source measured by a Geiger counter

Notes

---

---

---

---

---

---

---

---

---

---

92
Pseudo-random bits generation

Random function from the C standard:

```

1  /* Linear congruential generator */
2  static unsigned long next = 1;
3
4  /* RAND_MAX assumed to be 32767 */
5  int rand(void) {
6      next = next * 1103515245 + 12345;
7      return((unsigned)(next/65536) % 32768);
8  }
9
10 void srand(unsigned int seed) {
11     next = seed;
12 }

```

Notes

---

---

---

---

---

---

---

---

---

---

93 Pseudo-random bits generation – BBS generator

A secure method from Blum, Blum and Shub:

- 1 Generate two large primes  $p$  and  $q$ , both being  $3 \bmod 4$
- 2 Set  $n = pq$
- 3 Choose a random integer  $x$  coprime to  $n$
- 4 Define
 
$$\begin{cases} x_0 & \equiv x^2 \bmod n \\ x_{i+1} & \equiv x_i^2 \bmod n \end{cases}$$
- 5 At each iteration select the least significant bit of  $x_i$

Notes

---

---

---

---

---

---

---

---

---

---

94 Why is BBS secure?

*Can bits generated using BBS be predicted?*

**Problem (Quadratic Residuosity (QR))**

Let  $n = pq$  be the product of two primes. Given an integer  $y$ , is it a square mod  $n$ , i.e. is there an  $x$  such that  $x^2 \equiv y \bmod n$ ?

This loose formulation will be refined in the next chapter (3.166).

Strategy:

- Prove that the QR problem is hard
- If this is hard the previous bit cannot be predicted
- A sequence a pseudo-random bits generated by BBS cannot be compressed

Notes

---

---

---

---

---

---

---

---

---

---

95 Reminder

In order to prove that the QR problem is hard we first recall and prove few results from number theory. The goal is to prove that solving the QR problem is as hard as factoring. That is, knowing how to solve one implies knowing how to solve the other one.

**Theorem (Fermat's little theorem)**

Let  $p \in \mathbb{N}$  and  $a \in \mathbb{Z}$ . If  $p$  is prime and  $p \nmid a$ , then

$$a^{p-1} \equiv 1 \bmod p.$$

More generally, for any prime  $p \in \mathbb{N}$  and  $a \in \mathbb{Z}$ ,

$$a^p \equiv a \bmod p.$$

Notes

---

---

---

---

---

---

---

---

---

---

96 Squares modulo a prime

**Lemma**

If  $p \equiv 3 \bmod 4$  is prime, then the equation  $x^2 \equiv -1 \bmod p$  has no solution.

Proof. Suppose such an  $x$  exists. Then raising it to the power of  $(p-1)/2$  and applying Fermat's little theorem (2.95) yields

$$(x^2)^{\frac{p-1}{2}} \equiv x^{p-1} \equiv 1 \bmod p.$$

On the other hand  $p \equiv 3 \bmod 4$ , implies  $(p-1)/2$  odd and

$$(-1)^{\frac{p-1}{2}} \equiv -1 \bmod p. \neq$$

□

Notes

---

---

---

---

---

---

---

---

---

---



**Proposition**

Let  $p \equiv 3 \pmod{4}$  be a prime,  $y$  be an integer and  $x \equiv y^{\frac{p+1}{4}} \pmod{p}$ .

- If  $y$  has a square root mod  $p$ , then its square roots are  $\pm x \pmod{p}$
- If  $y$  has no square root mod  $p$ , then the square roots of  $-y$  are  $\pm x \pmod{p}$

**Proof.** The case  $y \equiv 0 \pmod{p}$  being trivial, we assume  $y \not\equiv 0 \pmod{p}$ . Applying Fermat's little theorem (2.95) we get

$$x^4 \equiv y^{p+1} \equiv y^2 y^{p-1} \equiv y^2 \pmod{p}. \quad (2.1)$$

## Notes

**Proof (continued).** Since  $p$  is prime all the non zero elements have a multiplicative inverse (prop. 1.52). Therefore rewriting eq. (2.1) into

$$(x^2 - y)(x^2 + y) \equiv 0 \pmod{p},$$

implies  $x^2 \equiv \pm y \pmod{p}$ . Hence at least one of  $y$  and  $-y$  is a square mod  $p$ .

Suppose that both  $y$  and  $-y$  are square mod  $p$ , i.e. there exist  $a$  and  $b$  such that  $y \equiv a^2 \pmod{p}$  and  $-y \equiv b^2 \pmod{p}$ .

Then  $(b^{-1}a)^2 \equiv -1 \pmod{p}$ , that is  $-1$  is a square mod  $p$ , contradicting lem. 2.96.

Hence exactly one of  $y$  and  $-y$  has square roots  $\pm x \pmod{p}$ .  $\square$

## Notes

Keeping in mind the initial goal of studying the BBS generator where the squares are computed mod  $n = pq$ , with both  $p$  and  $q$  congruent to 3 modulo 4, we recall the following result.

**Theorem (Chinese Remainder Theorem (CRT))**

Let  $m_1, \dots, m_k \in \mathbb{N} \setminus \{0\}$  be pairwise relatively prime and  $a_1, \dots, a_k \in \mathbb{Z}$ . Then the system of congruences

$$\begin{cases} x \equiv a_1 \pmod{m_1}, \\ x \equiv a_2 \pmod{m_2}, \\ \vdots \\ x \equiv a_k \pmod{m_k}. \end{cases}$$

has a unique solution modulo  $m = m_1 m_2 \dots m_k$ .

## Notes

**Example.** Find  $x$  such that  $x^2 \equiv 71 \pmod{77}$ .

As  $77 = 7 \times 11$ , the congruency can be rewritten

$$\begin{cases} x^2 \equiv 71 \equiv 1 \pmod{7} \\ x^2 \equiv 71 \equiv 5 \pmod{11}. \end{cases}$$

As both 7 and 11 are congruent to 3 mod 4, from prop. 2.97 we derive

$$\begin{cases} x \equiv \pm 1 \pmod{7} \\ x \equiv \pm 4 \pmod{11}. \end{cases}$$

Finally, by applying the CRT (2.99) the four solutions can be recombined modulo 77 such as to get

$$x \equiv \pm 15, \pm 29 \pmod{77}.$$

## Notes

101
From square roots to factors

In the previous example we used the factorisation of  $n$  in order to calculate the square root of  $x$  modulo  $n$ . We now show that if we know the square root then we can factorize  $n$ .

**Proposition**

Let  $n$  be a product of two unknown primes  $p$  and  $q$ , both being 3 mod 4. Let  $x \equiv \pm a, \pm b \pmod n$  be the four solutions to  $x^2 \equiv y \pmod n$ . Then  $\gcd(a - b, n)$  is a non-trivial factor of  $n$ .

Proof. From the construction of  $a$  and  $b$ , we know that  $a \equiv b \pmod p$  and  $a \equiv -b \pmod q$  (or the other way around). Therefore  $p \mid (a - b)$  while  $q \nmid (a - b)$ , which means that  $\gcd(a - b, n) = p$ .  $\square$

Notes

---

---

---

---

---

---

---

---

---

---

102
Remarks on the BBS generator

We showed that:

- Solving the factorization problem allows to solve the QR problem
- Solving the QR problem gives the factorization of the modulus

The previous reasoning is:

- Not a formal security reduction
- Enough to “informally” consider BBS as a secure pseudo-random number generator

Notes

---

---

---

---

---

---

---


---

---

---

103
Building a block cipher

A few informal definitions:



- A *random oracle* is a “black box” that returns a truly uniform random output on an input. Submitting the same input more than once leads to the same output.
- A *pseudorandom function* is a function that emulates a random oracle

- A pseudorandom function that cannot be distinguished from a random permutation is called *pseudo random permutation*
- A *blockcipher* is a pseudorandom permutation
- A *one way function* is a function easy to evaluate but hard to invert

Notes

---

---

---

---

---

---


---

---

---

---

104
Chapter organisation



Notes

---

---

---

---

---

---


---

---

---

---

We want to build a random bijection over  $2n$  bits



- Size of a block:  $2n$  bits
- Split the block into two blocks of  $n$  bits each
- $F : \{0, 1\}^n \times \{0, 1\}^k \rightarrow \{0, 1\}^n$

We define the function

$$\Psi_F : \{0, 1\}^{2n} \longrightarrow \{0, 1\}^{2n}$$

$$[L, R] \mapsto [R, L \oplus F(R, K)]$$

### Proposition

For any function  $F$ ,  $\Psi_F$  is a bijection and  $\Psi_F^{-1} = \sigma \circ \Psi_F \circ \sigma$ , with  
 $\sigma : \{0, 1\}^{2n} \longrightarrow \{0, 1\}^{2n}$   
 $[L, R] \mapsto [R, L]$

Proof. By definition of  $\Psi_F$ ,  $\Psi_F([L_0, R_0]) = [R_0, L_0 \oplus F(R_0, K)] = [L_1, R_1]$ .

Equivalently,

$$\begin{cases} R_0 = L_1 \\ L_0 = R_1 \oplus F(L_1, K). \end{cases}$$

Moreover


$$\begin{aligned} \sigma \circ \Psi_F \circ \sigma([L_1, R_1]) &= \sigma \circ \Psi_F \circ \sigma([R_0, L_0 \oplus F(R_0, K)]) \\ &= \sigma(\Psi_F([L_0 \oplus F(R_0, K), R_0])) \\ &= \sigma(R_0, L_0 \oplus F(R_0, K) \oplus F(R_0, K)) \\ &= [L_0, R_0]. \end{aligned}$$

□

Setting up two black boxes, a random oracle and a Feistel network, the goal for an attacker is to distinguish them.

Number of messages necessary to reach the goal:

Rounds	KPA	CPA	CPCA
1	1	1	1
2	$\mathcal{O}(\sqrt{2^n})$	2	2
3	$\mathcal{O}(\sqrt{2^n})$	$\mathcal{O}(\sqrt{2^n})$	3
4	$\mathcal{O}(2^n)$	$\mathcal{O}(\sqrt{2^n})$	$\mathcal{O}(\sqrt{2^n})$



Attack strategy:

- For simplicity we denote  $F(X, K)$  by  $F_K(X)$  and  $\Psi_{F_{K_2}} \circ \Psi_{F_{K_1}}$  by  $\Psi_{F_{K_1}, F_{K_2}}^2$
- $\Psi_{F_{K_1}, F_{K_2}}^2([L_0, R_0]) = [L_2, R_2]$  with  $L_2 = L_0 \oplus F_{K_1}(R_0)$  and  $R_2 = R_0 \oplus F_{K_2}(L_2)$
- The inverse of  $\Psi_{F_{K_1}, F_{K_2}}^2$  is  

$$\begin{aligned} \Psi_{F_{K_1}, F_{K_2}}^{-2} &= \Psi_{F_{K_1}}^{-1} \circ \Psi_{F_{K_2}}^{-1} \\ &= \sigma \circ \Psi_{F_{K_1}} \circ \sigma \circ \sigma \circ \Psi_{F_{K_2}} \circ \sigma \\ &= \sigma \circ \Psi_{F_{K_2}, F_{K_1}}^2 \circ \sigma \end{aligned}$$

What if we use  $m_1 = [m_{1L}, m_{1R}]$  and  $m_2 = [m_{2L}, m_{2R}]$  such that

$$\begin{cases} m_{1L} \neq m_{2L} \\ m_{1R} = m_{2R} \end{cases}$$


Basic KPA strategy:

- ① Find a collision over the  $m_{iR}$ ,  $1 \leq i \leq 2^n$
- ② If a collision is found for  $m_j$  and  $m_l$  check if

$$m_{jL_2} \oplus m_{lL_2} = m_{jL_0} \oplus m_{lL_0}$$

By the birthday paradox (slide 4.231):

- Number of plaintext-ciphertext pairs needed:  $\mathcal{O}(\sqrt{2^n})$
- No better than  $\mathcal{O}(\sqrt{2^n})$ :
  - Collision on  $m_{iL_2} = m_{iL_0} \oplus F_{K_1}(m_{iR_0})$  for two messages
  - The variables  $m_{iL_2}$ ,  $m_{iL_0}$ , and  $m_{iR_0}$  are fixed
  - It only depends on  $F_{K_1}$ , which can take  $2^n$  different values
  - From  $l$  messages  $\frac{l(l-1)}{2}$  pairs can be constructed
  - Probability of collision:  $\approx \frac{l(l-1)}{2 \cdot 2^n}$



Attack strategy:


- $\Psi_{F_{K_1}, F_{K_2}, F_{K_3}}^3([L_0, R_0]) = [L_3, R_3]$  with
 
$$\begin{cases} L_3 = R_0 \oplus F_{K_2}(L_2) \\ R_3 = L_2 \oplus F_{K_3}(L_3) \end{cases}$$
 and  $L_2 = L_0 \oplus F_{K_1}(R_0)$
- Notice for a pair of messages  $(m_a, m_b)$ 

$$\begin{aligned} m_{aR_0} = m_{bR_0} &\Leftrightarrow m_{aL_2} \oplus m_{bL_2} = m_{aL_0} \oplus m_{bL_0} \\ m_{aL_2} = m_{bL_2} &\Leftrightarrow m_{aL_3} \oplus m_{bL_3} = m_{aR_0} \oplus m_{bR_0} \\ m_{aL_3} = m_{bL_3} &\Leftrightarrow m_{aR_3} \oplus m_{bR_3} = m_{aL_2} \oplus m_{bL_2} \end{aligned} \quad (2.2)$$

Attack strategy:


- Choose two plaintexts  $m_1$  and  $m_2$  such that  $m_{2R_0} = m_{1R_0}$
- Choose a ciphertext  $c_3$  such that  $m_{3L_3} = m_{2L_3}$
- From the third equation of (2.2)
 
$$m_{3R_3} \oplus m_{2R_3} = m_{3L_2} \oplus m_{2L_2}$$
- Using the first equation of (2.2) enforce  $m_{3L_2}$  to be  $m_{1L_2}$ 

$$m_{3R_3} = m_{2R_3} \oplus m_{1L_0} \oplus m_{2L_0}$$
- How to conclude?



Data Encryption Standard (DES):

- 1974: IBM uses Feistel networks to create LUCIFER
- 1975: LUCIFER is sent to NSA for review and modifications
- 1977: renamed DES and becomes the official encryption standard
- 2002: DES is not secure anymore and is replaced by AES



Notes

---

---

---

---

---

---

---

---

---

---

- 114 Advanced Encryption Standard
- Advanced Encryption Standard (AES):
- 1997: call for candidates to replace DES
  - Requirements:
    - Possible key sizes: 128, 192 and 256 bits
    - Input block size: 128 bits
    - Work on various hardware (e.g. 8-bit processors)
    - Speed
  - Five finalists: MARS, RC6, Rijndael, Serpent, and Twofish
  - 2001: Rijndael is chosen to become AES

Notes

---

---

---

---

---

---

---

---

---

---

- 115 AES – General description
- Brief outline of AES:
- 10 rounds for a 128-bit key (12 and 14 for 192 and 256-bit)
  - A round is formed of layers
    - *SubBytes*: substitution operation
    - *ShiftRows*: linear mixing step on the rows
    - *MixColumns*: linear mixing on the columns
    - *AddRoundKey*: apply a round key derived from the main key

Notes

---

---

---

---

---


---

---

---

---

---



Notes

---

---

---

---

---

---

---

---

---

---

So far we worked with the set  $S = \{0, \dots, n-1\}$  using modular congruences (def. 1.38). In the proof of prop. 2.97 we noted that when  $n$  is prime all the non-zero elements of  $S$  are invertible.

Example.

- i The set  $S = \{0, \dots, 4\}$  has five elements, and since five is prime all the non-zero elements are invertible. Indeed,

$$1 \cdot 1 \equiv 1 \pmod{5}, \quad 2 \cdot 3 = 6 \equiv 1 \pmod{5}, \quad \text{and} \quad 4^2 = 16 \equiv 1 \pmod{5}.$$

- ii The set  $S = \{0, \dots, 5\}$  has six elements, and as six is not prime some non-zero elements are not invertible. In fact since

$$2 \cdot 3 \equiv 0 \pmod{6},$$

we conclude that 2 and 3 are not invertible mod 6.

Loosely speaking a set where the addition and multiplication operations are defined and such that every non-zero element is invertible for the multiplication is called a *field*.

When a field has a finite number of elements it is called *finite field*. For each prime  $p$  and positive integer  $n$  there exists a finite field with  $p^n$  elements, often denoted  $\text{GF}(p^n)$  or  $\mathbb{F}_{p^n}$  (GF standing for Galois Field).

Remark. The set  $S = \{0, \dots, 8\}$  has  $9 = 3^2$  elements and is not a field since 3 is not invertible. Therefore the question remaining to answer is "how to construct a finite field with nine elements", or more generally with  $p^n$  elements.

Similarly to how polynomials are defined over common fields such as the real numbers, they can also be defined over finite fields. The main difference relies on their coefficients which take their values in the base field.

In a field, a polynomial which cannot be written as the product of two polynomials of lower degree is said to be *irreducible*.

Example.

- i In  $\mathbb{F}_2[X]$ ,  $X^2 + 3X + 1$  and  $X^2 + X + 1$  are equal.  
 ii In  $\mathbb{F}_5[X]$ ,  $X^3 + X + 3 = (X + 4)(X^2 + X + 2)$  is not irreducible.  
 iii In  $\mathbb{F}_{17}[X]$ ,  $X^3 + X + 3$  is irreducible.

### Theorem

Let  $P(X)$  be an irreducible polynomial of degree  $n$  in  $\mathbb{F}_p[X]$ , and  $F$  be the set of all the polynomials of degree less than  $n$ . Then  $F$  is a finite field with  $p^n$  elements.

Proof. Assuming addition and multiplication are properly defined we need to prove that  $F$  has  $p^n$  elements and that all but 0 are invertible.

It is simple to see that  $F$  has  $p^n$  elements since each of the  $n$  monomials (from degree 0 to  $n-1$ ) can take  $p$  different values (from 0 to  $p-1$ ).

Proof (continued). Let  $A(X)$ ,  $B(X)$  and  $C(X)$  be three distinct non-zero polynomials such that

$$A(X)B(X) \equiv A(X)C(X) \pmod{P(X)}.$$

This implies  $A(X)(B(X) - C(X)) \equiv 0 \pmod{P(X)}$ , which is not possible since  $P(X)$  is irreducible.

Hence multiplying a polynomial  $A(X)$  by all the non-zero elements of  $F$  results in covering all the non-zero polynomials of  $F$ , meaning that there is a polynomial  $B(X)$  such that

$$A(X)B(X) \equiv 1 \pmod{P(X)}.$$

□

## Notes

In Rijndael  $\mathbb{F}_{2^8}$  is used:

- $P(X) = X^8 + X^4 + X^3 + X + 1$  is the irreducible over  $\mathbb{F}_2[X]$
- Each element of  $\mathbb{F}_{2^8}$  is a polynomial of the form  $a_7X^7 + a_6X^6 + a_5X^5 + a_4X^4 + a_3X^3 + a_2X^2 + a_1X + a_0$
- The polynomial is described as a byte  $a_7a_6a_5a_4a_3a_2a_1a_0$
- The sum of two polynomials is the XOR of their bit representation
- Multiplying a polynomial  $Q(X)$  by  $X$ :
  - ① Shift left the byte representation of  $Q(X)$  and append a 0
  - ② If the first bit is 0 stop and otherwise XOR with  $P(X)$
- Multiplying  $Q(X)$  by  $R(X)$ :
  - ① Split  $R(X)$  into the monomials  $M_i(X)$ ,  $i \leq \deg R(X)$
  - ② For  $M_i(X)$  applying the multiplication by  $X$   $\deg M_i(X)$  times
  - ③ Add all the results using XOR

## Notes


**Example.** Let  $Q(X) = X^7 + X^4 + X + 1$  and  $R(X) = X^2 + 1$ . Determine the product  $Q(X)R(X)$  in  $\mathbb{F}_{2^8}[X]$ .

1. Regular strategy: multiply and reduce mod  $P(X)$ 
  - $Q(X)R(X) = X^9 + X^7 + X^6 + X^4 + X^3 + X^2 + X + 1$
  - Since  $P(X) = 0$ ,  $X^9 = X^5 + X^4 + X^2 + X$  and  $Q(X)R(X) \equiv X^7 + X^6 + X^5 + X^3 + 1 \pmod{P(X)}$
2. Represent polynomials as bytes and apply XOR operations:
 

Write  $Q(X) = 10010011$  and decompose  $R(X)$  as  $X \cdot X + 1$

  - $Q(X) \cdot X = 100100110 \oplus 100011011 = 000111101$
  - $(Q(X) \cdot X) \cdot X = 001111010$
  - $(Q(X) \cdot X) \cdot X + Q(X) = 01111010 \oplus 10010011 = 11101001$
  - $Q(X)R(X) \equiv X^7 + X^6 + X^5 + X^3 + 1 \pmod{P(X)}$

## Notes



For each byte in the matrix:

- Split it into two 4-bit numbers  $a$  and  $b$
- Find byte  $c$  in the S-Box table at row  $a$  and column  $b$
- Replace the original byte by  $c$

## Notes

125

S-Box

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
0	99	124	119	123	242	107	111	197	48	1	103	43	254	215	171	118
1	202	130	201	125	250	89	71	240	173	212	162	175	156	164	114	192
2	183	253	147	38	54	63	247	204	52	165	229	241	113	216	49	21
3	4	199	35	195	24	150	5	154	7	18	128	226	235	39	178	117
4	9	131	44	26	27	110	90	160	82	59	214	179	41	227	47	132
5	83	209	0	237	32	252	177	91	106	203	190	57	74	76	88	207
6	208	239	170	251	67	77	51	133	69	249	2	127	80	60	159	168
7	81	163	64	143	146	157	56	245	188	182	218	33	16	255	243	210
8	205	12	19	236	95	151	68	23	196	167	126	61	100	93	25	115
9	96	129	79	220	34	42	144	136	70	238	184	20	222	94	11	219
10	224	50	58	10	73	6	36	92	194	211	172	98	145	149	228	121
11	231	200	55	109	141	213	78	169	108	86	244	234	101	122	174	8
12	186	120	37	46	28	166	180	198	232	221	116	31	75	189	139	138
13	112	62	181	102	72	3	246	14	97	53	87	185	134	193	29	158
14	225	248	152	17	105	217	142	148	155	30	135	233	206	85	40	223
15	140	161	137	13	191	230	66	104	65	153	45	15	176	84	187	22

Notes

---

---

---

---

---

---

---

---

---

---

126

Generating the S-Box

Simple construction:

- For  $a$  in  $\mathbb{F}_{2^8}^*$  compute its inverse  $b = a^{-1}$  or set  $b = 0$  if  $a = 0$
- Represent  $b$  as a column vector  $B = (b_0, \dots, b_7)$
- Compute
 
$$\begin{pmatrix} 1 & 0 & 0 & 0 & 1 & 1 & 1 & 1 \\ 1 & 1 & 0 & 0 & 0 & 1 & 1 & 1 \\ 1 & 1 & 1 & 0 & 0 & 0 & 1 & 1 \\ 1 & 1 & 1 & 1 & 0 & 0 & 0 & 1 \\ 1 & 1 & 1 & 1 & 1 & 0 & 0 & 0 \\ 0 & 1 & 1 & 1 & 1 & 1 & 0 & 0 \\ 0 & 0 & 1 & 1 & 1 & 1 & 1 & 0 \\ 0 & 0 & 0 & 1 & 1 & 1 & 1 & 1 \end{pmatrix} \begin{pmatrix} b_0 \\ b_1 \\ b_2 \\ b_3 \\ b_4 \\ b_5 \\ b_6 \\ b_7 \end{pmatrix} + \begin{pmatrix} 1 \\ 1 \\ 0 \\ 0 \\ 0 \\ 1 \\ 1 \\ 0 \end{pmatrix} = \begin{pmatrix} c_0 \\ c_1 \\ c_2 \\ c_3 \\ c_4 \\ c_5 \\ c_6 \\ c_7 \end{pmatrix}$$
- The entry located at row  $(a_7 \dots a_4)_2$  and column  $(a_3 \dots a_0)_2$  of the S-Box is  $(c_7 \dots c_0)_2$

Notes

---

---

---

---

---

---

---

---

---

---

127

Generating the S-Box

Example. Find the S-Box entry corresponding to the byte 11001011?

The byte 11001011 stands for  $a(X) = X^7 + X^6 + X^3 + X + 1$ , and we observe that

$$\begin{aligned} a(X) \cdot X^2 &= X^9 + X^8 + X^5 + X^3 + X^2 \\ &\equiv X^8 + X^4 + X^3 + X \pmod{P(X)} \\ &\equiv 1 \pmod{P(X)}. \end{aligned}$$

Therefore we calculate

$$\begin{pmatrix} 1 & 0 & 0 & 0 & 0 & 1 & 1 & 1 & 1 \\ 1 & 1 & 0 & 0 & 0 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 0 & 0 & 0 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 0 & 0 & 0 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 & 0 & 0 & 0 & 0 \\ 0 & 1 & 1 & 1 & 1 & 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 1 & 1 & 1 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 & 1 & 1 & 1 & 1 & 1 \end{pmatrix} \cdot \begin{pmatrix} 0 \\ 0 \\ 1 \\ 1 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \end{pmatrix} + \begin{pmatrix} 1 \\ 1 \\ 0 \\ 0 \\ 0 \\ 1 \\ 1 \\ 0 \end{pmatrix} = \begin{pmatrix} 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 0 \\ 1 \\ 0 \end{pmatrix},$$

and finally conclude that the entry at row 12 and column 11 is 31.

Notes

---

---

---

---

---

---

---

---

---

---

128

The ShiftRows layer

Cyclically shift to the left row  $i$  by offset  $i$ ,  $0 \leq i \leq 3$

Notes

---

---

---

---

---

---

---

---

---

---



129
The MixColumns layer

Left multiply the output of ShiftRows by the matrix

$$C(X) = \begin{pmatrix} 00000010 & 00000011 & 00000001 & 00000001 \\ 00000001 & 00000010 & 00000011 & 00000001 \\ 00000001 & 00000001 & 00000010 & 00000011 \\ 00000011 & 00000001 & 00000001 & 00000010 \end{pmatrix}$$

Notes

---

---

---

---

---

---

---

---

---

---

130
The AddRoundKey layer

Combine each byte from the MixColumns output with a byte from the round key

Notes

---

---

---

---

---

---

---

---

---

---

131
Generating a round key

The original 128 bits key is arranged into a  $4 \times 4$  matrix  $K(X)$

Label the first four columns  $K(0), \dots, K(3)$  and add forty more:

- $K(i) = K(i-4) \oplus K(i-1)$ , for  $i \not\equiv 0 \pmod 4$
- $K(i) = K(i-4) \oplus T(K(i-1))$ , for  $i \equiv 0 \pmod 4$

The transformation  $T(K(i-1))$  is defined over the column  $i$ :

- Compute  $r(i) = 00000010 \cdot x^{i-4}$
- Cyclically top shift the elements of the column by 1
- Apply the SubBytes layer (2.124) to each byte of the column and get the column vector  $(a, b, c, d)$
- Finally return the column vector

$$T(K(i-1)) = (a \oplus r(i), b, c, d)$$

The  $i$ -th round key is given by the columns  $K(4i), \dots, K(4i+3)$

Notes

---

---

---

---

---

---

---

---

---

---

132
Generating a round key

Example.  $K(i)$  being simple to generate for  $i \not\equiv 0 \pmod 4$ , we focus on the case  $i \equiv 0 \pmod 4$ . For instance if  $i = 40$  and  $K(39)$  is the column vector  $(10001100, 00001100, 11000110, 11110011)$ , then

- Cyclical top shift:  $(00001100, 11000110, 11110011, 10001100)$
- SubBytes transformation:
 

00001100	→	11111110	11000110	→	10110100
11110011	→	00001101	10001100	→	01100100
- $r(40) = X^9 \equiv X^5 + X^4 + X^2 + X \pmod{P(X)} = 00110110$
- Get the final column vector  $T(K(39))$ 

$$T(K(39)) = (11111110 \oplus 00110110, 10110100, 00001101, 01100100)$$

$$= (11001000, 10110100, 00001101, 01100100)$$
- Finally define  $K(40)$  as  $K(36) \oplus T(K(39))$

Notes

---

---

---

---

---

---

---

---

---

---

133

Decryption

The decryption process is simple:

- Perform all the operations in reverse order
- Replace the SubBytes, ShiftRows and MixColumns operations by their inverse

Remark. It is possible to construct an inverse cipher performing decryption by applying a sequence of inverse operations in the same order as it is done for encryption

Notes

134

Key points

- What does it mean to be random?
- Recall Fermat's little theorem
- Recall the CRT
- How is a Feistel network organised?
- Describe AES

Notes

3. Public Key Cryptography

Notes

136

Chapter organisation

```
graph TD; A((Public Key Cryptography)) --- B((Factoring problem)); A --- C((Discrete logarithm problem)); A --- D((Mathematics to the rescue))
```

Notes

Symmetric-key cryptosystem:

- Encryption depends on a secret key  $K$
- Decryption depends on a secret key  $K'$  easily derived from  $K$
- Knowing  $K$  or  $K'$  is the same
- The key must be securely shared beforehand

Public-key cryptosystem:

- Encryption depends on a public key  $K$
- Decryption depends on a secret key  $K'$
- Finding  $K'$  when knowing  $K$  is computationally infeasible
- No prior communication is required

*One way function*: function easy to evaluate but hard to invert

Requirements for encrypting with a one-way function  $E$ :

- $E$  must be injective
- Some secret that allows to invert  $E$

*Trapdoor one-way function*: one-way function, easy to invert when knowing a *trapdoor*

#### Definition (Group)

A *group* is a pair  $(G, \circ)$  consisting of a set  $G$  and a *group operation*  $\circ: G \times G \rightarrow G$  that verifies the following properties:

- i **Associativity**:  $a \circ (b \circ c) = (a \circ b) \circ c$  for all  $a, b, c \in G$
- ii **Existence of a unit element**: there exists an element  $e \in G$  such that  $a \circ e = e \circ a = a$  for all  $a \in G$
- iii **Existence of inverse**: for every  $a \in G$  there exists an element  $a^{-1} \in G$  such that  $a \circ a^{-1} = a^{-1} \circ a = e$

A group is called *abelian* if in addition to the above properties

- iv **Commutativity**:  $a \circ b = b \circ a$  for all  $a, b \in G$ .

#### Definition (Ring)

A *ring* is a triple  $(R, +, \cdot)$  consisting of a set  $R$  and two *binary operations*  $+, \cdot: R \times R \rightarrow R$  such that

- i  $(R, +)$  is an abelian group
  - ii **Multiplicative unit**: there exists an element  $1 \in R$  such that  $a \cdot 1 = 1 \cdot a = a$  for all  $a \in R$
  - iii **Associativity**: for any  $a, b, c \in R$ ,  $a \cdot (b \cdot c) = (a \cdot b) \cdot c$
  - iv **Distributivity**: for any  $a, b, c \in R$ ,  $a \cdot (b + c) = (a \cdot b) + (a \cdot c)$ ,  $(b + c) \cdot a = (b \cdot a) + (c \cdot a)$
- A ring is called *commutative* if in addition to the above properties
- v **Commutativity**:  $a \cdot b = b \cdot a$  for all  $a, b \in R$

## Definition (Field)

Let  $(F, +, \cdot)$  be a commutative ring with unit element of addition 0 and unit element of multiplication 1. Then  $F$  is a *field* if

- i  $0 \neq 1$
- ii For every  $a \in F \setminus \{0\}$  there exists an element  $a^{-1}$  such that
 
$$a \cdot a^{-1} = 1.$$

Remark. Another way of writing this definition is to say that  $(F, +, \cdot)$  is a field if  $(F, +)$  and  $(F \setminus \{0\}, \cdot)$  are abelian groups and  $0 \neq 1$ , and  $\cdot$  distributes over  $+$ .

## Notes

Example. Let  $n$  be an integer, and  $\mathbb{Z}/n\mathbb{Z}$  be the set of the integers modulo  $n$

- $(\mathbb{Z}/n\mathbb{Z}, +)$  also denoted  $(\mathbb{Z}_n, +)$  is a group
- $(\mathbb{Z}/n\mathbb{Z}, +, \cdot)$  is a ring
- If  $n$  is prime then  $(\mathbb{Z}/n\mathbb{Z}, +, \cdot)$  is the field  $\mathbb{F}_n$
- The invertible elements of  $\mathbb{Z}/n\mathbb{Z}$ , with respect to ' $\cdot$ ', form a group denoted  $U(\mathbb{Z}/n\mathbb{Z})$  or sometimes  $\mathbb{Z}_n^\times$  or  $\mathbb{Z}_n^*$
- $(\mathbb{Z}/n\mathbb{Z}[X], +, \cdot)$  is the ring of the polynomials over  $\mathbb{Z}/n\mathbb{Z}$
- If  $n$  is prime and the polynomial  $P(X)$  is irreducible over  $\mathbb{F}_n[X]$ , then  $(\mathbb{F}_n[X]/\langle P(X) \rangle, +, \cdot)$  is a field; this is  $\mathbb{F}_{n^{\deg P(X)}}$

## Notes

## Definitions

Let  $G$  be a group.

- i The *order* of  $G$  is its cardinality
- ii The *order* of an element  $g \in G$  is the smallest positive integer  $m$  such that  $g^m = 1$
- iii An element of order equal to the order of the group is called a *primitive element* or a *generator*
- iv When  $G = \mathbb{Z}/n\mathbb{Z}$ , Euler's totient function  $\varphi(n)$  counts the number of invertible elements, that is the number of elements  $k$  such that  $\gcd(n, k) = 1$

## Notes

Example. The order of  $U(\mathbb{Z}/13\mathbb{Z}) = 12$  and 2 is a generator:

$i$	$2^i \bmod 13$	$i$	$2^i \bmod 13$	$i$	$2^i \bmod 13$	$i$	$2^i \bmod 13$
1	2	4	3	7	11	10	10
2	4	5	6	8	9	11	7
3	8	6	12	9	5	12	1

Remark. Let  $p$  be a prime and  $\alpha$  be a generator of  $G = U(\mathbb{Z}/p\mathbb{Z})$ . Then any element  $\beta \in G$  can be written  $\beta = \alpha^i$ ,  $1 \leq i \leq p-1$ . Noting  $d = \gcd(i, p-1)$  we have

$$\beta^{\frac{p-1}{d}} = (\alpha^i)^{\frac{p-1}{d}} = (\alpha^{p-1})^{\frac{i}{d}} = 1.$$

Suppose that the order of  $\beta$  divides  $\frac{p-1}{d}$ . Then  $\text{ord}(\beta) = \frac{p-1}{kd}$  for some  $k > 1$  such that  $kd \nmid i$ , meaning that  $\frac{p-1}{k} \cdot \frac{i}{d}$  is not a multiple of  $p-1$ . Hence the order of  $\beta$  is  $\frac{p-1}{d}$ .

## Notes

In theorem 2.99 we recalled that a system of congruences has a unique solution modulo the product of all the moduli of the system. In fact this result can be rephrased in term of group structure.

We first recall that an *isomorphism* is a bijection that preserves algebraic structures.

**Theorem (Chinese Remainder theorem (CRT))**

Let  $n$  be a positive integer with prime decomposition  $n = \prod_i p_i^{e_i}$ . Then there exists a ring *isomorphism* between  $\mathbb{Z}/n\mathbb{Z}$  and  $\prod_i \mathbb{Z}/p_i^{e_i}\mathbb{Z}$ .

## Notes

From the previous theorem (3.145)

$$U(\mathbb{Z}/n\mathbb{Z}) \approx U\left(\prod_i \mathbb{Z}/p_i^{e_i}\mathbb{Z}\right).$$

Noting that a non invertible element of  $\mathbb{Z}/p_i^{e_i}\mathbb{Z}$  is of the form  $kp_i$  for some integer  $k$ , it cannot be coprime to  $n$  and as such is not invertible modulo  $n$ . Conversely an element that is not invertible mod  $n$  is a multiple of some  $p_i$ . Therefore

$$U(\mathbb{Z}/n\mathbb{Z}) \approx U\left(\prod_i \mathbb{Z}/p_i^{e_i}\mathbb{Z}\right) \approx \prod_i U(\mathbb{Z}/p_i^{e_i}\mathbb{Z}).$$

**Proposition**

If  $m$  and  $n$  are two coprime integers then  $\varphi(mn) = \varphi(m)\varphi(n)$ . In particular if  $m$  and  $n$  are prime  $\varphi(mn) = (m-1)(n-1)$ .

## Notes

Having a way to determine the order of  $U(\mathbb{Z}/n\mathbb{Z})$ , we now focus on the order of its elements. We first recall a fundamental result from group theory.

**Theorem (Lagrange's theorem)**

Let  $G$  be a finite group and  $H$  be a subgroup of  $G$ . Then the order of  $H$  divides the order of  $G$ .

Noting that each element  $x$  of  $G$  generates a subgroup of order  $\text{ord}_G x$ , it follows that the order of any element  $x$  of  $G$  divides the order of  $G$ .

Using Lagrange's theorem it is then possible to derive a result to quickly verify whether an invertible element modulo a prime  $p$  is a generator of  $U(\mathbb{Z}/p\mathbb{Z})$ . But first we provide an example and then extend Fermat's little theorem (2.95).

## Notes

**Example.** For  $n = 5$ ,  $U(\mathbb{Z}/5\mathbb{Z}) = \{1, 2, 3, 4\}$  which is a group of order 4. Therefore each of those four elements generates a subgroup of  $U(\mathbb{Z}/5\mathbb{Z})$ . Moreover these subgroups will have order 1, 2, or 4, since 4 is divisible by 1, 2, and 4.

In fact we have

$$\begin{aligned} \langle 1 \rangle &= \{1\}, & \langle 2 \rangle &= \{2, 4, 3, 1\}, \\ \langle 4 \rangle &= \{4, 1\}, & \langle 3 \rangle &= \{3, 4, 2, 1\}. \end{aligned}$$

That is, we have two groups of order 4 ( $\langle 2 \rangle$  and  $\langle 3 \rangle$ ), one group of order 2 ( $\langle 4 \rangle$ ), and one group of order 1 ( $\langle 1 \rangle$ ).

In particular note that the order of an element is equal to the order of the subgroup it generates.

## Notes

**Theorem (Euler's theorem)**

Let  $a$  and  $n$  be two coprime integers. Then

$$a^{\varphi(n)} \equiv 1 \pmod{n}.$$

**Proof.** From the previous reasoning on Lagrange's theorem (3.147) there exists  $k > 0$  such that  $k|\varphi(n)$  and  $a^k = 1$ . Writing  $\varphi(n) = kl$  for some integer  $l$  we have

$$a^{\varphi(n)} = a^{kl} \equiv (a^k)^l \equiv 1^l = 1 \pmod{n}.$$

□

## Notes

**Example.** Calculate  $2^{639613} \pmod{5353}$ .

First we note that 5353 can be written as the product of two primes: 101 and 53. Therefore  $\varphi(5353) = 100 \cdot 52 = 5200$ .

Observing that  $639613 \equiv 13 \pmod{5200}$  we need to consider  $2^{13} \pmod{5353}$ .

As  $2^{13} = 8192$  we obtain  $2^{639613} \equiv 2839 \pmod{5353}$ .

**Remark.** The previous discussion can be simply summarized as follows: when working modulo  $n$ , the exponent must be considered modulo  $\varphi(n)$ .

## Notes

**Theorem**

Let  $p > 2$  be a prime and  $\alpha \in U(\mathbb{Z}/p\mathbb{Z})$ . Then  $\alpha$  is a generator of  $U(\mathbb{Z}/p\mathbb{Z})$  if and only if for all primes  $q$  such that  $q|(p-1)$ ,  $\alpha^{(p-1)/q} \not\equiv 1 \pmod{p}$ .

**Proof.**

( $\Rightarrow$ ) Since  $\alpha$  is a generator, for all  $1 \leq i < p-1$ ,  $\alpha^i \not\equiv 1 \pmod{p}$ .

( $\Leftarrow$ ) Suppose that  $\alpha$  is invertible but does not generate  $U(\mathbb{Z}/p\mathbb{Z})$ . Calling its order  $d$ , the fraction  $(p-1)/d$  defines an integer larger than 1. This is true because  $d|(p-1)$  (Lagrange's theorem (3.147)) and  $d < (p-1)$ . If  $q$  is a prime divisor of  $(p-1)/d$ , then  $d$  divides  $\frac{p-1}{q}$ . So  $\alpha^{(p-1)/q} \equiv 1 \pmod{p}$ .

□

## Notes

**Corollary**

Let  $\alpha$  be a generator of  $U(\mathbb{Z}/p\mathbb{Z})$ .

- ① Let  $n$  be an integer. Then  $\alpha^n \equiv 1 \pmod{p}$  if and only if  $n \equiv 0 \pmod{p-1}$ .
- ② Let  $j$  and  $k$  be two integers. Then  $\alpha^j \equiv \alpha^k \pmod{p}$  if and only if  $j \equiv k \pmod{p-1}$ .

**Proof.** (1) This is straightforward from the previous theorem (3.151).

(2) Without loss of generality assume  $j \geq k$ . First suppose that  $\alpha^j \equiv \alpha^k \pmod{p}$ . Dividing both sides by  $\alpha^k$  yields  $\alpha^{j-k} \equiv 1 \pmod{p}$ . From (1) we have  $j-k \equiv 0 \pmod{p-1}$ .

Conversely if  $j \equiv k \pmod{p-1}$  then  $j-k \equiv 0 \pmod{p-1}$ , and by (1)  $\alpha^{j-k} \equiv 1 \pmod{p}$ . Finally we multiply by  $\alpha^k$ . □

## Notes

We now relate the order of the elements in  $U(\mathbb{Z}/n\mathbb{Z})$ , where  $n$  is a composite integer, to factoring  $n$ .

Let  $x$  be an element of order  $r$  in  $U(\mathbb{Z}/n\mathbb{Z})$ . By definition we have  $x^r \equiv 1 \pmod{n}$ , that is  $n \mid (x^r - 1)$ .

If the order  $r$  is even then  $x^r - 1 = (x^{r/2} - 1)(x^{r/2} + 1)$ . In this case both  $\gcd(x^{r/2} - 1, n)$  and  $\gcd(x^{r/2} + 1, n)$  are factors of  $n$ .

Conversely knowing the factorization of  $n$  gives  $\varphi(n)$ . Since the order of an element  $x$  in  $U(\mathbb{Z}/n\mathbb{Z})$  divides  $\varphi(n)$  it suffices to write  $\varphi(n) = \prod_i p_i$ , where the  $p_i$  are the prime factors of  $\varphi(n)$ . Then calculate  $x^{a/p_i} \pmod{n}$ , with  $a = \varphi(n)$ . If  $x^{a/p_i} \equiv 1 \pmod{n}$ , for some  $i$ , then redefine  $a$  as  $a/p_i$ .

When all the  $p_i$  have been tested  $a$  defines the order of  $x$ . If none of the  $x^{a/p_i} \pmod{n}$  is 1 then  $x$  is a generator, i.e. has order  $\varphi(n)$ .

The previous discussion highlights the difficulty of determining the order of a random element of  $U(\mathbb{Z}/n\mathbb{Z})$ , since it is equivalent to factoring  $n$ .

Another hard problem related to factorization was presented in chapter 2, namely the QR problem (2.94). In that chapter we studied the case where the primes are congruent to 3 modulo 4.

We now provide a more general result that gives a method to determine whether or not an element is a square modulo an arbitrary prime  $p$ .

#### Proposition

For  $p$  an odd prime and  $a$  such that  $a \not\equiv 0 \pmod{p}$ ,  $a^{\frac{p-1}{2}} \equiv \pm 1 \pmod{p}$ . Moreover  $a$  is a square mod  $p$  if and only if  $a^{\frac{p-1}{2}} \equiv 1 \pmod{p}$ .

Proof. Defining  $y \equiv a^{\frac{p-1}{2}} \pmod{p}$  and applying Fermat's little theorem (2.95), we have  $y^2 \equiv a^{p-1} \equiv 1 \pmod{p}$ . Therefore we have

$$y^2 - 1 \equiv (y - 1)(y + 1) \equiv 0 \pmod{p}.$$

As  $p$  is prime all the elements but 0 are invertible, meaning that either  $y \equiv 1 \pmod{p}$  or  $y \equiv -1 \pmod{p}$ .

If  $a \equiv x^2 \pmod{p}$ , then  $a^{\frac{p-1}{2}} \equiv x^{p-1} \equiv 1 \pmod{p}$ .

Conversely let  $g$  be a generator mod  $p$  and write  $a \equiv g^j$  for some  $j$ . If  $a^{\frac{p-1}{2}} \equiv 1 \pmod{p}$ , then

$$g^{j\frac{p-1}{2}} \equiv a^{\frac{p-1}{2}} \equiv 1 \pmod{p}.$$

From corollary 3.152 we see that  $j\frac{p-1}{2} \equiv 0 \pmod{p-1}$  implying that  $j$  must be even. Hence  $a \equiv g^j \equiv g^{2k}$  and  $a$  is a square.  $\square$

Proposition 3.154 provides a simple way to computationally check if an element is a square modulo a prime. Since this criteria is difficult to use by hand we now introduce an alternative strategy.

#### Definition (Legendre symbol)

Given  $p$  be an odd prime and  $a \not\equiv 0 \pmod{p}$ , we define the *Legendre symbol* by

$$\left(\frac{a}{p}\right) = \begin{cases} +1 & \text{if } a \text{ is a square mod } p \\ -1 & \text{if } a \text{ is not a square mod } p \end{cases}$$

## Proposition

Let  $p$  be an odd prime.

- ① If  $a \equiv b \pmod{p}$ , then  $\left(\frac{a}{p}\right) = \left(\frac{b}{p}\right)$ .
- ② If  $a \not\equiv 0 \pmod{p}$ , then  $\left(\frac{a}{p}\right) \equiv a^{\frac{p-1}{2}} \pmod{p}$ .
- ③ If  $ab \not\equiv 0 \pmod{p}$ , then  $\left(\frac{ab}{p}\right) = \left(\frac{a}{p}\right) \left(\frac{b}{p}\right)$ .
- ④ If  $p \equiv 1 \pmod{4}$  then  $-1$  is a square mod  $p$ .

Proof.

- ① The solutions to the congruence  $x^2 \equiv a \pmod{p}$  and  $x^2 \equiv b \pmod{p}$  are the same when  $a \equiv b \pmod{p}$ .
- ② Combining the definition of Legendre symbol (3.156) with proposition 3.154 yields the result.

## Notes

Proof (continued).

- ③ From (2), we have  $\left(\frac{ab}{p}\right) = (ab)^{\frac{p-1}{2}} \equiv a^{\frac{p-1}{2}} b^{\frac{p-1}{2}} \equiv \left(\frac{a}{p}\right) \left(\frac{b}{p}\right) \pmod{p}$ .

Both ends being congruent to  $\pm 1$  modulo the odd prime  $p$  they are equal.

- ④ Applying (2) with  $a = -1$  we have  $\left(\frac{-1}{p}\right) \equiv (-1)^{\frac{p-1}{2}} \pmod{p}$ .

Again, since both ends are congruent to  $\pm 1$  modulo the odd prime  $p$  they are equal. Noting that when  $p \equiv 1 \pmod{4}$ ,  $(p-1)/2$  is even gives the result.  $\square$

## Notes

Example. Is 12 a square mod 31?

Since  $12 = 2^2 \cdot 3$  we write

$$\left(\frac{12}{31}\right) = \left(\frac{2}{31}\right)^2 \left(\frac{3}{31}\right).$$

Moreover

$$\left(\frac{3}{31}\right) \equiv 3^{15} \equiv -1 \pmod{31}.$$

Hence 12 is not a square mod 31.

## Notes

In definition 3.156 the Legendre symbol is defined for primes. We would like to extend this definition to any odd integer  $n$ .

As a first attempt we define the symbol to be  $+1$  if an integer  $a$  is a square and  $-1$  otherwise.

Example. Is 6 a square mod 35?

Noting that  $6 = 2 \cdot 3$  we need to consider whether 2 and 3 are squares mod 35. In fact neither of them is, since they are not squares mod 5.

Similarly 6 is not a square mod 7, and as such cannot be a square mod 35.

Consequently, none of 2, 3, and 6 is a square mod 35, implying the third property of proposition 3.157 to give  $(-1) \cdot (-1) = -1$ .

## Notes



To preserve the third property of the Legendre symbol (3.157) we define the Jacobi symbol as follows.

**Definition (Jacobi symbol)**

Given  $n = \prod_i p_i^{e_i}$  an odd integer and  $a$  a non-zero integer coprime to  $n$ , we define the *Jacobi symbol* by

$$\left(\frac{a}{n}\right) = \prod_i \left(\frac{a}{p_i}\right)^{e_i},$$

where each of the  $\left(\frac{a}{p_i}\right)$  is a Legendre symbol.

Notes

Remark.

- When  $n$  is prime the Jacobi symbol reduces to the Legendre symbol
- Let  $n = 135 = 3^3 \cdot 5$ . Then

$$\left(\frac{2}{135}\right) = \left(\frac{2}{3}\right)^3 \left(\frac{2}{5}\right) = (-1)^3(-1) = 1.$$

However 2 is not a square mod 135 since it is not a square mod 5.

Hence a value of +1 for the Jacobi symbol does not imply that an integer is a square mod  $n$ .

Notes

**Proposition**

Let  $n$  be an odd integer.

- 1 If  $a \equiv b \pmod{n}$  and  $\gcd(a, n) = 1$ , then  $\left(\frac{a}{n}\right) = \left(\frac{b}{n}\right)$ .
- 2 If  $\gcd(ab, n) = 1$  then  $\left(\frac{ab}{n}\right) = \left(\frac{a}{n}\right) \left(\frac{b}{n}\right)$ .
- 3  $\left(\frac{-1}{n}\right) = (-1)^{\frac{n-1}{2}}$ .
- 4  $\left(\frac{2}{n}\right) = \begin{cases} +1 & \text{if } n \equiv 1 \text{ or } 7 \pmod{8} \\ -1 & \text{if } n \equiv 3 \text{ or } 5 \pmod{8} \end{cases}$
- 5 If  $m$  and  $n$  are odd coprime positive integers, then

$$\left(\frac{m}{n}\right) = \begin{cases} -\left(\frac{n}{m}\right) & \text{if } m \equiv n \equiv 3 \pmod{4} \\ +\left(\frac{n}{m}\right) & \text{otherwise} \end{cases}$$

Notes

**Example.** Calculate  $\left(\frac{4567}{12345}\right)$ .

$$\begin{aligned} \left(\frac{4567}{12345}\right) &= +\left(\frac{12345}{4567}\right) && \text{by (5), since } 12345 \equiv 1 \pmod{4} \\ &= +\left(\frac{3211}{4567}\right) && \text{by (1), since } 12345 \equiv 3211 \pmod{4567} \\ &= -\left(\frac{1356}{3211}\right) && \text{by (5) and (1)} \\ &= -\left(\frac{2}{3211}\right)^2 \left(\frac{339}{3211}\right) && \text{by (2)} \\ &= +\left(\frac{3211}{339}\right) && \text{since } (\pm 1)^2 = 1 \text{ and by (5)} \\ &= +\left(\frac{2}{339}\right)^5 \left(\frac{5}{339}\right) && \text{by (5) and since } 2^5 \cdot 5 = 160 \equiv 3211 \pmod{339} \\ &= -\left(\frac{2}{5}\right)^2 && \text{by (4), (5), and (2)} \\ &= -1 \end{aligned}$$

Notes

## Remark.

- In proposition 3.163 the fifth point is called the *quadratic reciprocity law*. When  $m$  and  $n$  are primes it relates the question of  $m$  being a square mod  $n$  to the one of  $n$  being a square mod  $m$ .
- Let  $n$  be the product of two primes  $p$  and  $q$  and  $a$  be an integer. If  $\left(\frac{a}{n}\right) = -1$ , then  $a$  is not a square mod  $n$ . What can be concluded if  $\left(\frac{a}{n}\right) = +1$ ?

As  $\left(\frac{a}{n}\right) = \left(\frac{a}{p}\right) \left(\frac{a}{q}\right)$ , either

$$\left(\frac{a}{p}\right) = \left(\frac{a}{q}\right) = -1 \text{ or } \left(\frac{a}{p}\right) = \left(\frac{a}{q}\right) = +1.$$

In the first case  $a$  is not a square mod  $p$  and as such cannot be a square mod  $n$ , while in the second case  $a$  is a square.


## Notes

From the previous remark (3.165) we see that if  $\left(\frac{a}{n}\right) = +1$  then  $a$  can be either a square or a non-square. Deciding which one holds is known as the *Quadratic Residuosity Problem*, loosely introduced in problem 2.94.

**Problem (Quadratic Residuosity (QR))**

Let  $n = pq$  be the product of two primes. Let  $y$  be an integer such that  $\left(\frac{y}{n}\right) = 1$ . Determining whether or not  $y$  is a square modulo  $n$  is called the *Quadratic Residuosity Problem*.

## Notes



## Notes

From the previous mathematical discussions in chapters 1 and 3 we know that given two primes  $p$  and  $q$ , it is easy to compute their product  $n$  as well as  $\varphi(n)$  (proposition 3.146).

Then if an integer  $e$ , coprime to  $\varphi(n)$ , is chosen, it suffices to run the extended Euclidean algorithm (1.51) in order to determine the integer  $d$  such that  $ed \equiv 1 \pmod{\varphi(n)}$ .

Therefore given  $e$  and  $n$  it is possible to compute  $c \equiv m^e \pmod{n}$  for any integer  $m$ . Then computing  $c^d \pmod{n}$  yields  $m$  since

$$c^d \equiv (m^e)^d \equiv m^{ed} \pmod{\varphi(n)} \equiv m \pmod{n}.$$

The goal is now to use this mathematical setup in order to build a trapdoor one-way function and design a public key cryptosystem.

## Notes

Intuition:

- Generate  $p$  and  $q$ , then compute  $n$  and  $\varphi(n)$
- Choose  $e$  coprime to  $\varphi(n)$  and determine  $d$
- Anybody can encrypt:  $n$  and  $e$  are public
- Only one person can decrypt:  $d$  is secret

Questions:

- How to effectively define the cryptosystem?
- Can the modular exponentiations to encrypt and decrypt be efficiently computed?
- How to efficiently generate  $p$  and  $q$ ?
- How secure is it?

This cryptosystem, named RSA after its inventors Rivest, Shamir and Adleman, is the most popular public key cryptosystem.

## Notes

Initial setup:



- $p, q$  two primes
- $n = pq$  and  $\varphi(n)$
- $e, d$  such that  $ed \equiv 1 \pmod{\varphi(n)}$
- The  $n$  from Bob
- The  $e$  from Bob



Encryption:

- A message  $m$
- Send  $c \equiv m^e \pmod{n}$  to Bob



Decryption:



- Receive  $c$  from Alice or Eve
- Compute  $m \equiv c^d \pmod{n}$

## Notes

Example.

- Bob generates:
  - $p = 101$  and  $q = 113$
  - $n = 11413$  and  $\varphi(n) = 11200$
  - Select a random  $e$  and compute both its  $\gcd(e, \varphi(n))$  and  $d = e^{-1}$  using the Extended Euclidian Algorithm (1.51). If the gcd is not one select a different  $e$  and retry. Let  $e$  be 3533, then  $\gcd(e, \varphi(n)) = 1$  and  $d = 6597$ .
- Bob publishes  $n$  and  $e$
- Anybody can use those parameters to encrypt a message and send it to Bob. In particular Alice or Eve can encrypt 9726:
 
$$9726^{3533} \equiv 5761 \pmod{11413}.$$
- On receiving the message Bob computes
 
$$5761^{6597} \equiv 9726 \pmod{11413}.$$

## Notes

The modular exponentiations required to encrypt and decrypt the message can be done efficiently in  $\mathcal{O}((\log n)^2 \log d)$  bit operations, using the following algorithm.

Algorithm. (*Square and multiply*)

**Input** :  $m$  an integer,  $d = (d_{k-1} \dots d_0)_2$  and  $n$  two positive integers

**Output** :  $x = m^d \pmod{n}$

**put** :

- $power \leftarrow 1;$
- for**  $i \leftarrow k-1$  **to** 0 **do**
  - $power \leftarrow (power \cdot power) \pmod{n};$
  - if**  $d_i = 1$  **then**  $power \leftarrow (m \cdot power) \pmod{n};$
- end for**
- return**  $power$

## Notes

Example. Calculate  $9726^{3533} \bmod 11413$ .

We run the previous algorithm with:  $m = 9726$ ,  $n=11413$  and  $d = 3533 = (110111001101)_2$ .

$i$	$d_i$	$power \bmod 11413$	$i$	$d_i$	$power \bmod 11423$
11	1	$1^2 \cdot 9726 \equiv 9726$	5	0	$7783^2 \equiv 6298$
10	1	$9726^2 \cdot 9726 \equiv 2659$	4	0	$6298^2 \equiv 4629$
9	0	$2659^2 \equiv 5634$	3	1	$4629^2 \cdot 9726 \equiv 10185$
8	1	$5634^2 \cdot 9726 \equiv 9167$	2	1	$10185^2 \cdot 9726 \equiv 105$
7	1	$9167^2 \cdot 9726 \equiv 4958$	1	0	$105^2 \equiv 11025$
6	1	$4958^2 \cdot 9726 \equiv 7783$	0	1	$11025^2 \cdot 9726 \equiv 5761$

## Notes

Two useful optimizations to the decryption can be applied. The first and most obvious consists in saving  $d \bmod \varphi(n)$  such that it is not recomputed at each decryption.

The second idea consists in using the CRT (2.99, 3.145) to speed up the computation. Instead of storing  $d \bmod \varphi(n)$  one can save  $d \bmod (p-1)$  as well as  $d \bmod (q-1)$ , recover the "two sub-messages" in  $\mathbb{Z}/p\mathbb{Z}$  and  $\mathbb{Z}/q\mathbb{Z}$ , and combine them over  $\mathbb{Z}/n\mathbb{Z}$ .

Example. Let  $p = 11$ ,  $q = 23$  and  $e = 3$ . Then  $n = 253$ ,  $\varphi(n) = 220$  and  $d = 147$ . To encrypt  $m = 57$  we compute  $c = 57^3 \equiv 250 \bmod 253$ .

Instead of computing  $m \equiv 250^{147} \bmod 253$  we do

$$\begin{cases} 250^{147 \bmod 10} \equiv 8^7 \equiv 2 \bmod 11 \\ 250^{147 \bmod 22} \equiv 20^{15} \equiv 11 \bmod 23. \end{cases}$$

## Notes

It now suffices to combine the results mod  $p$  and  $q$  into a single result mod  $n$ .

Bézout's identity gives  $(-2) \cdot 11 + 1 \cdot 23 = 1$ . Therefore  $1_p$  is mapped into  $23 \bmod 253$  and  $1_q$  into  $-22 \equiv 231 \bmod 253$ .

Hence,

$$\begin{aligned} (2, 11) &= 2 \cdot 1_p + 11 \cdot 1_q \\ &= 2 \cdot 23 + 11 \cdot 231 \bmod 253 \\ &\equiv 2587 \bmod 253 \\ &\equiv 57 \bmod 253. \end{aligned}$$

And the plaintext is recovered.

## Notes

Which strategy to choose:

- Generate a random integer, pick the next prime
- Generate random integers until one of them is prime

Remark.

- The prime number theorem states that in the range  $1-n$  approximately  $n/\ln n$  integers are prime. As we will discuss later, the primes  $p$  and  $q$  are expected to be about 1024 bits long. Therefore the probability for a random integer between 1 and  $2^{1024}$  to be prime is  $1/\ln 2^{1024} \approx 1/710$ .
- Although a deterministic polynomial time algorithm exists for primality testing (AKS), Monte Carlos algorithms, which are much faster solutions, are often used in practice.

## Notes

From proposition 3.157 we know that if  $n$  is prime then for any  $a \not\equiv 0 \pmod n$ ,

$$\left(\frac{a}{n}\right) \equiv a^{(n-1)/2} \pmod n. \quad (3.1)$$

Unfortunately there exist some integers  $a$  for which it is also true although  $n$  is not prime. It is therefore impossible to derive a deterministic algorithm from this proposition.

On the other hand, we can observe the following property. Let  $n$  be composite and  $A = \{a / \gcd(a, n) = 1 \text{ and } (3.1) \text{ holds}\}$ . Since  $n$  is composite there exists an integer  $b$  such that  $\gcd(b, n) = 1$  and  $\left(\frac{b}{n}\right) \not\equiv b^{(n-1)/2} \pmod n$ . For any  $a \in A$  we have

$$(ab)^{\frac{n-1}{2}} \equiv a^{\frac{n-1}{2}} b^{\frac{n-1}{2}} \equiv \left(\frac{a}{n}\right) b^{\frac{n-1}{2}} \not\equiv \left(\frac{a}{n}\right) \left(\frac{b}{n}\right) \pmod n.$$

Hence, for any  $a \in A$  there is an element coprime to  $n$  that does not belong to  $A$ . It is then possible to construct a Monte Carlo Algorithm that determines whether or not  $n$  is prime.

The following algorithm requires  $\mathcal{O}(k(\log n)^3)$  operations to test the primality of  $n$ ,  $k$  being the number of random elements generated for the test.

Algorithm. (*Solovay-Strassen*)

**Input** :  $n$  an integer, and  $k$  the number of tests to run

**Out-** :  $n$  is composite or probably prime

**put** :

```

1 for  $i \leftarrow 1$  to  $k$  do
2    $a \leftarrow \text{rand}(2, n-2)$ ;
3   if  $\gcd(a, n) \neq 1$  then return  $n$  is composite;
4    $x \leftarrow \left(\frac{a}{n}\right)$ ;
5    $y \leftarrow a^{(n-1)/2} \pmod n$ ;
6   if  $x \not\equiv y \pmod n$  then return  $n$  is composite;
7 end for
8 return  $n$  is probably prime
```

The Miller-Rabin test is a Monte Carlo Algorithm that determines whether or not an integer is prime.

Let  $n \in \mathbb{N}$  be an odd integer. Then  $n-1 = 2^s m$ , where  $s$  is an integer and  $m$  is odd. The integer  $n$  passes the *Miller-Rabin test to base  $a$*  if either

$$a^m \equiv 1 \pmod n \quad \text{or} \quad a^{2^j m} \equiv -1 \pmod n$$

for some  $j$  with  $0 \leq j \leq s-1$ .

To see it, observe that if  $n$  is prime then  $x^2 \equiv 1 \pmod n$  has only two solutions:  $+1$  and  $-1$ . Moreover Fermat's little theorem (2.95) applies and  $a^{n-1} \equiv 1 \pmod n$ .

Therefore taking the square root of  $a^{n-1}$  yields  $1$  or  $-1$ . On  $-1$  the second congruence holds. If this is  $1$  then the square root can be taken again until it is either  $-1$  or only  $m$  is left. Hence one of the two congruences holds.

Finally the contrapositive states that if neither of the congruences holds then  $n$  is composite.

Noticing the two following points we can now derive a probabilistic algorithm which returns whether an integer is composite or probably prime.

- If  $n$  is prime and  $1 < a < n$ , then  $n$  passes Miller's test to base  $a$ .
- If  $n$  is composite, then there are fewer than  $n/4$  bases  $a$  with  $1 < a < n$  such that  $n$  passes Miller's test to base  $a$ .

The Monte Carlo algorithm now randomly selects  $k$  bases  $a$  and performs the Miller-Rabin test.

- If  $n$  fails the test for any of the bases used, the algorithm will return "true" ( $n$  is composite).
- If  $n$  passes each test, the answer is still unknown. Nevertheless, the algorithm will return "false" ( $n$  is probably prime).

The probability that  $n$  is composite and still passes the test each of the  $k$  times is

$$p_k = \frac{1}{4^k}.$$

For instance if  $k = 30$  tests are performed,  $p_k < 10^{-18}$ . It is almost certain that a number that the algorithm returns as prime actually is prime.

### Algorithm. (Miller-Rabin)

**Input** :  $n$  an odd integer, and  $k$  the number of tests to run

**Output** :  $n$  is composite or probably prime

```

1  $m \leftarrow (n-1)/2$ ;  $s \leftarrow 1$ ;
2 while  $2|m$  do  $m \leftarrow m/2$ ;  $s \leftarrow s+1$ ;
3 for  $i \leftarrow 1$  to  $k$  do
4    $a \leftarrow \text{rand}(2, n-2)$ ;
5   if  $\text{gcd}(a, n) \neq 1$  then return  $n$  is composite;
6    $a \leftarrow a^m \bmod n$ ;
7   if  $a = \pm 1$  then continue;
8   for  $j \leftarrow 1$  to  $s-1$  do
9      $a \leftarrow a^2 \bmod n$ ;
10    if  $a \equiv 1 \bmod n$  then return  $n$  is composite;
11    if  $a \equiv -1 \bmod n$  then break;
12  end for
13  if  $a \neq 1$  then continue else return  $n$  is composite;
14 end for
15 return  $n$  is probably prime

```

The last question that remains to be answered is related to the security of RSA. The RSA cryptosystem can be viewed as having three secret parameters:  $p$ ,  $q$  and  $d$ .

If  $n$  and  $\varphi(n)$  are known, then  $p$  and  $q$  can be efficiently recovered.

Note that

$$n - \varphi(n) + 1 = pq - (p-1)(q-1) + 1 = p + q.$$

Since we know  $pq$  and  $p + q$ ,  $p$  and  $q$  are the roots of the quadratic equation  $X^2 - (n - \varphi(n) + 1)X + n$ . Hence

$$p, q = \frac{n - \varphi(n) + 1 \pm \sqrt{(n - \varphi(n) + 1)^2 - 4n}}{2}.$$

Said otherwise, if  $\varphi(n)$  can be computed then  $n$  can be factorised. Since factorizing  $n$  is believed to be hard there should be no way of efficiently compute  $\varphi(n)$ .

Suppose that both  $e$  and  $d$  are known. Then  $n$  can be efficiently factorised.

Since  $de \equiv 1 \bmod \varphi(n)$ , for any  $a$  coprime to  $n$ ,  $a^{de-1} \equiv 1 \bmod n$ .

The idea is now to select some random  $a$  coprime to  $n$ , and apply the strategy described on slide 3.153. Note that if  $a$  and  $n$  are not coprime then  $\text{gcd}(a, n)$  is factor of  $n$ . Therefore let's assume their gcd to be 1.

We start by writing  $ed - 1$  as  $2^s m$  and then define  $b_0 = a^m$  and  $b_{i+1} \equiv b_i^2 \bmod n$ . As we expect to find the order of  $a$  we want  $b_{i+1} \equiv 1 \bmod n$ , while  $b_i \not\equiv 1 \bmod n$ . Moreover if  $b_i \equiv -1 \bmod n$  then the factors are trivial. Therefore our aim is to find an  $a$  such that  $b_i \not\equiv \pm 1$  and  $b_{i+1} \equiv 1 \bmod n$ . In this case,  $\text{gcd}(b_i - 1, n)$  and  $\text{gcd}(b_i + 1, n)$  are non-trivial factors of  $n$ .

Hence finding  $d$  should be hard since it allows to factorize  $n$ .

From the previous discussion it appears that the RSA cryptosystem relies on the hardness of factoring large composite integers. But more precisely it is the hardness of determining  $\varphi(n)$  when only  $n$  is known without its prime decomposition. The RSA problem can be formally stated as follows.

#### Problem (RSA problem)

Let  $n$  be a large integer and  $e > 0$  be coprime to  $\varphi(n)$ . Given  $y$  in  $\mathbb{U}(\mathbb{Z}/n\mathbb{Z})$ , compute  $y^{1/e} \bmod n$ , i.e. find  $x$  such that  $x^e \equiv y \bmod n$ .

Although factoring  $\varphi(n)$  or computing  $d$  solves the RSA problem there is no proof that no other way of solving it exists. Therefore it cannot be concluded that the RSA problem is as hard as factoring. Indeed it may be that the RSA problem can be solved in polynomial time even though the factoring problem cannot.

#### Notes

Complexity of a few factorization algorithms for  $n$  a  $k$ -bit integer:

Algorithm	Complexity
Trial division	$\mathcal{O}(2^{k/2}/k)$
Pollard- $\rho$	$\mathcal{O}(\sqrt[4]{n})$
ECM	$L_p\left[1/2, \sqrt{2}\right]$
GNFS	$L_n\left[1/3, \sqrt[3]{64/9}\right]$

The  $L_n(\alpha, c)$  function is defined by

$$L_n(\alpha, c) = e^{(c+o(1))((\ln n)^\alpha (\ln \ln n)^{1-\alpha})}.$$

#### Notes

Given a large random integer  $N$ , the probability for  $N$  to be divisible by 2 is  $1/2$ ; by 3,  $1/3$ ; by 5,  $1/5$  etc. One can deduce that about 88% of integers have a factor smaller than 100 and 92% a factor smaller than 1000.

Therefore, despite its exponential complexity, trial division is used in almost all factoring programs. All the small factors are first removed before more advanced strategies are employed to totally factorize  $N$ .

In practice, trial division is implemented through a large table containing all the primes, or alternatively the difference between two consecutive primes, up to 10 million. Then even for a 1000 digit long integer it only takes a few seconds to perform all the trial divisions and ensure that  $N$  is free of any small factor.

#### Notes

Another simple idea in order to remove small factors consists in computing  $\gcd(n, P)$  where  $P$  corresponds to the product of all the prime numbers below a given bound  $B$ . Compared to trial division this strategy seems appealing since computing a gcd can be done in polynomial time. In practice, this method is much more efficient when considering primes below 1000 but it becomes extremely slow when checking prime factors of size around one million.

In the first case the product of all the primes is about 1,400 bits while in the second case it is approximately 1,500,000! Computing the gcd of an integer around  $2^{3072}$  and  $P$ , then takes much longer.

This simple example highlights how practical cases can highly diverge from the theoretical asymptotic analysis.

#### Notes

189

Pollard's Rho Algorithm

We now introduce an example of a more sophisticated factoring scheme. It is asymptotically faster than trial factorization and can be used when small numbers have been eliminated as possible factors.

Let  $n$  be a composite integer with an unknown prime factor  $p \leq \sqrt{n}$ . Define the function

$$f: \mathbb{Z}/n\mathbb{Z} \rightarrow \mathbb{Z}/n\mathbb{Z}, \quad f(x) = x^2 + 1 \bmod n$$

(other functions  $f: \mathbb{Z}/n\mathbb{Z} \rightarrow \mathbb{Z}/n\mathbb{Z}$  can be used). We now recursively define a sequence  $(x_k)$  by

$$x_0 = 2, \quad x_{k+1} = f(x_k), \quad k \in \mathbb{N}.$$

Since there are exactly  $n$  elements in  $\mathbb{Z}/n\mathbb{Z}$ , the sequence must at some point produce a repeated value and enter a cycle.

Notes

190

Pollard's Rho Algorithm

We then **hope** that the cycle contains two or more elements with the same remainder modulo  $p$ , i.e., that we can find  $x_i$  and  $x_j$ ,  $i \neq j$ , in the cycle such that

$$x_i \equiv x_j \bmod p.$$

If that is the case, then  $x_i - x_j$  is divisible by  $p$  and  $\gcd(x_i - x_j, n)$  gives a factor of  $n$ .

In summary, when testing all of the  $x_i$  and  $x_j$  of the cycle, this GCD can evaluate as follows:

$$\gcd(x_i - x_j, n) = \begin{cases} n & \text{if } x_i = x_j, \\ 1 & \text{if } x_i \not\equiv x_j \bmod p \text{ for all factors } p \text{ of } n, \\ t & \text{if } x_i \equiv x_j \bmod p, \text{ where } p \mid t \text{ and } t \mid n. \end{cases}$$

Notes

191

Pollard's Rho Algorithm

The algorithm now uses the following method to evaluate pairs  $x_i, x_j$  in the cycle: two sequences  $(x_k)$  and  $(y_k)$  are defined,

$$x_0 = 2, \quad x_{k+1} = f(x_k) \quad \text{and} \quad y_0 = 2, \quad y_{k+1} = f(f(y_k)).$$

The sequences  $(x_k)$  traverses the cycle normally, while the sequence  $(y_k)$  traverses the cycle in double steps. This is intended to be an efficient manner of generating "random" pairs  $(x_i, x_j)$ . For each pair,  $\gcd(x_i - x_j, n)$  is evaluated.

Example. Suppose that we want to factor the number  $n = 8051$ . We start with  $x_0 = 2$  and set  $x_{k+1} = x_k^2 + 1 \bmod 8051$ . We obtain the sequence  $(x_i) = (2, 5, 26, 677, \mathbf{7474}, 2839, 871, 1848, 1481, 3490, 6989, 705, 5915, 5631, 3324, 3005, 4855, 5749, 1647, \mathbf{7474}, 2839, \dots)$  and we have found a cycle starting at  $x_4 = 7474$ .

Notes

192

Pollard's Rho Algorithm

In practice, we simply generate the sequences  $(x_k)$  and  $(y_k)$  and evaluate the GCDs:

$x_k$	2	5	26	677	7474	2839
$y_k$	2	26	7474	871	1481	6989
$\gcd(x_k - y_k, n)$	8051	1	1	97	1	83
$x_k$	871	1848	1481	3490	6989	705
$y_k$	5915	3324	4855	1647	2839	1848
$\gcd(x_k - y_k, n)$	97	1	1	97	83	1
$x_k$	5915	5631	3324	3005	4855	5749
$y_k$	3490	705	5631	3005	5749	7474
$\gcd(x_k - y_k, n)$	97	1	1	8051	1	1

Even before the cycle is entered by  $(x_k)$ , a factor  $p = 97$  of  $n = 8051$  is found.

Notes



**Algorithm.** (*Pollard- $\rho$  – Factorization*)**Input:**  $n$ , a composite integer,  $f(x) = x^2 + 1 \bmod n$ .**Output:**  $d$  a non-trivial factor of  $n$ , or failure.

```

1  $a \leftarrow 2; b \leftarrow 2;$ 
2 repeat
3    $a \leftarrow f(a); b \leftarrow f(f(b));$ 
4    $d \leftarrow \gcd(a - b, n);$ 
5 until  $d \neq 1;$ 
6 if  $d = n$  then
7   return failure
8 else
9   return  $d$ 
10 end if
```

## Notes

## Complexity of Pollard's Rho Algorithm

The Pollard Rho algorithm derives its name from the shape of the sequence  $(x_k)$ . At some point in the sequence,  $x_k \equiv x_{k+T} \bmod p$  for some  $T > 0$  and the sequence can be represented as a cycle from that point onwards - this is the circle of the letter  $\rho$ . The sequence terms  $x_0, x_1, \dots, x_{k-1}$  then form the "tail" of  $\rho$ .

Remark.

- The role of  $f$  is to "randomly" select numbers in  $\mathbb{Z}/n\mathbb{Z}$ . Its precise form is not essential, but it should be a polynomial for  $f(f(x) \bmod n) \bmod n = f(f(x)) \bmod n$  when calculating the sequence  $(y_k)$ .
- It is not guaranteed that the Pollard Rho algorithm actually will be successful - it could happen that all of the  $x_i$  in the cycle have distinct remainders modulo  $p$ . In that case, a different starting point  $x_0$  should be chosen and the algorithm run once more.

## Notes

## Complexity of Pollard's Rho Algorithm

We now attempt to make a rough estimate of the average time complexity of the algorithm. Let us ignore the specifics and suppose that the algorithm simply selects random numbers  $x_i, x_j \in \mathbb{Z}/n\mathbb{Z}$  for comparison of their remainders.

Suppose that any given number between 0 and  $n$  has an equal probability  $1/p$  of having a remainder  $m$  modulo  $p$ ,  $0 \leq m < p$ :

$$P[x_k \bmod p = m] = \frac{1}{p} \quad \text{for all } m = 0, \dots, p-1 \text{ and all } k \in \mathbb{N}.$$

Suppose that for any two  $x_i$  and  $x_j$ ,  $i \neq j$ , these probabilities are independent. Then the probability that  $x_i$  and  $x_j$  have different remainders is

$$P[x_i \not\equiv x_j \bmod p] = \frac{p-1}{p},$$

## Notes

## Complexity of Pollard's Rho Algorithm

Suppose that  $x_0, \dots, x_{k-1}$  have distinct remainders modulo  $p$ , then the probability of  $x_k$  to have a remainder different from  $x_0, \dots, x_{k-1}$  is  $\frac{p-k}{p}$ .

Then (assuming the independence of the value of the remainder) the probability that a group of  $k$  numbers has distinct remainders mod  $p$  is

$$P_k := P[x_i \not\equiv x_j \bmod p, 0 \leq i < j \leq k] \\ = \prod_{l=0}^{k-1} \frac{p-l}{p} = \frac{p!}{(p-k)!p^k}.$$

It can be shown that  $1 - P_k < 1/2$  if  $k > 1.177\sqrt{p}$ .

This indicates that the average-case complexity of Pollard's Rho algorithm should be

$$\mathcal{O}(\sqrt{p}) = \mathcal{O}(\sqrt[4]{n}).$$

## Notes

In the RSA case  $n$  is known to be product of two large primes. Therefore the algorithm of choice is the GNFS. Then applying the strategy described on slide 1.70 we set

$$2^{128} = e^{\sqrt[3]{\frac{64}{9}(\ln n)^{1/3}(\ln \ln n)^{2/3}}},$$

which gives approximately  $n = 7.65 \cdot 10^{763}$ . In terms of bit length,  $n$  should be about 2500 bits long. In practice, this is rounded up to 3072 bits (2048+1024), and a bit length of 3072 is considered "secure" as it corresponds to 128 bits security.

As of 2014, the largest product of two large primes officially factorized occurred in the breaking of RSA-768 (a 768 bits RSA modulus):

```
123018668453011775513049495838496272077285356959533479219732452151726400507263657518745202199786
4693899564749427740638459251925732 6303453731548268507917026122142913461670429214311602221240479
274737794080665351419597459856902143413
=
3347807169895689878604416984821269081770479498371376856891243138898288379387800228761471165253174
3087737814467999489
x
3674604366679959042824463379962795263227915816434308764267603228381573966651127923337341714339681
0270092798736308917
```

Strategy for short messages and small  $e$ :

- A message  $m < n^{1/e}$
- The ciphertext is  $c \equiv m^e \pmod n$
- The encryption does not require any modular reduction
- Over the integers  $c$  is also  $m^e$
- Solve  $c^{1/e}$  over the integers recovers  $m$

Typical use: encrypt a 128 bits long secret key using RSA

Strategy for short messages:

- A message  $m$  of less than about  $10^{17}$  bits
- The ciphertext is  $c = m^e \pmod n$
- Compute and store in a table  $cx^{-e} \pmod n$ , for all  $1 \leq x \leq 10^9$
- Compute  $y^e \pmod n$ , for all  $1 \leq y \leq 10^9$ , and test for a collision
- If a collision is found then  $c = (xy)^e \pmod n$
- If  $m \leq 10^{17}$  it is likely that such  $x$  and  $y$  exist

Strategy for small  $e$ :

- A message  $m$  sent to  $i \geq e$  persons using the keys  $\langle n_i, e \rangle$
- If  $\gcd(n_k, n_j) \neq 1$  then one of the  $n_i$  can be factorized
- Otherwise set  $n = \prod_i n_i$
- Use the CRT over all the ciphertext  $c_i = m^e \pmod{n_i}$  to compute  $c \equiv m^e \pmod n$
- As  $m < \min_i(n_i)$  and  $i \geq e$ , then  $m^e < n$
- Finally  $m = c^{1/e}$  can be computed in  $\mathbb{N}$

201
A more secure RSA

Current version of RSA:

- Referred to as "textbook RSA"
- Insecure but simple to understand

PKCS #1 v1.5:

- Randomly pad the message before encrypting
- Assumed to be CPA secure
- No proof based on the RSA problem
- Not CCA secure
- Still widely used for backward-compatibility reasons

Notes

---

---

---

---

---

---

---

---

---

---

202
Toward a secure RSA

Optimal Asymmetric Encryption Padding (RSA-OAEP):

- Due to Bellare and Rogaway
- Standardized as PKCS #1 v2
- Similar to feistel network in the construction
- Proved to be CCA secure

Notations:

- Concatenation of two bit strings  $a$  and  $b$ :  $a||b$
- Repetition of a bit  $b$ ,  $d$  times:  $b^d$
- Random oracle are informally defined on slide 2.103

Notes

---

---

---

---

---

---

---

---

---

---

203
RSA-OAEP

Generate: set  $p, q, n, e$ , and  $d$ , and choose two random oracles  $G : \{0, 1\}^{2l} \rightarrow \{0, 1\}^{2l}$  and  $H : \{0, 1\}^{2l} \rightarrow \{0, 1\}^{2l}$ , for  $l \in \mathbb{N}$

Encrypt: a message  $m \in \{0, 1\}^l$

- Pick a random  $r \in \{0, 1\}^{2l}$
- Set  $m' = m || 0^l$
- Compute  $m'' = (G(r) \oplus m') || (r \oplus H(G(r) \oplus m'))$
- Define the ciphertext as  $c = (m'')^e \bmod n$ .

Decrypt: a ciphertext  $c$

- Compute  $m'' = c^d \bmod n$ .
- Parse  $m''$  as  $m_1 || m_2$ , with  $m_1, m_2$  of size  $2l$
- Recover  $r = H(m_1) \oplus m_2$
- Recover  $m' = m_1 \oplus G(r)$
- If the  $l$  last bits are not  $0^l$  output error
- Otherwise output  $m$ , the first  $l$  bits of  $m'$

Notes

---

---

---

---

---

---

---

---

---

---

204
Chapter organisation

```

graph TD
    A((Public Key Cryptography)) --- B((Factoring problem))
    A --- C((Discrete logarithm problem))
    A --- D((Mathematics to the rescue))

```

Notes

---

---

---

---

---

---

---

---

---

---

After investigating the RSA problem (3.185) we now turn our attention to another hard problem from number theory.

**Problem (Discrete Logarithm Problem (DLP))**

Let  $\mathbb{F}_q$  be a finite field, with  $q = p^n$ , for a positive integer  $n$ . Given  $\alpha$  a generator of  $G$ , a subgroup of  $\mathbb{F}_q^*$ , and  $\beta \in G$ , find  $x$  such that  $\beta = \alpha^x$  in  $\mathbb{F}_q$ .

Note that  $x$  is unique only up to congruence mod  $|G|$ , therefore  $x$  is usually restricted to  $0 \leq x < \text{ord}_{\mathbb{F}_q}(\alpha)$ .

## Notes

Example. For  $p = 13$  and  $n = 1$  the field of concern is  $\mathbb{Z}/13\mathbb{Z}$ . The multiplicative group  $U(\mathbb{Z}/13\mathbb{Z})$  has order 12 and as such has a subgroup of order 6 (Lagrange's theorem (3.147)).

From example 3.144, 2 has order 12 and is a generator of  $U(\mathbb{Z}/13\mathbb{Z})$ . Therefore 4 generates a subgroup of order 6, namely

$$G = \{4, 3, 12, 9, 10, 1\}.$$

Example of DLP in  $G$ : find  $x$  such that  $4^x \equiv 9 \pmod{13}$ .

Clearly 4 is a solution, but also 10, 16, 22... However, restricting  $x$  to the range  $0 - 6$  makes it unique.

## Notes

In the previous section Pollard's Rho algorithm was investigated as a way to solve the factorization problem. Since Factorization and Discrete Logarithm have much in common Pollard's Rho algorithm can be adjusted to this new context. We now present its details.

Let  $\alpha$  be a generator of a group  $G$  of prime order  $p$ . Any element of  $G$  can be written  $\alpha^a \beta^b$  for some  $a, b \in \mathbb{N}$  and  $\beta \in G$ .

Assuming two integers  $x$  and  $y$  such that  $x \equiv y \pmod{p}$  can be found, then there exist  $a_1, b_1$  such that  $x \pmod{p}$  can be written  $\alpha^{a_1} \beta^{b_1}$ , and  $a_2, b_2$  such that  $\alpha^{a_2} \beta^{b_2} \equiv y \pmod{p}$ .

Rewriting  $x \equiv y \pmod{p}$  as  $\alpha^{a_1} \beta^{b_1} \equiv \alpha^{a_2} \beta^{b_2} \pmod{p}$  yields

$$\beta^{b_1 - b_2} \equiv \alpha^{a_2 - a_1} \pmod{p}.$$

Taking the  $\log_\alpha$  on both sides leads to

$$(b_1 - b_2) \log_\alpha \beta = a_2 - a_1 \pmod{p}.$$

## Notes

As long as  $p \nmid (b_1 - b_2)$  we get

$$\log_\alpha \beta = \frac{a_2 - a_1}{b_1 - b_2}.$$

Therefore the goal of Pollard's Rho algorithm is to find  $x$  and  $y$  with  $x \equiv y \pmod{p}$ . This is achieved by considering three partitions  $S_1$ ,  $S_2$  and  $S_3$  of  $G$  of approximately the same size, based on an easily testable property, and defining three functions  $f$ ,  $g$  and  $h$ .

$$f(x) = \begin{cases} \beta x & x \in S_1 \\ x^2 & x \in S_2 \\ \alpha x & x \in S_3 \end{cases}$$

$$g(a, x) = \begin{cases} a & x \in S_1 \\ 2a \pmod{p} & x \in S_2 \\ a + 1 \pmod{p} & x \in S_3 \end{cases} \quad h(b, x) = \begin{cases} b + 1 \pmod{p} & x \in S_1 \\ 2b \pmod{p} & x \in S_2 \\ b & x \in S_3 \end{cases}$$

## Notes

Starting with two elements  $x = y = 1$ ,  $f$  is iteratively applied, once to  $x$  and twice to  $y$ . Since  $G$  is a cyclic group repeatedly applying  $f$  to  $x$  and  $y$  will result in a collision at some stage.

The function  $f$ ,  $g$  and  $h$  are defined such as the progress of  $x$  and  $y$  appears "random", while  $y$  goes twice as fast as  $x$ . Then by the birthday paradox (4.231) a collision can be expected in time  $\sqrt{p}$ , since  $p$  is the order of the group  $G$ .

**Remark.** The cyclic group  $G$  is taken as generic and no further assumption is made. This means that Pollard's Rho method applies to any group  $G$  of prime order  $p$ .

**Algorithm.** (*Pollard- $\rho$  – Discrete Logarithm*)

**Input :**  $\alpha$  a generator of  $G$ , a group of prime order  $p$  and  $\beta \in G$ ,  $f$ ,  $g$  and  $h$  three functions.

**Out-**  $\log_{\alpha} \beta$ , or failure.

**put :**

```

1  $a_1 \leftarrow 0; b_1 \leftarrow 0; x \leftarrow 1; a_2 \leftarrow 0; b_2 \leftarrow 0; y \leftarrow 1;$ 
2 repeat
3    $a_1 \leftarrow g(a_1, x); b_1 \leftarrow h(b_1, x);$ 
4    $x \leftarrow f(x);$ 
5    $a_2 \leftarrow g(a_2, y), f(y); b_2 \leftarrow h(b_2, y), f(y);$ 
6    $y \leftarrow f(f(y));$ 
7 until  $x \equiv y \pmod{p};$ 
8  $r \leftarrow b_1 - b_2;$ 
9 if  $r \neq 0$  then return  $r^{-1}(a_2 - a_1) \pmod{p};$ 
10 else return failed;
```

**Example.** Let  $\alpha = 2$  be a generator of  $G$ , the subgroup of order 191 of  $\mathbb{Z}_{383}^*$ . Let  $\beta = 228$ . Partition  $G$  into  $S_1 = \{x \in G | x \equiv 1 \pmod{3}\}$ ,  $S_2 = \{x \in G | x \equiv 0 \pmod{3}\}$  and  $S_3 = \{x \in G | x \equiv 2 \pmod{3}\}$ .

$x$	228	279	92	184	205	14	28
$a_1$	0	0	0	1	1	1	2
$b_1$	1	2	4	4	5	6	6
$y$	279	184	14	256	304	121	144
$a_2$	0	1	1	2	3	6	12
$b_2$	2	4	6	7	8	18	38
$x$	256	152	304	372	121	12	<b>144</b>
$a_1$	2	2	3	3	6	6	12
$b_1$	7	8	8	9	18	19	38
$y$	235	72	14	256	304	121	<b>144</b>
$a_2$	48	48	96	97	98	5	10
$b_2$	152	154	118	119	120	51	104

Then compute  $(38 - 104)^{-1}(10 - 12) \equiv 110 \pmod{191}$ . Hence in  $\mathbb{Z}_{383}^*$   
 $\log_2(228) = 110$ .

Although slightly more advanced Pollig-Hellman Algorithm is interesting in the sense that it takes advantage of the structure of the prime  $p$ . In fact it was noticed that if  $p - 1$ , the order of the multiplicative group of  $\mathbb{Z}_p$ , is featuring many small primes then the Discrete Logarithm Problem can be solved using the Chinese Remainder Theorem.

Let  $p - 1 = q_1^{e_1} q_2^{e_2} \dots q_r^{e_r}$ ,  $r \in \mathbb{N}$ . If  $x = \log_{\alpha} \beta$  then it suffices to determine  $x_i = x \pmod{q_i^{e_i}}$  for  $1 \leq i \leq r$  and then use the Chinese Remainder Theorem in order to recover  $x$ . Therefore it only remains to compute all the  $x_i$ . This can be efficiently achieved at the cost of some mathematical technicalities.

**Remark.** A common mathematical strategy consists in transposing a difficult problem over a given structure into an easier one over a similar structure. Following this idea one could think of solving a hard Discrete Logarithm Problem into an isomorphic group and then map it back to the original group.

In particular since the Discrete Logarithm Problem is easy to solve in the additive group  $\mathbb{Z}_n$ ,  $n \in \mathbb{N}$ , it is possible to map the multiplicative group of  $\mathbb{Z}_p$  into the additive group  $\mathbb{Z}_{p-1}$ . Solving the problem in this simpler group and mapping back the solution to  $\mathbb{Z}_p$  seems to be a very attractive solution.

The major problem with this approach is finding the map. In fact such a map would have to be built element by element, which would be time consuming. As a result this solution is not applicable in practice.

It is simple to see that the DLP is the inverse operation of the modular exponentiation, which can be very efficiently computed (3.172). However solving the DLP is not an easy task if the group is carefully chosen.

For instance as we will study in chapter 8, in groups having only a very basic algebraic structure the best algorithm available is the Pollard's Rho algorithm.

For more common groups over finite fields the best algorithms have a sub-exponential complexity similar to the one of the GNFS. Therefore in a cryptographic context, that is for the DLP to be intractable, the group is expected to have order larger than  $2^{3072}$ .

We now present several cryptographic protocols based on the hardness of solving the DLP.

Alice and Bob publicly agree on some parameters:



$G$  a group of order  $p$   
 $\alpha$  a generator of  $G$



Both Alice and Bob generate a random secret:



Choose a random  
 element  $x$  in  $G$

Choose a random  
 element  $y$  in  $G$



Alice and Bob send each other  $\alpha^{\text{secret}}$ :



•  $x$  in  $G$  and  $\alpha^x$   
 •  $\alpha^{yx}$

•  $y$  in  $G$  and  $\alpha^y$   
 •  $\alpha^{xy}$



Clearly solving the DLP implies breaking the Diffie-Hellman key exchange protocol. However in order to determine  $\alpha^{xy}$  it might not be necessary to solve the DLP, but only to solve the so called Computational Diffie-Hellman problem.

#### Problem (Diffie-Hellman problems)

Let  $G$  be a group of prime order  $p$  and  $\alpha$  be a generator of  $G$ .

- 1 **Computational Diffie-Hellman (CDH):** given  $\alpha^x$  and  $\alpha^y$ , for some unknown integers  $x$  and  $y$ , compute  $\alpha^{xy}$ .
- 2 **Decisional Diffie-Hellman (DDH):** given  $\alpha^x$  and  $\alpha^y$ , decide whether or not some  $c \in G$  is equal to  $\alpha^{xy}$ .

While solving the DLP implies solving the CDH problem, it is not known whether or not solving the CDH problem solves the DLP.

At present no method to solve CDH from DDH is known, and in fact in some groups DDH is efficiently solved while CDH remains hard.

## Initial setup:



- $G$  a group of prime order  $p$
- $\alpha$  a generator of  $G$
- $x$  a secret integer
- $G$  from Bob
- $\alpha$  from Bob
- $\beta \equiv \alpha^x \pmod p$  from Bob



## Encryption:

- A message  $m$
- $r \equiv \alpha^k \pmod p$  for some random integer  $k$
- Compute  $t \equiv \beta^k m \pmod p$
- Send  $c = \langle r, t \rangle$  to Bob



## Decryption:



- Receive  $c$  from Alice or Eve
- Compute  $tr^{-x} \equiv \beta^k m (\alpha^k)^{-x} \equiv (\alpha^x)^k m \alpha^{-xk} \equiv m \pmod p$

## Notes

## Proposition

Solving the CDH problem is equivalent to breaking Elgamal.

Proof. Assume we can decrypt any Elgamal ciphertext and we are given  $\alpha^a$  and  $\alpha^b$ . First set  $\beta$  to  $\alpha^a$ , i.e.  $a$  is the secret key, and  $r$  to  $\alpha^b$ . Then choosing a non zero value for  $t$  we get

$$m \equiv tr^{-a} \equiv t\alpha^{-ab}.$$

Hence  $tm^{-1} \equiv \alpha^{ab} \pmod p$  solves the CDH problem (3.216).

Conversely assume we can solve the CDH problem and are given the Elgamal ciphertext  $\langle r, t \rangle$ . Then we can determine  $\alpha^{xk} \pmod p$ , and since  $m$  is  $t\alpha^{-xk}$  we can recover the plaintext.  $\square$

## Notes

Given an Elgamal ciphertext  $c = \langle r, t \rangle$ , the goal is to recover the plaintext corresponding to  $c$  by constructing another ciphertext  $c' = \langle r', t' \rangle$  and getting it decrypted by a "decryption oracle".

Constructing a chosen ciphertext  $c''$ :

- By definition  $c = \langle r, t \rangle = \langle \alpha^k, \beta^k m \rangle$
- For a message  $m'$ , compute  $c'' = \langle r\alpha^{k'}, t\beta^{k'} m' \rangle$
- Submitting  $c''$  to the decryption oracle,  $m''$  is returned

Recovering  $m$  from  $m''$ :

- In the group  $G$ , observe that  $c''$ :
  - $r\alpha^{k''} = \alpha^{k+k'} = \alpha^{k''}$
  - $t\beta^{k''} m' = \beta^k m \beta^{k'} m' = mm'\beta^{k+k'}$
- Then  $c''$  is the ciphertext corresponding to  $m'' = mm'$
- Finally compute  $m = m''m'^{-1}$

## Notes

- What is the order of a group, of an element?
- How to efficiently perform primality testing?
- Which version of RSA is secure? Describe it
- When to use Diffie-Hellman key exchange protocol?
- Describe Elgamal

## Notes

## 4. Hash functions

### Notes

---

---

---

---


---

---

---

---

### Chapter organisation



### Notes

---

---

---

---

---

---

---

---

### Data integrity

Components of modern cryptography:

- Confidentiality
- Authentication
- Data integrity
- Non-repudiation

Common setup for data integrity:

- Insecure environment
- Unencrypted data
- Data must not be altered

Example.

- Files in an OS
- Software to be downloaded or installed from internet

### Notes

---

---

---

---

---

---

---

---

### Fingerprint

Simple high-level idea:

- Construct a short fingerprint of the data
- Store the fingerprint in a secure place
- Recompute and compare the fingerprint on a regular basis
  - Fingerprint is changed: data was altered
  - Fingerprint is unchanged: data was not altered

Construction goals:

- The fingerprint must be a few hundreds of bits long
- A tiny change in that data radically impacts the fingerprint
- It is impossible to alter the data without totally changing the fingerprint

### Notes

---

---

---

---

---

---

---

---




## Definition (Hash function)

A *hash function* is a function  $h$  that verifies the following properties:

- i Efficiently computed for any input.
- ii *Pre-image resistant*: given  $y$  it is computationally infeasible to find  $x$  such that  $h(x) = y$ .
- iii *Second pre-image resistant*: given  $x$ , it is computationally infeasible to find  $x' \neq x$  with  $h(x) = h(x')$ .
- iv *Collision resistant*: it is computationally infeasible to find  $x$  and  $x'$  with  $x' \neq x$  and  $h(x) = h(x')$ .

The output of a hash function is called *message digest* or *digest*.

## Notes



By definition a hash function is a one-way function since the definition of pre-image resistant is the same as the one of a one-way function.

The collision resistance is the most general of the three resistance properties. Roughly speaking collision resistance implies second pre-image resistance, which implies pre-image resistance.

## Notes

**Remark.** A hash function takes inputs of any size and output values of fixed sizes, independently of the input.

Applications requiring the resistance properties:

- Pre-image resistant: password
- Second pre-image resistant: virus
- Collision resistance: signature

## Notes

We present a first example of a hash function due to Chaum, van Heijst and Pfitzmann. Although it satisfies conditions (ii), (iii), and (iv) of a hash function, it is too slow to be used in practice.

Let  $p$  be a prime such that  $q = \frac{p-1}{2}$  is also a prime and choose  $\alpha$  and  $\beta$  two generators of  $U(\mathbb{Z}/p\mathbb{Z})$ . We write any  $x$  in  $\mathbb{Z}/q^2\mathbb{Z}$  as  $x_0 + x_1q$  with  $0 \leq x_0, x_1 \leq q-1$ , and define  $h$  from  $\mathbb{Z}/q^2\mathbb{Z}$  into  $U(\mathbb{Z}/p\mathbb{Z})$  by

$$h(x) = \alpha^{x_0} \beta^{x_1} \bmod p.$$

We will now show that  $h$  is collision resistant, by proving that finding a collision means solving the DLP. To prove this result we will need to recall a result on the number of solutions of a modular equation.

## Notes

**Proposition**

If two values  $x \neq x'$  with  $h(x) = h(x')$  are known then the discrete logarithm of  $\beta$  in base  $\alpha$  can be efficiently computed.

In order to prove this result we recall the following lemma.

**Lemma**

Let  $a, b \in \mathbb{Z}$  and  $m \in \mathbb{N} \setminus \{0\}$  and  $d = \gcd(a, m)$ . The linear congruence  $ax \equiv b \pmod{m}$  has a solution if and only if  $d \mid b$ . In that case, it has  $d$  solutions that are mutually incongruent mod  $m$ .

## Notes

**Proof.** Suppose  $h(x) = h(x')$ , with  $x = x_0 + x_1 q$  and  $x' = x'_0 + x'_1 q$ . Since  $\alpha$  is a generator of  $U(\mathbb{Z}/p\mathbb{Z})$ ,  $\beta = \alpha^a$  for some integer  $a$  and

$$\alpha^{x_0 + ax_1} \equiv \alpha^{x'_0 + ax'_1} \pmod{p}.$$

From corollary 3.152,  $a(x_1 - x'_1) \equiv x'_0 - x_0 \pmod{p-1}$ . To solve this equation for  $a$  we see that if  $x_1 = x'_1$  then  $x_0 = x'_0$  and  $x = x'_1$ .

Therefore we assume  $x_1 \neq x'_1$ , and find  $d = \gcd(x_1 - x'_1, p-1)$  incongruent solutions (lemma 4.229). But as  $q = \frac{p-1}{2}$  is prime, the only factors of  $p-1$  are 1, 2,  $q$ , and  $p-1$ . Also note that  $0 \leq x_1, x'_1 \leq q-1$  implies  $-(q-1) \leq x_1 - x'_1 \leq q-1$ . And since  $x_1 - x'_1 \not\equiv 0 \pmod{p-1}$  it means that  $d$  is either 1 or 2.

Thus it suffices to test the two solutions to determine  $a$ . Hence finding  $x \neq x'$  with  $h(x) = h(x')$  implies solving the DLP.  $\square$

## Notes

As we have already mentioned the birthdays paradox on several occasions (2.109, 3.209) we now present some more details on this "birthday attack".

The essence of the birthday paradox can be expressed by considering the birthdays of 23 persons. We first assume the birthdays to be independent and equiprobable. If those 23 people all have a different birthday, it means that the second person has 364/365 chance of not sharing a birthday with the first one. Then for the third one the probability is 363/365 and so on until the twenty-third whose probability is 343/365. Therefore the probability of at least two sharing the same birthday is

$$1 - \prod_{i=1}^{22} \frac{365-i}{365} = 0.507 > \frac{1}{2}.$$

## Notes

Suppose we now have a large number of objects  $n$ , that are randomly chosen with replacement by two groups of  $r$  persons each. The probability of someone in the first group choosing the same object as someone in the second group can be approximated by  $1 - e^{-r^2/n}$ .<sup>1</sup> And the probability of  $i$  matches is  $\binom{r^2}{i} \frac{e^{-r^2/n}}{i!}$ .

As the probability of a match (i.e. two persons choosing the same object) is expected to be larger than 1/2 we set  $r^2/n$  to be  $\ln 2$ . This yields  $r \approx 1.117\sqrt{n}$ . Since for  $a \ll n$ ,  $a\sqrt{n}$  is of the same order of magnitude as  $\sqrt{n}$ , it means that a match will be found in average after  $\mathcal{O}(\sqrt{n})$  persons have chosen an object.

We now investigate how to transform this observation into an effective cryptographic attack.

<sup>1</sup>This approximation will be derived in the homework.

## Notes

233

## The birthday attack

Let  $h$  be a hash function which digest are of length  $n$ . The first obvious strategy is to compute  $h(x)$  for about  $\mathcal{O}(\sqrt{n})$  random  $x$  and hope for a collision, as the probability is larger than a half.

Example. Let  $h$  be a hash function whose output is 128 bits long. Then the above attack leads to a collision in  $\mathcal{O}(2^{64})$  steps.

An important drawback in this attack is the amount of storage required, since all the values must be stored in order to be tested for collisions.

Example. What is the hardest: perform  $2^{64}$  operations or store  $2^{64}$  bytes?

## Notes

234

## An improved birthday attack

Following the Pollard's rho idea (3.209) it is possible to decrease the amount of storage necessary by computing and comparing two hash sequences.

Select a random initial  $x_0$  and then compute  $x_i = h(x_{i-1})$  and  $x_{2i} = h(h(x_{2i-1}))$ . At each step compare  $x_i$  and  $x_{2i}$ : a collision on  $x_{i-1}$  and  $h(x_{2(i-1)})$  is found as soon as  $x_i = x_{2i}$ .

Note that we implicitly assumed  $h$  to act as a random oracle (2.103) such that the probability of having  $x_{i-1}$  equal to  $h(x_{2(i-1)})$  is very low. In such case no information would be gained.

So far we focused on how to find collisions from a theoretical point of view, that is without considering whether or not the generated hash originates from a meaningful message.

## Notes

235

## A real life birthday attack



Alice is happy: she has received a nice contract for a new job in Eve's company.



## Contract

Alice will work 16 hours a week for a base salary of 50,000 RMB a month. Alice can take as much paid holidays as she wants.

## Contract

Alice will work 16 hours a day for a base salary of 500 RMB a month; Alice can take as little paid holidays as Eve wants.

Eve constructed the two contracts such that they have the same hash. Alice signed one but Eve can pretend it was the other one.

## Notes

236

## A real life birthday attack


Why is it working?

- Eve generated many good and bad contracts
- She altered each base contract by
  - Changing the punctuation
  - Expressing the same idea using different synonyms
  - Adding extra spaces
- She computed their hash and found a collision

Example. How many ways are there to read this short paragraph?

I {hate|despise|detest} this {terrible|awful|horrible|disastrous} course. It is so {hard|complex|difficult|complicated} and the explanations are always {unclear|confused|doubtful}.

## Notes



Notes

238

Designing hash functions

The goal is to design collision resistant hash functions

Difficulty:

- Number of possible input: infinite
- Number of possible output: finite

Conclusion: any hash function has an infinite number of collisions

Merkle-Damgård construction: methodology to convert a hash function on strings of fixed length into a hash function accepting arbitrary input lengths

We will prove that if the original hash function is collision resistant then so is the constructed one.

Notes

239

Iterated hash functions

Definitions

- A function  $g$  defined by
 
$$g : \{0,1\}^{m+t} \longrightarrow \{0,1\}^m, \quad t \geq 1,$$
 is called a *compression function*.
- A hash function constructed by iteratively applying a compression function is called an *iterated hash function*.

Let  $x$  be a bitstring,  $|x|$  stands for the length of  $x$  and for any bitstring  $y$  the concatenation of  $x$  and  $y$  is denoted  $x||y$ . In particular for a bit  $x$ ,  $\underbrace{x||x||\dots||x}_{k \text{ times}}$  is denoted  $x^k$ .

Let  $a$  be an integer, then  $(a)_2$  designates its binary representation.

Notes

240

Merkle-Damgård construction

Let  $g : \{0,1\}^{m+t} \rightarrow \{0,1\}^m$ ,  $t \geq 2$ , be a compression function and  $x$  be a bitstring of length  $n > 0$ .

- Split  $x$  into  $k = \lceil \frac{n}{t-1} \rceil$  blocks
- For  $i = 1$  to  $k$  set  $y_i$  to  $x_i$
- Set  $y_k$  to  $x_k || 0^d$
- Set  $y_{k+1}$  to  $(d)_2$
- Compute  $z_1 = g(0^{m+1} || y_1)$
- For  $i = 1$  to  $k$  compute  $z_{i+1} = g(z_i || 1 || y_{i+1})$
- Define  $h(x)$  as  $z_{k+1}$

Notes

**Theorem (Merkle-Damgård)**

Let  $g$  be a collision resistant compression function defined from  $\{0, 1\}^{m+t}$  into  $\{0, 1\}^m$ , with  $t \geq 2$ . Then the Merkle-Damgård construction is a collision resistant hash function.

Remark. Before proving this theorem we first note that the map  $x \mapsto y$  must be injective. In fact if it is not injective then it is possible to find  $x \neq x'$  such that  $y = y'$ . As a result we have  $h(x) = h(x')$ , that is  $h$  is not collision resistant.

## Notes

Proof. Assuming we have a collision on  $h$ , i.e.  $x \neq x'$  and  $h(x) = h(x')$ , we will prove that a collision on the compression function  $g$  can be efficiently found.

First note that if  $|x| \neq |x'|$ , then they are padded with two different values  $d$  and  $d'$ , respectively. Similarly  $k+1$  and  $k'+1$  denote the number of blocks for  $x$  and  $x'$ .

Case 1: consider  $x \neq x'$  with  $|x| \not\equiv |x'| \pmod{t-1}$ . Then  $d \neq d'$  and  $y_{k+1} \neq y'_{k'+1}$ . We then have

$$\begin{aligned} g(z_k \| 1 \| y_{k+1}) &= z_{k+1} = h(x) \\ &= h(x') = z'_{k'+1} \\ &= g(z'_k \| 1 \| y'_{k'+1}) \end{aligned}$$

which is a collision on  $g$  since  $y_{k+1} \neq y'_{k'+1}$ .

## Notes

Proof (continued). Case 2a: consider  $|x| \equiv |x'| \pmod{t-1}$  with  $k = k'$ .

This implies  $y_{k+1} = y'_{k'+1}$ , and we have

$$\begin{aligned} g(z_k \| 1 \| y_{k+1}) &= z_{k+1} = h(x) \\ &= h(x') = z'_{k+1} \\ &= g(z'_k \| 1 \| y'_{k+1}). \end{aligned}$$

If  $z_k \neq z'_k$  then a collision is found. Otherwise we repeat the process and get

$$\begin{aligned} g(z_{k-1} \| 1 \| y_k) &= z_k \\ &= z'_k = g(z'_{k-1} \| 1 \| y'_k). \end{aligned}$$

Then either we have found a collision or we continue backward until one is obtained. If none is found then we get

$$z_1 = z'_1, \dots, z_{k+1} = z'_{k+1}.$$

## Notes

Proof (continued). Case 2b: consider  $|x| \equiv |x'| \pmod{t-1}$  with  $k \neq k'$ . Without loss of generality assume  $k' > k$  and proceed as in case 2a. If no collision is found before  $k = 1$  then we have

$$\begin{aligned} g(0^{m+1} \| y_1) &= z_1 \\ &= z'_{k'-k+1} \\ &= g(z'_{k'-k} \| 1 \| y'_{k'-k+1}). \end{aligned}$$

By construction the  $m+1$ st bit on the left is 0 while on the right it is 1. Hence we have found a collision.

All the cases being covered this completes the proof.  $\square$

## Notes


Remark. We have proven the Merkle-Damgård theorem in the case  $t \geq 2$ . In fact this is true for any  $t \geq 1$  but the case  $t = 1$  requires a different approach as  $|x| \bmod (t - 1)$  cannot be considered<sup>2</sup>.

Merkle-Damgård construction served as a basis for the design of various hash functions. Two common examples are MD5 and SHA-1.

MD5 hash function:

- Designed in 1991
- First flaw discovered in 1996
- Collisions found in 2004
- Practical collisions demonstrated in 2005
- Flame malware used collisions on Windows certificates to infect computers... in 2012!

<sup>2</sup>This case will be proven in the homework.



Secure Hash Algorithm (SHA):

- 1993: SHA-0, 160 bits hash function, never widely adopted
- 1995: SHA-1, similar to SHA-0, with several weaknesses fixed
- 2001: SHA-2, significantly different from SHA-1
- 2005: first attacks against SHA-1
- 2008: SHA-0 totally broken ( $< 1$  hour to find collisions)
- 2012: best theoretical attack on SHA-1 in  $2^{61}$  operations
- 2012: Keccak hash function is selected to become SHA-3
- 2017: major companies have stopped accepting SHA-1 certificates

Given  $x$  of length  $|x|$ :

- 1 Append 1 to the message
- 2 Append 0s until the length is  $-64 \bmod 512$
- 3 Append  $|x|$  written in base 2 over 64 bits

Let  $y$  be the padded value of  $x$ . By construction  $|y| \equiv 0 \bmod 512$ . Break  $y$  into

$$k = \left\lfloor \frac{|x|}{512} \right\rfloor + 1$$

blocks of 512 bits each.

Example. Assume  $|x| = 2800$  bits. Since  $2800 \equiv 240 \bmod 512$  append a 1 followed by 207 0s, and the bit representation of 2800 over 64 bits. Thus  $y$  is composed of  $k = 6$ , 512-bit blocks.

As SHA-1 follows the Merkle-Damgård construction it is simply described as an algorithm, while most of the work is performed by the compression function.

#### Algorithm. (SHA-1)

**Input** :  $x$  a bit string

**Output** :  $h(x)$ , where  $h$  is SHA-1

**put** :

```

1  $H_0 \leftarrow 67452301; H_1 \leftarrow \text{EFCDA889}; H_2 \leftarrow 98\text{BADCFE};$ 
2  $H_3 \leftarrow 10325476; H_4 \leftarrow \text{C3D2E1F0};$ 
3  $d \leftarrow (447 - |x|) \bmod 512;$ 
4  $y \leftarrow x || 1 || 0^d || (|x|)_2;$  /*  $|x|$  expressed over 64 bits */
5 for  $i \leftarrow 1$  to  $k$  do
6    $H_0, H_1, H_2, H_3, H_4 \leftarrow \text{compress}(H_0, H_1, H_2, H_3, H_4, y_i)$ 
7 end for
8 return  $H_0 || H_1 || H_2 || H_3 || H_4$ 
```

The compression function onto which SHA-1 relies uses:

- The functions  $f_0, \dots, f_{79}$  defined by

$$f_i(B, C, D) = \begin{cases} (B \wedge C) \vee (\neg B \wedge D) & \text{if } 0 \leq i \leq 19 \\ B \oplus C \oplus D & \text{if } 20 \leq i \leq 39 \\ (B \wedge C) \vee (B \wedge D) \vee (C \wedge D) & \text{if } 40 \leq i \leq 59 \\ B \oplus C \oplus D & \text{if } 60 \leq i \leq 79 \end{cases}$$

- The constants  $K_0, \dots, K_{79}$  defined by

$$K_i = \begin{cases} 5A827999 & \text{if } 0 \leq i \leq 19 \\ 6ED9EBA1 & \text{if } 20 \leq i \leq 39 \\ 8F1BBCDC & \text{if } 40 \leq i \leq 59 \\ CA62C1D6 & \text{if } 60 \leq i \leq 79 \end{cases}$$

#### Algorithm. (SHA-1 compression function)

**Input** : Five 32-bit values  $H_0, H_1, H_2, H_3, H_4$  and a 512-bit block  $y$

**Output** : Five 32-bit values  $H_0, H_1, H_2, H_3, H_4$

```

1 Function  $\text{compress}(H_0, H_1, H_2, H_3, H_4, y)$ :
2   split  $y$  into 16 words  $W_0, \dots, W_{15}$ ;
3   for  $i \leftarrow 16$  to  $79$  do
4      $W_i \leftarrow \text{ROTL}(W_{i-3} \oplus W_{i-8} \oplus W_{i-14} \oplus W_{i-16})$ 
5   end for
6    $A \leftarrow H_0; B \leftarrow H_1; C \leftarrow H_2; D \leftarrow H_3; E \leftarrow H_4;$ 
7   for  $i \leftarrow 0$  to  $79$  do
8      $T \leftarrow \text{ROTL}^5(A) + f_i(B, C, D) + E + W_i + K_i;$ 
9      $E \leftarrow D; D \leftarrow C;$ 
10     $C \leftarrow \text{ROTL}^{30}(B);$ 
11     $B \leftarrow A; A \leftarrow T;$ 
12  end for
13   $H_0 \leftarrow H_0 + A; H_1 \leftarrow H_1 + B; H_2 \leftarrow H_2 + C; H_3 \leftarrow H_3 + D; H_4 \leftarrow H_4 + E;$ 
14  return  $H_0, H_1, H_2, H_3, H_4$ 
15 end
```

#### Remark.

- Compared to SHA-0, SHA-1 only adds *ROTL* in the construction of  $W_{16}$  to  $W_{79}$
- All the constant in SHA-1 are constructed such as to be above any suspicion
- Weaknesses on SHA-1 lead to the SHA-3 competition
- SHA-2 is a family of six hash functions
- SHA-2 digests can have values 224, 256, 384 and 512
- To date there is no known security issue on any of the SHA-2 hash functions

253

Key points

- What is a hash function?
- Why are hash function important in cryptography?
- Explain the birthday paradox
- Describe the Merkle-Damgård construction
- What secure hash function should be used in 2021?

Notes

254

5. Digital signatures

Notes

255

Chapter organisation

Notes

256

Real life signatures

Middle age:

- Document sealed with a wax imprint of an insignia
- Nobody can reproduce the insignia

Modern time:

- Sign credit card slip
- Compare to the signature at the back of the credit card

Reusing a signature:

- Photocopy
- Cut and paste
- Highly noticeable

Notes



257
Toward digital signatures

Signing an electronic document:

- Digitalize the signature
- Paste it on the electronic document

Reusing a signature:

- Copy and paste on any document
- Anybody can do it
- Signature is not specific to an individual

Basic idea for a solution:

- Prevent the signature from being separated from its message
- Signature must be easily verified

Notes

258
Digital signatures

Setup for signatures:

- Message to encrypt is not necessarily secret
- A message might be encrypted after being signed

The signature must be:

- Tied to the signer and to the message being signed
- Easy to verify by anybody
- Hard to forge

*Similar to public key cryptography*

Notes

259
Attacks on signatures

Similar to attacks on encryption schemes (1.30) we define attacks on signature schemes:

- Key-only attack: Eve has only access to the public key
- Known message attack: Eve has a list of previously signed messages
- Chosen message attack: Eve chooses the messages to be signed
- Selective forgery: Eve is given a message and is able to sign it without being given the private key
- Existential forgery: Eve can find a pair  $\langle \text{message}, \text{signature} \rangle$  without being given the private key

Notes

260
Signatures and hash functions

Drawback:

- Public key cryptography primitives are used
- Signing a whole message  $m$  is then slow

Solution: sign the hash of  $m$  using a public hash function

Benefits:

- Faster to generate
- Smaller to store or send
- Conveys the same knowledge as  $m$  itself

Given a hash function  $h$ , denote the signature of the hash of a message  $m$  by  $\text{sig}(h(m))$

Notes

261

Signatures and hash functions

Existential forgery:

- Using known message attack:
  - Get a pair  $\langle m, \text{sig}(h(m)) \rangle$
  - Compute  $h(m)$  and attempt to find  $m'$  such that  $h(m) = h(m')$
  - Considered impossible if  $h$  is second pre-image resistant
- Using chosen message attack:
  - Find two message  $m$  and  $m'$  such that  $h(m) = h(m')$
  - Persuade the signer to sign  $m$
  - Attach  $\text{sig}(h(m)) = \text{sig}(h(m'))$  to  $m'$
  - Considered impossible if  $h$  is collision resistant
- Using key-only attack:
  - Take a signature scheme, without hash function, which is vulnerable to existential forgery using key-only attack
  - Compute a signature on  $h(m)$  for some unknown  $m$
  - Determine such an  $m$
  - Considered impossible if  $h$  is pre-image resistant

Notes

---

---

---

---

---

---

---

---

---

---

262

Signatures and the birthday attack

In the previous chapter we investigated the birthday paradox and illustrated how Eve could use this attack to cheat Alice when signing a contract (4.235).

Such an attack can be conducted as soon as the hash is used in place of the whole document. Therefore Alice should be careful and not sign the document. She should rather slightly alter it, for instance by adding a comma or space.

The document being different from the original its hash will be a totally different value. Hence, Eve cannot append Alice signature to the fraudulent contract.

Eve is then defeated and Alice can enjoy a nice contract.

Notes

---

---

---

---

---

---

---

---

---

---

263

Chapter organisation

Notes

---

---

---

---

---

---

---

---

---

---

264

RSA signatures

Initial setup:

- $p, q$  two primes
- $n = pq$  and  $\varphi(n)$
- $e, d$  such that  $ed \equiv 1 \pmod{\varphi(n)}$

- The  $n$  from Bob
- The  $e$  from Bob

Signature:

- Compute  $s \equiv m^d \pmod{n}$
- Share  $m$  and  $s$

Verification:

- The message  $m$  from Bob
- Compute  $m' \equiv s^e \pmod{n}$
- Compare  $m'$  to  $m$

Notes

---

---

---

---

---

---

---

---

---

---

## Reusing a signature:

- Given a signature  $s$  with its message  $m$
- Impossible to sign  $m'$  using  $s$  since  $s^e \not\equiv m' \pmod{n}$

## Generating a signature:

- Given a message  $m$  find  $s$  such that  $s^e \equiv m \pmod{n}$
- This is exactly solving the RSA problem (3.185)

## Generating a message:

- Given a signature  $s$  generate a message  $m \equiv s^e \pmod{n}$
- It is very unlikely that  $m$  is meaningful

## Initial setup:



- $G$  a group of prime order  $p$
- $\alpha$  a generator of  $G$
- $x$  a secret integer
- $G$  from Bob
- $\alpha$  from Bob
- $\beta \equiv \alpha^x \pmod{p}$  from Bob



## Signature:



- Select a random  $k$ , with  $\gcd(k, p-1) = 1$
- Compute  $r \equiv \alpha^k \pmod{p}$
- Compute  $s \equiv k^{-1}(m - xr) \pmod{p-1}$

## Verification:

- The triple  $\langle m, r, s \rangle$
- Compute  $v = \beta^r r^s \equiv \alpha^{xr} \alpha^{k-k^{-1}(m-xr)} \equiv \alpha^m \pmod{p}$
- The signature is valid only if  $v \equiv \alpha^m \pmod{p}$



Example. Set  $p = 467$ ,  $\alpha = 2$  and  $x = 127$ . Then  $\beta = 2^{127} \equiv 132 \pmod{467}$ . The variable  $x$  is kept secret, all the others are publicly known.

Signing the message  $m = 100$ :

- Randomly choose  $k = 213$  and keep it since  $\gcd(213, 466) = 1$
- Compute  $r = 2^{213} \equiv 29 \pmod{467}$
- As  $k^{-1} \equiv 431 \pmod{466}$ ,  $s = 431 \cdot (100 - 127 \cdot 29) \equiv 51 \pmod{466}$

To verify the signature  $\langle 100, 29, 51 \rangle$ , anyone can compute both:

- $132^{29} \cdot 29^{51} \equiv 189 \pmod{467}$
- $2^{100} \equiv 189 \pmod{467}$

First we notice that if  $x$  is discovered by an attacker, he can signed any document.

Then we observe that given only a message  $m$  he can try to:

- Find  $s$  such that

$$\beta^r r^s \equiv \alpha^m \pmod{p}. \quad (5.1)$$

This can be rewritten  $r^s \equiv \beta^{-r} \alpha^m \pmod{p}$ , and finding  $s$  means solving the DLP.

- Set  $s$  and solve eq. (5.1) for  $r$ . No feasible solution is known.
- Find  $r$  and  $s$  simultaneously. It is not known how to do it, but there is no prove that it is impossible to do.

Note that  $k$  must remain secret otherwise it is simple to recover  $x$ . Indeed if  $\gcd(r, p-1) = 1$ , then  $x \equiv (m - ks)r^{-1} \pmod{p-1}$ .

*Generating a message and its signature only knowing the public key*

Let  $i$  and  $j$  be two integers such that  $0 \leq i, j \leq p-2$ . Define  $r$  as  $\alpha^i \beta^j \bmod p$ . Then  $\alpha^m$  can be expressed as

$$\alpha^m \equiv \beta^r (\alpha^i \beta^j)^s \bmod p.$$

Rearranging the different terms yields  $\alpha^{m-is} \equiv \beta^{r+js} \bmod p$ . This congruence is clearly true if both  $m-is$  and  $r+js$  are  $0 \bmod (p-1)$ .

Assuming  $\gcd(j, p-1) = 1$ , we can determine  $m$  and  $s$  from the two previous equations. Therefore, by construction the signature

$$\langle m, r, s \rangle = \langle -rij^{-1} \bmod (p-1), \alpha^i \beta^j \bmod p, -rj^{-1} \bmod (p-1) \rangle$$

is a valid signature. Note that  $m$  is very unlikely to be meaningful.

## Notes

Example. Set  $p = 467$ ,  $\alpha = 2$  and  $\beta = 132$ . Select  $i = 99$  and  $j = 179$ , and then  $j^{-1} \equiv 151 \bmod 466$ .

The signature is defined by  $\langle m, r, s \rangle$  with

$$\begin{cases} r \equiv 2^{99} \cdot 132^{179} \equiv 117 \bmod 467 \\ s \equiv -117 \cdot 151 \equiv 41 \bmod 466 \\ m \equiv 99 \cdot 41 \equiv 331 \bmod 466 \end{cases}$$

The verification is given by

$$132^{117} \cdot 117^{41} \equiv 303 \equiv 2^{331} \bmod 467$$

## Notes

Given a valid signature  $\langle m, r, s \rangle$  an attacker can construct and sign various other messages.

Generate  $h, i$ , and  $j$  such that  $\gcd(hr - js, p-1) = 1$ . Then the triple  $\langle m', r', s' \rangle$  defines a valid signature if

$$\begin{cases} r' \equiv r^h \alpha^i \beta^j \bmod p \\ s' \equiv sr'(hr - js)^{-1} \bmod (p-1) \\ m' \equiv r'(hm + is)(hr - js)^{-1} \bmod (p-1) \end{cases}$$

Again this method leads to an existential forgery but cannot be modified into selective forgery. As such those two attacks represent no real threat for Elgamal signatures.

## Notes

Let  $\langle m_1, r_1, s_1 \rangle$  and  $\langle m_2, r_2, s_2 \rangle$  be the two signatures. If they are generated using a common  $k$ , then  $r_1 = r_2 = r = \alpha^k \bmod p$  and

$$\begin{cases} \beta^{r_1} r_1^{s_1} \equiv \alpha^{m_1} \bmod p \\ \beta^{r_2} r_2^{s_2} \equiv \alpha^{m_2} \bmod p. \end{cases}$$

Thus  $\alpha^{m_1-m_2} \equiv \alpha^{k(s_1-s_2)} \bmod p$ , and from corollary 3.152 we get

$$m_1 - m_2 \equiv k(s_1 - s_2) \bmod (p-1).$$

Since this congruence has  $d = \gcd(s_1 - s_2, p-1)$  solutions (lemma 4.229) it is simple to test all of them and recover  $k$ . Once  $k$  is known  $x$  can be recovered as noticed on slide 5.268, and signatures can be forged at will.

## Notes

## Digital Signature Algorithm (DSA):

- Proposed in 1991 by the NSA
- Adopted as a standard in 1994
- Variant of Elgamal signature scheme
- As in Elgamal the hash of the message is signed
- SHA-1 is the historical choice but SHA-2 (SHA-3) is now recommended
- For a given security level DSA defines two lengths  $l_1$  and  $l_2$  for the DLP and the hash to feature a balanced security

## Notes

## Initial setup:



- A prime  $q$ ,  $|q| = l_2$
- A prime  $p$ ,  $|p| = l_1$  and  $q \mid (p-1)$
- $g$  a generator of  $G = U(\mathbb{F}_p)$
- $\alpha \equiv g^{(p-1)/q} \bmod p$
- $x$  a secret integer
- $p$  from Bob
- $q$  from Bob
- $\alpha$  from Bob
- $\beta \equiv \alpha^x \bmod p$  from Bob



## Signature:



- Select a random  $k$ ,  $0 < k < q$
- Compute  $r \equiv (\alpha^k \bmod p) \bmod q$
- Compute  $s \equiv k^{-1}(m + xr) \bmod q$

## Verification:

- The triple  $(m, r, s)$
- Compute  $v = (\alpha^{s^{-1}m \bmod q} \beta^{s^{-1}r \bmod q} \bmod p) \bmod q$
- The signature is valid only if  $v = r$



## Notes

## Observe how the verification works:

By definition of  $s$  we know that  $m \equiv (-xr + ks) \bmod q$ . This implies  $s^{-1}m \equiv (-xrs^{-1} + k) \bmod q$ . Therefore we can write

$$k \equiv s^{-1}m + xrs^{-1} \bmod q.$$

And we finally get


$$\begin{aligned} r &\equiv \alpha^k \bmod p \\ &\equiv \alpha^{s^{-1}m + xrs^{-1} \bmod q} \bmod p \\ &\equiv \alpha^{s^{-1}m \bmod q} \beta^{s^{-1}r \bmod q} \bmod p \\ &= v. \end{aligned}$$

## Notes

## Why is DSA different from Elgamal?

- $r$  only "carries part of the information" on  $k$   
e.g. if  $l_1 = 3072$  and  $l_2 = 256$ , then about  $2^{2816}$  values mod  $p$  reduce to a same integer mod  $q$
- From the initial setup (slide 5.274),  $\alpha^q \equiv 1 \bmod p$ . Pohlig-Hellman attack (3.212) does not apply, since  $q$  is prime. Not even a little piece of information can be recovered.
- Verification step requires only two modular exponentiations vs. three in Elgamal case

## Notes



Notes

---

---

---

---

---

---

---

---

278 Blind signatures

Basic idea: sign a document without knowing its content

Typical setup: Bob made a new discovery and wants to record it publicly without unveiling it

Strategy: Bob gets his discovery signed by some known authority but without revealing or showing it the content

Danger: what is signed?

Notes

---

---

---

---

---

---

---

---

279 RSA blind signatures

Initial setup:

- $p, q$  two primes
- $n = pq$  and  $\varphi(n)$
- $e, d$  such that  $ed \equiv 1 \pmod{\varphi(n)}$
- $n, e$  from Alice
- A random integer  $k$ ,  $\gcd(k, n) = 1$
- For a message  $m$  compute  $t \equiv k^e m$

Blind signature:

- $t$  from Bob
- Compute  $s \equiv t^d \pmod{n}$
- Send  $s$  to Bob

Message signature:

- Bob computes  $\frac{s}{k} \equiv \frac{t^d}{k} \equiv \frac{k^{ed} m^d}{k} \equiv m^d \pmod{n}$
- Bob later shares  $n, k$  and  $e$

Notes

---

---

---

---

---

---

---

---

280 RSA blind signatures

Remark.

- $k$  being random  $k^e \pmod{n}$  is also random and so is  $k^e m \pmod{n}$
- Alice cannot get any information on what she is signing
- The final value is the same as if Bob had gotten his message signed following the standard procedure
- Verification happens as in "regular RSA signatures"
- There is no need to keep  $d, p$  and  $q$

Notes

---

---

---

---

---

---

---

---

Primary goal: design a signature that cannot be verified without the co-operation of the signer

Secondary goals:

- Prevent the signer to disavow a previous signature
- Allow the signer to prove that a forged signature is a forgery

Applications: prevent the illegal distribution of documents without the approval of the author

Structure: composed of three algorithm: signature, verification, and disavowal

Initial setup:



- $p$  and  $q$  two primes  $p = 2q + 1$
- $G$  a subgroup of  $\mathbb{F}_p^*$  of order  $q$
- $\alpha$  a generator of  $G$
- $x$  a secret integer

- $G$  from Bob
- $\alpha$  from Bob
- $\beta \equiv \alpha^x \pmod{p}$  from Bob



Signature:



- A message  $m$  in  $G$
- Compute  $s \equiv m^x \pmod{p}$

Verification:



- 3 Compute  $t \equiv r^{x^{-1} \pmod{q}} \pmod{p}$
- 4 Share  $t$  with Alice

- 1 Choose random  $e_1, e_2 \in \mathbb{F}_q^*$
- 2  $r \equiv s^{e_1} \beta^{e_2} \pmod{p}$
- 5 Valid if and only if  $t \equiv m^{e_1} \alpha^{e_2} \pmod{p}$



Remark. On a valid signature we have:

$$t \equiv r^{x^{-1} \pmod{q}} \pmod{p}$$

$$\equiv s^{e_1 x^{-1}} \beta^{e_2 x^{-1}} \pmod{p}$$

Noting that  $s \equiv m^x \pmod{p}$ , and  $\beta \equiv \alpha^x \pmod{p}$ , we get

$$t \equiv m^{e_1} \alpha^{e_2} \pmod{p}$$

Example. Let  $p = 467$ , then 2 is a primitive element of  $\mathbb{F}_p^*$  and 4 is a generator of the group  $G$  of order 233. Taking  $x = 101$ ,  $\beta \equiv 4^{101} \equiv 449 \pmod{467}$ .

Signing the message  $m = 119$  yields  $119^{101} \equiv 129 \pmod{467}$ .

To verify the signature, randomly select  $e_1 = 38$  and  $e_2 = 397$ , then send  $r = 13$  while  $t = 9$  is replied. Finally test that 9 is congruent to  $119^{38} 4^{397} \pmod{467}$ .

2-round verification:



Play the verification protocol using two random values  $e_1, e_2 \in \mathbb{F}_q^*$  and expect  $t_1 \not\equiv m^{e_1} \alpha^{e_2} \pmod{p}$



Re-play the verification protocol using two random values  $f_1, f_2 \in \mathbb{F}_q^*$  and expect  $t_2 \not\equiv m^{f_1} \alpha^{f_2} \pmod{p}$



Concludes that the signature is a forgery if and only if

$$(t_1 \alpha^{-e_2})^{f_1} \equiv (t_2 \alpha^{-f_2})^{e_1} \pmod{p}$$



285

Chaum-van Antwerpen signatures – Disavowal

Remark. The disavowal protocol has two goals:

- Convince Alice that an invalid signature is a forgery
- Prevent Bob from pretending that a valid signature is a forgery

If the signature is invalid then the verification fails. The question is then to know if Bob played a fair game, following the protocol when constructing  $t_1$  and  $t_2$ .

The last step, testing the congruence

$$\left(t_1\alpha^{-e_2}\right)^{f_1} \equiv \left(t_2\alpha^{-f_2}\right)^{e_1} \bmod p,$$

ensures Alice that Bob is not trying to disavow a valid signature.

Notes

286

From authentication to signature

As investigated earlier (1.80), zero-knowledge proofs can be used to authenticate. In fact this can also be extended to signatures.

General strategy:

- Send at once all the committed values  $C_1, \dots, C_n$
- For a message  $m$  compute  $h$ , the hash of  $\langle C_1, \dots, C_n, m \rangle$
- Extract  $n$  bits,  $h_1, \dots, h_n$ , from  $h$  to represent the random requests
- Define the signature of  $m$  as  $\langle h_1, \dots, h_n, R_1, \dots, R_n \rangle$ , where  $R_i$  is the response to challenge  $h_i$  for the committed  $C_i$
- To ensure a proper security level  $n$  should be at least 128

Notes

287

Key points


- How to overcome the birthday attack on digital signatures?
- Cite two famous solutions for digital signatures
- What is the reference choice in terms of digital signatures?
- How to transform a zero-knowledge authentication scheme into a signature scheme?

Notes

6. Secret sharing

Notes





Notes

---

---

---

---



---

---


---

---

290 Intuition

Bob and Alice are now old, famous, and rich      Their mean family wants to get all their money



- All their money is in a safe
- Only them know the secret combination
- They want to teach their family cooperation
- They split the combination such that they need to be at least three to reconstruct it

Notes

---

---

---

---

---

---

---

---

291 Simple secret splitting

Sharing a secret  $m$  between two people:

- Generate a random integer  $r$
- Give  $r$  to a user and  $m - r$  to the other

The idea easy extends to the general case of  $n$  people:

- Take  $l > m$
- Generate  $n - 1$  random integers,  $r_1, \dots, r_{n-1}$  between 1 and  $l$
- Select  $n - 1$  persons and give each an  $r_i$ ,  $1 \leq i < n$
- Give the remaining person  $m - \sum_{i=1}^{n-1} r_i \bmod l$

Notes

---

---

---

---

---

---



---

---

292 More refined setup

In the previous secret splitting strategy all the participants must be together in order to reconstruct the secret  $m$ . At times it might be desirable that only a subset of the people is able to reconstruct it.

Example.

Notes

---

---

---

---

---

---

---


---

## Definition

Let  $t$  and  $w$  be two integers such that  $t \leq w$ . A  $(t, w)$ -threshold scheme is a way to share a secret  $m$  among  $w$  people, such that any subset of at least  $t$  participants can reconstruct  $m$ , while no smaller subset is able to do it.

In practice,  $(t, w)$ -threshold schemes constitute a basic building block for many applications where information need to be shared among many users. For instance they can be used for broadcasting.

## Notes



## Notes

Shamir threshold scheme was invented by Shamir in 1979

- Choose a prime  $p$  larger than the number of participants and the secret  $m$
- Split  $m$  among  $w$  people such that  $t$  persons can reconstruct it
- Choose  $t - 1$  random integers,  $r_1, \dots, r_{t-1} \bmod p$  and define
 
$$S(X) = m + r_1X + \dots + r_{t-1}X^{t-1} \bmod p$$
- Give each participant a pair  $(x_i, y_i)$ , with  $y_i \equiv S(x_i) \bmod p$
- Keep  $S(X)$  secret

*If  $t$  people get together and share their pairs they can recover  $m$*

## Notes

Lets see how  $t$  people can recover  $m$

- Assume the  $t$  participants have the pairs  $(x_1, y_1), \dots, (x_t, y_t)$
- They can derive the following expression

$$\underbrace{\begin{pmatrix} 1 & x_1 & \dots & x_1^{t-1} \\ 1 & x_2 & \dots & x_2^{t-1} \\ \vdots & \vdots & \ddots & \vdots \\ 1 & x_t & \dots & x_t^{t-1} \end{pmatrix}}_V \begin{pmatrix} m \\ r_1 \\ \vdots \\ r_{t-1} \end{pmatrix} \equiv \begin{pmatrix} y_1 \\ y_2 \\ \vdots \\ y_t \end{pmatrix} \bmod p \quad (6.1)$$

- $V$  is the Vandermonde matrix, which has determinant

$$\det V = \prod_{1 \leq j < k \leq t} (x_k - x_j)$$

- Eq. (6.1) has a unique solution when  $V$  is invertible
- From theorem 1.53,  $V$  is invertible if  $\det V \not\equiv 0 \bmod p$ , i.e. for all  $k$  and  $j$ ,  $x_k \not\equiv x_j \bmod p$

## Notes

Example. We want to construct a (3,8)-threshold scheme to protect the secret message "secret", which corresponds to  $m = 190503180520$ .

We choose  $p = 1234567890133$  to be larger than  $m$  and 8, and generate  $r_1 = 482943028839$  and  $r_2 = 1206749628665$ . Then the polynomial of concern is

$$S(X) = 190503180520 + 482943028839X + 1206749628665X^2.$$

We now distribute the pairs  $(x_i, y_i)$ , with  $1 \leq i \leq 8$ :

$x_i$	$y_i$	$x_i$	$y_i$
1	645627947891	5	675193897882
2	1045116192326	6	852136050573
3	154400023692	7	973441680328
4	442615222255	8	1039110787147

## Notes

If 2, 3, and 7 want to recover the message they construct

$$\begin{pmatrix} 1 & 2 & 4 \\ 1 & 3 & 9 \\ 1 & 7 & 49 \end{pmatrix} \begin{pmatrix} m \\ r_1 \\ r_2 \end{pmatrix} \equiv \begin{pmatrix} 1045116192326 \\ 154400023692 \\ 973441680328 \end{pmatrix} \pmod{1234567890133}.$$

This yields

$$(m, r_1, r_2) = 190503180520, 482943028839, 1206749628665.$$

What if only two participants try to reconstruct  $m$ ?

Remark. A quadratic polynomial is defined by three points, and more generally a polynomial of degree  $n$  is defined by  $n+1$  points. Therefore if two participants share their information they will still miss a point and as such will not be able to reconstruct the polynomial at discover  $m$ . Note that there are infinite number of possibilities for this last point.

## Notes

Example. In a company a secret is split into eight shares. The boss decides eight employees should be required to recover the secret. However he also requests that only four managers or only two board members should be able to recover the secret.


Give each regular employee one share, two to managers, and four to board members. The problem is solved, but note that now one board member together with one manager and two employees can recover the secret.

## Notes

Example. Two companies share a bank vault. They want a setup where four employees from the first company and three from the second are required to be together in order to reconstruct the secret combination.

As each company needs more than 4 or 3 shares, each one could reconstruct the whole secret by itself. The idea is then to write the secret  $s = s_1 + s_2$ , and give  $s_1$  as a shared secret for the first company while  $s_2$  becomes a shared secret for the second company. Each of them can apply Shamir threshold scheme to recover its part of the secret. Finally they only need to meet to totally recover the secret combination.

## Notes



Notes

---

---

---


---

---

---

---

---



Notes

---

---

---

---

---

---

---

---

- 303 Practical setup
- A 3-dimensional setup:
- 1 Choose a large prime  $p$
  - 2 Set  $x_s$  to the secret value
  - 3 Select two random values  $y_s$  and  $z_s$  and define  $m = (x_s, y_s, z_s)$
  - 4 Consider the 3-dimensional space mod  $p$
  - 5 Give each participant  $i$  a plane passing by  $m$ :
    - Generate two random integers mod  $p$ ,  $a_i$  and  $b_i$
    - Define  $c_i \equiv (z_s - a_i x_s - b_i y_s) \bmod p$
    - The equation of the plane is  $z = a_i x + b_i y + c_i$

Notes

---

---

---

---

---

---

---

---

304 Recovering the secret

In a 3-dimensional setup three people can deduce the secret  $x_s$ :

- Each participant has a plane
 
$$a_i x + b_i y + c_i \equiv z \bmod p, \quad 1 \leq i \leq 3$$
- They construct the matrix equation
 
$$\underbrace{\begin{pmatrix} a_1 & b_1 & -1 \\ a_2 & b_2 & -1 \\ a_3 & b_3 & -1 \end{pmatrix}}_M \begin{pmatrix} x_s \\ y_s \\ z_s \end{pmatrix} \equiv \begin{pmatrix} -c_1 \\ -c_2 \\ -c_3 \end{pmatrix} \bmod p$$
- If  $\det M$  is invertible mod  $p$  then the system of equations can be solved and  $x_s$  can be recovered

Notes

---

---

---

---

---

---

---

---

305

Example

Let  $p = 73$ , and suppose five people are given the following shares

$$\begin{cases} A : z = 4x + 19y + 68 \\ B : z = 52x + 27y + 10 \\ C : z = 36x + 65y + 18 \\ D : z = 57x + 12y + 16 \\ E : z = 34x + 19y + 49 \end{cases}$$

A, B, and C decide to recover the secret:

$$\begin{pmatrix} 4 & 19 & -1 \\ 52 & 27 & -1 \\ 36 & 65 & -1 \end{pmatrix} \begin{pmatrix} x_s \\ y_s \\ z_s \end{pmatrix} \equiv \begin{pmatrix} -68 \\ -10 \\ -18 \end{pmatrix} \pmod{73}$$

The solution yields  $x_s = 42$ ,  $y_s = 29$ , and  $z_s = 57$

Notes

306

Blakley vs. Shamir

Blakley's scheme

- Matrix  $M$  not always invertible
- Hard to select  $a_i$ ,  $b_i$ , and  $c_i$  for  $M$  to be always invertible
- More general setup
- Much information carried by each participant  $(a_i, b_i, \dots)$

Shamir's threshold scheme

- Matrix  $V$  is invertible, as long as no two shares are congruent mod  $p$
- Method can be view as a particular case of Blakley
- Little information carried by each participant  $(x_i, y_i)$

Notes

307


Key points

- Explain what is secret sharing
- Describe Shamir's threshold scheme
- What is the key idea behind Blakley's scheme?
- Provide several examples where secret sharing is useful

Notes

7. Traitor tracing

Notes



Notes

---

---

---


---

---

---

---

---



Notes

---

---

---

---

---

---

---

---

311 A (too) simple solution

In this setup each user:

- Generates a pair of public/private keys
- Shares his public key with the service provider
- Receives the broadcast encrypted using his public key
- Decrypts and enjoys the program

Drawback: inefficient due to the amount of bandwidth required

Improving the solution: design a scheme where the encrypted information can be decrypted using different secret keys

Notes

---

---

---

---

---

---

---

---

312 Possible attacks

Three general types of attack:

- Decrypt the broadcast and share it
- Record the encrypted broadcast and share the decryption key with other people such that they can watch it
- Create a new secret key from several secret keys collected from various users

The two first cases are not traceable. The third scenario allows the construction of pirate decoders which can be sold at a large scale. The goal is to construct a scheme where tracing the "traitors" who shared their secret key is possible.

Notes

---

---

---

---

---

---

---

---

313
Tracing goals

Desirable properties of the scheme:

- Allows to trace the piracy
- Prevent legitimate users from being incriminated or framed by the traitors
- Allows the disconnection of illegitimate users
- Supplies legal evidence of the pirate's identity

Notes

---

---

---

---

---

---

---

---

---

---

314
Generalities

Types of schemes:

- Symmetric vs. asymmetric: how is encryption done
- Static vs. dynamic: keys changes at certain intervals
- Alternate approach: include credit card number in the user's key or use watermarking

Components of a Traitor Tracing scheme:

- Key generation and distribution
- Encryption and decryption methods
- Tracing algorithm

Notes

---

---

---

---

---

---

---

---

---

---

315
Resilience

When several users collude to generate a new pirate decoder, they use some personal information. The goal of the tracing algorithm is then to spot at least one traitor.

Definition

Assuming the underlying encryption to be secure, a scheme is said to be *m-resilient* if it can trace at least one traitor from a coalition of at most *m* malicious users.

Notes

---

---

---

---

---

---

---

---

---

---

316
Chapter organisation

```

graph TD
    A((Traitor tracing)) --- B((General setup))
    A --- C((Chor-Fiat-Naor scheme))
    A --- D((Boneh-Franklin scheme))

```

Notes

---

---

---

---

---

---

---

---

---

---

Given  $n$  users  $u_1, \dots, u_n$  and  $2 \log n$  keys

$$k_{1,0}, k_{1,1}, k_{2,0}, \dots, k_{\log n,0}, k_{\log n,1},$$

define the key  $K_i$  of user  $u_i$  by

$$K_i = \langle k_{1,b_{i,1}}, k_{2,b_{i,2}}, \dots, k_{\log n, b_{i,\log n}} \rangle,$$

where  $b_{i,j}$  is the  $j$ -th bit in the binary representation of  $i$ .

Applying this strategy, minimizes the number of keys as well as the bandwidth necessary to transmit the encrypted program to all the users.

Example. For eight users six keys  $k_{1,0}, k_{1,1}, k_{2,0}, \dots, k_{3,1}$  are defined. Since  $(5)_{10} = (101)_2$ , user  $u_5$  has key  $K_5 = \langle k_{1,1}, k_{2,0}, k_{3,1} \rangle$ .

Given some information  $m$  to broadcast, it is encrypted using a symmetric encryption protocol  $E$  with a secret key  $S$ . Then proceed as follows.

- Choose  $s_i$ ,  $1 \leq i \leq \log n$  such that

$$S = s_1 \oplus s_2 \oplus \dots \oplus s_{\log n}$$

- Encrypt  $s_i$  using  $E$  and  $k_{i,0}, k_{i,1}$
- Broadcast both the encrypted version of  $m$  and of the secret key  $S$ .

As each user  $u_i$ ,  $1 \leq i \leq n$ , knows either  $k_{i,0}$  or  $k_{i,1}$ , everybody can recover the secret key  $S$  and then decrypt the information  $m$  contained in  $E_S(m)$ .

### Definitions

Let  $E$  be a symmetric encryption protocol with keys of size  $l$ .

- 1 A *codeword* is a  $k$ -tuple of elements from  $\mathbb{F}_q$ , where  $q = 2^l$
- 2 A set of codewords is called a *code*
- 3 Let  $\mathcal{C} \subset (\mathbb{F}_q)^k$  be a code and  $d = \langle d_1, \dots, d_k \rangle$  be a codeword that is not in  $\mathcal{C}$ . If for all  $1 \leq i \leq k$  there exists a codeword  $c = \langle c_1, \dots, c_k \rangle$  in  $\mathcal{C}$  such that  $d_i = c_i$ , then  $d$  is called a *descendant* of  $\mathcal{C}$ . All the descendants of  $\mathcal{C}$  form a *descendant code* of  $\mathcal{C}$ , denoted  $\text{desc}(\mathcal{C})$
- 4 Let  $d$  be a descendant of  $\mathcal{C}$  and  $\mathcal{S}_d = \{C_p \subseteq \mathcal{C} : d \in \text{desc}(C_p)\}$ . A codeword  $c \in \mathcal{C}$  is an *identifiable parent* for  $d$  if

$$c \in \bigcap_{C_p \in \mathcal{S}_d}$$

In the context of a PayTV the previous definitions can be interpreted by identifying each codeword to a decoder.

The idea is then to define a code  $\mathcal{C}$  by assigning a codeword to each decoder, in such a way that  $\text{desc}(\mathcal{C}) \cap \mathcal{C}$  is empty.

The key used in a pirate decoder being constructed from elements of  $\mathcal{C}$ , it is a descendant of  $\mathcal{C}$ . Then  $\mathcal{S}_d$  defines the set of suspects who could be involved in the generation of  $d$ .

An *identifiable parent*  $c$  from  $\mathcal{S}_d$  is a suspect decoder which can be identified as guilty, since  $d$  is derived from  $c$ .



Example. Let  $\mathcal{C}$  be the code defined by

$$\begin{aligned} c_1 &= \langle 0, 0, 0 \rangle, & c_2 &= \langle 0, 1, 1 \rangle, & c_3 &= \langle 0, 2, 2 \rangle, & c_4 &= \langle 1, 0, 3 \rangle, \\ c_5 &= \langle 2, 0, 4 \rangle, & c_6 &= \langle 3, 3, 0 \rangle, & c_7 &= \langle 4, 4, 0 \rangle. \end{aligned}$$

Assume that among the  $c_i$ ,  $1 \leq i \leq 7$ , two traitors collude to construct a codeword  $d = \langle d_1, d_2, d_3 \rangle$ . If any coordinate of  $d$  is non-zero then at least one parent can be identified:

$$\begin{aligned} d_1 = 1 &\rightarrow c_4, & d_1 = 2 &\rightarrow c_5, & d_1 = 3 &\rightarrow c_6, & d_1 = 4 &\rightarrow c_7, \\ d_2 = 1 &\rightarrow c_2, & d_2 = 2 &\rightarrow c_3, & d_2 = 3 &\rightarrow c_6, & d_2 = 4 &\rightarrow c_7, \\ d_3 = 1 &\rightarrow c_2, & d_3 = 2 &\rightarrow c_3, & d_3 = 3 &\rightarrow c_4, & d_3 = 4 &\rightarrow c_5. \end{aligned}$$

Finally if  $d = \langle 0, 0, 0 \rangle$ , then  $c_1$  is an identifiable parent.

### Definitions

- 1 The *hamming distance* between two elements  $a$  and  $b$  of  $(\mathbb{F}_q)^k$  is defined as  $\text{dist}(a, b) = |\{i : a_i \neq b_i, 1 \leq i \leq k\}|$
- 2 Let  $\mathcal{C}$  be a code, then the minimal distance of  $\mathcal{C}$  is  $\text{dist}(\mathcal{C}) = \min \{\text{dist}(a, b) : a, b \in \mathcal{C}, a \neq b\}$

Example. Reusing the code from example 7.321 we note that  $\text{dist}(c_1, c_i)$ ,  $2 \leq i \leq 7$ , is 2, while  $\text{dist}(c_2, c_4) = 3$ . We can observe that no distance is smaller than 2 such that  $\text{dist}(\mathcal{C}) = 2$ .

We now introduce a result which provides some hint on how to choose the distance in order to be able to identify at least one parent of an illegal decoder.

### Theorem

Let  $\mathcal{C} \subset (\mathbb{F}_q)^k$  be a code of length  $k$  and minimal distance  $D$ . If  $D > k(1 - 1/w^2)$ , where  $w$  is the size of the coalition, then it is possible to identify a parent of a descendant of  $\mathcal{C}$ .

Proof. For any  $a, b$  in  $(\mathbb{F}_q)^k$ , we define  $\text{match}(a, b) = k - \text{dist}(a, b)$ . Let  $\mathcal{S}_d = \{C_p \subseteq \mathcal{C} : d \in \text{desc}(C_p)\}$  denote the set of suspects and  $d$  be a descendant of  $C_p \in \mathcal{S}_d$ . Let  $c$  be the closest element from  $d$ . We will now prove that  $c$  belongs to  $C_p$ .

Proof (continued). First note that since  $d$  is a descendant of  $C_p$ , it follows that

$$\sum_{c' \in C_p} \text{match}(d, c') \geq k.$$

Then as the coalition features  $w$  users it means that  $|C_p| \leq w$ , and we can find a codeword  $c'$  in  $C_p$  such that

$$\text{match}(d, c') \geq \frac{k}{w}.$$

Recalling that  $c$  is the closest element from  $d$  we get

$$\text{match}(d, c) \geq \frac{k}{w}.$$

Proof (continued). Finally we consider the number of common coordinates between  $b \in \mathcal{C} \setminus \mathcal{C}_p$  and  $d \in \text{desc}(\mathcal{C}_p)$

$$\text{match}(d, b) \leq \sum_{c' \in \mathcal{C}_p} \text{match}(c', b) \leq w(k - D).$$


If  $D > k(1 - 1/w^2)$ , then clearly  $\text{match}(d, b) < \text{match}(d, c)$ . Since this is true for any  $b \notin \mathcal{C}_p$ , this means that  $c$  belongs to  $\mathcal{C}_p$ .  $\square$

This result is extremely useful as it provides information on how to construct the code and appropriately select the distance in order to trace traitors. As a general rule, the larger the minimum distance between two codewords, the easier to trace. On the other hand, having a large minimum distance will decrease the number of possible codewords in the code.

We notice the following properties:

- The scheme is using symmetric cryptography
- The number of decoders is  $n$
- Each decoder is represented by a  $k$ -tuple of  $\mathbb{F}_q$ , with  $k = \log n$
- The scheme is 1-resilient

*The key aspect of this method is to choose a "good code"*



#### Problem (Representation Problem)

Let  $G$  be a cyclic group of order  $n$  and  $g_1, \dots, g_m$  be  $m$  distinct generators of  $G$ . Then any element  $y \in G$  can be expressed as  $\prod_{i=1}^m g_i^{e_i}$ , for some  $0 \leq e_i \leq \varphi(n)$ . We say that  $(e_1, \dots, e_m)$  is a representation of  $y$  in the base  $(g_1, \dots, g_m)$ . Given  $G$ ,  $y$  and a base  $(g_1, \dots, g_m)$ , find the representation of  $y$ .

This problem can be seen as a generalisation of the DLP (3.205). Moreover when the generators are chosen randomly, finding two different representations of a given element is as hard as solving the DLP.

Simple description:

- $p$  is prime
- $G$  is a subgroup of prime order  $q$
- $g$  is a generator of  $G$
- $m$  is the maximal size of the coalition the scheme can trace
- $l \geq 2m + 2$  is the number of private keys
- $\mathcal{C} = \{c_1, \dots, c_l\}$  is a code of  $\mathbb{Z}^{2m}$

The scheme now described is CPA-1 secure but it can be extended into an enhanced CCA-2 version. This has the effect of more closely mirroring a real life context.

The public and private keys are generated as follows:

- 1 Choose  $2m$  random elements  $r_i$ ,  $1 \leq i \leq 2m$ , in  $\mathbb{F}_q$  and for each  $r_i$  compute  $g_i = g^{r_i}$
- 2 Set the public key to  $\langle y, g_1, \dots, g_{2m} \rangle$ , where  $y = \prod_{i=1}^{2m} g_i^{\alpha_i}$ , with the  $\alpha_i$  being random elements from  $\mathbb{F}_q$
- 3 Set the private key  $k_i \in \mathbb{F}_q$  such that  $k_i c_i$  is a representation of  $y$  in the base  $(g_1, \dots, g_{2m})$ . That is

$$k_i = \frac{\sum_{j=1}^{2m} r_j \alpha_{ij}}{\sum_{j=1}^{2m} r_j c_{ij}} \bmod q$$

Encryption:

- A message  $M$  in  $G$
- Generate a random  $a$  in  $\mathbb{F}_q$
- Define the ciphertext as  $C = \langle My^a, g_1^a, \dots, g_{2m}^a \rangle$

Decryption:

- A ciphertext  $C = \langle My^a, g_1^a, \dots, g_{2m}^a \rangle$
  - Use the  $i$ -th secret key  $k_i$  to compute  $U = \left( \prod_{j=1}^{2m} (g_j^a)^{c_{ij}} \right)^{k_i}$
- $$U = \left( g^{\sum_{j=1}^{2m} r_j c_{ij}} \right)^{k_i a}$$
- $$= \left( g^{\sum_{j=1}^{2m} r_j \alpha_{ij}} \right)^a$$
- Recover  $My^a / U = M = y^a$

The tracing algorithm being more advanced we do not detail it here but only highlight the main ideas.

The key principle behind the tracing ability is related to the difficulty of finding new representations. In fact if several users collude they are able to construct a new representation  $y$ . However this construction leads to a so called "convex combination" of the traitor's keys. It can be proved that if one can find a new representation that is not a convex combination of already known representations then one can solve the DLP.

By analysing the newly generated representation it is then possible to trace at least one traitor.

333

Revocation

Traitor tracing in practice:

- Simple case: the value of the constructed  $k$  is known
- Harder case:
  - Only a card containing the key  $k$  is available
  - Not possible to directly read  $k$
  - Blackbox traitor tracing

Key revocation:

- Black list: too complex
- Alternative:
  - Define the set of all the secret keys  $\mathcal{K} = \{k_1, \dots, k_m\}$
  - For each subset  $\mathfrak{R}$  of  $\mathcal{K}$  generate a public key whose encryption can only be decrypted by the keys in  $\mathfrak{R}$
  - To revoke a secret key change the encryption key

Notes

334

Key points

- List the type of attacks a multicast system can undergo
- What is the resilience?
- Explain the basic idea to trace traitors
- How to handle key revocation?

Notes

335

8. Elliptic Curve Cryptography

Notes

336

Chapter organisation

```
graph TD; A((Elliptic Curve Cryptography)) --- B((Paring based cryptography)); A --- C((Identity based cryptography)); A --- D((Elliptic curves))
```

Notes

Main public key cryptography problems:

- RSA problem (3.185)
- Discrete Logarithm Problem (3.205)

Both problems can be solved using algorithms with sub-exponential complexity; that is algorithm with complexity neither polynomial nor exponential but somewhere in-between.

Consequence on the key size:

Security level (bits)	80	112	128	192	256
Key size (bits)	1024	2048	3072	7680	15360

## Notes


In chapter 3 it was noted that Pollard's rho was a generic algorithm solving the DLP (remark 3.209). In contrast with more efficient algorithms, such as the NFS, Pollard's rho algorithm does not take advantage of the underlying structure of the group.

Therefore a simple idea for the DLP consists in finding a group where no algorithm performs better than Pollard-rho (3.207).

Abstract algebraic structures can be studied from the perspective of geometry. A simple example is the group structure of the integers  $(\mathbb{Z}, +)$  which can be represented on the number line.



## Notes



## Notes

The red curve:

- Is called an *elliptic curve*
- Is defined over a field, here the reals
- Can be defined over other fields
- Is given by the equation

$$y^2 + a_1xy + a_3y = x^3 + a_2x^2 + a_4x + a_6 \quad (8.1)$$

In most cases, a change of variable allows to rewrite equation (8.1) in the more simple form

$$y^2 = x^3 + bx + c$$

## Notes

By construction this is almost a group: only a unit element is missing. Therefore we adjoin the point  $\mathcal{O}$ , called *point at the infinity*. This point can be viewed as the point where all the vertical lines intersect.

### Proposition

Let  $E$  be an elliptic curve of equation  $y^2 = x^3 + bx + c$ . Taking two point  $P_1 = (x_1, y_1)$  and  $P_2 = (x_2, y_2)$  on  $E$ , we define the addition law over  $E$  by  $P_1 + P_2 = P_3 = (x_3, y_3)$  by

$$x_3 = m^2 - x_1 - x_2, \quad y_3 = m(x_1 - x_3) - y_1,$$

with

$$m = \begin{cases} (y_2 - y_1)/(x_2 - x_1) & \text{if } P_1 \neq P_2 \\ (3x_1^2 + b)/(2y_1) & \text{if } P_1 = P_2. \end{cases}$$

This addition law is both associative and commutative. If taking  $\mathcal{O}$  as unit element, then  $E$  is an abelian group.

### Notes

Example. Let  $E$  be the elliptic curve defined by  $y^2 \equiv x^3 + 4x + 4 \pmod{5}$ . The points on  $E$  are all the pairs of elements  $(x, y)$  in  $\mathbb{F}_5 \times \mathbb{F}_5$  that satisfy the equation.

$x \pmod{5}$	$y^2 \pmod{5}$	$y \pmod{5}$	Points on $E$
0	4	2 or 3	(0,2) and (0,3)
1	4	2 or 3	(1,2) and (1,3)
2	0	0	(2,0)
3	3		
4	4	2 or 3	(4,2) and (4,3)

The elliptic curve  $E$  has eight points: seven calculated from the equation plus the point at the infinity  $\mathcal{O}$ .

### Notes

Example. We now determine the sum of the two points (1,2) and (4,3) on  $E$ .

First we note that as 3 is invertible mod 5 then

$$m = \frac{3-2}{4-1} \equiv 2 \pmod{5}.$$

Then we compute  $x_3$  and  $y_3$ ,

$$\begin{aligned} x_3 &\equiv 2^2 - 1 - 4 &\equiv 4 \pmod{5} \\ y_3 &\equiv 2(1 - 4) - 2 &\equiv 2 \pmod{5}. \end{aligned}$$

Finally we have  $(1, 2) + (4, 3) = (4, 2)$  on  $E$ .

### Notes

Simple strategy to count points on any elliptic curve mod  $p$ :

- Compute  $t = x^3 + bx + c$  for  $0 \leq x \leq p-1$
- If  $t$  is square then  $(x, \sqrt{t})$  and  $(x, -\sqrt{t})$  are on  $E$
- Approximately one over two values of  $t$  are squares
- An elliptic curve mod  $p$  has about  $p$  points

### Theorem (Hasse's theorem)

If  $E$  is an elliptic curve with  $n$  points, then

$$|n - p| < 2\sqrt{p}.$$

### Notes

345

Elliptic Curve Discrete Logarithm Problem

Since an elliptic curve gives rise to a group structure it means that we can define a discrete logarithm problem on them.

**Problem (Elliptic Curve Discrete Logarithm Problem (ECDLP))**

Let  $E$  be an elliptic curve over a finite field  $\mathbb{F}_q$ ,  $q = p^n$  for some prime  $p$  and integer  $n$ , and  $P$  be a generator of the group. Given a point  $Q$  on the  $E$ , find  $k$  in  $\mathbb{N}$  such that  $[k]P = Q$ , where  $[k]P$  represent the operation of adding  $k - 1$  times the point  $P$  to itself.

From a geometrical point of view it is clear that given  $k$  and  $P$  is it easy to find  $[k]P$ . However given  $Q$  and  $P$  is it hard to determine  $k$  such that  $[k]P = Q$ . Therefore the ECDLP allows the definition of a 1-way function.

Notes

346

Security of the ECDLP

In the general case, the best known algorithm to solve the ECDLP is Pollard's rho algorithm. From a cryptographic angle it means that the key size, in terms of bits, is only twice the security level.

Security level (bits)	Key size (bits)	
	DLP	ECDLP
80	1024	160
112	2048	224
128	3072	256
192	7680	384
256	15360	512

Notes

347

Chapter organisation

```
graph TD; A((Elliptic Curve Cryptography)) --- B((Paring based cryptography)); A --- C((Elliptic curves)); A --- D((Identity based cryptography))
```

Notes

348

Solving the ECDLP

In remark 3.213 we noted that it was possible to map a hard instance of the DLP into an easier one, for instance in an additive group. Unfortunately this strategy is not practical since computing the map is too time consuming and as such would not provide an speedup.

The question now needs to be reconsidered in the case of elliptic curves. As mentioned earlier (8.346) the best algorithm to solve the ECDLP has exponential complexity. Therefore exhibiting a map from an elliptic curve into a subgroup of a finite field could bring much improvement in solving the ECDLP.

Although such maps exist only a few families of elliptic curves are vulnerable to this attack as in most cases the map is again to hard to compute. In the case where is can be efficiently computed it is called a *cryptographic pairing*.

Notes

## Definition

A *cryptographic pairing* is a map  $e$  from two additive groups  $G_1$  and  $G_2$  into a multiplicative group  $G_T$ . For some given  $P_1, P_2, P \in G_1$  and  $Q_1, Q_2, Q \in G_2$  a pairing has the following properties:

- Bilinearity:

$$e(P, Q_1 + Q_2) = e(P, Q_1)e(P, Q_2)$$

$$e(P_1 + P_2, Q) = e(P_1, Q)e(P_2, Q),$$

- Non-degeneracy:

$$\forall P \in G_1, P \neq \mathcal{O} \quad \exists Q \in G_2 \text{ such that } e(P, Q) \neq 1$$

$$\forall Q \in G_2, Q \neq \mathcal{O} \quad \exists P \in G_1 \text{ such that } e(P, Q) \neq 1,$$

- The map  $e$  is efficiently computable.

## Notes

## Pairings in practice

History of elliptic curves in cryptography:

- Discovered in the mid 80es
- In the 90es pairings were used to attack the ECDLP
- Then some families were abandoned since they were insecure
- Around 2000 pairings were used in a "constructive way"

The most useful property of a pairing is bilinearity. It was realised that it could be used to construct new efficient protocols. We now describe one such example, due to Joux, where three parties can construct a common secret key in only one round.

Notations:

- For  $p$  a prime and  $n$  an integer,  $q = p^n$
- An elliptic curve over  $\mathbb{F}_q$ ,  $E(\mathbb{F}_q)$
- A subgroup of  $E(\mathbb{F}_q)$ ,  $G = G_1 = G_2$

## Notes

## Tripartite key exchange protocol

Initial setup:



Common:  $G$  a subgroup of  $E(\mathbb{F}_q)$ , and  $P$  a generator of  $G$

Personal: a secret key  $x_b$  (Bob),  $x_a$  (Alice), or  $x_c$  (Charly)

Key broadcasting:



Common: broadcast  $Q_i = [x_i]P$ ,  $a \leq i \leq c$

Personal:  $e(Q_a, Q_c)^{x_b}$  (Bob),  $e(Q_b, Q_c)^{x_a}$  (Alice), or  $e(Q_a, Q_b)^{x_c}$  (Charly)

Shared secret key:



Common:  $e([x_a x_b x_c]P, P) = e(P, P)^{x_a x_b x_c}$

## Notes

## Security of pairings

Security:

- $x_a$ ,  $x_b$ , and  $x_c$  must remain secret
- $e(P, P)^{x_a x_b x_c}$  must remain secret

Conclusion: both the DLP and the ECDLP must be secure

Efficiency:


- Pairings become more expensive as  $E(\mathbb{F}_q)$  gets larger
- The group  $G_T$  is a subgroup of  $\mathbb{F}_{q^k}$ , for some integer  $k$
- Arithmetic in  $\mathbb{F}_{q^k}$  becomes more expensive as  $p$ ,  $n$ , and  $k$  grow

Conclusion: balance both security and efficiency

*Always ensure both the ECDLP and DLP have a similar security level*

## Notes





Notes

---

---

---

---

---

---

---

---

354 From PKC to IBC

All the protocols presented in chapter 3 require the use of a directory. This implies first that the user must register with a directory provider when he generates his keys but also that any other user who wants to communicate with should must connect to the directory in order to retrieve a public key.

An alternative, and more convenient solution, would be to use the identity of a user to automatically generate his public key. This would in turn eliminate the necessity of a directory.

Two common ways to solve this problem are to use pairings, or lattice based cryptography. We now present the first identity based protocol proposed by Boneh and Franklin in 2001.

Notes

---

---

---

---

---


---

---

---

355 Initial setup

Trusted Authority (TA)



The TA prepares the system:

- Select an elliptic curve  $E(\mathbb{F}_q)$
- Choose  $G$ , a subgroup of  $E(\mathbb{F}_q)$ , and  $P$  a generator of  $G$
- Pick a random  $s$  and set  $Q = [s]P$
- Choose a hash function  $H_1$  mapping a string into a point in  $G$
- Choose a hash function  $H_2$
- For each user identity  $ID$  compute the secret key  $s_{ID} = [s]H_1(ID)$
- Public parameters:  $\langle H_1, H_2, G, G_T, P, Q \rangle$

Notes

---

---

---

---


---

---

---

---

356 Encryption



Alice sends a message to Bob

Given a message  $m$ :

- Get Bob's ID, e.g. bob@ve475.sjtu.edu.cn
- Compute  $g = e(H_1(\text{bob@ve475.sjtu.edu.cn}), Q)$
- Select a random  $r$  in  $\mathbb{Z}_q^*$
- Compute  $t = m \oplus H_2(g^r)$
- Send the ciphertext  $C = \langle [r]P, t \rangle$

Notes

---

---

---

---

---

---


---

---

357

Decryption

Bob recovers Alice's message



Given a ciphertext  $C = ([r]P, t)$ :

- Set  $ID$  to bob@ve475.sjtu.edu.cn
- Compute  $h = e(s_{ID}, [r]P)$ 

$$h = e([s]H_1(ID), [r]P) = e(H_1(ID), P)^{sr}$$

$$= e(H_1(ID), [s]P)^r = e(H_1(ID), Q)^r$$

$$= g^r$$
- Recover the message as
 
$$t \oplus H_2(h) = m \oplus H_2(g^r) \oplus H_2(g^r) = m$$

Notes

---

---

---

---

---

---

---

---

---

---

358

Security

Basic remarks on the security:

- If  $s$  can be recovered then all the secret keys can be revealed
- If  $r$  can be computed from  $[r]P$  then the message can be recovered
- The hash functions must be collision resistant  
e.g.  $h = e(H_1(ID), [r]P)^s = g_p^s = g^r$ . Neither  $s$  nor  $g^r$  is known but if we can find  $s'$  such that  $H_2(g_p^{s'}) = H_2(g^r)$  then  $m$  can be recovered
- The TA must be trusted

Notes

---

---

---

---

---

---

---

---

---

---

359

Attribute based cryptography

Identity Based Cryptography: public key generated from an ID

Attribute Based Cryptography: public key generated from attributes

Typical use:

- Company: a class of employees is sent some encrypted information; no need to encrypt using the public key of each employee
- Social media: people can belong to many different groups and want to share information only with a certain group without encrypting a special version for each member of the group
- Broadcast encryption: different class of users have paid for different services

Notes

---

---

---

---

---

---

---

---

---

---

360

Key points

- What is an elliptic curve?
- What is the main advantage of elliptic curves in cryptography?
- What is the most useful property of a pairing?
- Explain what Identity Based Cryptography and Attribute Based Cryptography are

Notes

---

---

---

---

---

---

---

---

---

---

## 9. Quantum Cryptography

### Notes

---

---

---

---


---

---

---

---

### Chapter organisation



### Notes

---

---

---

---

---

---

---

---

### Quantum mechanics

#### Basics on quantum mechanics:

- Physics at the atomic and subatomic levels
- Accurate and precise theory
- The state of the system is not given by a physical observation
- Impossible to know exactly the state of the system
- Probabilistic predictions can be made

### Notes

---

---

---

---

---

---

---

---

### Formalism

#### Mathematical formulation:

- Every system is associated with a separable Hilbert space  $H$
- A state of the system is represented by a unit vector in  $H$
- The Ket  $A$  denoted  $|A\rangle$  represents the column vector  $A = a_1|e_1\rangle + a_2|e_2\rangle + \dots + a_n|e_n\rangle$ , where  $|e_1\rangle, \dots, |e_n\rangle$  form a basis for  $H$

$$|A\rangle = \begin{pmatrix} a_1 \\ a_2 \\ \vdots \\ a_n \end{pmatrix}$$

- The Bra  $B$  denoted  $\langle B|$  is the conjugate transpose of  $|B\rangle$

$$\langle B| = \begin{pmatrix} b_1^* & b_2^* & \dots & b_n^* \end{pmatrix}$$

### Notes

---

---

---

---

---

---

---

---

Mathematical formulation:

- The *inner product* of  $B$  and  $A$  is

$$\langle B|A\rangle = b_1^* a_1 + b_2^* a_2 + \cdots + b_n^* a_n$$

- The *outer product* of  $A$  and  $B$  is the tensor product of  $A$  and  $B$  and is denoted

$$|A\rangle\langle B| = \begin{pmatrix} a_1 \\ a_2 \\ \vdots \\ a_n \end{pmatrix} \otimes \begin{pmatrix} b_1^* & b_2^* & \cdots & b_n^* \end{pmatrix} = \begin{pmatrix} a_1 b_1^* & a_1 b_2^* & \cdots & a_1 b_n^* \\ a_2 b_1^* & a_2 b_2^* & \cdots & a_2 b_n^* \\ \vdots & \vdots & \ddots & \vdots \\ a_n b_1^* & a_n b_2^* & \cdots & a_n b_n^* \end{pmatrix}$$

- An *observable* quantity is represented by an Hermitian matrix  $M$

## Notes

Basic ideas behind quantum physics:

- $M$  can be unitarily diagonalized
- The possible outcomes of  $M$  are its eigenvectors
- Its eigenvectors  $|\phi_i\rangle$ ,  $1 \leq i \leq n$ , generate an orthogonal basis
- Any vector  $|\psi\rangle$  can be written as a *superposition* of the  $|\phi_i\rangle$ 

$$|\psi\rangle = c_1 |\phi_1\rangle + \cdots + c_n |\phi_n\rangle$$
- A measurement of  $M$  results in  $|\phi_i\rangle$  with probability  $|c_i|^2$
- Two quantum objects, whose states can only be described with reference to each other, are said to be *entangled*

## Notes

For  $|A\rangle = \begin{pmatrix} 1/2 \\ 1/2 \\ 1/2 \\ 1/2 \end{pmatrix}$ ,  $\langle A|A\rangle = \begin{pmatrix} 1/2 & 1/2 & 1/2 & 1/2 \end{pmatrix} \cdot \begin{pmatrix} 1/2 \\ 1/2 \\ 1/2 \\ 1/2 \end{pmatrix} = 1$ , and

$$|A\rangle\langle A| = \begin{pmatrix} 1/2 \\ 1/2 \\ 1/2 \\ 1/2 \end{pmatrix} \otimes \begin{pmatrix} 1/2 & 1/2 & 1/2 & 1/2 \end{pmatrix}$$

$$= \begin{pmatrix} 1/4 & 1/4 & 1/4 & 1/4 \\ 1/4 & 1/4 & 1/4 & 1/4 \\ 1/4 & 1/4 & 1/4 & 1/4 \\ 1/4 & 1/4 & 1/4 & 1/4 \end{pmatrix}.$$

## Notes

Given two particles which can collapse in the states 0 or 1, the four possible outcomes are  $|00\rangle$ ,  $|01\rangle$ ,  $|10\rangle$ ,  $|11\rangle$ .

The general state of the two particles is given by the superposition

$$|\psi\rangle = a_0|00\rangle + a_1|01\rangle + a_2|10\rangle + a_3|11\rangle, \text{ with } \sum_{i=0}^3 |a_i|^2 = 1.$$

Some states might be written as a product of states for each particle. For instance

$$\frac{1}{2}(|00\rangle + |01\rangle + |10\rangle + |11\rangle) = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \otimes \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle).$$

However in some other cases, such as  $\frac{1}{\sqrt{2}}(|01\rangle + |10\rangle)$ , it cannot be factorized. The particles are then said to be *entangled*.

## Notes

Einstein Podolsky Rosen paper (1935):

- Two particles interact and get entangled
- They form a system which remains in this superposition until a measurement is performed
- The two particles travel far from each other

For instance if a measurement is realised on the first particle from the previous example (9.368) and the outcome is  $|0\rangle$  then the second particle must be in state  $|1\rangle$ .

This idea conflicts with the theory of relativity which states that nothing can travel faster than the speed of light. In fact the measurement of  $|0\rangle$  on the first particle implies probability 1 of getting  $|1\rangle$  whatever the distance between the two particles.

## Notes

Basic idea: create a system where a radioactive atom is "entangled with a cat". If the atom decays and emit radiation some poison is released and the cat dies.




## Notes

High level idea:

- Alice and Bob meet to construct an EPR pair  $(A, B)$ , Alice takes  $A$  and Bob  $B$
- Alice wants to share quantum information on a particle  $C$  with Bob
- Alice creates an EPR pair  $(A, C)$  such that  $A$ ,  $B$ , and  $C$  are now entangled
- Alice measures  $A$  such that  $B$  collapses in a state that "resembles" the state of  $C$
- Using a classical channel Alice sends the state of  $A$  to Bob
- When Bob knows the state of  $A$  he can easily work out the state  $C$  is in

## Notes

## Notes



Notes

---

---

---

---

---

---

---

---

---

---

374 Bit vs. Qubit

- A *qubit* is to a quantum computer, what a bit is to a classical computer
- A qubit can be in any superposition of the states  $|0\rangle = \begin{pmatrix} 1 \\ 0 \end{pmatrix}$  and  $|1\rangle = \begin{pmatrix} 0 \\ 1 \end{pmatrix}$
- Several entangled qubits taken together form a *register*
- A *quantum gate* is a unitary transform on a fixed number of qubits
- A *quantum circuit* is a set of quantum gates linked together

Notes

---

---

---

---

---

---

---

---

---

---

375 Quantum gates

Hadamard transform:

$$H = \frac{1}{\sqrt{2}} \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix}$$

Inverse the phase of the third state in a superposition of two qubits:

$$F_a = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & -1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

More generally  $F_a|x\rangle = \begin{cases} -|a\rangle & \text{if } x = a \\ |x\rangle & \text{otherwise} \end{cases}$

Notes

---

---

---

---

---

---

---

---

---

---

376 Quantum gates

Diffusion transform for a superposition of two qubits:

$$D = \frac{1}{2} \begin{pmatrix} -1 & 1 & 1 & 1 \\ 1 & -1 & 1 & 1 \\ 1 & 1 & -1 & 1 \\ 1 & 1 & 1 & -1 \end{pmatrix}$$

Calling the initial superposition of  $n$  states  $|\psi_0\rangle$  it is generalized as

$$D = 2|\psi_0\rangle\langle\psi_0| - I_n,$$

where  $I_n$  is the identity matrix of dimension  $n$ .

Notes

---

---

---

---

---

---

---

---

---

---

377
A quantum search

Notes

---

---

---

---

---

---

---

---

378
Grover's algorithm

Notes

---

---

---

---

---

---

---

---

379
Finding the horse

For the sake of simplicity we define  $wolf = |00\rangle$ ,  $horse = |01\rangle$ ,  $fish = |10\rangle$ , and  $snake = |11\rangle$ . Therefore only two qubits are needed.

We start with the superposition

$$\frac{1}{2}(|00\rangle + |01\rangle + |10\rangle + |11\rangle) = \frac{1}{2} \begin{pmatrix} 1 \\ 1 \\ 1 \\ 1 \end{pmatrix}.$$

This is achieved by setting the two qubits to  $|0\rangle$  and applying a Hadamard transform to each of them:

$$\frac{1}{\sqrt{2}} \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix} \begin{pmatrix} 1 \\ 0 \end{pmatrix} = \frac{1}{\sqrt{2}} \begin{pmatrix} 1 \\ 1 \end{pmatrix}.$$

Notes

---

---

---

---

---

---

---

---

380
Finding the horse

Then applying the transform  $F_{horse}$  yields

$$\frac{1}{2} \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & -1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} 1 \\ 1 \\ 1 \\ 1 \end{pmatrix} = \frac{1}{2} \begin{pmatrix} 1 \\ -1 \\ 1 \\ 1 \end{pmatrix}.$$

Finally after applying  $D$  we get

$$\frac{1}{4} \begin{pmatrix} -1 & 1 & 1 & 1 \\ 1 & -1 & 1 & 1 \\ 1 & 1 & -1 & 1 \\ 1 & 1 & 1 & -1 \end{pmatrix} \begin{pmatrix} 1 \\ -1 \\ 1 \\ 1 \end{pmatrix} = \begin{pmatrix} 0 \\ 1 \\ 0 \\ 0 \end{pmatrix}.$$

Notes

---

---

---

---

---

---

---

---

381
Quantum circuit

In the case of four elements this can be represented using the following quantum circuit.

This can easily be extended to a set of  $n$  elements, by using a register of  $\log_2 n$  qubits. Hadamard transforms are applied to get the superposition

$$|s\rangle = \frac{1}{\sqrt{n}} \sum_{i=1}^n |i\rangle.$$

The horse can be found by repetitively applying the  $F_{\text{horse}}$  and  $D$  transforms  $O(\sqrt{n})$  times.

Notes

---

---

---

---

---

---

---

---

---

---

382
Quantum computing and cryptography

A few additional remarks:

- Grover's algorithm can be used to find collisions in  $\mathcal{O}(n^{1/3})$  queries
- Quantum algorithms solving the RSA and the DLP in polynomial time exist
- The actual record, established in 2012, is  $56153 = 233 \cdot 241$
- Several hard problems in multivariate and lattice cryptography cannot be solved in polynomial time on a quantum computer

Notes

---

---

---

---

---

---

---

---

---

---

383
Chapter organisation

Notes

---

---

---

---

---

---

---

---

---

---

384
The true story of Alice and Bob

Notes

---

---

---

---

---

---

---

---

---

---





## Notes

386 Quantum bit commitment

3 Commit to  $b$  by choosing a basis for the measurements

4 Send to Alice with  $b =$

1 0 1 1 1

1 Pick  $n$  elements in  $\{0, 1\}$  and  $n$  basis at random

2 Send to Bob

5 Only verify qubits in base  $b$

1 0 1

## Notes

387 Security

Security of the protocol:

- Alice generates the 0,1 and the basis but has no idea on  $b$ , so she cannot cheat
- If Bob has access to a large quantum memory he can copy the qubits, measure them in a basis and their copy in the other basis
- Qubits are very hard to store, so it is a fair assumption to assume that Bob cannot store the  $n$  qubits
- As a measurement destroys the information he cannot measure again in another basis and as such he cannot cheat

## Notes

388 Bit commitment

Bit commitment protocols are very simple, and can easily be realised without the help of quantum cryptography.

Example. Simple bit commitment protocol:

- Bob generates a 100-bit long string
- He appends his bit  $b$  and another 100-bit long string
- He sends the hash of the 201-bit long string to Alice
- To reveal  $b$  Bob sends the 201-bit long string

## Notes

389
The end...

While figuring out a bit commitment protocol Alice and Bob forgot why they wanted to get a divorce and they fell in love again...



Notes

390
Key points


- For two particles what does it mean to be entangled?
- What is a qubit?
- What is the advantage of quantum computing over classical computing?
- What is a bit commitment protocol?

Notes

10. Side channel attacks


Notes

392
Chapter organisation



Notes

393Basic idea



Curious Bob want to know what is his present

Notes

---

---

---

---


---

---

---

---

394Basic idea



Notes

---

---

---

---


---

---

---

---

395Replay



Notes

---

---

---

---

---

---

---

---

396Side channel attacks

Computers leak information when performing an operation:

- Amount of power used
- Time spent
- Area of the memory used
- Electromagnetic radiations
- Sounds (hard disk, beep...)
- Frequency of sending packets on the network

Notes

---

---

---

---

---

---

---

---


397
General remarks

A few important notes:

- Side channel attacks apply to any protocol
- A secure cipher with no attack on the protocol is not immune to side channel attacks
- Not many way to get protected

Example. SSH is a secure way to connect to a remote computer. If a user authenticate using a password, the time between each keystroke, or packet sent on the network, can be analysed and the password recovered.

An audio recording of someone typing on a keyboard is enough to know what he is writing.



399
RSA implementations

To break RSA the goal is to find the secret key:

- When a user decrypts a message
- When a user signs a message

The attacker can access to the host device to:

- Run some malicious code
- Perform measurements

As running RSA leaks information the attacker only needs to read it and then perform some analysis in order to interpret it.

400
Timing attack

General approach:

- RSA decryption/signature uses the square and multiply algorithm (3.172)
- On a 0 only a squaring occurs
- On a 1 a squaring and a multiplication occur

The mean not being precise enough the variance is used to analyse a large number of decryption requests. The attacker then uses the fact that the variance of the sum of two independent random processes is the sum of their respective variance. He gains little information on the secret key but he reuses it to perform more accurate measurements and in the end he is able to totally recover the key.

Notes

---

---

---

---

---

---

---

---

---

---

Notes

---

---

---

---

---

---

---

---

---

---

Notes

---

---

---

---

---

---

---

---

---

---

Notes

---

---

---

---

---

---

---

---

---

---

401

## Power analysis attack

In this attack the key idea is to observe the power consumption of the computer when decrypting or signing a message.



On a 1 both a square and a multiply are carried out. When only a squaring occurs the power consumption is much lower. This attack is clearly much more powerful and efficient than the previous one. In fact no more than one decryption is necessary to recover the secret key.

We now present an algorithm that performs modular exponentiation without leaking much information.

## Notes

402

## Montgomery's ladder technique

Algorithm. (*Modular exponentiation*)

**Input** :  $m$  an integer,  $d = (d_{k-1} \dots d_0)_2$  and  $n$  two positive integers

**Output** :  $x = m^d \bmod n$

**put** :

```

1 power1  $\leftarrow m$ ; power2  $\leftarrow m^2$ ;
2 for  $i \leftarrow k-2$  to 0 do
3   if  $d_i = 0$  then
4     power2  $\leftarrow (power1 \cdot power2) \bmod n$ ;
5     power1  $\leftarrow power1^2 \bmod n$ ;
6   else
7     power1  $\leftarrow (power1 \cdot power2) \bmod n$ ;
8     power2  $\leftarrow power2^2 \bmod n$ ;
9   end if
10 end for
11 return power1

```

## Notes

403

## Preventing attacks on RSA

The previous algorithm has the advantage of performing both multiplication and squaring whatever the bit considered. Therefore monitoring the power consumption would not bring any information on the secret key as it would look as on the following picture.




Note that the Montgomery's ladder technique is still vulnerable to cache timing attacks. Indeed an attacker could measure the time necessary to access the memory, and as this depends on which variable is used he could recover some information on the bits composing the secret key.

## Notes

404

## Chapter organisation



## Notes

Extract information on the design and process of a program:

- Get the binary file
- Disassemble it
- Understand the generated assembly code
- Extract some important information

*Never store a secret key in a binary, "everybody" can retrieve it*

## Notes

Page sharing:

- Share parts of the memory between processes
- Avoid replicated copies of identical content
- Pages are read-only
- On a write request, copy the page onto a new writable location

Cache structure in modern processors:

- Each core has two levels of cache L1 and L2
- A third level L3 is shared among all the cores
- Removing data from L3 also flushes it from both L1 and L2
- The closer from the CPU the faster to retrieve data

A cache timing attack measures how long it takes the CPU to fetch the data. This leaks information on what operation is performed.

## Notes

High level idea applied by the attacker:

- Use `mmap` to map the victim's executable file into the attacker's address space
- Mark up memory lines related to specific operations
- Flush the memory line from the L3 cache and wait
- Call the memory line and measure how long it takes it load it
- Slow loading: the line was not called by the victim
- Fast loading: the line is in the cache, meaning it was used

It is impossible to prevent this attack on a multi-user system as it is inherent to the implementation of the X86 architecture. Only a hardware fix could solve this weakness.

## Notes

Simple conclusion:

- It is impossible to prevent all the kinds of side channel attack
- A system can never be 100% secure

What can be done:

- Chose secure protocols
- Select secure libraries
- GMP implements function intended for a cryptographic use
- Such functions are slower but more resistant to side channel attacks

## Notes

VMWare View is a popular remote desktop protocol. VMWare recommends to switch from AES-128 to SALSA20-256 for the "best user experience".

A closer look at the specs shows that AES-128 refers to AES-128-GCM, which includes AES and message authentication. On the other hand SALSA20-256 refers to SALSA20-256-Round12, which does not feature any message authentication.


Although SALSA20 has speed and security advantages over AES an attacker can easily forge packets if it is not used in conjunction with message authentication.

*Is it worth sacrificing security for the sake of speed?*

## Notes

- Explain what are side channel attacks
- List two examples of side channel attacks
- How to prevent side channel attacks?
- Can a system be made fully secure?

## Notes



Thank you, enjoy the Summer break!

## Notes

## References I

- 1.31 <https://www.xkcd.com/538/>
- 1.47 Simon Singh, *The Code Book – How to make it, break it, hack it, crack it?*
- 1.61 <https://cdn.globalauctionplatform.com/7187abcf-14de-4d26-9a48-a48e012a3bd3/1f194fa9-87f4-45cd-b6db-a48e012de5c7/original.jpg>
- 2.86 <https://upload.wikimedia.org/wikipedia/commons/5/56/Tux.jpg>
- 2.86 [https://upload.wikimedia.org/wikipedia/commons/f/f0/Tux\\_ecb.jpg](https://upload.wikimedia.org/wikipedia/commons/f/f0/Tux_ecb.jpg)
- 2.86 [https://upload.wikimedia.org/wikipedia/commons/a/a0/Tux\\_secure.jpg](https://upload.wikimedia.org/wikipedia/commons/a/a0/Tux_secure.jpg)
- 2.89 <https://www.xkcd.com/221/>
- 10.401 G. Hollestelle, W. Burgers, J. den Hartog, *Power analysis on smartcard algorithms using simulation*
- 10.403 G. Hollestelle, W. Burgers, J. den Hartog, *Power analysis on smartcard algorithms using simulation*

## Notes