

Theory of Computation

MIEIC, 2nd Year

João M. P. Cardoso

Email: jmpc@acm.org

Outline


- ▶ Non-Deterministic Finite Automata with ε transitions (ε -NFAs)
- ▶ Conversion of ε -NFAs into DFAs

Finite Automata with ϵ Transitions

- ▶ What is an ϵ transition?
- ▶ A spontaneous transition (empty-string transition) that can be followed without receiving/consuming/processing input symbols (i.e., for any input symbol)
- ▶ An ϵ -NFA is an NFA with ϵ transitions

Finite Automata with ϵ Transitions (cont.)

- ▶ Example: ϵ -NFA that recognizes decimal numbers
 - ▶ Signal + or – optional
 - ▶ Sequence of digits
 - ▶ A decimal point
 - ▶ Another sequence of digits (at least one of the sequences of digits is non-empty)




Exercise 1

- ▶ Modify the previous state diagram in order to not recognize inputs like: .5, +.1, and -.1
- ▶ More precise, this new definition of a decimal number is:
 - ▶ Signal + or – optional
 - ▶ A sequence of digits with length greater or equal 1
 - ▶ A decimal part consisting of a ‘.’ followed by an optional sequence of digits x, such that $|x| \geq 0$.

Formal Notation ε -NFA

- ▶ ε -NFA $E = (Q, \Sigma, \delta, q_0, F)$
 - ▶ The major difference is in the transition function δ to deal with ε
 - ▶ $\delta(q, a)$: state $q \in Q$ and $a \in \Sigma \cup \{\varepsilon\}$
- ▶ Example: $E = (\{q_0, q_1, q_2, q_3, q_4, q_5\}, \{., +, -, 0, \dots, 9\}, \delta, q_0, \{q_5\})$
- ▶ The symbol representing the empty-string, ε , is not visible in the sequence of digits
 - ▶ It represents spontaneous transitions
 - ▶ We deal with it in the same way as with the non-determinism, i.e., considering that the automaton can be in all the states before and after the ε transition
- ▶ To know which are the states we can reach from a state q with ε , we calculate the ε -close(q)
 - ▶ ε -close(q_0) = $\{q_0, q_1\}$; ε -close(q_3) = $\{q_3, q_5\}$



δ	ε	$+, -$	$.$	$0, \dots, 9$
$\rightarrow q_0$	$\{q_1\}$	$\{q_1\}$	\emptyset	\emptyset
q_1	\emptyset	\emptyset	$\{q_2\}$	$\{q_1, q_4\}$
q_2	\emptyset	\emptyset	\emptyset	$\{q_3\}$
q_3	$\{q_5\}$	\emptyset	\emptyset	$\{q_3\}$
q_4	\emptyset	\emptyset	$\{q_3\}$	\emptyset
$*q_5$	\emptyset	\emptyset	\emptyset	\emptyset

Extended Transitions

► ε -close(q) or $EClose(q)$

► Basis: State q is in $EClose(q)$

► Induction: if p is in $EClose(q)$ and exists an ε -transition from p to r , then r is also in $EClose(q)$

► Extended transition $\hat{\delta}$

► Basis: $\hat{\delta}(q, \varepsilon) = EClose(q)$

► Induction: $w = xa$, $a \in \Sigma$ (thus, $a \neq \varepsilon$)

► 1. let's $\hat{\delta}(q, x) = \{p_1, p_2, \dots, p_k\}$

► 2.

$$\bigcup_{i=1}^k \delta(p_i, a) = \{r_1, \dots, r_m\}$$

► 3.

$$\delta(q, w) = \bigcup_{j=1}^m EClose(r_j)$$


► (1.) gives the states reached from q following a path representing x that can include (and/or terminate in) one or more ε

Eliminating ε Transitions

- ▶ Given an ε -NFA E there exists always an equivalent DFA D
 - ▶ E and D accept the same language
- ▶ Technique of subsets construction
 - ▶ ε -NFA $E = (Q_E, \Sigma, \delta_E, q_0, F_E) \rightarrow$ DFA $D = (Q_D, \Sigma, \delta_D, q_D, F_D)$
- ▶ Q_D is the set of subsets of Q_E closed in ε
 - ▶ $Q_D = \text{EClose}(Q_E)$
- ▶ Start state: $q_D = \text{EClose}(q_0)$
- ▶ $F_D = \{S \mid S \text{ is in } Q_D \text{ and } S \cap F_E \neq \emptyset\}$
- ▶ Transition $\delta_D(S, a)$, with a in Σ and S in Q_D
 - ▶ $S = \{p_1, p_2, \dots, p_k\}$
 - ▶ Calculate
$$\bigcup_{i=1}^k \delta_E(p_i, a) = \{r_1, \dots, r_m\}$$
 - ▶ Terminate with
$$\delta_D(S, a) = \bigcup_{j=1}^m \text{EClose}(r_j)$$


Example of the Recognizer of Decimals

► Convert the ε -NFA to a DFA:



Example of the Recognizer of Decimals

► Convert the ε -NFA to a DFA:



δ	ε	$+,-$	$.$	$0,...,9$
$\rightarrow q_0$	$\{q_1\}$	$\{q_1\}$	\emptyset	\emptyset
q_1	\emptyset	\emptyset	$\{q_2\}$	$\{q_1, q_4\}$
q_2	\emptyset	\emptyset	\emptyset	$\{q_3\}$
q_3	$\{q_5\}$	\emptyset	\emptyset	$\{q_3\}$
q_4	\emptyset	\emptyset	$\{q_3\}$	\emptyset
$*q_5$	\emptyset	\emptyset	\emptyset	\emptyset




$\varepsilon\text{-close}(q_0) = \{q_0, q_1\}$
 $\varepsilon\text{-close}(q_1) = \{q_1\}$
 $\varepsilon\text{-close}(q_2) = \{q_2\}$
 $\varepsilon\text{-close}(q_3) = \{q_3, q_5\}$
 $\varepsilon\text{-close}(q_4) = \{q_4\}$
 $\varepsilon\text{-close}(q_5) = \{q_5\}$

Example of the Recognizer of Decimals

$\epsilon\text{-close}(q_0)=\{q_0, q_1\}$
 $\epsilon\text{-close}(q_1)=\{q_1\}$
 $\epsilon\text{-close}(q_2)=\{q_2\}$
 $\epsilon\text{-close}(q_3)=\{q_3, q_5\}$
 $\epsilon\text{-close}(q_4)=\{q_4\}$
 $\epsilon\text{-close}(q_5)=\{q_5\}$

► Convert the ϵ -NFA to a DFA:




δ	ϵ	$+, -$	$.$	$0, \dots, 9$
$\rightarrow q_0$	$\{q_1\}$	$\{q_1\}$	\emptyset	\emptyset
q_1	\emptyset	\emptyset	$\{q_2\}$	$\{q_1, q_4\}$
q_2	\emptyset	\emptyset	\emptyset	$\{q_3\}$
q_3	$\{q_5\}$	\emptyset	\emptyset	$\{q_3\}$
q_4	\emptyset	\emptyset	$\{q_3\}$	\emptyset
$*q_5$	\emptyset	\emptyset	\emptyset	\emptyset




δ	$+, -$	$.$	$0, \dots, 9$
$\rightarrow\{q_0, q_1\}$	$\{q_1\}$	$\{q_2\}$	$\{q_1, q_4\}$
$\{q_1\}$	\emptyset	$\{q_2\}$	$\{q_1, q_4\}$
$\{q_2\}$	\emptyset	\emptyset	$\{q_3, q_5\}$
$\{q_1, q_4\}$	\emptyset	$\{q_2, q_3, q_5\}$	$\{q_1, q_4\}$
$*\{q_3, q_5\}$	\emptyset	\emptyset	$\{q_3, q_5\}$
$*\{q_2, q_3, q_5\}$	\emptyset	\emptyset	$\{q_3, q_5\}$
\emptyset	\emptyset	\emptyset	\emptyset

Example of the Recognizer of Decimals

► Convert the ε -NFA to a DFA:



δ	$+, -$	$.$	$0, \dots, 9$
$\rightarrow \{q_0, q_1\}$	$\{q_1\}$	$\{q_2\}$	$\{q_1, q_4\}$
$\{q_1\}$	\emptyset	$\{q_2\}$	$\{q_1, q_4\}$
$\{q_2\}$	\emptyset	\emptyset	$\{q_3, q_5\}$
$\{q_1, q_4\}$	\emptyset	$\{q_2, q_3, q_5\}$	$\{q_1, q_4\}$
$*\{q_3, q_5\}$	\emptyset	\emptyset	$\{q_3, q_5\}$
$*\{q_2, q_3, q_5\}$	\emptyset	\emptyset	$\{q_3, q_5\}$
\emptyset	\emptyset	\emptyset	\emptyset



(note that the state/transition diagram is omitting the dead state)

Exercise 2

- ▶ Consider the following ε -NFA:

	ε	a	b	c
$\rightarrow p$	\emptyset	$\{p\}$	$\{q\}$	$\{r\}$
q	$\{p\}$	$\{q\}$	$\{r\}$	\emptyset
$*r$	$\{q\}$	$\{r\}$	\emptyset	$\{p\}$

- ▶ Calculate the ε -close for each state
- ▶ Indicate all the strings with length ≤ 3 accepted by the automaton
- ▶ Convert the ε -NFA into a DFA