

A Markov model for automatic segmentation in audio recordings

Rafael de Jesús Robledo Juárez

`rrobledo@cimat.mx`

Advisor: Salvador Ruíz-Correa Ph.D

Computer Science Department
Center for Mathematical Research (CIMAT), Guanajuato




CIMAT

Preliminary thesis presentation, 2013

Main objectives

- Use a Hidden Markov Model to partitioning an audio recording into similar-speaker regions. Each segment should correspond to a different speaker.
- This task is known as Speaker diarization. Has two main stages: segmentation and clustering.



- Each of the segments will be labeled according to different speakers found in the conversation.




Motivation

- ▶ Speaker identification in a audio recording it's an important stage for improving results in different NPL applications such as automatic transcription and speech recognition, as long as it allow us to fit a model for each different found speaker.
- ▶ A remarkable point in the automation of this process is to perform segmentation with out needing of priori knowledge on the number or gender of persons involved in recording.




Methodology


Signal processing (1)



► Original signal



► Silence identifier




► Truncated signal




Methodology


Signal processing (2)



► FFT + Filter Bank




► log + DCT



► k-means ++

Methodology

Model




Progress


- ▶ System implementation completed.
- ▶ Results for synthetic data (randomly generated).
- ▶ Starting tests for synthetic voice recordings.



Synthetic data tests




Synthetic data tests



Schedule

Activities



Reference material



L.R. Rabiner, B.H. Juang
Fundamentals of speech recognition
Pearson Education India, 2008.



C. M. Bishop.
Pattern Recognition and Machine Learning.
Springer, 2006.



L.R. Rabiner
A tutorial on hidden Markov models and selected applications in speech recognition
Proceedings of the IEEE, 1989.



T. Rydén.
EM versus Markov chain Monte Carlo for Estimation of Hidden Markov Models: A Computational Perspective
Bayesian Analysis (2008) 3, Number 4, p. 659-688



E.B. Fox, E.B. Sudderth, M.I. Jordan, A.S. Willsky.
A sticky HDP-HMM with application to Speaker diarization.
Annals of Applied Statistics, 2011.

