

Higher-Order Programming I: Map and Filter

Principles of Programming Languages
Lecture 8

Introduction

Administrivia

Assignment 3 is due on **Friday** by 11:59PM.

Assignment 4 will be out later today.

The midterm for this course is in two weeks (2/27).

Objectives

Introduce the notion of `higher-order functions` and how they can help us write cleaner, more general code.

Examine two classic higher-order functions, `map` and `filter`.

Keywords

higher-order functions

first-class values

functions as function parameters

the abstraction principle

map and filter

tail-recursive map and filter

Practice Problem

*Implement a function **split_sorted** which given*

l : a sorted int list

i : int

*returns two sorted lists, one which has the elements of **l** which are at most **i** , and the other which has the elements of **l** which are greater than **i** .*

Higher-Order Functions

Higher-Order Programming

Higher-Order Programming

In OCaml, functions are **first-class values**:

Higher-Order Programming

In OCaml, functions are **first-class values**:

1. They can be given names with `let-definitions`.

Higher-Order Programming

In OCaml, functions are **first-class values**:

1. They can be given names with `let-definitions`.
2. They can be `returned` by another function.

Higher-Order Programming

In OCaml, functions are **first-class values**:

1. They can be given names with `let-definitions`.
2. They can be `returned` by another function.
3. They can be `passed as arguments` to another function.

Higher-Order Programming

In OCaml, functions are **first-class values**:

1. They can be given names with `let-definitions`.
2. They can be `returned` by another function.
3. They can be `passed as arguments` to another function.

Note. Types are *not* first-class values.

An Aside: Robin Popplestone

"He started a PhD at Manchester University before moving to Leeds University. His project was to develop a program for automated theorem proving, but he got caught up in **using the university computer to design a boat**. He built the boat and set sail for the University of Edinburgh, where he had been offered a research position. A storm hit while crossing the North Sea, and **the boat sank**. A widely believed story about Popplestone was that he never completed his PhD in mathematics because he **lost his thesis manuscript in the boat**, although Popplestone refused to corroborate this."



Functions as Returned Values

```
# let f x y = x + y;;  
val f : int -> int -> int = <fun>  
# f 2;;  
- : int -> int = <fun>
```

Functions as Returned Values

```
# let f x y = x + y;;  
val f : int -> int -> int = <fun>  
# f 2;;  
- : int -> int = <fun>
```

This is not interesting in OCaml...

Functions as Returned Values

```
# let f x y = x + y;;  
val f : int -> (int -> int) = <fun>  
# f 2;;  
- : int -> int = <fun>
```

This is not interesting in OCaml...

Functions as Returned Values

```
# let f x y = x + y;;  
val f : int -> (int -> int) = <fun>  
# f 2;;  
- : int -> int = <fun>
```

This is not interesting in OCaml...

Multi-argument functions in OCaml are really single-argument functions which **return functions**.

Functions as Named Values

`let f x y = x + y`

is shorthand for...

`let f = fun x -> fun y -> x + y`

Functions as Named Values

```
let f x y = x + y
```

is shorthand for...

```
let f = fun x -> fun y -> x + y
```

This is also not interesting in OCaml...

Functions as Named Values

```
let f x y = x + y
```

is shorthand for...

```
let f = fun x -> fun y -> x + y
```

This is also not interesting in OCaml...

When we **let-define any function**, we're giving a (anonymous) function value a name.

Functions as Named Values

```
let f x y = x + y
```

is shorthand for...

```
let f = fun x -> fun y -> x + y
```

anonymous function

This is also not interesting in OCaml...

When we **let-define any function**, we're giving a (anonymous) function value a name.

Functions and parameters

```
# let apply f x = f x;;  
val apply : ('a -> 'b) -> 'a -> 'b = <fun>  
# apply add_five 10;;  
- : int = 15
```

Functions and parameters

```
# let apply f x = f x;;  
val apply : ('a -> 'b) -> 'a -> 'b = <fun>  
# apply add_five 10;;  
- : int = 15
```

This is *very* interesting in OCaml...

Functions and parameters

```
# let apply f x = f x;;  
val apply : ('a -> 'b) -> 'a -> 'b = <fun>  
# apply add_five 10;;  
- : int = 15
```

note the type

This is *very* interesting in OCaml...

Functions and parameters

```
# let apply f x = f x;;  
val apply : ('a -> 'b) -> 'a -> 'b = <fun>  
# apply add_five 10;;  
- : int = 15
```

note the type

This is *very* interesting in OCaml...

This allows us to create new functions which are **parametrized** by old ones.

Higher-Order Functions Elsewhere

$$\text{fun } f \rightarrow \frac{f(x)}{dx} \qquad \text{e.g.} \qquad x^2 \mapsto 2x$$


We might think of the type of an **derivative** as

$$(\mathbb{R} \rightarrow \mathbb{R}) \rightarrow \mathbb{R} \rightarrow \mathbb{R}$$

because it takes one function and produces a new function.

An Aside: What does Higher-Order Mean?

"Like things and functions are different, so are functions whose **arguments are functions** radically different from functions whose **arguments must be things**. I call the latter functions of first order, the former functions of second order."



Gottlob Frege

First-Order Function Types

`int -> string`

`t -> t`

`() -> bool`

`bool * bool -> bool`

Second-Order Function Types

$(\text{int} \rightarrow \text{string}) \rightarrow (\text{int} \rightarrow \text{string})$

$t \rightarrow (s \rightarrow t)$

$(() \rightarrow \text{bool}) \rightarrow \text{bool}$

$\text{bool} \rightarrow \text{bool} \rightarrow \text{bool}$

Third-Order Function Types

`(int -> string) -> (int -> string) -> (int -> string)`

`(t -> (s -> t)) -> t`

`((() -> bool) -> bool) -> bool`

`(bool -> bool -> bool) * bool -> bool`

And so on...

$t \rightarrow t \rightarrow t \rightarrow t \rightarrow t \rightarrow \dots$

The **higher-order** part comes from the fact that we can do this *ad infinitum*.

(In practice, we rarely use higher than third-order or fourth-order functions.)

The Abstraction Principle

Motivation

Motivation

One of the three virtues of a great programmer
is **laziness**.

Motivation

One of the three virtues of a great programmer is **laziness**.

The **abstraction principle** helps use be lazy.

Motivation

One of the three virtues of a great programmer is **laziness**.

The **abstraction principle** helps use be lazy.

When we write general programs, we **avoid rewriting programs** we've (pretty much) written before.

A Simple Example

```
let rec reverse (l : int list) : int list =  
  match l with  
  | [] -> []  
  | x :: xs -> reverse xs @ [x]
```

A Simple Example

```
let rec reverse (l : int list) : int list =  
  match l with  
  | [] -> []  
  | x :: xs -> reverse xs @ [x]
```

Recall. Polymorphism allows us to write general functions by being *agnostic* to the input type.

A Simple Example

```
let rec reverse (l : 'a list) : 'a list =  
  match l with  
  | [] -> []  
  | x :: xs -> reverse xs @ [x]
```

Recall. Polymorphism allows us to write general functions by being *agnostic* to the input type.

A Simple Example

```
let rec reverse (l : 'a list) : 'a list =  
  match l with  
  | [] -> []  
  | x :: xs -> reverse xs @ [x]
```

Recall. Polymorphism allows us to write general functions by being *agnostic* to the input type.

*It doesn't matter if we're reversing a list of **ints** or a list of **strings**, the function is the same.*

A Simple Example

```
let rec fact n =  
  match n with  
  | 0 -> 1  
  | n -> n * fact (n - 1)
```

```
let rec sum n =  
  match n with  
  | 0 -> 0  
  | n -> n + sum (n - 1)
```

A Simple Example

```
let rec fact n =  
  match n with  
  | 0 -> 1  
  | n -> n * fact (n - 1)
```

```
let rec sum n =  
  match n with  
  | 0 -> 0  
  | n -> n + sum (n - 1)
```

Some functions cannot be polymorphic.

A Simple Example

```
let rec fact n =  
  match n with  
  | 0 -> 1  
  | n -> n * fact (n - 1)
```

```
let rec sum n =  
  match n with  
  | 0 -> 0  
  | n -> n + sum (n - 1)
```

Some functions cannot be polymorphic.

But can we abstract the core functionality?

A Simple Example

```
let rec fact n =  
  match n with  
  | 0 -> 1  
  | n -> n * fact (n - 1)
```

```
let rec sum n =  
  match n with  
  | 0 -> 0  
  | n -> n + sum (n - 1)
```

Some functions cannot be polymorphic.

But can we abstract the core functionality?

A Simple Example

```
let rec upto f n start =  
  let rec go n =  
    match n with  
    | 0 -> start  
    | n -> f n (go (n - 1))  
  in go n
```

A Simple Example

```
let rec upto f n start =  
  let rec go n =  
    match n with  
    | 0 -> start  
    | n -> f n (go (n - 1))  
  in go n
```

In order to generalize this function, we need to be able to take the **operation as a parameter**.

A Simple Example

```
let rec upto f n start =  
  let rec go n =  
    match n with  
    | 0 -> start  
    | n -> f n (go (n - 1))  
  in go n
```

In order to generalize this function, we need to be able to take the **operation as a parameter**.

A Simple Example

```
let rec upto f n start =  
  let rec go n =  
    match n with  
    | 0 -> start  
    | n -> f n (go (n - 1))  
  in go n
```

In order to generalize this function, we need to be able to take the **operation as a parameter**.

Now we have a single function which we can **reuse** elsewhere.

demo
(fact_sum.ml)

Another Example: Sorting

```
let rec insert (x : 'a) (l : 'a list) : 'a list =  
  match l with  
  | [] -> [x]  
  | y :: ys -> if x <= y then x :: y :: ys else y :: insert x ys
```

```
let rec sort (l : 'a list) : 'a list =  
  match l with  
  | [] -> []  
  | x :: xs -> insert x (sort xs)
```

Another Example: Sorting

```
let rec insert (x : 'a) (l : 'a list) : 'a list =  
  match l with  
  | [] -> [x]  
  | y :: ys -> if x <= y then x :: y :: ys else y :: insert x ys
```

```
let rec sort (l : 'a list) : 'a list =  
  match l with  
  | [] -> []  
  | x :: xs -> insert x (sort xs)
```

Note. Sorting *is* polymorphic.

Another Example: Sorting

```
let rec insert (x : 'a) (l : 'a list) : 'a list =  
  match l with  
  | [] -> [x]  
  | y :: ys -> if x <= y then x :: y :: ys else y :: insert x ys  
  
let rec sort (l : 'a list) : 'a list =  
  match l with  
  | [] -> []  
  | x :: xs -> insert x (sort xs)
```

Note. Sorting *is* polymorphic.

But what if we want to sort in **reverse order**?

Another Example: Sorting

```
let rec insert (x : 'a) (l : 'a list) : 'a list =  
  match l with  
  | [] -> [x]  
  | y :: ys -> if x >= y then x :: y :: ys else y :: insert x ys  
  
let rec sort (l : 'a list) : 'a list =  
  match l with  
  | [] -> []  
  | x :: xs -> insert x (sort xs)
```

Note. Sorting *is* polymorphic.

But what if we want to sort in **reverse order**?

Another Example: Sorting

```
let rec insert (x : 'a) (l : 'a list) : 'a list =  
  match l with  
  | [] -> [x]  
  | y :: ys -> if x >= y then x :: y :: ys else y :: insert x ys  
  
let rec sort (l : 'a list) : 'a list =  
  match l with  
  | [] -> []  
  | x :: xs -> insert x (sort xs)
```

Note. Sorting *is* polymorphic.

But what if we want to sort in reverse order?

We shouldn't rewrite the whole function.

Another Example: Sorting

```
let insert (le : 'a -> 'a -> bool) =  
  let rec go x l =  
    match l with  
    | [] -> [x]  
    | y :: ys ->  
      if le x y then  
        x :: y :: ys  
      else  
        y :: go x ys  
  in go  
  
let rec sort (le : 'a -> 'a -> bool) =  
  let rec go l =  
    match l with  
    | [] -> []  
    | x :: xs -> insert le x (go xs)  
  in go
```


Another Example: Sorting

```
let insert (le : 'a -> 'a -> bool) =  
  let rec go x l =  
    match l with  
    | [] -> [x]  
    | y :: ys ->  
      if le x y then  
        x :: y :: ys  
      else  
        y :: go x ys  
  in go
```

```
let rec sort (le : 'a -> 'a -> bool) =  
  let rec go l =  
    match l with  
    | [] -> []  
    | x :: xs -> insert le x (go xs)  
  in go
```

Instead, we take a
comparison function as
a parameter.

Another Example: Sorting

```
let insert (le : 'a -> 'a -> bool) =  
  let rec go x l =  
    match l with  
    | [] -> [x]  
    | y :: ys ->  
      if le x y then  
        x :: y :: ys  
      else  
        y :: go x ys  
  in go
```

```
let rec sort (le : 'a -> 'a -> bool) =  
  let rec go l =  
    match l with  
    | [] -> []  
    | x :: xs -> insert le x (go xs)  
  in go
```

Instead, we take a
comparison function as
a parameter.

Another Example: Sorting

```
let insert (le : 'a -> 'a -> bool) =  
  let rec go x l =  
    match l with  
    | [] -> [x]  
    | y :: ys ->  
      if le x y then  
        x :: y :: ys  
      else  
        y :: go x ys  
  in go
```

```
let rec sort (le : 'a -> 'a -> bool) =  
  let rec go l =  
    match l with  
    | [] -> []  
    | x :: xs -> insert le x (go xs)  
  in go
```

Instead, we take a
comparison function as
a parameter.

Otherwise, the code is
pretty much identical.

Another Example: Sorting

```
let insert (le : 'a -> 'a -> bool) =  
  let rec go x l =  
    match l with  
    | [] -> [x]  
    | y :: ys ->  
      if le x y then  
        x :: y :: ys  
      else  
        y :: go x ys  
  in go
```

```
let rec sort (le : 'a -> 'a -> bool) =  
  let rec go l =  
    match l with  
    | [] -> []  
    | x :: xs -> insert le x (go xs)  
  in go
```

Instead, we take a
comparison function as
a parameter.

Otherwise, the code is
pretty much identical.

An Aside. Also note the
arguments. Why doesn't
sort take a list?

The Abstraction Principle

The Abstraction Principle

As noted in the text, the abstraction principle comes from MacLennan's ***Functional Programming: Theory and Practice.***

The Abstraction Principle

As noted in the text, the abstraction principle comes from MacLennan's ***Functional Programming: Theory and Practice***.

It's not a concrete principle. Roughly it says:

The Abstraction Principle

As noted in the text, the abstraction principle comes from MacLennan's ***Functional Programming: Theory and Practice***.

It's not a concrete principle. Roughly it says:

- Abstract out **core functionality**.

The Abstraction Principle

As noted in the text, the abstraction principle comes from MacLennan's ***Functional Programming: Theory and Practice***.

It's not a concrete principle. Roughly it says:

- Abstract out **core functionality**.
- Use higher-order functions to **parametrize** by functionality specific to the problem.

The Abstraction Principle

As noted in the text, the abstraction principle comes from MacLennan's ***Functional Programming: Theory and Practice***.

It's not a concrete principle. Roughly it says:

- Abstract out **core functionality**.
- Use higher-order functions to **parametrize** by functionality specific to the problem.
- (Try to understand the **algebra** of programming.)

Understanding Check

```
let rec next_word (cs : char list) =  
  match cs with  
  | [] -> []  
  | x :: xs ->  
    if (not (x = ' ')) then x :: next_word xs else []
```

```
let rec pos_prefix (l : int list) : int list =  
  match l with  
  | [] -> []  
  | x :: xs ->  
    if x > 0 then x :: pos_prefix xs else []
```

Write a function which factors out the core functionality of the above two functions.

Map

Simple Example: Update All Users

```
type user = {  
  name : string ;  
  id : int ;  
}
```

```
let capitalize = ...
```

```
let fix_usernames (us : user list) =  
  List.map (fun u -> { u with name = capitalize u.name }) us
```

map is used to apply a function to every element in a list (or other structure).

Definition of Map

```
let rec map f l =  
  match l with  
  | [] -> []  
  | x :: xs -> f x :: map f xs
```

Definition of Map

```
let rec map f l =  
  match l with  
  | [] -> []  
  | x :: xs -> f x :: map f xs
```

If the list is empty there is nothing to do.

Definition of Map

```
let rec map f l =  
  match l with  
  | [] -> []  
  | x :: xs -> f x :: map f xs
```

If the list is empty there is nothing to do.

If the list is nonempty, we apply f to its first element, and recurse.

Tail-Recursive Map

```
let rec map_t f l =  
  let rec go l acc =  
    match l with  
    | [] -> List.rev acc  
    | x :: xs -> go xs (f x :: acc)  
  in go l []
```

Tail-Recursive Map

```
let rec map_t f l =  
  let rec go l acc =  
    match l with  
    | [] -> List.rev acc  
    | x :: xs -> go xs (f x :: acc)  
  in go l []
```

For a tail-recursive version we can build the list in reverse in **acc** and then **reverse it at the end**.

Tail-Recursive Map

```
let rec map_t f l =  
  let rec go l acc =  
    match l with  
    | [] -> List.rev acc  
    | x :: xs -> go xs (f x :: acc)  
  in go l []
```

For a tail-recursive version we can build the list in reverse in **acc** and then **reverse it at the end**.

Tail-Recursive Map

```
let rec map_t f l =  
  let rec go l acc =  
    match l with  
    | [] -> List.rev acc  
    | x :: xs -> go xs (f x :: acc)  
  in go l []
```

For a tail-recursive version we can build the list in reverse in **acc** and then **reverse it at the end**.

This may seem inefficient, but its just a **constant factor** slower.

Tail-Recursive Map

```
let rec map_t f l =  
  let rec go l acc =  
    match l with  
    | [] -> List.rev acc  
    | x :: xs -> go xs (f x :: acc)  
  in go l []
```

For a tail-recursive version we can build the list in reverse in **acc** and then **reverse it at the end**.

This may seem inefficient, but its just a **constant factor** slower.

An Aside. The standard library map is *not* tail-recursive.

Additional Notes

Additional Notes

The text mentions two additional things about **map**:

Additional Notes

The text mentions two additional things about **map**:

1. There is a function **rev_map**, which is tail-recursive and does give the output in reverse order.

Additional Notes

The text mentions two additional things about **map**:

1. There is a function **rev_map**, which is tail-recursive and does give the output in reverse order.
2. **map** is defined somewhat differently to account for **side-effects**.

Additional Notes

The text mentions two additional things about **map**:

1. There is a function **rev_map**, which is tail-recursive and does give the output in reverse order.
2. **map** is defined somewhat differently to account for **side-effects**.

We won't dwell on these for now, but it may be worth reading about.

demo
(normalize.ml)

Understanding Check

*Using a single call to map, implement function **pointwise_max** which, given*

*$f : 'a \rightarrow int$
 $g : 'a \rightarrow int$
 $l : 'a\ list$*

returns l with f or g applied to each element, whichever gives a larger value.

Filter

Simple Example:

```
type user = {  
  name : string ;  
  id : int ;  
  num_likes : int ;  
}
```

```
let popular (us : user list) (cap : int) =  
  List.filter (fun u -> u.num_likes > cap) us
```

filter is used to grab all elements in a list which **satisfy a given property**.

Predicates

Predicates

A Boolean predicate on 'a is a function of type

`'a -> bool`

Predicates

A Boolean predicate on 'a is a function of type

`'a -> bool`

A predicate is a function which represents a
property.

Predicates

A Boolean predicate on 'a is a function of type

`'a -> bool`

A predicate is a function which represents a **property**.

Example. `let even n = n mod 2 = 0`

Definition of Filter

```
let rec filter p l =  
  match l with  
  | [] -> []  
  | x :: xs ->  
    (if p x then [x] else []) @ filter p xs
```

If the list is empty there is nothing to do.

If the first element satisfies our predicate we keep it and recurse.

Otherwise, we drop it and recurse.

Tail Recursive Filter

```
let filter_tail p =  
  let rec go acc l =  
    match l with  
    | [] -> List.rev acc  
    | x :: xs -> go ((if p x then [x] else []) @ acc) xs  
  in go []
```

Tail Recursive Filter

```
let filter_tail p =  
  let rec go acc l =  
    match l with  
    | [] -> List.rev acc  
    | x :: xs -> go ((if p x then [x] else []) @ acc) xs  
  in go []
```

As with map, we have to **reverse** the output before returning it.

Tail Recursive Filter

```
let filter_tail p =  
  let rec go acc l =  
    match l with  
    | [] -> List.rev acc  
    | x :: xs -> go ((if p x then [x] else []) @ acc) xs  
  in go []
```

As with map, we have to **reverse** the output before returning it.

The standard library implementation of **filter** *is* tail-recursive.

demo
(primes.ml)

Understanding Check

What do the following functions do?

```
let f = List.filter (fun i -> i mod 2 <> 0)
```

```
let g l = l |> List.map (fun x -> x * x) |> f
```

```
let h p q = List.filter (fun i -> p i && q i)
```


Summary

Higher-order function allow for better `abstraction` because we can parameterize functions by other functions.

`map` and `filter` are very common patterns which can be used to write clean and simple code.