

MOBILE DATA CHARGING:

NEW ATTACKS AND COUNTERMEASURES

Chunyi Peng,

Chi-Yu Li, Guan-Hua Tu, Songwu Lu, Lixia Zhang


University of California, Los Angeles

ACM CCS'12

Mobile Data Access


2

□ **1.2 billion** global users



Mobile Data Charging

3




Security:

Can any attack make the users pay **MORE/LESS?**


How Charging Works & Be Secured

4



Two Security Issues

5



#1: Can the attacker bypass the security mechanism to exploit the **Stealth-spam-attack** the users pay **MORE**?

#2: Can the **Toll-Free-Data-Access-Attack** **LESS**?

Threat Models

6

- Cellular network is **not compromised**
 - ▣ Charging subsystem works as designed
 - ▣ Security mechanism works as designed

- Attacker's capability
 - ▣ Only use **installed apps** @ mobile, or
 - ▣ Deploy malicious servers **outside cellular networks**

Outline

7

- Stealth-spam-attack (pay MORE)
 - Vulnerability
 - Attack design & implementation & damage
 - Countermeasures & insight

- Toll-free-data-access-attack (pay LESS)
 - Vulnerability
 - Attack design & implementation & damage
 - Countermeasures & insight


- Summary

8


Stealth-Spam-Attack

Security Against Spamming

9



Vulnerability



Stealth-Spam-Attack

11

- Step1-**Trap**: init data access
 - ▣ Example-1: click a malicious web link
 - ▣ Example-2: login Skype once / stay online

- Step2-**Spam**: keep spamming
 - ▣ No matter what status @mobile

Web-based Attack

12


- Implementation
 - ▣ Phone: click a malicious web link
 - ▣ Attacker (server): send spam data at constant rate (disable TCP congest control and tear-down)

- Result: charging keeps going
 - ▣ Even after the phone tears down TCP
 - TCP FIN, timeout
 - ▣ Even when many “TCP RESET” sent from the mobile

Damage vs. Spamming Rate

13

Charging volume vs. spamming rate



In proportion to spamming rate when rate is low


Charging blocked when rate is high ($> 1\text{Mbps}$)

The charged volume could be $>$ the received one [Mobicom'12]

Damage vs. Duration

14

Spamming rate = 150Kbps



No observed sign to end when the attack lasts **2 hours** if the rate is low (spamming > **120MB**)


Skype-based Attack

15

- Implementation
 - ▣ **Phone: do nothing (stay online once in Skype)**
 - ▣ **Attacker: Skype call the victim and hang up**
 - ▣ Attacker (server): send spam data at constant rate
- Exploit Skype “loophole”
 - ▣ allows data access from the host who attempts to call the victim before the attempt is accepted
- Demo

Demo: for a specific victim

- Result: charging keeps going
 - Even after **Skype logout**
 - Even when there is **no any skype call session**
 - Even when many “**ICMP unreachable**” sent from the mobile




Phone Type: GSM
Phone No.: [REDACTED]
Operator: [REDACTED]
Country: US

Damage vs. Spamming Rate


17

Charging volume vs. spamming rate

Operator-I



Operator-II




No bounds on spamming rate compared with TCP-based attack

Damage vs. Duration

18

Spamming rate = 50Kbps



No observed sign to end when the attack lasts **24 hours** (spamming > **500MB**)

Root Cause

19

Current system:
Secure only the initialization

IP forwarding can **push**
packets to the victim (**not**
controlled by the victim)

#1: Initial authentication \neq authentication all along

Current system:
Keep charging if data comes
Local view @ core gateway

Different views @ mobile:
data conn. ends or never starts
or exception happens
Lack of feedback/control

#2: Data flow termination @ the phone

\neq charging termination @ the operator

Countermeasures

20

- Spamming inevitable due to IP push model
- Remedy: **stop early** when spamming happens
 - ▣ **Detection** of unwanted traffic @mobile/operator
 - ▣ **Feedback** (esp. from the mobile to the operator)
 - At least allow users to stop data charging (no service)
 - Exploit/design mechanisms in cellular networks: *implicit-block, explicit-allow, explicit-stop*
 - ▣ Precaution, e.g., set a volume limit
 - Application: be aware of spamming attack


21

Toll-Free-Data-Access-Attack

Vulnerability

22

Both operators provide **free DNS** service



Real data over 53

#1: free fake DNS loophole

OP-I: Free via **port 53**
 DNS flow ID: (srcIP, destIP, srcPort, destPort, protocol) **UDP+Port 53**

#2: no volume-check loophole

~~OP-II: Packets via **UDP+Port 53** free~~
 Any enforcement for packets over port 53?

OP-I: **no observed limits**, except 29KB for one request packet

OP-II: **no observed limits**

Toll-Free-Data-Access-Attack

23

- Proxy outside cellular network
 - ▣ **Tunneling over 53** between the mobile and external network
 - ▣ similar to calling 800-hotline
- Implementation
 - ▣ HTTP-proxy on port 53 (only for web, OP-I)
 - ▣ Sock-proxy on port 53 (for more apps, OP-I)
 - ▣ DNS-tunneling on UDP-53 (all apps, OP-I, II)
- Results
 - ▣ Free data access > 200MB, no sign of limits
 - ▣ Demo if interested

Countermeasures

24

- Simplest fix: **stop free DNS service**
 - ▣ OP-II stopped it since this July

- Other suggestions
 - ▣ Authenticate DNS service
 - Only allow using authenticated DNS resolvers
 - DNS message integrity check
 - ▣ Provide free DNS quota

Beyond DNS

25

- Existing DNS tunneling tools: iodine etc,
 - ▣ Designed for data access when Internet access is blocked



differentiated-charging policy
e.g., free access to one website/ via some APN, or cheaper VoIP than Web

Incentive to pay less
(Attackers or even normal users)

Gap btw policy and its enforcement
Bullet-proof design & practice

On Incentive

26

- Toll-Free-Data-Access-Attack ✓

- Stealth-Spam-Attack
 - **Good news:** no obvious and strong incentive
 - No immediate gain for the attacker unless the ill-intentioned operator does it
 - Monetary loss against the attacker's adversary
 - **Unexpected incentive** in the future?

More information/demo in
<http://metro.cs.ucla.edu/projects.html>

27

- Assess the **vulnerability** of 3G/4G data charging system
- **Two** types of attacks,
 - ▣ **Toll-free-data-access-attack** (free > 200MB)
 - Enforcement of **differentiated-charging** policy
 - ▣ **Stealth-spam-attack** (overcharging > 500MB)
 - Rooted in charging architecture, security mechanism and IP model
 - ▣ **No observed volume limits**
- **Insight**
 - ▣ IP push model is not ready for metered-charging
 - ▣ Feedback or control needed during data charging
 - ▣ Differentiated-charging policy has to secure itself