Chapter 3
Transport Layer

Yaxiong Xie

Department of Computer Science and Engineering
University at Buffalo, SUNY



Computer Networking: A Top-Down Approach
8th edition
Jim Kurose, Keith Ross
Pearson, 2020

Adapted from the slides of the book's authors

Stop-and-wait operation



Stop-and-wait operation



Pipelined protocols operation

pipelining: sender allows multiple, “in-flight”, yet-to-be-acknowledged packets

- range of sequence numbers must be increased
- buffering at sender and/or receiver



(a) a stop-and-wait protocol in operation

Pipelining



How many packets shall we sent before receiving the ACK?



Sliding Window



sent and ACKed

Not yet sent

sent, not yet ACKed

Sliding Window





Sliding Window





Sliding Window





Sliding Window



- Timer for oldest in-flight packet
- *Timeout(n):* retransmit packet n and all higher seq # packets in window

Sliding Window + cumulative ACK



sent and ACKed

Not yet sent

sent, not yet ACKed

Sender

Receiver



received and ACKed

Not yet received

received, not yet ACKed

Sliding Window + cumulative ACK



Sliding Window + cumulative ACK

Sliding Window + cumulative ACK

- *cumulative ACK:* ACK(*n*): ACKs all packets up to, including seq # *n*
  - on receiving ACK(*n*): move window forward to begin at *n+1*

Sliding Window + cumulative ACK: out-of-order

Two Question:

1. do we need to send ACK when we receive an out-of-order packet? If yes, what kind of ACK?

Sliding Window + cumulative ACK: out-of-order



Two Question:

1. do we need to send ACK when we receive an out-of-order packet? If yes, what kind of ACK?
2. how shall we deal with the out-of-order packets we received?

Sliding Window + cumulative ACK: out-of-order



Two Question:

1. do we need to send ACK when we receive an out-of-order packet? If yes, what kind of ACK?
2. how shall we deal with the out-of-order packets we received?

Sliding Window + cumulative ACK: out-of-order



- ACK-only: always send ACK for correctly-received packet so far, with highest *in-order* seq #
  - may generate duplicate ACKs

Sliding Window + cumulative ACK: out-of-order



- on receipt of out-of-order packet:
  - can discard (don't buffer) or buffer: an implementation decision
  - re-ACK pkt with highest in-order seq #

Go-Back-N: sender

- sender: "window" of up to N, consecutive transmitted but unACKed pkts
  - k-bit seq # in pkt header



- *cumulative ACK:* ACK(*n*): ACKs all packets up to, including seq # *n*
  - on receiving ACK(*n*): move window forward to begin at *n+1*
- timer for oldest in-flight packet
- *timeout(n):* retransmit packet n and all higher seq # packets in window

Go-Back-N: receiver

- ACK-only: always send ACK for correctly-received packet so far, with highest *in-order* seq #
  - may generate duplicate ACKs
  - need only remember `rcv_base`
- on receipt of out-of-order packet:
  - can discard (don't buffer) or buffer: an implementation decision
  - re-ACK pkt with highest in-order seq #

Receiver view of sequence number space:





Go-Back-N in action



Sliding Window + selective repeat

Sliding Window + selective repeat



sent and ACKed

Not yet sent

sent, not yet ACKed

Sender

Receiver



received and ACKed

Not yet received

received, not yet ACKed

Sliding Window + selective repeat



Sliding Window + selective repeat



Sliding Window + selective repeat: out-of-order

Sliding Window + selective repeat: out-of-order

Sliding Window + selective repeat: out-of-order

- *receiver individually ACKs* all correctly received packets
  - buffers packets, as needed, for in-order delivery to upper layer

Sliding Window + selective repeat: out-of-order

- *receiver individually ACKs* all correctly received packets
  - buffers packets, as needed, for in-order delivery to upper layer

Sliding Window + selective repeat: out-of-order

- *receiver individually ACKs* all correctly received packets
  - buffers packets, as needed, for in-order delivery to upper layer

Sliding Window + selective repeat: out-of-order

- *receiver individually ACKs* all correctly received packets
  - buffers packets, as needed, for in-order delivery to upper layer

Sliding Window + selective repeat: out-of-order

- *receiver individually ACKs* all correctly received packets
  - buffers packets, as needed, for in-order delivery to upper layer

Sliding Window + selective repeat: out-of-order



- *receiver individually ACKs* all correctly received packets
  - buffers packets, as needed, for in-order delivery to upper layer

Sliding Window + selective repeat: out-of-order



- *receiver individually ACKs* all correctly received packets
  - buffers packets, as needed, for in-order delivery to upper layer

Sliding Window + selective repeat



- Maintains (conceptually) a timer for each unACKed pkt
  - timeout: retransmits single unACKed packet associated with timeout

Selective repeat: the approach

- *pipelining*: *multiple* packets in flight
- *receiver individually ACKs* all correctly received packets
  - buffers packets, as needed, for in-order delivery to upper layer
- sender:
  - maintains (conceptually) a timer for each unACKed pkt
    - timeout: retransmits single unACKed packet associated with timeout
  - maintains (conceptually) "window" over *N* consecutive seq #s
    - limits pipelined, "in flight" packets to be within this window

Selective repeat: sender, receiver windows



(a) sender view of sequence numbers

Selective repeat: sender and receiver

sender

data from above:

- if next available seq # in window, send packet

timeout(*n*):

- resend packet *n*, restart timer

ACK(*n*) in [sendbase,sendbase+N-1]:

- mark packet *n* as received
- if n smallest unACKed packet, advance window base to next unACKed seq #

receiver

packet *n* in [rcvbase, rcvbase+N-1]

- send ACK(*n*)
- out-of-order: buffer
- in-order: deliver (also deliver buffered, in-order packets), advance window to next not-yet-received packet

packet *n* in [rcvbase-N,rcvbase-1]

- ACK(*n*)

otherwise:

- ignore

Selective Repeat in action



Selective repeat: a dilemma!

example:

- seq #s: 0, 1, 2, 3 (base 4 counting)
- window size=3



(a) no problem



(b) oops!

Selective repeat: a dilemma!

example:

- seq #s: 0, 1, 2, 3 (base 4 counting)
- window size=3



Chapter 3: roadmap

- Transport-layer services
- Multiplexing and demultiplexing
- Connectionless transport: UDP
- Principles of reliable data transfer
- Connection-oriented transport: TCP
  - segment structure
  - reliable data transfer
  - flow control
  - connection management
- Principles of congestion control
- TCP congestion control

TCP: overview RFCs: 793,1122, 2018, 5681, 7323

- point-to-point:
  - one sender, one receiver
- reliable, in-order *byte steam:*
  - no “message boundaries"
- full duplex data:
  - bi-directional data flow in same connection
  - MSS: maximum segment size
- cumulative ACKs
- pipelining:
  - TCP congestion and flow control set window size
- connection-oriented:
  - handshaking (exchange of control messages) initializes sender, receiver state before data exchange
- flow controlled:
  - sender will not overwhelm receiver

TCP segment structure



ACK: seq # of next expected byte; A bit: this is an ACK

length (of TCP header)

Internet checksum

C, E: congestion notification

TCP options

RST, SYN, FIN: connection management

segment seq #: counting bytes of data into bytestream (not segments!)

flow control: # bytes receiver willing to accept

data sent by application into TCP socket

TCP sequence numbers, ACKs

Sequence numbers:

- byte stream "number" of first byte in segment's data

Acknowledgements:

- seq # of next byte expected from other side
- cumulative ACK

Q: how receiver handles out-of-order segments

- *A:* TCP spec doesn't say, - up to implementor



TCP sequence numbers, ACKs



simple telnet scenario

TCP round trip time, timeout

Q: how to set TCP timeout value?

- longer than RTT, but RTT varies!
- *too short:* premature timeout, unnecessary retransmissions
- *too long:* slow reaction to segment loss

Q: how to estimate RTT?

- `SampleRTT`: measured time from segment transmission until ACK receipt
  - ignore retransmissions
- `SampleRTT` will vary, want estimated RTT "smoother"
  - average several *recent* measurements, not just current `SampleRTT`

TCP round trip time, timeout

EstimatedRTT = (1- α)*EstimatedRTT + α*SampleRTT

- exponential weighted moving average (EWMA)
- influence of past sample decreases exponentially fast
- typical value: α = 0.125



TCP round trip time, timeout

- timeout interval: **EstimatedRTT** plus "safety margin"
  - large variation in **EstimatedRTT**: want a larger safety margin

```
TimeoutInterval = EstimatedRTT + 4*DevRTT
```

estimated RTT

"safety margin"

- **DevRTT**: EWMA of **SampleRTT** deviation from **EstimatedRTT**:

```
DevRTT = (1-β)*DevRTT + β*|SampleRTT-EstimatedRTT|
```

(typically, β = 0.25)

* Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive/

TCP Sender (simplified)

event: data received from application

- create segment with seq #
- seq # is byte-stream number of first data byte in segment
- start timer if not already running
  - think of timer as for oldest unACKed segment
  - expiration interval: **`TimeOutInterval`**

event: timeout

- retransmit segment that caused timeout
- restart timer

event: ACK received

- if ACK acknowledges previously unACKed segments
  - update what is known to be ACKed
  - start timer if there are still unACKed segments

TCP Receiver: ACK generation [RFC 5681]



TCP: retransmission scenarios



lost ACK scenario



premature timeout

TCP: retransmission scenarios



TCP fast retransmit

TCP fast retransmit

if sender receives 3 additional ACKs for same data ("triple duplicate ACKs"), resend unACKed segment with smallest seq #

- likely that unACKed segment lost, so don't wait for timeout

Receipt of three duplicate ACKs indicates 3 segments received after a missing segment – lost segment is likely. So retransmit!