JIANGSU CHANGJIANG ELECTRONICS TECHNOLOGY CO., LTD

SOP8 Plastic-Encapsulate MOSFETS

CJQ4407 P-Channel Power MOSFET

$V_{(BR)DSS}$	$R_{DS(on)}$MAX	I_D
-30 V	13mΩ@-10V	-12A
	17mΩ@-6V	

SOP8



DESCRIPTION

The CJQ4407 combines advanced trench MOSFET technology with a low resistance package to provide extremely low $R_{DS(ON)}$. This device is ideal for load switch and battery protection applications

APPLICATIONS

- Battery protection applications
- Load switch

MARKING

Front side

Q4407= Device code
Solid dot=Pin1 indicator
Solid dot = Green molding compound device, if none, the normal device
YY=Date Code

Equivalent Circuit



MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	±20	V
Continuous Drain Current	I_D	-12	A
Pulsed Drain Current	I_{DM}	-48	A
Single Pulsed Avalanche Energy	E_{AS}(1)	115	mJ
Power Dissipation	P_D	1.4	W
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	89	℃/W
Junction Temperature	T_J	150	℃
Storage Temperature Range	T_{stg}	-55 ~+150	℃
Lead Temperature for Soldering Purposes(1/8'' from case for 10s)	T_L	260	℃

(1).E_{AS} condition: V_{DD}=-50V,L=0.5mH, R_G=25Ω, Starting T_J = 25°C

MOSFET ELECTRICAL CHARACTERISTICS

T_a=25℃ unless otherwise specified

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Off characteristics						
Drain-source breakdown voltage	$V_{(BR)\,DSS}$	V_{GS} = 0V, I_D =-250μA	-30			V
Zero gate voltage drain current	I_{DSS}	V_{DS} =-30V, V_{GS} =0V			-1	μA
Gate-body leakage current	I_{GSS}	V_{DS} =0V, V_{GS} =±20V			±100	nA
On characteristics (note1)						
Gate-threshold voltage	$V_{GS(th)}$	V_{DS} =V_{GS}, I_D =-250μA	-1.0	-1.5	-2.2	V
Static drain-source on-sate resistance	$R_{DS(on)}$	V_{GS} =-10V, I_D =-12A		7.8	13	mΩ
		V_{GS} =-6V, I_D =-10A		9	17	mΩ
Forward transconductance	g_{Fs}	V_{DS} =-5V, I_D =-15A	25			S
Dynamic characteristics (note 2)						
Input capacitance	C_{iss}	V_{DS} =-15V,V_{GS} =0V, f =1MHz		2900		pF
Output capacitance	C_{oss}			410		
Reverse transfer capacitance	C_{rss}			280		
Switching characteristics (note 2)						
Total gate charge	Q_g	V_{DS}=-15V, V_{GS}=-10V, I_D=-10A		48		nC
Gate-source charge	Q_{gs}			12		
Gate-drain charge	Q_{gd}			14		
Turn-on delay time	$t_{d(on)}$	V_{DD}=-15V, V_{GS}=-10V,R_G=3Ω, R_L=1.25Ω		15		ns
Turn-on rise time	t_r			11		
Turn-off delay time	$t_{d(off)}$			44		
Turn-off fall time	t_f			21		
Gate Resistance	R_g	f =1MHz, V_{DS}=0V, V_{GS}=0V,			3.6	Ω
Drain-Source Diode Characteristics						
Drain-source diode forward voltage(note1)	V_{SD}	V_{GS} =0V, I_S=-2A			-1.2	V
Continuous drain-source diode forward current	I_S				-15	A
Pulsed drain-source diode forward current	I_{SM}				-60	A

Notes:

1. Pulse Test : Pulse Width≤300μs, duty cycle ≤2%.
2. Guaranteed by design, not subject to production testing.

Typical Characteristics

Output Characteristics



Transfer Characteristics



$R_{DS(ON)}$ —— I_D



$R_{DS(ON)}$ —— V_{GS}



I_S —— V_{SD}



Threshold Voltage



SOP8 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	**Max**	**Min**	**Max**
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.007	0.010
D	4.800	5.000	0.189	0.197
e	1.270 (BSC)		0.050 (BSC)	
E	5.800	6.200	0.228	0.244
E1	3.800	4.000	0.150	0.157
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°

SOP8 Suggested Pad Layout



Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.05mm.
3.The pad layout is for reference purposes only.

NOTICE

JCET reserve the right to make modifications,enhancements, improvements, corrections or other changes without further notice to any product herein.JCET does not assume any liability arising out of the application or use of any product described herein.

SOP8 Tape and Reel

SOP8 Embossed Carrier Tape



Packaging Description:

SOP8 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 2,500 units per 13" or 33cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

ALL DIM IN mm

Dimensions are in millimeter										
Pkg type	a	B	C	d	E	F	P0	P	P1	W
SOP8	6.40	5.40	2.10	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

SOP8 Tape Leader and Trailer



SOP8 Reel





Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
13"Dia	Ø330.00	100.00	13.00	R151.00	R56.00	R6.50	12.40	17.60

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
4,000 pcs	13 inch	8,000 pcs	360×360×65	64,000 pcs	565×380×390	