

SOT-89-3L PACKAGE OUTLINE DIMENSIONS $\mathbf{E}_{\mathbf{I}}$ b1 <u>b</u> D2


Symbol	Dimensions	In Millimeters	Dimensions In Inches			
	Min.	Max.	Min.	Max.		
Α	1.400	1.600	0.055	0.063		
b	0.320	0.520	0.013	0.020		
b1	0.400	0.580	0.016	0.023		
С	0.350	0.440	0.014	0.017		
D	4.400	4.600	0.173	0.181		
D1	1.550	REF.	0.061 REF.			
D2	1.750	REF.	0.069 REF.			
E	2.300	2.600	0.091	0.102		
E1	3.940	4.250	0.155	0.167		
E2	1.900	REF.	0.075 REF.			
е	1.500	TYP.	0.060 TYP.			
e1	3.000	TYP.	0.118 TYP.			
L	0.900	1.200	0.035	0.047		
θ	4:	5°	45°			





SOT-89-3L Tape and reel

SOT-89-3L Embossed Carrier Tape




Packaging Description:


SOT-89-3L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 1,000 units per 7" or 18.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	Α	В	С	d	E	F	P0	Р	P1	W
SOT-89-3L	4.85	4.45	1.85	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00
(Tolerance)	+/-0.1	+/-0.1	+/-0.1	+/-0.1	+/-0.1	+/-0.1	+/-0.1	+/-0.1	+/-0.1	+0.3/-0.1

SOT-89-3L Tape Leader and Trailer



SOT-89-3L Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	Н	1	W1	W2
7"Dia	Ø180.00	60.00	R32.00	R86.50	R30.00	Ø13.00	13.20	16.50
Tolerance	+/-2	+/-1	+/-1	+/-1	+/-1	+/-1	+/-1	+/-1

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
1000 pcs	7 inch	10,000 pcs	203×203×195	40,000 pcs	438×438×220	

