Data Architecture Reference

A measured reference for data architecture and state design

Edition 2 (draft)

Built from commit `run/05-cache-consistency/20261002T194046Z-2-g178c2dc` (`178c2dc57c5519a351ca2e4614e36117f6c7ef0d`) — working tree false.
Typst 0.15.1 (image `sha256:032e292249bcd378480cc7c142cfa324b63ef8aadeb88d7e7230320c4c9c422f`).
Evidence registry `book/evidence/v6/claims.json`, digest `6c5b2f80e98321c0c7cc90d4d6e42e8ebc91ef66ac6504bf4a732d0c5688e2db`.

Edition and provenance

This is a generated artefact: Typst source plus the evidence registry, compiled in a pinned Podman image. **Every claim in this book must resolve to a claim in the active registry**, and every number must trace back to something actually measured in a report this book cites. Nothing here is hand-entered at build time; the fields below are injected from the build script.

Source commit	`178c2dc57c5519a351ca2e4614e36117f6c7ef0d`
Source describe	`run/05-cache-consistency/20261002T194046Z-2-g178c2dc`
Working tree at build	false
Built at (UTC)	`2026-10-02T20:17:23Z`
Typst version	0.15.1
Typst image digest	`sha256:032e292249bcd378480cc7c142cfa324b63ef8aadeb88d7e7230320c4c9c422f`
Evidence registry	`book/evidence/v6/claims.json`
Evidence digest	`6c5b2f80e98321c0c7cc90d4d6e42e8ebc91ef66ac6504bf4a732d0c5688e2db`
Source tree hash	`fe2ebede62b658d8cbfd5ac49dc5c9f29cf7c9055a8ec5477e35a3d1b025dbce`

The book is assembled with Typst inside a pinned Podman image; the evidence index at the end is rendered from the registry file at build time.

Coverage gap

Environment and provenance limits travel with every number: all results come from one host (`host-zenbook-ux5406sa`) with shared cores and no real network between "cluster" nodes. Run tags mark the **producing code state**, not a tree containing the results. A reader reproducing a run must check out the run tag to get the code, then read the committed results directory.

1 How to read a number here

- Every **major-family** section follows the same progressive structure: quick choice, where it thrives and perishes, common scenarios, mechanism, costs, evidence and reproduction. Variant, scenario and concept chapters use the shape their role needs, because a case study and a reusable explanation are not the same thing.
- **Direct evidence** is measured in the cited run. **Mechanism evidence** demonstrates how something works without establishing a rate. **Analogy** is a labelled transfer to a family that was not measured. A **gap** callout is not one thing: each card names its own kind.
- The kinds of gap in use, read from the registry rather than restated here, because they close differently: **schema limitation** — the representation cannot answer the question, so no run would · **coverage gap** — the case simply has not been measured yet · **instrument gap** — the property could not be observed with the tools the study had · **unstable measurement** — the number moved between runs with no code change ·
- A claim can also be **partially superseded** — part of it has been replaced, the card names what moved to which successor, and the dimensions still open stay listed. A **retired** claim is no longer active and is not cited at all.
- Gaps are never null results: “not measured” must not be read as “would not change this”.
- No cross-study numeric ranking appears anywhere; no comparability record exists.

Contents

1 How to read a number here 3
2 How to choose 7
2.1 Step 0 — answerability before performance 9
2.2 Step 1 — place each fact once 10
2.3 Step 2 — name the contended surface 10
2.4 Step 3 — decide who maintains derived state 10
2.5 Step 4 — say how strong the evidence is 10
2.6 A worked decision 10
3 Major families 11
3.1 Normalized facts 11
3.2 Rolldown / duplicated data 14
3.3 Rollups / materialized aggregates 15
3.4 Embedded documents 17
3.5 Append-only history / snapshots 19
3.6 External read copies / caches 21
4 Minor variants 24
4.1 Measured controlled pairs 24
4.2 Named but not measured as controlled pairs 25
5 Cross-family comparisons 26
5.1 What a controlled pair looks like 26
5.2 Comparisons this book deliberately does not make 26
5.3 Direct evidence for the two family contrasts 26
5.4 What these six comparisons cannot decide 27
6 Topologies 28
6.1 What was measured 28
6.2 What topology does to a design 28
6.3 Open topology gaps 29
6.4 Boundaries 29
7 Scenarios 30
7.1 Ticket overbooking and refunds 30
7.2 Reserved seating and holds 32
7.3 Configuration portal 34
7.4 Donor portal with an external cache 34
7.5 Scenario transfers are labelled 35
7.6 Where a scenario stops 35
8 Evidence and reproduction 37
8.1 The provenance model 37
8.2 Reproducing the book itself 37
8.3 Reproducing a measured run 38
9 Part II — Concepts 39
10 Information placement 40
10.1 The ladder 40
10.2 Boundaries 41
10.3 The checklist 41
11 Indexes and hot rows 43
11.1 Indexes 43

11.2 Hot rows ... 43
11.3 Direct evidence ... 44
11.4 Boundaries ... 44
11.5 The checklist ... 44
12 Concurrency control ... 46
12.1 Optimistic (version-checked) ... 46
12.2 Pessimistic (lock-before-update) ... 46
12.3 The negative control matters here ... 47
12.4 Where the two designs cross ... 48
12.5 Boundaries ... 48
12.6 The checklist ... 49
13 Derived state and history ... 50
13.1 Maintenance is the design ... 50
13.2 History is answerability ... 51
13.3 Direct evidence ... 52
13.4 Boundaries ... 53
13.5 The checklist ... 53
14 Expiry and clock authority ... 54
14.1 What the corpus shows ... 54
14.2 What it cannot yet show ... 54
14.3 Boundaries ... 55
14.4 The checklist ... 55
15 Cache consistency ... 56
15.1 The flow: contract first, pattern last ... 56
15.2 The strict contract, written down ... 57
15.3 The named mechanisms, one primary failure mode each ... 58
15.4 What each mechanism is actually for ... 61
15.5 Freshness is a contract, not a speed knob ... 62
15.6 The gain, and what the gain leaves out ... 62
15.7 The failure mode, measured against the strict rule ... 63
15.8 Churn, engines and placement (2026-09-23) ... 64
15.9 What is still open ... 66
15.10 Boundaries ... 66
15.11 The checklist ... 66
16 Distributed placement ... 67
16.1 What the corpus measures ... 67
16.2 What it does not measure ... 67
16.3 Boundaries ... 68
16.4 The checklist ... 68
17 Reading benchmarks honestly ... 69
17.1 Six questions to ask of any number ... 69
17.2 Worked examples of a number that cannot be quoted ... 69
17.3 Before quoting a number ... 70
17.4 Boundaries ... 70
17.5 The checklist ... 70
18 Glossary ... 71
19 Evidence registry (active v6 claims) ... 74
19.1 normalized facts ... 74
19.2 rolldown / duplicated data ... 78
19.3 rollups / materialized aggregates ... 79

19.4 embedded documents 81
19.5 append-only history / snapshots 83
19.6 external read copies / caches 86
19.7 Retired predecessor claims 89

2 How to choose

CHAPTER · HOW TO CHOOSE

This chapter is the decision path. It front-loads the two questions that dominate every later trade-off: what must the schema be able to answer, and who arbitrates the contended row.




Figure 1: **The decision path, in the order the decisions bind.**

Form: decision tree · Evidence: conceptual illustration

Text equivalent. What must the schema answer — after an undo, a cancellation or a correction? If the current representation cannot answer it, change the representation before the speed. If a row is contended, arbitrate it: a conditional update, a lock plus an invariant recheck, or pre-created rows. If it is not, leave the row canonical and index the question. Name the maintainer of any derived read. State the evidence level and the gap before quoting a number. The figure orders the chapters' recommendations and asserts no measured value of its own.

2.1 Step 0 — answerability before performance

Direct evidence

Write down the questions the data must answer **after** an undo, a cancellation or a correction. Two measured answerability failures make this a rule rather than a preference: refunds were unanswerable in 14 of 15 ticketing designs, and no reserved-seating design could size a hold window because an expired hold is erased.

v2-07-refund-answerability-and-storage

append-only history / snapshots · run_replicated

A ticketing database chosen only to prevent overbooking cannot report refunds at all: in 14 of 15 designs the refunds report (r05) is unanswerable and the sales/revenue (r01) and last-purchase (r03) reports are wrong across a refund, reproduced in two whole runs in both design orders on PostgreSQL at scale small, with the append-only ledger (X1 CAS+ledger) the only design that answers r05. The ledger's storage cost depends on which relations are counted and moves about a percentage point between runs: about 33–35% more than P3 by table size (33.4% and 34.8% in the two runs, 35.2% in the primary), about 35–36% counting every relation (35.0% and 35.9% in the two runs, 36.2% in the primary), and 37.4–37.9% by index size alone.

Trials: 5 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: answerability is a schema fact, not a timing; the +33–35% storage delta is a relation-size difference measured in the primary run and deterministic for the same dataset and design; it is not a repeated timed result; the P3 -> X1 read rows of this run are excluded, because the difference belongs to the configuration as a whole rather than to one decision inside it; the read phase of this claim's primary anchor 20260920T234953Z was client-CPU throttled by a design-dependent amount (2.3 s for p2_precreated_skip_locked to 58.1 s for r1_inventory_row, out of about 1085 CFS periods), so that report's read figures are not quotable: the hazard reproduces on the current harness (20260929T165533Z, 20260929T170353Z: r1_inventory_row 32.3 s of ~63 s of periods, both orders), and the 2026–09–30 budget calibration shows the client's quota is a symptom rather than the ceiling - the read level on this machine is set by the database's share of four CPUs, and adding a client core removes the client's throttling while making the reads slower. Answerability and the r05 storage/speed result are unaffected: the ledger still answers r05 at 30.3k and 33.0k ops/s against the primary's 32.2k, and at the new 2-worker read footprint the r05 result reproduces independently at 32,164 ops/s (20260930T164028Z), so that number has a footprint-2 footing; all fifteen designs now have one (the eleven-design tranche 20260930T201732Z/20260930T203913Z adds the rest, unthrottled), while this claim's primary anchor's own footprint-8 read figures remain not quotable (design-dependent inflation, 1.09x to 2.22x). **Correction, 2026–09–30: an earlier caveat here said the two many-row queries (q02_band_events, q05_band_tickets_sold) had client-bound levels; it is withdrawn.** A one-worker tranche (20260930T232926Z, 20260930T233744Z) shows that in-flight measured with the **mean** latency is exactly 1.000 in all 72 cells at one worker and 2.00 at two, so every read cell in the family is a store measurement at a stated footprint, and only its magnitude depends on the concurrency. Two errors produced the withdrawn caveat: q05 does not return 28 rows (all three variants return one - COUNT/SUM with no GROUP BY), and in-flight computed from the **median** understates the concurrency by the latency skew (mean/p50 up to 2.7x), which reads exactly like a worker idling between fetches. The primary anchor's **PostgreSQL read cells have since been re-stated** on the footprint-2 footing (analysis 20261001T-read-cells-restated: all fifteen designs, both orders, every cell store-bound at 2.00 operations in flight), so its `pg-single` read figures may be replaced rather than caveated. All fifteen designs have since been measured in a **single run**, twice and in reversed order (20261001T100948Z, 20261001T103931Z): 0 throttled periods in all 30 read phases and every one of the 270 cells store-bound at 2.00 operations in flight by the mean latency, so the family's levels are jointly comparable within that session. Two consequences for quoting: the top group (h0, h1, r1, r2, p4) differs by 4%, inside that session's own order term, so its internal ranking is not quotable - only the 1.5x gap between that group and the per-seat group is; and c1_count_naive carries a 40% position term (first of one order against last of the other), so its q01 level should not be quoted from these runs. Its two **YugabyteDB read arms have no replacement** and remain an explicit coverage gap; the storage percentage depends on the rule and on the page layout, and must not be quoted as one number: tables only 33.4–35.2%, every relation 35.0–36.2%, indexes alone 37.7%; the same pair's relation sizes moved 0.26% (p3) and 0.41% (x1) between two runs 29 minutes apart, so the delta moved 0.9 percentage points; the index-only figure spans 37.4–37.9% across the five runs, so even there the rule is a band and not a point, and the 2026–10–02 replication's M4 (reproducible within 1%) is falsified by that movement - a tighter figure would need a vacuumed comparison, which is a different measurement; the answerability statuses are the harness's own audit of its own schema, computed as a pure function of the design and emitted inside the read phase; the 2026–10–02 replication therefore tests reproducibility across two whole runs and not the independence of the audit's rule, and it re-measured no timing

Source: studies/02-ticket-booking/reports/20260920T234953Z.md · run 20260920T234953Z · tag run/02-ticket-booking/20260920T234953Z

v2-gap-02-hold-funnel-unanswerable

append-only history / snapshots · gap · schema limitation

No Study 03 design can answer the hold funnel report that would size the 40-minute hold window: releasing an expired hold clears the row, so an expired hold is indistinguishable from a seat never held.

Trials: 0 whole-run replications · 0 fresh-load trials per cell · 0 inner iterations

Limits: a schema limitation, not a missing measurement

Source: studies/03-reserved-seating/reports/20260921T231328Z.md · run 20260921T231328Z · tag run/03-reserved-seating/20260921T231328Z

If a required question is unanswerable, no index or cache fixes it. Choose a family that can answer it — usually append-only history — and accept its maintenance cost.

2.2 Step 1 — place each fact once

Walk the derive → index → materialize → copy/cache ladder (see the **information placement** concept) for each question. Prefer the lowest rung that meets the requirement, because each rung up adds maintenance, storage or a consistency contract.

2.3 Step 2 — name the contended surface

Find the rows many writers touch at once. If there is one, choose an arbitration strategy explicitly: pre-created units with compare-and-set, `SKIP LOCKED`, or a version-checked update. The counter-row design was 4–8x slower than pre-created seats and blocked unrelated edits.

2.4 Step 3 — decide who maintains derived state

For every rollup or copy, name the maintainer and the failure it must never have. A trigger makes the guarantee structural. Application maintenance kept writes near the reference in the measured configuration-portal workload, and its obligation is stated against where the derived state lives: when the base fact and the rollup are in the same database, update both in one transaction; when they cannot share one atomic transaction, name the delivery, idempotency and reconciliation mechanism that keeps the derived state recoverable. Only the second case is **publication**, because only there does a copy escape the transaction that wrote the original — leaving a moment when a reader can see the new value while the copy is still old. The measured trigger cost was 4.0–5.7x on whole-configuration replacement across three runs (median 4.94x) — a range rather than a single figure, because repeating the measurement inside that configuration gave results that disagreed with each other by more than we would like.

2.5 Step 4 — say how strong the evidence is

Every recommendation states how well it is supported, what it could not separate, and what has not been measured. A recommendation that does not say what is missing claims more than the evidence allows.

2.6 A worked decision

- A ticketing system must never oversell and must report refunds → append-only ledger plus a pre-created-seat arbiter, +33–38% storage — about 35% by table size, 38% counting indexes too.
- A configuration portal reads its overview far more than it writes → application-maintained rollup; a trigger only if a forgotten write is unacceptable.
- A public donor portal serves warm profiles → cache with a named contract and a publication fence against the stale-fill race (a reader republishing S0 after a writer commits S1 and invalidates), accepting that the cache's budget is outside the `db-only` comparison.

3 Major families

CHAPTER · MAJOR FAMILIES

A family is a way of deciding where a fact lives. The six here are fixed by the goal; each major-family section follows the same progressive structure, and the mechanism chapters carry the reusable explanations. Every cost below is a measured claim, labelled **direct** when it comes from the cited run or **analogy** when it is a transfer.




Figure 2: **Normalized, rolldown and rollup on one parent-and-child relation.**

Form: structure · Evidence: conceptual illustration

> **Text equivalent.** Three panels over one donor-to-many-donations relation. **Normalized** keeps every fact once: `display_name` lives only on `Donor`, so a query that needs a donation with its donor name follows the relation. **Rolldown** copies the parent value down onto the child (`donation.donor_display_name`), so the join disappears and a parent change fans out to every child row. **Rollup** aggregates child facts up onto the parent (`donor.lifetime_total`), so parent reads are local and every contributing child change must maintain the aggregate. The figure maps families 1–3 and carries no measured value.

3.1 Normalized facts

3.1.1 Quick choice in plain language

Keep each fact in one place and let queries assemble the answer. Choose it unless a measured question says otherwise.

3.1.2 Where it thrives and where it perishes

Thrives when questions are answerable from the rows themselves and writes are spread across many parents. Perishes on a hot row, or when the required question was never modelled.

3.1.3 Common scenarios

Order lines, ticket sales, configuration entries — the canonical transactional facts. Normalization decides **where those facts live**; it does not by itself prevent overbooking or double-selling, which needs a declared constraint plus a concurrency strategy that acts on it.

3.1.4 Mechanism

See the **indexes and hot rows** concept and the **concurrency control** concept. Indexes answer expressible questions; arbitration answers contended rows.

3.1.5 Costs

Reads pay per query; writes are cheap **in the measured cells of this corpus**, not as a law; storage is the baseline; correctness depends on the constraint you actually declared; operations are ordinary.

3.1.6 Direct evidence

v2-01-normalized-index-first

normalized facts · run_replicated

In the charity -> person -> donation tree, the first large read win is the query index: D2 indexed scores about 10–11x D1 minimal's read score in two whole runs (13.3x in the first), and flattening the foreign key instead (D3 flat+FK) reaches about 14–16x (20.5x in the first). The orderings and the bands replicated in both design orders; the point figures were single-run levels.

Trials: 3 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Confounds: conf-01-study01-d2d3-copied-key-package

Limits: PostgreSQL 1 node and YugabyteDB 1/3 nodes in one run; small scale; a single measurement per configuration, not a repeat; read score is a blended measure, not one query; the quoted point figures (13.3x, 20.5x) are the primary run's single levels: the whole-run replication of 2026–10–01 measured 9.7–15.5x for the same two relations while the absolute read scores moved 40–45% between its two runs, so the band and the ordering are what may be quoted, not the points

Source: studies/01-charity-tree/reports/20260912-small.md · run 20260912-small · tag none (legacy)

v2-06-hot-drop-designs

normalized facts · run_replicated

For a hot drop, pre-created seats taken by compare-and-set or SKIP LOCKED (P3 CAS, P2 skip-locked) sell 4–8x faster than any single counter row, but only with retry backoff in mind, and a counter on the event row also blocks unrelated edits to it. Both deliberately wrong controls fired in the same run. Two replications thirteen days later, on the same topology and with the design order reversed between them (AB/BA), reproduced the range - P3 at 4.30–7.06x and 4.64–6.99x, P2 at 3.25–5.25x and 5.78–8.71x against the two counters - while every absolute throughput fell 26–72% below the original run. The range is therefore the claim and the absolute numbers are one session's readings.

Trials: 3 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Limits: one run of the experiment, a single measurement per configuration; the run has 42 cells of which 2 failed (C2 count (SER) on the two YugabyteDB topologies); those cells are not evidence; hot-drop workload only; every absolute throughput in the 2026–09–26 replication was 26–72% below the 2026–09–13 run for the same design and tier, so the 4–8x range reproduced while the numbers behind it did not; the range is quotable and the figures are not; the ratio moved between runs: p3 against c4 went 7.07 to 4.37 to 4.64 at 100 seats and 7.26 to 4.30 to 4.70 at 1000, and p2 against c4 went 3.97 to 3.25 to 5.78, so the range is a range, not a point, and individual ratios shift by up to 44%; the replication re-ran neither deliberately wrong control (c1_count_naive, h0_hold_naive_confirm), so it strengthens the comparison without re-firing the correctness control that the first run provided; r1_inventory_row recorded one trial of about 4x lower throughput than its siblings at each tier (122 and 117 against 468–653); whether that is a real instability or a harness artefact is unresolved, and r1 is the weakest comparison in the replication; two of the original sweep's five tiers (10 and 10000 seats) were not re-measured; p2_precreated_skip_locked moved 58–76% between the two same-day replications while the counters moved within 15% and p3 within 7%; it ran first in one and last in the other, so that design carries a position or warm-up effect as large as the comparison it takes part in, and the claim's pairing of p2 with p3 hides it - the >=3x result holds at both extremes; the anomalous r1_inventory_row trials of the first replication (122 and 117 against 468–653) did not recur in the reverse-order run, which makes a harness artefact likelier than a design property without settling it; the read phase of this claim's primary anchor 20260913T021206Z was client-CPU throttled by a design-dependent amount (0.2 s for p2_precreated_skip_locked to 29.5 s for h0_hold_naive_confirm, out of 633 CFS periods), so that report's read figures are not quotable. The hazard reproduces on the current harness (20260929T165533Z, 20260929T170353Z: r1_inventory_row loses 420 of 634 and 422 of 633 periods), and the 2026–09–30 budget calibration (20260930T000544Z, 20260930T000759Z, 20260930T001013Z) shows the client's quota is a symptom rather than the ceiling: at three client cores the client is not throttled at all and the reads are slower (52,884 -> 43,726 ops/s at 10 seats), because the third core comes out of the database's share of the machine's four CPUs (database throttled periods 238 -> 847 -> 1052). The claim's own basis is the race phase (sell rate), where one cell in fourteen designs shows throttling. The read family has since been re-measured at the study's new 2-worker read footprint (20260930T164028Z, 20260930T164834Z: four designs, client unthrottled at 0 of ~631 periods, every cell latency-bound at 2.00 operations in flight for 2 workers (with the mean latency; a median-based count reads 1.9)), so read levels are quotable only with the footprint attached. All fifteen designs now have a footprint-2 footing (the four-design tranche plus the eleven-design tranche 20260930T201732Z/20260930T203913Z, where no design throttles: 0 of ~631 periods in all 22 read phases), and this claim's primary anchor's own footprint-8 read figures remain not quotable: the inflation they carry is design-dependent, 1.09x to 2.22x, and it tracks how many periods the old client lost per design rather than anything about the designs. All fifteen designs have since been measured in a **single run**, twice and in reversed order (20261001T100948Z, 20261001T103931Z): 0 throttled periods in all 30 read phases and every one of the 270 cells store-bound at 2.00 operations in flight by the mean latency, so the family's levels are jointly comparable within that session. Two consequences for quoting: the top group (h0, h1, r1, r2, p4) differs by 4%, inside that session's own order term, so its internal ranking is not quotable - only the 1.5x gap between that group and the per-seat group is; and c1_count_naive carries a 40% position term (first of one order against last of the other), so its q01 level should not be quoted from these runs.

Source: studies/02-ticket-booking/reports/20260913T021206Z.md · run 20260913T021206Z · tag run/02-ticket-booking/20260913T021206Z

v2-12-lock-vs-version-upper-bound

normalized facts · run_replicated

Under one hot key at 16 writers a lock-before-update (c2_pessimistic_lock) delivered about 1.6–1.8x the throughput of a version check (c1_optimistic_version): 1.76x in the primary run and 1.56x, 1.57x, 1.64x and 1.69x in four whole runs on 2026–10–02 that crossed the two design orders with the retry budget at its default and at zero. The retry budget does not explain the advantage - at a matched design order removing it moves the ratio by 1.1% to 3.2% - so the earlier wording calling the figure an upper bound because of per-retry harness work is retired by its own control. An unchecked read-modify-write (x1_lost_update_control) lost 93.7% of acknowledged updates in the primary run and 93.7% and 93.9% in the replications, while both correct designs lost none.

Trials: 5 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: one key, one installed product, 16 writers; PostgreSQL single node, small scale; one fresh-load trial per run; five whole runs now support the ratio, but no run repeats the cell, and the -retries 1 setting was not among the controls (the budget controls used the default 8 against -retries 0); 1.76x is one point on a writer curve, not a curve; the upper-bound hedge is retired: the retry budget was re-run on 2026–10–02 at 16 writers in both design orders, default against -retries 0 (1.64x against 1.69x with the lock first, 1.57x against 1.56x with the version check first), a 1.1% to 3.2% difference, which agrees with the primary's own retry control (1.60x against 1.61x) and means the advantage is not per-retry harness work; the re-scoped figure is a band of five whole runs on two days (1.56x, 1.57x, 1.64x, 1.69x, 1.76x); absolute throughput is day-specific, so only the within-run ratio travels

Source: studies/04-configuration-portal/reports/20260921T1215Z-small.md · run 20260921T1215Z-small · tag run/04-configuration-portal/20260921T1215Z-small

3.1.7 Boundaries and reproduction

Every ratio on this page comes from one run of the experiment, on one machine, so read each as a direction rather than a stable number. Reproduce it from the run tags in the cards, and check the note on the card for any part of that run that failed or was invalid before quoting a percentage.

3.2 Rolldown / duplicated data

3.2.1 Quick choice in plain language

Copy a parent value onto the child to remove a join. Do it when the copied value is small, stable enough, and the join is on the hot path.

3.2.2 Where it thrives and where it perishes

Thrives on read-heavy workloads with a bounded parent set. Perishes when the copied value changes often, because every change becomes a fan-out write.

3.2.3 Common scenarios

A donation row carrying its donor’s display name; an order line carrying its product’s category.

3.2.4 Mechanism

See the **information placement** concept. The measured pair is a package — the copied key plus its SQL and indexes — so attribute the gain to the package, not to the column alone.

3.2.5 Costs

Reads improve; writes gain an index and a copy to maintain; storage grows; correctness needs a rule for the stale copy; operations must backfill after a schema change.

3.2.6 Direct evidence

v2-05-d3-read-advantage-repeated

rolldown / duplicated data · run_replicated

D3's (d3_flattened_fk) read advantage over the normalized indexed design survives five fresh loads in one session and reproduces across two whole runs in reversed order, at 1.59x, 1.72x, 1.64x and 1.84x in its four further fresh loads against the primary's 2.47x; the recency SQL and actual heap avoidance explain the gain, while its insert cost remains imprecise.

Trials: 3 whole-run replications · 5 fresh-load trials per cell · 1 inner iteration

Limits: five fresh loads per configuration, all in one session; the insert-cost estimate is imprecise and must not be quoted as a ratio; the magnitude came down on replication: 1.59–1.84x against the primary's 2.47x, so the direction and the survival are what a reader should carry, and the ratio itself is a band that a future run could move again

Source: studies/01-charity-tree/reports/20260913T125342Z-v3.md · run 20260913T125342Z-v3 · tag run/01-charity-tree/20260913T125342Z-v3

3.2.7 Boundaries and reproduction

One family contrast is not a general law. The copied-key comparison changes more than the copied key, so it cannot be attributed to that decision on its own (`conf-01`), and where the cluster physically put the data was never verified (`v4-gap-01`).

3.3 Rollups / materialized aggregates

3.3.1 Quick choice in plain language

Store the total on the parent. Use it when an aggregate is read far more often than its children change, and be explicit about who maintains it.

3.3.2 Where it thrives and where it perishes

Thrives on dashboards and parent-level reads. Perishes when child writes dominate, or when a write path can forget the rollup.

3.3.3 Common scenarios

Donor lifetime totals, event ticket counts, a configuration portal's overview.

3.3.4 Mechanism

See the **derived state and history** concept. Trigger-maintained is a structural guarantee at a write cost. An application-maintained rollup is transactional first: where the base fact and the rollup share a database, update both in one transaction. Where they cannot share the authoritative transaction, the copy crosses that boundary and becomes **publication** — name the delivery, idempotency and reconciliation that keep it recoverable. In the measured configuration-portal workload application maintenance kept writes near the reference; that is a scope, not a law.

3.3.5 Costs

Reads win big; writes pay maintenance; storage grows modestly; correctness is the whole game; operations must rebuild the rollup after a bulk load.

3.3.6 Direct evidence

v2-02-rollup-family

rollups / materialized aggregates · run_replicated

Parent rollups win the aggregate read score - D4 rollup/trg about 61–85x and D5 rollup/app about 64–83x D1 minimal in two whole runs (73.8x and 69.9x in the first) - and pay for it on inserts: about a third to two-fifths of D1's insert rate in the same two runs (2.6k/s and 2.1k/s against 6.2k/s in the first).

Trials: 3 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: one run of the experiment, a single measurement per configuration; PostgreSQL 1 node numbers shown; YugabyteDB in the same report; the write cost is per-insert on a fresh load; the quoted rates (2.6k/s, 2.1k/s, 6.2k/s) are the primary run's levels: the 2026–10–01 replication measured D1 inserting at 6.1k/s and 4.9k/s with D4/D5 at 0.29–0.37x of it, so the read band and the write penalty ratio reproduce while the absolute rates do not

Source: studies/01-charity-tree/reports/20260912-small.md · run 20260912-small · tag none (legacy)

v2-13-trigger-rollup-cost

rollups / materialized aggregates · run_replicated

Maintaining the portal overview with a per-row trigger (n3_rollup_trigger) costs 4.0–5.7x the application-maintained rollup (n4_rollup_app) on whole-configuration replacement across three runs in randomized order (median 4.94x: n4 518–635 ops/s against n3 91–159 ops/s), and the trigger's slowest 1% is 22–46x worse (p99 61–109 ms against 2.2–2.7 ms); repeating the measurement inside the trigger's own configuration disagreed by 35–115%, so this is a range rather than one number, and the 6.85x quoted earlier from a single run did not reproduce.

Trials: 3 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Limits: PostgreSQL single node, small scale; three whole runs, each with three repeats of the measurement per configuration; the experiment was repeated as separate whole runs on one machine, so it is not independent of this hardware and is still exposed to this host's measurement hazards; repeating the measurement in that configuration disagreed by 35–115% across the three runs, more than the ~20% this project allows, so only the direction and an order of magnitude are supported, not a single ratio; the ~15x read gain belongs to the earlier single run and was not re-measured in the replication; the 6.85x figure from the earlier one-off run did not reproduce and must not be quoted; the trigger's product is a structural guarantee, not speed; the three runs realized only two distinct design orders (seeds 202 and 303 coincided, and in the sibling read tranche all three seeds coincided); randomized order describes the method, and the realized order is recorded in each manifest; the penalty is size-dependent, not a constant: crossing the same pair with entries per installed product gives 2.07x at 10 entries, 4.38x at 60 and 24.20x at 240, so this ratio holds at the small scale default of 60 entries and must not be quoted as a property of the design without the size (v2–18-maintenance-size-interaction)

Source: studies/04-configuration-portal/reports/20260925T190831Z.md · run 20260925T190831Z · tag run/04-configuration-portal/20260925T190831Z

v2-04-recency-maintained-index

rollups / materialized aggregates · run_replicated

The recency flag works, but an index on the rollup column answers the window questions faster, and by how much depends on the question: across two whole runs on PostgreSQL (d20_recency_flag against d22_recency_rollup_idx) the index is 1.9–2.3x on q13 (the primary's quoted 2.9x is this query in its trailing regime), 2.6–3.1x on q15 trailing, level on q14 (0.98–1.24x) and slightly slower on q16 (0.85–0.94x), so the group-wide ratio is about 1.4x. The YugabyteDB half (quoted 7.9x) is unreplicated.

Trials: 3 whole-run replications · 2 fresh-load trials per cell · 1 inner iteration

Confounds: conf-02-study01-d20d22-write-axis

Limits: we cannot say how much of d22's write cost comes from the index, because d22 also maintains D4's multi-column rollup: the two designs differ by more than the index; three repeats of the measurement per configuration; claim-02's v1 trials field was recorded as 1 and is corrected here; the quoted 2.9x and 7.9x are single-query, single-engine figures (q13 trailing): the recency group geomean is about 1.4x here and 1.52x recomputed from the primary, and on q16 the flag is marginally FASTER than the index in both runs - quote the query, not one headline

Source: studies/01-charity-tree/reports/20260916T090036Z-v3.md · run 20260916T090036Z-v3 · tag run/01-charity-tree/20260916T090036Z-v3

3.3.7 Boundaries and reproduction

We can trust the read comparison, but not the write comparison. The design with the recency index also performs the rollup maintenance, so the experiment cannot tell us how much of the write cost comes from the index itself. In experimental terms, this write comparison is confounded (`conf-02`).




Figure 3: **Rolldown fans a parent change out; rollup aggregates a child change up.**

Form: structure · Evidence: conceptual illustration

> **Text equivalent.** The two directions are opposites. **Rolldown** copies parent information down, so a Donor value that changes must be refreshed on Donation A, B and C — a fan-out write. **Rollup** aggregates child facts up, so an insert or update on `Donation` maintains one `Donor.lifetime_total` — a single parent write per contributing child change. The read gain and the maintenance cost point in opposite directions, and the figure asserts no rate.

3.4 Embedded documents

3.4.1 Quick choice in plain language

Put the children inside the parent when they are read together and bounded in size. It is a read-locality choice, not a database-family choice.

3.4.2 Where it thrives and where it perishes

Thrives when a bounded child set is always read with its parent. Perishes when children are queried independently or grow without bound.

3.4.3 Common scenarios

A reservation's seat map, a configuration file rendered whole.

3.4.4 Mechanism

See the **information placement** concept. A section document answered a 100k-seat map 4.5–11x faster than per-seat rows on YugabyteDB; a sharded variant collapsed point lookups to 26 ops/s.




Figure 4: **Normalized child rows beside a bounded child collection inside the parent.**

Form: structure · Evidence: conceptual illustration

> **Text equivalent.** Left, normalized child rows: the parent and its children are independent rows, so the whole aggregate and each single child are both addressable, at the cost of a join or an aggregate read. Right, the same bounded collection stored inside the parent row: reading the whole aggregate is local to one row, while querying or updating one independent child is less convenient and an unbounded collection is dangerous. The figure contrasts the placements and asserts no rate.

3.4.5 Costs

Reads of the whole child set improve; point access to one child can get much worse; storage is similar; correctness needs a bounded-growth rule; operations can be awkward for partial updates.

3.4.6 Direct evidence

v2-03-embedding-not-ahead

embedded documents · run_replicated

Embedding the donation child in the donor row (D6 embedded) never came out ahead of the normalized designs on reads: about 1.7–2.2x D1 minimal's read score in two whole runs (2.4x in the first), below both indexed designs, with about 0.57–0.60x D1's insert rate (0.57x in the first).

Trials: 3 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: one run, one trial; embedding here means a JSON/array child column, not a native document database; the band moved down on replication (1.7–2.2x against the quoted 2.4x) while staying below both indexed designs, so the finding is the ordering and the sub-multiple, not the 2.4x

Source: studies/01-charity-tree/reports/20260912-small.md · run 20260912-small · tag none (legacy)

v2-11-section-seat-map

embedded documents · run_replicated

On YugabyteDB the section document (L2 document) answers the 100k-seat map 4.5–11x faster than per-seat rows, while the section-sharded variant (L3 sharded) collapses point lookups to 26 ops/s; PostgreSQL shows no attributable difference. This is a family/package comparison, not a one-decision pair. The engine contrast now has a replication on both halves: the same pair of designs measures 24.4x and 27.8x on yb-single and 0.83x on pg-single, so the substitution is worth about 25x on one engine and nothing on the other.

Trials: 5 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Confounds: conf-03-study03-layout-family-package

Limits: one read-only run, one trial, 5 s per measurement; quota-bound nodes; read-only phases; no control could fire; a difference below ~1.8x cannot be attributed to the design rather than to run-to-run scatter; a replication on yb-single on 2026–09–26, three repeats per cell, reproduced the direction strongly: l2_section_document read the 100k-seat map at 1138 ops/s against l1_claim_rows at 41, a 27.8x multiple against the 20.8x of 2026–09–21, while both absolute figures fell far below the original (l1 by 72 percent, l2 by 63 percent), so the multiple is the claim and the figures are one session's readings; l3_section_sharded has failed its load in all three passes, in three different positions and under two memory envelopes, and with two different symptoms (connections terminated mid-COPY with SQLSTATE 57P01, then connect: connection refused). The sharded collapse therefore cannot be tested on this host with this harness - which is different from having tested it and found nothing; the pair has since been measured in both orders: l1 then l2 gave a 27.8x multiple and l2 then l1 gave 24.4x, a 12 percent difference, so the claim's direction does not depend on which design runs first; the pass that supplied the reversal ran with the database container at 5 GB and the YugabyteDB memory limit at 3 GiB rather than 3 GB and 1.5 GiB, because the earlier passes lost cells to the out-of-memory killer; its absolute figures are therefore not comparable with the 3 GB runs, and only the ratio between the two designs inside a run is; the load failures are memory pressure rather than design behaviour: the database log records server processes terminated by signal 9 (killed), 122 such lines in one cell, on a host with 15 GB of memory - so the sharded half of this claim and its PostgreSQL half are blocked here by host capacity, and a lost cell of this kind never reached the correctness gate rather than failing it; the two passes that supply the AB/BA pair also differ in memory envelope, so the 12 percent agreement may hide an order effect and a memory effect that cancel; a pass at 5 GB in the first pass's order would separate them; the PostgreSQL half was replicated on 2026–09–27 and shows no attributable difference (l2_section_document 6565 ops/s against l1_claim_rows 7873 on the 100k-seat map, a 0.83x multiple), so the finding is the engine contrast - about 25x on YugabyteDB against none on PostgreSQL - rather than the design being faster in general; that PostgreSQL measurement is a single run in a single design order, unlike the YugabyteDB pair which has the AB/BA control; a reverse-order pass there is still owed; l3_section_sharded is declared yugabyte_only_designs in this study's runner and is therefore never attempted on PostgreSQL, so the claim's sharded element can only ever be engine-specific evidence; its 2026–09–21 figures (15.9 and 28.3 ops/s) have not been reproduced on any pass since because its load fails on yb-single; the PostgreSQL half has since been measured in both orders as well: l1 before l2 gave a 0.83x multiple and l2 before l1 gave 0.88x on the 100k-seat map, so the engine contrast (about 25x on YugabyteDB against none on PostgreSQL) now has the same order control on both engines and both halves; l3_section_sharded loads, verifies 65/65 and reproduces its collapse when it is the only cell in a session (2026–09–27), which shows its repeated load failures inside a matrix are a session effect on a machine whose declared container budgets cannot be enforced and not a property of the design; that dedicated run was pre-registered as a diagnostic that would not be folded into this claim, so it is recorded here as a route to measuring the sharded element rather than as the element's replication - accepting it as such is a decision, not a mechanical update

Source: studies/03-reserved-seating/reports/20260921T231328Z.md · run 20260921T231328Z · tag run/03-reserved-seating/20260921T231328Z

3.4.7 Boundaries and reproduction

Embedding here means a JSON/array child column in PostgreSQL or a document row in YugabyteDB — a labelled **analogy** to a native document database, which was not measured here (`v2-gap-06`). The comparison of a table of rows against a stored document changes both designs at once, so it contrasts two whole ways of organising the data rather than one decision (`conf-03`).

3.5 Append-only history / snapshots

3.5.1 Quick choice in plain language

Never overwrite the fact; append what happened. Choose it when a question must survive an undo.

3.5.2 Where it thrives and where it perishes

Thrives wherever refunds, cancellations or corrections are in scope. Perishes under storage limits with no retention policy.

3.5.3 Common scenarios

Refund reporting, audit trails, last-purchase questions after a cancellation.

3.5.4 Mechanism

See the **derived state and history** concept and the **expiry and clock authority** concept.

3.5.5 Costs

Reads need a report over history; writes append and storage grows (about 33–35% more in the ticketing ledger); **answerability improves** — this family is the answerability fix, because retained history keeps enough information to answer across refunds, cancellations and corrections. An append-only history does not itself fence concurrent writers, order events, deduplicate, reject invalid events or provide atomicity; concurrency and arbitration must be specified separately. Operations need retention.

3.5.6 Direct evidence

v2-07-refund-answerability-and-storage · run_replicated · answerability is a schema fact, not a timing; the +33–35% storage delta is a relation-size difference measured in the primary run and deterministic for the same dataset and design; it is not a repeated timed result; the P3 -> X1 read rows of this run are excluded, because the difference belongs to the configuration as a whole rather than to one decision inside it; the read phase of this claim's primary anchor 20260920T234953Z was client-CPU throttled by a design-dependent amount (2.3 s for p2_precreated_skip_locked to 58.1 s for r1_inventory_row, out of about 1085 CFS periods), so that report's read figures are not quotable: the hazard reproduces on the current harness (20260929T165533Z, 20260929T170353Z: r1_inventory_row 32.3 s of ~63 s of periods, both orders), and the 2026–09–30 budget calibration shows the client's quota is a symptom rather than the ceiling - the read level on this machine is set by the database's share of four CPUs, and adding a client core removes the client's throttling while making the reads slower. Answerability and the r05 storage/speed result are unaffected: the ledger still answers r05 at 30.3k and 33.0k ops/s against the primary's 32.2k, and at the new 2-worker read footprint the r05 result reproduces independently at 32,164 ops/s (20260930T164028Z), so that number has a footprint-2 footing; all fifteen designs now have one (the eleven-design tranche 20260930T201732Z/20260930T203913Z adds the rest, unthrottled), while this claim's primary anchor's own footprint-8 read figures remain not quotable (design-dependent inflation, 1.09x to 2.22x). **Correction, 2026–09–30: an earlier caveat here said the two many-row queries (q02_band_events, q05_band_tickets_sold) had client-bound levels; it is withdrawn.** A one-worker tranche (20260930T232926Z, 20260930T233744Z) shows that in-flight measured with the **mean** latency is exactly 1.000 in all 72 cells at one worker and 2.00 at two, so every read cell in the family is a store measurement at a stated footprint, and only its magnitude depends on the concurrency. Two errors produced the withdrawn caveat: q05 does not return 28 rows (all three variants return one - COUNT/SUM with no GROUP BY), and in-flight computed from the **median** understates the concurrency by the latency skew (mean/p50 up to 2.7x), which reads exactly like a worker idling between fetches. The primary anchor's **PostgreSQL read cells have since been re-stated** on the footprint-2 footing (analysis 20261001T-read-cells-restated: all fifteen designs, both orders, every cell store-bound at 2.00 operations in flight), so its `pg-single` read figures may be replaced rather than caveated. All fifteen designs have since been measured in a **single run**, twice and in reversed order (20261001T100948Z, 20261001T103931Z): 0 throttled periods in all 30 read phases and every one of the 270 cells store-bound at 2.00 operations in flight by the mean latency, so the family's levels are jointly comparable within that session. Two consequences for quoting: the top group (h0, h1, r1, r2, p4) differs by 4%, inside that session's own order term, so its internal ranking is not quotable - only the 1.5x gap between that group and the per-seat group is; and c1_count_naive carries a 40% position term (first of one order against last of the other), so its q01 level should not be quoted from these runs. Its two **YugabyteDB read arms have no replacement** and remain an explicit coverage gap; the storage percentage depends on the rule and on the page layout, and must not be quoted as one number: tables only 33.4–35.2%, every relation 35.0–36.2%, indexes alone 37.7%; the same pair's relation sizes moved 0.26% (p3) and 0.41% (x1) between two runs 29 minutes apart, so the delta moved 0.9 percentage points; the index-only figure spans 37.4–37.9% across the five runs, so even there the rule is a band and not a point, and the 2026–10–02 replication's M4 (reproducible within 1%) is falsified by that movement - a tighter figure would need a vacuumed comparison, which is a different measurement; the answerability statuses are the harness's own audit of its own schema, computed as a pure function of the design and emitted inside the read phase; the 2026–10–02 replication therefore tests reproducibility across two whole runs and not the independence of the audit's rule, and it re-measured no timing · full card in the evidence registry index

v2-08-ledger-race-cost-128-buyers

append-only history / snapshots · run_replicated

At 128 buyers the append-only ledger's cost over compare-and-set rises with the size of the event rather than sitting in one band: on PostgreSQL it is about 1.1x at 10 seats (where the direction is not reliable), about 1.2–1.4x at 100–1000 seats, about 1.8x at 10000 seats and about 2.5x at 100000 seats, measured in twelve whole runs in both design orders, with wide spreads at the small tiers. The 1.8–2.2x on YugabyteDB, the 2.1–2.5x on the refund itself and the up-to-5x delay to the organiser's own edit are single-run figures that have not been re-measured, and no design ever under-booked a seat.

Trials: 12 whole-run replications · 5 fresh-load trials per cell · 1 inner iteration

Confounds: conf-05-study02-buyer-arms-disagree

Limits: one small run, closed loop, quota-bound nodes; scoped to 128 buyers; must not be extrapolated to 32 buyers; single run, three trials per tier; replicated on 2026–09–27 in both design orders at 128 buyers, three trials per tier: the p3/x1 ratio came out 1.53x, 1.71x and 2.00x at 100, 1000 and 10000 seats in the first order and 0.99x, 1.30x and 1.74x in the reversed order, so the ratios reproduce in size while the lowest of them falls below this claim's 1.1x floor; the ordering is not stable at the smallest tier: CAS read 4163 against the ledger's 2724 at 100 seats in the first order (1.53x) and 3588 against 3618 in the reversed order (0.99x), i.e. the ledger marginally faster - so the designs swap places at a fixed buyer count, which is what v2–09 records for changing buyer counts; the former 'tight spreads' wording did not hold at that tier: the 100-seat cell spread 57% for CAS and 37% for the ledger in the first order, and 47% and 51% in the reversed order, while every other tier stayed within 4–17% - and because the wide spread appeared at the same tier in both orders it belongs to the cell rather than to a design's position in the session; re-scoped on 2026–09–27 (HIGH, task repo/v2–08-rescope): the flat 1.1–2.3x band and the words 'tight spreads' were removed from the statement because the cost measured across the tier axis is monotone (about 1.1x at 10 seats to about 2.5x at 100000) and the small-tier cells spread 47–77%; the superseded wording, the evidence behind each change, and the earlier post-v6 re-scopings of v2–06 and v2–11, are recorded in book/evidence/v6/SUPERSESSION_LEDGER.md; the earlier 'single run, three trials per tier' limit describes the primary run only; the claim now rests on 8 whole runs (2 at 3 trials across 3 tiers, then 6 at 5 trials across the 100- and 1000-seat tiers); settled on 2026–09–27 by a third tranche of six runs (5 fresh-load trials per cell, three in each design order): the 100-seat p3/x1 run median was 1.279, 1.333, 1.257, 1.712, 1.328 and 1.476, so the single 0.99x reading of the reversed replication does not reproduce and the former band is not widened by this evidence; the ledger was slower in 29 of the 30 individual trial pairs (pooled per-trial median ratio 1.391x, range 0.940–1.920); the former 'tight spreads' wording still failed at the 100-seat tier across all eight runs: the cell's spread was 47–77% for CAS and 26–54% for the ledger in the six settle runs, and the run-to-run spread of the tier-100 ratio is 34% over those six and 54% over all eight (0.992–1.712, median 1.331), so that tier supports a direction and not a point ratio; the 1000-seat positive control read 1.304–1.712 in all six settle runs, so the harness detected the ledger's cost in every run; correctness was green throughout (46/46 P3, 48/48 X1 verifications, 0 over-booked, 0 under-booked, 0 timed-out), and no settle cell is void; the tier axis was then measured on 2026–09–27 in four more whole runs (5 trials per cell, two runs in each design order, all five tiers measured in every run): the pooled run-median p3/x1 rose 1.075, 1.237, 1.409, 1.845 and 2.505 at 10, 100, 1000, 10000 and 100000 seats, monotone in the pooled medians and in every individual run, so the ledger's cost is a function of tier and the claim's former 1.1–2.3x band described its middle three tiers rather than the whole axis; the statement's YugabyteDB, refund and organiser-edit figures come from the primary run alone and are labelled as not re-measured; the replication programme covered only the PostgreSQL race, so nothing here re-measures them, and v2–09's finding that the design order moves the ratio at the small sizes still applies; both endpoint tiers lie outside the former band and had never been repeated before this tranche: at 10 seats the run medians were 1.023–1.180 (pooled 1.075, below its 1.1x floor) while the per-trial median was 1.131 and the ledger was slower in only 12 of 20 trial pairs, so the cost there sits at the floor and its direction flips in 40% of trials; at 100000 seats the ledger was slower in 20 of 20 pairs (pooled per-trial median 2.456, run medians 2.249–2.637), above the 2.3x top; the 100000-seat tier is a single event per trial, so its 20 trial pairs are 20 readings of one event and an event-specific effect would be indistinguishable from a tier effect; the 10-seat cell is near-degenerate (100 events of 10 seats against 128 buyers) and its cells spread 16–71%; correctness was green in all four tier-axis runs (0 over-booked, 0 under-booked, 0 timed-out, 0 errors); with the two earlier tranches the tier-100 reading now rests on twelve runs whose run medians span 0.992–1.712 (median 1.331, spread 54%), so that tier still offers a direction rather than a point ratio

Source: studies/02-ticket-booking/reports/20260921T205212Z.md · run 20260921T205212Z · tag run/02-ticket-booking/20260921T205212Z

3.5.7 Boundaries and reproduction

The PostgreSQL ledger cost rises with the size of the event — about 1.1x at 10 seats to about 2.5x at 100,000 — and the design order moves the absolute throughput at the small sizes without changing which design is faster (`v2-09`); the load multiplier is not published (`v2-gap-01`). Quote the tier, never one pooled ratio.

3.6 External read copies / caches

3.6.1 Quick choice in plain language

Serve the answer from beside the database, with a stated freshness contract. Do it for warm, cacheable, read-heavy questions.

3.6.2 Where it thrives and where it perishes

Thrives on repeated reads of stable keys. Perishes when many instances share a cache under relaxed freshness without a publication fence. The fence closes one specific race: a reader that snapshotted committed state S0 republishes it after a writer commits S1 and invalidates.

3.6.3 Common scenarios

A donor portal's hot profile reads, a public dashboard over changing totals.

3.6.4 Mechanism

See the **cache consistency** concept for the guarantee-first flow: name the contract, establish change-observation completeness, read the source's capabilities, then choose topology (process-local versus shared) and the fill path (cache-aside versus write-through). Topology and fill path are not guarantees; performance controls (fill lease, TTL, early expiry) are added separately.

3.6.5 Costs

Reads gain about 2.2–2.5x in two whole replications, with the tail improving about 3x rather than an order of magnitude; a strict protocol adds a write-path fence; storage moves to the cache (whose budget is outside the `db-only` comparison); operations gain a new failure domain.

3.6.6 Direct evidence

v2-14-cache-throughput-gain

external read copies / caches · run_replicated

Adding a cache to warm cacheable reads buys 2.2–2.5x in throughput: two whole pg-single + Redis runs on 2026–10–02 measured the cached warm read at 2.54x and 2.24x the no-cache owned baseline, inside the primary's 2.2–3.5x band. The primary's p99 clause did not reproduce: the cached tail here was 8.5–10.1 ms against the baseline's 26.9–27.6 ms, a cut of about 3x rather than the primary's order of magnitude (0.8–2.0 ms against 15.8–27.1 ms), so the claim carries the throughput band and records the tail as not reproduced under this client. The cache's own CPU and memory are not counted against the database side (db-only framing), and Redis here is a shared cache, never an authoritative key-value store.

Trials: 3 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Confounds: conf-04-study05-db-only-cache

Limits: one machine, closed loop, small scale (800 donors), PostgreSQL + Redis cache only; the p99 clause did not reproduce: cached p99 8.5–10.1 ms against the baseline's 26.9–27.6 ms (about 3x), where the primary recorded 0.8–2.0 ms against 15.8–27.1 ms; the tail is suspected client-bound at this client budget and was not isolated with a plan or a footprint cell; warm cacheable reads only; the Redis container's budget is outside the db-only comparison (the equal-total framing is a separate claim, v3–03); absolute throughput is session-specific; only the within-run ratio travels; the 2.2–3.5x range remains supported only by the PostgreSQL single-node + Redis cells; do not transfer it to YugabyteDB, a cluster, or open-loop demand

Source: studies/05-cache-consistency/reports/20260921T-survey3.md · run 20260921T-survey3 · tag run/05-cache-consistency/20260921T-survey3

v2-15-three-instance-staleness

external read copies / caches · mechanism_supported

Three logical application instances sharing one Redis cache on write-through with relaxed freshness record about 87% wrong reads, while every relaxed configuration on a single instance records none; a private in-memory lease cannot coordinate separate instances, and a database version token that is never checked does not remove the problem. The 87.81% belongs to the owned model (o:opt:red:wth:rel) and 87.24% to the legacy model.

Trials: 1 whole-run replication · 1 fresh-load trial per cell · 1 inner iteration

Confounds: conf-04-study05-db-only-cache

Limits: single trial, one machine, small scale; generality unproven; the 87%-vs-0% separation is far outside the ~20% noise floor, but the exact rate is one trial; the signed all-green analysis swapped the two models' rows; this claim uses the report and JSON attribution

Source: studies/05-cache-consistency/reports/20260921T-survey3.md · run 20260921T-survey3 · tag run/05-cache-consistency/20260921T-survey3

v2-16-strict-freshness-read-cost

external read copies / caches · run_replicated

The strict-freshness contract cost nothing measurable in READ throughput: the controlled strict/relaxed pair differed by 7.3% in one whole run and 5.7% in the other with the sign flipping, inside the cells' 8.7%-22.8% trial spread, so the null reproduced in both design orders. This claim measures read throughput only: it does not quantify the write-path cost of a strict protocol, and it must never be restated as 'strict freshness is free'.

Trials: 3 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Confounds: conf-06-claim12-full-noise-range, conf-04-study05-db-only-cache

Limits: read throughput only; the two fresh runs' trial spreads reached 22.8%, so only an effect larger than that could have been seen; small scale, closed loop, one machine; the strict/relaxed pair here is the owned write-through pair; a strict protocol's write-path cost is not measured

Source: studies/05-cache-consistency/reports/20260921T-survey3.md · run 20260921T-survey3 · tag run/05-cache-consistency/20260921T-survey3

v3-03-equal-total-framing-labelled

external read copies / caches · run_replicated

Cache resource accounting carries a second, separately labelled comparison in which both sides are given the same total resources: two whole runs on 2026–10–02 recorded the db-only framing at 8,199 warm ops/s (cache budget none) and the equal-total framing at 7,931 (cache 1 CPU / 768 MiB), 3.3% apart inside the 17.7%/18.4% trial spread, with resource_framing and both budgets recorded in every result. What the claim asserts is that the two ways of counting resources are labelled and never pooled; the primary's 11k/8.0k point figures did not reproduce and are not quoted.

Trials: 4 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Limits: what matters is that the two framings are labelled and kept apart, not the ratio between them; the fresh runs are 3.3% apart, inside the 17.7%/18.4% spread; the primary's 11k/8.0k figures did not reproduce; one host, small scale, each framing measured once per session

Source: studies/05-cache-consistency/reports/20260923T1150Z-res2-equaltotal-pg.md · run 20260923T1150Z-res2-equaltotal-pg · tag run/05-cache-consistency/20260923T1150Z-res2-equaltotal-pg

3.6.7 Boundaries and reproduction

Redis was measured as a cache, never as an authoritative store. The gain is measured against a database-only reference point, so it cannot be attributed to the cache by itself (`conf-04`), and the comparison against equal total resources per side is labelled separately. The failure with three instances shows the mechanism at work rather than a rate to predict from, and the in-process designs' zero wrong reads are a bypass result (`v2-15`), not safety.

4 Minor variants

CHAPTER · MINOR VARIANTS

A minor variant is one controlled change inside a family. The corpus has measured pairs for some; the rest are named with their evidence status so a reader can tell the difference.

4.1 Measured controlled pairs

4.1.1 Index selection

Read score — used from here on — is this corpus's blended within-run composite of a family's read queries. It compares variants inside one run and nothing else: it is not the throughput or the latency of any single query, and it must not be quoted across runs.

Adding the query index was the first large read win in the charity tree (D2 indexed, about 10-11x the minimal design's read score in two whole runs, 13.3x in the first); flattening the foreign key reached about 14-16x (20.5x in the first).

v2-01-normalized-index-first · run_replicated · PostgreSQL 1 node and YugabyteDB 1/3 nodes in one run; small scale; a single measurement per configuration, not a repeat; read score is a blended measure, not one query; the quoted point figures (13.3x, 20.5x) are the primary run's single levels: the whole-run replication of 2026–10–01 measured 9.7–15.5x for the same two relations while the absolute read scores moved 40–45% between its two runs, so the band and the ordering are what may be quoted, not the points · full card in the evidence registry index

4.1.2 Optimistic versus pessimistic concurrency

Under one hot key and 16 writers, lock-before-update delivered about 1.6–1.8x the version-checked design (1.76x in the first run, 1.56x–1.69x in four fresh runs in both design orders). The obvious explanation — that the version check pays for its retries — was tested and rejected: with the retry budget at zero the ratio moves by 1.1%–3.2%. An unchecked read-modify-write lost 93.7% of acknowledged updates, and both correct designs lost none.

v2-12-lock-vs-version-upper-bound · run_replicated · one key, one installed product, 16 writers; PostgreSQL single node, small scale; one fresh-load trial per run; five whole runs now support the ratio, but no run repeats the cell, and the -retries 1 setting was not among the controls (the budget controls used the default 8 against -retries 0); 1.76x is one point on a writer curve, not a curve; the upper-bound hedge is retired: the retry budget was re-run on 2026–10–02 at 16 writers in both design orders, default against -retries 0 (1.64x against 1.69x with the lock first, 1.57x against 1.56x with the version check first), a 1.1% to 3.2% difference, which agrees with the primary's own retry control (1.60x against 1.61x) and means the advantage is not per-retry harness work; the re-scoped figure is a band of five whole runs on two days (1.56x, 1.57x, 1.64x, 1.69x, 1.76x); absolute throughput is day-specific, so only the within-run ratio travels · full card in the evidence registry index

4.1.3 Trigger versus application maintenance

Trigger-maintained rollups cost 4.0–5.7x on whole-configuration replacement across three randomized-order runs (median 4.94x), and their latency tail is 22–46x worse (p99 61–109 ms against 2.2–2.7 ms); the application rollup kept writes near the reference. Repeating the measurement inside that one configuration gave 35–115% disagreement, so quote the range and never a point.

v2-13-trigger-rollup-cost · run_replicated · PostgreSQL single node, small scale; three whole runs, each with three repeats of the measurement per configuration; the experiment was repeated as separate whole runs on one machine, so it is not independent of this hardware and is still exposed to this host's measurement hazards; repeating the measurement in that configuration disagreed by 35–115% across the three runs, more than the ~20% this project allows, so only the direction and an order of magnitude are supported, not a single ratio; the ~15x read gain belongs to the earlier single run and was not re-measured in the replication; the 6.85x figure from the earlier one-off run did not reproduce and must not be quoted; the trigger's product is a structural guarantee, not speed; the three runs realized only two distinct design orders (seeds 202 and 303 coincided, and in the sibling read tranche all three seeds coincided); randomized order describes the method, and the realized order is recorded in each manifest; the penalty is size-dependent, not a constant: crossing the same pair with entries per installed product gives 2.07x at 10 entries, 4.38x at 60 and 24.20x at 240, so this ratio holds at the small scale default of 60 entries and must not be quoted as a property of the design without the size (v2–18-maintenance-size-interaction) · full card in the evidence registry index

4.1.4 Strict versus relaxed freshness

Strict after acknowledgement means a read that starts after a write to the same key is acknowledged never returns an older committed value. **Relaxed** is a family of weaker contracts, not one contract: compared with the strict promise just stated, a relaxed contract may permit a committed but older value according to its declared semantics. Only a **bounded-staleness** member declares a maximum Δ; eventual and best-effort freshness need not, and the relaxed contracts measured here declared no maximum, so they are unbounded-relaxed. No member permits a dirty, torn or impossible value. Every controlled pair differed by −14.2% to +12.3% in read throughput — noise. The visible cost of strictness is on the write path, where a publication fence is added against the stale-fill race (a reader republishing S0 after a writer commits S1 and invalidates).

v2-16-strict-freshness-read-cost · run_replicated · read throughput only; the two fresh runs' trial spreads reached 22.8%, so only an effect larger than that could have been seen; small scale, closed loop, one machine; the strict/relaxed pair here is the owned write-through pair; a strict protocol's write-path cost is not measured · full card in the evidence registry index

4.2 Named but not measured as controlled pairs

- **Full versus bounded embedding.** Embedding was measured as a family, not against a bounded variant.
- **Locks / CAS / isolation levels.** The corpus has CAS and lock designs, but not an isolation-level sweep under one invariant.
- **Pre-created versus on-demand inventory.** Measured in ticketing as a family contrast with arbitration, not isolated from concurrency strategy.
- **Cache-aside versus write-through.** Both appear; the three-instance failure is about fencing, not about the two patterns head-to-head.

Coverage gap

No variant above is a cross-study ranking, and none is an equal-total-resource comparison. Treat the unmeasured variants as open, not as null results.

5 Cross-family comparisons

CHAPTER · CROSS-FAMILY COMPARISONS

Comparisons across families are where over-claiming happens. The rule here: a pair is quoted only when one decision changed, and every comparison carries its confounds on the page.

5.1 What a controlled pair looks like

- **One decision changed.** The charity tree's index and rolldown pairs each change one placement decision; their confounds are named (`conf-01`).
- **Same workload and resources.** Logical data, operations and per-node budget held constant.
- **Controls present and fired.** A pair whose negative control did not fire is weaker than it looks.

5.2 Comparisons this book deliberately does not make

- **No cross-study numeric ranking.** No comparability record exists, so ratios from different runs are not pooled.
- **No equal-total-resource ranking.** Single-versus-cluster answers "add machines", not "same budget".
- **No native-family transfer.** JSONB/state is not a native document store and Redis was measured only as a cache; such a transfer is analogy, labelled as such.

5.3 Direct evidence for the two family contrasts

v2-03-embedding-not-ahead · run_replicated · one run, one trial; embedding here means a JSON/array child column, not a native document database; the band moved down on replication (1.7–2.2x against the quoted 2.4x) while staying below both indexed designs, so the finding is the ordering and the sub-multiple, not the 2.4x · full card in the evidence registry index

v2-11-section-seat-map · run_replicated · one read-only run, one trial, 5 s per measurement; quota-bound nodes; read-only phases; no control could fire; a difference below ~1.8x cannot be attributed to the design rather than to run-to-run scatter; a replication on yb-single on 2026–09–26, three repeats per cell, reproduced the direction strongly: l2_section_document read the 100k-seat map at 1138 ops/s against l1_claim_rows at 41, a 27.8x multiple against the 20.8x of 2026–09–21, while both absolute figures fell far below the original (l1 by 72 percent, l2 by 63 percent), so the multiple is the claim and the figures are one session's readings; l3_section_sharded has failed its load in all three passes, in three different positions and under two memory envelopes, and with two different symptoms (connections terminated mid-COPY with SQLSTATE 57P01, then connect: connection refused). The sharded collapse therefore cannot be tested on this host with this harness - which is different from having tested it and found nothing; the pair has since been measured in both orders: l1 then l2 gave a 27.8x multiple and l2 then l1 gave 24.4x, a 12 percent difference, so the claim's direction does not depend on which design runs first; the pass that supplied the reversal ran with the database container at 5 GB and the YugabyteDB memory limit at 3 GiB rather than 3 GB and 1.5 GiB, because the earlier passes lost cells to the out-of-memory killer; its absolute figures are therefore not comparable with the 3 GB runs, and only the ratio between the two designs inside a run is; the load failures are memory pressure rather than design behaviour: the database log records server processes terminated by signal 9 (killed), 122 such lines in one cell, on a host with 15 GB of memory - so the sharded half of this claim and its PostgreSQL half are blocked here by host capacity, and a lost cell of this kind never reached the correctness gate rather than failing it; the two passes that supply the AB/BA pair also differ in memory envelope, so the 12 percent agreement may hide an order effect and a memory effect that cancel; a pass at 5 GB in the first pass's order would separate them; the PostgreSQL half was replicated on 2026–09–27 and shows no attributable difference (l2_section_document 6565 ops/s against l1_claim_rows 7873 on the 100k-seat map, a 0.83x multiple), so the finding is the engine contrast - about 25x on YugabyteDB against none on PostgreSQL - rather than the design being faster in general; that PostgreSQL measurement is a single run in a single design order, unlike the YugabyteDB pair which has the AB/BA control; a reverse-order pass there is still owed; l3_section_sharded is declared yugabyte_only_designs in this study's runner and is therefore never attempted on PostgreSQL, so the claim's sharded element can only ever be engine-specific evidence; its 2026–09–21 figures (15.9 and 28.3 ops/s) have not been reproduced on any pass since because its load fails on yb-single; the PostgreSQL half has since been measured in both orders as well: l1 before l2 gave a 0.83x multiple and l2 before l1 gave 0.88x on the 100k-seat map, so the engine contrast (about 25x on YugabyteDB against none on PostgreSQL) now has the same order control on both engines and both halves; l3_section_sharded loads, verifies 65/65 and reproduces its collapse when it is the only cell in a session (2026–09–27), which shows its repeated load failures inside a matrix are a session effect on a machine whose declared container budgets cannot be enforced and not a property of the design; that dedicated run was pre-registered as a diagnostic that would not be folded into this claim, so it is recorded here as a route to measuring the sharded element rather than as the element's replication - accepting it as such is a decision, not a mechanical update · full card in the evidence registry index

5.4 What these six comparisons cannot decide

Each item below is a comparison the book shows, followed by the reason it cannot settle the question it looks like it settles. The reason comes first because it is the useful part; the short label in brackets is only how the rest of the book refers back to it.

- **A copied key carries more than the key.** The D2⟶D3 rolldown compares two whole designs, so the read gain it measures includes the copied column, the index that supports it and the changed SQL — not the copied column on its own. [**conf-01**]
- **The recency pair's write cost is not only about recency.** The design with the recency index also does all of the rollup maintenance, so the experiment cannot say how much of the write cost comes from the index itself. Quote its read comparison, not its write cost. [**conf-02**]
- **A table of rows against a stored document is a whole-family comparison.** The seat map differs both in storage shape and in how the data is organised, so any difference belongs to the two designs together, not to one decision inside them. [**conf-03**]
- **The cache gain was measured against one baseline.** The reference point was the database alone, so the measured gain cannot be attributed to the cache by itself. [**conf-04**]
- **The two buyer models swap places.** On PostgreSQL the two designs change order depending on the workload, so neither can be reported as the faster one. [**conf-05**]
- **The strict-freshness numbers run in both directions.** The range goes from −14.2% to +12.3%, so quoting either end alone would misrepresent the result; the whole range travels with any summary. [**conf-06**]

6 Topologies

CHAPTER · TOPOLOGIES

Topology is a separate axis from design family: how many nodes there are, how many copies of the data exist, where those copies sit, how clients are routed to them, how resources are divided between the two sides of a comparison, what the network does, and what happens when a node fails. A design that is best on one node is not thereby best on three.

6.1 What was measured

Studies 01–03 run PostgreSQL single-node and YugabyteDB single-node (RF=1) and 3-node (RF=3). Each measured configuration is capped at a documented per-node budget, and every run manifest records it. The comparison is therefore “the same budget on every node”, not “the same total resources on both sides”.

6.2 What topology does to a design

In the measured YugabyteDB RF=3 topology, replication puts consensus work on the foreground write path, so write-heavy designs move differently from read-heavy ones there; asynchronous replication would not necessarily impose that. The section-document experiment shows that one **layout package** can affect two access patterns in opposite directions: the sharded variant answered the 100k-seat whole-map read 4.5–11x faster than a row design while collapsing point lookups to 26 ops/s. Because that package changes representation and placement together, it isolates no pure topology effect; the lesson is that a layout has to be measured again under each topology and access pattern you care about.

v2-11-section-seat-map · run_replicated · one read-only run, one trial, 5 s per measurement; quota-bound nodes; read-only phases; no control could fire; a difference below ~1.8x cannot be attributed to the design rather than to run-to-run scatter; a replication on yb-single on 2026–09–26, three repeats per cell, reproduced the direction strongly: l2_section_document read the 100k-seat map at 1138 ops/s against l1_claim_rows at 41, a 27.8x multiple against the 20.8x of 2026–09–21, while both absolute figures fell far below the original (l1 by 72 percent, l2 by 63 percent), so the multiple is the claim and the figures are one session's readings; l3_section_sharded has failed its load in all three passes, in three different positions and under two memory envelopes, and with two different symptoms (connections terminated mid-COPY with SQLSTATE 57P01, then connect: connection refused). The sharded collapse therefore cannot be tested on this host with this harness - which is different from having tested it and found nothing; the pair has since been measured in both orders: l1 then l2 gave a 27.8x multiple and l2 then l1 gave 24.4x, a 12 percent difference, so the claim's direction does not depend on which design runs first; the pass that supplied the reversal ran with the database container at 5 GB and the YugabyteDB memory limit at 3 GiB rather than 3 GB and 1.5 GiB, because the earlier passes lost cells to the out-of-memory killer; its absolute figures are therefore not comparable with the 3 GB runs, and only the ratio between the two designs inside a run is; the load failures are memory pressure rather than design behaviour: the database log records server processes terminated by signal 9 (killed), 122 such lines in one cell, on a host with 15 GB of memory - so the sharded half of this claim and its PostgreSQL half are blocked here by host capacity, and a lost cell of this kind never reached the correctness gate rather than failing it; the two passes that supply the AB/BA pair also differ in memory envelope, so the 12 percent agreement may hide an order effect and a memory effect that cancel; a pass at 5 GB in the first pass's order would separate them; the PostgreSQL half was replicated on 2026–09–27 and shows no attributable difference (l2_section_document 6565 ops/s against l1_claim_rows 7873 on the 100k-seat map, a 0.83x multiple), so the finding is the engine contrast - about 25x on YugabyteDB against none on PostgreSQL - rather than the design being faster in general; that PostgreSQL measurement is a single run in a single design order, unlike the YugabyteDB pair which has the AB/BA control; a reverse-order pass there is still owed; l3_section_sharded is declared yugabyte_only_designs in this study's runner and is therefore never attempted on PostgreSQL, so the claim's sharded element can only ever be engine-specific evidence; its 2026–09–21 figures (15.9 and 28.3 ops/s) have not been reproduced on any pass since because its load fails on yb-single; the PostgreSQL half has since been measured in both orders as well: l1 before l2 gave a 0.83x multiple and l2 before l1 gave 0.88x on the 100k-seat map, so the engine contrast (about 25x on YugabyteDB against none on PostgreSQL) now has the same order control on both engines and both halves; l3_section_sharded loads, verifies 65/65 and reproduces its collapse when it is the only cell in a session (2026–09–27), which shows its repeated load failures inside a matrix are a session effect on a machine whose declared container budgets cannot be enforced and not a property of the design; that dedicated run was pre-registered as a diagnostic that would not be folded into this claim, so it is recorded here as a route to measuring the sharded element rather than as the element's replication - accepting it as such is a decision, not a mechanical update · full card in the evidence registry index

6.3 Open topology gaps

Coverage gap

Physical placement is unverified (`v4-gap-01`) and endpoint distribution is measured only for the 2026-09-23 Study 05 three-node cells (`v4-gap-02`); the earlier multi-node cells reach the cluster through a single endpoint, and there is no real network between “cluster” nodes. Multi-node results here are placement experiments, not distributed-systems results.

6.4 Boundaries

Do not scale these numbers to production capacity. The nodes share one host’s eight cores, are CPU-throttled, and communicate over a loopback-class path.

7 Scenarios

CHAPTER · SCENARIOS

A scenario is a set of questions plus a workload shape. The same family can be right in one and wrong in another, so each scenario below states its answerability question and its evidence status.

7.1 Ticket overbooking and refunds

Never oversell, then report refunds. Pre-created seats with compare-and-set or `SKIP LOCKED` sold 4–8x faster than a counter row; a ledger made refunds answerable at +33–35% storage. The ledger's own cost over compare-and-set at 128 simultaneous buyers grows with the size of the event — about 1.1x at 10 seats, about 1.2–1.4x at 100–1,000 seats and about 1.8–2.5x at 10,000–100,000 — so no single ratio covers the axis, and at the smallest size the direction is not reliable.

v2-06-hot-drop-designs · run_replicated · one run of the experiment, a single measurement per configuration; the run has 42 cells of which 2 failed (C2 count (SER) on the two YugabyteDB topologies); those cells are not evidence; hot-drop workload only; every absolute throughput in the 2026–09–26 replication was 26–72% below the 2026–09–13 run for the same design and tier, so the 4–8x range reproduced while the numbers behind it did not; the range is quotable and the figures are not; the ratio moved between runs: p3 against c4 went 7.07 to 4.37 to 4.64 at 100 seats and 7.26 to 4.30 to 4.70 at 1000, and p2 against c4 went 3.97 to 3.25 to 5.78, so the range is a range, not a point, and individual ratios shift by up to 44%; the replication re-ran neither deliberately wrong control (c1_count_naive, h0_hold_naive_confirm), so it strengthens the comparison without re-firing the correctness control that the first run provided; r1_inventory_row recorded one trial of about 4x lower throughput than its siblings at each tier (122 and 117 against 468–653); whether that is a real instability or a harness artefact is unresolved, and r1 is the weakest comparison in the replication; two of the original sweep's five tiers (10 and 10000 seats) were not re-measured; p2_precreated_skip_locked moved 58–76% between the two same-day replications while the counters moved within 15% and p3 within 7%; it ran first in one and last in the other, so that design carries a position or warm-up effect as large as the comparison it takes part in, and the claim's pairing of p2 with p3 hides it - the >=3x result holds at both extremes; the anomalous r1_inventory_row trials of the first replication (122 and 117 against 468–653) did not recur in the reverse-order run, which makes a harness artefact likelier than a design property without settling it; the read phase of this claim's primary anchor 20260913T021206Z was client-CPU throttled by a design-dependent amount (0.2 s for p2_precreated_skip_locked to 29.5 s for h0_hold_naive_confirm, out of 633 CFS periods), so that report's read figures are not quotable. The hazard reproduces on the current harness (20260929T165533Z, 20260929T170353Z: r1_inventory_row loses 420 of 634 and 422 of 633 periods), and the 2026–09–30 budget calibration (20260930T000544Z, 20260930T000759Z, 20260930T001013Z) shows the client's quota is a symptom rather than the ceiling: at three client cores the client is not throttled at all and the reads are slower (52,884 -> 43,726 ops/s at 10 seats), because the third core comes out of the database's share of the machine's four CPUs (database throttled periods 238 -> 847 -> 1052). The claim's own basis is the race phase (sell rate), where one cell in fourteen designs shows throttling. The read family has since been re-measured at the study's new 2-worker read footprint (20260930T164028Z, 20260930T164834Z: four designs, client unthrottled at 0 of ~631 periods, every cell latency-bound at 2.00 operations in flight for 2 workers (with the mean latency; a median-based count reads 1.9)), so read levels are quotable only with the footprint attached. All fifteen designs now have a footprint-2 footing (the four-design tranche plus the eleven-design tranche 20260930T201732Z/20260930T203913Z, where no design throttles: 0 of ~631 periods in all 22 read phases), and this claim's primary anchor's own footprint-8 read figures remain not quotable: the inflation they carry is design-dependent, 1.09x to 2.22x, and it tracks how many periods the old client lost per design rather than anything about the designs. All fifteen designs have since been measured in a **single run**, twice and in reversed order (20261001T100948Z, 20261001T103931Z): 0 throttled periods in all 30 read phases and every one of the 270 cells store-bound at 2.00 operations in flight by the mean latency, so the family's levels are jointly comparable within that session. Two consequences for quoting: the top group (h0, h1, r1, r2, p4) differs by 4%, inside that session's own order term, so its internal ranking is not quotable - only the 1.5x gap between that group and the per-seat group is; and c1_count_naive carries a 40% position term (first of one order against last of the other), so its q01 level should not be quoted from these runs. · full card in the evidence registry index

v2-08-ledger-race-cost-128-buyers · run_replicated · one small run, closed loop, quota-bound nodes; scoped to 128 buyers; must not be extrapolated to 32 buyers; single run, three trials per tier; replicated on 2026–09–27 in both design orders at 128 buyers, three trials per tier: the p3/x1 ratio came out 1.53x, 1.71x and 2.00x at 100, 1000 and 10000 seats in the first order and 0.99x, 1.30x and 1.74x in the reversed order, so the ratios reproduce in size while the lowest of them falls below this claim's 1.1x floor; the ordering is not stable at the smallest tier: CAS read 4163 against the ledger's 2724 at 100 seats in the first order (1.53x) and 3588 against 3618 in the reversed order (0.99x), i.e. the ledger marginally faster - so the designs swap places at a fixed buyer count, which is what v2–09 records for changing buyer counts; the former 'tight spreads' wording did not hold at that tier: the 100-seat cell spread 57% for CAS and 37% for the ledger in the first order, and 47% and 51% in the reversed order, while every other tier stayed within 4–17% - and because the wide spread appeared at the same tier in both orders it belongs to the cell rather than to a design's position in the session; re-scoped on 2026–09–27 (HIGH, task repo/v2–08-rescope): the flat 1.1–2.3x band and the words 'tight spreads' were removed from the statement

because the cost measured across the tier axis is monotone (about 1.1x at 10 seats to about 2.5x at 100000) and the small-tier cells spread 47–77%; the superseded wording, the evidence behind each change, and the earlier post-v6 re-scopings of v2–06 and v2–11, are recorded in book/evidence/v6/SUPERSESSION_LEDGER.md; the earlier 'single run, three trials per tier' limit describes the primary run only; the claim now rests on 8 whole runs (2 at 3 trials across 3 tiers, then 6 at 5 trials across the 100- and 1000-seat tiers); settled on 2026–09–27 by a third tranche of six runs (5 fresh-load trials per cell, three in each design order): the 100-seat p3/x1 run median was 1.279, 1.333, 1.257, 1.712, 1.328 and 1.476, so the single 0.99x reading of the reversed replication does not reproduce and the former band is not widened by this evidence; the ledger was slower in 29 of the 30 individual trial pairs (pooled per-trial median ratio 1.391x, range 0.940–1.920); the former 'tight spreads' wording still failed at the 100-seat tier across all eight runs: the cell's spread was 47–77% for CAS and 26–54% for the ledger in the six settle runs, and the run-to-run spread of the tier-100 ratio is 34% over those six and 54% over all eight (0.992–1.712, median 1.331), so that tier supports a direction and not a point ratio; the 1000-seat positive control read 1.304–1.712 in all six settle runs, so the harness detected the ledger's cost in every run; correctness was green throughout (46/46 P3, 48/48 X1 verifications, 0 over-booked, 0 under-booked, 0 timed-out), and no settle cell is void; the tier axis was then measured on 2026–09–27 in four more whole runs (5 trials per cell, two runs in each design order, all five tiers measured in every run): the pooled run-median p3/x1 rose 1.075, 1.237, 1.409, 1.845 and 2.505 at 10, 100, 1000, 10000 and 100000 seats, monotone in the pooled medians and in every individual run, so the ledger's cost is a function of tier and the claim's former 1.1–2.3x band described its middle three tiers rather than the whole axis; the statement's YugabyteDB, refund and organiser-edit figures come from the primary run alone and are labelled as not re-measured; the replication programme covered only the PostgreSQL race, so nothing here re-measures them, and v2–09's finding that the design order moves the ratio at the small sizes still applies; both endpoint tiers lie outside the former band and had never been repeated before this tranche: at 10 seats the run medians were 1.023–1.180 (pooled 1.075, below its 1.1x floor) while the per-trial median was 1.131 and the ledger was slower in only 12 of 20 trial pairs, so the cost there sits at the floor and its direction flips in 40% of trials; at 100000 seats the ledger was slower in 20 of 20 pairs (pooled per-trial median 2.456, run medians 2.249–2.637), above the 2.3x top; the 100000-seat tier is a single event per trial, so its 20 trial pairs are 20 readings of one event and an event-specific effect would be indistinguishable from a tier effect; the 10-seat cell is near-degenerate (100 events of 10 seats against 128 buyers) and its cells spread 16–71%; correctness was green in all four tier-axis runs (0 over-booked, 0 under-booked, 0 timed-out, 0 errors); with the two earlier tranches the tier-100 reading now rests on twelve runs whose run medians span 0.992–1.712 (median 1.331, spread 54%), so that tier still offers a direction rather than a point ratio · full card in the evidence registry index

v2-09-postgres-ledger-ratio-unsettled

append-only history / snapshots · run_replicated

On PostgreSQL the ledger is slower than compare-and-set at 1,000 seats at every buyer count tested, 8 to 128, and in both design orders (55 of 55 trial pairs over eleven runs), so the two designs do not change places with the load: the primary run's apparent swap came from its own confound, buyer count and design order having moved together. The size of the cost does vary without a simple trend (about 1.2–1.3x near 16–32 buyers and 1.4–1.9x at 64–128; one 8-buyer cell changed state mid-run), and the design order moves absolute throughput several-fold without changing which design is faster. On YugabyteDB the primary run's own range is 1.7–5.7x, wider than a headline would quote.

Trials: 11 whole-run replications · 5 fresh-load trials per cell · 1 inner iteration

Confounds: conf-05-study02-buyer-arms-disagree

Limits: the stable direction is measured at 1,000 seats across 8–128 buyers and at 32 buyers across all five tiers; the buyer-count axis is not swept at the other four tiers, so the full buyer x tier surface is open; one primary run per (buyers, order) cell, with a reference cell that moved 8.6% between the two ends of the tranche, so a level whose two orders differ by more than that is placed by the ratio and not by the absolutes; the direction is stable but the ratio is not: the eleven run medians span 1.06–5.10 (1.22–1.86 with the collapsed 8-buyer cell set aside), so the cost is a range and not a point; the 8-buyer level's pooled median is not interpreted: a recurrence test of six runs and twelve cells (2026–09–29, tag study-02/v2–09–8buyer) found four low-throughput events in 60 trials, readings of 619–655 ops/s against a session normal of about 2500 (a 4x drop), and they hit both designs (three of the four in the CAS arm) and both orders, so the low mode is a property of this buyer count's very short trials and not of the ledger; the original p3-first cell read as a state change only because its slow trials were its last three, which set the cell median; the primary evidence is from a different harness state (phases verify,write,race,churn on a five-day-old image), so comparing it with this tranche mixes the confound with a period effect and the re-scope is stated as a direction, not a ratio; one side of the primary comparison is a partial configuration on yb-cluster3 (medians of two measurements); at 32 buyers the ledger was slower in all ten tier x order cells of two 2026–09–29 runs (ratios 1.021–1.606) and below the 128-buyer pooled ratio at every tier (1.06 vs 1.08, 1.06 vs 1.24, 1.23 vs 1.41, 1.56 vs 1.85, 1.56 vs 2.51), so the primary's tier-wide reversal does not reproduce anywhere on the axis; those two runs are anchors but are not counted in the eleven-run replication record, which is the buyer-count sweep at one tier; at 32 buyers and 10–100 seats the direction sits at the measurement's floor: only 3 of 10 trial pairs at 10 seats and 6 of 10 at 100 favour the CAS design, with cell spreads of 86–174%, so those two tiers support the median and not a per-pair claim, while the 1,000-seat cell reproduced the sweep's ratio a day later within 1% (1.245 and 1.219 against 1.233 and 1.219); the 8-buyer low-throughput mode is not a quota effect on either side: the twelve cells' per-trial client_cpu entries (present since the study's first commit, and corrects an earlier limit here that said the client was not recorded) show zero client throttling and *more* client CPU in the slow trials (2.6–2.8 s against about 1.9 s), so the client waits rather than starves, while the database container's cpu.stat throttled about 4 ms across the collapsed cell; the cause is narrowed to a latency excursion on the response path and is not identified further, since no per-trial plan or server-side clock is recorded; three of the four 8-buyer low events were single trials that recovered on the next trial and one spanned consecutive trials, so 'persistent collapse' and 'transient spike' are names for where the event fell in the cell (a five-trial median cannot distinguish them at a ~7% event rate); no 8-buyer magnitude is quoted from either tranche

Source: studies/02-ticket-booking/reports/20260921T183722Z.md · run 20260921T183722Z · tag run/02-ticket-booking/20260921T183722Z

7.2 Reserved seating and holds

Hold, expire, confirm, and re-sell. Guarantees held everywhere, but YugabyteDB refused valid confirmations until the refused statement was retried; and the funnel that would size the hold window is unanswerable because releasing an expired hold erases the evidence.

v2-10-guarded-confirm-refusals

normalized facts · run_replicated

On YugabyteDB a guarded confirmation is not enough, but the refusals are spurious rather than a design fault: at the 10,000-seat tier the correct designs refused valid holds (s1_conditional_update 2 refusals in one whole run and 3 in the reversed run, s2_lock_then_update 1 in each), and every refusal is classified transient - the identical statement re-issued inside the refusing transaction matched every seat - while the retry-once variant s1r_confirm_retry refused nothing and every retry it made succeeded (5 across the forward run). On PostgreSQL the same three designs refused nothing at any of five tiers from 10 to 100,000 seats in two whole runs, so the guarantee held everywhere there. The study's negative control s0_check_then_hold_rc refused at every tier on both engines and stole 474–599 holds per tier on YugabyteDB and 1,168–6,231 on PostgreSQL, so the audit detects both the spurious refusal and the real theft. This claim is about refusals, not throughput, and no cost conclusion follows from it.

Trials: 3 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: v1 matrix run, a single measurement per configuration; the claim is about refusals, not throughput; retry-once is a design variant (S1r), not a tuning flag; the replicated refusals are few and tier-bound: 2, 3 and 1 refusal events in the correct designs across two whole runs, all at the 10,000-seat tier except s2's single 1,000-seat refusal in the reversed order, so the claim is that refusals happen and are transient - not a rate, and not a tier law; the YugabyteDB arm measured four tiers (10 to 10,000 seats) while the PostgreSQL control measured five (10 to 100,000), because that is how the study configures its tiers per engine; 'the guarantee held everywhere' therefore means everywhere the PostgreSQL arm ran; the refusals are the harness's own classification of its own designs, and the transient sub-class is decided by re-issuing the statement inside the refusing transaction (AM-01), so this replicates the mechanism and its detection, not an independent definition of a valid hold; the 2 GiB podman-machine blocker recorded in CONTEXT.md is a multi-node limit: a single-node YugabyteDB arm fits and completes here, which is what makes this replication possible, while yb-cluster3 remains unmeasurable on this machine; the spread figure is the refusal count's own movement, not a throughput spread: s1_conditional_update refused 2 times in the forward run and 3 in the reversed one, so the count moves 40% across the two runs and the phenomenon is established, not quantified

Source: studies/03-reserved-seating/reports/20260915T002411Z.md · run 20260915T002411Z · tag run/03-reserved-seating/20260915T002411Z

v2-gap-02-hold-funnel-unanswerable · gap · a schema limitation, not a missing measurement · full card in the evidence registry index




Figure 5: **Two buyers choose the same marked seats at the same moment.**

Form: sequence · Evidence: implemented design contract

> **Text equivalent.** Because a reserved-seating buyer may not be moved to another seat, Study 02's `SKIP LOCKED` scan does not apply here: the arbitration is a conditional update on the chosen seats (or a lock first, with the loser retrying) and one unguarded design is shown as a negative control. The figure is the contract the reserved-seating designs implement; it carries no measured value. Source: `studies/03-reserved-seating/diagrams/s_arbitration.puml`

7.3 Configuration portal

Read the overview often, replace configurations occasionally. A trigger-maintained rollup cost 4.0–5.7x on replacement across three runs; the application rollup kept writes near the reference. This is a small-scale result at one cardinality, and the trigger's own trials were imprecise.

v2-13-trigger-rollup-cost · run_replicated · PostgreSQL single node, small scale; three whole runs, each with three repeats of the measurement per configuration; the experiment was repeated as separate whole runs on one machine, so it is not independent of this hardware and is still exposed to this host's measurement hazards; repeating the measurement in that configuration disagreed by 35–115% across the three runs, more than the ~20% this project allows, so only the direction and an order of magnitude are supported, not a single ratio; the ~15x read gain belongs to the earlier single run and was not re-measured in the replication; the 6.85x figure from the earlier one-off run did not reproduce and must not be quoted; the trigger's product is a structural guarantee, not speed; the three runs realized only two distinct design orders (seeds 202 and 303 coincided, and in the sibling read tranche all three seeds coincided); randomized order describes the method, and the realized order is recorded in each manifest; the penalty is size-dependent, not a constant: crossing the same pair with entries per installed product gives 2.07x at 10 entries, 4.38x at 60 and 24.20x at 240, so this ratio holds at the small scale default of 60 entries and must not be quoted as a property of the design without the size (v2–18-maintenance-size-interaction) · full card in the evidence registry index

7.4 Donor portal with an external cache

Serve warm profile reads from a cache. Throughput rose about 2.2–2.5x in two whole replications, with the tail improving about 3x rather than an order of magnitude. Three instances sharing one relaxed cache recorded 87.81% wrong reads on the owned model and 87.24% on the legacy model: the publication must be fenced against the stale-fill race — a reader republishing S0 after a writer commits S1 and invalidates — not merely ordered after the commit. The single-instance relaxed cells recorded zero wrong reads, and the legacy process-local arms' zero was a bypass result (`v2-15`), so neither is evidence that an unfenced relaxed cache is safe.

v2-14-cache-throughput-gain · run_replicated · one machine, closed loop, small scale (800 donors), PostgreSQL + Redis cache only; the p99 clause did not reproduce: cached p99 8.5–10.1 ms against the baseline's 26.9–27.6 ms (about 3x), where the primary recorded 0.8–2.0 ms against 15.8–27.1 ms; the tail is suspected client-bound at this client budget and was not isolated with a plan or a footprint cell; warm cacheable reads only; the Redis container's budget is outside the db-only comparison (the equal-total framing is a separate claim, v3–03); absolute throughput is session-specific; only the within-run ratio travels; the 2.2–3.5x range remains supported only by the PostgreSQL single-node + Redis cells; do not transfer it to YugabyteDB, a cluster, or open-loop demand · full card in the evidence registry index

v2-15-three-instance-staleness · mechanism_supported · single trial, one machine, small scale; generality unproven; the 87%-vs-0% separation is far outside the ~20% noise floor, but the exact rate is one trial; the signed all-green analysis swapped the two models' rows; this claim uses the report and JSON attribution · full card in the evidence registry index

v3-01-churn-crosses-real-ttl

external read copies / caches · single_run_directional

A sustained 1801 s churn phase against the fixed 300 s TTL crossed 6.0 real TTL boundaries with 0 wrong reads in 2,879,077 blended reads and 380,824 writes; the hard-expiry counter is 0 and only probabilistic early expiry fired (37,063), so an entry was never observed to be removed by its hard TTL. This is scoped mechanism and duration evidence, not a general cache result.

Trials: 1 whole-run replication · 1 fresh-load trial per cell · 1 inner iteration

Limits: one PostgreSQL + Redis configuration at small scale; one sustained measurement, never repeated; hard expiry fired zero times; that clause is an open gap, not a confirmation; closed loop, so read volumes are a floor; the 5x-for-120 s burst has no write-rate knob and was not run; the 1800 s horizon was not re-run on 2026–10–02: the 600 s pair recorded for v3–02 re-tests the same mechanism at a shorter horizon, and this claim's 1801 s / 6.0-boundary figure remains the primary's single run

Source: studies/05-cache-consistency/reports/20260923T1100Z-churn1800-through.md · run 20260923T1100Z-churn1800-through · tag run/05-cache-consistency/20260923T1100Z-churn1800-through

v3-03-equal-total-framing-labelled · run_replicated · what matters is that the two framings are labelled and kept apart, not the ratio between them; the fresh runs are 3.3% apart, inside the 17.7%/18.4% spread; the primary's 11k/8.0k figures did not reproduce; one host, small scale, each framing measured once per session · full card in the evidence registry index

7.5 Scenario transfers are labelled

Analogy — not measured here

A supermarket stock counter, an auction bid ledger or an e-commerce inventory pool is structurally similar to the ticketing hot row, but none of them was measured here. Use those transfers as analogies from the hot-row mechanism, never as separate evidence.

7.6 Where a scenario stops

Coverage gap

Two scenario families are explicitly incomplete, and the book does not fill them with words: the configuration-portal study did not build eight of its eighteen designs and did not measure cardinality or cadence, and the cache study still owes its hard TTL expiry, medium scale, tablet/leader placement and open-loop demand. The cache study **did** measure real TTL churn, in-run repeats and equal-total cache accounting on 2026-09-23, so those are no longer gaps. The vocabulary is worth fixing here: an **in-run repeat** is another measurement window inside one benchmark process, which reduces the scatter inside that process but is not a separate run of the whole experiment — where the cards say `Trials: 1`, they mean the experiment was run once and no more. None of the things listed above has been measured yet, which is not the same as having been measured and shown to make no difference: these are absences of evidence, not neutral or negative results.

v2-gap-03-study04-missing-designs

normalized facts · gap · coverage gap

Eight of the eighteen planned Study 04 configuration-portal designs are not implemented, and cardinality, cadence/churn, repeated randomized trials, equal-total resources, placement and YugabyteDB are unmeasured. These are coverage gaps, not null results.

Trials: 1 whole-run replication · 1 fresh-load trial per cell · 1 inner iteration

Limits: no conclusion may read 'the missing designs would not change this'; owned by task-20260922T025912Z-study04-v2-protocol

Source: studies/04-configuration-portal/reports/20260921T1215Z-small.md · run 20260921T1215Z-small · tag run/04-configuration-portal/20260921T1215Z-small

v3-gap-01-study05-remaining-regimes

external read copies / caches · gap · partially superseded by v4-gap-01-physical-placement-unverified, v4-gap-02-endpoint-distribution-partial · coverage gap + instrument gap

Moved to successor claims: v4-gap-01-physical-placement-unverified, v4-gap-02-endpoint-distribution-partial.

Still open in this claim: hard-TTL expiry never observed removing an entry; medium scale beyond the harness maximum of 3,000 people; open-loop arrival demand.

Statement below is unchanged from its source registry; the moved dimensions are not restated as open here.

Four things about the cache study remain unmeasured, and they are absences of evidence rather than results: no entry was ever seen to reach its hard expiry (0 hard expiries in all three churn configurations), nothing beyond the harness maximum of 3,000 people was run, the distribution of tables and leaders across the cluster is unrecorded, and no open-loop arrival pattern was run.

Trials: 0 whole-run replications · 0 fresh-load trials per cell · 0 inner iterations

Limits: these are coverage gaps, not null results; medium scale is an order of magnitude beyond the current generator; placement verification needs an instrument the runner does not have; open-loop demand is owned by task-20260922T200831Z-study05-v2-open-loop

Source: studies/05-cache-consistency/reports/20260923T1100Z-churn1800-through.md · run 20260923T1100Z-churn1800-through · tag run/05-cache-consistency/20260923T1100Z-churn1800-through

8 Evidence and reproduction

CHAPTER · EVIDENCE AND REPRODUCTION

Every number in this book resolves to a claim in `book/evidence/v6/claims.json`, and every claim to something actually measured in a report this book cites. This chapter explains the confidence cards, the run-tag provenance model, and how to reproduce a run in Podman.

8.1 The provenance model

Direct evidence

A run tag marks the producing code state, not a tree that contains the run's results. Check out the tag for the code, then read the committed results directory for the data.

v2-gap-06-native-datastore-families

embedded documents · gap · coverage gap

No native document, key-value, graph or wide-column database was measured: JSONB/state is not evidence for a native document database, and Redis was measured only as a cache. Cross-family transfers to native datastores are analogy, not evidence.

Trials: 0 whole-run replications · 0 fresh-load trials per cell · 0 inner iterations

Limits: do not transfer the embedded-document or cache results to a native family

Source: studies/05-cache-consistency/reports/20260921T-survey3.md · run 20260921T-survey3 · tag run/05-cache-consistency/20260921T-survey3

v2-gap-01-ledger-load-multiplier-unstable

append-only history / snapshots · gap · unstable measurement

The append-only ledger's load-time multiplier is not published: the same pair and loader measured X1's pg-single load at 7.8x P3's in one run and 1.2x in the two sibling runs, with an empty harness diff.

Trials: 3 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: a single one-off load of one configuration is not a cost of the design; needs its own repeated load-only measurement before any multiplier can be quoted; the read phase of this claim's primary anchor 20260920T234953Z was client-CPU throttled by a design-dependent amount (2.3 s to 58.1 s across designs, out of about 1085 CFS periods) and the hazard reproduces on the current harness (20260929T165533Z, 20260929T170353Z), so that report's read figures are not quotable; the load-phase figures this claim rests on are a separate phase and were not throttled. The read family has since been re-measured at the new 2-worker read footprint for four designs (20260930T164028Z, 20260930T164834Z): their read levels are quotable with the footprint attached, and all fifteen designs now have a footprint-2 footing (the eleven-design tranche 20260930T201732Z/20260930T203913Z adds the rest, unthrottled, and 20261001T100948Z/20261001T103931Z measures all fifteen together in one session); this claim's primary anchor's own footprint-8 read figures remain not quotable

Source: studies/02-ticket-booking/reports/20260920T234953Z.md · run 20260920T234953Z · tag run/02-ticket-booking/20260920T234953Z

8.2 Reproducing the book itself

The book is built in Podman from a pinned toolchain; the manifest records every input and the resulting hash.

```
book/build.sh          # builds the pinned image, compiles, verifies, writes the manifest
cat book/dist/build-manifest.json
```

8.3 Reproducing a measured run

```
git checkout run/<study>/<run-id>     # the producing code state
infra/<topology>.sh up                # take the benchmark lock first
cd studies/<study> && ./run-<engine>.sh
```

A run's results live in `studies/<study>/results/<run-id>/`; the report beside them is generated, never hand-edited, and its inputs digest identifies the data.

9 Part II — Concepts

The first part measured what each family does under this corpus's workloads. This part explains the mechanisms those results came from, in the order the decisions bind: where information is placed, what the indexes cost, who arbitrates a contended row, what derived state owes its maintainer, who owns expiry, what a cache must prove, and where a cluster actually puts the data. The last chapter is the checklist for reading any number in the first part.

Each concept names the claim cards that measured it, and the glossary at the end of the book is the single definition site for every term used here.

10 Information placement

CONCEPT · INFORMATION PLACEMENT

Placement is the decision the rest of the book hangs on: which single fact owns which question, and what is allowed to exist only because it answers a question faster. Every design in the corpus is a different answer to "where does this fact live, and who maintains it".

10.1 The ladder

- **Derive it.** Answer the question from normalized facts at read time. Nothing to maintain, nothing to go stale; the cost is paid per read.
- **Index an existing fact.** Add the structure that turns a scan into a lookup. The cheapest derived object, but it taxes every write and only helps questions the schema can already express.
- **Materialize it.** Store the aggregate on the parent. Big read wins, a maintenance cost on every child write, and a correctness question whenever a write path forgets it.
- **Copy it down (rolldown).** Put parent information on the child to avoid a join. Measured as a package with its indexes, never as a bare column.
- **Copy it out (cache).** Serve the answer from beside the database, outside the authoritative transaction. It can be the lowest-latency hot read for the measured cacheable workload, and it is the step that crosses the transaction boundary — so the design acquires a separate freshness and failure-domain contract. Indexes, rollups and rolldowns carry their own maintenance correctness; what is special here is where the copy lives, not that it is copied.




Figure 6: **Placement and ownership: where an answer may live.**

Form: structure · Evidence: conceptual illustration

> **Text equivalent.** The leaf row stays canonical for row questions. **Derive stores no additional copy.** The remaining rungs introduce some stored derived structure or copy, each owning its own maintenance cost and its own correctness contract: **index** adds a copy of an ordering, **materialize** copies the aggregate upward, **copy down** copies a parent key onto the child, and **copy out** serves the answer beside the database under a freshness contract. The ladder is ordered by how much read work each stored structure removes. The figure is a map of the corpus's decisions and carries no measured value.

Direct evidence

Ask what the schema must be able to **answer** before asking how fast it answers. Two measured answerability failures make this concrete: refunds were unanswerable in 14 of 15 ticketing designs, and no reserved-seating design could size a hold window because releasing an expired hold erases the evidence that it existed.

v2-07-refund-answerability-and-storage · run_replicated · answerability is a schema fact, not a timing; the +33–35% storage delta is a relation-size difference measured in the primary run and deterministic for the same dataset and design; it is not a repeated timed result; the P3 -> X1 read rows of this run are excluded, because the difference belongs to the configuration as a whole rather than to one decision inside it; the read phase of this claim's primary anchor 20260920T234953Z was client-CPU throttled by a design-dependent

amount (2.3 s for p2_precreated_skip_locked to 58.1 s for r1_inventory_row, out of about 1085 CFS periods), so that report's read figures are not quotable: the hazard reproduces on the current harness (20260929T165533Z, 20260929T170353Z: r1_inventory_row 32.3 s of ~63 s of periods, both orders), and the 2026–09–30 budget calibration shows the client's quota is a symptom rather than the ceiling - the read level on this machine is set by the database's share of four CPUs, and adding a client core removes the client's throttling while making the reads slower. Answerability and the r05 storage/speed result are unaffected: the ledger still answers r05 at 30.3k and 33.0k ops/s against the primary's 32.2k, and at the new 2-worker read footprint the r05 result reproduces independently at 32,164 ops/s (20260930T164028Z), so that number has a footprint-2 footing; all fifteen designs now have one (the eleven-design tranche 20260930T201732Z/20260930T203913Z adds the rest, unthrottled), while this claim's primary anchor's own footprint-8 read figures remain not quotable (design-dependent inflation, 1.09x to 2.22x). **Correction, 2026–09–30: an earlier caveat here said the two many-row queries (q02_band_events, q05_band_tickets_sold) had client-bound levels; it is withdrawn.** A one-worker tranche (20260930T232926Z, 20260930T233744Z) shows that in-flight measured with the **mean** latency is exactly 1.000 in all 72 cells at one worker and 2.00 at two, so every read cell in the family is a store measurement at a stated footprint, and only its magnitude depends on the concurrency. Two errors produced the withdrawn caveat: q05 does not return 28 rows (all three variants return one - COUNT/SUM with no GROUP BY), and in-flight computed from the **median** understates the concurrency by the latency skew (mean/p50 up to 2.7x), which reads exactly like a worker idling between fetches. The primary anchor's **PostgreSQL read cells have since been re-stated** on the footprint-2 footing (analysis 20261001T-read-cells-restated: all fifteen designs, both orders, every cell store-bound at 2.00 operations in flight), so its `pg-single` read figures may be replaced rather than caveated. All fifteen designs have since been measured in a **single run**, twice and in reversed order (20261001T100948Z, 20261001T103931Z): 0 throttled periods in all 30 read phases and every one of the 270 cells store-bound at 2.00 operations in flight by the mean latency, so the family's levels are jointly comparable within that session. Two consequences for quoting: the top group (h0, h1, r1, r2, p4) differs by 4%, inside that session's own order term, so its internal ranking is not quotable - only the 1.5x gap between that group and the per-seat group is; and c1_count_naive carries a 40% position term (first of one order against last of the other), so its q01 level should not be quoted from these runs. Its two **YugabyteDB read arms have no replacement** and remain an explicit coverage gap; the storage percentage depends on the rule and on the page layout, and must not be quoted as one number: tables only 33.4–35.2%, every relation 35.0–36.2%, indexes alone 37.7%; the same pair's relation sizes moved 0.26% (p3) and 0.41% (x1) between two runs 29 minutes apart, so the delta moved 0.9 percentage points; the index-only figure spans 37.4–37.9% across the five runs, so even there the rule is a band and not a point, and the 2026–10–02 replication's M4 (reproducible within 1%) is falsified by that movement - a tighter figure would need a vacuumed comparison, which is a different measurement; the answerability statuses are the harness's own audit of its own schema, computed as a pure function of the design and emitted inside the read phase; the 2026–10–02 replication therefore tests reproducibility across two whole runs and not the independence of the audit's rule, and it re-measured no timing · full card in the evidence registry index

v2-gap-02-hold-funnel-unanswerable · gap · a schema limitation, not a missing measurement · full card in the evidence registry index

10.2 Boundaries

Coverage gap

Placement says nothing about **physical** colocation. The corpus does not verify where a cluster put its data, so a placement claim here is a design claim, not a topology result.

10.3 The checklist

The eight questions, answered for this concept; the status in brackets is the evidence behind the answer.

- **Invariant.** After every acknowledged mutation, a derived answer equals what the base facts imply. [direct]
- **Where the information lives.** In the base table, in a copied parent key on the child, in an aggregate on the parent, or inside an embedded child document. [direct]
- **Where the contention is.** The parent row that every child write touches once an aggregate or a document lives there. [direct]
- **What work moved from reads to writes.** Aggregation (rollup) and child retrieval (embedding) both move to the write path. [direct]
- **What state is derived.** Parent aggregates, copied parent keys, and embedded child arrays. [direct]
- **What can become stale.** An application-maintained rollup published outside the mutation's transaction, and an embedded slice that lags its table. [mechanism]
- **Where it stops working.** Embedding, once a parent's history grows without bound; a rollup, once its maintenance cost exceeds the read gain it buys. [gap]

- **The experiment that would settle it.** Isolated pairs at matched SQL, swept over cardinality and history so the crossing is visible. [direct]

11 Indexes and hot rows

CONCEPT · INDEXES AND HOT ROWS

Two different tools get confused because both look like “make the query fast”. An index changes how many rows the engine touches; a hot-row decision changes who may touch one row at the same time.

two different tools: the index narrows the scan, the hot row serialises the writers




Figure 7: **An index narrows the scan; a hot row serialises the writers.**

Form: structure · Evidence: conceptual illustration

> **Text equivalent.** Left, the index panel: a query follows a narrow index path to a small subset of rows, so the engine touches less — the index is a copy of an ordering and taxes every write to the indexed column. Right, the hot-row panel: several writers converge on one contended row, so they serialise and the design question is arbitration, not structure. The figure separates the two tools and asserts no rate.

11.1 Indexes

An index answers a question the schema can already express, at the cost of every write to the indexed column. In the charity tree the first index was the first large read win, and flattening the foreign key (a rolldown package) bought more still.

11.2 Hot rows

When one row is the contention point — one event’s ticket count, one product’s stock — the design question is arbitration, not structure. Pre-created seats taken by compare-and-set or `SKIP LOCKED` sold 4–8x faster than

any single counter row; the counter also blocks unrelated edits to the same row, which is a correctness-adjacent cost the throughput number hides.

11.3 Direct evidence

v2-01-normalized-index-first · run_replicated · PostgreSQL 1 node and YugabyteDB 1/3 nodes in one run; small scale; a single measurement per configuration, not a repeat; read score is a blended measure, not one query; the quoted point figures (13.3x, 20.5x) are the primary run's single levels: the whole-run replication of 2026–10–01 measured 9.7–15.5x for the same two relations while the absolute read scores moved 40–45% between its two runs, so the band and the ordering are what may be quoted, not the points · full card in the evidence registry index

v2-06-hot-drop-designs · run_replicated · one run of the experiment, a single measurement per configuration; the run has 42 cells of which 2 failed (C2 count (SER) on the two YugabyteDB topologies); those cells are not evidence; hot-drop workload only; every absolute throughput in the 2026–09–26 replication was 26–72% below the 2026–09–13 run for the same design and tier, so the 4–8x range reproduced while the numbers behind it did not; the range is quotable and the figures are not; the ratio moved between runs: p3 against c4 went 7.07 to 4.37 to 4.64 at 100 seats and 7.26 to 4.30 to 4.70 at 1000, and p2 against c4 went 3.97 to 3.25 to 5.78, so the range is a range, not a point, and individual ratios shift by up to 44%; the replication re-ran neither deliberately wrong control (c1_count_naive, h0_hold_naive_confirm), so it strengthens the comparison without re-firing the correctness control that the first run provided; r1_inventory_row recorded one trial of about 4x lower throughput than its siblings at each tier (122 and 117 against 468–653); whether that is a real instability or a harness artefact is unresolved, and r1 is the weakest comparison in the replication; two of the original sweep's five tiers (10 and 10000 seats) were not re-measured; p2_precreated_skip_locked moved 58–76% between the two same-day replications while the counters moved within 15% and p3 within 7%; it ran first in one and last in the other, so that design carries a position or warm-up effect as large as the comparison it takes part in, and the claim's pairing of p2 with p3 hides it - the >=3x result holds at both extremes; the anomalous r1_inventory_row trials of the first replication (122 and 117 against 468–653) did not recur in the reverse-order run, which makes a harness artefact likelier than a design property without settling it; the read phase of this claim's primary anchor 20260913T021206Z was client-CPU throttled by a design-dependent amount (0.2 s for p2_precreated_skip_locked to 29.5 s for h0_hold_naive_confirm, out of 633 CFS periods), so that report's read figures are not quotable. The hazard reproduces on the current harness (20260929T165533Z, 20260929T170353Z: r1_inventory_row loses 420 of 634 and 422 of 633 periods), and the 2026–09–30 budget calibration (20260930T000544Z, 20260930T000759Z, 20260930T001013Z) shows the client's quota is a symptom rather than the ceiling: at three client cores the client is not throttled at all and the reads are slower (52,884 -> 43,726 ops/s at 10 seats), because the third core comes out of the database's share of the machine's four CPUs (database throttled periods 238 -> 847 -> 1052). The claim's own basis is the race phase (sell rate), where one cell in fourteen designs shows throttling. The read family has since been re-measured at the study's new 2-worker read footprint (20260930T164028Z, 20260930T164834Z: four designs, client unthrottled at 0 of ~631 periods, every cell latency-bound at 2.00 operations in flight for 2 workers (with the mean latency; a median-based count reads 1.9)), so read levels are quotable only with the footprint attached. All fifteen designs now have a footprint-2 footing (the four-design tranche plus the eleven-design tranche 20260930T201732Z/20260930T203913Z, where no design throttles: 0 of ~631 periods in all 22 read phases), and this claim's primary anchor's own footprint-8 read figures remain not quotable: the inflation they carry is design-dependent, 1.09x to 2.22x, and it tracks how many periods the old client lost per design rather than anything about the designs. All fifteen designs have since been measured in a **single run**, twice and in reversed order (20261001T100948Z, 20261001T103931Z): 0 throttled periods in all 30 read phases and every one of the 270 cells store-bound at 2.00 operations in flight by the mean latency, so the family's levels are jointly comparable within that session. Two consequences for quoting: the top group (h0, h1, r1, r2, p4) differs by 4%, inside that session's own order term, so its internal ranking is not quotable - only the 1.5x gap between that group and the per-seat group is; and c1_count_naive carries a 40% position term (first of one order against last of the other), so its q01 level should not be quoted from these runs. · full card in the evidence registry index

11.4 Boundaries

The hot-row result is one workload at small scale on one host. Read it as “the counter row serialises everything”, not as a capacity figure.

11.5 The checklist

The eight questions, answered for this concept; the status in brackets is the evidence behind the answer.

- **Invariant.** The answer must not change because an access path changed; an index may only change how the answer is found. [direct]
- **Where the information lives.** In the table. An index locates rows; it does not hold the answer. [direct]
- **Where the contention is.** The single hot row that a counter or an aggregate lives on — one event row, one parent. [direct]
- **What work moved from reads to writes.** Maintaining an index, or a counter, is write work bought to make reads cheap. [mechanism]

- **What state is derived.** Nothing, for an index. A counter or rollup column is derived, and belongs to the derived-state concept. [mechanism]
- **What can become stale.** A rollup column can disagree with its entries. An index cannot be stale, only unused. [mechanism]
- **Where it stops working.** On a table small enough that the whole relation is cached, an index stops paying — measured only as a control that could not fire at 3,600 rows. [mechanism]
- **The experiment that would settle it.** An identical-SQL index-versus-no-index pair, plus a writer sweep to show where the hot row takes over. [direct]

12 Concurrency control

CONCEPT · CONCURRENCY CONTROL

Two strategies at minimum: check a version and retry, or take a lock before updating. Both protect the same invariant; they differ in where contention is paid and what the failure looks like.

12.1 Optimistic (version-checked)

The writer reads, checks that the version is unchanged, writes conditionally, and retries on a mismatch. Under low contention it is close to free; under high contention retries become the workload. Under one hot key and 16 writers, lock-before-update measured about 1.6–1.8x the optimistic design across four fresh runs in both design orders, and the retry budget does not explain the gap: removing it moves the ratio by 1.1% to 3.2%.

12.2 Pessimistic (lock-before-update)

The writer waits for the row, then updates. With pessimistic locking, contention is primarily paid as waiting/blocking rather than optimistic conflict retries; depending on the workload that may increase **or** decrease observed latency. Application-level retries can still be required — for deadlocks, lock timeouts, serialization failures or other transient failures — so the retry loop does not universally disappear. On a single engine primitive, `SKIP LOCKED` and compare-and-set both avoid the counter-row bottleneck measured in ticketing.




Figure 8: **The invariant recheck, not the lock, rejects an operation that has become invalid.**

Form: sequence · Evidence: conceptual illustration

Text equivalent. Two parallel sequences over one row at version 5. **Optimistic**: both writers read version 5; R1′s `UPDATE … WHERE version = 5` updates one row and moves the version to 6, so R2′s conditional update touches zero rows and R2 re-reads and retries. **Pessimistic**: R1 takes `SELECT … FOR UPDATE`, R2 waits, R1 rechecks the invariant, updates and commits, then R2 acquires the lock and rechecks the invariant before deciding. In both panels the lock or the version check serialises the writers, and the **invariant recheck** is what rejects the operation that has become invalid. The figure draws `v2-12`′s mechanism and asserts no rate.

12.3 The negative control matters here

An unchecked read-modify-write lost 93.7% of acknowledged updates in the same run that measured the lock advantage. A concurrency result without its lost-update control is not evidence.

v2-12-lock-vs-version-upper-bound · run_replicated · one key, one installed product, 16 writers; PostgreSQL single node, small scale; one fresh-load trial per run; five whole runs now support the ratio, but no run repeats the cell, and the -retries 1 setting was not among the controls (the budget controls used the default 8 against -retries 0); 1.76x is one point on a writer curve, not a curve; the upper-bound hedge is retired: the retry budget was re-run on 2026–10–02 at 16 writers in both design orders, default against -retries 0 (1.64x against 1.69x with the lock first, 1.57x against 1.56x with the version check first), a 1.1% to 3.2% difference, which agrees with

the primary's own retry control (1.60x against 1.61x) and means the advantage is not per-retry harness work; the re-scoped figure is a band of five whole runs on two days (1.56x, 1.57x, 1.64x, 1.69x, 1.76x); absolute throughput is day-specific, so only the within-run ratio travels · full card in the evidence registry index

12.4 Where the two designs cross

The lock is not simply faster. Swept across concurrent writers on one hot key, it gives up about 5–10% of the version check's throughput at one writer — 0.905x, 0.939x and 0.948x in three whole runs — and leads from two writers up: 1.035x, 1.106x and 1.166x at 2, 1.56x–1.69x at 16, and 1.73x–1.96x at 64, reaching 1.68x at 32 in the first sweep. The movement is on the optimistic side: its throughput falls about 2.3x from one writer to 64 while its conflict count rises from 0 to about 25,000. That correlation is not an explanation, and the obvious one was tested and rejected — with the retry budget set to zero the ratio at 16 writers does not narrow (1.60 against 1.61 in the first control, 1.1%–3.2% in the replications), and the design that never retries moves by the same amount as the one that does. One run is an exception worth naming: a single 1-writer run measured 3.85x, not because its order changed but because the version check itself read 306 ops/s there against 1,286 in another run at the same level and order, with no throttling recorded. So "which is faster" has no answer without the concurrency level, and the interval where the ordering reverses — between one and two writers — is what a recommendation should name.

v2-17-optimistic-pessimistic-crossover

normalized facts · run_replicated

Under one hot key a bounded-retry version check (c1_optimistic_version) and a lock-before-update (c2_pessimistic_lock) cross over between one and two writers: in the primary sweep the lock delivered 0.89x the version check's throughput at 1 writer (1,177 against 1,329 ops/s) and 1.10x at 2 (1,285 against 1,167), rising to 1.68x at 32 and 1.60x at 64, while the version check's throughput fell 2.9x across the sweep and its conflict count rose from 0 to 21,301. Three whole runs on 2026–10–02 reproduced the crossing (0.905x, 0.939x and 0.948x at 1 writer; 1.035x, 1.106x and 1.166x at 2) and the divergence above it (1.56x-1.69x at 16 writers and 1.73x-1.96x at 64, in both design orders), with the version check's conflicts rising from 0 to about 25,000 and its throughput falling from 1,286 to 563 ops/s. One further 1-writer run measured 3.85x because c1 itself read 306 ops/s there while another run at the same level and design order read 1,286; no client or database throttling was recorded, and the added version-check-first runs read 0.905x and 0.948x at that level, so the excursion is reported as unexplained rather than as an order effect.

Trials: 23 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: PostgreSQL single node, small scale, one hot key; one fresh-load trial per run; the 2026–10–02 tranche measured the pair at 1, 2, 16 and 64 writers in both design orders, and at 16 writers with the retry budget at zero, but the primary's 4, 8 and 32-writer levels were not re-measured, so the claim's 32-writer point (1.68x) rests on the primary alone; we tested the obvious explanation for the lock's advantage and it failed: with the retry budget set to zero the c2/c1 ratio at 16 writers is unchanged within 1.1% to 3.2% in both design orders, and c2_pessimistic_lock, which never retries either way, moved by the same amount as c1, so the advantage cannot be put down to retry work; the primary's seven runs used two phase sets (the first four also ran read and write phases); the contention metric should not depend on that, but it is an assumption rather than a measurement; at 1 writer the unsafe control x1_lost_update_control cannot lose an update because there is no concurrency, so its gate cannot fire: three runs that included it at that level (20261002T162400Z-w1, 20261002T162737Z-w1 and 20261002T165329Z) record a failed x1 cell, and the claim's control_coverage comes from the levels at two writers and above, where x1 lost 50.0% and 93.7%-98.0% of acknowledged updates; one 1-writer run (20261002T162737Z-w1) measured 3.85x because c1 read 306 ops/s there against 1,286 in the other run with the same design order; the version-check-first runs gave 0.905x and 0.948x at that level and no client or database throttling was recorded in any of them, so the excursion is reported as unexplained; absolute throughput is day-specific: c2 measured 869 ops/s on 2026–09–23 and 1,056 on 2026–09–26 at identical settings, phases and writer count, so only the within-run ratio is carried across days

Source: studies/04-configuration-portal/reports/20260923T0011Z-ctlC-w1.md · run 20260923T0011Z-ctlC-w1 · tag run/04-configuration-portal/20260923T0011Z-ctlC-w1

12.5 Boundaries

One key, one engine, small scale. The 16-writer ratio is a band of five whole runs on two days; the 32-writer point rests on the primary alone, and one 1-writer run is an unexplained exception.

12.6 The checklist

The eight questions, answered for this concept; the status in brackets is the evidence behind the answer.

- **Invariant.** The business rule holds under concurrent writers: no lost increment, no oversold seat, no double sale. [direct]
- **Where the information lives.** In the current row the writers contend for, plus whatever version or lock column guards it. [direct]
- **Where the contention is.** One hot key or row; the corpus measures one event or one installed product. [direct]
- **What work moved from reads to writes.** Conflict resolution itself: a version check or a lock turns a read-then-decide into one guarded write. [mechanism]
- **What state is derived.** Nothing in this concept; a counter or rollup a concurrent writer maintains is derived state, which is its own concept. [mechanism]
- **What can become stale.** The value a writer read before losing the race — which is why the guard has to be part of the write. [mechanism]
- **Where it stops working.** The ordering is workload-dependent: at one writer the version check leads, and from four writers the lock leads by 1.26–1.60x. [mechanism]
- **The experiment that would settle it.** A writer-count sweep of the same pair with retries disabled, so the lock's advantage is separated from per-retry work. [direct]

13 Derived state and history

CONCEPT · DERIVED STATE AND HISTORY

Two different things are stored beside the canonical row, and conflating them produces the wrong design. **Derived state** — a rollup, a rolldown, an external read copy — optimizes an answer from current state and owes its maintainer a correctness contract on every contributing write. **Retained history** — an event or ledger table, an audit trail, a temporal history, snapshots — preserves information that would otherwise disappear. Derived state can be rebuilt from the facts; retained history cannot be rebuilt from a current-state-only representation.




Figure 9: **One canonical fact feeds a derived current-state copy or a retained history.**

Form: structure · Evidence: conceptual illustration

> **Text equivalent.** A canonical fact has two stored branches. A **derived current-state copy** (rollup or rolldown) answers from current state, can be rebuilt from the facts and owes its maintainer a correctness contract on every contributing write. **Retained historical facts** (an event/ledger) preserve information that would otherwise disappear and cannot be rebuilt once a current-state-only representation has destroyed it. The figure asserts no rate.

13.1 Maintenance is the design

A rollup can be maintained by the application or by a database trigger. The trigger makes the guarantee structural; the measured cost was 4.0–5.7x on whole-configuration replacement across three runs (median 4.94x), with a 22–46x worse latency tail, while the application rollup kept writes near the reference. That ratio is a reading at one size, not a property of the design: crossed with the size of a replacement it runs about 1.1–3.2x at 10 entries per installation, 2.5–9.0x at 60 and 10–24x at 240, because the trigger does its work once per row written while the application does one statement per replacement. Those are ranges and not single figures, and the ranges are wide: the runs at each size disagreed by more than a factor of two, because the machine's speed wanders during a session — sometimes up, sometimes down. What survives the wandering is the ordering: the same ranking appeared in every arrangement that was measured, so treat the ranking as the finding and the size of the penalty as uncertain by a factor of two or more. Neither is universally right: choose who must never forget, and then ask how large a replacement is.

v2-13-trigger-rollup-cost · run_replicated · PostgreSQL single node, small scale; three whole runs, each with three repeats of the measurement per configuration; the experiment was repeated as separate whole runs on one machine, so it is not independent of this hardware and is still exposed to this host's measurement hazards; repeating the measurement in that configuration disagreed by 35–115% across the three runs, more than the ~20% this project allows, so only the direction and an order of magnitude are supported, not a single ratio; the ~15x read gain belongs to the earlier single run and was not re-measured in the replication; the 6.85x figure from the earlier one-off run did not reproduce and must not be quoted; the trigger's product is a structural guarantee, not speed; the three runs realized only two distinct design orders (seeds 202 and 303 coincided, and in the sibling read tranche all three seeds coincided); randomized order describes the method, and the realized order is recorded in each manifest; the penalty is size-dependent, not a constant: crossing the same pair with entries per installed product gives 2.07x at 10 entries, 4.38x at 60 and 24.20x at 240, so this ratio holds at the small scale default of 60 entries and must not be quoted as a property of the design without the size (v2–18-maintenance-size-interaction) · full card in the evidence registry index

v2-18-maintenance-size-interaction

rollups / materialized aggregates · run_replicated

Crossing who maintains the parent rollup (trigger n3_rollup_trigger against application n4_rollup_app) with the size of a replacement (10, 60 and 240 entries per installed product) shows the maintenance penalty is a function of size rather than a constant: across 7, 9 and 7 runs at the three sizes the application design delivers roughly 1.1–3.2x the trigger design on whole-configuration replacement at 10 entries, 2.5–9.0x at 60 and 10–24x at 240, the ordering by size holding in every arrangement measured, and no rollup mismatch is recorded at any size.

Trials: 7 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: PostgreSQL single node, small scale, one measurement per tier across 10, 60 and 240 entries per installed product, so the curve carries no spread at any level; one operation only: w05_replace_all replaces the whole configuration, and a workload that appends a single entry would sit at the low end of this curve at any size; the axis is capped by the small scale at 240 entries and the curve is still rising steeply there, so nothing here bounds where it flattens; no negative control in these three runs; control_coverage is recorded absent rather than implied; two designs cannot separate the two mechanisms that predict this shape: the trigger fires once per row written, and its per-row work may also be heavier than the application's single statement; at 60 entries per installation the three runs give a median of 3.42x, about 22% below the 4.38x the first run recorded and below the 3.99–5.69x v2–13 replicated for the same operation, so the corroboration of v2–13 here is approximate - same operation, same size, same direction - and not a match; the ratio at each size is a band describing what has been seen, not a range a future reading must fall inside: 7 runs at 10 entries span 1.06–3.15x, 9 at 60 span 2.51–8.95x and 7 at 240 span 10.20–24.20x, and the two lower bands touch when everything is pooled (3.15 against 2.51) even though every individual arrangement ordered them correctly; arrangement in time decides what a repeat can see: three runs of a size placed next to each other in the session agreed within 15–55%, while the same three runs spread across the session (a Latin square) spread by about 100% - the sequential layout understated the uncertainty because adjacent runs share the session's state; a reference cell measured immediately before and after this tranche moved 445 to 640 ops/s, +44%, so the session was not a stable instrument and the drift it produced is measured rather than inferred; the reference is a different operation from the one compared here and bounds the movement without being its exact size; a band built from six runs did not contain a seventh: tier 10 measured 1.06 against the 1.34–3.15 range the earlier tranches had established; the session does not drift in one direction, it wanders: three readings of one reference cell taken through a single tranche gave 8.64, 5.21 and 8.53, so reading only the start and the end of that tranche would have reported no movement while the middle sat 39% below both; the ratio is more portable than the absolute numbers: over those same three reference readings the ratio spread 40% against 49% for the application design's throughput and 114% for the trigger's, because a session term shared by both designs cancels in the ratio

Source: studies/04-configuration-portal/reports/20260926T152621Z.md · run 20260926T152621Z · tag run/04-configuration-portal/20260926T152621Z

13.2 History is answerability

Retained history is not faster; it is the difference between being able to answer a question after the event was undone and not. A current-state-only representation that overwrites or deletes the earlier fact cannot reconstruct it, whichever physical structure stores the answer — an event table, an audit trail, a temporal history or a snapshot can each supply it. The refunds window was unanswerable in 14 of 15 ticketing designs and cost about 33–35% more storage with a ledger. That is a correctness purchase, priced honestly. Retaining history does not itself fence concurrent writers or order events; that is a separate, explicit decision.




Figure 10: **Undoing the state is not the same as erasing the evidence.**

Form: structure · Evidence: conceptual illustration

> **Text equivalent.** Left, a current-state-only representation overwrites a Donation's PAID status on refund, so "was this ever paid?" becomes unanswerable. Right, appended `DonationEvent` rows (PLEDGED, PAID, REFUNDED) answer the same question: undoing the state keeps the evidence. The figure is the difference between derived state and retained history, and it asserts no rate.

13.3 Direct evidence

v2-13-trigger-rollup-cost · run_replicated · PostgreSQL single node, small scale; three whole runs, each with three repeats of the measurement per configuration; the experiment was repeated as separate whole runs on one machine, so it is not independent of this hardware and is still exposed to this host's measurement hazards; repeating the measurement in that configuration disagreed by 35–115% across the three runs, more than the ~20% this project allows, so only the direction and an order of magnitude are supported, not a single ratio; the ~15x read gain belongs to the earlier single run and was not re-measured in the replication; the 6.85x figure from the earlier one-off run did not reproduce and must not be quoted; the trigger's product is a structural guarantee, not speed; the three runs realized only two distinct design orders (seeds 202 and 303 coincided, and in the sibling read tranche all three seeds coincided); randomized order describes the method, and the realized order is recorded in each manifest; the penalty is size-dependent, not a constant: crossing the same pair with entries per installed product gives 2.07x at 10 entries, 4.38x at 60 and 24.20x at 240, so this ratio holds at the small scale default of 60 entries and must not be quoted as a property of the design without the size (v2–18-maintenance-size-interaction) · full card in the evidence registry index

v2-09-postgres-ledger-ratio-unsettled · run_replicated · the stable direction is measured at 1,000 seats across 8–128 buyers and at 32 buyers across all five tiers; the buyer-count axis is not swept at the other four tiers, so the full buyer x tier surface is open; one primary run per (buyers, order) cell, with a reference cell that moved 8.6% between the two ends of the tranche, so a level whose two orders differ by more than that is placed by the ratio and not by the absolutes; the direction is stable but the ratio is not: the eleven run medians span 1.06–5.10 (1.22–1.86 with the collapsed 8-buyer cell set aside), so the cost is a range and not a point; the 8-buyer level's pooled median is not interpreted: a recurrence test of six runs and twelve cells (2026–09–29, tag study-02/v2–09–8buyer) found four low-throughput events in 60 trials, readings of 619–655 ops/s against a session normal of about 2500 (a 4x drop), and they hit both designs (three of the four in the CAS arm) and both orders, so the low mode is a property of this buyer count's very short trials and not of the ledger; the original p3-first cell read as a state change only because its slow trials were its last three, which set the cell median; the primary evidence is from a different harness state (phases verify,write,race,churn on a five-day-old image), so comparing it with this tranche mixes the confound with a period effect and the re-scope is stated as a direction, not a ratio; one side of the primary comparison is a partial configuration on yb-cluster3 (medians of two measurements); at 32 buyers the ledger was slower in all ten tier x order cells of two 2026–09–29 runs (ratios 1.021–1.606) and below the 128-buyer pooled ratio at every tier (1.06 vs 1.08, 1.06 vs 1.24,

1.23 vs 1.41, 1.56 vs 1.85, 1.56 vs 2.51), so the primary's tier-wide reversal does not reproduce anywhere on the axis; those two runs are anchors but are not counted in the eleven-run replication record, which is the buyer-count sweep at one tier; at 32 buyers and 10–100 seats the direction sits at the measurement's floor: only 3 of 10 trial pairs at 10 seats and 6 of 10 at 100 favour the CAS design, with cell spreads of 86–174%, so those two tiers support the median and not a per-pair claim, while the 1,000-seat cell reproduced the sweep's ratio a day later within 1% (1.245 and 1.219 against 1.233 and 1.219); the 8-buyer low-throughput mode is not a quota effect on either side: the twelve cells' per-trial client_cpu entries (present since the study's first commit, and corrects an earlier limit here that said the client was not recorded) show zero client throttling and *more* client CPU in the slow trials (2.6–2.8 s against about 1.9 s), so the client waits rather than starves, while the database container's cpu.stat throttled about 4 ms across the collapsed cell; the cause is narrowed to a latency excursion on the response path and is not identified further, since no per-trial plan or server-side clock is recorded; three of the four 8-buyer low events were single trials that recovered on the next trial and one spanned consecutive trials, so 'persistent collapse' and 'transient spike' are names for where the event fell in the cell (a five-trial median cannot distinguish them at a ~7% event rate); no 8-buyer magnitude is quoted from either tranche · full card in the evidence registry index

13.4 Boundaries

The ledger's write cost depends on the engine and on the size of the event — about 1.1x at 10 seats against about 2.5x at 100,000 on PostgreSQL — and the design order moves the absolute throughput at the smallest sizes without changing which design is faster, so quote the tier and the run's own range rather than a single headline multiplier. The load-time multiplier is not published at all.

13.5 The checklist

The eight questions, answered for this concept; the status in brackets is the evidence behind the answer.

- **Invariant.** Published derived state agrees with the entries it summarises, and retained history is never erased by the mutation that follows it. [direct]
- **Where the information lives.** In the base entries, in an aggregate on the parent, and — for answerability — in an append-only record that the mutation does not overwrite. [direct]
- **Where the contention is.** The parent row an aggregate is maintained on, which every child write touches. [direct]
- **What work moved from reads to writes.** Aggregate maintenance. History is different: it is write-only work bought for the questions it lets you answer later. [direct]
- **What state is derived.** The rollup columns. History is a fact, not a derived value, which is why it is not "stale" when it disagrees with current state. [direct]
- **What can become stale.** Any aggregate published after the commit that produced it — the drift control demonstrates it. [mechanism]
- **Where it stops working.** A per-row trigger's cost grows with the rows a replacement touches — now measured at three sizes, six runs each (about 1.3–3.2x, 2.5–9.0x and 10–24x at 10, 60 and 240 entries, with the ranking holding in every sweep) rather than stated as a tendency; history costs storage (33–35% for the ledger). [direct]
- **The experiment that would settle it.** The n3/n4/x2 isolation pair, swept over entries per installation to find where the two maintenance strategies cross. [direct]

14 Expiry and clock authority

CONCEPT · EXPIRY AND CLOCK AUTHORITY

Expiry is a write that no client issues. That makes it the place where “whose clock is right” stops being philosophical: the sweeper, the application clock and the database all disagree eventually, and the design must say who is allowed to decide.

14.1 What the corpus shows

YugabyteDB refused valid hold confirmations under a guarded design — every refusal of that kind was **transient**, meaning the identical statement re-issued inside the refusing transaction matched every seat — and retrying the refused statement once removed every refusal at no measurable cost. The practical lesson is smaller than it sounds: an expiry design needs a retry story, because the mechanism can refuse a correct write.




Figure 11: **When an abandoned hold gives its seat back, and whose clock says so.**

Form: sequence · Evidence: implemented design contract

> **Text equivalent.** The figure lays out the expiry designs side by side — lazy expiry judged by the database clock, a sweeper that decides when a seat returns, and an application clock shown as a negative control that can release a seat early. It is the contract the reserved-seating designs implement and carries no measured value; the funnel that would size a hold window remains unanswerable (`v2-gap-02`). Source: `studies/03-reserved-seating/diagrams/e_expiry.puml`

14.2 What it cannot yet show

No design can answer the funnel that would size a hold window. Releasing an expired hold clears the row, so an expired hold is indistinguishable from a seat that was never held. The missing evidence is a schema property, not a missing measurement.

v2-10-guarded-confirm-refusals · run_replicated · v1 matrix run, a single measurement per configuration; the claim is about refusals, not throughput; retry-once is a design variant (S1r), not a tuning flag; the replicated refusals are few and tier-bound: 2, 3 and 1 refusal events in the correct designs across two whole runs, all at the 10,000-seat tier except s2's single 1,000-seat refusal in the reversed order, so the claim is that refusals happen and are transient - not a rate, and not a tier law; the YugabyteDB arm measured four tiers (10 to 10,000 seats) while the PostgreSQL control measured five (10 to 100,000), because that is how the study configures its tiers per engine;

'the guarantee held everywhere' therefore means everywhere the PostgreSQL arm ran; the refusals are the harness's own classification of its own designs, and the transient sub-class is decided by re-issuing the statement inside the refusing transaction (AM-01), so this replicates the mechanism and its detection, not an independent definition of a valid hold; the 2 GiB podman-machine blocker recorded in CONTEXT.md is a multi-node limit: a single-node YugabyteDB arm fits and completes here, which is what makes this replication possible, while yb-cluster3 remains unmeasurable on this machine; the spread figure is the refusal count's own movement, not a throughput spread: s1_conditional_update refused 2 times in the forward run and 3 in the reversed one, so the count moves 40% across the two runs and the phenomenon is established, not quantified · full card in the evidence registry index

v2-gap-02-hold-funnel-unanswerable · gap · a schema limitation, not a missing measurement · full card in the evidence registry index

14.3 Boundaries

Do not transfer a single-engine expiry result to a clock-synchronised cluster without a placement and clock test; the corpus has neither.

14.4 The checklist

The eight questions, answered for this concept; the status in brackets is the evidence behind the answer.

- **Invariant.** A hold made while it is valid is honoured, nothing is granted or sold after expiry, and no seat leaks. [direct]
- **Where the information lives.** In `expires_at` on the held row — or, in one variant, once on a cart row rather than copied to every seat. [direct]
- **Where the contention is.** The seat rows of one chosen block, which cannot be skipped the way study 02′s interchangeable seats can. [mechanism]
- **What work moved from reads to writes.** Expiry checks move to the moment of use, and a sweeper does the work at rest instead of on the buyer's path. [mechanism]
- **What state is derived.** Availability is derived, not stored: with lazy expiry an expiry changes no row, so no exact availability counter can be maintained. [mechanism]
- **What can become stale.** Any judgement of expiry made from an application clock, and any cached availability figure. [direct]
- **Where it stops working.** When the clock is not the database's — the injected-skew control fired — and when the sweeper stalls, which leaks seats. [gap]
- **The experiment that would settle it.** An injected application-clock skew and a sweeper outage, beside the honoured-hold invariant. [direct]

15 Cache consistency

CONCEPT · CACHE CONSISTENCY

A cache is a read copy with a freshness contract. The design question is not “which cache pattern?” but “what does a hit **prove**, and who can observe every change?”.

Invalidation and publication fencing are different operations. Invalidation removes or marks an existing cache entry stale. It cannot stop a reader that loaded an older value from publishing it afterwards — which is exactly the race the stale-fill figure below draws. A **publication fence** is the additional check that refuses that fill when the source moved after the reader took its snapshot; its strongest form is **source-generation validation**, where the filler checks the authoritative current generation against the one it observed before publishing. A **sink-side fencing token** is a different mechanism: the protected sink remembers the highest token it has accepted and rejects an older one, so it orders operations only once a newer token has actually reached the sink. Neither is **cache CAS**, which conditionally modifies cache state against an explicitly stated expected generation, and neither is **hit validation**, which checks a served value against authoritative state at the hit boundary. Writing “invalidation is a fence” makes the fence sound like a deletion, and the deletion is the part that does not close the race. This is the concept the external-read-copies family exists to hold.

source correctness belongs to the mutation; copy correctness belongs to the publication




Figure 12: **The cache is a non-authoritative read copy beside the authoritative database.**

Form: structure · Evidence: conceptual illustration

> **Text equivalent.** A client reaches the application, which talks to the authoritative source database and to a cache. Mutation and source reads belong to the database; **source correctness** is decided by the mutation itself (a lock plus invariant recheck, or a conditional update). The cache holds a **non-authoritative read copy**: **copy correctness** is decided by propagation, publication or hit validation, and the declared freshness contract says what a hit is allowed to mean. The figure is the architecture the races below take place in, and it asserts no rate.

15.1 The flow: contract first, pattern last

- **1. Name the contract.** *Strict after acknowledgement*: a read that starts after a write to the same key is acknowledged must not return an older committed value. Or a **bounded-staleness** budget, or **session / read-your-writes**, or best effort. State which one, on the page.
- **2. Establish change-observation completeness.** Can every mutation participate — bulk jobs, migrations, deletes, recreates, external writers? If not, a strict **cache-hit** proof is unavailable: use an authoritative read, a complete change source, or downgrade the contract explicitly.

- **3. Identify the source capabilities.** A frozen schema still supports service-side generations and authoritative reads; an owned schema can add a monotonic version, a transactional outbox and a deletion generation. These improve proof and recovery; they do not confer freshness.
- **4. Choose topology and the publication protocol.** Process-local versus shared decides the coordination domain; cache-aside versus write-through decides who fills or republishes. State the ordering proof — one of the named mechanisms below.
- **5. Add performance controls separately.** A bounded fill lease suppresses duplicate fills while it is held; a hard TTL bounds how long an entry is **eligible to serve** and probabilistic early expiry spreads the refill work. None of these supplies currentness.

Forbidden is separate from stale. A value that is impossible or was never committed is a defect under every contract, not a relaxation of one. **Relaxed** is a family of weakenings rather than one contract, so which member is in force has to be named:

- **Strict after acknowledgement** — the rule the comparison in this chapter is made against.
- **Session / read-your-writes** — a client can see its own committed writes.
- **Bounded staleness** ($\leq \Delta$) — a hit may lag the latest commit by at most a declared Δ.
- **Eventual freshness** — convergence is required; no distance or deadline is declared.
- **Best effort** — nothing beyond a valid committed value is promised.

None of these permits a dirty, torn or uncommitted value, and no configuration measured here produced an impossible value — measuring that is how the sentence is checked rather than assumed. The relaxed contracts this study measured are unbounded-relaxed: compared with the strict rule below, they allow a committed but older value, without declaring how old it may be. They are therefore not bounded-staleness contracts, and counting how often they break the strict rule says nothing about whether they stay inside a Δ window.

15.2 The strict contract, written down

Strict after acknowledgement is the rule every configuration measured here is judged against, so it is worth stating formally rather than in prose. Let `W1` be a write to a key, `ack(W1)` the moment its acknowledgement is observed, `R1` a read of the same key, and `begin(R1)` the moment it starts.

`begin(R1) > ack(W1)` ⇒ `R1` must not return a version older than `W1`
unless a later write to the key supersedes `W1`

Every other contract is a weakening of that line, and the weakening must be named: a **bounded-staleness** budget, **session / read-your-writes**, or **best effort**. That line is the yardstick for the counts in this chapter — a “wrong read” is one that breaks it, not one that returns something impossible.




Figure 13: **The strict-after-acknowledgement contract, and the point on the timeline where it binds.**

Form: timeline · Evidence: conceptual illustration

> **Text equivalent.** A writer commits `W1`, the acknowledgement is observed, and a later read begins. The contract binds at `begin(R1) > ack(W1)`: the read must not return a version older than `W1` unless a later write supersedes it. Everything the book calls relaxed is a named weakening of that line, and a bounded-staleness contract adds a declared delta the measured cells do not declare. The figure draws the contract; the rates beside it are the registry's.

15.3 The named mechanisms, one primary failure mode each

A mechanism is not a synonym for freshness. Each one addresses one primary failure mode or control objective, and the "does not solve" line matters as much as the guarantee: several of these can be present and the contract still be broken.

Source correctness — arbitrating the mutation itself

These protect the authoritative row. They decide **who wins** a contended update; they say nothing about a copy that has already left the transaction.

Pessimistic lock + invariant recheck

Race closed	two database writers updating the same row
Mechanism	`SELECT … FOR UPDATE` serialises the writers, and the writer re-reads the row under the lock and rechecks the transition's precondition before applying it
Guarantee	serialisation: the two writers do not interleave. Rejecting the obsolete operation is the **recheck's** contribution, not the lock's — a lock alone guarantees neither
Does not solve	a stale read in another connection, a lost write outside the lock's scope, or any copy of the row

Evidence: active registered claim — `v2-12`

Conditional update / compare-and-set

Race closed	an update applied to a row whose state has already moved on
Mechanism	the expected state or version goes into the write itself (`WHERE … AND status = …`); a zero-row update reports that another writer got there first
Guarantee	the transition applies only while the row still satisfies the expectation, so the loser is rejected rather than merely serialised
Does not solve	the retry cost the loser now pays, and any copy of the row

Evidence: active registered claim — `v2-06`

Copy correctness — ordering what leaves the transaction

These protect the cache. One of them closes the stale-fill race; two of them — the fill lease and the TTL — are load controls that prove nothing about freshness.

Invalidation

Race closed	an entry that is still resident after its source changed
Mechanism	the writer removes or marks the entry stale after committing
Guarantee	once the invalidation has been applied, subsequent lookups of that cache entry miss or see it marked stale — call it what it is: a deletion with a message attached. Reads and fills already in flight are outside this guarantee
Does not solve	the stale-fill race. A reader that snapshotted S0 before the invalidation can still publish S0 afterwards; deletion orders nothing about a fill already in flight

Evidence: used by every write-through configuration measured here; on its own it never made a shared relaxed cache strict




Figure 14: **A lease orders ownership; a sink-side token and a source-generation check refuse the stale publish.**

Form: sequence · Evidence: conceptual illustration

Text equivalent. Two panels plus a distinction note. **Lease only**: filler R1 holds lease 7, its source read outlasts the lease, R2 takes lease 8 and publishes S1, and R1 then publishes S0 — nothing in the lease rejects it, because a lease orders ownership rather than publication. **Sink-side fencing token**: R1 holds token 7 and R2 token 8; when R2's `(S1, token 8)` reaches the sink first, the sink records 8 and rejects R1's later `(S0, token 7)` — so the ordering depends on a newer token having actually reached the sink. **Distinct from both**, as the closing note says: source-generation validation checks the authoritative current generation before publishing and can refuse token 7 even when no token-8 operation has reached the sink. The figure is why the fill-lease card claims load coordination and not freshness, and it asserts no rate of its own. Source: `book/assets/sources/fig_lease_vs_fence.puml`

Publication fence — source-generation validation

Race closed	a reader that snapshotted committed state S0 republishes it **after** a writer commits S1 and invalidates
Mechanism	before publishing, verify that the source generation still equals the generation the reader observed; refuse the fill if it moved
Guarantee	the stale-fill race specifically — "publish after commit" is necessary and **not** sufficient. In the measured strict writer protocol the writer fences before and after the commit and treats the acknowledgement, not

	the commit, as the contract boundary; a strict contract can also be established without writer-side fencing, by synchronous source validation or an authoritative read
Does not solve	an unobserved writer, a dirty source read, or an indefinitely stale hit that is never revalidated

Evidence: active registered claim — `v2-15`

Source version token validated at the hit boundary

Race closed	a hit that never consults the source version
Mechanism	every hit compares the entry's version against the source's current version and misses on a mismatch
Guarantee	a process-local cache can be answerable: the hit carries its own proof — **provided** every relevant mutation advances the token atomically, including deletes, recreates and writers outside the application, and the validating read is authoritative enough for the declared contract
Does not solve	the read cost it adds, and a shared relaxed cache that never consults the token — an unconsulted token is decoration, not a guarantee

Evidence: mechanism demonstrated — the owned process-local arms of `20260921T-survey3`; no registered rate for the validation cost

Fill lease

Race closed	duplicate concurrent fills of the same key — a stampede
Mechanism	a bounded lease lets one filler work while the others wait, fall back or time out
Guarantee	Effect: duplicate fills are suppressed **while a valid lease is held**. Duplicate work can reappear if the lease expires or ownership is lost before the first filler finishes — which is exactly why a lease is not a fence
Does not solve	**any** freshness question. It is a load control; it guarantees nothing about the value filled

Evidence: newer evidence, signed but not yet registered — the churn configuration measured on 2026-09-23 demonstrates the lease path (`20260923T1100Z-churn1800-through`); no registry claim states a lease rate

TTL and early expiry

Race closed	an entry that would otherwise live forever, and the thundering herd that follows a mass expiry
Mechanism	a hard TTL bounds how long an entry is **eligible to serve**; probabilistic early expiry spreads the refill work before many entries reach the same deadline
Guarantee	Effect: logical validity is bounded, and refill work is spread. Neither is a hard upper bound on refill traffic
Does not solve	currentness. An entry inside its TTL is **permitted** to be stale, which is the opposite of a freshness proof, and early expiry does not by itself cap refill load

Evidence: active registered claim — `v3-01`, `v3-02`; hard expiry has still never been observed to fire

Transactional outbox

Race closed	a change lost between the commit and its asynchronous notification
Mechanism	the change is written in the same transaction as the mutation and consumed by the publisher, so the notification is durable and ordered after the commit
Guarantee	a committed change cannot disappear between the commit and its notification, and the delivery path is recoverable
Does not solve	freshness, and it is not universally required. **When** coherence depends on asynchronous publication, an outbox is what makes the committed change durably observable; strictness can also be established by synchronous source validation or an authoritative read, with no asynchronous step to protect. Even with an outbox, strict after-acknowledgement hits still need an acknowledgement policy and a read protocol that closes the window

Evidence: proposed / unmeasured — no committed measurement exists

15.4 What each mechanism is actually for

The dimensions are the point, and the header is short so no word breaks in a narrow column: **mutation** is whether the mechanism makes the source transition correct, **observation** whether a committed change is durably seen, **freshness** whether a read is proved current, **load** whether it changes how much work the system does, and **recovery** whether it helps reconcile after a failure. Reading a table like this is faster than holding eight cards in your head.

Mechanism	Mutation	Observation	Freshness	Load	Recovery
Pessimistic lock + recheck	yes	—	—	may cost	—
Conditional update / CAS	yes	—	—	may cost	—
Invalidation	—	partial: clears, does not fence	partial	—	—
Publication fence — source-gen. validation	—	—	yes, race-specific	—	—
Source version at hit boundary	—	—	yes	read cost	—
Fill lease	—	—	—	yes, while held	—
TTL / early expiry	—	—	bounds eligibility, not proof	yes	fallback only
Transactional outbox	—	yes	prerequisite in async designs	—	yes

Evidence status. *Active registered claim*: the active `book/evidence/v6/claims.json` states it. *Newer signed but unregistered evidence*: a signed 2026-09-23 study analysis demonstrates the mechanism, but no registry claim states a rate for it. *Mechanism demonstrated*: the harness or study demonstrates the mechanism without a registered number. *Proposed / unmeasured*: no committed measurement exists.

15.5 Freshness is a contract, not a speed knob

Every controlled strict/relaxed pair differed by −14.2% to +12.3% in read throughput — inside the run's single-trial noise. Mechanically a strict protocol adds write-path fencing, but the claim beside this paragraph measures read throughput only and does not quantify that cost, so quote no write-path figure from it. What the read result does forbid is the other direction: never restate this as "strict freshness is free".

v2-16-strict-freshness-read-cost · run_replicated · read throughput only; the two fresh runs' trial spreads reached 22.8%, so only an effect larger than that could have been seen; small scale, closed loop, one machine; the strict/relaxed pair here is the owned write-through pair; a strict protocol's write-path cost is not measured · full card in the evidence registry index

15.6 The gain, and what the gain leaves out

Adding a cache to warm cacheable reads bought about 2.2–2.5x throughput in two whole replications (2.24x and 2.54x over the no-cache baseline). The tail did not reproduce as strongly: p99 fell from 27 ms to 9–10 ms, about 3x, not the order of magnitude the first run recorded. One thing is left out of the ratio: the cache's own CPU and memory are not counted against the database side, so it compares a database with a database **plus** a cache, rather than the same total resources arranged two ways (`conf-04`). A second comparison counts the resources the other way — both sides given the same total — and the two ways are labelled and never averaged together; the ratio between them (8.2k against 7.9k ops/s in the replications) is inside the run's spread and is not attributed.

v2-14-cache-throughput-gain · run_replicated · one machine, closed loop, small scale (800 donors), PostgreSQL + Redis cache only; the p99 clause did not reproduce: cached p99 8.5–10.1 ms against the baseline's 26.9–27.6 ms (about 3x), where the primary recorded 0.8–2.0 ms against 15.8–27.1 ms; the tail is suspected client-bound at this client budget and was not isolated with a plan or a footprint cell; warm cacheable reads only; the Redis container's budget is outside the db-only comparison (the equal-total framing is a separate claim, v3–03); absolute throughput is session-specific; only the within-run ratio travels; the 2.2–3.5x range remains supported only by the PostgreSQL single-node + Redis cells; do not transfer it to YugabyteDB, a cluster, or open-loop demand · full card in the evidence registry index

v3-03-equal-total-framing-labelled · run_replicated · what matters is that the two framings are labelled and kept apart, not the ratio between them; the fresh runs are 3.3% apart, inside the 17.7%/18.4% spread; the primary's 11k/8.0k figures did not reproduce; one host, small scale, each framing measured once per session · full card in the evidence registry index

15.7 The failure mode, measured against the strict rule

Three logical application instances sharing one Redis cache on write-through + **relaxed** freshness recorded 87.81% wrong reads on the owned model and 87.24% on the legacy model, while every relaxed configuration running on a single instance recorded none.

What the counter counts. The harness field is named `wrong_reads`, and it counts reads that broke the strict rule stated above: a read that starts after a write is acknowledged must not return an older value. In this configuration the offending values had been committed, just earlier — which is exactly what choosing a relaxed contract permits — and were **not** dirty, torn, uncommitted or impossible values. Read it as those broken promises, never as corruption: no configuration in that survey produced an impossible value, though the 2026-10-02 churn replication later recorded exactly one, reported with `v3-02`. Where a contract promises staleness bounded to a window, a further question arises that this run cannot answer — whether the stale values also stayed inside that window — so the counter is only evidence about staleness once the window is known.

The designs that keep the cache inside one process are the trap. The legacy process-local design's zero wrong reads are a **bypass** result, not safety: it served **0** cache hits across 15,578–21,756 reads, so there was effectively no cache to be wrong (`reports/20260921T-survey3.md`, the anchor of the registered claim). The owned process-local design did serve hits and checked the source version at the moment of the hit; those configurations recorded no broken promises. Checking the version at the hit is one way to obtain that guarantee — but whether it is the only way is not tested here, because no owned process-local design without the check was run. Read it as the mechanism these results are consistent with, not as a controlled removal of one part. A private in-memory lease cannot coordinate separate instances, and a source version token that is never consulted at the hit or at publication does not make a shared relaxed cache strict.




Figure 15: **The stale-fill race, and the source-generation check that closes it.**

Form: sequence · Evidence: observed result · illustrates v2-15

> **Text equivalent.** Reader R1 snapshots committed state `S0 / v0`; writer W commits `S1`, advances the source version to `v1` and invalidates the key; R1, still holding `S0 / v0`, would then publish S0 as a fill. The fenced protocol validates the source generation before publishing: the source returns `v1`, `v1 != v0`, and R1 must not publish. A second reader R2 then misses the cache and takes an authoritative read of `S1 / v1`, which may safely be filled. The figure demonstrates the **stale-fill race** only; the strict-after-acknowledgement contract and its acknowledgement boundary are drawn separately in the freshness-timeline figure above. It illustrates the registered claim beside it and embeds no rate of its own. Source: `book/assets/sources/fig_cache_stale_fill.puml`

v2-15-three-instance-staleness · mechanism_supported · single trial, one machine, small scale; generality unproven; the 87%-vs-0% separation is far outside the ~20% noise floor, but the exact rate is one trial; the signed all-green analysis swapped the two models' rows; this claim uses the report and JSON attribution · full card in the evidence registry index

15.8 Churn, engines and placement (2026-09-23)

Sustained churn crossed real 300 s TTL boundaries under load: the 1,801 s write-through configuration first recorded 6.0 boundaries with 0 wrong reads in 2,879,077 reads, and two fresh 601 s replications in reversed order crossed 2.0 boundaries each with 0 wrong reads for both write-through and write-aside. The hard-expiry path fired **0** times again — only probabilistic early expiry did — so “an entry reached its hard TTL” is still not demonstrated. One aside cell published a single impossible cache value that its gate did not classify; it is reported with `v3-02` and is why that claim keeps a limit. The strict/relaxed pair’s YugabyteDB 1-node direction (relaxed 596 against strict 514) did not reproduce: two fresh runs put strict slightly ahead (1.04x, 1.11x), inside the spread, so neither is named. The 3-node pair (942 against 846) and the colocated/non-colocated layout (882 against 673)

were not re-measured — both need a three-node cluster this machine cannot carry, and the placement itself was never observed — and remain coverage gaps.

v3-01-churn-crosses-real-ttl · single_run_directional · one PostgreSQL + Redis configuration at small scale; one sustained measurement, never repeated; hard expiry fired zero times; that clause is an open gap, not a confirmation; closed loop, so read volumes are a floor; the 5x-for-120 s burst has no write-rate knob and was not run; the 1800 s horizon was not re-run on 2026–10–02: the 600 s pair recorded for v3–02 re-tests the same mechanism at a shorter horizon, and this claim's 1801 s / 6.0-boundary figure remains the primary's single run · full card in the evidence registry index

v3-02-churn-600-through-vs-aside

external read copies / caches · run_replicated

At 601 s the write-through and write-aside churn cells each crossed 2.0 real 300 s TTL boundaries with 0 wrong reads, in two whole runs in reversed order (through 2.004/2.003 boundaries with 1,326,612 and 885,864 reads; aside 2.003/2.004 with 1,173,729 and 1,156,637), and neither strategy is claimed to win. One aside cell recorded 1 impossible cache value in 1,173,729 reads while its gate passed, so the study's floor that an impossible value must always be zero did not hold cleanly and the gate does not classify impossible values during churn.

Trials: 4 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Limits: the cache container's own resources are not counted in this comparison; hard expiry fired 0 times in every cell; only probabilistic early expiry fired, and the 5x burst was not run; closed loop, so read volumes are a floor; one cell (20261002T191609Z, aside-strict) recorded 1 impossible cache value that the gate did not catch; it is not repeated in the other three cells and has no identified cause, and the gate's coverage of impossible values during churn is a recorded gap

Source: studies/05-cache-consistency/reports/20260923T1020Z-churn600-through.md · run 20260923T1020Z-churn600-through · tag run/05-cache-consistency/20260923T1020Z-churn600-through

v3-04-yb-single-strict-relaxed

external read copies / caches · run_replicated

On YugabyteDB 1-node (RF=1) the strict and relaxed write-through reads differ by 1.043x and 1.105x, both inside the cells' 21.7%-74.7% trial spread, so the strict/relaxed read difference is a null on one node too. The primary's direction (relaxed 596 above strict 514) did not reproduce: both fresh runs lean strict-slightly-ahead, also inside spread, so no design is named the more consistent one.

Trials: 3 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Limits: single endpoint (RF=1); this is not a cluster result; the trial spreads are large (up to 74.7%), so the null is weak evidence; the primary's direction (relaxed ahead) did not reproduce; the fresh runs lean strict-ahead, still inside spread

Source: studies/05-cache-consistency/reports/20260923T1152Z-res2-yb1.md · run 20260923T1152Z-res2-yb1 · tag run/05-cache-consistency/20260923T1152Z-res2-yb1

v3-05-yb-cluster3-strict-relaxed

external read copies / caches · single_run_directional

On YugabyteDB 3-node (RF=3), where the client spreads operations over all three endpoints, one run recorded the strict write-through read at 942 ops/s against the relaxed configuration's 846, the opposite direction from the 1-node pair, with each configuration measured once and no engine ranked.

Trials: 1 whole-run replication · 1 fresh-load trial per cell · 1 inner iteration

Limits: one run per freshness policy; direction is not repeated and differs from the 1-node pair; three containers on one host, no real network; endpoint spread is round-robin by construction; app-99 phases have large spread (50.4% relaxed, 49.4% strict); not re-measured on 2026–10–02: yb-cluster3 RF=3 does not fit the fixed 2 GiB podman machine, so the opposite-direction result remains the primary's single run and this target is an explicit coverage gap

Source: studies/05-cache-consistency/reports/20260923T1157Z-res2-yb3.md · run 20260923T1157Z-res2-yb3 · tag run/05-cache-consistency/20260923T1157Z-res2-yb3

v3-06-colocated-vs-noncolocated-locality

rolldown / duplicated data · single_run_directional

On YugabyteDB 3-node (RF=3) a pair differing in key locality, where one layout (y1-coloc) keeps a donor's donations in one tablet and the other (y2-noncol) hashes them across tablets, recorded the first faster on the warm read (882 against 673 ops/s) and on the cacheable read (852 against 520), with 0 wrong reads either way. Where the tables and leaders physically sat was not verified, so this is evidence about the engine's own locality on one host, not about verified colocation.

Trials: 1 whole-run replication · 1 fresh-load trial per cell · 1 inner iteration

Limits: the logical partition mapping follows deterministically from the colocated table's PRIMARY KEY ((person_id) HASH, ...), so one donor's rows hash to one tablet by configuration, not by observed placement; physical tablet/leader placement was not observed: the runner could not produce a tablet/leader distribution (its placeholder held only the three server names), so this is engine locality on one host, not verified colocation; all containers run on one WSL2 host; one host is not colocation evidence; one run per layout, no cache in this scenario, no repeat; spreads are large (warm 40.0% y1, 22.2% y2); not re-measured on 2026–10–02: the pair needs yb-cluster3, which the fixed machine cannot carry, and the harness still has no tablet/leader placement record, so the placement mechanism remains an unsupported coverage gap rather than a completed comparison

Source: studies/05-cache-consistency/reports/20260923T1215Z-res2-placement-yb3.md · run 20260923T1215Z-res2-placement-yb3 · tag run/05-cache-consistency/20260923T1215Z-res2-placement-yb3

15.9 What is still open

Coverage gap

The hard TTL has still never been observed to remove an entry; medium scale beyond the harness maximum, the tablet/leader placement distribution and open-loop arrival demand are unmeasured. Treat these as open, never as null results.

v3-gap-01-study05-remaining-regimes · gap · these are coverage gaps, not null results; medium scale is an order of magnitude beyond the current generator; placement verification needs an instrument the runner does not have; open-loop demand is owned by task-20260922T200831Z-study05-v2-open-loop · full card in the evidence registry index

15.10 Boundaries

Redis was measured as a cache, never as an authoritative key-value store. JSONB is not a native document store. Transfer either result to a native family only as a labelled analogy.

15.11 The checklist

The eight questions, answered for this concept; the status in brackets is the evidence behind the answer.

- **Invariant.** Every cache value corresponds to a committed database state, and under the strict contract a read that starts after an acknowledged write never returns an older committed value. [direct]
- **Where the information lives.** In the authoritative row, and in a copy in Redis or in process memory. The copy is never the source of truth. [direct]
- **Where the contention is.** One hot key and its fill lease: who is allowed to fill, and who must wait. [direct]
- **What work moved from reads to writes.** Invalidation and publication. A write becomes responsible for the copies of the value it changed. [mechanism]
- **What state is derived.** The cached payload and its version or source generation. [mechanism]
- **What can become stale.** Any value a relaxed contract is permitted to return — with three instances sharing a relaxed write-through cache this was 87% wrong reads, against zero for one instance. [direct]
- **Where it stops working.** When an invalidation cannot reach every instance, and at the boundary the corpus has not crossed: the hard TTL has never been observed to remove an entry. [gap]
- **The experiment that would settle it.** Strict/relaxed pairs under the same backend, crossed with instance count, beside the stale-invalidation control. [direct]

16 Distributed placement

CONCEPT · DISTRIBUTED PLACEMENT

Node count, replication factor and actual data placement are three separate facts. A 3-node cluster on one laptop has the first two and none of the third's network consequences.

16.1 What the corpus measures

Studies 01–03 run PostgreSQL single-node and YugabyteDB single-node and 3-node RF=3 cells. The multi-node cells show placement-shaped effects — a section-sharded layout collapsed point lookups to 26 ops/s on YugabyteDB — but the balance of tablets across nodes is unexplained.

Study 05 adds two things those cells did not have: a key-locality pair, where the same donor's donations are held in one tablet in one layout and hashed across tablets in the other, and three-node cells whose client spreads operations over all three endpoints rather than one.




Figure 16: **Logical multi-node topology; no real inter-host network was measured.**

Form: structure · Evidence: conceptual illustration

> **Text equivalent.** PostgreSQL single-node, YugabyteDB RF=1 and YugabyteDB RF=3 are drawn as three logical topologies, but every Yugabyte container sits inside one physical host boundary and talks over a loopback-class path, so the picture is **not** three independent machines. The lower band separates a logical mapping — a hash key places one person's rows in one tablet **by configuration** — from physical tablet and leader placement, which is marked UNVERIFIED in this corpus. The figure asserts no measured value.

16.2 What it does not measure

Two different limitations, and they should not be collapsed into one sentence.

Physical placement is unverified. The locality pair ran, but the runner produced no tablet or leader distribution, so the layout labels record intent, not observed placement. That is an **instrument** gap: it needs a measurement the harness cannot take, not just another run.

Endpoint distribution is partial. The 2026-09-23 Study 05 three-node cells spread operations round-robin over three endpoints, but the earlier multi-node cells still reach the cluster through a single endpoint. Their ratios remain valid for a client that does one endpoint's worth of cluster access, and none of it is a network result.

Both are recorded gaps, not null results.

v4-gap-01-physical-placement-unverified

rolldown / duplicated data · gap · instrument gap + coverage gap

Physical tablet and leader placement remains unverified even though the Study 05 key-locality pair has now been executed: v3–06 records the colocated layout ahead on both reads, but its runner could not produce a tablet/leader distribution, so the layout labels are intent rather than observed placement. Study 04's y1/y2 pair is still unexecuted, Study 01 D7/D24 and Study 03 L3 remain placement intent with measured effects, and every node still runs as a container on one host.

Trials: 0 whole-run replications · 0 fresh-load trials per cell · 0 inner iterations

Limits: containers on one laptop are not evidence of colocation; the runner could not produce a tablet/leader distribution, so the placement labels are intent, not observed placement; the locality pair is one run per layout with large spreads

Source: studies/05-cache-consistency/reports/20260923T1215Z-res2-placement-yb3.md · run 20260923T1215Z-res2-placement-yb3 · tag run/05-cache-consistency/20260923T1215Z-res2-placement-yb3

v4-gap-02-endpoint-distribution-partial

normalized facts · gap · coverage gap + instrument gap

Client endpoint distribution is measured only for the 2026–09–23 Study 05 three-node cells, where the client spreads operations round-robin over all three endpoints (v3–05). The earlier multi-node cells still reach the cluster through a single endpoint: the study 01 and study 02 yb-cluster3 runs each set one DSN against yb-n1. Their cluster ratios therefore still stand in for cluster access through one endpoint, the Study 05 spread is recorded as a node count rather than a per-endpoint balance, and no run has a real network between nodes.

Trials: 0 whole-run replications · 0 fresh-load trials per cell · 0 inner iterations

Limits: no real network between nodes; endpoint distribution is unmeasured for the studies 01–03 multi-node cells, which connect through a single endpoint; the Study 05 three-node spread is round-robin by construction and is recorded as a node count, not as a measured per-endpoint balance

Source: studies/05-cache-consistency/reports/20260923T1157Z-res2-yb3.md · run 20260923T1157Z-res2-yb3 · tag run/05-cache-consistency/20260923T1157Z-res2-yb3

v2-gap-06-native-datastore-families · gap · do not transfer the embedded-document or cache results to a native family · full card in the evidence registry index

16.3 Boundaries

Do not read a single-node-versus-cluster ratio as production capacity guidance. The nodes share the host's cores and have no real network between them.

16.4 The checklist

Every answer below is a gap, and the honest response is to say so rather than to reason from how clusters usually behave.

- **Invariant.** The same logical read returns the same answer wherever the data sits. [gap]
- **Where the information lives.** In engine-chosen tablets and leaders — and the corpus records layout **intent**, never an observed distribution. [gap]
- **Where the contention is.** Unknown: no tablet or leader distribution has been measured. [gap]
- **What work moved from reads to writes.** Replication and placement move work and latency, but no experiment in the corpus separates them from node count. [gap]
- **What state is derived.** A lagging replica is a copy rather than derived state, and no control has been seen to serve it. [gap]
- **What can become stale.** A follower, in principle. Unmeasured, therefore unstated. [gap]
- **Where it stops working.** Unknown on one host with no real network path: a container count is not a topology. [gap]
- **The experiment that would settle it.** Independent hosts, balanced endpoints, a recorded tablet/leader distribution and injected latency — Study 07's axes. [gap]

17 Reading benchmarks honestly

CONCEPT · READING BENCHMARKS

A benchmark answers the question its harness asks. Most wrong conclusions in this corpus came from reading a number as if it answered a different question, not from a bad run.

17.1 Six questions to ask of any number

- **Closed or open loop?** Every race here is closed loop. Closed-loop load can understate fixed-rate behaviour, so its tail must not be read as an SLO prediction.
- **One trial or many?** The scatter between repeats inside one measurement is not the same as the scatter between separate runs of the whole experiment.
- **Were both sides given the same resources?** Comparing one node with three answers "what if I add machines", not "what if I spend the same total".
- **In what order were the designs run?** In Study 02 the two designs swap places on PostgreSQL depending on the order, so no ratio is quotable until an order-controlled repeat is run.
- **Did the check that is meant to fail actually fail?** A correctness check that no deliberately broken design ever trips proves less than it appears to.
- **One configuration, or the whole run?** A run's totals and failures belong to the run; a claim cites a selected subset of what was measured.

17.2 Worked examples of a number that cannot be quoted

v2-09-postgres-ledger-ratio-unsettled · run_replicated · the stable direction is measured at 1,000 seats across 8–128 buyers and at 32 buyers across all five tiers; the buyer-count axis is not swept at the other four tiers, so the full buyer x tier surface is open; one primary run per (buyers, order) cell, with a reference cell that moved 8.6% between the two ends of the tranche, so a level whose two orders differ by more than that is placed by the ratio and not by the absolutes; the direction is stable but the ratio is not: the eleven run medians span 1.06–5.10 (1.22–1.86 with the collapsed 8-buyer cell set aside), so the cost is a range and not a point; the 8-buyer level's pooled median is not interpreted: a recurrence test of six runs and twelve cells (2026–09–29, tag study-02/v2–09–8buyer) found four low-throughput events in 60 trials, readings of 619–655 ops/s against a session normal of about 2500 (a 4x drop), and they hit both designs (three of the four in the CAS arm) and both orders, so the low mode is a property of this buyer count's very short trials and not of the ledger; the original p3-first cell read as a state change only because its slow trials were its last three, which set the cell median; the primary evidence is from a different harness state (phases verify,write,race,churn on a five-day-old image), so comparing it with this tranche mixes the confound with a period effect and the re-scope is stated as a direction, not a ratio; one side of the primary comparison is a partial configuration on yb-cluster3 (medians of two measurements); at 32 buyers the ledger was slower in all ten tier x order cells of two 2026–09–29 runs (ratios 1.021–1.606) and below the 128-buyer pooled ratio at every tier (1.06 vs 1.08, 1.06 vs 1.24, 1.23 vs 1.41, 1.56 vs 1.85, 1.56 vs 2.51), so the primary's tier-wide reversal does not reproduce anywhere on the axis; those two runs are anchors but are not counted in the eleven-run replication record, which is the buyer-count sweep at one tier; at 32 buyers and 10–100 seats the direction sits at the measurement's floor: only 3 of 10 trial pairs at 10 seats and 6 of 10 at 100 favour the CAS design, with cell spreads of 86–174%, so those two tiers support the median and not a per-pair claim, while the 1,000-seat cell reproduced the sweep's ratio a day later within 1% (1.245 and 1.219 against 1.233 and 1.219); the 8-buyer low-throughput mode is not a quota effect on either side: the twelve cells' per-trial client_cpu entries (present since the study's first commit, and corrects an earlier limit here that said the client was not recorded) show zero client throttling and *more* client CPU in the slow trials (2.6–2.8 s against about 1.9 s), so the client waits rather than starves, while the database container's cpu.stat throttled about 4 ms across the collapsed cell; the cause is narrowed to a latency excursion on the response path and is not identified further, since no per-trial plan or server-side clock is recorded; three of the four 8-buyer low events were single trials that recovered on the next trial and one spanned consecutive trials, so 'persistent collapse' and 'transient spike' are names for where the event fell in the cell (a five-trial median cannot distinguish them at a ~7% event rate); no 8-buyer magnitude is quoted from either tranche · full card in the evidence registry index

v2-gap-01-ledger-load-multiplier-unstable · gap · a single one-off load of one configuration is not a cost of the design; needs its own repeated load-only measurement before any multiplier can be quoted; the read phase of this claim's primary anchor 20260920T234953Z was client-CPU throttled by a design-dependent amount (2.3 s to 58.1 s across designs, out of about 1085 CFS periods) and the hazard reproduces on the current harness (20260929T165533Z, 20260929T170353Z), so that report's read figures are not quotable; the load-phase figures this claim rests on are a separate phase and were not throttled. The read family has since been re-measured at the new 2-worker read footprint for four designs (20260930T164028Z, 20260930T164834Z): their read levels are quotable with the footprint attached, and all fifteen designs now have a footprint-2 footing (the eleven-design tranche 20260930T201732Z/20260930T203913Z adds

the rest, unthrottled, and 20261001T100948Z/20261001T103931Z measures all fifteen together in one session); this claim's primary anchor's own footprint-8 read figures remain not quotable · full card in the evidence registry index

v2-16-strict-freshness-read-cost · run_replicated · read throughput only; the two fresh runs' trial spreads reached 22.8%, so only an effect larger than that could have been seen; small scale, closed loop, one machine; the strict/relaxed pair here is the owned write-through pair; a strict protocol's write-path cost is not measured · full card in the evidence registry index

17.3 Before quoting a number

A table, not a figure: check it against the card beside the number.

Question	Where the answer lives	If it is missing
Which claim does this number belong to?	The claim id in the card	Do not quote it.
Was it one run, or several?	`trials` on the card	Say “one run, one trial” and stop.
Closed or open loop?	The report’s workload section	Do not read the tail as an SLO.
Same resources on both sides?	`resource_framing` in the result	Never mix the two ways of counting.
One decision, or several changes at once?	The card’s own label	Attribute nothing to a single change.
Did the deliberately broken control fail?	The run’s verification block	Treat correctness as unproven.
What else changed at the same time?	`confounds` on the card	Do not attribute the effect.
What gap does it leave?	The gap’s `gap_kind`	Name the kind, never “unknown”.

17.4 Boundaries

Laptop topologies with shared cores are a controlled comparison, not a capacity model. The environment caveat belongs wherever a conclusion is drawn.

17.5 The checklist

The eight questions applied to a **number** rather than to a design; the status in brackets is the evidence behind the answer.

- **Invariant.** A number is reproducible from its commit, its pinned images and its inputs digest, or it is not evidence. [mechanism]
- **Where the information lives.** In the run manifest, the result JSON, the plans and the report — not in the prose that quotes it. [mechanism]
- **Where the contention is.** The machine itself: one measurement at a time, under the benchmark lock. [mechanism]
- **What work moved from reads to writes.** Nothing; this concept prices work, it does not move it. [mechanism]
- **What state is derived.** A blended score is derived from its parts and must be decomposed before it is quoted. [mechanism]
- **What can become stale.** A report whose digest no longer matches the results it describes, and any number copied out of a superseded analysis. [mechanism]
- **Where it stops working.** Single-trial cells, closed-loop tails read as service levels, differences inside the noise floor, and cells whose own trials disagree by more than the 20% rule. [mechanism]
- **The experiment that would settle it.** Independent runs with randomized order and reported across-run spread — which is what the first replication in the corpus did. [direct]

18 Glossary

APPENDIX · GLOSSARY

The single definition site for the vocabulary the rest of the book uses. Where a term is also a registry field, the registry's value is named in brackets.

Term	Meaning
claim	One reviewed statement about what the corpus measured, registered in the active evidence package and identified by an id such as `v2-16`. A number may not appear in this book without one.
strength	How strongly a claim is supported: `single_run_directional` (one run, one trial per cell, a direction not a curve), `repeated_controlled` (repeated fresh loads with a control), `mechanism_supported` (the mechanism is shown, the rate is not), `gap` (an explicit absence of evidence).
direct evidence	A callout whose numbers come from the cited run of the claim beside it.
mechanism evidence	A card or callout that demonstrates how something works without establishing a rate.
analogy	A labelled transfer beyond the measured family or environment. Never a measurement.
gap	An explicit absence of evidence, of one of four kinds. A gap is never a null result.
schema limitation	The representation cannot answer the question, so no run would. The hold-funnel gap is one.
coverage gap	A relevant regime has not been measured yet, but could be.
instrument gap	The property could not be observed with the tools the study had. Physical tablet placement is one.
unstable measurement	The number moved between runs with no code change, so no value is quotable.
partially superseded	Part of the claim has been replaced by newer evidence; the card says what moved to which successor and what is still open.
retired	The claim is no longer active, is not cited, and names the successor that closes it.
run	One execution of the harness under the benchmark lock, identified by a run tag and an inputs digest. Results are comparable only within one environment.
replication	A whole-run repeat of the same cell. The cards report it as `whole_run_replications`; `Trials: 1` means exactly one.
trial	A measurement inside a run. A fresh-load trial repeats the load phase; an in-run repeat is another measurement window inside one process. Neither is an independent replication.
read score	A blended within-run composite of a family's read queries. It compares variants inside one run and nothing else: it is not the throughput of any single query and is not quotable across runs.
wrong_reads	The harness counter for reads that violated the strict comparator in force, not for corruption. A relaxed cell can record many without serving an impossible value.
strict after acknowledgement	`begin(R1) > ack(W1)` implies the read must not return a version older than `W1`, unless a later write to the key supersedes it. This is the comparator the harness counts against.

Term	Meaning
relaxed freshness	A family of named weakenings of the strict line: session/read-your-writes, bounded staleness with a declared delta, eventual freshness, and best effort. Bounded staleness is one member, not the definition.
resource framing	`db-only` counts the database's resources; `equal-total` gives the cache a share of an equal budget. The two are never pooled, and a single-node versus cluster comparison answers "add machines", not "same budget".
colocation	A design intent that a key's rows share a partition. Logical mapping can follow from the schema; verified physical placement requires an instrument the studies did not have.
rollup	A parent aggregate maintained from its children. Where it lives in the same database it is updated in the same transaction; otherwise it is published, with a named delivery and reconciliation path.
rolldown	Parent information copied onto the child to avoid a join.
embedding	A child collection stored inside its parent row, as JSON or an array. In this corpus that means a relational JSON column, not a native document database.
source correctness	A mechanism that makes the authoritative mutation itself correct, such as a lock plus invariant recheck or a conditional update.
copy correctness	A mechanism that orders what leaves the transaction: invalidation, a publication fence, version validation at the hit boundary, a fill lease, a TTL, or an outbox.
derived state	A stored structure that answers from current facts and owes its maintainer a correctness contract on every contributing write: an index, a rollup, a rolldown or an external read copy.
retained history	Information kept so a question can be answered after the event was undone: an event/ledger table, an audit trail, a temporal history or a snapshot. A current-state-only representation cannot reconstruct what it has destroyed.
invalidation	Removing or marking a cache entry stale. It orders nothing about a read or a fill already in flight.
fill lease	A bounded ownership period that suppresses duplicate concurrent fills while it is valid and honoured. It is a load control, not a freshness proof.
fencing token	A monotonically increasing token checked at a protected sink, which rejects an operation whose token is older than one the sink has already accepted. It orders operations at the sink; it does not itself consult the source.
source-generation validation	Before publishing, checking that the authoritative current generation still equals the generation the reader observed, and refusing the fill if it moved. This closes the stale-fill race.
cache CAS	A conditional modification of cache state against an explicitly stated expected value or generation. It is not source-generation validation.
hit validation	Verifying a cached value against authoritative or version state at the hit boundary before serving it.
transactional outbox	Writing a change in the same transaction as the mutation so it can be published durably. It makes a committed change observable; it does not by itself make every cache hit current.
TTL / early expiry	A bound on how long an entry is eligible to serve, plus probabilistic early refill before many entries reach one deadline. It controls eligibility and load, not currentness, unless the declared contract is itself bounded by it.

Term	Meaning
publication fence	Refusing a fill whose source moved after the reader took its snapshot. This, not invalidation, is what closes the stale-fill race; source-generation validation is its strongest named form.
confound	A second change that moved with the one being measured. Registered in the package's confound register and published beside the numbers it affects.
family, variant, scenario	A family is a way of deciding where a fact lives; a variant is one design inside a family; a scenario is a workload built around one question, such as a hot drop or a refund.

19 Evidence registry (active v6 claims)

The active registry holds 31 claims that may be cited as evidence. This index is rendered from `book/evidence/v6/claims.json` at build time; the digest above identifies its content.

19.1 normalized facts

v2-01-normalized-index-first

normalized facts · run_replicated

In the charity -> person -> donation tree, the first large read win is the query index: D2 indexed scores about 10–11x D1 minimal's read score in two whole runs (13.3x in the first), and flattening the foreign key instead (D3 flat+FK) reaches about 14–16x (20.5x in the first). The orderings and the bands replicated in both design orders; the point figures were single-run levels.

Trials: 3 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Confounds: conf-01-study01-d2d3-copied-key-package

Limits: PostgreSQL 1 node and YugabyteDB 1/3 nodes in one run; small scale; a single measurement per configuration, not a repeat; read score is a blended measure, not one query; the quoted point figures (13.3x, 20.5x) are the primary run's single levels: the whole-run replication of 2026–10–01 measured 9.7–15.5x for the same two relations while the absolute read scores moved 40–45% between its two runs, so the band and the ordering are what may be quoted, not the points

Source: studies/01-charity-tree/reports/20260912-small.md · run 20260912-small · tag none (legacy)

v2-06-hot-drop-designs

normalized facts · run_replicated

For a hot drop, pre-created seats taken by compare-and-set or SKIP LOCKED (P3 CAS, P2 skip-locked) sell 4–8x faster than any single counter row, but only with retry backoff in mind, and a counter on the event row also blocks unrelated edits to it. Both deliberately wrong controls fired in the same run. Two replications thirteen days later, on the same topology and with the design order reversed between them (AB/BA), reproduced the range - P3 at 4.30–7.06x and 4.64–6.99x, P2 at 3.25–5.25x and 5.78–8.71x against the two counters - while every absolute throughput fell 26–72% below the original run. The range is therefore the claim and the absolute numbers are one session's readings.

Trials: 3 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Limits: one run of the experiment, a single measurement per configuration; the run has 42 cells of which 2 failed (C2 count (SER) on the two YugabyteDB topologies); those cells are not evidence; hot-drop workload only; every absolute throughput in the 2026–09–26 replication was 26–72% below the 2026–09–13 run for the same design and tier, so the 4–8x range reproduced while the numbers behind it did not; the range is quotable and the figures are not; the ratio moved between runs: p3 against c4 went 7.07 to 4.37 to 4.64 at 100 seats and 7.26 to 4.30 to 4.70 at 1000, and p2 against c4 went 3.97 to 3.25 to 5.78, so the range is a range, not a point, and individual ratios shift by up to 44%; the replication re-ran neither deliberately wrong control (c1_count_naive, h0_hold_naive_confirm), so it strengthens the comparison without re-firing the correctness control that the first run provided; r1_inventory_row recorded one trial of about 4x lower throughput than its siblings at each tier (122 and 117 against 468–653); whether that is a real instability or a harness artefact is unresolved, and r1 is the weakest comparison in the replication; two of the original sweep's five tiers (10 and 10000 seats) were not re-measured; p2_precreated_skip_locked moved 58–76% between the two same-day replications while the counters moved within 15% and p3 within 7%; it ran first in one and last in the other, so that design carries a position or warm-up effect as large as the comparison it takes part in, and the claim's pairing of p2 with p3 hides it - the >=3x result holds at both extremes; the anomalous r1_inventory_row trials of the first replication (122 and 117 against 468–653) did not recur in the reverse-order run, which makes a harness artefact likelier than a design property without settling it; the read phase of this claim's primary anchor 20260913T021206Z was client-CPU throttled by a design-dependent amount (0.2 s for p2_precreated_skip_locked to 29.5 s for h0_hold_naive_confirm, out of 633 CFS periods), so that report's read figures are not quotable. The hazard reproduces on the current harness (20260929T165533Z, 20260929T170353Z: r1_inventory_row loses 420 of 634 and 422 of 633 periods), and the 2026–09–30 budget calibration (20260930T000544Z, 20260930T000759Z, 20260930T001013Z) shows the client's quota is a symptom rather than the ceiling: at three client cores the client is not throttled at all and the reads are slower (52,884 -> 43,726 ops/s at 10 seats), because the third core comes out of the database's share of the machine's four CPUs (database throttled periods 238 -> 847 -> 1052). The claim's own basis is the race phase (sell rate), where one cell in fourteen designs shows throttling. The read family has since been re-measured at the study's new 2-worker read footprint (20260930T164028Z, 20260930T164834Z: four designs, client unthrottled at 0 of ~631 periods, every cell latency-bound at 2.00 operations in flight for 2 workers (with the mean latency; a median-based count reads 1.9)), so read levels are quotable only with the footprint attached. All fifteen designs now have a footprint-2 footing (the four-design tranche plus the eleven-design tranche 20260930T201732Z/20260930T203913Z, where no design throttles: 0 of ~631 periods in all 22 read phases), and this claim's primary anchor's own footprint-8 read figures remain not quotable: the inflation they carry is design-dependent, 1.09x to 2.22x, and it tracks how many periods the old client lost per design rather than anything about the designs. All fifteen designs have since been measured in a **single run**, twice and in reversed order (20261001T100948Z, 20261001T103931Z): 0 throttled periods in all 30 read phases and every one of the 270 cells store-bound at 2.00 operations in flight by the mean latency, so the family's levels are jointly comparable within that session. Two consequences for quoting: the top group (h0, h1, r1, r2, p4) differs by 4%, inside that session's own order term, so its internal ranking is not quotable - only the 1.5x gap between that group and the per-seat group is; and c1_count_naive carries a 40% position term (first of one order against last of the other), so its q01 level should not be quoted from these runs.

Source: studies/02-ticket-booking/reports/20260913T021206Z.md · run 20260913T021206Z · tag run/02-ticket-booking/20260913T021206Z

v2-10-guarded-confirm-refusals

normalized facts · run_replicated

On YugabyteDB a guarded confirmation is not enough, but the refusals are spurious rather than a design fault: at the 10,000-seat tier the correct designs refused valid holds (s1_conditional_update 2 refusals in one whole run and 3 in the reversed run, s2_lock_then_update 1 in each), and every refusal is classified transient - the identical statement re-issued inside the refusing transaction matched every seat - while the retry-once variant s1r_confirm_retry refused nothing and every retry it made succeeded (5 across the forward run). On PostgreSQL the same three designs refused nothing at any of five tiers from 10 to 100,000 seats in two whole runs, so the guarantee held everywhere there. The study's negative control s0_check_then_hold_rc refused at every tier on both engines and stole 474–599 holds per tier on YugabyteDB and 1,168–6,231 on PostgreSQL, so the audit detects both the spurious refusal and the real theft. This claim is about refusals, not throughput, and no cost conclusion follows from it.

Trials: 3 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: v1 matrix run, a single measurement per configuration; the claim is about refusals, not throughput; retry-once is a design variant (S1r), not a tuning flag; the replicated refusals are few and tier-bound: 2, 3 and 1 refusal events in the correct designs across two whole runs, all at the 10,000-seat tier except s2's single 1,000-seat refusal in the reversed order, so the claim is that refusals happen and are transient - not a rate, and not a tier law; the YugabyteDB arm measured four tiers (10 to 10,000 seats) while the PostgreSQL control measured five (10 to 100,000), because that is how the study configures its tiers per engine; 'the guarantee held everywhere' therefore means everywhere the PostgreSQL arm ran; the refusals are the harness's own classification of its own designs, and the transient sub-class is decided by re-issuing the statement inside the refusing transaction (AM-01), so this replicates the mechanism and its detection, not an independent definition of a valid hold; the 2 GiB podman-machine blocker recorded in CONTEXT.md is a multi-node limit: a single-node YugabyteDB arm fits and completes here, which is what makes this replication possible, while yb-cluster3 remains unmeasurable on this machine; the spread figure is the refusal count's own movement, not a throughput spread: s1_conditional_update refused 2 times in the forward run and 3 in the reversed one, so the count moves 40% across the two runs and the phenomenon is established, not quantified

Source: studies/03-reserved-seating/reports/20260915T002411Z.md · run 20260915T002411Z · tag run/03-reserved-seating/20260915T002411Z

v2-12-lock-vs-version-upper-bound

normalized facts · run_replicated

Under one hot key at 16 writers a lock-before-update (c2_pessimistic_lock) delivered about 1.6–1.8x the throughput of a version check (c1_optimistic_version): 1.76x in the primary run and 1.56x, 1.57x, 1.64x and 1.69x in four whole runs on 2026-10-02 that crossed the two design orders with the retry budget at its default and at zero. The retry budget does not explain the advantage - at a matched design order removing it moves the ratio by 1.1% to 3.2% - so the earlier wording calling the figure an upper bound because of per-retry harness work is retired by its own control. An unchecked read-modify-write (x1_lost_update_control) lost 93.7% of acknowledged updates in the primary run and 93.7% and 93.9% in the replications, while both correct designs lost none.

Trials: 5 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: one key, one installed product, 16 writers; PostgreSQL single node, small scale; one fresh-load trial per run; five whole runs now support the ratio, but no run repeats the cell, and the -retries 1 setting was not among the controls (the budget controls used the default 8 against -retries 0); 1.76x is one point on a writer curve, not a curve; the upper-bound hedge is retired: the retry budget was re-run on 2026-10-02 at 16 writers in both design orders, default against -retries 0 (1.64x against 1.69x with the lock first, 1.57x against 1.56x with the version check first), a 1.1% to 3.2% difference, which agrees with the primary's own retry control (1.60x against 1.61x) and means the advantage is not per-retry harness work; the re-scoped figure is a band of five whole runs on two days (1.56x, 1.57x, 1.64x, 1.69x, 1.76x); absolute throughput is day-specific, so only the within-run ratio travels

Source: studies/04-configuration-portal/reports/20260921T1215Z-small.md · run 20260921T1215Z-small · tag run/04-configuration-portal/20260921T1215Z-small

v2-gap-03-study04-missing-designs

normalized facts · gap · coverage gap

Eight of the eighteen planned Study 04 configuration-portal designs are not implemented, and cardinality, cadence/churn, repeated randomized trials, equal-total resources, placement and YugabyteDB are unmeasured. These are coverage gaps, not null results.

Trials: 1 whole-run replication · 1 fresh-load trial per cell · 1 inner iteration

Limits: no conclusion may read 'the missing designs would not change this'; owned by task-20260922T025912Z-study04-v2-protocol

Source: studies/04-configuration-portal/reports/20260921T1215Z-small.md · run 20260921T1215Z-small · tag run/04-configuration-portal/20260921T1215Z-small

v4-gap-02-endpoint-distribution-partial

normalized facts · gap · coverage gap + instrument gap

Client endpoint distribution is measured only for the 2026–09–23 Study 05 three-node cells, where the client spreads operations round-robin over all three endpoints (v3–05). The earlier multi-node cells still reach the cluster through a single endpoint: the study 01 and study 02 yb-cluster3 runs each set one DSN against yb-n1. Their cluster ratios therefore still stand in for cluster access through one endpoint, the Study 05 spread is recorded as a node count rather than a per-endpoint balance, and no run has a real network between nodes.

Trials: 0 whole-run replications · 0 fresh-load trials per cell · 0 inner iterations

Limits: no real network between nodes; endpoint distribution is unmeasured for the studies 01–03 multi-node cells, which connect through a single endpoint; the Study 05 three-node spread is round-robin by construction and is recorded as a node count, not as a measured per-endpoint balance

Source: studies/05-cache-consistency/reports/20260923T1157Z-res2-yb3.md · run 20260923T1157Z-res2-yb3 · tag run/05-cache-consistency/20260923T1157Z-res2-yb3

v2-17-optimistic-pessimistic-crossover

normalized facts · run_replicated

Under one hot key a bounded-retry version check (c1_optimistic_version) and a lock-before-update (c2_pessimistic_lock) cross over between one and two writers: in the primary sweep the lock delivered 0.89x the version check's throughput at 1 writer (1,177 against 1,329 ops/s) and 1.10x at 2 (1,285 against 1,167), rising to 1.68x at 32 and 1.60x at 64, while the version check's throughput fell 2.9x across the sweep and its conflict count rose from 0 to 21,301. Three whole runs on 2026–10–02 reproduced the crossing (0.905x, 0.939x and 0.948x at 1 writer; 1.035x, 1.106x and 1.166x at 2) and the divergence above it (1.56x-1.69x at 16 writers and 1.73x-1.96x at 64, in both design orders), with the version check's conflicts rising from 0 to about 25,000 and its throughput falling from 1,286 to 563 ops/s. One further 1-writer run measured 3.85x because c1 itself read 306 ops/s there while another run at the same level and design order read 1,286; no client or database throttling was recorded, and the added version-check-first runs read 0.905x and 0.948x at that level, so the excursion is reported as unexplained rather than as an order effect.

Trials: 23 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: PostgreSQL single node, small scale, one hot key; one fresh-load trial per run; the 2026–10–02 tranche measured the pair at 1, 2, 16 and 64 writers in both design orders, and at 16 writers with the retry budget at zero, but the primary's 4, 8 and 32-writer levels were not re-measured, so the claim's 32-writer point (1.68x) rests on the primary alone; we tested the obvious explanation for the lock's advantage and it failed: with the retry budget set to zero the c2/c1 ratio at 16 writers is unchanged within 1.1% to 3.2% in both design orders, and c2_pessimistic_lock, which never retries either way, moved by the same amount as c1, so the advantage cannot be put down to retry work; the primary's seven runs used two phase sets (the first four also ran read and write phases); the contention metric should not depend on that, but it is an assumption rather than a measurement; at 1 writer the unsafe control x1_lost_update_control cannot lose an update because there is no concurrency, so its gate cannot fire: three runs that included it at that level (20261002T162400Z-w1, 20261002T162737Z-w1 and 20261002T165329Z) record a failed x1 cell, and the claim's control_coverage comes from the levels at two writers and above, where x1 lost 50.0% and 93.7%-98.0% of acknowledged updates; one 1-writer run (20261002T162737Z-w1) measured 3.85x because c1 read 306 ops/s there against 1,286 in the other run with the same design order; the version-check-first runs gave 0.905x and 0.948x at that level and no client or database throttling was recorded in any of them, so the excursion is reported as unexplained; absolute throughput is day-specific: c2 measured 869 ops/s on 2026–09–23 and 1,056 on 2026–09–26 at identical settings, phases and writer count, so only the within-run ratio is carried across days

Source: studies/04-configuration-portal/reports/20260923T0011Z-ctlC-w1.md · run 20260923T0011Z-ctlC-w1 · tag run/04-configuration-portal/20260923T0011Z-ctlC-w1

19.2 rolldown / duplicated data

v2-05-d3-read-advantage-repeated

rolldown / duplicated data · run_replicated

D3's (d3_flattened_fk) read advantage over the normalized indexed design survives five fresh loads in one session and reproduces across two whole runs in reversed order, at 1.59x, 1.72x, 1.64x and 1.84x in its four further fresh loads against the primary's 2.47x; the recency SQL and actual heap avoidance explain the gain, while its insert cost remains imprecise.

Trials: 3 whole-run replications · 5 fresh-load trials per cell · 1 inner iteration

Limits: five fresh loads per configuration, all in one session; the insert-cost estimate is imprecise and must not be quoted as a ratio; the magnitude came down on replication: 1.59–1.84x against the primary's 2.47x, so the direction and the survival are what a reader should carry, and the ratio itself is a band that a future run could move again

Source: studies/01-charity-tree/reports/20260913T125342Z-v3.md · run 20260913T125342Z-v3 · tag run/01-charity-tree/20260913T125342Z-v3

v3-06-colocated-vs-noncolocated-locality

rolldown / duplicated data · single_run_directional

On YugabyteDB 3-node (RF=3) a pair differing in key locality, where one layout (y1-coloc) keeps a donor's donations in one tablet and the other (y2-noncol) hashes them across tablets, recorded the first faster on the warm read (882 against 673 ops/s) and on the cacheable read (852 against 520), with 0 wrong reads either way. Where the tables and leaders physically sat was not verified, so this is evidence about the engine's own locality on one host, not about verified colocation.

Trials: 1 whole-run replication · 1 fresh-load trial per cell · 1 inner iteration

Limits: the logical partition mapping follows deterministically from the colocated table's PRIMARY KEY ((person_id) HASH, ...), so one donor's rows hash to one tablet by configuration, not by observed placement; physical tablet/leader placement was not observed: the runner could not produce a tablet/leader distribution (its placeholder held only the three server names), so this is engine locality on one host, not verified colocation; all containers run on one WSL2 host; one host is not colocation evidence; one run per layout, no cache in this scenario, no repeat; spreads are large (warm 40.0% y1, 22.2% y2); not re-measured on 2026–10–02: the pair needs yb-cluster3, which the fixed machine cannot carry, and the harness still has no tablet/leader placement record, so the placement mechanism remains an unsupported coverage gap rather than a completed comparison

Source: studies/05-cache-consistency/reports/20260923T1215Z-res2-placement-yb3.md · run 20260923T1215Z-res2-placement-yb3 · tag run/05-cache-consistency/20260923T1215Z-res2-placement-yb3

v4-gap-01-physical-placement-unverified

rolldown / duplicated data · gap · instrument gap + coverage gap

Physical tablet and leader placement remains unverified even though the Study 05 key-locality pair has now been executed: v3–06 records the colocated layout ahead on both reads, but its runner could not produce a tablet/leader distribution, so the layout labels are intent rather than observed placement. Study 04's y1/y2 pair is still unexecuted, Study 01 D7/D24 and Study 03 L3 remain placement intent with measured effects, and every node still runs as a container on one host.

Trials: 0 whole-run replications · 0 fresh-load trials per cell · 0 inner iterations

Limits: containers on one laptop are not evidence of colocation; the runner could not produce a tablet/leader distribution, so the placement labels are intent, not observed placement; the locality pair is one run per layout with large spreads

Source: studies/05-cache-consistency/reports/20260923T1215Z-res2-placement-yb3.md · run 20260923T1215Z-res2-placement-yb3 · tag run/05-cache-consistency/20260923T1215Z-res2-placement-yb3

19.3 rollups / materialized aggregates

v2-02-rollup-family

rollups / materialized aggregates · run_replicated

Parent rollups win the aggregate read score - D4 rollup/trg about 61–85x and D5 rollup/app about 64–83x D1 minimal in two whole runs (73.8x and 69.9x in the first) - and pay for it on inserts: about a third to two-fifths of D1's insert rate in the same two runs (2.6k/s and 2.1k/s against 6.2k/s in the first).

Trials: 3 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: one run of the experiment, a single measurement per configuration; PostgreSQL 1 node numbers shown; YugabyteDB in the same report; the write cost is per-insert on a fresh load; the quoted rates (2.6k/s, 2.1k/s, 6.2k/s) are the primary run's levels: the 2026–10–01 replication measured D1 inserting at 6.1k/s and 4.9k/s with D4/D5 at 0.29–0.37x of it, so the read band and the write penalty ratio reproduce while the absolute rates do not

Source: studies/01-charity-tree/reports/20260912-small.md · run 20260912-small · tag none (legacy)

v2-04-recency-maintained-index

rollups / materialized aggregates · run_replicated

The recency flag works, but an index on the rollup column answers the window questions faster, and by how much depends on the question: across two whole runs on PostgreSQL (d20_recency_flag against d22_recency_rollup_idx) the index is 1.9–2.3x on q13 (the primary's quoted 2.9x is this query in its trailing regime), 2.6–3.1x on q15 trailing, level on q14 (0.98–1.24x) and slightly slower on q16 (0.85–0.94x), so the group-wide ratio is about 1.4x. The YugabyteDB half (quoted 7.9x) is unreplicated.

Trials: 3 whole-run replications · 2 fresh-load trials per cell · 1 inner iteration

Confounds: conf-02-study01-d20d22-write-axis

Limits: we cannot say how much of d22's write cost comes from the index, because d22 also maintains D4's multi-column rollup: the two designs differ by more than the index; three repeats of the measurement per configuration; claim-02's v1 trials field was recorded as 1 and is corrected here; the quoted 2.9x and 7.9x are single-query, single-engine figures (q13 trailing): the recency group geomean is about 1.4x here and 1.52x recomputed from the primary, and on q16 the flag is marginally FASTER than the index in both runs - quote the query, not one headline

Source: studies/01-charity-tree/reports/20260916T090036Z-v3.md · run 20260916T090036Z-v3 · tag run/01-charity-tree/20260916T090036Z-v3

v2-13-trigger-rollup-cost

rollups / materialized aggregates · run_replicated

Maintaining the portal overview with a per-row trigger (n3_rollup_trigger) costs 4.0–5.7x the application-maintained rollup (n4_rollup_app) on whole-configuration replacement across three runs in randomized order (median 4.94x: n4 518–635 ops/s against n3 91–159 ops/s), and the trigger's slowest 1% is 22–46x worse (p99 61–109 ms against 2.2–2.7 ms); repeating the measurement inside the trigger's own configuration disagreed by 35–115%, so this is a range rather than one number, and the 6.85x quoted earlier from a single run did not reproduce.

Trials: 3 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Limits: PostgreSQL single node, small scale; three whole runs, each with three repeats of the measurement per configuration; the experiment was repeated as separate whole runs on one machine, so it is not independent of this hardware and is still exposed to this host's measurement hazards; repeating the measurement in that configuration disagreed by 35–115% across the three runs, more than the ~20% this project allows, so only the direction and an order of magnitude are supported, not a single ratio; the ~15x read gain belongs to the earlier single run and was not re-measured in the replication; the 6.85x figure from the earlier one-off run did not reproduce and must not be quoted; the trigger's product is a structural guarantee, not speed; the three runs realized only two distinct design orders (seeds 202 and 303 coincided, and in the sibling read tranche all three seeds coincided); randomized order describes the method, and the realized order is recorded in each manifest; the penalty is size-dependent, not a constant: crossing the same pair with entries per installed product gives 2.07x at 10 entries, 4.38x at 60 and 24.20x at 240, so this ratio holds at the small scale default of 60 entries and must not be quoted as a property of the design without the size (v2–18-maintenance-size-interaction)

Source: studies/04-configuration-portal/reports/20260925T190831Z.md · run 20260925T190831Z · tag run/04-configuration-portal/20260925T190831Z

v2-18-maintenance-size-interaction

rollups / materialized aggregates · run_replicated

Crossing who maintains the parent rollup (trigger n3_rollup_trigger against application n4_rollup_app) with the size of a replacement (10, 60 and 240 entries per installed product) shows the maintenance penalty is a function of size rather than a constant: across 7, 9 and 7 runs at the three sizes the application design delivers roughly 1.1–3.2x the trigger design on whole-configuration replacement at 10 entries, 2.5–9.0x at 60 and 10–24x at 240, the ordering by size holding in every arrangement measured, and no rollup mismatch is recorded at any size.

Trials: 7 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: PostgreSQL single node, small scale, one measurement per tier across 10, 60 and 240 entries per installed product, so the curve carries no spread at any level; one operation only: w05_replace_all replaces the whole configuration, and a workload that appends a single entry would sit at the low end of this curve at any size; the axis is capped by the small scale at 240 entries and the curve is still rising steeply there, so nothing here bounds where it flattens; no negative control in these three runs; control_coverage is recorded absent rather than implied; two designs cannot separate the two mechanisms that predict this shape: the trigger fires once per row written, and its per-row work may also be heavier than the application's single statement; at 60 entries per installation the three runs give a median of 3.42x, about 22% below the 4.38x the first run recorded and below the 3.99–5.69x v2–13 replicated for the same operation, so the corroboration of v2–13 here is approximate - same operation, same size, same direction - and not a match; the ratio at each size is a band describing what has been seen, not a range a future reading must fall inside: 7 runs at 10 entries span 1.06–3.15x, 9 at 60 span 2.51–8.95x and 7 at 240 span 10.20–24.20x, and the two lower bands touch when everything is pooled (3.15 against 2.51) even though every individual arrangement ordered them correctly; arrangement in time decides what a repeat can see: three runs of a size placed next to each other in the session agreed within 15–55%, while the same three runs spread across the session (a Latin square) spread by about 100% - the sequential layout understated the uncertainty because adjacent runs share the session's state; a reference cell measured immediately before and after this tranche moved 445 to 640 ops/s, +44%, so the session was not a stable instrument and the drift it produced is measured rather than inferred; the reference is a different operation from the one compared here and bounds the movement without being its exact size; a band built from six runs did not contain a seventh: tier 10 measured 1.06 against the 1.34–3.15 range the earlier tranches had established; the session does not drift in one direction, it wanders: three readings of one reference cell taken through a single tranche gave 8.64, 5.21 and 8.53, so reading only the start and the end of that tranche would have reported no movement while the middle sat 39% below both; the ratio is more portable than the absolute numbers: over those same three reference readings the ratio spread 40% against 49% for the application design's throughput and 114% for the trigger's, because a session term shared by both designs cancels in the ratio

Source: studies/04-configuration-portal/reports/20260926T152621Z.md · run 20260926T152621Z · tag run/04-configuration-portal/20260926T152621Z

19.4 embedded documents

v2-03-embedding-not-ahead

embedded documents · run_replicated

Embedding the donation child in the donor row (D6 embedded) never came out ahead of the normalized designs on reads: about 1.7–2.2x D1 minimal's read score in two whole runs (2.4x in the first), below both indexed designs, with about 0.57–0.60x D1's insert rate (0.57x in the first).

Trials: 3 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: one run, one trial; embedding here means a JSON/array child column, not a native document database; the band moved down on replication (1.7–2.2x against the quoted 2.4x) while staying below both indexed designs, so the finding is the ordering and the sub-multiple, not the 2.4x

Source: studies/01-charity-tree/reports/20260912-small.md · run 20260912-small · tag none (legacy)

v2-11-section-seat-map

embedded documents · run_replicated

On YugabyteDB the section document (L2 document) answers the 100k-seat map 4.5–11x faster than per-seat rows, while the section-sharded variant (L3 sharded) collapses point lookups to 26 ops/s; PostgreSQL shows no attributable difference. This is a family/package comparison, not a one-decision pair. The engine contrast now has a replication on both halves: the same pair of designs measures 24.4x and 27.8x on yb-single and 0.83x on pg-single, so the substitution is worth about 25x on one engine and nothing on the other.

Trials: 5 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Confounds: conf-03-study03-layout-family-package

Limits: one read-only run, one trial, 5 s per measurement; quota-bound nodes; read-only phases; no control could fire; a difference below ~1.8x cannot be attributed to the design rather than to run-to-run scatter; a replication on yb-single on 2026–09–26, three repeats per cell, reproduced the direction strongly: l2_section_document read the 100k-seat map at 1138 ops/s against l1_claim_rows at 41, a 27.8x multiple against the 20.8x of 2026–09–21, while both absolute figures fell far below the original (l1 by 72 percent, l2 by 63 percent), so the multiple is the claim and the figures are one session's readings; l3_section_sharded has failed its load in all three passes, in three different positions and under two memory envelopes, and with two different symptoms (connections terminated mid-COPY with SQLSTATE 57P01, then connect: connection refused). The sharded collapse therefore cannot be tested on this host with this harness - which is different from having tested it and found nothing; the pair has since been measured in both orders: l1 then l2 gave a 27.8x multiple and l2 then l1 gave 24.4x, a 12 percent difference, so the claim's direction does not depend on which design runs first; the pass that supplied the reversal ran with the database container at 5 GB and the YugabyteDB memory limit at 3 GiB rather than 3 GB and 1.5 GiB, because the earlier passes lost cells to the out-of-memory killer; its absolute figures are therefore not comparable with the 3 GB runs, and only the ratio between the two designs inside a run is; the load failures are memory pressure rather than design behaviour: the database log records server processes terminated by signal 9 (killed), 122 such lines in one cell, on a host with 15 GB of memory - so the sharded half of this claim and its PostgreSQL half are blocked here by host capacity, and a lost cell of this kind never reached the correctness gate rather than failing it; the two passes that supply the AB/BA pair also differ in memory envelope, so the 12 percent agreement may hide an order effect and a memory effect that cancel; a pass at 5 GB in the first pass's order would separate them; the PostgreSQL half was replicated on 2026–09–27 and shows no attributable difference (l2_section_document 6565 ops/s against l1_claim_rows 7873 on the 100k-seat map, a 0.83x multiple), so the finding is the engine contrast - about 25x on YugabyteDB against none on PostgreSQL - rather than the design being faster in general; that PostgreSQL measurement is a single run in a single design order, unlike the YugabyteDB pair which has the AB/BA control; a reverse-order pass there is still owed; l3_section_sharded is declared yugabyte_only_designs in this study's runner and is therefore never attempted on PostgreSQL, so the claim's sharded element can only ever be engine-specific evidence; its 2026–09–21 figures (15.9 and 28.3 ops/s) have not been reproduced on any pass since because its load fails on yb-single; the PostgreSQL half has since been measured in both orders as well: l1 before l2 gave a 0.83x multiple and l2 before l1 gave 0.88x on the 100k-seat map, so the engine contrast (about 25x on YugabyteDB against none on PostgreSQL) now has the same order control on both engines and both halves; l3_section_sharded loads, verifies 65/65 and reproduces its collapse when it is the only cell in a session (2026–09–27), which shows its repeated load failures inside a matrix are a session effect on a machine whose declared container budgets cannot be enforced and not a property of the design; that dedicated run was pre-registered as a diagnostic that would not be folded into this claim, so it is recorded here as a route to measuring the sharded element rather than as the element's replication - accepting it as such is a decision, not a mechanical update

Source: studies/03-reserved-seating/reports/20260921T231328Z.md · run 20260921T231328Z · tag run/03-reserved-seating/20260921T231328Z

v2-gap-06-native-datastore-families

embedded documents · gap · coverage gap

No native document, key-value, graph or wide-column database was measured: JSONB/state is not evidence for a native document database, and Redis was measured only as a cache. Cross-family transfers to native datastores are analogy, not evidence.

Trials: 0 whole-run replications · 0 fresh-load trials per cell · 0 inner iterations

Limits: do not transfer the embedded-document or cache results to a native family

Source: studies/05-cache-consistency/reports/20260921T-survey3.md · run 20260921T-survey3 · tag run/05-cache-consistency/20260921T-survey3

19.5 append-only history / snapshots

v2-07-refund-answerability-and-storage

append-only history / snapshots · run_replicated

A ticketing database chosen only to prevent overbooking cannot report refunds at all: in 14 of 15 designs the refunds report (r05) is unanswerable and the sales/revenue (r01) and last-purchase (r03) reports are wrong across a refund, reproduced in two whole runs in both design orders on PostgreSQL at scale small, with the append-only ledger (X1 CAS+ledger) the only design that answers r05. The ledger's storage cost depends on which relations are counted and moves about a percentage point between runs: about 33–35% more than P3 by table size (33.4% and 34.8% in the two runs, 35.2% in the primary), about 35–36% counting every relation (35.0% and 35.9% in the two runs, 36.2% in the primary), and 37.4–37.9% by index size alone.

Trials: 5 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: answerability is a schema fact, not a timing; the +33–35% storage delta is a relation-size difference measured in the primary run and deterministic for the same dataset and design; it is not a repeated timed result; the P3 -> X1 read rows of this run are excluded, because the difference belongs to the configuration as a whole rather than to one decision inside it; the read phase of this claim's primary anchor 20260920T234953Z was client-CPU throttled by a design-dependent amount (2.3 s for p2_precreated_skip_locked to 58.1 s for r1_inventory_row, out of about 1085 CFS periods), so that report's read figures are not quotable: the hazard reproduces on the current harness (20260929T165533Z, 20260929T170353Z: r1_inventory_row 32.3 s of ~63 s of periods, both orders), and the 2026–09–30 budget calibration shows the client's quota is a symptom rather than the ceiling - the read level on this machine is set by the database's share of four CPUs, and adding a client core removes the client's throttling while making the reads slower. Answerability and the r05 storage/speed result are unaffected: the ledger still answers r05 at 30.3k and 33.0k ops/s against the primary's 32.2k, and at the new 2-worker read footprint the r05 result reproduces independently at 32,164 ops/s (20260930T164028Z), so that number has a footprint-2 footing; all fifteen designs now have one (the eleven-design tranche 20260930T201732Z/20260930T203913Z adds the rest, unthrottled), while this claim's primary anchor's own footprint-8 read figures remain not quotable (design-dependent inflation, 1.09x to 2.22x). **Correction, 2026–09–30: an earlier caveat here said the two many-row queries (q02_band_events, q05_band_tickets_sold) had client-bound levels; it is withdrawn.** A one-worker tranche (20260930T232926Z, 20260930T233744Z) shows that in-flight measured with the **mean** latency is exactly 1.000 in all 72 cells at one worker and 2.00 at two, so every read cell in the family is a store measurement at a stated footprint, and only its magnitude depends on the concurrency. Two errors produced the withdrawn caveat: q05 does not return 28 rows (all three variants return one - COUNT/SUM with no GROUP BY), and in-flight computed from the **median** understates the concurrency by the latency skew (mean/p50 up to 2.7x), which reads exactly like a worker idling between fetches. The primary anchor's **PostgreSQL read cells have since been re-stated** on the footprint-2 footing (analysis 20261001T-read-cells-restated: all fifteen designs, both orders, every cell store-bound at 2.00 operations in flight), so its `pg-single` read figures may be replaced rather than caveated. All fifteen designs have since been measured in a **single run**, twice and in reversed order (20261001T100948Z, 20261001T103931Z): 0 throttled periods in all 30 read phases and every one of the 270 cells store-bound at 2.00 operations in flight by the mean latency, so the family's levels are jointly comparable within that session. Two consequences for quoting: the top group (h0, h1, r1, r2, p4) differs by 4%, inside that session's own order term, so its internal ranking is not quotable - only the 1.5x gap between that group and the per-seat group is; and c1_count_naive carries a 40% position term (first of one order against last of the other), so its q01 level should not be quoted from these runs. Its two **YugabyteDB read arms have no replacement** and remain an explicit coverage gap; the storage percentage depends on the rule and on the page layout, and must not be quoted as one number: tables only 33.4–35.2%, every relation 35.0–36.2%, indexes alone 37.7%; the same pair's relation sizes moved 0.26% (p3) and 0.41% (x1) between two runs 29 minutes apart, so the delta moved 0.9 percentage points; the index-only figure spans 37.4–37.9% across the five runs, so even there the rule is a band and not a point, and the 2026–10–02 replication's M4 (reproducible within 1%) is falsified by that movement - a tighter figure would need a vacuumed comparison, which is a different measurement; the answerability statuses are the harness's own audit of its own schema, computed as a pure function of the design and emitted inside the read phase; the 2026–10–02 replication therefore tests reproducibility across two whole runs and not the independence of the audit's rule, and it re-measured no timing

Source: studies/02-ticket-booking/reports/20260920T234953Z.md · run 20260920T234953Z · tag run/02-ticket-booking/20260920T234953Z

v2-08-ledger-race-cost-128-buyers

append-only history / snapshots · run_replicated

At 128 buyers the append-only ledger's cost over compare-and-set rises with the size of the event rather than sitting in one band: on PostgreSQL it is about 1.1x at 10 seats (where the direction is not reliable), about 1.2–1.4x at 100–1000 seats, about 1.8x at 10000 seats and about 2.5x at 100000 seats, measured in twelve whole runs in both design orders, with wide spreads at the small tiers. The 1.8–2.2x on YugabyteDB, the 2.1–2.5x on the refund itself and the up-to-5x delay to the organiser's own edit are single-run figures that have not been re-measured, and no design ever under-booked a seat.

Trials: 12 whole-run replications · 5 fresh-load trials per cell · 1 inner iteration

Confounds: conf-05-study02-buyer-arms-disagree

Limits: one small run, closed loop, quota-bound nodes; scoped to 128 buyers; must not be extrapolated to 32 buyers; single run, three trials per tier; replicated on 2026–09–27 in both design orders at 128 buyers, three trials per tier: the p3/x1 ratio came out 1.53x, 1.71x and 2.00x at 100, 1000 and 10000 seats in the first order and 0.99x, 1.30x and 1.74x in the reversed order, so the ratios reproduce in size while the lowest of them falls below this claim's 1.1x floor; the ordering is not stable at the smallest tier: CAS read 4163 against the ledger's 2724 at 100 seats in the first order (1.53x) and 3588 against 3618 in the reversed order (0.99x), i.e. the ledger marginally faster - so the designs swap places at a fixed buyer count, which is what v2–09 records for changing buyer counts; the former 'tight spreads' wording did not hold at that tier: the 100-seat cell spread 57% for CAS and 37% for the ledger in the first order, and 47% and 51% in the reversed order, while every other tier stayed within 4–17% - and because the wide spread appeared at the same tier in both orders it belongs to the cell rather than to a design's position in the session; re-scoped on 2026–09–27 (HIGH, task repo/v2–08-rescope): the flat 1.1–2.3x band and the words 'tight spreads' were removed from the statement because the cost measured across the tier axis is monotone (about 1.1x at 10 seats to about 2.5x at 100000) and the small-tier cells spread 47–77%; the superseded wording, the evidence behind each change, and the earlier post-v6 re-scopings of v2–06 and v2–11, are recorded in book/evidence/v6/SUPERSESSION_LEDGER.md; the earlier 'single run, three trials per tier' limit describes the primary run only; the claim now rests on 8 whole runs (2 at 3 trials across 3 tiers, then 6 at 5 trials across the 100- and 1000-seat tiers); settled on 2026–09–27 by a third tranche of six runs (5 fresh-load trials per cell, three in each design order): the 100-seat p3/x1 run median was 1.279, 1.333, 1.257, 1.712, 1.328 and 1.476, so the single 0.99x reading of the reversed replication does not reproduce and the former band is not widened by this evidence; the ledger was slower in 29 of the 30 individual trial pairs (pooled per-trial median ratio 1.391x, range 0.940–1.920); the former 'tight spreads' wording still failed at the 100-seat tier across all eight runs: the cell's spread was 47–77% for CAS and 26–54% for the ledger in the six settle runs, and the run-to-run spread of the tier-100 ratio is 34% over those six and 54% over all eight (0.992–1.712, median 1.331), so that tier supports a direction and not a point ratio; the 1000-seat positive control read 1.304–1.712 in all six settle runs, so the harness detected the ledger's cost in every run; correctness was green throughout (46/46 P3, 48/48 X1 verifications, 0 over-booked, 0 under-booked, 0 timed-out), and no settle cell is void; the tier axis was then measured on 2026–09–27 in four more whole runs (5 trials per cell, two runs in each design order, all five tiers measured in every run): the pooled run-median p3/x1 rose 1.075, 1.237, 1.409, 1.845 and 2.505 at 10, 100, 1000, 10000 and 100000 seats, monotone in the pooled medians and in every individual run, so the ledger's cost is a function of tier and the claim's former 1.1–2.3x band described its middle three tiers rather than the whole axis; the statement's YugabyteDB, refund and organiser-edit figures come from the primary run alone and are labelled as not re-measured; the replication programme covered only the PostgreSQL race, so nothing here re-measures them, and v2–09's finding that the design order moves the ratio at the small sizes still applies; both endpoint tiers lie outside the former band and had never been repeated before this tranche: at 10 seats the run medians were 1.023–1.180 (pooled 1.075, below its 1.1x floor) while the per-trial median was 1.131 and the ledger was slower in only 12 of 20 trial pairs, so the cost there sits at the floor and its direction flips in 40% of trials; at 100000 seats the ledger was slower in 20 of 20 pairs (pooled per-trial median 2.456, run medians 2.249–2.637), above the 2.3x top; the 100000-seat tier is a single event per trial, so its 20 trial pairs are 20 readings of one event and an event-specific effect would be indistinguishable from a tier effect; the 10-seat cell is near-degenerate (100 events of 10 seats against 128 buyers) and its cells spread 16–71%; correctness was green in all four tier-axis runs (0 over-booked, 0 under-booked, 0 timed-out, 0 errors); with the two earlier tranches the tier-100 reading now rests on twelve runs whose run medians span 0.992–1.712 (median 1.331, spread 54%), so that tier still offers a direction rather than a point ratio

Source: studies/02-ticket-booking/reports/20260921T205212Z.md · run 20260921T205212Z · tag run/02-ticket-booking/20260921T205212Z

v2-09-postgres-ledger-ratio-unsettled

append-only history / snapshots · run_replicated

On PostgreSQL the ledger is slower than compare-and-set at 1,000 seats at every buyer count tested, 8 to 128, and in both design orders (55 of 55 trial pairs over eleven runs), so the two designs do not change places with the load: the primary run's apparent swap came from its own confound, buyer count and design order having moved together. The size of the cost does vary without a simple trend (about 1.2–1.3x near 16–32 buyers and 1.4–1.9x at 64–128; one 8-buyer cell changed state mid-run), and the design order moves absolute throughput several-fold without changing which design is faster. On YugabyteDB the primary run's own range is 1.7–5.7x, wider than a headline would quote.

Trials: 11 whole-run replications · 5 fresh-load trials per cell · 1 inner iteration

Confounds: conf-05-study02-buyer-arms-disagree

Limits: the stable direction is measured at 1,000 seats across 8–128 buyers and at 32 buyers across all five tiers; the buyer-count axis is not swept at the other four tiers, so the full buyer x tier surface is open; one primary run per (buyers, order) cell, with a reference cell that moved 8.6% between the two ends of the tranche, so a level whose two orders differ by more than that is placed by the ratio and not by the absolutes; the direction is stable but the ratio is not: the eleven run medians span 1.06–5.10 (1.22–1.86 with the collapsed 8-buyer cell set aside), so the cost is a range and not a point; the 8-buyer level's pooled median is not interpreted: a recurrence test of six runs and twelve cells (2026–09–29, tag study-02/v2–09–8buyer) found four low-throughput events in 60 trials, readings of 619–655 ops/s against a session normal of about 2500 (a 4x drop), and they hit both designs (three of the four in the CAS arm) and both orders, so the low mode is a property of this buyer count's very short trials and not of the ledger; the original p3-first cell read as a state change only because its slow trials were its last three, which set the cell median; the primary evidence is from a different harness state (phases verify,write,race,churn on a five-day-old image), so comparing it with this tranche mixes the confound with a period effect and the re-scope is stated as a direction, not a ratio; one side of the primary comparison is a partial configuration on yb-cluster3 (medians of two measurements); at 32 buyers the ledger was slower in all ten tier x order cells of two 2026–09–29 runs (ratios 1.021–1.606) and below the 128-buyer pooled ratio at every tier (1.06 vs 1.08, 1.06 vs 1.24, 1.23 vs 1.41, 1.56 vs 1.85, 1.56 vs 2.51), so the primary's tier-wide reversal does not reproduce anywhere on the axis; those two runs are anchors but are not counted in the eleven-run replication record, which is the buyer-count sweep at one tier; at 32 buyers and 10–100 seats the direction sits at the measurement's floor: only 3 of 10 trial pairs at 10 seats and 6 of 10 at 100 favour the CAS design, with cell spreads of 86–174%, so those two tiers support the median and not a per-pair claim, while the 1,000-seat cell reproduced the sweep's ratio a day later within 1% (1.245 and 1.219 against 1.233 and 1.219); the 8-buyer low-throughput mode is not a quota effect on either side: the twelve cells' per-trial client_cpu entries (present since the study's first commit, and corrects an earlier limit here that said the client was not recorded) show zero client throttling and *more* client CPU in the slow trials (2.6–2.8 s against about 1.9 s), so the client waits rather than starves, while the database container's cpu.stat throttled about 4 ms across the collapsed cell; the cause is narrowed to a latency excursion on the response path and is not identified further, since no per-trial plan or server-side clock is recorded; three of the four 8-buyer low events were single trials that recovered on the next trial and one spanned consecutive trials, so 'persistent collapse' and 'transient spike' are names for where the event fell in the cell (a five-trial median cannot distinguish them at a ~7% event rate); no 8-buyer magnitude is quoted from either tranche

Source: studies/02-ticket-booking/reports/20260921T183722Z.md · run 20260921T183722Z · tag run/02-ticket-booking/20260921T183722Z

v2-gap-01-ledger-load-multiplier-unstable

append-only history / snapshots · gap · unstable measurement

The append-only ledger's load-time multiplier is not published: the same pair and loader measured X1's pg-single load at 7.8x P3's in one run and 1.2x in the two sibling runs, with an empty harness diff.

Trials: 3 whole-run replications · 1 fresh-load trial per cell · 1 inner iteration

Limits: a single one-off load of one configuration is not a cost of the design; needs its own repeated load-only measurement before any multiplier can be quoted; the read phase of this claim's primary anchor 20260920T234953Z was client-CPU throttled by a design-dependent amount (2.3 s to 58.1 s across designs, out of about 1085 CFS periods) and the hazard reproduces on the current harness (20260929T165533Z, 20260929T170353Z), so that report's read figures are not quotable; the load-phase figures this claim rests on are a separate phase and were not throttled. The read family has since been re-measured at the new 2-worker read footprint for four designs (20260930T164028Z, 20260930T164834Z): their read levels are quotable with the footprint attached, and all fifteen designs now have a footprint-2 footing (the eleven-design tranche 20260930T201732Z/20260930T203913Z adds the rest, unthrottled, and 20261001T100948Z/20261001T103931Z measures all fifteen together in one session); this claim's primary anchor's own footprint-8 read figures remain not quotable

Source: studies/02-ticket-booking/reports/20260920T234953Z.md · run 20260920T234953Z · tag run/02-ticket-booking/20260920T234953Z

v2-gap-02-hold-funnel-unanswerable

append-only history / snapshots · gap · schema limitation

No Study 03 design can answer the hold funnel report that would size the 40-minute hold window: releasing an expired hold clears the row, so an expired hold is indistinguishable from a seat never held.

Trials: 0 whole-run replications · 0 fresh-load trials per cell · 0 inner iterations

Limits: a schema limitation, not a missing measurement

Source: studies/03-reserved-seating/reports/20260921T231328Z.md · run 20260921T231328Z · tag run/03-reserved-seating/20260921T231328Z

19.6 external read copies / caches

v2-14-cache-throughput-gain

external read copies / caches · run_replicated

Adding a cache to warm cacheable reads buys 2.2–2.5x in throughput: two whole pg-single + Redis runs on 2026–10–02 measured the cached warm read at 2.54x and 2.24x the no-cache owned baseline, inside the primary's 2.2–3.5x band. The primary's p99 clause did not reproduce: the cached tail here was 8.5–10.1 ms against the baseline's 26.9–27.6 ms, a cut of about 3x rather than the primary's order of magnitude (0.8–2.0 ms against 15.8–27.1 ms), so the claim carries the throughput band and records the tail as not reproduced under this client. The cache's own CPU and memory are not counted against the database side (db-only framing), and Redis here is a shared cache, never an authoritative key-value store.

Trials: 3 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Confounds: conf-04-study05-db-only-cache

Limits: one machine, closed loop, small scale (800 donors), PostgreSQL + Redis cache only; the p99 clause did not reproduce: cached p99 8.5–10.1 ms against the baseline's 26.9–27.6 ms (about 3x), where the primary recorded 0.8–2.0 ms against 15.8–27.1 ms; the tail is suspected client-bound at this client budget and was not isolated with a plan or a footprint cell; warm cacheable reads only; the Redis container's budget is outside the db-only comparison (the equal-total framing is a separate claim, v3–03); absolute throughput is session-specific; only the within-run ratio travels; the 2.2–3.5x range remains supported only by the PostgreSQL single-node + Redis cells; do not transfer it to YugabyteDB, a cluster, or open-loop demand

Source: studies/05-cache-consistency/reports/20260921T-survey3.md · run 20260921T-survey3 · tag run/05-cache-consistency/20260921T-survey3

v2-15-three-instance-staleness

external read copies / caches · mechanism_supported

Three logical application instances sharing one Redis cache on write-through with relaxed freshness record about 87% wrong reads, while every relaxed configuration on a single instance records none; a private in-memory lease cannot coordinate separate instances, and a database version token that is never checked does not remove the problem. The 87.81% belongs to the owned model (o:opt:red:wth:rel) and 87.24% to the legacy model.

Trials: 1 whole-run replication · 1 fresh-load trial per cell · 1 inner iteration

Confounds: conf-04-study05-db-only-cache

Limits: single trial, one machine, small scale; generality unproven; the 87%-vs-0% separation is far outside the ~20% noise floor, but the exact rate is one trial; the signed all-green analysis swapped the two models' rows; this claim uses the report and JSON attribution

Source: studies/05-cache-consistency/reports/20260921T-survey3.md · run 20260921T-survey3 · tag run/05-cache-consistency/20260921T-survey3

v2-16-strict-freshness-read-cost

external read copies / caches · run_replicated

The strict-freshness contract cost nothing measurable in READ throughput: the controlled strict/relaxed pair differed by 7.3% in one whole run and 5.7% in the other with the sign flipping, inside the cells' 8.7%-22.8% trial spread, so the null reproduced in both design orders. This claim measures read throughput only: it does not quantify the write-path cost of a strict protocol, and it must never be restated as 'strict freshness is free'.

Trials: 3 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Confounds: conf-06-claim12-full-noise-range, conf-04-study05-db-only-cache

Limits: read throughput only; the two fresh runs' trial spreads reached 22.8%, so only an effect larger than that could have been seen; small scale, closed loop, one machine; the strict/relaxed pair here is the owned write-through pair; a strict protocol's write-path cost is not measured

Source: studies/05-cache-consistency/reports/20260921T-survey3.md · run 20260921T-survey3 · tag run/05-cache-consistency/20260921T-survey3

v3-01-churn-crosses-real-ttl

external read copies / caches · single_run_directional

A sustained 1801 s churn phase against the fixed 300 s TTL crossed 6.0 real TTL boundaries with 0 wrong reads in 2,879,077 blended reads and 380,824 writes; the hard-expiry counter is 0 and only probabilistic early expiry fired (37,063), so an entry was never observed to be removed by its hard TTL. This is scoped mechanism and duration evidence, not a general cache result.

Trials: 1 whole-run replication · 1 fresh-load trial per cell · 1 inner iteration

Limits: one PostgreSQL + Redis configuration at small scale; one sustained measurement, never repeated; hard expiry fired zero times; that clause is an open gap, not a confirmation; closed loop, so read volumes are a floor; the 5x-for-120 s burst has no write-rate knob and was not run; the 1800 s horizon was not re-run on 2026–10–02: the 600 s pair recorded for v3–02 re-tests the same mechanism at a shorter horizon, and this claim's 1801 s / 6.0-boundary figure remains the primary's single run

Source: studies/05-cache-consistency/reports/20260923T1100Z-churn1800-through.md · run 20260923T1100Z-churn1800-through · tag run/05-cache-consistency/20260923T1100Z-churn1800-through

v3-02-churn-600-through-vs-aside

external read copies / caches · run_replicated

At 601 s the write-through and write-aside churn cells each crossed 2.0 real 300 s TTL boundaries with 0 wrong reads, in two whole runs in reversed order (through 2.004/2.003 boundaries with 1,326,612 and 885,864 reads; aside 2.003/2.004 with 1,173,729 and 1,156,637), and neither strategy is claimed to win. One aside cell recorded 1 impossible cache value in 1,173,729 reads while its gate passed, so the study's floor that an impossible value must always be zero did not hold cleanly and the gate does not classify impossible values during churn.

Trials: 4 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Limits: the cache container's own resources are not counted in this comparison; hard expiry fired 0 times in every cell; only probabilistic early expiry fired, and the 5x burst was not run; closed loop, so read volumes are a floor; one cell (20261002T191609Z, aside-strict) recorded 1 impossible cache value that the gate did not catch; it is not repeated in the other three cells and has no identified cause, and the gate's coverage of impossible values during churn is a recorded gap

Source: studies/05-cache-consistency/reports/20260923T1020Z-churn600-through.md · run 20260923T1020Z-churn600-through · tag run/05-cache-consistency/20260923T1020Z-churn600-through

v3-03-equal-total-framing-labelled

external read copies / caches · run_replicated

Cache resource accounting carries a second, separately labelled comparison in which both sides are given the same total resources: two whole runs on 2026–10–02 recorded the db-only framing at 8,199 warm ops/s (cache budget none) and the equal-total framing at 7,931 (cache 1 CPU / 768 MiB), 3.3% apart inside the 17.7%/18.4% trial spread, with resource_framing and both budgets recorded in every result. What the claim asserts is that the two ways of counting resources are labelled and never pooled; the primary's 11k/8.0k point figures did not reproduce and are not quoted.

Trials: 4 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Limits: what matters is that the two framings are labelled and kept apart, not the ratio between them; the fresh runs are 3.3% apart, inside the 17.7%/18.4% spread; the primary's 11k/8.0k figures did not reproduce; one host, small scale, each framing measured once per session

Source: studies/05-cache-consistency/reports/20260923T1150Z-res2-equaltotal-pg.md · run 20260923T1150Z-res2-equaltotal-pg · tag run/05-cache-consistency/20260923T1150Z-res2-equaltotal-pg

v3-04-yb-single-strict-relaxed

external read copies / caches · run_replicated

On YugabyteDB 1-node (RF=1) the strict and relaxed write-through reads differ by 1.043x and 1.105x, both inside the cells' 21.7%-74.7% trial spread, so the strict/relaxed read difference is a null on one node too. The primary's direction (relaxed 596 above strict 514) did not reproduce: both fresh runs lean strict-slightly-ahead, also inside spread, so no design is named the more consistent one.

Trials: 3 whole-run replications · 3 fresh-load trials per cell · 1 inner iteration

Limits: single endpoint (RF=1); this is not a cluster result; the trial spreads are large (up to 74.7%), so the null is weak evidence; the primary's direction (relaxed ahead) did not reproduce; the fresh runs lean strict-ahead, still inside spread

Source: studies/05-cache-consistency/reports/20260923T1152Z-res2-yb1.md · run 20260923T1152Z-res2-yb1 · tag run/05-cache-consistency/20260923T1152Z-res2-yb1

v3-05-yb-cluster3-strict-relaxed

external read copies / caches · single_run_directional

On YugabyteDB 3-node (RF=3), where the client spreads operations over all three endpoints, one run recorded the strict write-through read at 942 ops/s against the relaxed configuration's 846, the opposite direction from the 1-node pair, with each configuration measured once and no engine ranked.

Trials: 1 whole-run replication · 1 fresh-load trial per cell · 1 inner iteration

Limits: one run per freshness policy; direction is not repeated and differs from the 1-node pair; three containers on one host, no real network; endpoint spread is round-robin by construction; app-99 phases have large spread (50.4% relaxed, 49.4% strict); not re-measured on 2026–10–02: yb-cluster3 RF=3 does not fit the fixed 2 GiB podman machine, so the opposite-direction result remains the primary's single run and this target is an explicit coverage gap

Source: studies/05-cache-consistency/reports/20260923T1157Z-res2-yb3.md · run 20260923T1157Z-res2-yb3 · tag run/05-cache-consistency/20260923T1157Z-res2-yb3

v3-gap-01-study05-remaining-regimes

external read copies / caches · gap · partially superseded by v4-gap-01-physical-placement-unverified, v4-gap-02-endpoint-distribution-partial · coverage gap + instrument gap

Moved to successor claims: v4-gap-01-physical-placement-unverified, v4-gap-02-endpoint-distribution-partial.

Still open in this claim: hard-TTL expiry never observed removing an entry; medium scale beyond the harness maximum of 3,000 people; open-loop arrival demand.

Statement below is unchanged from its source registry; the moved dimensions are not restated as open here.

Four things about the cache study remain unmeasured, and they are absences of evidence rather than results: no entry was ever seen to reach its hard expiry (0 hard expiries in all three churn configurations), nothing beyond the harness maximum of 3,000 people was run, the distribution of tables and leaders across the cluster is unrecorded, and no open-loop arrival pattern was run.

Trials: 0 whole-run replications · 0 fresh-load trials per cell · 0 inner iterations

Limits: these are coverage gaps, not null results; medium scale is an order of magnitude beyond the current generator; placement verification needs an instrument the runner does not have; open-loop demand is owned by task-20260922T200831Z-study05-v2-open-loop

Source: studies/05-cache-consistency/reports/20260923T1100Z-churn1800-through.md · run 20260923T1100Z-churn1800-through · tag run/05-cache-consistency/20260923T1100Z-churn1800-through

19.7 Retired predecessor claims

- `claim-gap-04-study02-03-validation-open` — Retired in v1->v2; the validation it described completed 2026-09-22. Kept in the v3 chain so the retirement history stays readable.
- `v2-gap-04-study05-unmeasured-regimes` — Superseded by v3-01..v3-06 plus v3-gap-01: real-TTL churn, repeated trials, equal-total accounting and YugabyteDB/cluster cells are now measured; the still-open regimes are retained explicitly in v3-gap-01.
- `v2-gap-05-colocation-unverified` — Retired: its clause 'Study 05's placement pair was never executed' is contradicted by v3-06, which executed the key-locality pair. The physical-placement clause is carried forward, narrowed, in v4-gap-01. *Closed:* Study 05 key-locality pair executed (v3-06).
- `v2-gap-07-real-network-balanced-endpoints` — Retired: its clause 'balanced client access across cluster endpoints is not proven' is contradicted for the 2026-09-23 Study 05 cells by v3-05, whose client spreads over all three endpoints. The remaining endpoint-distribution and no-real-network clauses are carried forward, narrowed, in v4-gap-02. *Closed:* Study 05 three-node endpoint spread (round-robin over three endpoints).