

# Magnetosensory Power Devices Based on AlGa<sub>N</sub>/Ga<sub>N</sub> Heterojunctions for Interactive Electronics

Xinyu Zhou, Qilin Hua, Wei Sha, Jiyuan Zhu, Ting Liu, Chunyan Jiang, Qi Guo, Liang Jing, Chunhua Du, Junyi Zhai,\* Weiguo Hu,\* and Zhong Lin Wang\*

The advances in biological magnetoreception and microelectronics have promoted the vigorous development of interactive electronic devices capable of noncontact interaction and control via magnetic fields. Here, a magnetosensory power device (MPD) that integrates a magnetic film ((Fe<sub>90</sub>Co<sub>10</sub>)<sub>78</sub>Si<sub>12</sub>B<sub>10</sub>) unit into a cantilever-structured AlGa<sub>N</sub>/Ga<sub>N</sub>-based high-electron-mobility-transistor is presented. The MPD is capable to not only sense external magnetic field, but also control device output power with the emulation of magnetoreception. Specifically, the device can achieve significant control of output power density (18.04 to 18.94 W mm<sup>-2</sup>) quasi-linearly with magnetic field stimuli (0–400 mT) at a gate bias of –5 V. In addition, the maximum output power density of the MPD can reach 85.8 W mm<sup>-2</sup> when a gate bias of 1 V is applied. The simulation and experimental results show that MPD has excellent orientation and magnetic field sensing functions under 0–400 mT magnetic fields. With the intelligent capabilities of magnetic sense and output power control, such interactive electronic devices will have broad application prospects in the fields of artificial intelligence, advanced robotics, and human-machine interfaces.

## 1. Introduction

Biological studies have suggested that a variety of animals have the ability to perceive the geomagnetic field, including insects,<sup>[1]</sup> amphibians,<sup>[2]</sup> reptiles,<sup>[3]</sup> fish,<sup>[4]</sup> and birds.<sup>[5]</sup> Migratory birds, for instance, have been suggested to not only orient themselves by sensing the inclination of the field,<sup>[6]</sup> but also may deduce their location by discerning minute local variations in the geomagnetic field.<sup>[7,8]</sup> Driven by the ongoing rapid advance of artificial intelligence (AI), neuroscience, and bionics, the development of bionic smart devices has made significant progress, such as the bionic eye,<sup>[9]</sup> artificial synapse network,<sup>[10]</sup> bionic artificial nerve,<sup>[11]</sup> bionic skins,<sup>[12]</sup> etc. The biomimetic applications of magnetoreception in nature would be an appealing source from which inspiration can be drawn to develop magnetosensory

X. Zhou, Q. Hua, W. Sha, C. Jiang, Q. Guo, L. Jing, J. Zhai, W. Hu, Z. L. Wang  
CAS Center for Excellence in Nanoscience  
Beijing Key Laboratory of Micro-nano Energy and Sensor  
Beijing Institute of Nanoenergy and Nanosystems  
Chinese Academy of Sciences  
Beijing 101400, China  
E-mail: jyzhai@binn.cas.cn; huweiguo@binn.cas.cn;  
zhong.wang@mse.gatech.edu

X. Zhou, Q. Hua, W. Sha, C. Jiang, Q. Guo, L. Jing, J. Zhai, W. Hu, Z. L. Wang  
School of Nanoscience and Technology  
University of Chinese Academy of Sciences  
Beijing 100049, China  
J. Zhu  
State Key Laboratory of ASIC and System  
School of Microelectronics  
Fudan University  
Shanghai 200433, China

T. Liu  
College of Mathematics and Physics  
Beijing University of Chemical Technology  
Beijing 100029, China  
C. Du  
Key Laboratory for Renewable Energy  
Beijing Key Laboratory for New Energy Materials and Devices  
Beijing National Laboratory for Condensed Matter Physics  
Institute of Physics  
Chinese Academy of Science  
Beijing 100190, China  
J. Zhai, W. Hu, Z. L. Wang  
Research Center for Optoelectronic Materials and Devices  
School of Physical Science and Technology  
Guangxi University  
Nanning 530004, China  
Z. L. Wang  
School of Materials Science and Engineering  
Georgia Institute of Technology  
Atlanta, GA 30332-0245, USA

The ORCID identification number(s) for the author(s) of this article can be found under <https://doi.org/10.1002/aelm.202200941>.

© 2022 The Authors. Advanced Electronic Materials published by Wiley-VCH GmbH. This is an open access article under the terms of the Creative Commons Attribution License, which permits use, distribution and reproduction in any medium, provided the original work is properly cited.

DOI: 10.1002/aelm.202200941