

## **ARTICLE**

https://doi.org/10.1038/s41467-019-14234-7

OPEN

## Strain-controlled power devices as inspired by human reflex

Shuo Zhang<sup>1,2,7</sup>, Bei Ma<sup>3,7</sup>, Xingyu Zhou<sup>1,2,7</sup>, Qilin Hua <sup>1,2\*</sup>, Jian Gong<sup>4</sup>, Ting Liu<sup>1,2</sup>, Xiao Cui<sup>1,2</sup>, Jiyuan Zhu<sup>1,2</sup>, Wenbin Guo<sup>1,2</sup>, Liang Jing<sup>1,2</sup>, Weiguo Hu<sup>1,2,5\*</sup> & Zhong Lin Wang <sup>1,2,5,6\*</sup>

Bioinspired electronics are rapidly promoting advances in artificial intelligence. Emerging AI applications, e.g., autopilot and robotics, increasingly spur the development of power devices with new forms. Here, we present a strain-controlled power device that can directly modulate the output power responses to external strain at a rapid speed, as inspired by human reflex. By using the cantilever-structured AIGaN/AIN/GaN-based high electron mobility transistor, the device can control significant output power modulation  $(2.30-2.72\times10^3\,\mathrm{W\,cm^{-2}})$  with weak mechanical stimuli (0–16 mN) at a gate bias of 1 V. We further demonstrate the acceleration-feedback-controlled power application, and prove that the output power can be effectively adjusted at real-time in response to acceleration changes, i.e.,  $\Delta P$  of 72.78–132.89 W cm<sup>-2</sup> at an acceleration of 1–5 G at a supply voltage of 15 V. Looking forward, the device will have great significance in a wide range of AI applications, including autopilot, robotics, and human-machine interfaces.

1

<sup>&</sup>lt;sup>1</sup>CAS Center for Excellence in Nanoscience, Beijing Key Laboratory of Micro-nano Energy and Sensor, Beijing Institute of Nanoenergy and Nanosystems, Chinese Academy of Sciences, Beijing 100083, China. <sup>2</sup> School of Nanoscience and Technology, University of Chinese Academy of Sciences, Beijing 100049, P. R. China. <sup>3</sup> Graduate School of Electrical and Electronic Engineering, Chiba University, Chiba 263-8522, Japan. <sup>4</sup> Estuarine and Coastal Environment Research Center, Chinese Research Academy of Environmental Sciences, Beijing 100012, P. R. China. <sup>5</sup> Center on Nanoenergy Research, School of Physical Science and Technology, Guangxi University, Nanning 530004, China. <sup>6</sup> School of Materials Science and Engineering, Georgia Institute of Technology, Atlanta, GA 30332-0245, USA. <sup>7</sup>These authors contributed equally: Shuo Zhang, Bei Ma, Xingyu Zhou. \*email: huaqilin@binn.cas.cn; huweiguo@binn.cas.cn; zhong.wang@mse.gatech.edu