Chapter 10 solutions

CH10-E1

1. Use -1 at the tail and $+1$ at the head.

$$A = \begin{bmatrix} -1 & 1 & 0 & 0 \\ 0 & -1 & 1 & 0 \\ -1 & 0 & 1 & 0 \\ 0 & 0 & -1 & 1 \end{bmatrix}.$$

2. The graph is connected, so

$$\operatorname{rank} A = 4 - 1 = 3, \qquad \dim N(A) = 1.$$

The kernel is the span of $(1, 1, 1, 1)^T$.

3. With $m = n = 4, r = 3$, left nullity is 1. The cycle $1 \to 2 \to 3 \to 1$ has edge signs $+1, +1, -1$, giving

$$y = (1, 1, -1, 0)^T, \qquad A^T y = 0.$$

The final edge $3 \to 4$ is outside the cycle.

4. Choose $x = (0, 0, 0, 2)^T$, whose differences are $(0, 0, 0, 2)^T$. Pairing with the cycle flow gives

$$y^T A x = 0 + 0 + (-1)0 + 0 = 0.$$

This verifies orthogonality between potential differences and circulations.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

CH10-E2

1. Delete the row for edge $2 \to 3$.

$$B = \begin{bmatrix} -1 & 1 & 0 & 0 \\ -1 & 0 & 1 & 0 \\ 0 & 0 & -1 & 1 \end{bmatrix}.$$

$$L = B^T B = \begin{bmatrix} 2 & -1 & -1 & 0 \\ -1 & 1 & 0 & 0 \\ -1 & 0 & 2 & -1 \\ 0 & 0 & -1 & 1 \end{bmatrix}.$$

2. Since $B\mathbf{1} = 0$, we have $L\mathbf{1} = 0$. Symmetry gives zero column sums as well.

3. Delete row and column 4 to ground node 4.

$$L_{\text{red}} = \begin{bmatrix} 2 & -1 & -1 \\ -1 & 1 & 0 \\ -1 & 0 & 2 \end{bmatrix}.$$

4. Solve

$$2x_1 - x_2 - x_3 = 1,$$
$$-x_1 + x_2 = 0, \qquad -x_1 + 2x_3 = 0.$$

The last two equations give $x_2 = x_1$ and $x_3 = x_1/2$. The first then gives $x_1 = 2$, so

$$x = (2, 2, 1, 0)^T.$$

Edge differences:

$$Bx = (0, -1, -1)^T.$$

Substitution gives

$$B^T B x = (1, 0, 0, -1)^T,$$

The first three entries match the reduced equation. The final -1 balances flow at the ground node. The complete Laplacian right-hand side must sum to zero.

Lin Cing https://github.com/xinhi6716/computer-science-self-study

CH10-E3

1. With fixed ends, the unknown displacements are u_1, u_2, u_3.

$$e = \begin{bmatrix} 1 & 0 & 0 \\ -1 & 1 & 0 \\ 0 & -1 & 1 \\ 0 & 0 & -1 \end{bmatrix} \begin{bmatrix} u_1 \\ u_2 \\ u_3 \end{bmatrix}.$$

2. For $C = \operatorname{diag}(c_1, c_2, c_3, c_4)$,

$$K = A^T C A = \begin{bmatrix} c_1 + c_2 & -c_2 & 0 \\ -c_2 & c_2 + c_3 & -c_3 \\ 0 & -c_3 & c_3 + c_4 \end{bmatrix}.$$

3. If every $c_i = 1$,

$$K = \begin{bmatrix} 2 & -1 & 0 \\ -1 & 2 & -1 \\ 0 & -1 & 2 \end{bmatrix}.$$

for nonzero u,

$$u^T K u = \sum_i e_i^2 > 0.$$

the fixed boundaries and connected springs force $Au = 0$ only at $u = 0$, so K is positive definite. Leading minors $2, 3, 4$ provide another check.

4. For the same three masses, free ends remove the two springs attached to walls. Set $c_1 = c_4 = 0$, retaining $c_2, c_3 > 0$. Then

$$u^T K u = c_2(u_2 - u_1)^2 + c_3(u_3 - u_2)^2.$$

zero energy holds exactly when $u_1 = u_2 = u_3$, so $N(K) = \operatorname{span}\{(1, 1, 1)^T\}$. Translating all masses together stretches no spring and produces no restoring force.

Lin Cing https://github.com/xinhi6716/computer-science-self-study

CH10-E4

1. Nonnegative entries and unit column sums prove the stated convention.
2. $$\det(P - \lambda I) = (0.8 - \lambda)(0.7 - \lambda) - 0.06 = \lambda^2 - 1.5\lambda + 0.5.$$

The eigenvalues are 1 and 0.5. For $\lambda = 1$,

$$(P - I)v = 0$$

writing a generic eigenvector as $(a, b)^T$ gives $2a = 3b$. Choose stationary eigenvector $(3, 2)^T$. For $\lambda = 0.5$, choose

$$v_2 = (1, -1)^T.$$

3. Normalize the stationary eigenvector to total 1.

$$u_\infty = (0.6, 0.4)^T.$$

4. Expand

$$u_0 = au_\infty + b(1, -1)^T.$$

The second component gives $b = 0.4a$, and the first gives

$$1 = 0.6a + b = 0.6a + 0.4a = a.$$

Hence $a = 1, b = 0.4$, so

$$u_k = u_\infty + 0.4(0.5)^k(1, -1)^T.$$

The nonstationary factor 0.5^k gives the exact convergence rate in this example.

Lin Cing https://github.com/xinhi6716/computer-science-self-study

CH10-E5

1.

$$\det(A - \lambda I) = (0.2 - \lambda)(0.1 - \lambda) - 0.12 = \lambda^2 - 0.3\lambda - 0.1.$$

Roots:

$$\lambda = \frac{0.3 \pm \sqrt{0.09 + 0.4}}{2} = \frac{0.3 \pm 0.7}{2},$$

The roots are $0.5, -0.2$, so the spectral radius is 0.5.

2.

$$I - A = \begin{bmatrix} 0.8 & -0.3 \\ -0.4 & 0.9 \end{bmatrix}.$$

The determinant is $0.72 - 0.12 = 0.6$, giving

$$(I - A)^{-1} = \frac{1}{0.6} \begin{bmatrix} 0.9 & 0.3 \\ 0.4 & 0.8 \end{bmatrix}.$$

3.

$$p = (I - A)^{-1} \begin{bmatrix} 1 \\ 2 \end{bmatrix}.$$

The components are $(0.9 + 0.6)/0.6 = 2.5$ and $(0.4 + 1.6)/0.6 = 10/3$. Therefore

$$p = \left(\frac{5}{2}, \frac{10}{3}\right)^T.$$

4. The spectral radius is below 1, so powers tend to zero and the Neumann series converges absolutely. Nonnegativity makes its terms direct demand, indirect demand, and successive rounds of intermediate demand.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

CH10-E6

1. The equality constraint is

$$x_1 + x_2 + 2x_3 = 4.$$

Set two nonbasic variables to zero to obtain vertices

$$(4, 0, 0), \quad (0, 4, 0), \quad (0, 0, 2).$$

Their convex hull is the complete feasible triangle.

2. Objective values:

$$20, \quad 12, \quad 16.$$

The unique minimum is 12 at $(0, 4, 0)$.

3. Primal:

$$\min 5x_1 + 3x_2 + 8x_3$$

subject to $x_1 + x_2 + 2x_3 = 4, x \geq 0$.

Dual:

$$\max 4y$$

subject to

$$y \in \mathbb{R}, \quad y \leq 5, \quad y \leq 3, \quad 2y \leq 8.$$

The dual point $y = 3$ is feasible and gives value 12. Weak duality then proves optimality with zero gap.

4. The three vertex costs differ strictly, giving one optimal vertex and hence one optimum on this triangle. Distinct reported optima require checking tolerances or errors. In a general LP, if two distinct vertices are optimal, their joining segment is optimal. Different bases representing one point instead indicate degeneracy.

Lin Cing https://github.com/xinhi6716/computer-science-self-study

CH10-E7

1. The mean over one period is zero. Also $f(2\pi - x) = -f(x)$ away from the jump endpoints, while cosine is unchanged, so the cosine integrals cancel.
2. $$b_n = \frac{1}{\pi}\left(\int_0^{\pi} \sin(nx)\,dx - \int_{\pi}^{2\pi} \sin(nx)\,dx\right).$$

This gives

$$b_n = \begin{cases} \dfrac{4}{\pi n}, & n \text{ odd}, \\ 0, & n \text{ even}. \end{cases}$$

3. $$f_N(x) = \frac{4}{\pi} \sum_{\substack{1 \le n \le N \\ n \text{ odd}}} \frac{\sin(nx)}{n}.$$
4. The coefficient $b_n = \langle f, \sin(nx)\rangle/\pi$ multiplies $\sin(nx)$; the product $b_n \sin(nx)$ is the orthogonal projection. Truncation omits the higher orthogonal components.

$$\|f - f_N\|_2^2 = \pi \sum_{n>N, n \text{ odd}} \frac{16}{\pi^2 n^2} = \frac{16}{\pi} \sum_{n>N, n \text{ odd}} \frac{1}{n^2}.$$

Since $\|\sin nx\|_2^2 = \pi$, the basis-norm factor must be retained. Adding a nonzero odd mode strictly decreases error; adding a zero-coefficient even mode leaves it unchanged. The finite identity $\|f - f_N\|^2 = 2\pi - \pi \sum_{n \le N} b_n^2$ checks the result without first using infinite Parseval. Pointwise behavior near jumps involves Gibbs oscillations and is a separate question.

CH10-E8

1. Use homogeneous column coordinates.

$$T(2,-1)=\begin{bmatrix}1&0&2\\0&1&-1\\0&0&1\end{bmatrix},$$

$$S(3)=\begin{bmatrix}3&0&0\\0&3&0\\0&0&1\end{bmatrix},$$

$$R_{90}=\begin{bmatrix}0&-1&0\\1&0&0\\0&0&1\end{bmatrix}.$$

2. Rotation about $c=(2,-1)$ gives

$$M=T(c)R_{90}T(-c)=\begin{bmatrix}0&-1&1\\1&0&-3\\0&0&1\end{bmatrix}.$$

Define the homogeneous center $c_h=(2,-1,1)^T$. Direct multiplication gives $Mc_h=c_h$. Multiplication of the 3×3 matrix by the two-dimensional c would be undefined.

3. The point $(1,0,1)^T$ becomes $(3,-1,1)^T$. The direction $(1,0,0)^T$ is unchanged because its last coordinate is zero.

4. Unit normal $n=(1,2)^T/\sqrt{5}$:

$$P=I-nn^T=\begin{bmatrix}4/5&-2/5\\-2/5&1/5\end{bmatrix},$$

$$M=I-2nn^T=\begin{bmatrix}3/5&-4/5\\-4/5&-3/5\end{bmatrix}.$$

P projects onto the line $n^Tx=0$ through the origin, and M reflects across that line. For column vectors, the rightmost matrix acts first. Since $x=Px+(n^Tx)n$, reflection gives $Mx=Px-(n^Tx)n=2Px-x$.

The displayed P, M are the two-dimensional linear parts. Their homogeneous forms are $\mathrm{diag}(P,1)$ and $\mathrm{diag}(M,1)$, both 3×3.

Lin Cing https://github.com/xinhi6716/computer-science-self-study

CH10-E9

1.

$$\det K = 1 \cdot 5 - 2 \cdot 3 = -1 \equiv 28 \pmod{29}.$$

Since 29 is prime and 28 is nonzero modulo 29, the key is invertible.

2. 2×2 inverse:

$$K^{-1} = 28^{-1} \begin{bmatrix} 5 & -2 \\ -3 & 1 \end{bmatrix}.$$

The inverse of $28 \equiv -1$ is itself. Negating the adjugate entries gives

$$K^{-1} = \begin{bmatrix} 24 & 2 \\ 3 & 28 \end{bmatrix} \pmod{29}.$$

Check $K^{-1}K = I \pmod{29}$.

3. Message $x = (5, 8)^T$:

$$y_1 = 5 + 16 = 21,$$
$$y_2 = 15 + 40 = 55 \equiv 26 \pmod{29}.$$

The ciphertext block is $(21, 26)^T$.

4. Decode:

$$x_1 = 24(21) + 2(26) \pmod{29} = 5,$$
$$x_2 = 3(21) + 28(26) \pmod{29} = 8.$$

This cipher uses $y = Kx \pmod{29}$, with no translation term. If two known plaintext blocks form invertible $X = [x^{(1)}\ x^{(2)}]$, with corresponding ciphertexts $Y = [y^{(1)}\ y^{(2)}]$, then $Y = KX$ gives $K = YX^{-1} \pmod{29}$. Blocks on a single line may fail to identify K uniquely; their rank matters, not merely their count. This linear structure and small key space do not provide modern cryptographic security.

CH10-E10

1. Using head potential minus tail potential,

$$A = \begin{bmatrix} -1 & 1 & 0 & 0 \\ -1 & 0 & 1 & 0 \\ 0 & -1 & 0 & 1 \\ 0 & 0 & -1 & 1 \end{bmatrix}, \qquad C = \operatorname{diag}(1, 2, 3, 4).$$

take x in V and c_e in S, or A/V. Then $e = Ax$ is in V; $y = Ce$, $j = -y$, and f are in A. Positive injection adds current to a node, balanced by net outward edge current. Summing the edge outer products gives

$$L = A^T C A = \begin{bmatrix} 3 & -1 & -2 & 0 \\ -1 & 4 & 0 & -3 \\ -2 & 0 & 6 & -4 \\ 0 & -3 & -4 & 7 \end{bmatrix}.$$

2. Reversing the second edge gives

$$D = \operatorname{diag}(1, -1, 1, 1), \qquad A' = DA.$$

Since both D and C are diagonal,

$$(A')^T C A' = A^T\, D\, C\, D\, A = A^T C A = L.$$

the second difference and weighted difference change sign, $e_2' = -e_2$, $y_2' = -y_2$. Therefore $(A')^T y' = A^T\, D^2 y = A^T y = f$. The orientation changes the coordinates, not the physical flow or balance.

3. The injection sum is

$$-4 - 4 - 10 + 18 = 0.$$

Deleting node 1 gives

$$L_{\text{red}} = \begin{bmatrix} 4 & 0 & -3 \\ 0 & 6 & -4 \\ -3 & -4 & 7 \end{bmatrix}, \qquad f_{\text{red}} = (-4, -10, 18)^T.$$

Solve

$$4x_2 - 3x_4 = -4, \qquad 6x_3 - 4x_4 = -10, \qquad -3x_2 - 4x_3 + 7x_4 = 18$$

so $x_2 = 2$, $x_3 = 1$, $x_4 = 4$, and $x = (0, 2, 1, 4)^T$.

4. The differences and weighted differences are

$$e = Ax = (2, 1, 2, 3)^T, \qquad y = Ce = (2, 2, 6, 12)^T.$$

The physical currents are $j = -y = (-2, -2, -6, -12)^T$. Also

$$-A^T j = A^T y = (-4, -4, -10, 18)^T = f.$$

The quadratic functional is

$$\frac{1}{2} x^T L x = \frac{1}{2}(1 \cdot 2^2 + 2 \cdot 1^2 + 3 \cdot 2^2 + 4 \cdot 3^2) = 27,$$

and

$$\frac{1}{2} f^T x = \frac{1}{2}(-4 \cdot 2 - 10 \cdot 1 + 18 \cdot 4) = 27.$$

the two forms agree and are independent of a common potential offset. Here $x^T L x = \sum_e c_e e_e^2 = 54$ has units W and is total dissipated power. Its half, 27, is half the power, not stored energy in J. In the spring model, $\frac{1}{2} u^T K u$ is elastic potential energy. The algebraic forms agree but the physical units differ.

Lin Cing https://github.com/xinhi6716/computer-science-self-study

5. Replacing the last source by 17 gives $\mathbf{1}^T f = -1 \neq 0$. Since $A\mathbf{1} = 0$, $\mathbf{1}^T L x = 0$, so $f \notin C(L) = C(A^T) = N(A)^\perp$ and the full system is inconsistent. A grounded solve can still return a vector, but implicitly changes node 1's injection from -4 to -3, adding $+1$ unit of current. Without an explicitly modeled ground reaction or external source, that silently changes conservation. Correct the data or explicitly add the compensating source and boundary conditions before solving.

CH10-E11

1. Initially $x_1 = 0, s_1 = 0, s_2 = 1, B = I_2$. The reduced cost is -1, the direction is $B^{-1}a_1 = (1, 1)^T$, and the ratios are 0 and 1. Choose 0. Variable x_1 enters and s_1 leaves, giving $x_1 = -s_1, s_2 = 1 + s_1$. The vertex stays fixed.
2. Choosing the strictly positive ratio 1 gives $(x_1, s_1, s_2) = (1, -1, 0)$. Both equalities hold, but $s_1 < 0$ violates feasibility. Even a zero basic value must constrain the step.
3. The new objective is $-x_1 = s_1 \geq 0$, attained at $(0, 0, 1)$, so the optimum is 0. This degenerate basic feasible solution has a zero basic value; a zero-step pivot changes the basis without strictly decreasing the objective.
4. For standard form $\min c^T x$, $Ax = b$, $x \geq 0$, assume full row rank and a feasible current basic solution. Every feasible point satisfies $c^T x = c_B^T B^{-1} b + \sum_{j \notin B} \bar{c}_j x_j$. Nonnegative reduced costs make this no smaller than the current basic objective. If some $\bar{c}_j < 0$ and $d = B^{-1}a_j \leq 0$, set $x_j = t$, $x_B(t) = B^{-1}b - dt \geq 0$ for any $t \geq 0$. The equalities remain valid while the objective tends to $-\infty$ through $\bar{c}_j t$, certifying unboundedness.

CH10-E12

The reduced matrix is [[5,−3],[−3,4]], with determinant 11 and inverse (1/11)[[4,3],[3,5]]. Multiplying by $(-3,15)^T$ gives $(3,6)^T$, so $x=(0,3,6)^T$ V. The omitted row gives $f_1=-2\cdot 3-6=-12$ A; $f=(-12,-3,15)^T$ A sums to zero.

Edge differences are $(3,3,6)^T$ V. Multiplying by diag(2,3,1) S gives $y=(6,9,6)^T$ A and $j=-y$. Thus actual currents are 6 A from 2 to 1, 9 A from 3 to 2 and 6 A from 3 to 1. Node 3 receives 15 A externally; nodes 1 and 2 withdraw 12 and 3 A. Power is $2\cdot 3^2+3\cdot 3^2+1\cdot 6^2=81$ W, equal to $x^TLx=x^Tf$.

With recorded injection $(-11,-3,15)^T$ A, the reduced right-hand side is unchanged but $Lx-f=(-1,0,0)^T$ A. Total recorded injection is 1 A, contradicting $1^TL=0$. A reference choice cannot remove this inconsistency. If a physical voltage source is added at ground, its unknown current must appear in the model. Ideal resistors dissipate power rather than store energy; $\frac{1}{2}x^TLx$ has units W here, not J. For constant power over duration Δt, dissipated energy is $81\Delta t$ joules when Δt is in seconds.

References and attribution

Lin Cing, handwritten linear algebra notes. Gilbert Strang, Introduction to Linear Algebra, 5th ed., Chapter 10. Original educational synthesis by Lin Cing, licensed under CC BY 4.0.
https://github.com/xinhi6716/computer-science-self-study

Lin Cing https://github.com/xinhi6716/computer-science-self-study