Chapter 7. Deadlocks. Exercises

Original problems. State assumptions, units, and intermediate reasoning. Answers are in the separate solutions PDF.

OS07-E01. Four necessary conditions

Two processes each hold one exclusive lock and wait for the other lock.

1. Identify the four necessary conditions concretely.
2. Does making one lock preemptible necessarily solve the whole system's deadlock problem?
3. Is a cycle sufficient if another instance can be released?

Check your approach. Necessary conditions organize the analysis; proof of deadlock must exclude the relevant progress transitions.

OS07-E02. Safe and unsafe states

Available=(2,1,0). Allocation is P1=(1,0,0), P2=(0,1,0), P3=(0,0,1). Need is P1=(1,1,0), P2=(2,1,0), P3=(3,0,0).

1. Find a safe completion order.
2. What is Work after P1 completes and returns its allocation?
3. Change P1's Need to (2,1,1). Validate Max against total resources and determine whether the changed state remains safe.

Check your approach. Check 0<=Allocation<=Max<=Total, then show every Work and Finish update.

OS07-E03. Victim selection

A resource is reclaimed while its owner has modified only half the nodes needed for a shared-tree update.

1. Why is merely releasing its lock unsafe?
2. Which recovery unit can restore a consistent state?
3. How can victim selection avoid starvation?

Check your approach. Recovery integrity and victim fairness require separate arguments.

Chapter 7. Deadlocks. Exercises (continued)

OS07-E04 Resource-graph cycle

R1 has two instances. P1 holds one and waits for unique R2. P2 holds R2 and waits for R1. P3 holds the other R1 and needs nothing else.

1. List request and assignment edges.
2. Is there a cycle and do the four conditions appear?
3. Is the state deadlocked? Give a completion order.

OS07-E05 Banker request

> T0 Total=(10,5,7), Available=(3,3,2). P0…P4 Allocation=(0,1,0),(2,0,0),(3,0,2),(2,1,1),(0,0,2); Need=(7,4,3),(1,2,2),(6,0,0),(0,1,1),(4,3,1). P1 requests(1,0,2).
>
> 1. Check claim and availability componentwise.
> 2. Give trial Available, Allocation1, Need1.
> 3. Show every safety Work row and a safe sequence.
> 4. What must happen if a trial is unsafe?

OS07-E06 Multi-instance detection and recovery

Total=(7,2,6), Available=(0,0,0). P0…P4 Allocation=(0,1,0),(2,0,0),(3,0,3),(2,1,1),(0,0,2); Request=(0,0,0),(2,0,2),(0,0,1),(1,0,0),(0,0,2).

1. Show Work, feasible process, and Finish at every reduction.
2. Identify the final deadlocked set.
3. Abort P1. Show returned resources and remaining reduction.
4. Why does recovery require rollback as well as reclaiming locks?

Chapter 7. Deadlocks. Exercises (continued)

OS07-E07 One cycle, two outcomes

> R1 has two instances and R2 one; vectors use (R1,R2). Initially Available=(0,0). Allocations for P1/P2/P3 are (1,0), (0,1), (1,0); current requests are (0,1), (1,0), (0,0). After its current request is satisfied, each process can finish and return all holdings. There is no early release, preemption, or cancellation.
>
> 1. Draw instances, assignment edges, and request edges. Identify a cycle. Does this cycle alone establish deadlock?
> 2. Reduce from Work=(0,0), giving every Request≤Work test, returned allocation, and new Work. Must live Available equal (2,1) when this simulation ends?
> 3. Execute that completion order and list Available after each grant and actual return. Include the deductions made by grants.
> 4. Change only P3's Request to (0,1). Show all three failed vector comparisons, identify the deadlocked set, and name the added edge.

References and attribution

Abraham Silberschatz, Peter B. Galvin, Greg Gagne. Operating System Concepts, 9th Edition.

Original educational synthesis by Lin Cing. Original material is licensed under CC BY 4.0. The referenced textbook is not distributed with these notes.

https://github.com/xinhi6716/computer-science-self-study