Chapter 7. Deadlocks. Full solutions

These original derivations correspond to the stable identifiers in the separate exercises PDF.

OS07-E01. Four necessary conditions

1. A and B are exclusive. P1 holds A while requesting B and P2 holds B while requesting A. Neither lock is reclaimable under the original rule. The allocation/request edges form A→P1→B→P2→A.
2. If reclamation safely releases a needed instance and allows a waiter to continue, it breaks this cycle. But reclamation may itself wait for another resource or leave inconsistent data. Its complete protocol must therefore be analyzed rather than treating a preemptible label as a solution.
3. No. In a multiple-instance model another owner can finish, release an instance, and start a sequence that resolves the cycle. A consistent reduction is needed.

Validation criterion. Necessary conditions organize the analysis; proof of deadlock must exclude the relevant progress transitions.

OS07-E02. Safe and unsafe states

1. Total resources are (3,2,1). The original maxima are P1=(2,1,0), P2=(2,2,0), P3=(3,0,1), all within that total. P1 fits Work=(2,1,0); after its completion Work=(3,1,0). P2 fits next, producing (3,2,0). P3 then fits, producing (3,2,1). Thus P1, P2, P3 is safe.
2. Work becomes (2,1,0)+(1,0,0)=(3,1,0). The temporary resources supplied to meet Need return on completion, leaving a net increase equal to the preexisting Allocation.
3. Changed Max1=(3,1,1) remains legal. P1 cannot start because the third resource is unavailable. P2 can finish and leaves Work=(2,2,0). P1 still lacks the third resource; P3 requires three first-type instances but only two are available. No further reduction is possible, so the changed state is unsafe. This does not prove a current deadlock, since maximum future demands need not already be outstanding.

Validation criterion. Check 0<=Allocation<=Max<=Total, then show every Work and Finish update.

Chapter 7. Deadlocks. Full solutions (continued)

OS07-E03. Victim selection

1. The new lock owner could see an intermediate representation that violates the tree invariant. Exclusion ends before the protected update is complete.
2. Roll back to a transaction or checkpoint, or publish a complete new copy using an atomic commit protocol. Saving only the lock's ownership cannot reconstruct the data.
3. Include prior victim counts or aging in a bounded selection rule, as well as rollback cost and priorities. Explicit scheduling and recovery assumptions are still needed to guarantee eventual completion.

Validation criterion. Recovery integrity and victim fairness require separate arguments.

OS07-E04 Resource-graph cycle

1. Requests P1→R2, P2→R1. Assignments R1→P1, R1→P3, R2→P2. No instance is initially free.
2. Cycle P1→R2→P2→R1→P1 exists. Resources are exclusive; P1/P2 hold and wait; there is no forced preemption; circular wait appears. Circular wait already implies hold-and-wait.
3. P3 can finish and release R1. P2 then takes it, finishes and returns R2. P1 then finishes. Thus this multiple-instance cycle does not establish deadlock. The completion argument assumes P3 is scheduled and actually returns its resource.

OS07-E05 Banker request

1. $(1,0,2) \le \text{Need1}(1,2,2)$ and $\le \text{Available}(3,3,2)$. This only authorizes trial.
2. Trial Available=(2,3,0), Allocation1=(3,0,2), Need1=(0,2,0); all other rows unchanged.
3. Work(2,3,0). P1 Need(0,2,0) fits→(5,3,2). P3 Need(0,1,1) fits→(7,4,3). P4 Need(4,3,1) fits→(7,4,5). P0 Need(7,4,3) fits→(7,5,5). P2 Need(6,0,0) fits→(10,5,7). Sequence ⟨P1, P3, P4, P0, P2⟩ certifies safety and the request can commit.
4. Restore Available, Allocation_i, and Need_i to the pre-request state before waiting. No partial debit/allocation may remain. The simulated completion adds existing Allocation, not Need.

Chapter 7. Deadlocks. Full solutions (continued)

OS07-E06 Multi-instance detection and recovery

1. All Allocation rows are nonzero, so initial Finish all false. Work=(0,0,0). P0's zero request fits, giving Work=(0,1,0), Finish=(true, false, false, false, false). No other request fits.
2. P1/P2/P3/P4 remain detected deadlocked holders; P0 can complete.
3. If P0 has not actually finished, safely aborting P1 returns only (2,0,0), so actual Available=(2,0,0). Restart Work at that value: simulate P0→(2,1,0), P3→(4,2,1), P2→(7,2,4), P4→(7,2,6), checking each current Request≤Work before returning its Allocation. This certifies a survivor completion sequence; simulated Finish does not release real resources. Available=(2,1,0) immediately after abort is valid only if P0 has already completed in the real execution.
4. Reclaiming exclusion does not undo partial updates. Roll back the victim to a consistent transaction/checkpoint before survivors observe its data; preserve resource conservation and prevent unlimited repeated victimization separately.

OS07-E07

> **Graph and criterion.** Assign R1a→P1, R1b→P3, R2a→P2. Requests are P1→R2 and P2→R1. The cycle is P1→R2→P2→R1→P1. R1 has two instances, so the cycle alone does not establish deadlock; P3 can finish first.
>
> **Simulated reduction.** P3: (0,0)≤(0,0), return (1,0), Work=(1,0). P2: (1,0)≤(1,0), return (0,1), Work=(1,1). P1: (0,1)≤(1,1), return (1,0), Work=(2,1). No process remains. If only this calculation has run, live Available is still (0,0).
>
> **Actual execution.** P3 finishes→(1,0); grant P2 one R1→(0,0); P2 finishes and returns both types→(1,1); grant P1 one R2→(1,0); P1 finishes→(2,1). Each actual return includes the newly granted request as well as previous holdings.
>
> **Modified case.** Start Work=(0,0). P1's (0,1) fails in component 2; P2's (1,0) fails in component 1; P3's (0,1) also fails in component 2. All hold resources and none can finish first, so the deadlocked set is {P1,P2,P3}. Adding P3→R2 blocks the owner that could previously release R1b. The new cycle P3→R2→P2→R1→P3 shares R2 with the original cycle.

References and attribution

Abraham Silberschatz, Peter B. Galvin, Greg Gagne. Operating System Concepts, 9th Edition.

Original educational synthesis by Lin Cing. Original material is licensed under CC BY 4.0. The referenced textbook is not distributed with these notes.

https://github.com/xinhi6716/computer-science-self-study