Prerequisites and objectives

- Prerequisites are binary heaps, linked trees, induction, logarithms, and amortized analysis.
- Derive structures from meld requirements. Trace leftist, binomial, Fibonacci, and standard two-pass pairing heaps.
- Distinguish actual work, worst-case bounds, and amortized bounds. State whether decrease-key already has a valid node handle.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Mergeable priority queue contract

- A heap represents a multiset, allowing duplicate keys. Meld combines all elements of two heaps while preserving element identities.
- We use destructive meld. Source heaps no longer own transferred nodes afterward. Keeping independently mutable source copies has different costs.
- Decrease-key uses a valid node handle and lowers that node's key. Searching for an arbitrary key cannot be hidden inside an O(1) or O(log n) bound.
- With tied minima, any minimum may be returned. Stable order requires a composite key such as key plus insertion sequence number.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Leftist heap rank

- Define `rank(null)=0` and `rank(x)=1+min(rank(left),rank(right))`. Rank measures the shortest path to an empty child position.
- Maintain min-heap order and the leftist property `rank(left)≥rank(right)`.
- Therefore `rank(x)=rank(right)+1`. The right-spine length equals rank. The left side may be deep. Overall height need not be balanced.
- Texts assigning null rank −1 shift all ranks by one. Do not mix their constants with this convention.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Why the right spine is logarithmic

- Rank r implies both child ranks are at least r−1. Minimum size satisfies $N(r) \geq 1 + 2N(r-1)$, with N(0)=0.
- Induction gives $N(r) \geq 2^r - 1$, hence $r \leq \log_2(n+1)$.
- The right spine is rank-bounded, but tree height can be Θ(n). General search or parent-chain decrease-key cannot inherit the spine bound.
- The asymmetric constraint bounds exactly the path used by meld without maintaining unnecessary global height balance.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Leftist meld and correctness

1. If either heap is empty, return the other. Otherwise let a be the smaller root.
2. Set `a.right=meld(a.right,b)`.
3. If left rank is smaller than right rank, swap children. Recompute a.rank.

The smaller root preserves heap order. Recursion returns a valid heap, and swapping restores the leftist property. Each recursive step consumes one original right-spine node, giving worst-case $O(1+\log(n_1+1)+\log(n_2+1))$ time and stack space.


Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Complete leftist operations and tree states

```
leftist_meld(a,b):
    if a==null: return b
    if b==null: return a
    if a.key>b.key: swap(a,b)
    a.right=leftist_meld(a.right,b)
    if rank(a.left)<rank(a.right): swap(a.left,a.right)
    a.rank=rank(a.right)+1; return a
```

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Complete leftist operations and tree states (continued)



H1=(3;7,9), H2=(4;8, null) keep 3 and recurse on meld(9,4). Keep 4 and attach 9 at its right, raising rank 4 from 1 to 2. At 3, left rank 1 is below right rank 2, so swap: 3.left=4,3.right=7, rank 3=2. The right spine is 3→7. Delete-min melds 4 with 7; recursively meld 9 with 7, keep 7 with 9 on its left, then return 4 with two rank 1 children and rank 2.

Leftist insertion and delete-min

- Insert melds with a singleton. Delete-min removes the root and melds its child heaps. Both have worst-case O(log n) heap work.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Binomial trees B_k

- B_0 is a singleton. Form B_k from two B_{k-1} trees by making one root a child of the other.
- Induction gives 2^k nodes, height k, root degree k, and child subtrees B_0 through B_{k-1}.
- A binomial heap stores heap-ordered binomial trees with at most one root of each degree.
- The binary expansion of n determines the degrees. For $n=13=1101_2$, the forest contains B_0, B_2, B_3.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Binomial meld as binary carrying

- Merge root lists by degree. For two equal-degree trees, compare roots and link the larger root below the smaller.
- Two B_k trees become B_{k+1}, like a binary carry. With three equal-degree trees, retain one and link the other two.
- At most $\lfloor \log_2 n \rfloor + 1$ roots exist. Standard eager consolidation meld takes worst-case O(log n).
- Melding sizes $5=101_2$ and $3=011_2$ carries through degrees 0,1,2, leaving one B_3 with eight nodes.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Binomial linking and dedicated insertion

```
binomial_link(a,b):
    require degree(a)==degree(b)
    if a.key>b.key: swap(a,b)
    make b a child of a; a.degree+=1; return a
binomial_insert(x):
    carry=singleton(x); d=0
    while tree[d] exists: carry=link(carry,tree[d]); clear tree[d]; d+=1
    tree[d]=carry; update min pointer
```

Binomial degree lists {0,2}+{0,1} carry B0+B0→B1, then B1+B1→B2, then B2+B2→B3. General meld merges ordered root lists and processes carries; with three equal degrees retain one and link the other two. Linking all three under one root would break binomial shape. Delete-min melds the removed root's B0..Bk−1 children with the remaining roots. Without a maintained min pointer, finding the minimum scans O(log n) roots. Decrease-key swaps payloads up O(log n) parents with corresponding handle-index maintenance.

Conditions for other binomial operations

- A dedicated insertion adds B_0 and carries from low degrees, stopping as soon as carrying ends. Its worst case is O(log n), but carry accounting gives amortized O(1). Calling a meld that always scans the entire root list does not automatically obtain this insertion bound.
- Delete-min finds and removes the minimum root, reverses its child list into increasing degree order, then melds. Worst-case time is O(log n).
- Find-min costs O(log n) if it scans roots. A maintained minimum-root pointer makes it O(1).
- Decrease-key can exchange contents up the parent chain in O(log n). Node-identity handles require compatible handling of those content exchanges.

Complete binomial meld and delete-min consolidation

```
meld_roots(R1,R2):
    by_degree=empty
    for x in concatenation of detached root snapshots R1,R2:
        while by_degree[x.degree] contains y:
            clear by_degree[x.degree]
            x=binomial_link(x,y)
        by_degree[x.degree]=x
    return roots in degree order; recompute minimum pointer
delete_min():
    require roots not empty
    z=minimum root
```

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Complete binomial meld and delete-min consolidation (continued)

```
    remove z from roots
    children=detach z.children; clear their parent pointers
    release z
    roots=meld_roots(roots,children)
decrease_key(x,new):
    require new<=x.key; x.key=new
    while x.parent!=null and x.key<x.parent.key:
        swap complete key-value contents and update handle mapping
        x=x.parent
    update minimum pointer
```

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

The degree-table meld has the same binary-carry semantics as ordered-list consolidation. Input forests have only O(log n) roots, and total links are O(log(n1+n2)). This does not apply to Fibonacci's unconsolidated Θ(n) root list.

Complete binomial meld and delete-min consolidation (continued)

Take B2 root 3 with child 7 and child 5→8. Deleting 3 produces B_0 root 7 and B_1 root 5. If another B_0 root 1 exists, meld links 1 with 7 into B_1, then links it with 5's B_1 into B_2 rooted at 1. Five original nodes become four after deletion, matching 2^2. Payload swapping requires synchronized handle-to-node mapping if handles identify logical elements.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Fibonacci heaps defer consolidation

- A Fibonacci heap has a heap-ordered forest, circular doubly linked root list, minimum-root pointer, and degree and mark fields per node.
- Insert adds a singleton root. Meld splices root lists and updates the minimum pointer. Neither immediately consolidates equal degrees.
- Delete-min promotes the removed root's children, links equal-degree roots using a degree table, then rebuilds the minimum pointer.
- Nodes can lose children, so trees do not retain fixed binomial shapes. Cascading cuts are needed for the degree bound.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Decrease-key and cascading cuts

1. Lower x.key. If it remains at least its parent's key, no cut is needed.
2. Otherwise cut x from parent p, add x to the root list, and clear x.mark.
3. If p is not a root, mark it on its first lost child. If already marked, cut p and continue upward.

A nonroot node can lose at most one child after its latest attachment and still remain under that parent. Roots need not be marked on losing children.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Fibonacci consolidation and mark operations

```
link_equal_degree_roots(a,b):
    require a.degree==b.degree
    if a.key>b.key: swap(a,b)
    roots=ring_remove(roots,b)
    a.child=ring_prepend(a.child,b)
    b.parent=a; b.mark=false; a.degree+=1
    return a
cut(x,p):
    p.child=ring_remove(p.child,x); p.degree-=1
    x.parent=null; x.mark=false; roots=ring_prepend(roots,x)
cascade(p):
    g=p.parent
```

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Fibonacci consolidation and mark operations (continued)

```
    if g==null: return
    if not p.mark: p.mark=true
    else: cut(p,g); cascade(g)
decrease_key(x,new):
    require new<=x.key; x.key=new
    p=x.parent
    if p!=null and x.key<p.key: cut(x,p); cascade(p)
    if x.key<min.key: min=x
delete_min():
    require min!=null
    return extract_root(min)
```

Consolidating singleton roots [7,3,8,5] in that order puts 7 at degree 0. Root 3 links 7 below it to form degree 1. Root 8 occupies degree 0; root 5 links 8 below it, then collides with degree 1 root 3. Root 3 wins, with child 7 and child 5→8, degree 2. Iterate a snapshot or use mutation-safe root traversal while linking.

Fibonacci consolidation and mark operations (continued)

For marked nonroots p and g in a valid state, illustrate r=2→g=3→p=5→x=7 with g and p marked. Decreasing x to 1 cuts x, p, g into roots. Root count changes 1→4 and marked count 2→0, so Φ changes 5→4, ΔΦ=−1. Scaling potential pays fixed cut costs with constant endpoints left over. This state illustrates accounting only; the general degree bound still requires the attachment-time and one-lost-child proof.

Insert adds an unmarked singleton root and updates min. Destructive meld splices root cycles and transfers ownership. Empty delete-min rejects, and removal of the last node sets min=null. Arbitrary-node deletion uses the complete erase(handle) and extract_root procedures below without changing keys. A forced cut notifies the old parent through cascade even when heap order was not violated.

Complete circular-list operations and shared consolidation

```
ring_remove(head,x):
    if x.right==x: head=null
    else:
        x.left.right=x.right; x.right.left=x.left
        if head==x: head=x.right
    x.left=x.right=x; return head
ring_prepend(head,x):
    require x.left==x and x.right==x
    if head!=null:
        x.left=head.left; x.right=head
        head.left.right=x; head.left=x
    return x
snapshot_of_root_ring():
    S=[]
    if roots==null: return S
    x=roots
    repeat: S.append(x); x=x.right
    until x==roots
```

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Complete circular-list operations and shared consolidation (continued)

```
    return S
consolidate():
    A=[]                        // missing degree entries mean null
    for x in snapshot_of_root_ring():
        if x.parent!=null: continue
        while len(A)<=x.degree: A.append(null)
        while A[x.degree]!=null:
            y=A[x.degree]; A[x.degree]=null
            x=link_equal_degree_roots(x,y)
            while len(A)<=x.degree: A.append(null)
        A[x.degree]=x
    roots=null; min=null
    for x in nonnull entries of A:
        x.left=x.right=x; x.parent=null; x.mark=false
        roots=ring_prepend(roots,x)
        if min==null or x.key<min.key: min=x
```

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Complete circular-list operations and shared consolidation (continued)

Ring_remove requires x to belong to the designated ring. A singleton yields null. Otherwise reconnect both neighbors and move the representative if necessary. Make the removed x a singleton before passing it to ring_prepend. Both operations change constantly many pointers without a predecessor search. Using them for root and child rings makes cut, promotion, and link explicit.

Snapshot root pointers before linking modifies the ring. Equal-degree roots compare keys; remove the larger root from roots, attach it to the smaller root's child ring, clear its mark, and increase the parent's degree, using link_equal_degree_roots from the earlier page. Clear the old table entry before carrying to the new degree. Each surviving table entry represents one valid heap-ordered tree.

Complete circular-list operations and shared consolidation (continued)

Rebuild roots and min from the table without traversing the discarded old ring. Never read old min.key after releasing its node, or skip comparisons merely because z was not the old minimum. Grow the degree table as needed, using O(1+log(n+1)) entries. With t′ roots after cutting and target degree d, this snapshot version additionally stores O(t′+d) root pointers, worst-case O(n); auxiliary space is not just the degree table. One operation may also take Θ(n) actual time. Amortized time and instantaneous space are different claims.

Why Fibonacci degrees stay logarithmic

- Order x's k retained children by attachment time. When child i was linked, x already had at least i−1 earlier retained children. Equal-degree linking means the new child then had degree at least i−1.
- A child retained under x can have lost at most one child. Its current degree is at least max(0, i−2).
- A minimum-subtree-size recurrence then gives at least F_{k+2} nodes for degree k, hence degree O(log n).
- The bound connects permitted child losses to degree. Omitting cascading cuts invalidates this argument.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Deriving the Fibonacci size bound

- Let S(k) be the minimum possible subtree size among nodes of degree at least k, including the root. This definition is nondecreasing in k. S(0)=1 and S(1)≥2.
- Any node of degree at least k has k children with degree lower bounds max(0, i−2). Thus for k≥2, $S(k) \geq 1 + 2S(0) + \sum_{j=1}^{k-2} S(j)$.
- Inductively substitute $S(j) \geq F_{j+2}$ to obtain $S(k) \geq 3 + \sum_{j=1}^{k-2} F_{j+2} = F_{k+2}$. The last identity is a Fibonacci prefix sum, with F_0=0, F_1=1.
- Since $F_{k+2} \geq \varphi^k$ for $\varphi = (1 + \sqrt{5})/2 > 1$, every degree in an n-node heap satisfies $k \leq \log_\varphi n$. This justifies an O(log n) degree table.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Potential accounts for deferred work

- Use $\Phi = t + 2m$, where t counts roots and m counts marked nonroots. Amortized cost is $\hat{c} = c + \Phi_{\text{after}} - \Phi_{\text{before}}$.
- Insert increases roots by one and potential by a constant. Meld combines additive potentials and takes constant amortized work.
- Cutting a marked ancestor adds one root but clears one mark, reducing potential by one. Repeated cuts release potential to pay their actual work, apart from constant endpoint changes.
- Multiplying Φ by a sufficient fixed implementation constant pays for the constant pointer work per cut or link. Starting empty, nonnegative potential makes total actual work at most total amortized work plus initial potential. This is a worst-sequence guarantee, not a random average.

One Fibonacci potential and complete amortized bounds

For Fibonacci decrease-key with k≥1 cuts, root count rises by k. Beyond the first cut, each cut ancestor was marked; at most the final stopping ancestor acquires a new mark. Thus $\Delta m \le 1 - (k-1) = 2 - k$ and $\Delta(t + 2m) \le 4 - k$. If actual work is at most ak+b, choose scaled potential $A(t + 2m),\ A \ge a$. Amortized cost is at most $ak + b + A(4 - k) \le b + 4A$, independent of k. With no cut, key/minimum updates and comparisons are constant work.

For delete-min, let the initial root count be t, removed degree d, and maximum degree D. Actual work is at most a(t+d+D)+b. Promotion, linking, and clearing root marks do not increase the marked count. Consolidation leaves at most D+1 roots, so $\Delta\Phi \le A(D + 1 - t)$. Choosing A≥a yields amortized cost at most $a(d + D) + A(D + 1) + b = O(D + 1) = O(1 + \log(n + 1))$, since d≤D. This is the algebra paying for root scans; one actual operation may still cost Θ(n).

- Fibonacci heaps yield Dijkstra's abstract O(E+V log V) bound with valid handles and decrease-key, under Dijkstra's nonnegative-weight condition.

Erase without changing a key and extraction of an arbitrary root

```
erase(h):
    z=resolve_live_owned_handle(h)   // reject stale/foreign handle first
    if z.parent!=null:
        p=z.parent; cut(z,p); cascade(p)
    return extract_root(z)
extract_root(z):
    require z is a live root owned by this heap
    result=copy(z.item)             // fixed-size nonthrowing model
    while z.child!=null:
        c=z.child
        z.child=ring_remove(z.child,c); z.degree-=1
        c.parent=null; c.mark=false; roots=ring_prepend(roots,c)
    roots=ring_remove(roots,z); min=null
    invalidate_handle(z); release(z); n-=1
    if n==0: roots=null; return result
    consolidate()
    return result
```


Erase without changing a key and extraction of an arbitrary root (continued)

Each node stores key, item, parent, child, degree, mark, and circular-list left/right pointers. Roots and child designate root and child rings; null denotes an empty ring. A handle identifies a particular live node, not an arbitrary node with an equal key. Only the erased handle becomes invalid; other items and node identities are never swapped. Resolve an opaque external handle through its owning container's live-node registry before accessing a node. Reading an already released raw pointer to inspect an alive flag is invalid. Pointer-work bounds assume a valid handle; additional lookup/validation costs are separate.

For nonroot z, cut it into the root ring and notify its old parent p through cascade. An unmarked nonroot p becomes marked; a marked p is cut and the process continues upward; a root stops the cascade. This cut is required for deletion even without a key decrease. Omitting cascade would allow a nonroot to lose two children and invalidate the degree proof. A target already at a root enters extract_root directly.

Erase without changing a key and extraction of an arbitrary root (continued)

Extract_root does not require z=min. Remove each child c from z's ring before decrementing degree, clearing parent/mark, and adding its entire subtree to roots. Remove z, clear min to avoid a dangling pointer, invalidate its handle, release it, and decrement n exactly once. If nodes remain, consolidate all roots and recompute the actual minimum. No key is changed. Reject empty delete-min before access; an empty heap has no valid erase handle. Removing the last node gives n=0 and roots=min=null. Reusing that handle must fail. After destructive meld, accepted handles follow the container's ownership contract; the emptied source must not erase destination-owned nodes.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study


Legal erase setup and three cuts

```
for i=0..32: h[i]=insert(i)     // v_i is permanent identity, initially key i
delete_min()                    // removes v_0; consolidates to root v_1
decrease_key(h[18],-10)
decrease_key(h[26],-11)
erase(h[29])                    // key stays 29 until release
```

Prepend to root and child rings and traverse snapshots through right links. After inserting 0..32 and removing v0, root v1 has degree 5. Its child v17 originally has children v25,v21,v19,v18; v25 has v29,v27,v26; v29 has v31,v30; v31 has v32. Lowering v18 to −10 cuts it and marks v17. Lowering v26 to −11 cuts it and marks v25. Before erase, roots are v26(key−11,d0),v18(key−10,d0),v1(key1,d5), with marked nonroots v17,v25. Target v29 is not the minimum and still has two child subtrees.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study


Legal erase setup and three cuts (continued)



Other roots: v18(key −10), v26(key −11). Gold = mark true.
Triangles retain child forests; counts exclude the parent. Both states have n=32.

The four displayed nodes, unchanged child forests of sizes 15,6,2,3, and two other roots account for all 32 nodes. Cutting changes parent links, not node identities. Each already marked ancestor becomes an unmarked root; root v1 is not marked when the cascade stops.


Promote target children and remove exactly one node



Unchanged roots: v1, v17, v25, v26, v18 (28 nodes); only h29 expires.

Moving v31 preserves its child v32, so it remains a two-node tree. Together with singleton v30, the promoted trees contain three nodes. Only v29 is removed; v26 with key −11 remains the minimum, and all surviving handles still identify their original nodes.

Three degree-table carry links



A[0]=v18, A[1]=v26, A[3]=v17, A[4]=v1; min=v26 (key −11)
Subtree sizes: 1 + 2 + 12 + 16 = 31; t=4, m=0, Φ=4.

The first link makes v25 a five-node tree of degree 2; the second attaches it to v17, producing degree 3 and twelve nodes. Linking v30 under v26 produces degree 1 and two nodes. Unchanged roots v18 and v1 have one and sixteen nodes, respectively.

Erase state table and identity conservation

Completed step	Roots t	Marked nonroots m	$\Phi = t + 2m$	Required change
Before erase	3	2	7	v29.parent=v25; v25.parent=v17
Cut v29	4	2	8	v25.degree falls 2→1
Cascading cut v25	5	1	7	Clear v25.mark; v17.degree falls 3→2
Cascading cut v17	6	0	6	Clear v17.mark; v1.degree falls 5→4
Promote v31,v30	8	0	8	Both parents become null; v29.degree=0
Remove/release v29	7	0	7	n falls 32→31; h29 is invalid
After three links	4	0	4	Distinct degrees; recompute min=v26

Erase state table and identity conservation (continued)

The root snapshot is v30(d0),v31(d1),v17(d2),v25(d1),v26(d0),v18(d0),v1(d4). Equal-degree v25 wins v31 and reaches degree 2; v17 then wins v25 and reaches degree 3. Root v26(key−11) wins v30 and reaches degree 1. Final table entries are 0→v18,1→v26,3→v17,4→v1. There are 31 nodes and the minimum remains key−11. Promoted v31,v30 later become children again, without changing node identities. Promotion describes an intermediate root state, not a promise to remain a root after consolidation.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Correctness and amortized derivation for arbitrary erase

```
// Potential Phi_A=A*(t+2*m), with a constant A large enough for pointer work.
// Cut/cascade phase: k cuts, actual <= a*k+b, Delta(t+2m)<=4-k.
// Root extraction: degree d, initial t' roots, final at most D(n)+1 roots.
// Actual <= a*(t'+d+D(n)+1)+b; marks never increase in this phase.
```

Correctness has three parts. Cutting z removes one parent edge and preserves every subtree's internal heap order. Cascading enforces the first-loss mark and second-loss cut rule needed by the degree proof. Promoting z's children preserves all their elements; only z.item is removed and only z's handle becomes invalid. Finally, linking equal-degree roots under the smaller root preserves order and node sets. Taking the least final root yields the global minimum, whether or not z was previously minimal.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Correctness and amortized derivation for arbitrary erase (continued)

If cutting uses k≥1 cuts, roots increase by k. Apart from the initial target, each further cut ancestor was marked, and at most one final ancestor acquires a new mark. Thus $\Delta m \leq 2 - k$ and $\Delta(t + 2m) \leq 4 - k$. For actual cost≤ak+b, choose scaled potential $\Phi_A = A(t + 2m)$, A≥a. Amortized cut cost is at most $ak + b + A(4 - k) \leq b + 4A = O(1)$. A target already at a root needs only constant checks in this phase.

After cutting, let there be t′ roots and let z have degree d. Maximum degree during consolidation has bound $D(n) = O(\log(n + 1))$. Extraction costs at most $a(t' + d + D(n) + 1) + b$. Promotion and linking never increase marks, and at most D(n)+1 roots survive, so $\Delta\Phi_A \leq A(D(n) + 1 - t')$. With A≥a and d≤D(n), amortized extraction is at most $a(d + D(n) + 1) + A(D(n) + 1) + b = O(1 + \log(n + 1))$. The two potential differences telescope using the same potential, proving the complete erase bound.

Correctness and amortized derivation for arbitrary erase (continued)

One operation can still cost Θ(n), due to long cascading cuts or a large root scan/snapshot. Start-from-empty sequence analysis uses the same nonnegative Φ_A; arbitrary startup adds its initial value. Key/result operations and node release follow the fixed-cost model, and handle lookup is separate.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Pairing heap link

- A standard pairing heap is a multi-child min-heap. Meld compares two roots and makes the larger a new child of the smaller, changing a constant number of pointers.
- Insert melds a singleton. Decrease-key usually cuts the lowered node with its subtree and melds it with the root.
- Constant-time removal from the sibling list requires sibling, parent, predecessor, or equivalent backlink information. A next-only list without a way to locate its predecessor may require scanning. Require a live handle owned by this heap before access.
- A small immediate pointer count does not justify assigning every operation O(1) amortized cost across a sequence.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Pairing sibling backlinks and detachment

```
// Pairing roots passed to link have parent=prev=next=null.
detach(x):
    p=x.parent
    if x.prev==null: p.first_child=x.next
    else: x.prev.next=x.next
    if x.next!=null: x.next.prev=x.prev
    x.parent=x.prev=x.next=null
link(a,b):
    if a==null: return b
    if b==null: return a
    if a.key>b.key: swap(a,b)
    b.parent=a; b.prev=null; b.next=a.first_child
    if b.next!=null: b.next.prev=b
    a.first_child=b; return a
```

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Pairing sibling backlinks and detachment (continued)

Each node stores parent, previous/next siblings, and first_child. Detach applies only to a nonroot. The first child's prev is null; other prev links point to the previous sibling. Removing the first child updates its parent's first_child, while removing another updates the previous sibling's next. Both cases repair the next sibling's prev. The entire subtree below x remains intact. Lowering the root needs no detach. Before delete-min pairs children, save each next pointer and clear parent/prev/next so every child becomes a detached root.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study


Complete two-pass pairing and deferred costs

```
link(a,b):
    if a==null: return b
    if b==null: return a
    if a.key>b.key: swap(a,b)
    prepend b to a.children; return a
delete_min():
    require root!=null
    children=detach_all_children(root); release(root)
    paired=[]
    for adjacent (a,b) left-to-right: paired.append(link(a,b))
    if odd last child remains: paired.append(last)
    root=null
    for heap in reverse(paired): root=link(heap,root)
decrease_key(x,new):
    require new<=x.key; x.key=new
    if x!=root: detach x in O(1) using backlinks; root=link(root,x)
```

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Complete two-pass pairing and deferred costs (continued)

Pairing first pass: adjacent pairs; unpaired 7 remains



Roots 8,3,9,5,7 pair (8,3) into 3 with child 8, (9,5) into 5 with child 9, leaving 7. Right-to-left accumulation links 7 with empty, then 5 with 7 to obtain children 7,9, then 3 with 5 to obtain children 5,8. Subtree 5 retains 7,9. No paired subtree is dismantled. Immediate delete-min link work is proportional to the old root degree and can be Θ(n).

Actual subtree shapes during the pairing second pass


```
paired=[root3(child8),root5(child9),root7]
acc=link(root7,null); acc=link(root5,acc)
acc=link(root3,acc)       // 4 nonempty links across both passes
```

Second pass folds right to left, preserving entire subtrees

link(5,7) → 5




link(3,5) → 3



LCRS representation and a nonnegative potential

View the ordered multiway tree as a left-child/right-sibling (LCRS) binary tree. Let s(v) count all nodes reachable from v through these two binary links, $\rho(v) = \log_2 s(v)$, and $\Phi = \sum_v \rho(v)$. This includes later sibling subtrees: **s(v) is not v's original multiway subtree size**. Every s(v)≥1, so Φ≥0; an empty heap has Φ=0. These are analysis variables, not metadata recomputed during operations.



Triangle +j: j collapsed descendants; the displayed root is excluded

LCRS representation and a nonnegative potential (continued)

Root 0 has child subtrees of sizes 3,2,4. In the binary representation s(A)=9,s(B)=6,s(C)=4, and s(root)=10. Removing the root leaves the ordered forest of children: only the root's $\log_2 10$ disappears; every other s is unchanged.


For independent live heaps, total potential is the sum of their separate potentials; roots are not sibling-linked. During delete-min, define a temporary forest with virtual right-sibling adjacency in component order. If an array implementation clears actual next pointers while detaching roots, interpret the virtual chain from this component order. Do not assign unrelated heap potentials to each cleared-pointer intermediate state. Each macro-link includes constant detach/reconnect work; scanning, temporary storage, and releasing the old root cost O(k+1). Both endpoint potentials match the actual heaps.

An adjacent link changes only two root ranks

Consider adjacent components A,B in one forest, with original multiway sizes a,b≥1 and a suffix containing R≥0 nodes. Before linking, s(A)=a+b+R and s(B)=b+R. Link makes the losing root the winner's **first child**. Resolve equal keys consistently.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

An adjacent link changes only two root ranks (continued)



After linking, the winner has s=a+b+R and the loser has s=a+b−1. All other sizes are unchanged: a root in the prefix reaches the same suffix nodes, and old child chains retain their contents. Either winner therefore gives

$$\Delta\Phi_{\text{link}} = \log_2(a+b-1) - \log_2(b+R)$$

First-pass inequality with a positive suffix

Write A=a+b and T=A+R. If R>0, the exact adjacent-link formula gives

$$1 + \Delta\Phi_{\text{link}} = \log_2 \frac{2(A-1)}{b+R} \le \log_2 \frac{2A}{R} \le 2\log_2 \frac{T}{R}$$

The first inequality uses A−1≤A and b+R≥R. The second is equivalent to $2AR \le (A+R)^2$, whose right side minus left side is $A^2 + R^2 \ge 0$. The argument depends only on sizes, not which root key wins.

Number the pairs processed left-to-right. Let $T_j = a_j + b_j + R_j$ be the size still present from pair j to the right end. The untouched suffix of one pair is precisely the total starting at the next pair, so $R_j = T_{j+1}$. Summing the logarithms cancels intermediate terms. A final pair with R=0 cannot use this division by R and is handled separately below.

Telescoping the first pass for odd degree

Before deletion there are n nodes; after removing the root N=n−1 remain. Suppose its degree is k=2q+1. The first pass makes q links and leaves the rightmost tree of size r≥1 unpaired. This tree lies in every processed pair's suffix, so every $R_j > 0$.

$$q + \Delta\Phi_1 \le 2\sum_{j=1}^{q} \log_2 \frac{T_j}{R_j} = 2\log_2 \frac{N}{r} \le 2\log_2 N$$

Consequently $\Delta\Phi_1 \le -q + 2\log_2 N$. The negative −q term is needed to pay for a linear number of links. A bound saying only that potential increases by O(log n) would omit this payment.

In the existing five-singleton example 8,3,9,5,7, N=5,q=2,r=1. The two exact link changes are $\log_2(1/4)$ and $\log_2(1/2)$, totaling −3. For k=1, q=0 and r=N: the empty sum is 0, and no link occurs. No log0 is needed.

The final zero-suffix pair for even degree

If k=2q≥2, the last pair has $R_q = 0$. Write $A_q = a_q + b_q \geq 2$. The first q−1 pairs telescope to

$$(q-1) + \Delta\Phi_{\text{previous}} \leq 2\log_2(N/A_q)$$

Use the exact formula for the last pair: $\Delta\Phi_{\text{last}} = \log_2(A_q - 1) - \log_2 b_q \leq \log_2 A_q$. Therefore

$$\Delta\Phi_1 \leq -q + 1 + 2\log_2(N/A_q) + \log_2 A_q \leq -q + 1 + 2\log_2 N$$

When q=1 the earlier sum is empty and $N = A_q$, so its upper bound is 0. A uniform odd/even bound is $\Delta\Phi_1 \leq -q + 2\log_2 N + 1$, where q=⌊k/2⌋. Degree zero is a separate singleton case.

Second pass and the complete delete-min bound

The first pass leaves m=⌈k/2⌉ trees. Accumulate right-to-left. If the next left tree has size a and the accumulated right tree has size b, then R=0, and

$$\Delta\Phi_{\text{link}} = \log_2(a + b - 1) - \log_2 b \leq \log_2 \frac{a+b}{b}$$

The next accumulator size is a+b, so $\Delta\Phi_2 \leq \log_2(N/b_0) \leq \log_2 N$, where $b_0 \geq 1$ is the rightmost component size. If m≤1 there are no links. The five-child example has second-pass ratios 2 and 4/3; including the first pass and removal of the original root gives total potential ratio (1/6)(1/4)(1/2)(2)(4/3)=1/18.

For k≥2, combine root removal and both passes: $\Delta\Phi \leq -\log_2 n - q + 3\log_2 N + 1 \leq -q + 3\log_2 n + 1$. Actual work is at most ck+d for fixed constants, and k≤2q+1. Choose the same scaled potential $\Psi = C\Phi$ with $C \geq 2c$. $\text{actual} + \Delta\Psi \leq (2c - C)q + 3C\log_2 n + c + d + C = O(1 + \log n)$. This pays for scanning and all k−1 links, not just first-pass links.

Second pass and the complete delete-min bound (continued)

For k=0, n=1 and deletion leaves an empty heap: ΔΦ=0 and actual cost O(1). For k=1, the sole child becomes root, $\Delta\Phi = -\log_2 n$, and actual cost is O(1). Reject empty delete-min. The array procedure stores O(k) roots, possibly O(n) space; the proof does not imply logarithmic temporary space.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Meld, insert, and decrease under the same potential

Meld two independent nonempty heaps of sizes a,b, with n=a+b. Initially their root ranks are $\log_2 a$ and $\log_2 b$. Afterward the winner has s=n and the loser s=n−1; other sizes do not change. Thus $\Delta\Phi_{\text{meld}} = \log_2 \frac{n(n-1)}{ab} \le \log_2 n$, since $ab \ge a + b - 1 = n - 1$. An empty operand gives ΔΦ=0. Inserting into a nonempty heap melds a singleton and has exactly $\Delta\Phi = \log_2 n$; inserting the first node has ΔΦ=0. Although both operations take O(1) immediate work, **this analysis charges O(1+log(n+1)) amortized for each**.

Decreasing the root's key does not change shape or potential. For a nonroot x of original multiway subtree size a, first cut it into a separate heap. The binary size of x loses its right-sibling suffix. Binary ancestors that previously reached the removed subtree only lose reachable nodes; other sizes are unchanged. Thus cutting has $\Delta\Phi \le 0$. Melding it back adds at most $\log_2 n$. A valid handle and the stated parent/prev/next backlinks make the actual cut O(1). The same Ψ therefore charges decrease-key O(1+log(n+1)); it does not establish constant amortized decrease-key.

Sequence cost and the scope of this analysis

Operation	Immediate actual cost	Amortized charge under this same Ψ
find-min	O(1)	O(1)
insert	O(1)	O(1+log(n+1))
meld	O(1)	O(1+log(n+1)), n combined size
decrease-key	O(1), valid handle/backlinks required	O(1+log(n+1))
delete-min	O(k+1), worst-case O(n)	O(1+log(n+1))

Starting with empty heaps, $\Psi_0=0$ and the final $\Psi \geq 0$. Hence $\sum c_i = \sum \hat{c}_i + \Psi_0 - \Psi_{\text{final}} \leq \sum \hat{c}_i$. If N is the maximum live-node count and I,M,D,K,F count insertions, melds, deletions, decreases, and find-min operations, total cost is $O((I + M + D + K)(1 + \log_2(N + 1)) + F)$, plus O(1) for each empty-heap creation. A nonempty initial state contributes Ψ_0.

Sequence cost and the scope of this analysis (continued)

This proves one compatible collection of bounds for the standard two-pass variant. Substituting a different analysis's constant amortized insert/meld into this proof does not establish $O(I + M + (D + K) \log N + F)$. Constant immediate cut work also does not imply constant amortized decrease-key. Changing pass directions or the prepend-child rule requires checking the inequalities again.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

Complexity comparison and selection

Structure	find-min	meld	delete-min	decrease-key
Leftist	O(1) worst	O(log n) worst	O(log n) worst	No fast bound supplied here
Eager binomial	O(1) with minimum pointer	O(log n) worst	O(log n) worst	O(log n) worst
Fibonacci	O(1) worst	O(1) worst	O(log n) amortized	O(1) amortized
Two-pass pairing	O(1) worst	O(1) immediate pointer work	O(log n) amortized	O(log n) amortized under this potential

Every decrease-key bound assumes a valid handle. Amortized bounds for different operations must belong to one compatible analysis. Independently selecting optimistic bounds can produce an invalid combination.

Complexity comparison and selection (continued)

Keep constant terms for empty and singleton cases. Melding two empty heaps still tests pointers and takes O(1); the precise leftist bound is O(1+log(n1+1)+log(n2+1)). Delete-min requires nonempty input. Reject an empty request instead of invoking log 0.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

References and further reading

- Fibonacci heaps: Fredman–Tarjan paper.
- Pairing heaps: original paper and authors' notes, and Pettie's advanced analysis.
- Binomial heaps: Stanford CS166 course.
- Prepend-child linking, pass directions, and backlinks for the standard two-pass variant: Sinnamon–Tarjan, § 2. The LCRS potential and compatible charges used in this chapter are derived in full above.

Lin Cing
https://github.com/xinhi6716/computer-science-self-study

References and attribution

Ellis Horowitz, Sartaj Sahni, Dinesh Mehta. Fundamentals of Data Structures in C++, 2nd Edition.

Original educational synthesis by Lin Cing. Original material is licensed under CC BY 4.0. The referenced textbook is not distributed with these notes.

https://github.com/xinhi6716/computer-science-self-study

Lin Cing
https://github.com/xinhi6716/computer-science-self-study