Chapter 6. CPU scheduling. Exercises

Original problems. State assumptions, units, and intermediate reasoning. Answers are in the separate solutions PDF.

OS06-E01. Nonpreemptive scheduling

Three jobs arrive at t=0 with bursts P1=8, P2=4, and P3=2. Ignore switching costs.

1. Compute completion, waiting, and turnaround for FCFS in order P1, P2, P3 and for nonpreemptive SJF.
2. Compare mean waiting and turnaround.
3. What information assumption supports the SJF conclusion?

Check your approach. Align every metric with its process identity and time unit.

OS06-E02. Round Robin

P1, P2, P3 arrive at zero with bursts 5,2,3. Use q=2 and ignore switching costs.

1. Give the timeline.
2. Compute each completion, waiting, and response time.
3. What changes when q=1?

Check your approach. Nonoverlapping intervals must account for all ten execution units, plus any explicitly included overhead.

OS06-E03. Priorities and starvation

High-priority interactive tasks keep arriving while a lower-priority batch job has no guaranteed waiting limit.

1. When can starvation be established?
2. How can aging help?
3. What else is needed if a priority-based system promises bounded waiting?

Check your approach. Mean performance and a fairness guarantee are different claims.

OS06-E04 HRTICK CFS event reasoning

One-CPU Linux 3.2 CFS has latency 6 ms, minimum granularity 0.75 ms, wakeup granularity 1 ms, GENTLE_FAIR_SLEEPERS=true, CONFIG_SCHED_HRTICK=y, and free switches. P1/P2 arrive at 0, P3 sleeps until 9, bursts 8/4/2. All nice 0, weight 1024, initial vruntime 0; P1 enters before P2 on equal keys.

Chapter 6. CPU scheduling. Exercises (continued)

1. Find period, ideal runtime, and vruntime increment per real ms with P1/P2 runnable.
2. Give current, other ready, min_vruntime, and switch cause at 0,3,6,9,11,12,14.
3. Derive every Gantt segment from events; do not invent a switch at 8.
4. Find P3's sleep placement and when it can preempt within [6,9).

OS06-E05 Strict periodic-tick comparison

Use E04's state, disable HRTICK, and run ordinary ticks at integer milliseconds.

1. Compare delta_exec at 3 and 4 with check_preempt_tick's first condition.
2. Derive Gantt and completions.
3. Why does ideal_runtime=3 not guarantee switches exactly at 3,6,9?
4. Restore HRTICK and wake P3 at 8.5. Which old interval first changes?

OS06-E06 CPU fairness and synchronization

A/B share a CFS runqueue, weights 1024/335, period 6 ms. B writes buffer then ordinary non-atomic ready=1. A checks ready by ordinary load when scheduled.

1. Compute slices and CPU shares.
2. Does higher weight replace exclusion? Give a two-writer counterexample.
3. Which publication contract allows A to safely observe buffer after ready=1?
4. Which guarantees does a mutex around counter++ provide? Is its publication contract automatic from its name?
5. Distinguish barriers, atomic operations, mutexes, and semaphores in exclusion and visibility.

Lin Cing https://github.com/xinhi6716/computer-science-self-study

References and attribution

Abraham Silberschatz, Peter B. Galvin, Greg Gagne. Operating System Concepts, 9th Edition.

Original educational synthesis by Lin Cing. Original material is licensed under CC BY 4.0. The referenced textbook is not distributed with these notes.

https://github.com/xinhi6716/computer-science-self-study