Model Numbering Guide – Crystal Units

Available options

Type	Package (mm)	Load Capacitance (pF)	Freq. Tol. @25°C (ppm)	Freq. Stability (ppm)	Temp. Range(°C)	Special Requirement	Oscillator Mode	Appearance	Lead Free	Dash	Freq. (MHz)
X: X'tal (MHz series)	4: 1.2x1.0 3: 1.6x1.2 Z: 2.0x1.6 Y: 2.5x2.0 X: 3.2x2.5 V: 5.0x3.2 (4Pads) R: 6.0x3.5 I : 11.1x4.68 (U4) J:13.0x4.85 (U4B)	L : 6 O: 7 A : 8 B: 9 C: 10 D : 12 E : 15 F : 16 G: 18 H: 20 P : 22 Q: 25 T : 30 J :32 K :50 N:No Standard S :Series	A:±5 B:±10 P:±15 C:±20 D:±25 E:±30 F:±40 G:±50 H:±100 I:±150	A: ±5 B: ±10 P: ±15 C: ±20 D: ±25 E: ±30 F: ±40 G: ±50 H: ±100 I: ±150 Z: ±150 above	A:+10~+40 B:+0~+55 E:+0~+85 I :-10~+60 C:-20~+70 D:-30~+85 L:-40~+85 M:-40~+95 J :-40~+105 H:-40~+125 G:-40~+150 F:-55~+125	A:For Automotive B:Spurious D: DLD N: No Special P: Pullability S: Several	A: AT Fundamental T:AT 3rd Overtone	O:Laser Seal N :Normal Y: Channel ID	F: RoHs Compliant Y:Channel ID	–	XX.XXXXXX
X: X'tal (32.768 kHz series)	A: 3.0x8.0 (Dip) B: 1.0x4.0 (Dip) /2.0x6.0 (Dip) D: 1.2x1.0 (4Pads) 1.6x1.0 (2Pads) 2.0x1.2 (2Pads) 3.2x1.5 (2Pads) N: 6.9x1.4 (4Pads) /8.0x3.8 (4Pads)	L: 6 O: 7 B: 9 M: 12.5	C: ±20	Z: ±150 above	C:-20~+70 L:-40~+85 J:-40~+105 H:-40~+125	N: No Special	D: Tuning Fork	N: Normal (XA3.0x8.0size XB 2.0x6.0 size) J: XB1.0x4.0size Q: XD 1.2x1.0 size P:XD1.6x1.0size M:XD2.0x1.2size D:XD3.2x1.5size H:XN6.9x1.4size E:XN8.0x3.8size Y: Channel ID	D: RoHS Compliant B: Non-RoHS Compliant Y:Channel ID	–	0.032768

X	Y	C	D	D	L	N	A	N	F	–	40.000000

*Not all combinations of options are available.

Example: XYCDDLNANF-40.000000

Type	X'tal
Package	2.5 x 2.0 mm
Load Capacitance	10 pF
Freq. Tol.	±25ppm
Freq. Stability	±25ppm
Temp Range	-40~+85 °C
Special Requirement	No Special
Oscillator Mode	AT Fundamental
Appearance	Normal Appearance
Lead Free	RoHs Compliant
Frequency	40.000000 MHz