Model Numbering Guide – Thermistor Crystal Units

Available options

Type	Package (mm)	Load Capacitance (pF)	Freq. Tol. @25°C (ppm)	Freq. Stability (ppm)	Temp. Range(°C)	Special Requirement	Oscillator Mode	Appearance	Lead Free	Dash	Freq. (MHz)
B: Ther-mistor X'tal (MHz series)	4: 1.2x1.0 3: 1.6x1.2 Z: 2.0x1.6 X: 3.2x2.5	L: 6 O: 7 A: 8 B: 9 C: 10 D: 12 E: 15 F: 16 G: 18 H: 20 N: No Standard S : Series	A:±5 B:±10 P:±15 C:±20 D:±25 E:±30	A: ±5 B: ±10 P: ±15 C: ±20 D: ±25 E: ±30 L: ±12	I :-10~+60 C:-20~+70 D:-30~+85 L:-40~+85 M:-40~+95 J :-40~+105 H:-40~+125	A:For Automotive B:Spurious D: DLD N: No Special P: Pullability S: Several	A: AT Fundamental	N :Normal	F: RoHs Compliant Y:Channel ID	–	XX.XXXXXX

B 3 O B L D N A N F – 76.800000

*Not all combinations of options are available.

Example: B3OBLDNANF-76.800000

Type	Thermistor X'tal
Package	1.6 x 1.2 mm
Load Capacitance	7 pF
Freq. Tol.	±10ppm
Freq. Stability	±12ppm
Temp Range	-30~+85 °C
Special Requirement	No Special
Oscillator Mode	AT Fundamental
Appearance	Normal Appearance
Lead Free	RoHs Compliant
Frequency	76.800000 MHz