TAITIEN
Our Performance, Your Reputation

Model Numbering Guide – Crystal Oscillator

Available options

Type	package (mm)	Supply Voltage(V)	Tri-State Function	Freq. Stability (ppm)	Temp. Range(°C)	Output Logic and Symmetry	Oscillator Mode	Appearance	Lead Free	Dash	Freq. (MHz)
O: Oscillator	3: 1.6 x 1.2 Z:2.0 x 1.6 Y:2.5 x 2.0 X:3.2 x 2.5 V:5.0 x 3.2 C:7.0 x 5.0	E: 2.8/3.0/3.3 J :2.5 K:1.8 P:1.5 L:1.2/1.25 M:0.9 Q:1.0 X:Un programmed	B:High Precision I: Low Power or Low Current T:Fixed-Freq with Tri-State M:Multiplier Freq with Tri-State(only for V/C package) U:Ultra Low Noise design D:Ultra Low Current	A: ±5 B: ±10 P: ±15 C: ±20 D: ±25 E: ±30 F: ±40 G: ±50 H: ±100 K: ±3 L: ±12	E: 0~+85 I: -10~+60 C: -20~+70 D: -30~+85 L: -40~+85 J: -40~+105 H: -40~+125 F: -55~+125	J: CMOS 15pF / 50±5% K: CMOS 15pF / 50±10%	A: AT Fundamental T: AT 3rd Overtone Not Selectable by Customer	N: Normal Y: Channel ID K: Plastic molding	F: RoHS Compliant O: No Marking Y:Channel ID	–	XX.XXXXXX
P: Programmable Oscillator	4:1.2 x 1.0 Z:2.05 x 1.65 Y:2.5 x 2.0 X:3.2 x 2.5 V: 5.0 x 3.2 C:7.0 x 5.0	E:2.8/3.0/3.3 J:2.5 K:1.8 X:Un-programmed	P: Un-programmed U: Low Noise	C: ±20 D: ±25 G: ±50 H: ±100 Z: over 150ppm	I:-10~+60 C:-20~+70 D:-30~+85 L:-40~+85 J: -40~+105 H: -40~+125 E:0~+85	J: CMOS 15pF / 50±5%					
S:Spread Spectrum Oscillator	Y: 2.5 x2.0 X:3.2 x 2.5	E:3.3 J:2.5 K:1.8	A:Down, -2.0% B:Down, -1.5% C:Down, -1.0% D:Down, -0.8% E:Center, ±1.0% F:Center, ±0.75% G:Center, ±0.5% H:Center, ±0.4%	D: ±25 G: ±50 H: ±100							
O: Oscillator (Differential Output)	A :3.2 x 2.5 W:5.0x3.2 T:7.0x5.0 B:2.5x2.0 O:2.0x1.6		Normal: R: Pin1 Tri-state (std) T: Pin2 Tri-state (case by case) Ultra Low Jitter: W: Pin1 Tri-state (std) U: Pin2 Tri-state (case by case)			L: LVPECL / 50±5% V: LVDS / 50±5% H: HCSL / 50±5%					
O: Oscillator (Fast Delivery series)	B:2.5x2.0 N:2.5x2.0 M:3.2x2.5 A :3.2 x 2.5 J:5.0x3.2 W:5.0x3.2 D:7.0x5.0 T:7.0x5.0	E:3.3 J:2.5 K:1.8 X:Un-programmed	M: Multiplier Freq with pin 2 Tri-State N: Multiplier Freq. with PIN 1 Tri-State P: With Tri-State Frequency Selection Function C: Multiplier Freq with pin 2 Tri-State (Low Enable)	D: ±25 G: ±50 H: ±100 Z: over 150ppm E: ±30		H: HCSL / 50±5% J: CMOS 15pF / 50±5% L: LVPECL / 50±5% M: CML V: LVDS / 50±5%					

O	Y	E	T	C	C	J	A	N	F	–	13.000000

*Not all combinations of options are available.

Example: OYETCCJANF-13.000000

Type	Oscillator
Package	2.5 x 2.0 mm
Supply Voltage(V)	3.3 V
Tri-State .	Fixed-Freq.
Freq. Stability	±20ppm
Temp Range	-20~+70 °C
Output	CMOS 15pF / Symmetry 50±5%
Oscillator Mode	AT Fundamental
Appearance	Normal Appearance
Lead Free	RoHs Compliant
Frequency	13.000000 MHz

Specifications subject to change without notice.