
NK-H Type
14.7 x 9.6 mm Hermetic Very Low Noise Oven Controlled Crystal Oscillator





RoHS Compliant

FEATURE
- Dimension 14.7 x 9.6 x 8.2 mm Typical
- 6-Pin Hermetic SMD Package
- Frequency Range, 10 MHz to 40MHz
- ±10 ppb Stability over -40 to 85°C
- Very Low Phase Noise


TYPICAL APPLICATION
- SDH/SONET , Telecommunication Base Station
- Test and Measurement Equipment
- Synthesizer , Digital switch , Reference Timing Circuit
- Packet Timing Protocol (e.g. 1588)

DIMENSION





SOLDER PAD LAYOUT



PIN CONNECTIONS	
PIN	FUNCTION
1 (See NOTE 1)	VCO INPUT or NOT CONNECTED
2 (See NOTE 1)	R.F.ENABLE or NOT CONNECTED
3	0 VOLTS AND CASE
4	R.F. OUTPUT
5	NOT CONNECTED
6	+VDC

Notes:
1.If the specification does not specify parameters for PIN 1 ,PIN 2 then that respective PIN is not internally CONNECTED.

INCH / mm (REFERENCE ONLY)

ELECTRICAL SPECIFICATION

Parameter		Min.	Typ.	Max.	Unit	Test Condition & Notes
Output	Frequency	–	20	–	MHz	Available frequency range is from 10MHz to 40MHz. Standard Frequencies :10, 19.2 and 20MHz.
	Wave Form	–	Rectangular	–	–	Please contact us for detail information
	Level	–	–	–	–	
	"1" Level	2.4	–	–	V	
	"0" Level	–	–	0.4		
	Load	–	15	–	pF	
	Duty Cycle	45	50	55	%	@+1.65 V
	Spurious	–	–	-60	dBc	
Frequency Stability	Ambient	-10	–	+10	ppb	-40°C to +85°C, referenced to +25°C Refer to Table : Freq.Stability vs Temp. Range.
	Aging	–	–	–		
	Daily	-1.0	–	+1.0	ppb	after 30 days
	Yearly	-0.2	–	+0.2	ppm	
	10 years	-1.0	–	+1.0		
	Voltage	-5	–	+5	ppb	±5% Change
	Warm-up	-0.1	–	+0.1	ppm	In 5 minutes @ +25°C, referenced to 1 hour
	Phase Noise @ 20 MHz (No Pulling)	–	-126	-120	dBc/Hz	@ 10 Hz
		–	-149	-145		@ 100 Hz
		–	-160	-157		@ 1 kHz
		–	-164	-162		@ 10 kHz
Electrical Frequency Adjustment		–	–	–		
	Range	–	–	-0.5	ppm	VCO@ 0V
		0.5	–	–		VCO@ 3.3V
	Control	0	1.65	3.3	V	
	Slope	–	Positive	–		
	Input impedance	100	–	–	Kohm	
Input Power	Voltage	3.135	3.3	3.465	V	5.0V input voltage is available. Please contact us for detail information.
	Current	–	–	600	mA	@ turn on
	Steady state	–	0.5	0.6	W	@ +25°C

FREQ. STABILITY vs. TEMP. RANGE

Temp. (C) \ ppb	±5	±10	±20	±30
-20 ~ +70	○	○	○	○
-40 ~ +85	△	○	○	○

* ○ : Available △:Conditional X: Not available

Note: not all combination of options are available. Other specifications may be available upon request.

Specifications subject to change without notice.
www.taitien.com
sales@taitien.com.tw