

Team Reference Document

Heltion

2024 年 10 月 3 日

目录

1	Template	1
2	Data	3
3	DP	31
4	Geometry	32
5	Graph	41
6	Math	57
7	String	81
8	Basic	90

1 Template

1.1 .clang-format

```
1 BasedOnStyle: Google
2 IndentWidth: 4
3 ColumnLimit: 160
```

1.2 debug.cpp

```
1 #include <bits/stdc++.h>
2
3 using namespace std;
4
5 template <class T, size_t size = tuple_size<T>::value>
6 string to_debug(T, string s = "") requires(not ranges::range<T>);
7
8 template<class T>
9 concept check = requires(T x, ostream &os) {
10     os << x;
11 };
12
13 template<check T>
```

```
14 string to_debug(T x) {
15     return static_cast<ostringstream>(ostringstream() << x).str();
16 }
17
18 string to_debug(ranges::range auto x, string s = "") requires(not is_same_v<
19     decltype(x), string>) {
20     for (auto xi : x) {
21         s += ", " + to_debug(xi);
22     }
23     return "[" + s.substr(s.empty() ? 0 : 2) + "]";
24 }
25
26 template <class T, size_t size>
27 string to_debug(T x, string s) requires(not ranges::range<T>) {
28     [&<size_t... I>(index_sequence<I...>) {
29         ((s += ", " + to_debug(get<I>(x))), ...);
30     }(make_index_sequence<size>());
31     return "{" + s.substr(s.empty() ? 0 : 2) + "}";
32 }
33
34 #define debug(...) [](auto... $){ ((cout << to_debug($) << " "), ...); cout
35     << endl; }("[" , __VA_ARGS__ , "]:", __VA_ARGS__)
```

1.3 gen.py

```
1 from random import *
2 n=10000
3 s='qwertyuiopasdfghjklzxcvbnm'
4 for i in range(n):
5     print(choice(s),end='')
6 print()
7 print(randint(0,1),randint(1,n))
```

1.4 head.cpp

```
1 #pragma GCC optimize(2,"Ofast","inline","unroll-loops")
2 #include <bits/stdc++.h>
3 using namespace std;
4 #define rep(i,a,n) for (int i=a;i<=n;i++)
5 #define per(i,a,n) for (int i=a;i>=n;i--)
6 #define pb push_back
7 #define eb emplace_back
8 #define mp make_pair
```

```

9  #define all(x) (x).begin(),(x).end()
10 #define bit(x) (1ll<<(x))
11 #define fi first
12 #define se second
13 #define SZ(x) ((int)(x).size())
14 typedef vector<int> VI;
15 typedef long long ll;
16 typedef pair<int, int> PII;
17 typedef double db;
18 mt19937_64 rng(random_device {}());
19 typedef long double ldb;
20 typedef unsigned long long ull;
21 ll powmod(ll a,ll b,const ll p) { ll res=1; while (b) { if (b&1) res=res*a%p
    ; b>>=1; a=a*a%p; } return res; }
22 // head
23
24 #ifdef DEBUG
25 #include "debug.cpp"
26 #else
27 #define debug(...) 42
28 #endif
29
30 const int mod = 1e9 + 7;
31 const ll inf = 1ll << 55;
32 const double pi = acosl(-1);
33 const double eps = 1e-12;
34 const int maxn = 2e5 + 105;
35 const int N = 2000005;
36
37 void solve() {}
38 int main() {
39     ios::sync_with_stdio(false);
40     cin.tie(nullptr);
41     int tt = 1;
42     // cin >> tt;
43     while (tt--) {
44         solve();
45     }
46 }

```

1.5 head-apiadu.cpp

```

1 #include <bits/stdc++.h>

```

```

2 using namespace std;
3 #define rep(i,a,n) for (int i=a;i<n;i++)
4 #define per(i,a,n) for (int i=n-1;i>=a;i--)
5 #define pb push_back
6 #define eb emplace_back
7 #define mp make_pair
8 #define all(x) (x).begin(),(x).end()
9 #define fi first
10 #define se second
11 #define SZ(x) ((int)(x).size())
12 typedef vector<int> VI;
13 typedef basic_string<int> BI;
14 typedef long long ll;
15 typedef pair<int,int> PII;
16 typedef double db;
17 mt19937 mrand(random_device {}());
18 const ll mod=1000000007;
19 int rnd(int x) { return mrand() % x;}
20 ll powmod(ll a,ll b) {ll res=1;a%=mod; assert(b>=0); for(;b>=1){if(b&1)
    res=res*a%mod;a=a%mod;}return res;}
21 ll gcd(ll a,ll b) { return b?gcd(b,a%b):a;}
22 // head

```

1.6 Makefile

```

1 %: %.cpp
2     g++-13 $< -o $@ -std=gnu++20 -g -O2 -Wall -Wextra -DDEBUG -
    D_GLIBCXX_DEBUG -D_GLIBCXX_DEBUG_PEDANTIC

```

1.7 pai.py

```

1 import os
2 tt=0
3 while True:
4     os.system('python gen.py>A.in')
5     os.system('./a<A.in>a.out')
6     os.system('./b<A.in>b.out')
7     if os.system('diff a.out b.out'):
8         print("WA")
9         exit(0)
10    else:
11        tt+=1
12        print("AC:",tt)

```

1.8 settings.json

```
1 {
2     "editor.formatOnSave": true,
3     "files.autoSave": "afterDelay",
4     "files.autoSaveDelay": 350,
5     "C_Cpp.default.cppStandard": "gnu++20"
6 }
```

1.9 template.cpp

```
1 #pragma GCC optimize(2, "Ofast", "inline", "unroll-loops")
2 #include <bits/stdc++.h>
3 using namespace std;
4 #define rep(i, a, n) for (int i = a; i <= n; i++)
5 #define per(i, a, n) for (int i = a; i >= n; i--)
6 #define pb push_back
7 #define eb emplace_back
8 #define all(x) (x).begin(), (x).end()
9 #define bit(x) (1ll << (x))
10 #define fi first
11 #define se second
12 #define SZ(x) ((int)(x).size())
13 using VI = vector<int>;
14 using PII = pair<int, int>;
15 using ll = long long;
16 using ull = unsigned long long;
17 using db = double;
18 using ldb = long double;
19 mt19937_64 rng(chrono::steady_clock::now().time_since_epoch().count());
20 // head
21
22 #ifdef DEBUG
23 #include "debug.cpp"
24 #else
25 #define debug(...) 42
26 #endif
27
28 void solve() {}
29 int main() {
30     cin.tie(nullptr)->sync_with_stdio(false);
31     cout << fixed << setprecision(16);
32     int tt = 1;
33     cin >> tt;
```

```
34     while (tt--) {
35         solve();
36     }
37 }
```

2 Data

2.1 01trie.cpp

```
1 struct node {
2     int son[2];
3     int end;
4     int sz;
5 } seg[maxn << 2];
6 int root, tot;
7 int n, m;
8
9 void insert(ll x) {
10     int cnt = root;
11     for (int i = 62; i >= 0; i--) {
12         int w = (x >> i) & 1;
13         if (seg[cnt].son[w] == 0) seg[cnt].son[w] = ++tot;
14         cnt = seg[cnt].son[w];
15         seg[cnt].sz++;
16     }
17     seg[cnt].end++;
18 }
19
20 ll query(ll x, ll k) {
21     ll res = 0;
22     int cnt = root;
23     for (int i = 62; i >= 0; i--) {
24         int w = (x >> i) & 1;
25         if (seg[seg[cnt].son[w]].sz >= k) cnt = seg[cnt].son[w];
26         else {
27             k -= seg[seg[cnt].son[w]].sz;
28             cnt = seg[cnt].son[abs(w - 1)];
29             res += bit(i);
30         }
31     }
32     return res;
33 }
```

2.2 2dtree(bqi343).cpp

```
1  const int SZ = 1.1e5;
2  template <class T>
3  struct node {
4      T val = 0;
5      node<T>* c[2];
6      node() { c[0] = c[1] = NULL; }
7      void upd(int ind, T v, int L = 0, int R = SZ - 1) { // add v
8          if (L == ind && R == ind) {
9              val += v;
10             return;
11         }
12         int M = (L + R) / 2;
13         if (ind <= M) {
14             if (!c[0]) c[0] = new node();
15             c[0]->upd(ind, v, L, M);
16         } else {
17             if (!c[1]) c[1] = new node();
18             c[1]->upd(ind, v, M + 1, R);
19         }
20         val = 0;
21         rep(i, 0, 1) if (c[i]) val += c[i]->val;
22     }
23     T query(int lo, int hi, int L = 0, int R = SZ - 1) { // query sum
24         of segment
25         if (hi < L || R < lo) return 0;
26         if (lo <= L && R <= hi) return val;
27         int M = (L + R) / 2;
28         T res = 0;
29         if (c[0]) res += c[0]->query(lo, hi, L, M);
30         if (c[1]) res += c[1]->query(lo, hi, M + 1, R);
31         return res;
32     }
33     void UPD(int ind, node* c0, node* c1, int L = 0, int R = SZ - 1) {
34         // for 2D segtree
35         if (L != R) {
36             int M = (L + R) / 2;
37             if (ind <= M) {
38                 if (!c[0]) c[0] = new node();
39                 c[0]->UPD(ind, c0 ? c0->c[0] : NULL, c1 ? c1
40                     ->c[0] : NULL, L, M);
41             } else {
42                 if (!c[1]) c[1] = new node();
```

```
40                 c[1]->UPD(ind, c0 ? c0->c[1] : NULL, c1 ? c1
41                     ->c[1] : NULL, M + 1, R);
42             }
43             val = (c0 ? c0->val : 0) + (c1 ? c1->val : 0);
44         }
45     };
46
47     /**
48      * Description: BIT of SegTrees. $x\in (0,SZ), y\in [0,SZ)$.
49      * Memory:  $O(N\log^2 N)$ 
50      * Source: USACO Mowing the Field
51      * Verification:
52      * USACO Mowing the Field
53      * http://www.usaco.org/index.php?page=viewproblem2&cpid=722 (13/15, 15/15
54          and 1857ms with BumpAllocator)
55      */
56     #include "../1D_Range_Queries_(9.2)/SparseSeg_(9.2).h"
57
58     template <class T>
59     struct BITseg {
60         node<T> seg[SZ];
61         BITseg() { fill(seg, seg + SZ, node<T>()); }
62         void upd(int x, int y, int v) { // add v
63             for (; x < SZ; x += x & -x) seg[x].upd(y, v);
64         }
65         T query(int x, int yl, int yr) {
66             T res = 0;
67             for (; x; x -= x & -x) res += seg[x].query(yl, yr);
68             return res;
69         }
70         T query(int xl, int xr, int yl, int yr) { // query sum of rectangle
71             return query(xr, yl, yr) - query(xl - 1, yl, yr);
72         }
73     };
74
75     /**
76      * Description: SegTree of SegTrees. $x,y\in [0,SZ)$.
77      * Memory:  $O(N\log^2 N)$ 
78      * Source: USACO Mowing the Field
79      * Verification:
80      * http://www.usaco.org/index.php?page=viewproblem2&cpid=722 (9/15 w/
```

```

        BumpAllocator)
81  * http://www.usaco.org/index.php?page=viewproblem2&cpid=601 (4238 ms, 2907
        ms w/ BumpAllocator)
82  */
83
84  #include "../1D_Range_Queries_(9.2)/SparseSeg_(9.2).h"
85
86  template <class T>
87  struct Node {
88      node<T> seg;
89      Node* c[2];
90      Node() { c[0] = c[1] = NULL; }
91      void upd(int x, int y, T v, int L = 0, int R = SZ - 1) { // add v
92          if (L == x && R == x) {
93              seg.upd(y, v);
94              return;
95          }
96          int M = (L + R) / 2;
97          if (x <= M) {
98              if (!c[0]) c[0] = new Node();
99              c[0]->upd(x, y, v, L, M);
100          } else {
101              if (!c[1]) c[1] = new Node();
102              c[1]->upd(x, y, v, M + 1, R);
103          }
104          seg.upd(y, v); // only for addition
105          // seg.UPD(y, c[0]?&c[0]->seg:NULL, c[1]?&c[1]->seg:NULL);
106      }
107      T query(int x1, int x2, int y1, int y2, int L = 0, int R = SZ - 1) {
108          // query sum of rectangle
109          if (x1 <= L && R <= x2) return seg.query(y1, y2);
110          if (x2 < L || R < x1) return 0;
111          int M = (L + R) / 2;
112          T res = 0;
113          if (c[0]) res += c[0]->query(x1, x2, y1, y2, L, M);
114          if (c[1]) res += c[1]->query(x1, x2, y1, y2, M + 1, R);
115          return res;
116      };
};

```

2.3 cdq.cpp

```

1  int ans[maxn], lev[maxn];

```

```

2  array<int, 5> v[maxn], tmp[maxn];
3
4  struct BIT {
5      ...
6  } c;
7
8  void solve(int l, int r) {
9      if (l >= r) return;
10     int mid = (l + r) / 2;
11     solve(l, mid), solve(mid + 1, r);
12     int i = l, j = mid + 1;
13     int piv = 1;
14     while (i <= mid || j <= r) {
15         if (i <= mid && (j > r || mp(v[i][1], v[i][2]) <= mp(v[j][1], v[j]
16             ] [2]))) {
17             c.modify(v[i][2], v[i][3]);
18             tmp[piv++] = v[i++];
19         } else {
20             v[j][4] += c.query(v[j][2]);
21             tmp[piv++] = v[j++];
22         }
23     }
24     rep(i, l, mid) c.modify(v[i][2], -v[i][3]);
25     rep(i, l, r) v[i] = tmp[i];
26 }
27 void solve() {
28     cin >> n >> k;
29     c.resize(k);
30     rep(i, 1, n) {
31         int s, c, m;
32         cin >> s >> c >> m;
33         v[i] = {s, c, m, 1, 0};
34     }
35     v[0][0] = -1;
36     sort(v + 1, v + n + 1);
37     int cnt = 0;
38     rep(i, 1, n) {
39         if (v[i][0] == v[cnt][0] && v[i][1] == v[cnt][1] && v[i][2] == v[cnt]
40             ] [2]) v[cnt][3]++;
41         else v[++cnt] = v[i];
42     }
43     solve(1, cnt);

```

```

43     rep(i, 1, cnt) {
44         ans[v[i][4] + v[i][3] - 1] += v[i][3];
45     }
46     rep(i, 0, n - 1) cout << ans[i] << '\n';
47 }

```

2.4 compact.cpp

```

1  namespace compact {
2  const int LOGN=18;
3  int l[N],r[N],tot,p[N][20],n;
4  map<int,int> cv;
5  int lca(int u,int v) {
6      if (dep[u]>dep[v]) swap(u,v);
7      per(i,LOGN-1,0) if (dep[p[v][i]]>=dep[u]) v=p[v][i];
8      if (u==v) return u;
9      per(i,LOGN-1,0) if (p[v][i]!=p[u][i]) u=p[u][i],v=p[v][i];
10     return p[u][0];
11 }
12 void dfs(int u,int f) {
13     l[u]=++tot; dep[u]=dep[f]+1; p[u][0]=f;
14     vec[dep[u]].pb(u);
15     for (auto v:vE[u]) {
16         if (v==f) continue;
17         dfs(v,u);
18     }
19     r[u]=tot;
20 }
21 void build(int _n) {
22     n=_n; tot=0;
23     dfs(1,0);
24     rep(j,1,LOGN-1) rep(i,1,n) p[i][j]=p[p[i][j-1]][j-1];
25 }
26
27 bool cmp(int u,int v) { return l[u]<l[v]; }
28 vector<PII> compact(VI v) {
29     int m=SZ(v);
30     vector<PII> E;
31     sort(all(v),cmp);
32     rep(i,0,m-2) {
33         int w=lca(v[i],v[i+1]);
34         v.pb(w);
35     }

```

```

36     v.pb(0);
37     v.pb(1);
38     sort(all(v),cmp);
39     v.erase(unique(all(v)),v.end());
40     cv.clear();
41     per(i, SZ(v)-1, 1) {
42         int u=v[i];
43         while (1) {
44             auto it=cv.lower_bound(l[u]);
45             if (it==cv.end()||it->fi>r[u]) break;
46             E.pb(mp(u,v[it->se]));
47             cv.erase(it);
48         }
49         cv[l[u]]=i;
50     }
51     return E;
52 }
53 };

```

2.5 dominator.cpp

```

1  void solve(int u, int S) {
2      int best = -1, cnt = S + 1;
3      auto find_best = [&](auto &find_best, int u, int par) -> void {
4          sz[u] = 1, sdom[u] = 0;
5          for (auto v : e[u]) {
6              if (v == par || del[v]) continue;
7              find_best(find_best, v, u);
8              sz[u] += sz[v];
9              sdom[u] = max(sdom[u], sz[v]);
10         }
11         sdom[u] = max(sdom[u], S - sz[u]);
12         if (sdom[u] < cnt) {
13             cnt = sdom[u], best = u;
14         }
15     };
16     find_best(find_best, u, 0);
17     int id1 = tot++, dep1 = 0;
18     int id2, dep2;
19     auto dfs = [&](auto &dfs, int u, int par, int dep) -> void {
20         dep1 = max(dep1, dep);
21         dep2 = max(dep2, dep);
22         Q[u].pb({id1, 1, dep});

```

```

23         Q[u].pb({id2, -1, dep});
24         for (auto v : e[u]) {
25             if (v == par || del[v]) continue;
26             dfs(dfs, v, u, dep + 1);
27         }
28     };
29     Q[best].pb({id1, 1, 0});
30     for (auto v : e[best]) {
31         if (del[v]) continue;
32         id2 = tot++, dep2 = 0;
33         dfs(dfs, v, best, 1);
34         fenw[id2] = BIT<ll>(dep2 + 1);
35     }
36     fenw[id1] = BIT<ll>(dep1 + 1);
37     del[best] = 1;
38     for (auto v : e[best]) {
39         if (!del[v]) solve(v, sz[v]);
40     }
41 }

```

2.6 dsu.cpp

```

1 class dsu {
2 public:
3     vector<int> fa;
4     vector<ll> dist;
5     int n;
6
7     dsu(int _n) : n(_n) {
8         fa.resize(n);
9         dist.assign(n, 0);
10        iota(fa.begin(), fa.end(), 0);
11    }
12
13    int find(int x) {
14        if (fa[x] == x) return x;
15        int par = fa[x];
16        fa[x] = find(fa[x]);
17        dist[x] += dist[par];
18        return fa[x];
19    }
20
21    void unite(int x, int y, ll v) {

```

```

22        int px = find(x);
23        int py = find(y);
24        fa[py] = px;
25        dist[py] = dist[x] - dist[y] - v;
26    }
27 };

```

2.7 dsu-on-tree.cpp

```

1 void dfs(int x, int fa) {
2     hs[x] = -1, w[x] = 1;
3     l[x] = ++tot;
4     id[tot] = x;
5     for (auto y : g[x]) if (y != fa) {
6         dfs(y, x);
7         w[x] += w[y];
8         if (hs[x] == -1 || w[y] > w[hs[x]])
9             hs[x] = y;
10    }
11    r[x] = tot;
12 }
13
14 void dsu(int x, int fa, int keep) {
15     for (auto y : g[x]) {
16         if (y != hs[x] && y != fa) {
17             dsu(y, x, 0);
18         }
19     }
20     if (hs[x] != -1) dsu(hs[x], x, 1);
21
22     for (auto y : g[x]) {
23         if (y != hs[x] && y != fa) {
24             for (int i = l[y]; i <= r[y]; i++) {
25
26             }
27         }
28     }
29     // add current node
30
31     ans[x] = cnt;
32
33     if (!keep) {
34         // clear

```



```

35     }
36 }

```

2.8 fenwick.cpp

```

1  template <typename T>
2  struct BIT {
3      vector<T> fenw;
4      int n, pw;
5
6      BIT(int n_ = 0) : n(n_) {
7          fenw.assign(n + 1, 0);
8          pw = bit_floor(unsigned(n));
9      }
10
11     void Modify(int x, T v) {
12         if (x <= 0) return; // assert(0 <= x && x < n);
13         while (x <= n) { // x < n
14             fenw[x] += v;
15             x += (x & -x); // x |= x + 1;
16         }
17     }
18
19     T Query(int x) {
20         // assert(0 <= x && x <= n);
21         T v{};
22         while (x > 0) {
23             v += fenw[x]; // fenw[x - 1];
24             x -= (x & -x); // x &= x - 1;
25         }
26         return v;
27     }
28
29     // Returns the length of the longest prefix with sum <= c
30     int MaxPrefix(T c) {
31         T v{};
32         int at = 0;
33         for (int i = 20; i >= 0; i--) {
34             if (at + bit(i) <= n && v + fenw[at + bit(i)] <= c) {
35                 v += fenw[at + bit(i)];
36                 at += bit(i);
37             }
38         }

```

```

39     /**
40      * for (int len = pw; len > 0; len >>= 1) {
41      *     if (at + len <= n) {
42      *         auto nv = v;
43      *         nv += fenw[at + len - 1];
44      *         if (!(c < nv)) {
45      *             v = nv;
46      *             at += len;
47      *         }
48      *     }
49      * }
50     * assert(0 <= at && at <= n);
51     */
52     return at;
53 }
54 };

```

2.9 fenwick2d.cpp

```

1  template <typename T>
2  class fenwick2d {
3  public:
4      vector<vector<T>> fenw;
5      int n, m;
6
7      fenwick2d(int _n, int _m) : n(_n), m(_m) {
8          fenw.resize(n);
9          for (int i = 0; i < n; i++) {
10             fenw[i].resize(m);
11         }
12     }
13
14     inline void modify(int i, int j, T v) {
15         int x = i;
16         while (x < n) {
17             int y = j;
18             while (y < m) {
19                 fenw[x][y] += v;
20                 y |= (y + 1);
21             }
22             x |= (x + 1);
23         }
24     }

```

```

25
26     inline T get(int i, int j) {
27         T v{};
28         int x = i;
29         while (x >= 0) {
30             int y = j;
31             while (y >= 0) {
32                 v += fenw[x][y];
33                 y = (y & (y + 1)) - 1;
34             }
35             x = (x & (x + 1)) - 1;
36         }
37         return v;
38     }
39 };
40
41 struct node {
42     int a = ...; // don't forget to set default value
43
44     inline void operator+=(node &other) {
45         ...
46     }
47 };

```

2.10 hash-table.cpp

```

1 struct Hash_table {
2     static const int V = 1000003;
3     int fst[V], nxt[V];
4     int ctm, ptm[V], T;
5     int val[V];
6     ll key[V];
7     void init() {T = 0, ctm++;}
8     void insert(ll k, int v) {
9         int s = k % V;
10        if (ptm[s] != ctm) ptm[s] = ctm, fst[s] = -1;
11        for (int i = fst[s]; i != -1; i = nxt[i]) if (key[i] == k) {
12            return;
13        }
14        nxt[T] = fst[s], fst[s] = T, key[T] = k, val[T] = v;
15        T++;
16    }
17    int query(ll k) {

```

```

18        int s = k % V;
19        if (ptm[s] != ctm) return -1;
20        for (int i = fst[s]; i != -1; i = nxt[i]) {
21            if (key[i] == k) return val[i];
22        }
23        return -1;
24    }
25 };

```

2.11 HLD.cpp

```

1 struct HLD {
2     int n;
3     std::vector<int> siz, top, dep, parent, in, out, seq;
4     std::vector<std::vector<int>>> adj;
5     int cur;
6
7     HLD() {}
8     HLD(int n) {
9         init(n);
10    }
11    void init(int n) {
12        this->n = n;
13        siz.resize(n);
14        top.resize(n);
15        dep.resize(n);
16        parent.resize(n);
17        in.resize(n);
18        out.resize(n);
19        seq.resize(n);
20        cur = 0;
21        adj.assign(n, {});
22    }
23    void addEdge(int u, int v) {
24        adj[u].push_back(v);
25        adj[v].push_back(u);
26    }
27    void work(int root = 0) {
28        top[root] = root;
29        dep[root] = 0;
30        parent[root] = -1;
31        dfs1(root);
32        dfs2(root);

```

```

33     }
34     void dfs1(int u) {
35         if (parent[u] != -1) {
36             adj[u].erase(std::find(adj[u].begin(), adj[u].end(), parent[u]))
37             ;
38         }
39         siz[u] = 1;
40         for (auto &v : adj[u]) {
41             parent[v] = u;
42             dep[v] = dep[u] + 1;
43             dfs1(v);
44             siz[u] += siz[v];
45             if (siz[v] > siz[adj[u][0]]) {
46                 std::swap(v, adj[u][0]);
47             }
48         }
49     }
50     void dfs2(int u) {
51         in[u] = cur++;
52         seq[in[u]] = u;
53         for (auto v : adj[u]) {
54             top[v] = v == adj[u][0] ? top[u] : v;
55             dfs2(v);
56         }
57         out[u] = cur;
58     }
59     int lca(int u, int v) {
60         while (top[u] != top[v]) {
61             if (dep[top[u]] > dep[top[v]]) {
62                 u = parent[top[u]];
63             } else {
64                 v = parent[top[v]];
65             }
66         }
67         return dep[u] < dep[v] ? u : v;
68     }
69
70     int dist(int u, int v) {
71         return dep[u] + dep[v] - 2 * dep[lca(u, v)];
72     }
73
74     int jump(int u, int k) {

```

```

75         if (dep[u] < k) {
76             return -1;
77         }
78
79         int d = dep[u] - k;
80
81         while (dep[top[u]] > d) {
82             u = parent[top[u]];
83         }
84
85         return seq[in[u] - dep[u] + d];
86     }
87
88     bool isAncestor(int u, int v) {
89         return in[u] <= in[v] && in[v] < out[u];
90     }
91
92     int rootedParent(int u, int v) {
93         std::swap(u, v);
94         if (u == v) {
95             return u;
96         }
97         if (!isAncestor(u, v)) {
98             return parent[u];
99         }
100         auto it = std::upper_bound(adj[u].begin(), adj[u].end(), v, [&](int
101             x, int y) {
102                 return in[x] < in[y];
103             }) - 1;
104         return *it;
105     }
106
107     int rootedSize(int u, int v) {
108         if (u == v) {
109             return n;
110         }
111         if (!isAncestor(v, u)) {
112             return siz[v];
113         }
114         return n - siz[rootedParent(u, v)];
115     }
116
117     int rootedLca(int a, int b, int c) {

```

```

117     return lca(a, b) ^ lca(b, c) ^ lca(c, a);
118 }
119 };

```

2.12 kdtree.cpp

```

1 namespace kd {
2     const int K = 2, N = 2.1e5;
3     template <typename T>
4     using P = array<T, K>;
5     template <typename T>
6     struct node {
7         P<T> pt, mx, mn;
8         ll val, sum;
9         node *l, *r, *p;
10        int id;
11        node(const P<T> &_pt = P<T>(), ll _val = 0, int _id = 0) :
12            pt(_pt), val(_val), sum(_val), id(_id) {
13            mx = mn = pt;
14            p = l = r = nullptr;
15        }
16    };
17    node<ll> *ptr[N];
18    template <typename T>
19    void pull(node<T> *u) {
20        if (not u) return;
21        u->sum = u->val;
22        rep(i, 0, K - 1) u->mx[i] = u->mn[i] = u->pt[i];
23        if (u->l) {
24            u->sum += u->l->sum;
25            u->l->p = u;
26        }
27        if (u->r) {
28            u->sum += u->r->sum;
29            u->r->p = u;
30        }
31        rep(i, 0, K - 1) {
32            if (u->l) {
33                u->mx[i] = max(u->mx[i], u->l->mx[i]);
34                u->mn[i] = min(u->mn[i], u->l->mn[i]);
35            }
36            if (u->r) {
37                u->mx[i] = max(u->mx[i], u->r->mx[i]);

```

```

37                u->mn[i] = min(u->mn[i], u->r->mn[i]);
38            }
39        }
40    }
41
42    template <typename T>
43    node<T> *build(vector<node<T>> &a, int l, int r, int d = 0) {
44        if (d == K) d = 0;
45        if (l >= r) {
46            return nullptr;
47        } else {
48            int md = (l + r) >> 1;
49            nth_element(a.begin() + l, a.begin() + md, a.begin()
50                + r, [&](node<T> &x, node<T> &y) { return x.pt[
51                d] < y.pt[d]; });
52            node<T> *p = new node<T>(a[md]);
53            ptr[p->id] = p;
54            p->l = build(a, l, md, d + 1);
55            p->r = build(a, md + 1, r, d + 1);
56            pull(p);
57            return p;
58        }
59    }
60
61    template <typename T>
62    node<T> *search(node<T> *u, P<T> p, int d = 0) {
63        if (d == K) d = 0;
64        if (not u) return nullptr;
65        if (u->pt == p) return u;
66        if (p[d] < u->pt[d]) {
67            return search(u->l, p, d + 1);
68        } else if (p[d] > u->pt[d]) {
69            return search(u->r, p, d + 1);
70        } else {
71            auto tmp = search(u->l, p, d + 1);
72            if (tmp) return tmp;
73            return search(u->r, p, d + 1);
74        }
75    }
76
77    template <typename T>
78    void modify(node<T> *u, ll v) {
79        if (not u) return;

```

```

78         u->val = v;
79         for (auto cur = u; cur; cur = cur->p) {
80             pull(cur);
81         }
82     }
83
84     template <typename T>
85     bool inside(node<T> *nd, P<T> p, ll c) {
86         int cc = 0;
87         if (nd->mx[0] * p[0] + nd->mx[1] * p[1] >= c) cc++;
88         if (nd->mn[0] * p[0] + nd->mn[1] * p[1] >= c) cc++;
89         if (nd->mx[0] * p[0] + nd->mn[1] * p[1] >= c) cc++;
90         if (nd->mn[0] * p[0] + nd->mx[1] * p[1] >= c) cc++;
91         return cc == 0;
92     }
93
94     template <typename T>
95     bool outside(node<T> *nd, P<T> p, ll c) {
96         int cc = 0;
97         if (nd->mx[0] * p[0] + nd->mx[1] * p[1] >= c) cc++;
98         if (nd->mn[0] * p[0] + nd->mn[1] * p[1] >= c) cc++;
99         if (nd->mx[0] * p[0] + nd->mn[1] * p[1] >= c) cc++;
100        if (nd->mn[0] * p[0] + nd->mx[1] * p[1] >= c) cc++;
101        return cc == 4;
102    }
103
104    template <typename T>
105    ll query(node<T> *u, P<T> p, ll c) {
106        if (inside(u, p, c)) return u->sum;
107        if (outside(u, p, c)) return 0;
108        ll s = 0;
109        if (u->pt[0] * p[0] + u->pt[1] * p[1] < c) {
110            s += u->val;
111        }
112        if (u->l) s += query(u->l, p, c);
113        if (u->r) s += query(u->r, p, c);
114        return s;
115    }
116
117    template <typename T>
118    T eval_min(node<T> *nd, P<T> p) { // 通过估价函数进行启发式搜索，根据当前结果对搜索剪枝
119        if (not nd) return numeric_limits<T>::max() / 4;

```

```

120        ll s = 0;
121        rep(i, 0, K - 1) {
122            if (p[i] <= nd->mn[i]) s += nd->mn[i] - p[i];
123            if (p[i] >= nd->mx[i]) s += p[i] - nd->mx[i];
124        }
125        return s;
126    }
127
128    template <typename T>
129    ll mindist(node<T> *u, P<T> p) {
130        ll s = numeric_limits<T>::max() / 4;
131        if (u->pt != p) {
132            s = min(s, abs(u->pt[0] - p[0]) + abs(u->pt[1] - p[1]));
133        }
134        ll best1 = eval_min(u->l, p), best2 = eval_min(u->r, p);
135        if (best1 < best2) {
136            if (u->l) s = min(s, mindist(u->l, p));
137            if (u->r and best2 < s) s = min(s, mindist(u->r, p));
138            ;
139            return s;
140        } else {
141            if (u->r) s = min(s, mindist(u->r, p));
142            if (u->l and best1 < s) s = min(s, mindist(u->l, p));
143            ;
144            return s;
145        }
146    }
147
148    template <typename T>
149    T eval_max(node<T> *nd, P<T> p) { // 通过估价函数进行启发式搜索，根据当前结果对搜索剪枝
150        if (not nd) return 0;
151        ll s = 0;
152        rep(i, 0, K - 1) s += max(abs(nd->mx[i] - p[i]), abs(nd->mn[i] - p[i]));
153        return s;
154    }
155
156    template <typename T>
157    ll maxdist(node<T> *u, P<T> p) {
158        ll s = 0;
159        if (u->pt != p) {

```

```

158         s = max(s, abs(u->pt[0] - p[0]) + abs(u->pt[1] - p
159             [1]));
160     }
161     ll best1 = eval_max(u->l, p), best2 = eval_max(u->r, p);
162     if (best1 > best2) {
163         if (u->l) s = max(s, maxdist(u->l, p));
164         if (u->r and best2 > s) s = max(s, maxdist(u->r, p))
165             ;
166         return s;
167     } else {
168         if (u->r) s = max(s, maxdist(u->r, p));
169         if (u->l and best1 > s) s = max(s, maxdist(u->l, p))
170             ;
171         return s;
172     }
173 } // namespace kd

```

2.13 LCT.cpp

```

1 namespace linkCutTree {
2 struct node {
3     node *child[2], *parent, *max;
4     int id;
5     ll sum, val, sz, weight, rev;
6     node(ll val, ll weight, int id) : child {nullptr, nullptr}, parent(
7         nullptr), max(this), sum(val), val(val), sz(weight), weight(weight),
8         id(id), rev(false) {}
9 };
10
11 bool isRoot(node *p) { return p->parent == nullptr || (p->parent->child[0]
12     != p && p->parent->child[1] != p); }
13
14 int side(node *p) { return p->parent->child[1] == p; }
15
16 ll sum(node *p) { return p == nullptr ? 0 : p->sum; }
17
18 ll sz(node *p) { return p == nullptr ? 0 : p->sz; }
19
20 node *max(node *p) { return p == nullptr ? nullptr : p->max; }
21
22 node *max(node *p, node *q) {
23     if (p == nullptr)

```

```

21         return q;
22     if (q == nullptr)
23         return p;
24     return p->weight > q->weight ? p : q;
25 }
26
27 void reverse(node *p) {
28     if (p == nullptr)
29         return;
30     swap(p->child[0], p->child[1]);
31     p->rev ^= 1;
32 }
33
34 void push(node *p) {
35     if (p->rev == 0)
36         return;
37     p->rev = 0;
38     reverse(p->child[0]);
39     reverse(p->child[1]);
40 }
41
42 void pull(node *p) {
43     p->sum = sum(p->child[0]) + sum(p->child[1]) + p->val;
44     p->max = max(max(max(p->child[0]), max(p->child[1])), p);
45     p->sz = p->weight + sz(p->child[0]) + sz(p->child[1]);
46 }
47
48 void connect(node *p, node *q, int side) {
49     q->child[side] = p;
50     if (p != nullptr)
51         p->parent = q;
52 }
53
54 void rotate(node *p) {
55     auto q = p->parent;
56     int dir = side(p) ^ 1;
57     connect(p->child[dir], q, dir ^ 1);
58     if (!isRoot(q))
59         connect(p, q->parent, side(q));
60     else
61         p->parent = q->parent;
62     connect(q, p, dir);
63     pull(q);

```

```

64 }
65
66 void splay(node *p) {
67     vector<node *> stk;
68     for (auto i = p; !isRoot(i); i = i->parent)
69         stk.push_back(i->parent);
70     while (!stk.empty()) {
71         push(stk.back());
72         stk.pop_back();
73     }
74     push(p);
75     while (!isRoot(p)) {
76         auto q = p->parent;
77         if (!isRoot(q))
78             rotate(side(p) == side(q) ? q : p);
79         rotate(p);
80     }
81     pull(p);
82 }
83
84 node *access(node *p) {
85     node *j = nullptr;
86     for (node *i = p; i != nullptr; j = i, i = i->parent) {
87         splay(i);
88         i->val -= sum(j);
89         i->val += sum(i->child[1]);
90         i->child[1] = j;
91         pull(i);
92     }
93     splay(p);
94     return j;
95 }
96
97 void makeRoot(node *p) {
98     access(p);
99     reverse(p);
100 }
101
102 void link(node *p, node *q) {
103     makeRoot(p);
104     access(q);
105     p->parent = q;
106     q->val += sum(p);

```

```

107 }
108
109 void cut(node *p, node *q) {
110     makeRoot(p);
111     access(q);
112     p->parent = q->child[0] = nullptr;
113 }
114
115 node *pathMax(node *p, node *q) {
116     makeRoot(p);
117     access(q);
118     return max(q);
119 }
120
121 ll pathSize(node *p, node *q) {
122     makeRoot(p);
123     access(q);
124     return sz(q);
125 }
126
127 ll rootedSum(node *p) {
128     makeRoot(p);
129     return sum(p);
130 }
131
132 ll getSubtree(node *rt, node *v) {
133     makeRoot(rt);
134     access(v);
135     return v->val;
136 }
137
138 bool connected(node *p, node *q) {
139     access(p);
140     access(q);
141     return p->parent != nullptr;
142 }
143
144 void fix(node *p, ll v) {
145     access(p);
146     push(p);
147     // modify ...
148     p->val += v;
149     pull(p);

```

```

150 }
151
152 node *lca(node *z,node *x,node *y) {
153     makeRoot(z);
154     access(x);
155     return access(y);
156 }
157 } // namespace linkCutTree
158 using namespace linkCutTree;

```

2.14 lichao-tree.cpp

```

1 struct Line {
2     i64 k, b;
3     i64 operator()(i64 x) const { return k * x + b; }
4 };
5 template <i64 L, i64 R>
6 struct Segments {
7     struct Node {
8         optional<Line> s;
9         Node *l, *r;
10    };
11    Node *root;
12    Segments() : root(nullptr) {}
13    void add(i64 l, i64 r, i64 k, i64 b) {
14        auto rec = [&](auto &rec, Node *p, i64 tl, i64 tr, Line s) -> void {
15            if (p == nullptr) p = new Node();
16            i64 tm = midpoint(tl, tr);
17            if (tl >= l and tr <= r) {
18                if (not p->s) return p->s = s, void();
19                auto t = p->s.value();
20                if (t(tl) >= s(tl)) {
21                    if (t(tr) >= s(tr)) return;
22                    if (t(tm) >= s(tm)) return rec(rec, p->r, tm + 1, tr, s);
23                    return p->s = s, rec(rec, p->l, tl, tm, t);
24                }
25                if (t(tr) <= s(tr)) return p->s = s, void();
26                if (t(tm) <= s(tm)) return p->s = s, rec(rec, p->r, tm + 1, tr, t);
27                return rec(rec, p->l, tl, tm, s);
28            }
29            if (l <= tm) rec(rec, p->l, tl, tm, s);
30            if (r > tm) rec(rec, p->r, tm + 1, tr, s);
31        };

```

```

32        rec(rec, root, L, R, {k, b});
33    }
34    optional<i64> get(i64 x) {
35        optional<i64> res = {};
36        auto rec = [&](auto &rec, Node *p, i64 tl, i64 tr) -> void {
37            if (p == nullptr) return;
38            i64 tm = midpoint(tl, tr);
39            if (p->s) {
40                i64 y = p->s.value()(x);
41                if (not res or res.value() < y) res = y;
42            }
43            if (x <= tm)
44                rec(rec, p->l, tl, tm);
45            else
46                rec(rec, p->r, tm + 1, tr);
47        };
48        rec(rec, root, L, R);
49        return res;
50    }
51 };

```

2.15 Mo.cpp

```

1 int main() {
2     std::ios::sync_with_stdio(false);
3     cin.tie(0); cout.tie(0);
4
5     for (int i = 1; i <= m; i++) {
6         int x, y;
7         cin >> x >> y;
8         q.pb({x, y, i});
9         rej[i] = (y - x + 1LL) * (y - x) / 2LL;
10    }
11    sort(q.begin(), q.end(), [&](array<int, 3> a, array<int, 3> b)->bool{
12        if (getb(a[0]) == getb(b[0]))
13            if (getb(a[0]) & 1)
14                return a[1] < b[1];
15            else
16                return a[1] > b[1];
17        else return getb(a[0]) < getb(b[0]);
18    });
19
20    int L = 1, R = 0;

```



```

21     for (int i = 0; i < m; i++) {
22         while (R < q[i][1]) R++, add(R);
23         while (L > q[i][0]) L--, add(L);
24         while (L < q[i][0]) del(L), L++;
25         while (R > q[i][1]) del(R), R--;
26         ans[q[i][2]] = tmp;
27     }
28 }

```

2.16 moTree.cpp

```

1 void add(int ind, int end) { ... } // add a [ ind ] (end = 0 or 1)
2 void del(int ind, int end) { ... } // remove a [ ind ]
3 int calc() { ... } // compute current answer
4 vi mo(vector<pii> Q) {
5     int L = 0, R = 0, blk = 350; // N/sqrt (Q)
6     vi s(sz(Q)), res = s;
7     #define K(x) pii(x.first/blk, x.second ^ -(x.first/blk & 1))
8     iota(all(s), 0);
9     sort(all(s), [&](int s, int t) { return K(Q[s]) < K(Q[t]); });
10    for (int qi : s) {
11        pii q = Q[qi];
12        while (L > q.first) add(--L, 0);
13        while (R < q.second) add(R++, 1);
14        while (L < q.first) del(L++, 0);
15        while (R > q.second) del(--R, 1);
16        res[qi] = calc();
17    }
18    return res;
19 }
20 vi moTree(vector<array<int, 2>> Q, vector<vi>& ed, int root = 0) {
21     int N = sz(ed), pos[2] = {}, blk = 350; // N/sqrt (Q)
22     vi s(sz(Q)), res = s, I(N), L(N), R(N), in(N), par(N);
23     add(0, 0), in[0] = 1;
24     auto dfs = [&](int x, int p, int dep, auto & f) -> void {
25         par[x] = p;
26         L[x] = N;
27         if (dep) I[x] = N++;
28         for (int y : ed[x]) if (y != p) f(y, x, !dep, f);
29         if (!dep) I[x] = N++;
30         R[x] = N;
31     };
32     dfs(root, -1, 0, dfs);

```

```

33 #define K(x) pii(I[x[0]] / blk, I[x[1]] ^ -(I[x[0]] / blk & 1))
34     iota(all(s), 0);
35     sort(all(s), [&](int s, int t) { return K(Q[s]) < K(Q[t]); });
36     for (int qi : s) rep(end, 0, 2) {
37         int &a = pos[end], b = Q[qi][end], i = 0;
38         #define step(c) { if (in[c]) { del(a, end); in[a] = 0; } \
39     else { add(c, end); in[c] = 1; } a = c; }
40         while (!(L[b] <= L[a] && R[a] <= R[b]))
41             I[i++] = b, b = par[b];
42         while (a != b) step(par[a]);
43         while (i--) step(I[i]);
44         if (end) res[qi] = calc();
45     }
46     return res;
47 }

```

2.17 MSTMo.cpp

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 #define rep(i,a,n) for (int i=a;i<n;i++)
4 #define per(i,a,n) for (int i=n-1;i>=a;i--)
5 #define pb push_back
6 #define mp make_pair
7 #define all(x) (x).begin(),(x).end()
8 #define fi first
9 #define se second
10 #define SZ(x) ((int)(x).size())
11 typedef vector<int> VI;
12 typedef long long ll;
13 typedef pair<int,int> PII;
14 typedef double db;
15 mt19937 mrand(random_device{}());
16 const ll mod=1000000007;
17 int rnd(int x) { return mrand() % x;}
18 ll powmod(ll a,ll b) {ll res=1;a%=mod; assert(b>=0); for(;b>=>1){if(b&1)
19     res=res*a%mod;a=a*a%mod;}return res;}
20 ll gcd(ll a,ll b) { return b?gcd(b,a%b):a;}
21 // head
22
23 const int N=1010000;
24 int a[N];

```

```

25 namespace Mo {
26     int Q,l[N],r[N],f[N],l0,r0,ans[N],n;
27     VI ne[N];
28     struct point {
29         int x, y, o;
30         point(int a, int b, int c): x(a), y(b), o(c) {}
31     };
32     inline bool operator<(const point &a, const point &b) {
33         if (a.x != b.x) return a.x > b.x;
34         else return a.y < b.y;
35     }
36     vector<point> p;
37     struct edge {
38         int s, t, d;
39         edge(const point &a, const point &b): s(a.o), t(b.o),
40             d(abs(a.x - b.x) + abs(a.y - b.y)) {}
41     };
42     inline bool operator<(const edge &a, const edge &b) {return a.d < b.d;}
43     vector<edge> e;
44     int g[N],z[N];
45     int cc,cnt[101000];
46     void addedge() {
47         sort(all(p));
48         memset(g,0,sizeof(g));
49         z[0]=N;
50         rep(i,0,SZ(p)) z[i+1]=p[i].x-p[i].y;
51         rep(i,0,SZ(p)) {
52             int k = 0, t = p[i].x + p[i].y;
53             for (int j = t; j; j -= j & -j)
54                 if (z[g[j]] < z[k]) k = g[j];
55             if (k) e.pb(edge(p[i], p[k - 1]));
56             k = z[i + 1];
57             for (int j = t; j < N; j += j & -j)
58                 if (k < z[g[j]]) g[j] = i + 1;
59         }
60     }
61     void updata(int i, bool j,bool k=0) {
62         // j=1 insert j=0 delete
63         // k=0 left k=1 right
64         if (j==1) {
65             cnt[a[i]]++;
66             if (cnt[a[i]]%2==0) cc++;
67         } else {

```

```

68             if (cnt[a[i]]%2==0) cc--;
69             cnt[a[i]]--;
70         }
71     }
72     void init(int l,int r) {
73         for (int i=l;i<=r;i++) {
74             cnt[a[i]]++;
75             if (cnt[a[i]]%2==0) cc++;
76         }
77     }
78     inline int query() {
79         return cc;
80     }
81     int find(int x) { if (f[x] != x) f[x] = find(f[x]); return f[x];}
82     void dfs(int i,int p) {
83         int l1 = l[i], r1 = r[i];
84         per(j,l1,l0) updata(j,1,0);
85         rep(j,r0+1,r1+1) updata(j,1,1);
86         rep(j,l0,l1) updata(j,0,0);
87         per(j,r1+1,r0+1) updata(j,0,1);
88         ans[i]=query();l0=l1;r0=r1;
89         rep(j,0,SZ(ne[i])) if (ne[i][j]!=p) dfs(ne[i][j],i);
90     }
91     void solve() {
92         p.clear();e.clear();
93         rep(i,1,Q+1) ans[i]=0;
94         rep(i,1,Q+1) p.pb(point(l[i],r[i],i));
95         addedge();
96         rep(i,0,SZ(p)) p[i].y =n-p[i].y+1;
97         addedge();
98         rep(i,0,SZ(p)) {
99             int j =n-p[i].x+1;
100             p[i].x = p[i].y; p[i].y = j;
101         }
102         addedge();
103         rep(i,0,SZ(p)) p[i].x=n-p[i].x+1;
104         addedge();
105         sort(all(e));
106         rep(i,1,Q+1) ne[i].clear(),f[i]=i;
107         rep(i,0,SZ(e)) {
108             int j=e[i].s,k=e[i].t;
109             if (find(j)!=find(k)) f[f[j]]=f[k],ne[j].pb(k),ne[k].pb(j);
110         }

```

```

111     l0=l[1];r0=r[1];
112     init(l0,r0);
113     dfs(1,0);
114 }
115 }
116
117 int main() {
118     scanf("%d",&Mo::n);
119     for (int i=1;i<=Mo::n;i++) scanf("%d",a+i);
120     scanf("%d",&Mo::Q);
121     rep(i,1,Mo::Q+1) scanf("%d%d",&Mo::l[i],&Mo::r[i]);
122     Mo::solve();
123     rep(i,1,Mo::Q+1) printf("%d\n",Mo::ans[i]);
124 }

```

2.18 psegt.cpp

```

1 struct node {
2     node *l, *r;
3     ll val, sz, add;
4 };
5
6 void pull(node *u) {
7     u->sz = 0, u->val = 0;
8     if (u->l) u->sz += u->l->sz, u->val += u->l->val;
9     if (u->r) u->sz += u->r->sz, u->val += u->r->val;
10 }
11
12 void push(node *u) {
13     if (u->add) {
14         if (u->l) {
15             node *p = new node();
16             *p = *u->l;
17             u->l = p;
18             p->add += u->add;
19             p->val += p->sz * u->add;
20         }
21         if (u->r) {
22             node *p = new node();
23             *p = *u->r;
24             u->r = p;
25             p->add += u->add;
26             p->val += p->sz * u->add;

```

```

27     }
28     u->add = 0;
29 }
30 }
31
32 node *build(int l, int r) {
33     node *p = new node();
34     p->add = 0;
35     if (l == r) {
36         p->l = p->r = nullptr;
37         p->val = a[l];
38         p->sz = 1;
39     } else {
40         int mid = (l + r) >> 1;
41         p->l = build(l, mid);
42         p->r = build(mid + 1, r);
43         pull(p);
44     }
45     return p;
46 }
47
48 ll query(node *v, int l, int r, int ql, int qr) {
49     if (ql == l && qr == r) {
50         return v->val;
51     } else {
52         push(v);
53         int mid = (l + r) >> 1;
54         if (qr <= mid)
55             return query(v->l, l, mid, ql, qr);
56         else if (ql > mid)
57             return query(v->r, mid + 1, r, ql, qr);
58         else
59             return query(v->l, l, mid, ql, mid) + query(v->r,
60                 mid + 1, r, mid + 1, qr);
61     }
62 }
63
64 node *modify(node *v, int l, int r, int ql, int qr, ll x) {
65     if (ql == l && qr == r) {
66         node *p = new node();
67         *p = *v;
68         p->add += x;
69         p->val += p->sz * x;

```

```

69         return p;
70     } else {
71         push(v);
72         int mid = (l + r) >> 1;
73         node *p = new node();
74         *p = *v;
75         if (qr <= mid)
76             p->l = modify(v->l, l, mid, ql, qr, x);
77         else if (ql > mid)
78             p->r = modify(v->r, mid + 1, r, ql, qr, x);
79         else
80             p->l = modify(v->l, l, mid, ql, mid, x),
81                 p->r = modify(v->r, mid + 1, r, mid
82                             + 1, qr, x);
83         pull(p);
84         return p;
85     }
}

```

2.19 rollbackMo.cpp

```

1  int n, q, k, block;
2  int cnt[maxn], ans[maxn], a[maxn], vis[maxn];
3  vector<array<int, 4>> que;
4
5  int getb(int x) {
6      return (x - 1) / block + 1;
7  }
8
9  int main() {
10     std::ios::sync_with_stdio(false);
11     cin.tie(0); cout.tie(0);
12
13     cin >> n;
14     block = sqrt(n);
15
16     rep(i, 1, n) cin >> a[i];
17     cin >> q;
18     rep(i, 1, q) {
19         int l, r;
20         cin >> l >> r >> k;
21         que.pb({l, r, i, k});
22     }
}

```

```

23     sort(ALL(que), [&](array<int, 4> a, array<int, 4> b)->bool{
24         if (getb(a[0]) != getb(b[0]))
25             return getb(a[0]) < getb(b[0]);
26         else
27             return a[1] < b[1];
28     });
29
30     int len = que.size();
31     int l, r;
32     auto add = [&](int x, int t) {
33         cnt[vis[a[x]]]--;
34         vis[a[x]]++;
35         cnt[vis[a[x]]]++;
36     };
37     auto del = [&](int x) {
38         cnt[vis[a[x]]]--;
39         vis[a[x]]--;
40         cnt[vis[a[x]]]++;
41     };
42
43     for (int x = 0; x < len; x++) {
44         int y = x;
45         while (y < len && getb(que[y][0]) == getb(que[x][0])) y++;
46         //暴力块内
47         while (x < y && que[x][1] <= getb(que[x][0])*block) {
48             for (int j = que[x][0]; j <= que[x][1]; j++)
49                 add(j, que[x][3]);
50             ans[que[x][2]] = cnt[que[x][3]];
51             for (int j = que[x][0]; j <= que[x][1]; j++)
52                 del(j);
53             x++;
54         }
55         //块外
56         r = getb(que[x][0]) * block;
57         while (x < y) {
58             l = getb(que[x][0]) * block + 1;
59             while (r < que[x][1]) r++, add(r, que[x][3]);
60             while (l > que[x][0]) l--, add(l, que[x][3]);
61             ans[que[x][2]] = cnt[que[x][3]];
62             for (int j = que[x][0]; j <= getb(que[x][0])*block; j++)
63                 del(j);
64             x++;
65         }
}

```

```

66         for (int j = getb(que[x - 1][0]) * block + 1; j <= que[x - 1][1]; j
            ++)
```

```

67             del(j);
68     }
69     rep(i, 1, q) cout << ans[i] << '\n';
70 }
```

2.20 segtree.cpp

```

1 struct info {
2     ll sum;
3     int sz;
4     friend info operator+(const info &a, const info &b) {
5         return {(a.sum + b.sum) % mod, a.sz + b.sz};
6     }
7 };
8
9 struct tag {
10     ll add, mul;
11     friend tag operator+(const tag &a, const tag &b) {
12         tag res = {(a.add * b.mul + b.add) % mod, a.mul * b.mul %
13             mod};
14         return res;
15     }
16 };
17 info operator+(const info &a, const tag &b) {
18     return {(a.sum * b.mul + a.sz * b.add) % mod, a.sz};
19 }
20 struct node {
21     info val;
22     tag t;
23 } seg[maxn << 2];
24
25 void update(int id) {
26     seg[id].val = seg[id * 2].val + seg[id * 2 + 1].val;
27 }
28 void settag(int id, tag t) {
29     seg[id].val = seg[id].val + t;
30     seg[id].t = seg[id].t + t;
31 }
32 void pushdown(int id) {
33     if (seg[id].t.mul == 1 and seg[id].t.add == 0) return;
```

```

34     settag(id * 2, seg[id].t);
35     settag(id * 2 + 1, seg[id].t);
36     seg[id].t.mul = 1;
37     seg[id].t.add = 0;
38 }
39 void build(int l, int r, int id) {
40     seg[id].t = {0, 1};
41     if (l == r) {
42         seg[id].val = {a[l], 1};
43     } else {
44         int mid = (l + r) >> 1;
45         build(l, mid, id * 2);
46         build(mid + 1, r, id * 2 + 1);
47         update(id);
48     }
49 }
50 void change(int l, int r, int id, int ql, int qr, tag t) {
51     if (l == ql && r == qr) {
52         settag(id, t);
53     } else {
54         int mid = (l + r) >> 1;
55         pushdown(id);
56         if (qr <= mid) {
57             change(l, mid, id * 2, ql, qr, t);
58         } else if (ql > mid) {
59             change(mid + 1, r, id * 2 + 1, ql, qr, t);
60         } else {
61             change(l, mid, id * 2, ql, mid, t);
62             change(mid + 1, r, id * 2 + 1, mid + 1, qr, t);
63         }
64         update(id);
65     }
66 }
67 info query(int l, int r, int id, int ql, int qr) {
68     if (l == ql && r == qr) {
69         return seg[id].val;
70     } else {
71         int mid = (l + r) >> 1;
72         pushdown(id);
73         if (qr <= mid)
74             return query(l, mid, id * 2, ql, qr);
75         else if (ql > mid)
76             return query(mid + 1, r, id * 2 + 1, ql, qr);
```

```

77         else
78             return query(l, mid, id * 2, ql, mid) +
79                 query(mid + 1, r, id * 2 + 1, mid + 1, qr
80                     );
81     }
82 ll search(int l, int r, int id, int ql, int qr, int d) {
83     if (ql == l && qr == r) {
84         int mid = (l + r) / 2;
85         // if (l != r) pushdown(id); ...
86         if (seg[id].val < d)
87             return -1;
88         else {
89             if (l == r)
90                 return l;
91             else if (seg[id * 2].val >= d)
92                 return search(l, mid, id * 2, ql, mid, d);
93             else
94                 return search(mid + 1, r, id * 2 + 1, mid +
95                     1, qr, d);
96         }
97     } else {
98         int mid = (l + r) >> 1;
99         // pushdown(id); ...
100         if (qr <= mid)
101             return search(l, mid, id * 2, ql, qr, d);
102         else if (ql > mid)
103             return search(mid + 1, r, id * 2 + 1, ql, qr, d);
104         else {
105             int tmp = search(l, mid, id * 2, ql, mid, d);
106             if (tmp != -1)
107                 return tmp;
108             else
109                 return search(mid + 1, r, id * 2 + 1, mid +
110                     1, qr, d);
111         }
112     }
113 }

```

2.21 segtreefast.cpp

```

1 /**
2  * Author: Lucian Bicsi

```

```

3  * Description: Very fast and quick segment tree.
4  * Only useful for easy invariants. 0-indexed.
5  * Range queries are half-open.
6  */
7 #pragma once
8
9 struct SegmTree {
10     vector<int> T; int n;
11     SegmTree(int n) : T(2 * n, (int)2e9), n(n) {}
12
13     void Update(int pos, int val) {
14         for (T[pos += n] = val; pos > 1; pos /= 2)
15             T[pos / 2] = min(T[pos], T[pos ^ 1]);
16     }
17
18     int Query(int b, int e) {
19         int res = (int)2e9;
20         for (b += n, e += n; b < e; b /= 2, e /= 2) {
21             if (b % 2) res = min(res, T[b++]);
22             if (e % 2) res = min(res, T[--e]);
23         }
24         return res;
25     }
26 };

```

2.22 SparseTable.cpp

```

1 template <typename T, class F = function<T(const T&, const T&>>>
2 class SparseTable {
3 public:
4     int n;
5     vector<vector<T>> mat;
6     F func;
7
8     SparseTable(const vector<T>& a, const F& f) : func(f) {
9         n = static_cast<int>(a.size());
10        int max_log = 32 - __builtin_clz(n);
11        mat.resize(max_log);
12        mat[0] = a;
13        for (int j = 1; j < max_log; j++) {
14            mat[j].resize(n - (1 << j) + 1);
15            for (int i = 0; i <= n - (1 << j); i++) {
16                mat[j][i] = func(mat[j - 1][i], mat[j - 1][i

```

```
        + (1 << (j - 1))));
```

```
17         }
18     }
19 }
20
21 T get(int from, int to) const {
22     assert(0 <= from && from <= to && to <= n - 1);
23     int lg = 32 - __builtin_clz(to - from + 1) - 1;
24     return func(mat[lg][from], mat[lg][to - (1 << lg) + 1]);
25 }
26 };
```

2.23 SparseTable2D.cpp

```
1 // lg[1] = 0;
2 // rep(i, 2, N - 1) {
3 //     lg[i] = lg[i / 2] + 1;
4 // }
5 // int k = log2(r - l + 1); very slow!!!
6 // int k = __lg(r - l + 1);
7 // int k = lg[r - l + 1];
8 // int k = 32 - __builtin_clz(r - l + 1) - 1;
9 vector<vector<int>> sparse[12];
10
11 int query(int x, int y, int d) {
12     int k = __lg(d);
13     int s = d - bit(k);
14     return min({sparse[k][x][y], sparse[k][x + s][y], sparse[k][x][y + s]
15         ], sparse[k][x + s][y + s]});
16 }
17 void build() {
18     rep(i, 1, n) rep(j, 1, m) sparse[0][i][j] = mat[i][j];
19     rep(k, 1, 11) rep(i, 1, n) rep(j, 1, m) {
20         int d = bit(k - 1);
21         if (i + d > n || j + d > m) continue;
22         sparse[k][i][j] = min({sparse[k - 1][i][j], sparse[k - 1][i
23             + d][j], sparse[k - 1][i][j + d], sparse[k - 1][i + d][j
24             + d]});
25     }
26 }
```

2.24 treap.cpp

```
1 /**
2  *   author:   tourist
3  *   created:  07.10.2022 20:32:03
4  */
5 #include <bits/stdc++.h>
6
7 using namespace std;
8
9 #ifdef LOCAL
10 #include "algo/debug.h"
11 #else
12 #define debug(...) 42
13 #endif
14
15 mt19937_64 rng(chrono::steady_clock::now().time_since_epoch().count());
16
17 class node {
18 public:
19     int id;
20     node* l;
21     node* r;
22     node* p;
23     bool rev;
24     int sz;
25     // declare extra variables:
26     long long P;
27     long long add;
28     long long x;
29
30     node(int _id, long long _x) {
31         id = _id;
32         l = r = p = nullptr;
33         rev = false;
34         sz = 1;
35         // init extra variables:
36         P = rng();
37         add = 0;
38         x = _x;
39     }
40
41     // push everything else:
42     void push_stuff() {
```

```

43     if (add != 0) {
44         if (l != nullptr) {
45             l->unsafe_apply(add);
46         }
47         if (r != nullptr) {
48             r->unsafe_apply(add);
49         }
50         add = 0;
51     }
52 }
53
54 void unsafe_reverse() {
55     push_stuff();
56     rev ^= 1;
57     swap(l, r);
58     pull();
59 }
60
61 // apply changes:
62 void unsafe_apply(long long delta) {
63     add += delta;
64     x += delta;
65 }
66
67 void push() {
68     if (rev) {
69         if (l != nullptr) {
70             l->unsafe_reverse();
71         }
72         if (r != nullptr) {
73             r->unsafe_reverse();
74         }
75         rev = 0;
76     }
77     push_stuff();
78 }
79
80 void pull() {
81     sz = 1;
82     if (l != nullptr) {
83         l->p = this;
84         sz += l->sz;
85     }

```

```

86     if (r != nullptr) {
87         r->p = this;
88         sz += r->sz;
89     }
90 }
91 };
92
93 void debug_node(node* v, string pref = "") {
94 #ifdef LOCAL
95     if (v != nullptr) {
96         debug_node(v->r, pref + "┐");
97         cerr << pref << "-" << "┐" << v->id << '\n';
98         debug_node(v->l, pref + "┐");
99     } else {
100         cerr << pref << "-" << "┐" << "nullptr" << '\n';
101     }
102 #endif
103 }
104
105 namespace treap {
106
107 pair<node*, int> find(node* v, const function<int(node*)> &go_to) {
108     // go_to returns: 0 -- found; -1 -- go left; 1 -- go right
109     // find returns the last vertex on the descent and its go_to
110     if (v == nullptr) {
111         return {nullptr, 0};
112     }
113     int dir;
114     while (true) {
115         v->push();
116         dir = go_to(v);
117         if (dir == 0) {
118             break;
119         }
120         node* u = (dir == -1 ? v->l : v->r);
121         if (u == nullptr) {
122             break;
123         }
124         v = u;
125     }
126     return {v, dir};
127 }
128

```



```

129 node* get_leftmost(node* v) {
130     return find(v, [&](node*) { return -1; }).first;
131 }
132
133 node* get_rightmost(node* v) {
134     return find(v, [&](node*) { return 1; }).first;
135 }
136
137 node* get_kth(node* v, int k) { // 0-indexed
138     pair<node*, int> p = find(v, [&](node * u) {
139         if (u->l != nullptr) {
140             if (u->l->sz > k) {
141                 return -1;
142             }
143             k -= u->l->sz;
144         }
145         if (k == 0) {
146             return 0;
147         }
148         k--;
149         return 1;
150     });
151     return (p.second == 0 ? p.first : nullptr);
152 }
153
154 int get_pos(node* v) { // 0-indexed
155     int k = (v->l != nullptr ? v->l->sz : 0);
156     while (v->p != nullptr) {
157         if (v == v->p->r) {
158             k++;
159             if (v->p->l != nullptr) {
160                 k += v->p->l->sz;
161             }
162         }
163         v = v->p;
164     }
165     return k;
166 }
167
168 node* get_root(node* v) {
169     while (v->p != nullptr) {
170         v = v->p;
171     }

```

```

172     return v;
173 }
174
175 pair<node*, node*> split(node* v, const function<bool(node*)> &is_right) {
176     if (v == nullptr) {
177         return {nullptr, nullptr};
178     }
179     v->push();
180     if (is_right(v)) {
181         pair<node*, node*> p = split(v->l, is_right);
182         if (p.first != nullptr) {
183             p.first->p = nullptr;
184         }
185         v->l = p.second;
186         v->pull();
187         return {p.first, v};
188     } else {
189         pair<node*, node*> p = split(v->r, is_right);
190         v->r = p.first;
191         if (p.second != nullptr) {
192             p.second->p = nullptr;
193         }
194         v->pull();
195         return {v, p.second};
196     }
197 }
198
199 pair<node*, node*> split_cnt(node* v, int k) {
200     if (v == nullptr) {
201         return {nullptr, nullptr};
202     }
203     v->push();
204     int left_and_me = (v->l != nullptr ? v->l->sz : 0) + 1;
205     if (k < left_and_me) {
206         pair<node*, node*> p = split_cnt(v->l, k);
207         if (p.first != nullptr) {
208             p.first->p = nullptr;
209         }
210         v->l = p.second;
211         v->pull();
212         return {p.first, v};
213     } else {
214         pair<node*, node*> p = split_cnt(v->r, k - left_and_me);

```

```

215     v->r = p.first;
216     if (p.second != nullptr) {
217         p.second->p = nullptr;
218     }
219     v->pull();
220     return {v, p.second};
221 }
222 }
223
224 node* merge(node* v, node* u) {
225     if (v == nullptr) {
226         return u;
227     }
228     if (u == nullptr) {
229         return v;
230     }
231     if (v->P > u->P) {
232         // if (rng() % (v->sz + u->sz) < (unsigned int) v->sz) {
233         v->push();
234         v->r = merge(v->r, u);
235         v->pull();
236         return v;
237     } else {
238         u->push();
239         u->l = merge(v, u->l);
240         u->pull();
241         return u;
242     }
243 }
244
245 int count_left(node* v, const function<bool(node*)> &is_right) {
246     if (v == nullptr) {
247         return 0;
248     }
249     v->push();
250     if (is_right(v)) {
251         return count_left(v->l, is_right);
252     }
253     return (v->l != nullptr ? v->l->sz : 0) + 1 + count_left(v->r, is_right);
254 }
255
256 int count_less(node* v, long long val) {
257     int res = 0;

```

```

258     while (v != nullptr) {
259         v->push();
260         if (v->x >= val) {
261             v = v->l;
262         } else {
263             res += (v->l != nullptr ? v->l->sz : 0) + 1;
264             v = v->r;
265         }
266     }
267     return res;
268 }
269
270 node* add(node* r, node* v, const function<bool(node*)> &go_left) {
271     pair<node*, node*> p = split(r, go_left);
272     return merge(p.first, merge(v, p.second));
273 }
274
275 node* remove(node* v) { // returns the new root
276     v->push();
277     node* x = v->l;
278     node* y = v->r;
279     node* p = v->p;
280     v->l = v->r = v->p = nullptr;
281     v->push();
282     v->pull(); // now v might be reusable...
283     node* z = merge(x, y);
284     if (p == nullptr) {
285         if (z != nullptr) {
286             z->p = nullptr;
287         }
288         return z;
289     }
290     if (p->l == v) {
291         p->l = z;
292     }
293     if (p->r == v) {
294         p->r = z;
295     }
296     while (true) {
297         p->push();
298         p->pull();
299         if (p->p == nullptr) {
300             break;

```

```

301     }
302     p = p->p;
303 }
304 return p;
305 }
306
307 node* next(node* v) {
308     if (v->r == nullptr) {
309         while (v->p != nullptr && v->p->r == v) {
310             v = v->p;
311         }
312         return v->p;
313     }
314     v->push();
315     v = v->r;
316     while (v->l != nullptr) {
317         v->push();
318         v = v->l;
319     }
320     return v;
321 }
322
323 node* prev(node* v) {
324     if (v->l == nullptr) {
325         while (v->p != nullptr && v->p->l == v) {
326             v = v->p;
327         }
328         return v->p;
329     }
330     v->push();
331     v = v->l;
332     while (v->r != nullptr) {
333         v->push();
334         v = v->r;
335     }
336     return v;
337 }
338
339 int get_size(node* v) {
340     return (v != nullptr ? v->sz : 0);
341 }
342
343 template<typename... T>

```

```

344 void Apply(node* v, T... args) {
345     v->unsafe_apply(args...);
346 }
347
348 void reverse(node* v) {
349     v->unsafe_reverse();
350 }
351
352 // extra of mine
353 long long lower(node* u, long long x) {
354     if (u == nullptr)
355         return numeric_limits<long long>::min();
356     else if (x <= u->x)
357         return lower(u->l, x);
358     else
359         return max(u->x, lower(u->r, x));
360 }
361
362 long long upper(node* u, long long x) {
363     if (u == nullptr)
364         return numeric_limits<long long>::max();
365     else if (u->x <= x)
366         return upper(u->r, x);
367     else
368         return min(u->x, upper(u->l, x));
369 }
370
371 } // namespace treap
372
373 using namespace treap;
374
375 int n;
376
377 int main() {
378     ios::sync_with_stdio(false);
379     cin.tie(0);
380     node* root = nullptr;
381     cin >> n;
382     for (int i = 1; i <= n; i++) {
383         int op;
384         long long x;
385         cin >> op >> x;
386         switch (op) {

```

```

387     case 1: {
388         root = add(root, new node(x, x), [&](node * u) {
389             return x < u->x;
390         });
391         break;
392     }
393     case 2: {
394         auto [pt, w] = find(root, [&](node * u) {
395             if (x < u->x) return -1;
396             else if (x == u->x) return 0;
397             else return 1;
398         });
399         assert(w == 0);
400         root = remove(pt);
401         break;
402     }
403     case 3: {
404         cout << count_less(root, x) + 1 << '\n';
405         break;
406     }
407     case 4: {
408         cout << get_kth(root, x - 1)->x << '\n';
409         break;
410     }
411     case 5: {
412         cout << lower(root, x) << '\n';
413         break;
414     }
415     case 6: {
416         cout << upper(root, x) << '\n';
417         break;
418     }
419 }
420 }
421 }

```

2.25 UnionFindRollback.cpp

```

1 vector<int> fa(n);
2 iota(all(fa), 0);
3 vector<int> sz(n, 1);
4 vector<pair<int, int>> ops;
5

```

```

6 auto Get = [&](int i) {
7     while (i != fa[i]) {
8         i = fa[i];
9     }
10    return i;
11 };
12 auto Unite = [&](int i, int j) {
13     i = Get(i), j = Get(j);
14     if (i == j) {
15         return;
16     }
17     if (sz[i] > sz[j]) {
18         swap(i, j);
19     }
20     ops.emplace_back(i, fa[i]);
21     fa[i] = j;
22     ops.emplace_back(~j, sz[j]);
23     sz[j] += sz[i];
24 };
25 auto RollBack = [&](int T) {
26     while (SZ(ops) > T) {
27         auto [i, j] = ops.back();
28         ops.pop_back();
29         if (i >= 0) {
30             fa[i] = j;
31         } else {
32             sz[~i] = j;
33         }
34     }
35 };
36
37 ll ans = 0;
38 auto Dfs = [&](auto &&Dfs, int l, int r) -> void {
39     if (l == r) {
40         for (auto [x, y] : g[l]) {
41             x = Get(x);
42             y = Get(y);
43             ans += 1ll * sz[x] * sz[y];
44         }
45     } else {
46         int mid = midpoint(l, r);
47         {
48             int save = SZ(ops);

```

```

49         for (int i = mid + 1; i <= r; i++) {
50             for (auto [x, y] : g[i]) {
51                 Unite(x, y);
52             }
53         }
54         Dfs(Dfs, l, mid);
55         RollBack(save);
56     }
57     {
58         int save = SZ(ops);
59         for (int i = 1; i <= mid; i++) {
60             for (auto [x, y] : g[i]) {
61                 Unite(x, y);
62             }
63         }
64         Dfs(Dfs, mid + 1, r);
65         RollBack(save);
66     }
67 }
68 };
69 Dfs(Dfs, 0, n - 1);

```

2.26 树哈希.cpp

```

1  basic_string<int> e[maxn];
2  ull hashv[maxn];
3  ull seed1, seed2, seed3, seed4;
4
5  ull f(ull x) { return x * x * x * seed1 + x * seed2; }
6  ull h(ull x) { return f(x) ^ ((x & seed3) >> 31) ^ ((x & seed4) << 31); }
7
8  void dfs1(int u, int fa) {
9      hashv[u] = 1;
10     for (auto v : e[u]) if (v != fa) {
11         dfs1(v, u);
12         hashv[u] += h(hashv[v]);
13     }
14 }
15
16 void dfs2(int u, int fa, ull fv) {
17     // for each root
18     hashv[u] += fv;
19     for (auto v : e[u]) if (v != fa) {

```

```

20         dfs2(v, u, h(hashv[u] - h(hashv[v])));
21     }
22 }
23
24 void solve() {
25     seed1 = rng(), seed2 = rng();
26     seed3 = rng(), seed4 = rng();
27     cin >> n;
28     rep(i, 2, n) {
29         int u, v;
30         cin >> u >> v;
31         e[u].pb(v);
32         e[v].pb(u);
33     }
34     dfs1(1, 0);
35     sort(hashv + 1, hashv + n + 1);
36     n = unique(hashv + 1, hashv + n + 1) - hashv - 1;
37     cout << n << '\n';
38 }

```

2.27 树链剖分 segtree.cpp

```

1  int n, m, a[N];
2  vector<int> e[N];
3  int l[N], r[N], idx[N];
4  int sz[N], hs[N], tot, top[N], dep[N], fa[N];
5
6  struct info {
7      int maxv, sum;
8  };
9
10 info operator + (const info &l, const info &r) {
11     return (info){max(l.maxv, r.maxv), l.sum + r.sum};
12 }
13
14 struct node {
15     info val;
16 } seg[N * 4];
17
18 // [l, r]
19
20 void update(int id) {
21     seg[id].val = seg[id * 2].val + seg[id * 2 + 1].val;

```

```

22 }
23
24 void build(int id, int l, int r) {
25     if (l == r) {
26         // l号点, DFS序中第l个点
27         seg[id].val = {a[idx[l]], a[idx[l]]};
28     } else {
29         int mid = (l + r) / 2;
30         build(id * 2, l, mid);
31         build(id * 2 + 1, mid + 1, r);
32         update(id);
33     }
34 }
35
36 void change(int id, int l, int r, int pos, int val) {
37     if (l == r) {
38         seg[id].val = {val, val};
39     } else {
40         int mid = (l + r) / 2;
41         if (pos <= mid) change(id * 2, l, mid, pos, val);
42         else change(id * 2 + 1, mid + 1, r, pos, val);
43         update(id);
44     }
45 }
46
47 info query(int id, int l, int r, int ql, int qr) {
48     if (l == ql && r == qr) return seg[id].val;
49     int mid = (l + r) / 2;
50     if (qr <= mid) return query(id * 2, l, mid, ql, qr);
51     else if (ql > mid) return query(id * 2 + 1, mid + 1, r, ql, qr);
52     else {
53         return query(id * 2, l, mid, ql, mid) +
54             query(id * 2 + 1, mid + 1, r, mid + 1, qr);
55     }
56 }
57
58 // 第一遍DFS, 子树大小, 重儿子, 父亲, 深度
59 void dfs1(int u, int f) {
60     sz[u] = 1;
61     hs[u] = -1;
62     fa[u] = f;
63     dep[u] = dep[f] + 1;
64     for (auto v : e[u]) {

```

```

65         if (v == f) continue;
66         dfs1(v, u);
67         sz[u] += sz[v];
68         if (hs[u] == -1 || sz[v] > sz[hs[u]])
69             hs[u] = v;
70     }
71 }
72
73 // 第二遍DFS, 每个点DFS序, 重链上的链头的元素。
74 void dfs2(int u, int t) {
75     top[u] = t;
76     l[u] = ++tot;
77     idx[tot] = u;
78     if (hs[u] != -1) {
79         dfs2(hs[u], t);
80     }
81     for (auto v : e[u]) {
82         if (v != fa[u] && v != hs[u]) {
83             dfs2(v, v);
84         }
85     }
86     r[u] = tot;
87 }
88
89 int LCA(int u, int v) {
90     while (top[u] != top[v]) {
91         if (dep[top[u]] < dep[top[v]]) v = fa[top[v]];
92         else u = fa[top[u]];
93     }
94     if (dep[u] < dep[v]) return u;
95     else return v;
96 }
97
98 info query(int u, int v) {
99     info ans{(int)-1e9, 0};
100     while (top[u] != top[v]) {
101         if (dep[top[u]] < dep[top[v]]) {
102             ans = ans + query(1, 1, n, l[top[v]], l[v]);
103             v = fa[top[v]];
104         } else {
105             ans = ans + query(1, 1, n, l[top[u]], l[u]);
106             u = fa[top[u]];
107         }

```

```

108     }
109     if (dep[u] <= dep[v]) ans = ans + query(1, 1, n, l[u], l[v]);
110     else ans = ans + query(1, 1, n, l[v], l[u]);
111     return ans;
112 }

```

2.28 笛卡尔树.cpp

```

1  int a[maxn], l[maxn], r[maxn], root;
2  int ans[maxn], tot;
3
4  void build() {
5      stack<int> stk;
6      for (int i = 1; i <= n; i++) {
7          int last = 0;
8          while (!stk.empty() && a[stk.top()] > a[i]) {
9              last = stk.top();
10             stk.pop();
11         }
12         if (stk.empty())
13             root = i;
14         else
15             r[stk.top()] = i;
16         l[i] = last;
17         stk.push(i);
18     }
19 }
20
21 void dfs(int c, int L, int R) {
22     ans[c] = ++tot;
23     if (l[c]) dfs(l[c], L, c - 1);
24     if (r[c]) dfs(r[c], c + 1, R);
25 }

```

2.29 线段树合并.cpp

```

1  struct node {
2      int sz, sum;
3      node *l, *r;
4      node() : sz(0), sum(0), l(nullptr), r(nullptr) {}
5  } pool[N * 20], *cur = pool;
6
7  node *newnode() {

```

```

8      return cur++;
9  }
10
11 void upd(node *rt) {
12     if (not rt) return;
13     rt->sum = rt->sz > 0;
14     if (rt->l) rt->sum += rt->l->sum;
15     if (rt->r) rt->sum += rt->r->sum;
16 }
17
18 node *modify(node *rt, int l, int r, int pos, int d) {
19     if (not rt) rt = newnode();
20     if (l == r) {
21         rt->sz += d;
22         upd(rt);
23         return rt;
24     } else {
25         int md = (l + r) >> 1;
26         if (pos <= md)
27             rt->l = modify(rt->l, l, md, pos, d);
28         else
29             rt->r = modify(rt->r, md + 1, r, pos, d);
30         upd(rt);
31         return rt;
32     }
33 }
34
35 node *merge(node *u, node *v, int l, int r) {
36     if (not u) return v;
37     if (not v) return u;
38     if (l == r) {
39         u->sz += v->sz;
40         upd(u);
41         return u;
42     } else {
43         int md = (l + r) >> 1;
44         u->l = merge(u->l, v->l, l, md);
45         u->r = merge(u->r, v->r, md + 1, r);
46         upd(u);
47         return u;
48     }
49 }
50

```

```

51 ll query(node *rt, int l, int r) {
52     if (not rt) return 0;
53     return rt->sum;
54 }
55
56 pair<node *, node *> split(node *rt, int l, int r, int ql, int qr) {
57     if (not rt) return {nullptr, nullptr};
58     if (ql == l && qr == r) {
59         return {nullptr, rt};
60     } else {
61         int md = (l + r) >> 1;
62         if (qr <= md) {
63             auto [p1, p2] = split(rt->l, l, md, ql, qr);
64             rt->l = p1;
65             upd(rt);
66             if (not p2) return {rt, nullptr};
67             node *u = newnode();
68             u->l = p2;
69             upd(u);
70             return {rt, u};
71         } else if (ql > md) {
72             auto [p1, p2] = split(rt->r, md + 1, r, ql, qr);
73             rt->r = p1;
74             upd(rt);
75             if (not p2) return {rt, nullptr};
76             node *u = newnode();
77             u->r = p2;
78             upd(u);
79             return {rt, u};
80         } else {
81             auto [p1, p2] = split(rt->l, l, md, ql, md);
82             auto [p3, p4] = split(rt->r, md + 1, r, md + 1, qr);
83             rt->l = p1, rt->r = p3;
84             upd(rt);
85             if (not p2 and not p4) return {rt, nullptr};
86             node *u = newnode();
87             u->l = p2, u->r = p4;
88             upd(u);
89             return {rt, u};
90         }
91     }
92 }

```

3 DP

3.1 Convex hull optimization.cpp

```

1  array<ll, 3> a[maxn];
2  int q[maxn];
3  ll ans[maxn];
4
5  ll X(int p) {
6      return 2ll * a[p][0];
7  }
8  ll Y(int p) {
9      return a[p][0] * a[p][0] + a[p][1];
10 }
11 ldb slope(int x, int y) {
12     return (ldb)(Y(y) - Y(x)) / (X(y) - X(x));
13 }
14 void solve() {
15     cin >> n;
16     int head = 1, rear = 0;
17     rep(i, 1, n) {
18         cin >> a[i][0] >> a[i][1];
19         a[i][2] = i;
20     }
21     sort(a + 1, a + n + 1);
22
23     rep(i, 1, n) {
24         while (head < rear && slope(q[rear], i) <= slope(q[rear], q[rear -
25             1])) rear--;
26         q[++rear] = i;
27     }
28     rep(i, 1, n) {
29         ll k = -a[i][0];
30         while (head < rear && slope(q[head], q[head + 1]) <= k) head++;
31         ans[a[i][2]] = (a[i][0] + a[q[head]][0]) * (a[i][0] + a[q[head]][0])
32             + a[i][1] + a[q[head]][1];
33     }
34     rep(i, 1, n) cout << ans[i] << '\n';
35 }

```

3.2 DivideAndConquerDP.cpp

```

1  ll w[N][N], sum[N][N], opt[N], dp[805][N];

```



```

2
3 ll calc(int i,int j) { return sum[j][j]-sum[j][i]-sum[i][j]+sum[i][i]; }
4
5 void rec(int d,int l,int r,int optl,int optr) {
6     if (l>r) return;
7     int md=(l+r)>>1;
8     rep(i,optl,optr) if (dp[d-1][i]+calc(i,md)<dp[d][md]) {
9         dp[d][md]=dp[d-1][i]+calc(i,md);
10        opt[md]=i;
11    }
12    rec(d,l,md-1,optl,opt[md]);
13    rec(d,md+1,r,opt[md],optr);
14 }

```

3.3 有依赖决策单调.cpp

```

1 pair<int, int> stk[N];
2 auto calc = [&](int i, int j) { ... } // dp[j] -> dp[i]
3 int h = 0, t = 0;
4 stk[t++] = {1, 0}; // {left, opt}
5
6 for (int i = 1; i <= n; i++) {
7     if (h < t && stk[h].first < i) stk[h].first++;
8     if (h + 1 < t && stk[h].first >= stk[h + 1].first) ++h;
9     dp[i] = calc(i, stk[h].second);
10    while (h < t && calc(stk[t - 1].first, stk[t - 1].second) >= calc(stk[t
        - 1].first, i))
11        --t;
12    if (h < t) {
13        int l = stk[t - 1].first, r = n + 1;
14        while (l + 1 < r) {
15            int md = (l + r) >> 1;
16            if (calc(md, stk[t - 1].second) < calc(md, i)) l = md; else r =
                md;
17        }
18        if (r <= n) stk[t++] = {r, i};
19    } else stk[t++] = {i, i};
20 }

```

4 Geometry

4.1 1 (1).cpp

```

1 typedef double db;
2 const db EPS = 1e-9;
3
4 inline int sign(db a) { return a < -EPS ? -1 : a > EPS; }
5
6 inline int cmp(db a, db b) { return sign(a - b); }
7
8 struct P {
9     db x, y;
10    P() {}
11    P(db _x, db _y) : x(_x), y(_y) {}
12    P operator+(P p) { return {x + p.x, y + p.y}; }
13    P operator-(P p) { return {x - p.x, y - p.y}; }
14    P operator*(db d) { return {x * d, y * d}; }
15    P operator/(db d) { return {x / d, y / d}; }
16
17    bool operator<(P p) const {
18        int c = cmp(x, p.x);
19        if (c) return c == -1;
20        return cmp(y, p.y) == -1;
21    }
22
23    bool operator==(P o) const {
24        return cmp(x, o.x) == 0 && cmp(y, o.y) == 0;
25    }
26
27    db dot(P p) { return x * p.x + y * p.y; }
28    db det(P p) { return x * p.y - y * p.x; }
29
30    db distTo(P p) { return (*this - p).abs(); }
31    db alpha() { return atan2(y, x); }
32    void read() { cin >> x >> y; }
33    void write() { cout << "(" << x << ", " << y << ")" << endl; }
34    db abs() { return sqrt(abs2()); }
35    db abs2() { return x * x + y * y; }
36    P rot90() { return P(-y, x); }
37    P unit() { return *this / abs(); }
38    int quad() const { return sign(y) == 1 || (sign(y) == 0 && sign(x)
        >= 0); }

```

```

39     P rot(db an) { return {x * cos(an) - y * sin(an), x * sin(an) + y *
40         cos(an)}; }
41 };
42 #define cross(p1,p2,p3) ((p2.x-p1.x)*(p3.y-p1.y)-(p3.x-p1.x)*(p2.y-p1.y))
43 #define crossOp(p1,p2,p3) sign(cross(p1,p2,p3))
44
45 // 直线  $p1p2$ ,  $q1q2$  是否恰有一个交点
46 bool chkLL(P p1, P p2, P q1, P q2) {
47     db a1 = cross(q1, q2, p1), a2 = -cross(q1, q2, p2);
48     return sign(a1 + a2) != 0;
49 }
50
51 // 求直线  $p1p2$ ,  $q1q2$  的交点
52 P isLL(P p1, P p2, P q1, P q2) {
53     db a1 = cross(q1, q2, p1), a2 = -cross(q1, q2, p2);
54     return (p1 * a2 + p2 * a1) / (a1 + a2);
55 }
56
57 // 判断区间  $[l1, r1]$ ,  $[l2, r2]$  是否相交
58 bool intersect(db l1, db r1, db l2, db r2) {
59     if (l1 > r1) swap(l1, r1); if (l2 > r2) swap(l2, r2);
60     return !( cmp(r1, l2) == -1 || cmp(r2, l1) == -1 );
61 }
62
63 // 线段  $p1p2$ ,  $q1q2$  相交
64 bool isSS(P p1, P p2, P q1, P q2) {
65     return intersect(p1.x, p2.x, q1.x, q2.x) && intersect(p1.y, p2.y, q1
        .y, q2.y) &&
66         crossOp(p1, p2, q1) * crossOp(p1, p2, q2) <= 0 && crossOp(q1,
            q2, p1)
67         * crossOp(q1, q2, p2) <= 0;
68 }
69
70 // 线段  $p1p2$ ,  $q1q2$  严格相交
71 bool isSS_strict(P p1, P p2, P q1, P q2) {
72     return crossOp(p1, p2, q1) * crossOp(p1, p2, q2) < 0 && crossOp(q1,
        q2, p1)
73     * crossOp(q1, q2, p2) < 0;
74 }
75
76 //  $m$  在  $a$  和  $b$  之间
77 bool isMiddle(db a, db m, db b) {

```

```

78     /*if (a > b) swap(a, b);
79     return cmp(a, m) <= 0 && cmp(m, b) <= 0;*/
80     return sign(a - m) == 0 || sign(b - m) == 0 || (a < m != b < m);
81 }
82
83 bool isMiddle(P a, P m, P b) {
84     return isMiddle(a.x, m.x, b.x) && isMiddle(a.y, m.y, b.y);
85 }
86
87 // 点  $p$  在线段  $p1p2$  上
88 bool onSeg(P p1, P p2, P q) {
89     return crossOp(p1, p2, q) == 0 && isMiddle(p1, q, p2);
90 }
91 //  $q1q2$  和  $p1p2$  的交点 在  $p1p2$  上?
92
93 // 点  $p$  严格在  $p1p2$  上
94 bool onSeg_strict(P p1, P p2, P q) {
95     return crossOp(p1, p2, q) == 0 && sign((q - p1).dot(p1 - p2)) * sign
        ((q - p2).dot(p1 - p2)) < 0;
96 }
97
98 // 求  $q$  到 直线 $p1p2$  的投影 (垂足)      :  $p1 \neq p2$ 
99 P proj(P p1, P p2, P q) {
100     P dir = p2 - p1;
101     return p1 + dir * (dir.dot(q - p1) / dir.abs2());
102 }
103
104 // 求  $q$  以 直线 $p1p2$  为轴的反射
105 P reflect(P p1, P p2, P q) {
106     return proj(p1, p2, q) * 2 - q;
107 }
108
109 // 求  $q$  到 线段 $p1p2$  的最小距离
110 db nearest(P p1, P p2, P q) {
111     if (p1 == p2) return p1.distTo(q);
112     P h = proj(p1, p2, q);
113     if (isMiddle(p1, h, p2))
114         return q.distTo(h);
115     return min(p1.distTo(q), p2.distTo(q));
116 }
117
118 // 求 线段 $p1p2$  与 线段 $q1q2$  的距离
119 db disSS(P p1, P p2, P q1, P q2) {

```

```

120         if (isSS(p1, p2, q1, q2)) return 0;
121         return min(min(nearest(p1, p2, q1), nearest(p1, p2, q2)), min(
            nearest(q1, q2, p1), nearest(q1, q2, p2)));
122     }
123
124     // 极角排序
125     sort(p, p + n, [&](P a, P b) {
126         int qa = a.quad(), qb = b.quad();
127         if (qa != qb) return qa < qb;
128         else return sign(a.det(b)) > 0;
129     });

```

4.2 1 (2).cpp

```

1  db area(vector<P> ps){
2      db ret = 0; rep(i,0,ps.size()) ret += ps[i].det(ps[(i+1)%ps.size()])
        ;
3      return ret/2;
4  }
5
6  int contain(vector<P> ps, P p){ //2:inside,1:on_seg,0:outside
7      int n = ps.size(), ret = 0;
8      rep(i,0,n){
9          P u=ps[i],v=ps[(i+1)%n];
10         if(onSeg(u,v,p)) return 1;
11         if(cmp(u.y,v.y)<=0) swap(u,v);
12         if(cmp(p.y,u.y) > 0 || cmp(p.y,v.y) <= 0) continue;
13         ret ^= crossOp(p,u,v) > 0;
14     }
15     return ret*2;
16 }
17
18 vector<P> convexHull(vector<P> ps) {
19     int n = ps.size(); if(n <= 1) return ps;
20     sort(ps.begin(), ps.end());
21     vector<P> qs(n * 2); int k = 0;
22     for (int i = 0; i < n; qs[k++] = ps[i++])
23         while (k > 1 && crossOp(qs[k - 2], qs[k - 1], ps[i]) <= 0)
24             --k;
25     for (int i = n - 2, t = k; i >= 0; qs[k++] = ps[i--])
26         while (k > t && crossOp(qs[k - 2], qs[k - 1], ps[i]) <= 0)
27             --k;
28     qs.resize(k - 1);

```

```

27     return qs;
28 }
29
30 vector<P> convexHullNonStrict(vector<P> ps) {
31     //caution: need to unique the Ps first
32     int n = ps.size(); if(n <= 1) return ps;
33     sort(ps.begin(), ps.end());
34     vector<P> qs(n * 2); int k = 0;
35     for (int i = 0; i < n; qs[k++] = ps[i++])
36         while (k > 1 && crossOp(qs[k - 2], qs[k - 1], ps[i]) < 0) --
37             k;
38     for (int i = n - 2, t = k; i >= 0; qs[k++] = ps[i--])
39         while (k > t && crossOp(qs[k - 2], qs[k - 1], ps[i]) < 0) --
40             k;
41     qs.resize(k - 1);
42     return qs;
43 }
44
45 db convexDiameter(vector<P> ps){
46     int n = ps.size(); if(n <= 1) return 0;
47     int is = 0, js = 0; rep(k,1,n) is = ps[k]<ps[is]?k:is, js = ps[js] <
48         ps[k]?k:js;
49     int i = is, j = js;
50     db ret = ps[i].distTo(ps[j]);
51     do{
52         if((ps[(i+1)%n]-ps[i]).det(ps[(j+1)%n]-ps[j]) >= 0)
53             (++j)%=n;
54         else
55             (++i)%=n;
56         ret = max(ret,ps[i].distTo(ps[j]));
57     }while(i!=is || j!=js);
58     return ret;
59 }
60
61 vector<P> convexCut(const vector<P>&ps, P q1, P q2) {
62     vector<P> qs;
63     int n = ps.size();
64     rep(i,0,n){
65         P p1 = ps[i], p2 = ps[(i+1)%n];
66         int d1 = crossOp(q1,q2,p1), d2 = crossOp(q1,q2,p2);
67         if(d1 >= 0) qs.push_back(p1);
68         if(d1 * d2 < 0) qs.push_back(isLL(p1,p2,q1,q2));
69     }

```

```

67     return qs;
68 }
69
70 void reorderPolygon(vector<P> &ps) {
71     size_t pos = 0;
72     for(size_t i = 1; i < ps.size(); i++){
73         if(ps[i].y < ps[pos].y || (ps[i].y == ps[pos].y && ps[i].x < ps[pos].x))
74             pos = i;
75     }
76     rotate(ps.begin(), ps.begin() + pos, ps.end());
77 }
78
79 vector<P> minkowski(vector<P> p, vector<P> q){
80     if(p.empty()) return q;
81     // the first vertex must be the lowest
82     reorderPolygon(p);
83     reorderPolygon(q);
84     // must ensure cyclic indexing
85     p.push_back(p[0]);
86     p.push_back(p[1]);
87     q.push_back(q[0]);
88     q.push_back(q[1]);
89     // main part
90     vector<P> result;
91     size_t i = 0, j = 0;
92     while(i < p.size() - 2 || j < q.size() - 2){
93         result.push_back(p[i] + q[j]);
94         auto cross = (p[i + 1] - p[i]).det(q[j + 1] - q[j]);
95         if(cross >= 0 && i < SZ(p) - 2)
96             ++i;
97         if(cross <= 0 && j < SZ(q) - 2)
98             ++j;
99     }
100     return result;
101 }
102
103 bool convexContain(const vector<P> &l, P p, bool strict = true) {
104     int a = 1, b = l.size() - 1, r = !strict;
105     if (l.size() < 3) return r && onSeg(l[0], l.back(), p);
106     if (crossOp(l[0], l[a], l[b]) > 0) swap(a, b);
107     if (crossOp(l[0], l[a], p) >= r || crossOp(l[0], l[b], p) <= -r)
108         return false;

```

```

109     while (abs(a - b) > 1) {
110         int c = (a + b) / 2;
111         (crossOp(l[0], l[c], p) > 0 ? b : a) = c;
112     }
113     return sign(cross(l[a], l[b], p)) < r;
114 }

```

4.3 1 (3).cpp

```

1  int type(P o1,db r1,P o2,db r2){
2      db d = o1.distTo(o2);
3      if(cmp(d,r1+r2) == 1) return 4;
4      if(cmp(d,r1+r2) == 0) return 3;
5      if(cmp(d,abs(r1-r2)) == 1) return 2;
6      if(cmp(d,abs(r1-r2)) == 0) return 1;
7      return 0;
8  }
9
10 vector<P> isCL(P o,db r,P p1,P p2){
11     if (cmp(abs((o-p1).det(p2-p1)/p1.distTo(p2)),r)>0) return {};
12     db x = (p1-o).dot(p2-p1), y = (p2-p1).abs2(), d = x * x - y * ((p1-o).abs2() - r*r);
13     d = max(d,(db)0.0); P m = p1 - (p2-p1)*(x/y), dr = (p2-p1)*(sqrt(d)/y);
14     return {m-dr,m+dr}; //along dir: p1->p2
15 }
16
17 vector<P> isCC(P o1, db r1, P o2, db r2) { //need to check whether two
    circles are the same
18     db d = o1.distTo(o2);
19     if (cmp(d, r1 + r2) == 1) return {};
20     if (cmp(d,abs(r1-r2))==-1) return {};
21     d = min(d, r1 + r2);
22     db y = (r1 * r1 + d * d - r2 * r2) / (2 * d), x = sqrt(r1 * r1 - y * y);
23     P dr = (o2 - o1).unit();
24     P q1 = o1 + dr * y, q2 = dr.rot90() * x;
25     return {q1-q2,q1+q2}; //along circle 1
26 }
27
28 // extanCC, intanCC : -r2, tanCP : r2 = 0
29 vector<pair<P, P>> tanCC(P o1, db r1, P o2, db r2) {
30     P d = o2 - o1;

```

```

31     db dr = r1 - r2, d2 = d.abs2(), h2 = d2 - dr * dr;
32     if (sign(d2) == 0 || sign(h2) < 0) return {};
33     h2 = max((db)0.0, h2);
34     vector<pair<P, P>> ret;
35     for (db sign : {-1, 1}) {
36         P v = (d * dr + d.rot90() * sqrt(h2) * sign) / d2;
37         ret.push_back({o1 + v * r1, o2 + v * r2});
38     }
39     if (sign(h2) == 0) ret.pop_back();
40     return ret;
41 }
42
43 db rad(P p1, P p2){
44     return atan2l(p1.det(p2), p1.dot(p2));
45 }
46
47 db areaCT(db r, P p1, P p2){
48     vector<P> is = isCL(P(0,0), r, p1, p2);
49     if(is.empty()) return r*r*rad(p1, p2)/2;
50     bool b1 = cmp(p1.abs2(), r*r) == 1, b2 = cmp(p2.abs2(), r*r) == 1;
51     if(b1 && b2){
52         P md=(is[0]+is[1])/2;
53         if(sign((p1-md).dot(p2-md)) <= 0)
54             return r*r*(rad(p1, is[0]) + rad(is[1], p2))/2 + is
55                 [0].det(is[1])/2;
56         else return r*r*rad(p1, p2)/2;
57     }
58     if(b1) return (r*r*rad(p1, is[0]) + is[0].det(p2))/2;
59     if(b2) return (p1.det(is[1]) + r*r*rad(is[1], p2))/2;
60     return p1.det(p2)/2;
61 }
62
63 P inCenter(P A, P B, P C) {
64     double a = (B - C).abs(), b = (C - A).abs(), c = (A - B).abs();
65     return (A * a + B * b + C * c) / (a + b + c);
66 }
67
68 P circumCenter(P a, P b, P c) {
69     P bb = b - a, cc = c - a;
70     double db = bb.abs2(), dc = cc.abs2(), d = 2 * bb.det(cc);
71     return a - P(bb.y * dc - cc.y * db, cc.x * db - bb.x * dc) / d;
72 }

```

```

73 P othroCenter(P a, P b, P c) {
74     P ba = b - a, ca = c - a, bc = b - c;
75     double Y = ba.y * ca.y * bc.y,
76     A = ca.x * ba.y - ba.x * ca.y,
77     x0 = (Y + ca.x * ba.y * b.x - ba.x * ca.y * c.x) / A,
78     y0 = -ba.x * (x0 - c.x) / ba.y + ca.y;
79     return {x0, y0};
80 }
81
82 pair<P, db> min_circle(vector<P> ps){
83     random_shuffle(ps.begin(), ps.end());
84     int n = ps.size();
85     P o = ps[0]; db r = 0;
86     rep(i, 1, n) if(o.distTo(ps[i]) > r + EPS){
87         o = ps[i], r = 0;
88         rep(j, 0, i) if(o.distTo(ps[j]) > r + EPS){
89             o = (ps[i] + ps[j]) / 2; r = o.distTo(ps[i]);
90             rep(k, 0, j) if(o.distTo(ps[k]) > r + EPS){
91                 o = circumCenter(ps[i], ps[j], ps[k]);
92                 r = o.distTo(ps[i]);
93             }
94         }
95     }
96     return {o, r};
97 }

```

4.4 all.cpp

```

1  typedef double db;
2  const db EPS = 1e-9;
3
4  inline int sign(db a) { return a < -EPS ? -1 : a > EPS; }
5
6  inline int cmp(db a, db b){ return sign(a-b); }
7
8  struct P {
9      db x, y;
10     P() {}
11     P(db _x, db _y) : x(_x), y(_y) {}
12     P operator+(P p) { return {x + p.x, y + p.y}; }
13     P operator-(P p) { return {x - p.x, y - p.y}; }
14     P operator*(db d) { return {x * d, y * d}; }
15     P operator/(db d) { return {x / d, y / d}; }

```

```

16
17     bool operator<(P p) const {
18         int c = cmp(x, p.x);
19         if (c) return c == -1;
20         return cmp(y, p.y) == -1;
21     }
22
23     bool operator==(P o) const{
24         return cmp(x,o.x) == 0 && cmp(y,o.y) == 0;
25     }
26
27     db dot(P p) { return x * p.x + y * p.y; }
28     db det(P p) { return x * p.y - y * p.x; }
29
30     db distTo(P p) { return (*this-p).abs(); }
31     db alpha() { return atan2(y, x); }
32     void read() { cin>>x>>y; }
33     void write() {cout<<"("<<x<<" "<<y<<" "<<endl;}
34     db abs() { return sqrt(abs2());}
35     db abs2() { return x * x + y * y; }
36     P rot90() { return P(-y,x);}
37     P unit() { return *this/abs(); }
38     int quad() const { return sign(y) == 1 || (sign(y) == 0 && sign(x) >= 0)
39         ; }
40     P rot(db an){ return {x*cos(an)-y*sin(an),x*sin(an) + y*cos(an)}; }
41 };
42 struct L{ //ps[0] -> ps[1]
43     P ps[2];
44     P& operator[(int i)] { return ps[i]; }
45     P dir() { return ps[1] - ps[0]; }
46     bool include(P p) { return sign((ps[1] - ps[0]).det(p - ps[0])) > 0; }
47     L push(){ // push eps outward
48         const double eps = 1e-6;
49         P delta = (ps[1] - ps[0]).rot90().unit() * eps;
50         return {{ps[0] - delta, ps[1] - delta}};
51     }
52 };
53
54 #define cross(p1,p2,p3) ((p2.x-p1.x)*(p3.y-p1.y)-(p3.x-p1.x)*(p2.y-p1.y))
55 #define crossOp(p1,p2,p3) sign(cross(p1,p2,p3))
56
57 bool chkLL(P p1, P p2, P q1, P q2) {

```

```

58     db a1 = cross(q1, q2, p1), a2 = -cross(q1, q2, p2);
59     return sign(a1+a2) != 0;
60 }
61
62 P isLL(P p1, P p2, P q1, P q2) {
63     db a1 = cross(q1, q2, p1), a2 = -cross(q1, q2, p2);
64     return (p1 * a2 + p2 * a1) / (a1 + a2);
65 }
66
67 P isLL(L l1,L l2){ return isLL(l1[0],l1[1],l2[0],l2[1]); }
68
69 bool intersect(db l1,db r1,db l2,db r2){
70     if(l1>r1) swap(l1,r1); if(l2>r2) swap(l2,r2);
71     return !( cmp(r1,l2) == -1 || cmp(r2,l1) == -1 );
72 }
73
74 bool isSS(P p1, P p2, P q1, P q2){
75     return intersect(p1.x,p2.x,q1.x,q2.x) && intersect(p1.y,p2.y,q1.y,q2.y)
76         &&
77     crossOp(p1,p2,q1) * crossOp(p1,p2,q2) <= 0 && crossOp(q1,q2,p1)
78     * crossOp(q1,q2,p2) <= 0;
79 }
80 bool isSS_strict(P p1, P p2, P q1, P q2){
81     return crossOp(p1,p2,q1) * crossOp(p1,p2,q2) < 0 && crossOp(q1,q2,p1)
82     * crossOp(q1,q2,p2) < 0;
83 }
84
85 bool isMiddle(db a, db m, db b) {
86     return sign(a - m) == 0 || sign(b - m) == 0 || (a < m != b < m);
87 }
88
89 bool isMiddle(P a, P m, P b) {
90     return isMiddle(a.x, m.x, b.x) && isMiddle(a.y, m.y, b.y);
91 }
92
93 bool onSeg(P p1, P p2, P q){
94     return crossOp(p1,p2,q) == 0 && isMiddle(p1, q, p2);
95 }
96
97 bool onSeg_strict(P p1, P p2, P q){
98     return crossOp(p1,p2,q) == 0 && sign((q-p1).dot(p1-p2)) * sign((q-p2).
99     dot(p1-p2)) < 0;

```

```

99  }
100
101  P proj(P p1, P p2, P q) {
102      P dir = p2 - p1;
103      return p1 + dir * (dir.dot(q - p1) / dir.abs2());
104  }
105
106  P reflect(P p1, P p2, P q){
107      return proj(p1,p2,q) * 2 - q;
108  }
109
110  db nearest(P p1,P p2,P q){
111      P h = proj(p1,p2,q);
112      if(isMiddle(p1,h,p2))
113          return q.distTo(h);
114      return min(p1.distTo(q),p2.distTo(q));
115  }
116
117  db disSS(P p1, P p2, P q1, P q2){
118      if(isSS(p1,p2,q1,q2)) return 0;
119      return min(min(nearest(p1,p2,q1),nearest(p1,p2,q2)), min(nearest(q1,q2,
120          p1),nearest(q1,q2,p2)));
121  }
122
123  db rad(P p1,P p2){
124      return atan2l(p1.det(p2),p1.dot(p2));
125  }
126
127  db incircle(P p1, P p2, P p3){
128      db A = p1.distTo(p2);
129      db B = p2.distTo(p3);
130      db C = p3.distTo(p1);
131      return sqrtl(A*B*C/(A+B+C));
132  }
133  //polygon
134
135  db area(vector<P> ps){
136      db ret = 0; rep(i,0,ps.size()) ret += ps[i].det(ps[(i+1)%ps.size()]);
137      return ret/2;
138  }
139
140  int contain(vector<P> ps, P p){ //2:inside,1:on_seg,0:outside

```

```

141      int n = ps.size(), ret = 0;
142      rep(i,0,n){
143          P u=ps[i],v=ps[(i+1)%n];
144          if(onSeg(u,v,p)) return 1;
145          if(cmp(u.y,v.y)<=0) swap(u,v);
146          if(cmp(p.y,u.y) >0 || cmp(p.y,v.y) <= 0) continue;
147          ret ^= crossOp(p,u,v) > 0;
148      }
149      return ret*2;
150  }
151
152  vector<P> convexHull(vector<P> ps) {
153      int n = ps.size(); if(n <= 1) return ps;
154      sort(ps.begin(), ps.end());
155      vector<P> qs(n * 2); int k = 0;
156      for (int i = 0; i < n; qs[k++] = ps[i++])
157          while (k > 1 && crossOp(qs[k - 2], qs[k - 1], ps[i]) <= 0) --k;
158      for (int i = n - 2, t = k; i >= 0; qs[k++] = ps[i--])
159          while (k > t && crossOp(qs[k - 2], qs[k - 1], ps[i]) <= 0) --k;
160      qs.resize(k - 1);
161      return qs;
162  }
163
164  vector<P> convexHullNonStrict(vector<P> ps) {
165      //caution: need to unique the Ps first
166      int n = ps.size(); if(n <= 1) return ps;
167      sort(ps.begin(), ps.end());
168      vector<P> qs(n * 2); int k = 0;
169      for (int i = 0; i < n; qs[k++] = ps[i++])
170          while (k > 1 && crossOp(qs[k - 2], qs[k - 1], ps[i]) < 0) --k;
171      for (int i = n - 2, t = k; i >= 0; qs[k++] = ps[i--])
172          while (k > t && crossOp(qs[k - 2], qs[k - 1], ps[i]) < 0) --k;
173      qs.resize(k - 1);
174      return qs;
175  }
176
177  db convexDiameter(vector<P> ps){
178      int n = ps.size(); if(n <= 1) return 0;
179      int is = 0, js = 0; rep(k,1,n) is = ps[k]<ps[is]?k:is, js = ps[js] < ps[
180          k]?k:js;
181      int i = is, j = js;
182      db ret = ps[i].distTo(ps[j]);
183      do{

```

```

183         if((ps[(i+1)%n]-ps[i]).det(ps[(j+1)%n]-ps[j]) >= 0)
184             (++j)%=n;
185         else
186             (++i)%=n;
187         ret = max(ret,ps[i].distTo(ps[j]));
188     }while(i!=is || j!=js);
189     return ret;
190 }
191
192 vector<P> convexCut(const vector<P>&ps, P q1, P q2) {
193     vector<P> qs;
194     int n = ps.size();
195     rep(i,0,n){
196         P p1 = ps[i], p2 = ps[(i+1)%n];
197         int d1 = crossOp(q1,q2,p1), d2 = crossOp(q1,q2,p2);
198         if(d1 >= 0) qs.pb(p1);
199         if(d1 * d2 < 0) qs.pb(isLL(p1,p2,q1,q2));
200     }
201     return qs;
202 }
203
204 //min_dist
205
206 db min_dist(vector<P>&ps,int l,int r){
207     if(r-l<=5){
208         db ret = 1e100;
209         rep(i,l,r) rep(j,l,i) ret = min(ret,ps[i].distTo(ps[j]));
210         return ret;
211     }
212     int m = (l+r)>>1;
213     db ret = min(min_dist(ps,l,m),min_dist(ps,m,r));
214     vector<P> qs; rep(i,l,r) if(abs(ps[i].x-ps[m].x)<= ret) qs.pb(ps[i]);
215     sort(qs.begin(), qs.end(),[](P a,P b) -> bool {return a.y<b.y; });
216     rep(i,1,qs.size()) for(int j=i-1;j>=0&&qs[j].y>=qs[i].y-ret;--j)
217         ret = min(ret,qs[i].distTo(qs[j]));
218     return ret;
219 }
220
221 int type(P o1,db r1,P o2,db r2){
222     db d = o1.distTo(o2);
223     if(cmp(d,r1+r2) == 1) return 4;
224     if(cmp(d,r1+r2) == 0) return 3;
225     if(cmp(d,abs(r1-r2)) == 1) return 2;

```

```

226     if(cmp(d,abs(r1-r2)) == 0) return 1;
227     return 0;
228 }
229
230 vector<P> isCL(P o,db r,P p1,P p2){
231     db x = (p1-o).dot(p2-p1), y = (p2-p1).abs2(), d = x * x - y * ((p1-o).
232         abs2() - r*r);
233     if(sign(d) < 0) return {};
234     d = max(d,0.0); P m = p1 - (p2-p1)*(x/y), dr = (p2-p1)*(sqrt(d)/y);
235     return {m-dr,m+dr}; //along dir: p1->p2
236 }
237
238 vector<P> isCC(P o1, db r1, P o2, db r2) { //need to check whether two
239     circles are the same
240     db d = o1.distTo(o2);
241     if (cmp(d, r1 + r2) == 1) return {};
242     d = min(d, r1 + r2);
243     db y = (r1 * r1 + d * d - r2 * r2) / (2 * d), x = sqrt(r1 * r1 - y * y);
244     P dr = (o2 - o1).unit();
245     P q1 = o1 + dr * y, q2 = dr.rot90() * x;
246     return {q1-q2,q1+q2};//along circle 1
247 }
248
249 vector<P> tanCP(P o, db r, P p) {
250     db x = (p - o).abs2(), d = x - r * r;
251     if (sign(d) <= 0) return {}; // on circle => no tangent
252     P q1 = o + (p - o) * (r * r / x);
253     P q2 = (p - o).rot90() * (r * sqrt(d) / x);
254     return {q1-q2,q1+q2}; //counter clock-wise
255 }
256
257 vector<L> extanCC(P o1, db r1, P o2, db r2) {
258     vector<L> ret;
259     if (cmp(r1, r2) == 0) {
260         P dr = (o2 - o1).unit().rot90() * r1;
261         ret.pb({{o1 + dr, o2 + dr}}), ret.pb({{o1 - dr, o2 - dr}});
262     } else {
263         P p = (o2 * r1 - o1 * r2) / (r1 - r2);
264         vector<P> ps = tanCP(o1, r1, p), qs = tanCP(o2, r2, p);
265         rep(i,0,min(ps.size(),qs.size())) ret.pb({{ps[i], qs[i]}}); //c1
266         counter-clock wise

```



```

266     return ret;
267 }
268
269 vector<L> intanCC(P o1, db r1, P o2, db r2) {
270     vector<L> ret;
271     P p = (o1 * r2 + o2 * r1) / (r1 + r2);
272     vector<P> ps = tanCP(o1,r1,p), qs = tanCP(o2,r2,p);
273     rep(i,0,min(ps.size(),qs.size())) ret.pb({ps[i], qs[i]}); //c1 counter
274     -clock wise
275     return ret;
276 }
277 db areaCT(db r, P p1, P p2){
278     vector<P> is = isCL(P(0,0),r,p1,p2);
279     if(is.empty()) return r*r*rad(p1,p2)/2;
280     bool b1 = cmp(p1.abs2(),r*r) == 1, b2 = cmp(p2.abs2(), r*r) == 1;
281     if(b1 && b2){
282         if(sign((p1-is[0]).dot(p2-is[0])) <= 0 &&
283             sign((p1-is[0]).dot(p2-is[0])) <= 0)
284             return r*r*(rad(p1,is[0]) + rad(is[1],p2))/2 + is[0].det(is[1])/2;
285         else return r*r*rad(p1,p2)/2;
286     }
287     if(b1) return (r*r*rad(p1,is[0]) + is[0].det(p2))/2;
288     if(b2) return (p1.det(is[1]) + r*r*rad(is[1],p2))/2;
289     return p1.det(p2)/2;
290 }
291
292 bool parallel(L l0, L l1) { return sign( l0.dir().det( l1.dir() ) ) == 0; }
293
294 bool sameDir(L l0, L l1) { return parallel(l0, l1) && sign(l0.dir().dot(l1.
295     dir() ) ) == 1; }
296
297 bool cmp (P a, P b) {
298     if (a.quad() != b.quad()) {
299         return a.quad() < b.quad();
300     } else {
301         return sign( a.det(b) ) > 0;
302     }
303 }
304
305 bool operator < (L l0, L l1) {
306     if (sameDir(l0, l1)) {
307         return l1.include(l0[0]);

```

```

307     } else {
308         return cmp( l0.dir(), l1.dir() );
309     }
310 }
311
312 bool check(L u, L v, L w) {
313     return w.include(isLL(u,v));
314 }
315
316 vector<P> halfPlaneIS(vector<L> &l) {
317     sort(l.begin(), l.end());
318     deque<L> q;
319     for (int i = 0; i < (int)l.size(); ++i) {
320         if (i && sameDir(l[i], l[i - 1])) continue;
321         while (q.size() > 1 && !check(q[q.size() - 2], q[q.size() - 1], l[i
322             ])) q.pop_back();
323         while (q.size() > 1 && !check(q[q.size() - 1], q[0], l[i])) q.pop_front();
324         q.push_back(l[i]);
325     }
326     while (q.size() > 2 && !check(q[q.size() - 2], q[q.size() - 1], q[0])) q
327         .pop_back();
328     while (q.size() > 2 && !check(q[q.size() - 1], q[0], q[q.size() - 1])) q.pop_front
329         ();
330     vector<P> ret;
331     for (int i = 0; i < (int)q.size(); ++i) ret.push_back(isLL(q[i], q[(i +
332         1) % q.size()]));
333     return ret;
334 }
335
336 P inCenter(P A, P B, P C) {
337     double a = (B - C).abs(), b = (C - A).abs(), c = (A - B).abs();
338     return (A * a + B * b + C * c) / (a + b + c);
339 }
340
341 P circumCenter(P a, P b, P c) {
342     P bb = b - a, cc = c - a;
343     double db = bb.abs2(), dc = cc.abs2(), d = 2 * bb.det(cc);
344     return a - P(bb.y * dc - cc.y * db, cc.x * db - bb.x * dc) / d;
345 }
346
347 P othroCenter(P a, P b, P c) {
348     P ba = b - a, ca = c - a, bc = b - c;
349     double Y = ba.y * ca.y * bc.y,

```

```

346     A = ca.x * ba.y - ba.x * ca.y,
347     x0 = (Y + ca.x * ba.y * b.x - ba.x * ca.y * c.x) / A,
348     y0 = -ba.x * (x0 - c.x) / ba.y + ca.y;
349     return {x0, y0};
350 }

```

4.5 圆面积并.cpp

```

1 db intergal(db x,db y,db r,db L,db R){
2     return r*r*(R-L) + x*r*(sinl(R) - sinl(L)) + y*r*(-cosl(R) + cosl(L));
3 }
4
5 db calc_area_circle(P c,db r,db L,db R){
6     return intergal(c.x,c.y,r,L,R) / 2;
7 }
8
9 db norm(db x){
10     while(x < 0) x += 2 * PI;
11     while(x > 2 * PI) x -= 2 * PI;
12     return x;
13 }
14
15 P cs[N]; db rs[N];
16
17 void work(){
18     vector<int> cand = {};
19     rep(i,0,m){
20         bool ok = 1;
21         rep(j,0,m) if(i!=j){
22             if(rs[j] > rs[i] + EPS && rs[i] + cs[i].distTo(cs[j])
23                <= rs[j] + EPS){
24                 ok = 0; break;
25             }
26             if(cs[i] == cs[j] && cmp(rs[i],rs[j]) == 0 && j < i)
27                 {
28                     ok = 0; break;
29                 }
30             if(ok) cand.pb(i);
31         }
32     rep(i,0,cand.size()) cs[i] = cs[cand[i]], rs[i] = rs[cand[i]];
33     m = cand.size();

```

```

34
35     db area = 0;
36
37     //work
38     rep(i,0,m){
39         vector<pair<db,int>> ev = {{0,0},{2*PI,0}};
40
41         int cur = 0;
42
43         rep(j,0,m) if(j!=i){
44             auto ret = isCC(cs[i],rs[i],cs[j],rs[j]);
45             if(!ret.empty()){
46                 db l = (ret[0] - cs[i]).alpha();
47                 db r = (ret[1] - cs[i]).alpha();
48                 l = norm(l); r = norm(r);
49                 ev.pb({l,1});ev.pb({r,-1});
50                 if(l > r) ++cur;
51             }
52         }
53
54         sort(ev.begin(), ev.end());
55         rep(j,0,ev.size() - 1){
56             cur += ev[j].se;
57             if(cur == 0){
58                 area += calc_area_circle(cs[i],rs[i],ev[j].
59                    fi,ev[j+1].fi);
60             }
61         }
62     }

```

5 Graph

5.1 bellmanford.cpp

```

1 vector<PII> e[N];
2
3 template <typename T>
4 void add(int u, int v, T w) {
5     e[u].eb(v, w);
6 }
7

```

```

8  template <typename T>
9  vector<T> bellmanford(vector<pair<int, T>> *g, int start) {
10      // assert(0 <= start && start < g->n);
11      // maybe use inf = numeric_limits<T>::max() / 4
12      const T inf = numeric_limits<T>::max() / 4;
13      vector<T> dist(n, inf);
14      dist[start] = 0;
15      int cnt = 0;
16      while (true) {
17          bool upd = 0;
18          cnt++;
19          for (int i = 0; i < n; i++) {
20              for (auto [to, cost] : e[i]) {
21                  if (dist[to] > dist[i] + cost) {
22                      upd = 1;
23                      dist[to] = dist[i] + cost;
24                  }
25              }
26          }
27          if (!upd || cnt == n) {
28              break;
29          }
30      }
31      return dist;
32      // returns inf if there's no path
33 }

```

5.2 BlockCutTree.cpp

```

1  struct BlockCutTree {
2      int n;
3      std::vector<std::vector<int>>> adj;
4      std::vector<int> dfn, low, stk;
5      int cnt, cur;
6      std::vector<std::pair<int, int>>> edges;
7
8      BlockCutTree() {}
9      BlockCutTree(int n) {
10         init(n);
11     }
12
13     void init(int n) {
14         this->n = n;

```

```

15         adj.assign(n, {});
16         dfn.assign(n, -1);
17         low.resize(n);
18         stk.clear();
19         cnt = cur = 0;
20         edges.clear();
21     }
22
23     void addEdge(int u, int v) {
24         adj[u].push_back(v);
25         adj[v].push_back(u);
26     }
27
28     void dfs(int x) {
29         stk.push_back(x);
30         dfn[x] = low[x] = cur++;
31
32         for (auto y : adj[x]) {
33             if (dfn[y] == -1) {
34                 dfs(y);
35                 low[x] = std::min(low[x], low[y]);
36                 if (low[y] == dfn[x]) {
37                     int v;
38                     do {
39                         v = stk.back();
40                         stk.pop_back();
41                         edges.emplace_back(n + cnt, v);
42                     } while (v != y);
43                     edges.emplace_back(x, n + cnt);
44                     cnt++;
45                 }
46             } else {
47                 low[x] = std::min(low[x], dfn[y]);
48             }
49         }
50     }
51
52     std::pair<int, std::vector<std::pair<int, int>>>> work() {
53         for (int i = 0; i < n; i++) {
54             if (dfn[i] == -1) {
55                 stk.clear();
56                 dfs(i);
57             }

```

```

58     }
59     return {cnt, edges};
60 }
61 };

```

5.3 boruvka.cpp

```

1  /**
2   * while component > 1:
3   *   for each component:
4   *     find select[i]
5   *   for each component:
6   *     if select[i] != i:
7   *       merge(i, select[i])
8   *     component--
9   */
10
11 ll ans = 0, cnt = n;
12 while (cnt > 1) {
13     fill(select + 1, select + n + 1, -1);
14     vector<int> cand;
15     for (int i = 1; i <= n; i++) {
16         cand.push_back(col[i]);
17     }
18     ranges::sort(cand);
19     cand.erase(unique(all(cand)), cand.end());
20
21     for (auto id : cand) {
22         for (auto x : S[id]) remove(x);
23         for (auto x : S[id]) {
24             auto [opt, w] = get(x);
25             if (select[id] == -1 || w < mn[id]) {
26                 select[id] = opt, mn[id] = w;
27             }
28         }
29         for (auto x : S[id]) insert(x);
30     }
31
32     for (int i = 1; i <= n; i++) if (col[i] == i) {
33         int j = col[select[i]];
34         if (i == j) continue;
35         ans += mn[i];
36         merge(i, j);

```

```

37     cnt--;
38 }
39 }

```

5.4 dijkstra.cpp

```

1  vector<PII> e[N];
2
3  template <typename T>
4  void add(int u, int v, T w) {
5      e[u].eb(v, w);
6  }
7
8  template <typename T>
9  vector<T> dijkstra(vector<pair<int, T>> *g, int start) {
10     // assert(0 <= start && start < g.n);
11     // maybe use inf = numeric_limits<T>::max() / 4
12     vector<T> dist(n, numeric_limits<T>::max());
13     priority_queue<pair<T, int>, vector<pair<T, int>>, greater<pair<T,
14         int>>> s;
15     dist[start] = 0;
16     s.emplace(dist[start], start);
17     while (!s.empty()) {
18         T expected = s.top().first;
19         int i = s.top().second;
20         s.pop();
21         if (dist[i] != expected) {
22             continue;
23         }
24         for (auto [to, cost] : g[i]) {
25             if (dist[i] + cost < dist[to]) {
26                 dist[to] = dist[i] + cost;
27                 s.emplace(dist[to], to);
28             }
29         }
30     }
31     return dist;
32     // returns numeric_limits<T>::max() if there's no path

```

5.5 dijkstra.cpp

```

1  vector<PII> e[N];

```

```

2
3 template <typename T>
4 void add(int u, int v, T w) {
5     e[u].eb(v, w);
6 }
7
8 template <typename T>
9 vector<T> dijkstra(vector<pair<int, T>> *g, int start) {
10     // assert(0 <= start && start < g.n);
11     // maybe use inf = numeric_limits<T>::max() / 4
12     const T inf = numeric_limits<T>::max();
13     vector<T> dist(n, inf);
14     vector<int> was(n, 0);
15     dist[start] = 0;
16     while (true) {
17         int cur = -1;
18         for (int i = 0; i < n; i++) {
19             if (was[i] || dist[i] == inf) continue;
20             if (cur == -1 || dist[i] < dist[cur]) {
21                 cur = i;
22             }
23         }
24         if (cur == -1 || dist[cur] == inf) {
25             break;
26         }
27         was[cur] = 1;
28         for (auto [to, cost] : g[cur]) {
29             dist[to] = min(dist[to], dist[cur] + cost);
30         }
31     }
32     return dist;
33     // returns inf if there's no path
34 }

```

5.6 dinic.cpp

```

1 template<typename T>
2 struct FlowGraph {
3     static const int V = 1015;
4     static const int E = 100015;
5     int s, t, vtot;
6     int head[V], etot;
7     int dis[V], cur[V];

```

```

8     struct edge {
9         int v, nxt;
10        T f;
11    } e[E * 2];
12    void addedge(int u, int v, T f) {
13        e[etot] = {v, head[u], f};
14        head[u] = etot++;
15        e[etot] = {u, head[v], 0};
16        head[v] = etot++;
17    }
18    bool bfs() {
19        for (int i = 1; i <= vtot; i++) {
20            dis[i] = 0;
21            cur[i] = head[i];
22        }
23        queue<int> q;
24        q.push(s); dis[s] = 1;
25        while (!q.empty()) {
26            int u = q.front(); q.pop();
27            for (int i = head[u]; i != -1; i = e[i].nxt) {
28                if (e[i].f && !dis[e[i].v]) {
29                    int v = e[i].v;
30                    dis[v] = dis[u] + 1;
31                    if (v == t) return true;
32                    q.push(v);
33                }
34            }
35        }
36        return false;
37    }
38    T dfs(int u, T m) {
39        if (u == t) return m;
40        T flow = 0;
41        for (int i = cur[u]; i != -1; cur[u] = i = e[i].nxt) {
42            if (e[i].f && dis[e[i].v] == dis[u] + 1) {
43                T f = dfs(e[i].v, min(m, e[i].f));
44                e[i].f -= f;
45                e[i ^ 1].f += f;
46                m -= f;
47                flow += f;
48                if (!m) break;
49            }
50        }

```

```

51         if (!flow) dis[u] = -1;
52         return flow;
53     }
54     T dinic() {
55         T flow = 0;
56         while (bfs()) flow += dfs(s, numeric_limits<T>::max());
57         return flow;
58     }
59     void init(int _s, int _t, int _vtot) {
60         s = _s;
61         t = _t;
62         vtot = _vtot;
63         etot = 0;
64         for (int i = 1; i <= vtot; i++) head[i] = -1;
65     }
66 };

```

5.7 dinic-tourist.cpp

```

1  template <typename T>
2  class flow_graph {
3  public:
4      static constexpr T eps = (T) 1e-9;
5
6      struct edge {
7          int from;
8          int to;
9          T c;
10         T f;
11     };
12
13     vector<vector<int>>> g;
14     vector<edge> edges;
15     int n;
16     int st;
17     int fin;
18     T flow;
19
20     flow_graph(int _n, int _st, int _fin) : n(_n), st(_st), fin(_fin) {
21         assert(0 <= st && st < n && 0 <= fin && fin < n && st != fin);
22         g.resize(n);
23         flow = 0;
24     }

```

```

25
26     void clear_flow() {
27         for (const edge &e : edges) {
28             e.f = 0;
29         }
30         flow = 0;
31     }
32
33     int add(int from, int to, T forward_cap, T backward_cap) {
34         assert(0 <= from && from < n && 0 <= to && to < n);
35         int id = (int) edges.size();
36         g[from].push_back(id);
37         edges.push_back({from, to, forward_cap, 0});
38         g[to].push_back(id + 1);
39         edges.push_back({to, from, backward_cap, 0});
40         return id;
41     }
42 };
43
44 template <typename T>
45 class dinic {
46 public:
47     flow_graph<T> &g;
48
49     vector<int> ptr;
50     vector<int> d;
51     vector<int> q;
52
53     dinic(flow_graph<T> &_g) : g(_g) {
54         ptr.resize(g.n);
55         d.resize(g.n);
56         q.resize(g.n);
57     }
58
59     bool expath() {
60         fill(d.begin(), d.end(), -1);
61         q[0] = g.fin;
62         d[g.fin] = 0;
63         int beg = 0, end = 1;
64         while (beg < end) {
65             int i = q[beg++];
66             for (int id : g.g[i]) {
67                 const auto &e = g.edges[id];

```

```

68         const auto &back = g.edges[id ^ 1];
69         if (back.c - back.f > g.eps && d[e.to] == -1) {
70             d[e.to] = d[i] + 1;
71             if (e.to == g.st) {
72                 return true;
73             }
74             q[end++] = e.to;
75         }
76     }
77 }
78 return false;
79 }
80
81 T dfs(int v, T w) {
82     if (v == g.fin) {
83         return w;
84     }
85     int &j = ptr[v];
86     while (j >= 0) {
87         int id = g.g[v][j];
88         const auto &e = g.edges[id];
89         if (e.c - e.f > g.eps && d[e.to] == d[v] - 1) {
90             T t = dfs(e.to, min(e.c - e.f, w));
91             if (t > g.eps) {
92                 g.edges[id].f += t;
93                 g.edges[id ^ 1].f -= t;
94                 return t;
95             }
96         }
97         j--;
98     }
99     return 0;
100 }
101
102 T max_flow() {
103     while (expath()) {
104         for (int i = 0; i < g.n; i++) {
105             ptr[i] = (int) g.g[i].size() - 1;
106         }
107         T big_add = 0;
108         while (true) {
109             T add = dfs(g.st, numeric_limits<T>::max());
110             if (add <= g.eps) {

```

```

111                 break;
112             }
113             big_add += add;
114         }
115         if (big_add <= g.eps) {
116             break;
117         }
118         g.flow += big_add;
119     }
120     return g.flow;
121 }
122
123 vector<bool> min_cut() {
124     max_flow();
125     vector<bool> ret(g.n);
126     for (int i = 0; i < g.n; i++) {
127         ret[i] = (d[i] != -1);
128     }
129     return ret;
130 }
131 };

```

5.8 eulerian-digraph.cpp

```

1 // http://oj.daimayuan.top/course/14/problem/765 单词接龙
2 vector<int> g[N];
3 int in[N], out[N], f[N], vis[N];
4 string s;
5 vector<int> path;
6
7 void dfs(int x) {
8     while (f[x] < SZ(g[x])) {
9         int y = g[x][f[x]];
10         f[x]++;
11         dfs(y);
12         path.pb(x);
13     }
14 }
15
16 bool euler() {
17     int start = -1, diff = 0, num = 0;
18     rep(i, 0, n - 1) {
19         if (in[i] + 1 == out[i]) num++, start = i;

```

```

20         if (in[i] != out[i]) diff++;
21     }
22     // 恰好都balance或者恰好一个in = out + 1, 一个in + 1 = out
23     if (!(diff == 0 || (diff == 2 && num == 1))) return false;
24     if (start == -1) {
25         rep(i, 0, n - 1) {
26             if (in[i]) {
27                 start = i;
28                 break;
29             }
30         }
31     }
32     dfs(start);
33     path.pb(start);
34     reverse(all(path));
35     if (SZ(path) != m + 1) return false;
36     return true;
37 }
38
39 void solve() {
40     cin >> m;
41     n = 26;
42     rep(i, 1, m) {
43         cin >> s;
44         int u = s[0] - 'a', v = s[SZ(s) - 1] - 'a';
45         g[u].pb(v);
46         in[v]++, out[u]++;
47     }
48     cout << (euler() ? "Yes" : "No") << '\n';
49 }

```

5.9 eulerian-undigraph.cpp

```

1 // http://oj.daimayuan.top/course/14/problem/763 欧拉路判断
2 vector<PII> g[N];
3 int d[N], f[N], vis[N], edge_idx;
4 vector<int> path;
5
6 void dfs(int x) {
7     while (f[x] < SZ(g[x])) {
8         auto [v, id] = g[x][f[x]];
9         f[x]++;
10        if (vis[id]) continue;

```

```

11        vis[id] = 1;
12        dfs(v);
13        path.pb(x);
14    }
15 }
16
17 bool euler() {
18     int start = -1, num = 0;
19     rep(i, 1, n) {
20         if (d[i] & 1) num++, start = i;
21     }
22     if (!(num == 0 || (num == 2 && start != -1))) return false;
23     if (start == -1) {
24         rep(i, 1, n) {
25             if (d[i]) {
26                 start = i;
27                 break;
28             }
29         }
30     }
31     dfs(start);
32     path.pb(start);
33     reverse(all(path));
34     if (SZ(path) != m + 1) return false;
35     return true;
36 }
37
38 void solve() {
39     cin >> n >> m;
40     rep(i, 1, m) {
41         int u, v;
42         cin >> u >> v;
43         edge_idx++;
44         g[u].pb({v, edge_idx});
45         g[v].pb({u, edge_idx});
46         d[u]++, d[v]++;
47     }
48     cout << (euler() ? "Yes" : "No") << '\n';
49 }

```

5.10 hungarian.cpp

```

1 vector<int> g[maxn];

```



```

2  int idx;
3  int a[N][N], use[N][N], p[maxn], vis[maxn];
4
5  bool find(int x) {
6      vis[x] = 1;
7      for (auto y : g[x]) {
8          if (!p[y] || (!vis[p[y]] && find(p[y]))) {
9              p[y] = x;
10             return true;
11         }
12     }
13     return false;
14 }
15
16 int match() {
17     int res = 0;
18     fill(p + 1, p + idx + 1, 0);
19     for (int i = 1; i <= idx; i++) {
20         fill(vis + 1, vis + idx + 1, 0);
21         if (find(i)) res++;
22     }
23     return res;
24 }

```

5.11 KM.cpp

```

1  #include <bits/stdc++.h>
2  using namespace std;
3  using ll = long long;
4
5  // L <= R, 左边完全匹配
6  // 最小权完备匹配
7
8  // 带权匹配: 使得该二分图的权值和最大 (或最小) 的匹配。
9  // 最大匹配: 使得该二分图边数最多的匹配。
10 // 完备匹配: 使得点数较小的点集中每个点都被匹配的匹配。
11 // 完美匹配: 所有点都被匹配的匹配。
12 // 定理1: 最大匹配数 = 最小点覆盖数 (Konig 定理)
13 // 定理2: 最大匹配数 = 最大独立数
14 // 定理3: 最小路径覆盖数 = 顶点数 - 最大匹配数
15
16 // 二分图的最小点覆盖
17 // 定义: 在二分图中, 求最少的点集, 使得每一条边至少都有端点在这个点集中。

```

```

18 // 二分图的最小点覆盖 = 二分图的最大匹配
19
20 // 二分图的最少边覆盖
21 // 定义: 在二分图中, 求最少的边, 使得他们覆盖所有的点, 并且每一个点只被一条
    边覆盖。
22 // 二分图的最少边覆盖 = 点数 - 二分图的最大匹配
23
24 // 二分图的最大独立集
25 // 定义: 在二分图中, 选最多的点, 使得任意两个点之间没有直接边连接。
26 // 二分图的最大独立集 = 点数 - 二分图的最大匹配
27
28 template<class T>
29 pair<T, vector<int>> hungarian(const vector<vector<T>> &a) {
30     if (a.empty()) return {0, {}};
31     int n = a.size() + 1, m = a[0].size() + 1;
32     vector<T> u(n), v(m); // 顶标
33     vector<int> p(m), ans(n - 1);
34     for (int i = 1; i < n; i++) {
35         p[0] = i;
36         int j0 = 0;
37         vector<T> dist(m, numeric_limits<T>::max());
38         vector<int> pre(m, -1);
39         vector<bool> done(m + 1);
40         do { // dijkstra
41             done[j0] = true;
42             int i0 = p[j0], j1;
43             T delta = numeric_limits<T>::max();
44             for (int j = 1; j < m; j++) if (!done[j]) {
45                 auto cur = a[i0 - 1][j - 1] - u[i0] - v[j];
46                 if (cur < dist[j]) dist[j] = cur, pre[j] =
                    j0;
47                 if (dist[j] < delta) delta = dist[j], j1 = j;
48             }
49             for (int j = 0; j < m; j++) {
50                 if (done[j]) u[p[j]] += delta, v[j] -= delta;
51                 else dist[j] -= delta;
52             }
53             j0 = j1;
54         } while (p[j0]);
55         while (j0) { // update alternating path
56             int j1 = pre[j0];

```

```

57         p[j0] = p[j1], j0 = j1;
58     }
59 }
60 for (int j = 1; j < m; j++) {
61     if (p[j]) ans[p[j] - 1] = j - 1;
62 }
63 return {-v[0], ans}; // min cost
64 }
65
66 int L, R, m;
67 int main() {
68     scanf("%d%d%d", &L, &R, &m);
69     R = max(L, R);
70     auto a = vector<vector<ll>>(L, vector<ll>(R, 0));
71     for (int i = 0; i < m; i++) {
72         int u, v, w;
73         scanf("%d%d%d", &u, &v, &w);
74         --u; --v;
75         a[u][v] = -w;
76     }
77     auto [val, ans] = hungarian(a);
78     printf("%lld\n", -val);
79     for (int i = 0; i < L; i++) {
80         if (a[i][ans[i]] >= 0) ans[i] = -1;
81         printf("%d%c", ans[i] + 1, "\n"[i == L - 1]);
82     }
83 }

```

5.12 kosaraju.cpp

```

1 vector<int> e[maxn], erev[maxn];
2 vector<int> c, out;
3 vector<vector<int>> scc;
4 int vis[maxn];
5 void dfs(int u) {
6     vis[u] = 1;
7     for (auto v : e[u]) if (!vis[v]) dfs(v);
8     out.pb(u);
9 }
10 void dfs_rev(int u) {
11     vis[u] = 1;
12     for (auto v : erev[u]) if (!vis[v]) dfs_rev(v);
13     c.pb(u);

```

```

14 }
15 void solve() {
16     cin >> n >> m;
17     rep(i, 1, m) {
18         int u, v;
19         cin >> u >> v;
20         e[u].pb(v);
21         erev[v].pb(u);
22     }
23     rep(i, 1, n) if (!vis[i]) dfs(i);
24     fill(vis + 1, vis + n + 1, 0);
25     reverse(all(out));
26     for (auto v : out) if (!vis[v]) {
27         c.clear();
28         dfs_rev(v);
29         scc.pb(c);
30     }
31 }

```

5.13 kruskal 重构树.cpp

```

1 /**
2  * 构建后是一颗二叉树，如果按最小生成树建立的话是大根堆。
3  * 性质：原图中两个点间所有路径上的边最大权值的最小值=最小生成树上两点简单路
   径的边最大权值
4  * =kruskal 重构树上两点 LCA 的权值。
5  * 重构树中代表原树中的点的节点全是叶子节点，其余节点都代表了一条边的边权。
6  * 利用这个性质可以找到点 P 的简单路径上边权最大值小于 lim 深度最小的节点。
7  * 要求最小权值最大值，可以建最大生成树的重构树从而达到一样的效果。
8  */
9
10 vector<tuple<ll, ll, ll>> E;
11 rep(i, 1, m) {
12     int u, v, w;
13     cin >> u >> v >> w;
14     E.emplace_back(w, u, v);
15 }
16 ranges::sort(E);
17 for (auto [w, u, v] : E) {
18     u = find(u), v = find(v);
19     if (u == v) continue;
20     int p = ++idx;
21     lim[p] = w;

```

```

22     fa[u] = p, fa[v] = p;
23     e[p].push_back(u);
24     e[u].push_back(p);
25     e[p].push_back(v);
26     e[v].push_back(p);
27 }

```

5.14 MCMF.cpp

```

1  template<typename T>
2  struct MinCostGraph {
3      static const int V = 20100;
4      static const int E = 201000;
5      int s, t, vtot;
6      int head[V], etot;
7      T dis[V], flow, cost;
8      int pre[V];
9      bool vis[V];
10
11     struct edge {
12         int v, nxt;
13         T f, c;
14     } e[E * 2];
15     void addedge(int u, int v, T f, T c, T f2 = 0){
16         e[etot] = {v, head[u], f, c}; head[u] = etot++;
17         e[etot] = {u, head[v], f2, -c}; head[v] = etot++;
18     }
19
20     bool spfa() {
21         T inf = numeric_limits<T>::max() / 2;
22         for (int i = 1; i <= vtot; i++) {
23             dis[i] = inf;
24             vis[i] = false;
25             pre[i] = -1;
26         }
27         dis[s] = 0;
28         vis[s] = true;
29         queue<int> q;
30         q.push(s);
31         while (!q.empty()) {
32             int u = q.front();
33             for (int i = head[u]; ~i; i = e[i].nxt) {
34                 int v = e[i].v;

```

```

35                 if (e[i].f && dis[v] > dis[u] + e[i].c) {
36                     dis[v] = dis[u] + e[i].c;
37                     pre[v] = i;
38                     if (!vis[v]) {
39                         vis[v] = 1;
40                         q.push(v);
41                     }
42                 }
43             }
44             q.pop();
45             vis[u] = false;
46         }
47         return dis[t] != inf;
48     }
49
50     void augment() {
51         int u = t;
52         T f = numeric_limits<T>::max();
53         while (~pre[u]) {
54             f = min(f, e[pre[u]].f);
55             u = e[pre[u] ^ 1].v;
56         }
57         flow += f;
58         cost += f * dis[t];
59         u = t;
60         while (~pre[u]) {
61             e[pre[u]].f -= f;
62             e[pre[u] ^ 1].f += f;
63             u = e[pre[u] ^ 1].v;
64         }
65     }
66
67     pair<T, T> solve() {
68         flow = 0;
69         cost = 0;
70         while (spfa()) augment();
71         return {flow, cost};
72     }
73
74     void init(int s_, int t_, int vtot_) {
75         s = s_;
76         t = t_;
77         vtot = vtot_;
78         etot = 0;

```

```

78     for (int i = 1; i <= vtot; i++) head[i] = -1;
79 }
80 };

```

5.15 MCMFfast.cpp

```

1  template <typename flow_t = int, typename cost_t = long long>
2  struct MCMF_SSPA {
3      int N;
4      vector<vector<int>>> adj;
5      struct edge_t {
6          int dest;
7          flow_t cap;
8          cost_t cost;
9      };
10     vector<edge_t> edges;
11
12     vector<char> seen;
13     vector<cost_t> pi;
14     vector<int> prv;
15
16     explicit MCMF_SSPA(int N_) : N(N_), adj(N), pi(N, 0), prv(N) {}
17
18     void addEdge(int from, int to, flow_t cap, cost_t cost) {
19         assert(cap >= 0);
20         int e = int(edges.size());
21         edges.emplace_back(edge_t{to, cap, cost});
22         edges.emplace_back(edge_t{from, 0, -cost});
23         adj[from].push_back(e);
24         adj[to].push_back(e+1);
25     }
26
27     const cost_t INF_COST = numeric_limits<cost_t>::max() / 4;
28     const flow_t INF_FLOW = numeric_limits<flow_t>::max() / 4;
29     vector<cost_t> dist;
30     __gnu_pbds::priority_queue<pair<cost_t, int>> q;
31     vector<typename decltype(q)::point_iterator> its;
32     void path(int s) {
33         dist.assign(N, INF_COST);
34         dist[s] = 0;
35
36         its.assign(N, q.end());
37         its[s] = q.push({0, s});

```

```

38
39     while (!q.empty()) {
40         int i = q.top().second; q.pop();
41         cost_t d = dist[i];
42         for (int e : adj[i]) {
43             if (edges[e].cap) {
44                 int j = edges[e].dest;
45                 cost_t nd = d + edges[e].cost;
46                 if (nd < dist[j]) {
47                     dist[j] = nd;
48                     prv[j] = e;
49                     if (its[j] == q.end()) {
50                         its[j] = q.push({-(dist[j] - pi[j]), j});
51                     } else {
52                         q.modify(its[j], {-(dist[j] - pi[j]), j});
53                     }
54                 }
55             }
56         }
57     }
58
59     swap(pi, dist);
60 }
61
62 vector<pair<flow_t, cost_t>> maxflow(int s, int t) {
63     assert(s != t);
64     flow_t totFlow = 0; cost_t totCost = 0;
65     vector<pair<flow_t, cost_t>> res;
66     while (path(s), pi[t] < INF_COST) {
67         flow_t curFlow = numeric_limits<flow_t>::max();
68         for (int cur = t; cur != s; ) {
69             int e = prv[cur];
70             int nxt = edges[e^1].dest;
71             curFlow = min(curFlow, edges[e].cap);
72             cur = nxt;
73         }
74         totFlow += curFlow;
75         totCost += pi[t] * curFlow;
76         for (int cur = t; cur != s; ) {
77             int e = prv[cur];
78             int nxt = edges[e^1].dest;
79             edges[e].cap -= curFlow;
80             edges[e^1].cap += curFlow;

```

```

81         cur = nxt;
82     }
83
84     res.emplace_back(totFlow, totCost);
85 }
86 return res;
87 }
88 };

```

5.16 MCMFfull.cpp

```

1  template <typename T, typename C>
2  class MCMF {
3  public:
4      static constexpr T eps = (T) 1e-9;
5
6      struct edge {
7          int from;
8          int to;
9          T c;
10         T f;
11         C cost;
12     };
13
14     int n;
15     vector<vector<int>>> g;
16     vector<edge> edges;
17     vector<C> d;
18     vector<C> pot;
19     __gnu_pbds::priority_queue<pair<C, int>>> q;
20     vector<typename decltype(q)::point_iterator> its;
21     vector<int> pe;
22     const C INF_C = numeric_limits<C>::max() / 2;
23
24     explicit MCMF(int n_) : n(n_), g(n), d(n), pot(n, 0), its(n), pe(n) {}
25
26     int add(int from, int to, T forward_cap, T backward_cap, C edge_cost) {
27         assert(0 <= from && from < n && 0 <= to && to < n);
28         assert(forward_cap >= 0 && backward_cap >= 0);
29         int id = static_cast<int>(edges.size());
30         g[from].push_back(id);
31         edges.push_back({from, to, forward_cap, 0, edge_cost});
32         g[to].push_back(id + 1);

```

```

33         edges.push_back({to, from, backward_cap, 0, -edge_cost});
34         return id;
35     }
36
37     void expath(int st) {
38         fill(d.begin(), d.end(), INF_C);
39         q.clear();
40         fill(its.begin(), its.end(), q.end());
41         its[st] = q.push({pot[st], st});
42         d[st] = 0;
43         while (!q.empty()) {
44             int i = q.top().second;
45             q.pop();
46             its[i] = q.end();
47             for (int id : g[i]) {
48                 const edge &e = edges[id];
49                 int j = e.to;
50                 if (e.c - e.f > eps && d[i] + e.cost < d[j]) {
51                     d[j] = d[i] + e.cost;
52                     pe[j] = id;
53                     if (its[j] == q.end()) {
54                         its[j] = q.push({pot[j] - d[j], j});
55                     } else {
56                         q.modify(its[j], {pot[j] - d[j], j});
57                     }
58                 }
59             }
60         }
61         swap(d, pot);
62     }
63
64     pair<T, C> calc(int st, int fin) { // max_flow_min_cost
65         T flow = 0;
66         C cost = 0;
67         bool ok = true;
68         for (auto& e : edges) {
69             if (e.c - e.f > eps && e.cost + pot[e.from] - pot[e.to] < 0) {
70                 ok = false;
71                 break;
72             }
73         }
74         if (ok) {
75             expath(st);

```

```

76 } else {
77     vector<int> deg(n, 0);
78     for (int i = 0; i < n; i++) {
79         for (int eid : g[i]) {
80             auto& e = edges[eid];
81             if (e.c - e.f > eps) {
82                 deg[e.to] += 1;
83             }
84         }
85     }
86     vector<int> que;
87     for (int i = 0; i < n; i++) {
88         if (deg[i] == 0) {
89             que.push_back(i);
90         }
91     }
92     for (int b = 0; b < (int) que.size(); b++) {
93         for (int eid : g[que[b]]) {
94             auto& e = edges[eid];
95             if (e.c - e.f > eps) {
96                 deg[e.to] -= 1;
97                 if (deg[e.to] == 0) {
98                     que.push_back(e.to);
99                 }
100             }
101         }
102     }
103     fill(pot.begin(), pot.end(), INF_C);
104     pot[st] = 0;
105     if (static_cast<int>(que.size()) == n) {
106         for (int v : que) {
107             if (pot[v] < INF_C) {
108                 for (int eid : g[v]) {
109                     auto& e = edges[eid];
110                     if (e.c - e.f > eps) {
111                         if (pot[v] + e.cost < pot[e.to]) {
112                             pot[e.to] = pot[v] + e.cost;
113                             pe[e.to] = eid;
114                         }
115                     }
116                 }
117             }
118         }

```

```

119     } else {
120         que.assign(1, st);
121         vector<bool> in_queue(n, false);
122         in_queue[st] = true;
123         for (int b = 0; b < (int) que.size(); b++) {
124             int i = que[b];
125             in_queue[i] = false;
126             for (int id : g[i]) {
127                 const edge &e = edges[id];
128                 if (e.c - e.f > eps && pot[i] + e.cost < pot[e.to]) {
129                     pot[e.to] = pot[i] + e.cost;
130                     pe[e.to] = id;
131                     if (!in_queue[e.to]) {
132                         que.push_back(e.to);
133                         in_queue[e.to] = true;
134                     }
135                 }
136             }
137         }
138     }
139 }
140 // debug(pot[fin]);
141 while (pot[fin] < INF_C) { // < 0
142     T push = numeric_limits<T>::max();
143     int v = fin;
144     while (v != st) {
145         const edge &e = edges[pe[v]];
146         push = min(push, e.c - e.f);
147         v = e.from;
148     }
149     v = fin;
150     while (v != st) {
151         edge &e = edges[pe[v]];
152         e.f += push;
153         edge &back = edges[pe[v] ^ 1];
154         back.f -= push;
155         v = e.from;
156     }
157     flow += push;
158     cost += push * pot[fin];
159     expath(st);
160 }
161 return {flow, cost};

```

```

162     }
163 };

```

5.17 prim.cpp

```

1  vector<PII> e[N];
2
3  template <typename T>
4  void add(int u, int v, T w) {
5      e[u].eb(v, w);
6  }
7
8  template <typename T>
9  T prim(vector<pair<int, T>> *g, int start) {
10     const T inf = numeric_limits<T>::max() / 4;
11     T res = 0;
12     vector<T> dist(n, inf);
13     dist[start] = 0;
14     priority_queue<pair<T, int>, vector<pair<T, int>>, greater<pair<T,
15         int>>> s;
16     s.emplace(dist[start], start);
17     vector<int> was(n, 0);
18     while (!s.empty()) {
19         T expected = s.top().first;
20         int i = s.top().second;
21         s.pop();
22         if (dist[i] != expected || was[i]) {
23             continue;
24         }
25         was[i] = 1;
26         res += expected;
27         for (auto [to, cost] : g[i]) {
28             if (cost < dist[to]) {
29                 dist[to] = cost;
30                 s.emplace(dist[to], to);
31             }
32         }
33     }
34     return res;

```

5.18 PushRelabel.cpp

```

1  /**
2   * Author: Simon Lindholm
3   * Date: 2015-02-24
4   * License: CC0
5   * Source: Wikipedia, tinyKACTL
6   * Description: Push-relabel using the highest label selection rule and the
7     gap heuristic. Quite fast in practice.
8   * To obtain the actual flow, look at positive values only.
9   * Time:  $O(V^2 \sqrt{E})$ 
10  * Status: Tested on Kattis and SPOJ, and stress-tested
11  */
12
13  struct PushRelabel {
14      typedef vector<int> vi;
15      struct Edge {
16          int dest, back;
17          ll f, c;
18      };
19      vector<vector<Edge>> g;
20      vector<ll> ec;
21      vector<Edge*> cur;
22      vector<vi> hs; vi H;
23      PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}
24
25      void addEdge(int s, int t, ll cap, ll rcap=0) {
26          if (s == t) return;
27          g[s].push_back({t, SZ(g[t]), 0, cap});
28          g[t].push_back({s, SZ(g[s])-1, 0, rcap});
29      }
30
31      void addFlow(Edge& e, ll f) {
32          Edge &back = g[e.dest][e.back];
33          if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
34          e.f += f; e.c -= f; ec[e.dest] += f;
35          back.f -= f; back.c += f; ec[back.dest] -= f;
36      }
37
38      ll calc(int s, int t) {
39          int v = SZ(g); H[s] = v; ec[t] = 1;
40          vi co(2*v); co[0] = v-1;
41          rep(i,0,v-1) cur[i] = g[i].data();
42          for (Edge& e : g[s]) addFlow(e, e.c);

```

```

43     for (int hi = 0;;) {
44         while (hs[hi].empty()) if (!hi--) return -ec[s];
45         int u = hs[hi].back(); hs[hi].pop_back();
46         while (ec[u] > 0) // discharge u
47             if (cur[u] == g[u].data() + SZ(g[u])) {
48                 H[u] = 1e9;
49                 for (Edge& e : g[u]) if (e.c && H[u]
50                     > H[e.dest]+1)
51                     H[u] = H[e.dest]+1, cur[u] =
52                         &e;
53                 if (++co[H[u]], !--co[hi] && hi < v)
54                     rep(i,0,v-1) if (hi < H[i]
55                         && H[i] < v)
56                         --co[H[i]], H[i] = v
57                             + 1;
58                 hi = H[u];
59             } else if (cur[u]->c && H[u] == H[cur[u]->
60                 dest]+1)
61                 addFlow(*cur[u], min(ec[u], cur[u]->
62                     c));
63             else ++cur[u];
64     }
65     bool leftOfMinCut(int a) { return H[a] >= SZ(g); }
66 };

```

5.19 tarjan 割点.cpp

```

1  vector<int> g[maxn], ans;
2  stack<int> stk;
3  int dfn[maxn], cut[maxn], low[maxn], idx;
4
5  void dfs(int x, int f) {
6      low[x] = dfn[x] = ++idx;
7      stk.push(x);
8      int ch = 0;
9      for (auto y : g[x]) {
10         if (!dfn[y]) {
11             ch++;
12             dfs(y, x);
13             low[x] = min(low[x], low[y]);
14             if (low[y] >= dfn[x]) cut[x] = 1;
15         } else {

```

```

16             if (y != f) low[x] = min(low[x], dfn[y]);
17         }
18     }
19     if (x == 1 && ch <= 1) cut[x] = 0;
20     if (cut[x]) ans.pb(x);
21 }

```

5.20 tarjan 割边.cpp

```

1  vector<PII> g[maxn];
2  stack<int> stk;
3  int dfn[maxn], ins[maxn], low[maxn];
4  int idx, tot;
5  VI ans;
6  void dfs(int x, int f) {
7      low[x] = dfn[x] = ++idx;
8      stk.push(x);
9      ins[x] = 1;
10     for (auto [y, id] : g[x]) {
11         if (!dfn[y]) {
12             dfs(y, id);
13             low[x] = min(low[x], low[y]);
14         } else {
15             if (ins[y] && id != f) low[x] = min(low[x], dfn[y]);
16         }
17     }
18     if (low[x] >= dfn[x]) {
19         ++tot;
20         while (true) {
21             int cur = stk.top();
22             stk.pop();
23             ins[cur] = 0;
24             if (cur == x) break;
25         }
26         if (f != 0) ans.pb(f);
27     }
28 }

```

5.21 tarjan 强连通分量.cpp

```

1  vector<int> g[maxn];
2  stack<int> stk;
3  int dfn[maxn], ins[maxn], low[maxn], belong[maxn];

```



```

4  int idx, tot;
5
6  void dfs(int x) {
7      low[x] = dfn[x] = ++idx;
8      ins[x] = 1;
9      stk.push(x);
10     for (auto y : g[x]) {
11         if (!dfn[y]) {
12             dfs(y);
13             low[x] = min(low[x], low[y]);
14         } else {
15             if (ins[y]) low[x] = min(low[x], dfn[y]);
16         }
17     }
18     if (low[x] >= dfn[x]) {
19         ++tot;
20         while (true) {
21             int cur = stk.top(); stk.pop();
22             ins[cur] = 0;
23             belong[cur] = tot;
24             if (cur == x) break;
25         }
26     }
27 }

```

5.22 tarjan 点双.cpp

```

1  vector<int> g[maxn];
2  stack<int> stk;
3  int dfn[maxn], low[maxn], idx, tot, cut[maxn];
4  vector<int> bcc[maxn];
5
6  void dfs(int x, int f) {
7      low[x] = dfn[x] = ++idx;
8      stk.push(x);
9      int ch = 0;
10     for (auto y : g[x]) {
11         if (!dfn[y]) {
12             ch++;
13             dfs(y, x);
14             low[x] = min(low[x], low[y]);
15             if (low[y] >= dfn[x]) {
16                 cut[x] = 1;

```

```

17                 ++tot;
18                 bcc[tot].pb(x);
19                 while (true) {
20                     int cur = stk.top();
21                     stk.pop();
22                     bcc[tot].pb(cur);
23                     if (cur == y) break;
24                 }
25             } else {
26                 if (y != f) low[x] = min(low[x], dfn[y]);
27             }
28         }
29     }
30     if (x == 1 && ch <= 1) cut[x] = 0;
31 }

```

5.23 tarjan 边双.cpp

```

1  vector<PII> g[maxn];
2  stack<int> stk;
3  int dfn[maxn], low[maxn], idx, tot, belong[maxn];
4  vector<int> bcc[maxn];
5
6  void dfs(int x, int f) {
7      low[x] = dfn[x] = ++idx;
8      stk.push(x);
9      for (auto [y, id] : g[x]) {
10         if (!dfn[y]) {
11             dfs(y, id);
12             low[x] = min(low[x], low[y]);
13         } else {
14             if (id != f) low[x] = min(low[x], dfn[y]);
15         }
16     }
17     if (low[x] >= dfn[x]) {
18         ++tot;
19         while (true) {
20             int cur = stk.top();
21             stk.pop();
22             belong[cur] = tot;
23             bcc[tot].pb(cur);
24             if (cur == x) break;
25         }

```

```

26     }
27 }

```

5.24 twosat.cpp

```

1  class twosat {
2  public:
3      digraph<int> g;
4      int n;
5
6      twosat(int _n) : g(digraph<int>(2 * _n)), n(_n) {
7      }
8
9      // (v[x] == value_x)
10     inline void add(int x, int value_x) {
11         assert(0 <= x && x < n);
12         assert(0 <= value_x && value_x <= 1);
13         g.add(2 * x + (value_x ^ 1), 2 * x + value_x);
14     }
15
16     // (v[x] == value_x || v[y] == value_y)
17     inline void add(int x, int value_x, int y, int value_y) {
18         assert(0 <= x && x < n && 0 <= y && y < n);
19         assert(0 <= value_x && value_x <= 1 && 0 <= value_y &&
20             value_y <= 1);
21         g.add(2 * x + (value_x ^ 1), 2 * y + value_y);
22         g.add(2 * y + (value_y ^ 1), 2 * x + value_x);
23     }
24
25     inline vector<int> solve() {
26         int cnt;
27         vector<int> c = find_scc(g, cnt);
28         vector<int> res(n);
29         for (int i = 0; i < n; i++) {
30             if (c[2 * i] == c[2 * i + 1]) {
31                 return vector<int>();
32             }
33             res[i] = (c[2 * i] < c[2 * i + 1]);
34         }
35         return res;
36     };

```

5.25 差分约束系统.cpp

```

1  /**
2      Description:
3      求解方程组  $x_u - x_v \leq w_i$ , 求出的  $x_i$  为满足条件的最大值
4      转化为  $x_u \leq x_v + w_i$ 
5      问题等价于求最短路 (bellmanford或Floyd)
6      即加一条有向边  $add(u, v, w)$ ,  $dist[v] = \min(dist[v], dist[u] + w)$ 
7      求最小值 (满足条件情况下尽量小) 等价于求  $(-x_i)$  最大 (或者转化为求最长
8          路)
9      求非负解只需要添加超级节点  $S$ ,  $S$  向各个点连边 ( $S + 0 \leq x_i$ ), 再设  $dist$ 
10          $[S] = 0$ 
11
12     */
13     void solve() {
14         cin >> n >> m;
15         vector<int> dist(n, 0);
16         vector<vector<PII>> g(n);
17         rep(i, 0, m - 1) {
18             int u, v, w;
19             cin >> u >> v >> w;
20             u--, v--;
21             g[u].eb(v, -w);
22         }
23         bool ok = 1;
24         rep(i, 1, n) {
25             bool upd = 0;
26             rep(u, 0, n - 1) {
27                 for (auto [v, w] : g[u]) {
28                     if (dist[v] < dist[u] + w) {
29                         dist[v] = dist[u] + w;
30                         upd = 1;
31                     }
32                 }
33             }
34             if (!upd) break;
35             // 仍然有约束未满足
36             if (i == n && upd) ok = 0;
37         }
38         if (!ok) {
39             return cout << -1 << '\n', void();
40         }
41         rep(i, 0, n - 1) {
42             cout << dist[i] << " " << '\n'[i == n - 1];
43         }

```

```
41 }
```

6 Math

6.1 binom.cpp

```
1 vector<Mint> fact(1, 1);
2 vector<Mint> inv_fact(1, 1);
3
4 Mint C(int n, int k) {
5     if (k < 0 || k > n) {
6         return 0;
7     }
8     while ((int)fact.size() < n + 1) {
9         fact.push_back(fact.back() * (int)fact.size());
10        inv_fact.push_back(1 / fact.back());
11    }
12    return fact[n] * inv_fact[k] * inv_fact[n - k];
13 }
14
15 const int mod = 1000000007;
16 const int T = 1000000;
17 ll fact[] = {};
18 ll powmod(ll a, ll b) {
19     ll ret = 1;
20     for (; b; b >>= 1) {
21         if (b & 1) ret = ret * a % mod;
22         a = a * a % mod;
23     }
24     return ret;
25 }
26 ll fac(int n) {
27     ll v = fact[n / T];
28     for (int i = n / T * T + 1; i <= n; i++)
29         v = v * i % mod;
30     return v;
31 }
32 ll binom(int n, int m) {
33     if (m < 0 || m > n) return 0;
34     return fac(n) * powmod(fac(m) * fac(n - m) % mod, mod - 2) % mod;
35 }
```

6.2 bsgs.cpp

```
1 int bsgs(int a, int b, int m) { //  $a^x=b(mod\ m)$ 
2     int res = m + 1;
3     int t = sqrt(m) + 2;
4     ll d = powmod(a, t, m);
5     ll cnt = 1;
6     //map<int,int> p;
7     hs.init();
8     for (int i = 1; i <= t; i++) {
9         cnt = cnt * d % m;
10        //if (!p.count(cnt)) p[cnt] = i;
11        if (hs.query(cnt) == -1) hs.insert(cnt, i);
12    }
13    cnt = b;
14    for (int i = 1; i <= t; i++) {
15        cnt = cnt * a % m;
16        //if (p.count(cnt)) res = min(res, p[cnt] * t - i);
17        int tmp = hs.query(cnt);
18        if (tmp != -1) res = min(res, tmp * t - i);
19    }
20    if (res >= m) res = -1;
21    return res;
22 }
```

6.3 cantor.cpp

```
1 ll fac[maxn], A[maxn], w[maxn];
2 void init(int n) {
3     fac[0] = 1;
4     rep(i, 1, n) fac[i] = fac[i - 1] * i % mod;
5 }
6 ll cantor(int w[], int n) {
7     ll ans = 1;
8     for (int i = 1; i <= n; i++) { // can optimize by BIT
9         for (int j = i + 1; j <= n; j++) {
10            if (w[i] > w[j]) A[i]++;
11        }
12    }
13    for (int i = 1; i < n; i++) {
14        ans += A[i] * fac[n - i];
15    }
16    return ans;
17 }
```

```

18
19 void decanter(ll x, int n) { // x->rank n->length
20     x--;
21     vector<int> rest(n, 0);
22     iota(rest.begin(), rest.end(), 1); // rest->1,2,3,4...
23     for (int i = 1; i <= n; i++) {
24         A[i] = x / fac[n - i];
25         x %= fac[n - i];
26     }
27     for (int i = 1; i <= n; i++) {
28         w[i] = rest[A[i]];
29         rest.erase(lower_bound(rest.begin(), rest.end(), w[i]));
30     }
31 }

```

6.4 EXCRT modequ exgcd.cpp

```

1 ll exgcd(ll a, ll b, ll &x, ll &y) {
2     if (b == 0) {
3         x = 1, y = 0;
4         return a;
5     }
6     ll d = exgcd(b, a % b, y, x);
7     y -= (a / b) * x;
8     return d;
9 }
10
11 // 求  $a * x = b \pmod m$  的解
12 ll modequ(ll a, ll b, ll m) {
13     ll x, y;
14     ll d = exgcd(a, m, x, y);
15     if (b % d != 0) return -1;
16     m /= d; a /= d; b /= d;
17     x = x * b % m;
18     if (x < 0) x += m;
19     return x;
20 }
21
22 void merge(ll &a, ll &b, ll c, ll d) {
23     if (a == -1 || b == -1) return;
24     ll x, y;
25     ll g = exgcd(b, d, x, y);
26     if ((c - a) % g != 0) {

```

```

27         a = -1, b = -1;
28         return;
29     }
30     d /= g;
31     ll t = ((c - a) / g) % d * x % d;
32     if (t < 0) t += d;
33     a = b * t + a;
34     b = b * d;
35 }

```

6.5 factor.cpp

```

1 namespace Factor {
2     const int N=1010000;
3     ll C,fac[10010],n,mul,a[1001000];
4     int T,cnt,i,l,prime[N],p[N],psize,_cnt;
5     ll _e[100],_pr[100];
6     vector<ll> d;
7     inline ll mul(ll a,ll b,ll p) {
8         if (p<=1000000000) return a*b%p;
9         else if (p<=1000000000000ll) return (((a*(b>>20)%p)<<20)+(a*(b
10             &&((1<<20)-1))))%p;
11         else {
12             ll d=(ll)floor(a*(long double)b/p+0.5);
13             ll ret=(a*b-d*p)%p;
14             if (ret<0) ret+=p;
15             return ret;
16         }
17     }
18     void prime_table(){
19         int i,j,tot,t1;
20         for (i=1;i<=psize;i++) p[i]=i;
21         for (i=2,tot=0;i<=psize;i++){
22             if (p[i]==i) prime[++tot]=i;
23             for (j=1;j<=tot && (t1=prime[j]*i)<=psize;j++){
24                 p[t1]=prime[j];
25                 if (i%prime[j]==0) break;
26             }
27         }
28     }
29     void init(int ps) {
30         psize=ps;
31         prime_table();

```

```

31     }
32     ll powl(ll a,ll n,ll p) {
33         ll ans=1;
34         for (;n;n>>=1) {
35             if (n&1) ans=mul(ans,a,p);
36             a=mul(a,a,p);
37         }
38         return ans;
39     }
40     bool witness(ll a,ll n) {
41         int t=0;
42         ll u=n-1;
43         for (;~u&1;u>>=1) t++;
44         ll x=powl(a,u,n),_x=0;
45         for (;t;t--) {
46             _x=mul(x,x,n);
47             if (_x==1 && x!=1 && x!=n-1) return 1;
48             x=_x;
49         }
50         return _x!=1;
51     }
52     bool miller(ll n) {
53         if (n<2) return 0;
54         if (n<=psize) return p[n]==n;
55         if (~n&1) return 0;
56         for (int j=0;j<=7;j++) if (witness(rng()%(n-1)+1,n)) return 0;
57         return 1;
58     }
59     ll gcd(ll a,ll b) {
60         ll ret=1;
61         while (a!=0) {
62             if ((~a&1) && (~b&1)) ret<<=1,a>>=1,b>>=1;
63             else if (~a&1) a>>=1; else if (~b&1) b>>=1;
64             else {
65                 if (a<b) swap(a,b);
66                 a-=b;
67             }
68         }
69         return ret*b;
70     }
71     ll rho(ll n) {
72         while (1) {
73             ll X=rng()%n,Y,Z,T=1,*lY=a,*lX=lY;

```

```

74             int tmp=20;
75             C=rng()%10+3;
76             X=mul(X,X,n)+C;*(lY++)=X;lX++;
77             Y=mul(X,X,n)+C;*(lY++)=Y;
78             for(;X!=Y;) {
79                 ll t=X-Y+n;
80                 Z=mul(T,t,n);
81                 if(Z==0) return gcd(T,n);
82                 tmp--;
83                 if (tmp==0) {
84                     tmp=20;
85                     Z=gcd(Z,n);
86                     if (Z!=1 && Z!=n) return Z;
87                 }
88                 T=Z;
89                 Y=*(lY++)=mul(Y,Y,n)+C;
90                 Y=*(lY++)=mul(Y,Y,n)+C;
91                 X=*(lX++);
92             }
93         }
94     }
95     void _factor(ll n) {
96         for (int i=0;i<cnt;i++) {
97             if (n%fac[i]==0) n/=fac[i],fac[cnt++]=fac[i];}
98         if (n<=psize) {
99             for (;n!=1;n/=p[n]) fac[cnt++]=p[n];
100             return;
101         }
102         if (miller(n)) fac[cnt++]=n;
103         else {
104             ll x=rho(n);
105             _factor(x);_factor(n/x);
106         }
107     }
108     void dfs(ll x,int dep) {
109         if (dep==_cnt) d.pb(x);
110         else {
111             dfs(x,dep+1);
112             for (int i=1;i<=_e[dep];i++) dfs(x*_pr[dep],dep+1);
113         }
114     }
115     void norm() {
116         sort(fac,fac+cnt);

```

```

117     _cnt=0;
118     rep(i,0,cnt-1) if (i==0||fac[i]!=fac[i-1]) _pr[_cnt]=fac[i],_e[_cnt
        ++]=1;
119     else _e[_cnt-1]++;
120 }
121 vector<ll> getd() {
122     d.clear();
123     dfs(1,0);
124     return d;
125 }
126 vector<ll> factor(ll n) {
127     cnt=0;
128     _factor(n);
129     norm();
130     return getd();
131 }
132 vector<PLL> factorG(ll n) {
133     cnt=0;
134     _factor(n);
135     norm();
136     vector<PLL> d;
137     rep(i,0,_cnt-1) d.pb(mp(_pr[i],_e[i]));
138     return d;
139 }
140 bool is_primitive(ll a,ll p) {
141     assert(miller(p));
142     vector<PLL> D=factorG(p-1);
143     rep(i,0,SZ(D)-1) if (powl(a,(p-1)/D[i].fi,p)==1) return 0;
144     return 1;
145 }
146 ll phi(ll n) {
147     auto d=factorG(n);
148     for (auto p:d) n=n/p.fi*(p.fi-1);
149     return n;
150 }
151 }

```

6.6 fft.cpp

```

1 namespace fft {
2     typedef double dbl;
3
4     struct num {

```

```

5     dbl x, y;
6     num() { x = y = 0; }
7     num(dbl x, dbl y) : x(x), y(y) { }
8 };
9
10 inline num operator+(num a, num b) { return num(a.x + b.x, a.y + b.y); }
11 inline num operator-(num a, num b) { return num(a.x - b.x, a.y - b.y); }
12 inline num operator*(num a, num b) { return num(a.x * b.x - a.y * b.y, a.x
    * b.y + a.y * b.x); }
13 inline num conj(num a) { return num(a.x, -a.y); }
14
15 int base = 1;
16 vector<num> roots = {{0, 0}, {1, 0}};
17 vector<int> rev = {0, 1};
18
19 const dbl PI = acosl(-1.0);
20
21 void ensure_base(int nbase) {
22     if (nbase <= base) {
23         return;
24     }
25     rev.resize(1 << nbase);
26     for (int i = 0; i < (1 << nbase); i++) {
27         rev[i] = (rev[i >> 1] >> 1) + ((i & 1) << (nbase - 1));
28     }
29     roots.resize(1 << nbase);
30     while (base < nbase) {
31         dbl angle = 2 * PI / (1 << (base + 1));
32         // num z(cos(angle), sin(angle));
33         for (int i = 1 << (base - 1); i < (1 << base); i++) {
34             roots[i << 1] = roots[i];
35             // roots[(i << 1) + 1] = roots[i] * z;
36             dbl angle_i = angle * (2 * i + 1 - (1 << base));
37             roots[(i << 1) + 1] = num(cos(angle_i), sin(angle_i));
38         }
39         base++;
40     }
41 }
42
43 void fft(vector<num> &a, int n = -1) {
44     if (n == -1) {
45         n = a.size();
46     }

```

```

47     assert((n & (n - 1)) == 0);
48     int zeros = __builtin_ctz(n);
49     ensure_base(zeros);
50     int shift = base - zeros;
51     for (int i = 0; i < n; i++) {
52         if (i < (rev[i] >> shift)) {
53             swap(a[i], a[rev[i] >> shift]);
54         }
55     }
56     /* for (int k = 1; k < n; k <= 1) {
57         for (int i = 0; i < n; i += 2 * k) {
58             for (int j = 0; j < k; j++) {
59                 num z = a[i + j + k] * roots[j + k];
60                 a[i + j + k] = a[i + j] - z;
61                 a[i + j] = a[i + j] + z;
62             }
63         }
64     }*/
65     for (int len = 1; len < n; len <= 1) {
66         for (int i = 0; i < n; i += 2 * len) {
67             for (int j = i, k = i + len; j < i + len; j++, k++) {
68                 num z = a[k] * roots[k - i];
69                 a[k] = a[j] - z;
70                 a[j] = a[j] + z;
71             }
72         }
73     }
74 }
75
76 vector<num> fa, fb;
77
78 vector<long long> multiply(vector<int> &a, vector<int> &b) {
79     int need = a.size() + b.size() - 1;
80     int nbase = 0;
81     while ((1 << nbase) < need) nbase++;
82     ensure_base(nbase);
83     int sz = 1 << nbase;
84     if (sz > (int) fa.size()) {
85         fa.resize(sz);
86     }
87     for (int i = 0; i < sz; i++) {
88         int x = (i < (int) a.size() ? a[i] : 0);
89         int y = (i < (int) b.size() ? b[i] : 0);

```

```

90         fa[i] = num(x, y);
91     }
92     fft(fa, sz);
93     num r(0, -0.25 / sz);
94     for (int i = 0; i <= (sz >> 1); i++) {
95         int j = (sz - i) & (sz - 1);
96         num z = (fa[j] * fa[j] - conj(fa[i] * fa[i])) * r;
97         if (i != j) {
98             fa[j] = (fa[i] * fa[i] - conj(fa[j] * fa[j])) * r;
99         }
100        fa[i] = z;
101    }
102    fft(fa, sz);
103    vector<long long> res(need);
104    for (int i = 0; i < need; i++) {
105        res[i] = fa[i].x + 0.5;
106    }
107    return res;
108 }
109
110 vector<int> multiply_mod(vector<int> &a, vector<int> &b, int m, int eq =
111     0) {
112     int need = a.size() + b.size() - 1;
113     int nbase = 0;
114     while ((1 << nbase) < need) nbase++;
115     ensure_base(nbase);
116     int sz = 1 << nbase;
117     if (sz > (int) fa.size()) {
118         fa.resize(sz);
119     }
120     for (int i = 0; i < (int) a.size(); i++) {
121         int x = (a[i] % m + m) % m;
122         fa[i] = num(x & ((1 << 15) - 1), x >> 15);
123     }
124     fill(fa.begin() + a.size(), fa.begin() + sz, num {0, 0});
125     fft(fa, sz);
126     if (eq) {
127         copy(fa.begin(), fa.begin() + sz, fb.begin());
128     } else {
129         if (sz > (int) fb.size()) {
130             fb.resize(sz);
131         }
132         for (int i = 0; i < (int) b.size(); i++) {

```

```

132     int x = (b[i] % m + m) % m;
133     fb[i] = num(x & ((1 << 15) - 1), x >> 15);
134 }
135 fill(fb.begin() + b.size(), fb.begin() + sz, num{0, 0});
136 fft(fb, sz);
137 }
138 dbl ratio = 0.25 / sz;
139 num r2(0, -1);
140 num r3(ratio, 0);
141 num r4(0, -ratio);
142 num r5(0, 1);
143 for (int i = 0; i <= (sz >> 1); i++) {
144     int j = (sz - i) & (sz - 1);
145     num a1 = (fa[i] + conj(fa[j]));
146     num a2 = (fa[i] - conj(fa[j])) * r2;
147     num b1 = (fb[i] + conj(fb[j])) * r3;
148     num b2 = (fb[i] - conj(fb[j])) * r4;
149     if (i != j) {
150         num c1 = (fa[j] + conj(fa[i]));
151         num c2 = (fa[j] - conj(fa[i])) * r2;
152         num d1 = (fb[j] + conj(fb[i])) * r3;
153         num d2 = (fb[j] - conj(fb[i])) * r4;
154         fa[i] = c1 * d1 + c2 * d2 * r5;
155         fb[i] = c1 * d2 + c2 * d1;
156     }
157     fa[j] = a1 * b1 + a2 * b2 * r5;
158     fb[j] = a1 * b2 + a2 * b1;
159 }
160 fft(fa, sz);
161 fft(fb, sz);
162 vector<int> res(need);
163 for (int i = 0; i < need; i++) {
164     long long aa = fa[i].x + 0.5;
165     long long bb = fb[i].x + 0.5;
166     long long cc = fa[i].y + 0.5;
167     res[i] = (aa + ((bb % m) << 15) + ((cc % m) << 30)) % m;
168 }
169 return res;
170 }
171
172 vector<int> square_mod(vector<int> &a, int m) {
173     return multiply_mod(a, a, m, 1);
174 }

```

```

175 // fft::multiply uses dbl, outputs vector<long long> of rounded values
176 // fft::multiply_mod might work for res.size() up to 2^21
177 // typedef long double dbl;          =>          up to 2^25 (but takes a lot
           of memory)
178 };

```

6.7 fftfast.cpp

```

1 // FFT_MAXN = 2^k
2 // fft_init() to precalc FFT_MAXN-th roots
3
4 typedef long double db;
5 const int FFT_MAXN = 262144;
6 const int N = 3.1e5;
7 const db pi = acos(-1.);
8 struct cp {
9     db a, b;
10     cp operator+(const cp &y) const { return (cp){a + y.a, b + y.b}; }
11     cp operator-(const cp &y) const { return (cp){a - y.a, b - y.b}; }
12     cp operator*(const cp &y) const { return (cp){a * y.a - b * y.b, a *
           y.b + b * y.a}; }
13     cp operator!() const { return (cp){a, -b}; };
14 } nw[FFT_MAXN + 1];
15 int bitrev[FFT_MAXN];
16 void dft(cp *a, int n, int flag = 1) {
17     int d = 0;
18     while ((1 << d) * n != FFT_MAXN) d++;
19     rep(i, 0, n - 1) if (i < (bitrev[i] >> d)) swap(a[i], a[bitrev[i] >>
           d]);
20     for (int l = 2; l <= n; l <= 1) {
21         int del = FFT_MAXN / l * flag;
22         for (int i = 0; i < n; i += l) {
23             cp *le = a + i, *ri = a + i + (l >> 1), *w = flag ==
                 1 ? nw : nw + FFT_MAXN;
24             rep(k, 0, l / 2 - 1) {
25                 cp ne = *ri * *w;
26                 *ri = *le - ne, *le = *le + ne;
27                 le++, ri++, w += del;
28             }
29         }
30     }
31     if (flag != 1) rep(i, 0, n - 1) a[i].a /= n, a[i].b /= n;
32 }

```



```

33 void fft_init() {
34     int L = 0;
35     while ((1 << L) != FFT_MAXN) L++;
36     bitrev[0] = 0;
37     rep(i, 1, FFT_MAXN - 1) bitrev[i] = bitrev[i >> 1] >> 1 | ((i & 1)
        << (L - 1));
38     nw[0] = nw[FFT_MAXN] = (cp){1, 0};
39     rep(i, 0, FFT_MAXN)
40     nw[i] = (cp){cosl(2 * pi / FFT_MAXN * i), sinl(2 * pi / FFT_MAXN * i
        )}; // very slow
41 }
42
43 void convo(db *a, int n, db *b, int m, db *c) {
44     static cp f[FFT_MAXN >> 1], g[FFT_MAXN >> 1], t[FFT_MAXN >> 1];
45     int N = 2;
46     while (N <= n + m) N <<= 1;
47     rep(i, 0, N - 1) if (i & 1) {
48         f[i >> 1].b = (i <= n) ? a[i] : 0.0;
49         g[i >> 1].b = (i <= m) ? b[i] : 0.0;
50     }
51     else {
52         f[i >> 1].a = (i <= n) ? a[i] : 0.0;
53         g[i >> 1].a = (i <= m) ? b[i] : 0.0;
54     }
55     dft(f, N >> 1);
56     dft(g, N >> 1);
57     int del = FFT_MAXN / (N >> 1);
58     cp qua = (cp){0, 0.25}, one = (cp){1, 0}, four = (cp){4, 0}, *w = nw
        ;
59     rep(i, 0, N / 2 - 1) {
60         int j = i ? (N >> 1) - i : 0;
61         t[i] = (four * !(f[j] * g[j]) - (!f[j] - f[i]) * (!g[j] - g[
            i]) * (one + *w)) * qua;
62         w += del;
63     }
64     dft(t, N >> 1, -1);
65     rep(i, 0, n + m) c[i] = (i & 1) ? t[i >> 1].a : t[i >> 1].b;
66 }
67
68 int mo;
69 void mul(int *a, int *b, int n) { // n<=N, 0<=a[i],b[i]<mo
70     static cp f[N], g[N], t[N], r[N];
71     int nn = 2;

```

```

72     while (nn <= n + n) nn <<= 1;
73     rep(i, 0, nn - 1) {
74         f[i] = (i <= n) ? (cp){(db)(a[i] >> 15), (db)(a[i] & 32767)}
            : (cp){0, 0};
75         g[i] = (i <= n) ? (cp){(db)(b[i] >> 15), (db)(b[i] & 32767)}
            : (cp){0, 0};
76     }
77     swap(n, nn);
78     dft(f, n, 1);
79     dft(g, n, 1);
80     rep(i, 0, n - 1) {
81         int j = i ? n - i : 0;
82         t[i] = ((f[i] + !f[j]) * (!g[j] - g[i]) + (!f[j] - f[i]) * (
            g[i] + !g[j])) * (cp){0, 0.25};
83         r[i] = (!f[j] - f[i]) * (!g[j] - g[i]) * (cp){-0.25, 0} + (
            cp){0, 0.25} * (f[i] + !f[j]) * (g[i] + !g[j]));
84     }
85     dft(t, n, -1);
86     dft(r, n, -1);
87     rep(i, 0, n - 1)
88     a[i] = ((ll(t[i].a + 0.5) % mo << 15) + ll(r[i].a + 0.5) + (ll(r[i].
        b + 0.5) % mo << 30)) % mo;
89 }

```

6.8 fftnew.cpp

```

1 namespace fft {
2
3 typedef double dbl;
4
5 struct num {
6     dbl x, y;
7     num() { x = y = 0; }
8     num(dbl x_, dbl y_) : x(x_), y(y_) {}
9 };
10
11 inline num operator+(num a, num b) { return num(a.x + b.x, a.y + b.y); }
12 inline num operator-(num a, num b) { return num(a.x - b.x, a.y - b.y); }
13 inline num operator*(num a, num b) { return num(a.x * b.x - a.y * b.y, a.x *
        b.y + a.y * b.x); }
14 inline num conj(num a) { return num(a.x, -a.y); }
15
16 int base = 1;

```

```

17 vector<num> roots = {{0, 0}, {1, 0}};
18 vector<int> rev = {0, 1};
19
20 const dbl PI = static_cast<dbl>(acosl(-1.0));
21
22 void ensure_base(int nbase) {
23     if (nbase <= base) {
24         return;
25     }
26     rev.resize(1 << nbase);
27     for (int i = 0; i < (1 << nbase); i++) {
28         rev[i] = (rev[i >> 1] >> 1) + ((i & 1) << (nbase - 1));
29     }
30     roots.resize(1 << nbase);
31     while (base < nbase) {
32         dbl angle = 2 * PI / (1 << (base + 1));
33         //      num z(cos(angle), sin(angle));
34         for (int i = 1 << (base - 1); i < (1 << base); i++) {
35             roots[i << 1] = roots[i];
36             //      roots[(i << 1) + 1] = roots[i] * z;
37             dbl angle_i = angle * (2 * i + 1 - (1 << base));
38             roots[(i << 1) + 1] = num(cos(angle_i), sin(angle_i));
39         }
40         base++;
41     }
42 }
43
44 void fft(vector<num>& a, int n = -1) {
45     if (n == -1) {
46         n = (int) a.size();
47     }
48     assert((n & (n - 1)) == 0);
49     int zeros = __builtin_ctz(n);
50     ensure_base(zeros);
51     int shift = base - zeros;
52     for (int i = 0; i < n; i++) {
53         if (i < (rev[i] >> shift)) {
54             swap(a[i], a[rev[i] >> shift]);
55         }
56     }
57     for (int k = 1; k < n; k <= 1) {
58         for (int i = 0; i < n; i += 2 * k) {
59             for (int j = 0; j < k; j++) {

```

```

60         num z = a[i + j + k] * roots[j + k];
61         a[i + j + k] = a[i + j] - z;
62         a[i + j] = a[i + j] + z;
63     }
64 }
65 }
66 }
67
68 vector<num> fa, fb;
69
70 vector<int64_t> square(const vector<int>& a) {
71     if (a.empty()) {
72         return {};
73     }
74     int need = (int) a.size() + (int) a.size() - 1;
75     int nbase = 1;
76     while ((1 << nbase) < need) nbase++;
77     ensure_base(nbase);
78     int sz = 1 << nbase;
79     if ((sz >> 1) > (int) fa.size()) {
80         fa.resize(sz >> 1);
81     }
82     for (int i = 0; i < (sz >> 1); i++) {
83         int x = (2 * i < (int) a.size() ? a[2 * i] : 0);
84         int y = (2 * i + 1 < (int) a.size() ? a[2 * i + 1] : 0);
85         fa[i] = num(x, y);
86     }
87     fft(fa, sz >> 1);
88     num r(1.0 / (sz >> 1), 0.0);
89     for (int i = 0; i <= (sz >> 2); i++) {
90         int j = ((sz >> 1) - i) & ((sz >> 1) - 1);
91         num fe = (fa[i] + conj(fa[j])) * num(0.5, 0);
92         num fo = (fa[i] - conj(fa[j])) * num(0, -0.5);
93         num aux = fe * fe + fo * fo * roots[(sz >> 1) + i] * roots[(sz >> 1) + i
94             ];
95         num tmp = fe * fo;
96         fa[i] = r * (conj(aux) + num(0, 2) * conj(tmp));
97         fa[j] = r * (aux + num(0, 2) * tmp);
98     }
99     fft(fa, sz >> 1);
100     vector<int64_t> res(need);
101     for (int i = 0; i < need; i++) {
102         res[i] = llround(i % 2 == 0 ? fa[i >> 1].x : fa[i >> 1].y);

```

```

102     }
103     return res;
104 }
105
106 vector<int64_t> multiply(const vector<int>& a, const vector<int>& b) {
107     if (a.empty() || b.empty()) {
108         return {};
109     }
110     if (a == b) {
111         return square(a);
112     }
113     int need = (int) a.size() + (int) b.size() - 1;
114     int nbase = 1;
115     while ((1 << nbase) < need) nbase++;
116     ensure_base(nbase);
117     int sz = 1 << nbase;
118     if (sz > (int) fa.size()) {
119         fa.resize(sz);
120     }
121     for (int i = 0; i < sz; i++) {
122         int x = (i < (int) a.size() ? a[i] : 0);
123         int y = (i < (int) b.size() ? b[i] : 0);
124         fa[i] = num(x, y);
125     }
126     fft(fa, sz);
127     num r(0, -0.25 / (sz >> 1));
128     for (int i = 0; i <= (sz >> 1); i++) {
129         int j = (sz - i) & (sz - 1);
130         num z = (fa[j] * fa[j] - conj(fa[i] * fa[i])) * r;
131         fa[j] = (fa[i] * fa[i] - conj(fa[j] * fa[j])) * r;
132         fa[i] = z;
133     }
134     for (int i = 0; i < (sz >> 1); i++) {
135         num A0 = (fa[i] + fa[i + (sz >> 1)]) * num(0.5, 0);
136         num A1 = (fa[i] - fa[i + (sz >> 1)]) * num(0.5, 0) * roots[(sz >> 1) + i];
137         fa[i] = A0 + A1 * num(0, 1);
138     }
139     fft(fa, sz >> 1);
140     vector<int64_t> res(need);
141     for (int i = 0; i < need; i++) {
142         res[i] = llround(i % 2 == 0 ? fa[i >> 1].x : fa[i >> 1].y);
143     }

```

```

144     return res;
145 }
146
147 vector<int> multiply_mod(const vector<int>& a, const vector<int>& b, int m)
148 {
149     if (a.empty() || b.empty()) {
150         return {};
151     }
152     int eq = (a.size() == b.size() && a == b);
153     int need = (int) a.size() + (int) b.size() - 1;
154     int nbase = 0;
155     while ((1 << nbase) < need) nbase++;
156     ensure_base(nbase);
157     int sz = 1 << nbase;
158     if (sz > (int) fa.size()) {
159         fa.resize(sz);
160     }
161     for (int i = 0; i < (int) a.size(); i++) {
162         int x = (a[i] % m + m) % m;
163         fa[i] = num(x & ((1 << 15) - 1), x >> 15);
164     }
165     fill(fa.begin() + a.size(), fa.begin() + sz, num {0, 0});
166     fft(fa, sz);
167     if (sz > (int) fb.size()) {
168         fb.resize(sz);
169     }
170     if (eq) {
171         copy(fa.begin(), fa.begin() + sz, fb.begin());
172     } else {
173         for (int i = 0; i < (int) b.size(); i++) {
174             int x = (b[i] % m + m) % m;
175             fb[i] = num(x & ((1 << 15) - 1), x >> 15);
176         }
177         fill(fb.begin() + b.size(), fb.begin() + sz, num {0, 0});
178         fft(fb, sz);
179     }
180     dbl ratio = 0.25 / sz;
181     num r2(0, -1);
182     num r3(ratio, 0);
183     num r4(0, -ratio);
184     num r5(0, 1);
185     for (int i = 0; i <= (sz >> 1); i++) {
186         int j = (sz - i) & (sz - 1);

```

```

186     num a1 = (fa[i] + conj(fa[j]));
187     num a2 = (fa[i] - conj(fa[j])) * r2;
188     num b1 = (fb[i] + conj(fb[j])) * r3;
189     num b2 = (fb[i] - conj(fb[j])) * r4;
190     if (i != j) {
191         num c1 = (fa[j] + conj(fa[i]));
192         num c2 = (fa[j] - conj(fa[i])) * r2;
193         num d1 = (fb[j] + conj(fb[i])) * r3;
194         num d2 = (fb[j] - conj(fb[i])) * r4;
195         fa[i] = c1 * d1 + c2 * d2 * r5;
196         fb[i] = c1 * d2 + c2 * d1;
197     }
198     fa[j] = a1 * b1 + a2 * b2 * r5;
199     fb[j] = a1 * b2 + a2 * b1;
200 }
201 fft(fa, sz);
202 fft(fb, sz);
203 vector<int> res(need);
204 for (int i = 0; i < need; i++) {
205     int64_t aa = llround(fa[i].x);
206     int64_t bb = llround(fb[i].x);
207     int64_t cc = llround(fa[i].y);
208     res[i] = static_cast<int>((aa + ((bb % m) << 15) + ((cc % m) << 30)) % m
209 );
210 }
211 return res;
212 }
213 } // namespace fft

```

6.9 FST.cpp

```

1 void fst(VI &a, bool inv) {
2     for (int n = SZ(a), step = 1; step < n; step *= 2) {
3         for (int i = 0; i < n; i += 2 * step) rep(j, i, i + step - 1) {
4             int &u = a[j], &v = a[j + step];
5             tie(u, v) =
6                 inv ? PII(v - u, u) : PII(v, u + v); // AND
7             inv ? PII(v, u - v) : PII(u + v, u); // OR
8             PII(u + v, u - v); // XOR
9         }
10    }
11    if (inv) for (auto &x : a) x /= SZ(a); // XOR only

```

```

12 }
13 VI conv(VI a, VI b) {
14     fst(a, 0), fst(b, 0);
15     rep(i, 0, SZ(a) - 1) a[i] = a[i] * b[i];
16     fst(a, 1); return a;
17 }

```

6.10 FWT.cpp

```

1 ll f[maxn], g[maxn], h[maxn];
2 int main() {
3     for (int i = 0; i < n; i++) {
4         for (int j = 0; j < bit(n); j++) {
5             if ((j & bit(i)) == 0) {
6                 f[j] += f[j + bit(i)];
7                 g[j] += g[j + bit(i)];
8             }
9         }
10    }
11    for (int i = 0; i < bit(n); i++) {
12        f[i] %= mod;
13        g[i] %= mod;
14        h[i] = f[i] * g[i] % mod;
15    }
16    for (int i = 0; i < n; i++) {
17        for (int j = 0; j < bit(n); j++) {
18            if ((j & bit(i)) == 0)
19                h[j] -= h[j + bit(i)];
20        }
21    }
22    for (int i = 0; i < bit(n); i++) {
23        h[i] %= mod;
24        if (h[i] < 0) h[i] += mod;
25    }
26
27    ll ans = 0;
28    rep(i, 0, bit(n) - 1) ans ^= h[i];
29    cout << ans << '\n';
30 }

```

6.11 gauss(合数).cpp

```

1 void gauss(int n) {

```

```

2   int ans = 1;
3   //rep(i,1,n) rep(j,1,n) p[i][j]%mod;
4   for (int i = 1; i <= n; i++) {
5       for (int j = i + 1; j <= n; j++) {
6           int x = i, y = j;
7           while (p[x][i]) {
8               int t = p[y][i] / p[x][i];
9               for (int k = i; k <= n; k++)
10                  p[y][k] = (p[y][k] - p[x][k] * t) % mod;
11               swap(x, y);
12           }
13           if (x == i) {
14               for (int k = i; k <= n; k++) swap(p[i][k], p[j][k]);
15               ans = -ans;
16           }
17       }
18   }
19 }

```

6.12 gauss.cpp

```

1  ll f[N][N];
2  ll v[N], a[N];
3  void gauss() {
4      for (int i = 1; i <= n; i++) {
5          for (int j = i; j <= n; j++) {
6              if (f[j][i] > f[i][i]) {
7                  swap(v[i], v[j]);
8                  for (int k = 1; k <= n; k++)
9                      swap(f[j][k], f[i][k]);
10             }
11         }
12         for (int j = i + 1; j <= n; j++) {
13             if (f[j][i]) {
14                 int delta = f[j][i] * fpow(f[i][i], mod - 2) % mod;
15                 for (int k = i; k <= n; k++) {
16                     f[j][k] -= f[i][k] * delta % mod;
17                     if (f[j][k] < 0)
18                         f[j][k] += mod;
19                 }
20                 v[j] -= v[i] * delta % mod;
21                 if (v[j] < mod)
22                     v[j] += mod;

```

```

23         }
24     }
25 }
26 for (int j = n; j > 0; j--) {
27     for (int k = j + 1; k <= n; k++) {
28         v[j] -= f[j][k] * a[k] % mod;
29         if (v[j] < 0)
30             v[j] += mod;
31     }
32     a[j] = v[j] * fpow(f[j][j], mod - 2) % mod;
33 }
34 }

```

6.13 linearbasis.cpp

```

1  struct linear_base {
2      ll w[64];
3      ll zero = 0;
4      ll tot = -1;
5      void clear() {
6          rep(i, 0, 63) w[i] = 0;
7          zero = 0;
8          tot = -1;
9      }
10     void insert(ll x) {
11         for (int i = 62; i >= 0; i--) {
12             if (x & bit(i))
13                 if (!w[i]) {w[i] = x; return;}
14                 else x ^= w[i];
15         }
16         zero++;
17     }
18     void build() {
19         rep(i, 0, 63) rep(j, 0, i - 1) {
20             if (w[i]&bit(j)) w[i] ^= w[j];
21         }
22         for (int i = 0; i <= 62; i++) {
23             if (w[i] != 0) w[++tot] = w[i];
24         }
25     }
26     ll qmax() {
27         ll res = 0;
28         for (int i = 62; i >= 0; i--) {

```

```

29         res = max(res, res ^ w[i]);
30     }
31     return res;
32 }
33 bool check(ll x) {
34     for (int i = 62; i >= 0; i--) {
35         if (x & bit(i))
36             if (!w[i]) return false;
37             else x ^= w[i];
38     }
39     return true;
40 }
41 ll query(ll k) {
42     ll res = 0;
43     // if (zero) k-=1;
44     // if (k >= bit(tot)) return -1;
45     for (int i = tot; i >= 0; i--) {
46         if (k & bit(i)) {
47             res = max(res, res ^ w[i]);
48         } else {
49             res = min(res, res ^ w[i]);
50         }
51     }
52     return res;
53 }
54 };

```

6.14 lucas.cpp

```

1 ll fac[maxn], fnv[maxn];
2
3 ll binom(ll a, ll b) {
4     if (b > a || b < 0) return 0;
5     return fac[a] * fnv[a - b] % p * fnv[b] % p;
6 }
7
8 ll lucas(ll a, ll b, ll p) {
9     ll ans = 1;
10    while (a > 0 || b > 0) {
11        ans = (ans * binom(a % p, b % p)) % p;
12        a /= p, b /= p;
13    }
14    return ans;

```

```

15 }
16
17 int main() {
18     cin >> p >> T;
19     fac[0] = 1;
20     rep(i, 1, p - 1) fac[i] = fac[i - 1] * i % p;
21     fnv[p - 1] = powmod(fac[p - 1], p - 2, p);
22     per(i, p - 2, 0) fnv[i] = fnv[i + 1] * (i + 1) % p;
23     assert(fnv[0] == 1);
24 }

```

6.15 mathdiv.cpp

```

1 ll floor_div(ll x, ll y) {
2     assert(y != 0);
3     if (y < 0) {
4         y = -y;
5         x = -x;
6     }
7     if (x >= 0) return x / y;
8     return (x + 1) / y - 1;
9 }
10 ll ceil_div(ll x, ll y) {
11     assert(y != 0);
12     if (y < 0) {
13         y = -y;
14         x = -x;
15     }
16     if (x <= 0) return x / y;
17     return (x - 1) / y + 1;
18 }

```

6.16 matrix.cpp

```

1 template <typename T>
2 vector<vector<T>> operator*(const vector<vector<T>>& a, const vector<vector<
    T>>& b) {
3     if (a.empty() || b.empty()) {
4         return {};
5     }
6     vector<vector<T>> c(a.size(), vector<T>(b[0].size()));
7     for (int i = 0; i < static_cast<int>(c.size()); i++) {
8         for (int j = 0; j < static_cast<int>(c[0].size()); j++) {

```

```

9             c[i][j] = 0;
10            for (int k = 0; k < static_cast<int>(b.size()); k++)
11                {
12                    c[i][j] += a[i][k] * b[k][j];
13                }
14        }
15        return c;
16    }
17
18    template <typename T>
19    vector<vector<T>>& operator*=(vector<vector<T>>& a, const vector<vector<T>>&
20        b) {
21        return a = a * b;
22    }
23
24    template <typename T, typename U>
25    vector<vector<T>> power(const vector<vector<T>>& a, const U& b) {
26        assert(b >= 0);
27        vector<U> binary;
28        U bb = b;
29        while (bb > 0) {
30            binary.push_back(bb & 1);
31            bb >>= 1;
32        }
33        vector<vector<T>> res(a.size(), vector<T>(a.size()));
34        for (int i = 0; i < static_cast<int>(a.size()); i++) {
35            res[i][i] = 1;
36        }
37        for (int j = (int)binary.size() - 1; j >= 0; j--) {
38            res *= res;
39            if (binary[j] == 1) {
40                res *= a;
41            }
42        }
43        return res;
44    }

```

6.17 matrixfast.cpp

```

1 Description: Basic operations on square matrices.
2 Usage: Matrix<int, 3> A;
3 A.d = {{{{1, 2, 3}}, {{4, 5, 6}}, {{7, 8, 9}}}};

```

```

4 vector<int> vec = {1, 2, 3};
5 vec = (A^N) * vec;
6
7 template<class T, int N> struct Matrix {
8     typedef Matrix M;
9     array<array<T, N>, N> d{};
10    M operator*(const M& m) const {
11        M a;
12        rep(i, 0, N) rep(j, 0, N)
13            rep(k, 0, N) a.d[i][j] += d[i][k] * m.d[k][j];
14        return a;
15    }
16    vector<T> operator*(const vector<T>& vec) const {
17        vector<T> ret(N);
18        rep(i, 0, N) rep(j, 0, N) ret[i] += d[i][j] * vec[j];
19        return ret;
20    }
21    M operator^(ll p) const {
22        assert(p >= 0);
23        M a, b(*this);
24        rep(i, 0, N) a.d[i][i] = 1;
25        while (p) {
26            if (p & 1) a = a * b;
27            b = b * b;
28            p >>= 1;
29        }
30        return a;
31    }
32 };

```

6.18 MillerRabbin pollard modmul.cpp

```

1 /*ModMulLL.h
2 Description: Calculate  $a \cdot b \bmod c$  (or  $a$ 
3  $b \bmod c$ ) for  $0 \leq a, b < c \leq 7.2 \cdot 10^{18}$ 
4 Time:  $O(1)$  for modmul,  $O(\log b)$  for modpow*/
5 /*ull modmul(ull a, ull b, ull M) {
6     ll ret = a * b - M * ull(1.L / M * a * b);
7     return ret + M * (ret < 0) - M * (ret >= (ll)M);
8 }
9 ull modpow(ull b, ull e, ull mod) {
10     ull ans = 1;
11     for (; e; b = modmul(b, b, mod), e /= 2)

```

```

12     if (e & 1) ans = modmul(ans, b, mod);
13     return ans;
14 }*/
15 ll modmul(ll a, ll b, ll m) {
16     a %= m, b %= m;
17     ll d = ((ldb)a * b / m);
18     d = a * b - d * m;
19     if (d >= m) d -= m;
20     if (d < 0) d += m;
21     return d;
22 }
23 ll modpow(ll a, ll b, ll p) {
24     ll ans = 1;
25     while (b) {
26         if (b & 1) ans = modmul(ans, a, p);
27         a = modmul(a, a, p); b >>= 1;
28     } return ans;
29 }
30 /*MillerRabin.h
31 Description: Deterministic Miller-Rabin primality test. Guaranteed to
32 work for numbers up to  $7 \cdot 10^{18}$ ; for larger numbers, use Python and extend A
33 randomly.
34 Time: 7 times the complexity of  $a^b \bmod c$ .*/
34 bool isPrime(ll n) {
35     if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
36     ll A[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022},
37     s = __builtin_ctzll(n - 1), d = n >> s;
38     for (ll a : A) { // ^ count trailing zeroes
39         ll p = modpow(a % n, d, n), i = s;
40         while (p != 1 && p != n - 1 && a % n && i--)
41             p = modmul(p, p, n);
42         if (p != n - 1 && i != s) return 0;
43     }
44     return 1;
45 }
46 /*Factor.h
47 Description: Pollard-rho randomized factorization algorithm. Returns
48 prime factors of a number, in arbitrary order (e.g. 2299 -> {11, 19, 11}).
49 Time:  $O(n^{1/4})$ , less for numbers with small factors.*/
50 ll pollard(ll n) {
51     auto f = [n](ll x) { return modmul(x, x, n) + 1; };
52     ll x = 0, y = 0, t = 30, prd = 2, i = 1, q;
53     while (t++ % 40 || __gcd(prd, n) == 1) {

```

```

54         if (x == y) x = ++i, y = f(x);
55         if ((q = modmul(prd, max(x, y) - min(x, y), n))) prd = q;
56         x = f(x), y = f(f(y));
57     }
58     return __gcd(prd, n);
59 }
60 vector<ll> factor(ll n) {
61     if (n == 1) return {};
62     if (isPrime(n)) return {n};
63     ll x = pollard(n);
64     auto l = factor(x), r = factor(n / x);
65     l.insert(l.end(), all(r));
66     return l;
67 }

```

6.19 ntt(polynomial).cpp

```

1 #include<bits/stdc++.h>
2 using namespace std;
3
4 const int mod = 998244353;
5
6 inline void add(int &x, int y) {
7     x += y;
8     if (x >= mod) {
9         x -= mod;
10    }
11 }
12
13 inline void sub(int &x, int y) {
14     x -= y;
15     if (x < 0) {
16         x += mod;
17    }
18 }
19
20 inline int mul(int x, int y) {
21     return (long long) x * y % mod;
22 }
23
24 inline int power(int x, int y) {
25     int res = 1;
26     for (; y; y >>= 1, x = mul(x, x)) {

```



```

27     if (y & 1) {
28         res = mul(res, x);
29     }
30 }
31 return res;
32 }
33
34 inline int inv(int a) {
35     a %= mod;
36     if (a < 0) {
37         a += mod;
38     }
39     int b = mod, u = 0, v = 1;
40     while (a) {
41         int t = b / a;
42         b -= t * a;
43         swap(a, b);
44         u -= t * v;
45         swap(u, v);
46     }
47     if (u < 0) {
48         u += mod;
49     }
50     return u;
51 }
52
53 namespace ntt {
54     int base = 1, root = -1, max_base = -1;
55     vector<int> rev = {0, 1}, roots = {0, 1};
56
57     void init() {
58         int temp = mod - 1;
59         max_base = 0;
60         while (temp % 2 == 0) {
61             temp >>= 1;
62             ++max_base;
63         }
64         root = 2;
65         while (true) {
66             if (power(root, 1 << max_base) == 1 && power(root, 1 << (max_base - 1))
67                 != 1) {
68                 break;
69             }

```

```

69         ++root;
70     }
71 }
72
73 void ensure_base(int nbase) {
74     if (max_base == -1) {
75         init();
76     }
77     if (nbase <= base) {
78         return;
79     }
80     assert(nbase <= max_base);
81     rev.resize(1 << nbase);
82     for (int i = 0; i < 1 << nbase; ++i) {
83         rev[i] = (rev[i >> 1] >> 1) | ((i & 1) << (nbase - 1));
84     }
85     roots.resize(1 << nbase);
86     while (base < nbase) {
87         int z = power(root, 1 << (max_base - 1 - base));
88         for (int i = 1 << (base - 1); i < 1 << base; ++i) {
89             roots[i << 1] = roots[i];
90             roots[i << 1 | 1] = mul(roots[i], z);
91         }
92         ++base;
93     }
94 }
95
96 void dft(vector<int> &a) {
97     int n = a.size(), zeros = __builtin_ctz(n);
98     ensure_base(zeros);
99     int shift = base - zeros;
100    for (int i = 0; i < n; ++i) {
101        if (i < rev[i] >> shift) {
102            swap(a[i], a[rev[i] >> shift]);
103        }
104    }
105    for (int i = 1; i < n; i <= 1) {
106        for (int j = 0; j < n; j += i << 1) {
107            for (int k = 0; k < i; ++k) {
108                int x = a[j + k], y = mul(a[j + k + i], roots[i + k]);
109                a[j + k] = (x + y) % mod;
110                a[j + k + i] = (x + mod - y) % mod;
111            }

```

```

112     }
113 }
114 }
115
116 vector<int> multiply(vector<int> a, vector<int> b) {
117     int need = a.size() + b.size() - 1, nbase = 0;
118     while (1 << nbase < need) {
119         ++nbase;
120     }
121     ensure_base(nbase);
122     int sz = 1 << nbase;
123     a.resize(sz);
124     b.resize(sz);
125     bool equal = a == b;
126     dft(a);
127     if (equal) {
128         b = a;
129     } else {
130         dft(b);
131     }
132     int inv_sz = inv(sz);
133     for (int i = 0; i < sz; ++i) {
134         a[i] = mul(mul(a[i], b[i]), inv_sz);
135     }
136     reverse(a.begin() + 1, a.end());
137     dft(a);
138     a.resize(need);
139     return a;
140 }
141
142 vector<int> inverse_new(const vector<int> &a) {
143     assert(!a.empty());
144     int n = (int) a.size();
145     vector<int> b = {inv(a[0])};
146     while ((int) b.size() < n) {
147         vector<int> x(a.begin(), a.begin() + min(a.size(), b.size() << 1));
148         x.resize(b.size() << 1);
149         b.resize(b.size() << 1);
150         vector<int> c = b;
151         // NTT<T>::fft(c);
152         // NTT<T>::fft(x);
153         dft(c);
154         dft(x);

```

```

155         // Modular<T> inv = 1 / static_cast<Modular<T>>((int) x.size());
156         int inv_sz = inv((int)x.size());
157         for (int i = 0; i < (int) x.size(); i++) {
158             // x[i] *= c[i] * inv;
159             x[i] = mul(x[i], mul(c[i], inv_sz));
160         }
161         reverse(x.begin() + 1, x.end());
162         // NTT<T>::fft(x);
163         dft(x);
164         rotate(x.begin(), x.begin() + (x.size() >> 1), x.end());
165         fill(x.begin() + (x.size() >> 1), x.end(), 0);
166         // NTT<T>::fft(x);
167         dft(x);
168         for (int i = 0; i < (int) x.size(); i++) {
169             // x[i] *= c[i] * inv;
170             x[i] = mul(x[i], mul(c[i], inv_sz));
171         }
172         reverse(x.begin() + 1, x.end());
173         // NTT<T>::fft(x);
174         dft(x);
175         for (int i = 0; i < ((int) x.size() >> 1); i++) {
176             // b[i + ((int) x.size() >> 1)] = -x[i];
177             int t = 0; sub(t, x[i]);
178             b[i + ((int) x.size() >> 1)] = t;
179         }
180     }
181     b.resize(n);
182     return b;
183 }
184
185 vector<int> inverse(vector<int> a) {
186     int n = a.size(), m = (n + 1) >> 1;
187     if (n == 1) {
188         return vector<int>(1, inv(a[0]));
189     } else {
190         vector<int> b = inverse(vector<int>(a.begin(), a.begin() + m));
191         int need = n << 1, nbase = 0;
192         while (1 << nbase < need) {
193             ++nbase;
194         }
195         ensure_base(nbase);
196         int sz = 1 << nbase;
197         a.resize(sz);

```

```

198     b.resize(sz);
199     dft(a);
200     dft(b);
201     int inv_sz = inv(sz);
202     for (int i = 0; i < sz; ++i) {
203         a[i] = mul(mul(mod + 2 - mul(a[i], b[i]), b[i]), inv_sz);
204     }
205     reverse(a.begin() + 1, a.end());
206     dft(a);
207     a.resize(n);
208     return a;
209 }
210 }
211 }
212
213 using ntt::multiply;
214 using ntt::inverse;
215
216 vector<int>& operator += (vector<int> &a, const vector<int> &b) {
217     if (a.size() < b.size()) {
218         a.resize(b.size());
219     }
220     for (int i = 0; i < b.size(); ++i) {
221         add(a[i], b[i]);
222     }
223     return a;
224 }
225
226 vector<int> operator + (const vector<int> &a, const vector<int> &b) {
227     vector<int> c = a;
228     return c += b;
229 }
230
231 vector<int>& operator -= (vector<int> &a, const vector<int> &b) {
232     if (a.size() < b.size()) {
233         a.resize(b.size());
234     }
235     for (int i = 0; i < b.size(); ++i) {
236         sub(a[i], b[i]);
237     }
238     return a;
239 }
240

```

```

241 vector<int> operator - (const vector<int> &a, const vector<int> &b) {
242     vector<int> c = a;
243     return c -= b;
244 }
245
246 vector<int>& operator *= (vector<int> &a, const vector<int> &b) {
247     if (min(a.size(), b.size()) < 128) {
248         vector<int> c = a;
249         a.assign(a.size() + b.size() - 1, 0);
250         for (int i = 0; i < c.size(); ++i) {
251             for (int j = 0; j < b.size(); ++j) {
252                 add(a[i + j], mul(c[i], b[j]));
253             }
254         }
255     } else {
256         a = multiply(a, b);
257     }
258     return a;
259 }
260
261 vector<int> operator * (const vector<int> &a, const vector<int> &b) {
262     vector<int> c = a;
263     return c *= b;
264 }
265
266 vector<int>& operator /= (vector<int> &a, const vector<int> &b) {
267     int n = a.size(), m = b.size();
268     if (n < m) {
269         a.clear();
270     } else {
271         vector<int> c = b;
272         reverse(a.begin(), a.end());
273         reverse(c.begin(), c.end());
274         c.resize(n - m + 1);
275         a *= inverse(c);
276         a.erase(a.begin() + n - m + 1, a.end());
277         reverse(a.begin(), a.end());
278     }
279     return a;
280 }
281
282 vector<int> operator / (const vector<int> &a, const vector<int> &b) {
283     vector<int> c = a;

```

```

284     return c /= b;
285 }
286
287 vector<int>& operator %= (vector<int> &a, const vector<int> &b) {
288     int n = a.size(), m = b.size();
289     if (n >= m) {
290         vector<int> c = (a / b) * b;
291         a.resize(m - 1);
292         for (int i = 0; i < m - 1; ++i) {
293             sub(a[i], c[i]);
294         }
295     }
296     return a;
297 }
298
299 vector<int> operator % (const vector<int> &a, const vector<int> &b) {
300     vector<int> c = a;
301     return c %= b;
302 }
303
304 vector<int> derivative(const vector<int> &a) {
305     int n = a.size();
306     vector<int> b(n - 1);
307     for (int i = 1; i < n; ++i) {
308         b[i - 1] = mul(a[i], i);
309     }
310     return b;
311 }
312
313 vector<int> primitive(const vector<int> &a) {
314     int n = a.size();
315     vector<int> b(n + 1), invs(n + 1);
316     for (int i = 1; i <= n; ++i) {
317         invs[i] = i == 1 ? 1 : mul(mod - mod / i, invs[mod % i]);
318         b[i] = mul(a[i - 1], invs[i]);
319     }
320     return b;
321 }
322
323 vector<int> logarithm(const vector<int> &a) {
324     vector<int> b = primitive(derivative(a) * inverse(a));
325     b.resize(a.size());
326     return b;

```

```

327 }
328
329 vector<int> exponent(const vector<int> &a) {
330     vector<int> b(1, 1);
331     while (b.size() < a.size()) {
332         vector<int> c(a.begin(), a.begin() + min(a.size(), b.size() << 1));
333         add(c[0], 1);
334         vector<int> old_b = b;
335         b.resize(b.size() << 1);
336         c -= logarithm(b);
337         c *= old_b;
338         for (int i = b.size() >> 1; i < b.size(); ++i) {
339             b[i] = c[i];
340         }
341     }
342     b.resize(a.size());
343     return b;
344 }
345
346 vector<int> power(vector<int> a, int m) {
347     int n = a.size(), p = -1;
348     vector<int> b(n);
349     for (int i = 0; i < n; ++i) {
350         if (a[i]) {
351             p = i;
352             break;
353         }
354     }
355     if (p == -1) {
356         b[0] = !m;
357         return b;
358     }
359     if ((long long) m * p >= n) {
360         return b;
361     }
362     int mu = power(a[p], m), di = inv(a[p]);
363     vector<int> c(n - m * p);
364     for (int i = 0; i < n - m * p; ++i) {
365         c[i] = mul(a[i + p], di);
366     }
367     c = logarithm(c);
368     for (int i = 0; i < n - m * p; ++i) {
369         c[i] = mul(c[i], m);

```

```

370     }
371     c = exponent(c);
372     for (int i = 0; i < n - m * p; ++i) {
373         b[i + m * p] = mul(c[i], mu);
374     }
375     return b;
376 }
377
378 vector<int> sqrt(const vector<int> &a) {
379     vector<int> b(1, 1);
380     while (b.size() < a.size()) {
381         vector<int> c(a.begin(), a.begin() + min(a.size(), b.size() << 1));
382         vector<int> old_b = b;
383         b.resize(b.size() << 1);
384         c *= inverse(b);
385         for (int i = b.size() >> 1; i < b.size(); ++i) {
386             b[i] = mul(c[i], (mod + 1) >> 1);
387         }
388     }
389     b.resize(a.size());
390     return b;
391 }
392
393 vector<int> multiply_all(int l, int r, vector<vector<int>> &all) {
394     if (l > r) {
395         return vector<int>();
396     } else if (l == r) {
397         return all[l];
398     } else {
399         int y = (l + r) >> 1;
400         return multiply_all(l, y, all) * multiply_all(y + 1, r, all);
401     }
402 }
403
404 vector<int> evaluate(const vector<int> &f, const vector<int> &x) {
405     int n = x.size();
406     if (!n) {
407         return vector<int>();
408     }
409     vector<vector<int>> up(n * 2);
410     for (int i = 0; i < n; ++i) {
411         up[i + n] = vector<int> {(mod - x[i]) % mod, 1};
412     }

```

```

413     for (int i = n - 1; i; --i) {
414         up[i] = up[i << 1] * up[i << 1 | 1];
415     }
416     vector<vector<int>> down(n * 2);
417     down[1] = f % up[1];
418     for (int i = 2; i < n * 2; ++i) {
419         down[i] = down[i >> 1] % up[i];
420     }
421     vector<int> y(n);
422     for (int i = 0; i < n; ++i) {
423         y[i] = down[i + n][0];
424     }
425     return y;
426 }
427
428 vector<int> interpolate(const vector<int> &x, const vector<int> &y) {
429     int n = x.size();
430     vector<vector<int>> up(n * 2);
431     for (int i = 0; i < n; ++i) {
432         up[i + n] = vector<int> {(mod - x[i]) % mod, 1};
433     }
434     for (int i = n - 1; i; --i) {
435         up[i] = up[i << 1] * up[i << 1 | 1];
436     }
437     vector<int> a = evaluate(derivative(up[1]), x);
438     for (int i = 0; i < n; ++i) {
439         a[i] = mul(y[i], inv(a[i]));
440     }
441     vector<vector<int>> down(n * 2);
442     for (int i = 0; i < n; ++i) {
443         down[i + n] = vector<int>(1, a[i]);
444     }
445     for (int i = n - 1; i; --i) {
446         down[i] = down[i << 1] * up[i << 1 | 1] + down[i << 1 | 1] * up[i << 1];
447     }
448     return down[1];
449 }
450
451 int main() {
452
453 }

```

6.20 simplex.cpp

```

1  /**
2   * Author: Stanford
3   * Source: Stanford Notebook
4   * License: MIT
5   * Description: Solves a general linear maximization problem: maximize  $c^T x$ 
   * subject to  $Ax \leq b$ ,  $x \geq 0$ .
6   * Returns  $-\infty$  if there is no solution,  $\infty$  if there are arbitrarily good
   * solutions, or the maximum value of  $c^T x$  otherwise.
7   * The input vector is set to an optimal  $x$  (or in the unbounded case, an
   * arbitrary solution fulfilling the constraints).
8   * Numerical stability is not guaranteed. For better performance, define
   * variables such that  $x = 0$  is viable.
9   * Usage:
10  * vvd A = {{1,-1}, {-1,1}, {-1,-2}};
11  * vd b = {1,1,-4}, c = {-1,-1}, x;
12  * T val = LPSolver(A, b, c).solve(x);
13  * Time:  $O(NM \cdot \#pivots)$ , where a pivot may be e.g. an edge relaxation.  $O(2^n)$ 
   * in the general case.
14  * Status: seems to work?
15  */
16
17 typedef long double T; // long double, Rational, double + mod<P>...
18 typedef vector<T> vd;
19 typedef vector<vd> vvd;
20
21 const T eps = 1e-8, inf = 1/.0;
22 #define MP make_pair
23 #define ltj(X) if(s == -1 || MP(X[j],N[j]) < MP(X[s],N[s])) s=j
24
25 struct LPSolver {
26     int m, n;
27     vector<int> N, B;
28     vvd D;
29
30     LPSolver(const vvd& A, const vd& b, const vd& c) :
31         m(b.size()), n(c.size()), N(n+1), B(m), D(m+2, vd(n+2)) {
32         for(int i = 0; i < m; i++){
33             for(int j = 0; j < n; j++){
34                 D[i][j] = A[i][j];
35             }
36         }
37         for(int i = 0; i < m; i++){

```

```

38             B[i] = n+i; D[i][n] = -1; D[i][n+1] = b[i];
39         }
40         for(int j = 0; j < n; j++){
41             N[j] = j; D[m][j] = -c[j];
42         }
43         N[n] = -1; D[m+1][n] = 1;
44     }
45
46     void pivot(int r, int s) {
47         T *a = D[r].data(), inv = 1 / a[s];
48         for(int i = 0; i < m+2; i++){
49             if (i != r && abs(D[i][s]) > eps) {
50                 T *b = D[i].data(), inv2 = b[s] * inv;
51                 for(int j = 0; j < n+2; j++){
52                     b[j] -= a[j] * inv2;
53                 }
54                 b[s] = a[s] * inv2;
55             }
56         }
57         for(int j = 0; j < n+2; j++){
58             if (j != s) D[r][j] *= inv;
59         }
60         for(int i = 0; i < m+2; i++){
61             if (i != r) D[i][s] *= -inv;
62         }
63         D[r][s] = inv;
64         swap(B[r], N[s]);
65     }
66
67     bool simplex(int phase) {
68         int x = m + phase - 1;
69         for (;;) {
70             int s = -1;
71             for(int j = 0; j < n+1; j++){
72                 if (N[j] != -phase) ltj(D[x]);
73             }
74             if (D[x][s] >= -eps) return true;
75             int r = -1;
76             for(int i = 0; i < m; i++){
77                 if (D[i][s] <= eps) continue;
78                 if (r == -1 || MP(D[i][n+1] / D[i][s], B[i])
79                     < MP(D[r][n+1] / D[r][s], B[

```

```

80         }
81         if (r == -1) return false;
82         pivot(r, s);
83     }
84 }
85
86 T solve(vd &x) {
87     int r = 0;
88     for(int i = 1; i < m; i++){
89         if (D[i][n+1] < D[r][n+1]) r = i;
90     }
91     if (D[r][n+1] < -eps) {
92         pivot(r, n);
93         if (!simplex(2) || D[m+1][n+1] < -eps) return -inf;
94         for(int i = 0; i < m; i++) if (B[i] == -1) {
95             int s = 0;
96             for(int j = 1; j < n+1; j++){
97                 ltj(D[i]);
98             }
99             pivot(i, s);
100         }
101     }
102     bool ok = simplex(1); x = vd(n);
103     for(int i = 0; i < m; i++){
104         if (B[i] < n) x[B[i]] = D[i][n+1];
105     }
106     return ok ? D[m][n+1] : inf;
107 }
108 };

```

6.21 区间互质.cpp

```

1 int p[N / 5], num;
2 void prime(int n) {
3     num = 0;
4     for (int i = 2; i * i <= n; i++) {
5         if ((n % i) == 0) {
6             p[++num] = i;
7             while ((n % i) == 0) n /= i;
8         }
9     }
10     if (n > 1) p[++num] = n;
11 }

```

```

12 ll solve(ll r, int k) {
13     prime(k);
14     ll res = 0;
15     for (int i = 1; i < (1 << num); i++) {
16         int k = 0;
17         ll div = 1;
18         for (int j = 1; j <= num; j++) {
19             if (i & (1 << (j - 1))) {
20                 k++;
21                 div *= p[j];
22             }
23         }
24         if (k % 2)
25             res += r / div;
26         else
27             res -= r / div;
28     }
29     return r - res;
30 }
31 ll que(ll L, ll R, ll k) {
32     return solve(R, k) - solve(L - 1, k);
33 }

```

6.22 幂转下降幂 (求幂和).cpp

```

1 ll comb[N][N];
2 ll s[maxn], inv[maxn], p;
3 //  $1^k + 2^k + \dots + n^k$ 
4 void solve() {
5     cin >> k >> n >> p;
6     rep(i, 0, k + 1) {
7         comb[i][0] = comb[i][i] = 1;
8         rep(j, 1, i - 1) {
9             comb[i][j] = (comb[i - 1][j - 1] + comb[i - 1][j]) %
10                 p;
11         }
12     }
13     inv[1] = 1;
14     rep(i, 2, k + 1) inv[i] = (p - p / i) * inv[p % i] % p;
15     assert(inv[k] * k % p == 1);
16
17     ll pw = 1;
18     //  $(k+1) * S[k] = (n+1)^{(k+1)} - [0-k-1](k+1, j) * S[j] - 1$ 

```

```

18     rep(i, 0, k) {
19         pw = pw * (n + 1) % p;
20         s[i] = (pw - 1 + p) % p;
21         rep(j, 0, i - 1) {
22             s[i] = (s[i] - comb[i + 1][j] * s[j] % p + p) % p;
23         }
24         s[i] = s[i] * inv[i + 1] % p;
25     }
26     cout << s[k] << '\n';
27 }

```

6.23 扩展欧拉定理.cpp

```

1 // mod {min(b, b % phi + phi)}
2 ll calc(ll p) {
3     if (p == 1) return 0;
4     int phi = p, q = p;
5     for (int i = 2; i * i <= p; i++) {
6         if (q % i == 0) {
7             phi = phi / i * (i - 1);
8             while (q % i == 0) q /= i;
9         }
10    }
11    if (q != 1) phi = phi / q * (q - 1);
12    return powmod(2, calc(phi) + phi, p);
13 }

```

6.24 拉格朗日插值.cpp

```

1 // k阶多项式(需要k+1个点)
2 // 求在点n上的值
3 // O(k)
4 ll lagrange(ll n, int k) {
5     vector<ll> x(k + 5), y(k + 5);
6     rep(i, 1, k + 1) {
7         x[i] = i;
8         // y[i]=(y[i-1]+powmod(i,k-1,mod))%mod;
9     }
10    if (n <= k + 1) return y[n];
11
12    vector<ll> fac(k + 5);
13    fac[0] = 1;
14    ll coe = 1;

```

```

15     rep(i, 1, k + 4) fac[i] = fac[i - 1] * i % mod;
16     rep(i, 1, k + 1) coe = coe * (n - i + mod) % mod;
17     ll ans = 0;
18     rep(i, 1, k + 1) {
19         ll sgn = (((k + 1 - i) % 2) ? -1 : 1);
20         ll f1 = powmod(fac[i - 1] * fac[k + 1 - i] % mod, mod - 2,
21             mod);
22         ll f2 = powmod(n - i, mod - 2, mod);
23         ans += sgn * coe * f1 % mod * f2 % mod * y[i] % mod;
24         ans = (ans + mod) % mod;
25     }
26     return ans;

```

6.25 整除分块.cpp

```

1 void solve() {
2     u64 ans = 0;
3     cin >> n;
4     for (ll l = 1; l <= n; l++) {
5         ll d = n / l, r = n / d;
6         ans += (l + r) * (r - l + 1) / 2 * d;
7         l = r;
8     }
9 }

```

6.26 枚举子集.cpp

```

1 void solve() {
2     f[0] = 1;
3     for (int i = 1; i < (1ll << n); i++) {
4         int t = i;
5         ll res = 0;
6         while (true) {
7             if (t == 0) break;
8             t = (t - 1) & i;
9             res = (res + f[t]) % mod;
10        }
11        f[i] = res * i;
12    }
13 }

```


6.27 枚举超集.cpp

```
1 void solve() {
2     for (int i = 1; i < (1ll << n); i++) {
3         int t = i;
4         while (true) {
5             t = (t + 1) | i;
6             if (t == bit(n) - 1) break;
7         }
8     }
9 }
```

6.28 狄利克雷卷积.cpp

```
1 const int N = 1010000;
2 int p[N], pr[N / 5], n, tot;
3 unsigned int A, B, C, mu[N], f[N], g[N];
4
5 inline unsigned int rng61() {
6     A ^= A << 16;
7     A ^= A >> 5;
8     A ^= A << 1;
9     unsigned int t = A;
10    A = B;
11    B = C;
12    C ^= t ^ A;
13    return C;
14 }
15
16 int main() {
17     scanf("%d%u%u%u", &n, &A, &B, &C);
18     for (int i = 1; i <= n; i++)
19         f[i] = rng61();
20
21     p[1] = 1; mu[1] = 1;
22     for (int i = 2; i <= n; i++) {
23         if (!p[i]) p[i] = i, mu[i] = (uint)-1, pr[++tot] = i;
24         for (int j = 1; j <= tot && pr[j] * i <= n; j++) {
25             p[i * pr[j]] = pr[j];
26             if (p[i] == pr[j]) {
27                 mu[i * pr[j]] = 0;
28                 break;
29             } else {
30                 mu[i * pr[j]] = (uint)-mu[i];
```

```
31             }
32         }
33     }
34     for (int d1 = 1; d1 <= n; d1++)
35         for (int d2 = 1; d1 * d2 <= n; d2++)
36             g[d1 * d2] += f[d1] * mu[d2];
37     uint ans = 0;
38     for (int i = 1; i <= n; i++) ans ^= g[i];
39     printf("%u\n", ans);
40 }
```

6.29 线性筛常见积性函数.cpp

```
1 const int N = 20010000;
2 int p[N], pr[N / 5], n, pe[N], tot;
3 uint f[N], a, b, ans;
4
5 void compute(int n, function<void(int)> calcpe) {
6     ans = 0;
7     f[1] = 1;
8     for (int i = 2; i <= n; i++) {
9         if (i == pe[i])
10            calcpe(i);
11        else
12            f[i] = f[pe[i]] * f[i / pe[i]];
13    }
14    for (uint i = 1; i <= n; i++) {
15        ans ^= (a * i * f[i] + b);
16    }
17    printf("%u\n", ans);
18 }
19
20 int main() {
21     scanf("%d%u%u", &n, &a, &b);
22     p[1] = 1;
23     for (int i = 2; i <= n; i++) {
24         if (!p[i]) p[i] = i, pe[i] = i, pr[++tot] = i;
25         for (int j = 1; j <= tot && pr[j] * i <= n; j++) {
26             p[i * pr[j]] = pr[j];
27             if (p[i] == pr[j]) {
28                 pe[i * pr[j]] = pe[i] * pr[j];
29                 break;
30             } else {
```

```

31         pe[i * pr[j]] = pr[j];
32     }
33 }
34 }
35 // 因子个数, 因子和, 欧拉函数, 莫比乌斯函数
36 compute(n, [&](int x) {
37     f[x] = f[x / p[x]] + 1;
38 });
39
40 compute(n, [&](int x) {
41     f[x] = f[x / p[x]] + x;
42 });
43
44 compute(n, [&](int x) {
45     f[x] = x / p[x] * (p[x] - 1);
46 });
47
48 compute(n, [&](int x) {
49     f[x] = x == p[x] ? -1 : 0;
50 });
51 }

```

6.30 莫比乌斯反演 gcd 常见结论.cpp

```

1 // u * 1 = e, phi * 1 = id, phi = id * u
2 const int N = 10100000, M = 10000000;
3 int p[N], pr[N / 5], n, tot;
4 int mu[N], smu[N];
5
6 int main() {
7     p[1] = 1; mu[1] = 1;
8     for (int i = 2; i <= M; i++) {
9         if (!p[i]) p[i] = i, mu[i] = -1, pr[++tot] = i;
10        for (int j = 1; j <= tot && pr[j] * i <= M; j++) {
11            p[i * pr[j]] = pr[j];
12            if (p[i] == pr[j]) {
13                mu[i * pr[j]] = 0;
14                break;
15            } else {
16                mu[i * pr[j]] = -mu[i];
17            }
18        }
19    }

```

```

20     for (int i = 1; i <= M; i++)
21         smu[i] = smu[i - 1] + mu[i];
22     int T;
23     scanf("%d", &T);
24     for (int tc = 0; tc < T; tc++) {
25         int n, m;
26         scanf("%d%d", &n, &m);
27         if (n > m) swap(n, m);
28         ll ans = 0;
29         for (int l = 1; l <= n; l++) {
30             int n1 = n / l, m1 = m / l;
31             int r = min(n / n1, m / m1);
32             // l ... r
33             ans += 1ll * (smu[r] - smu[l - 1]) * n1 * m1;
34             l = r;
35         }
36         printf("%lld\n", ans);
37     }
38 }

```

7 String

7.1 ACAM.cpp

```

1 const int AC_SIGMA = 26, AC_V = 26, AC_N = 810000;
2 struct AC_automaton {
3     struct node {
4         node *go[AC_V], *fail, *f;
5     } // declare extra variables:
6     } pool[AC_N], *cur, *root, *q[AC_N];
7     node* newnode() {
8         node *p = cur++;
9     } // init extra variables:
10    return p;
11 }
12 // CALL init() and CHECK all const variables:
13 void init() { cur = pool; root = newnode(); }
14 node* append(node *p, int w) {
15     if (!p->go[w]) p->go[w] = newnode(), p->go[w]->f = p;
16     return p->go[w];
17 }
18 void build() {

```

```

19         int t = 0;
20         q[t++] = root;
21         root->fail = root;
22         rep(i, 0, AC_SIGMA - 1) if (root->go[i]) {
23             q[t++] = root->go[i];
24             root->go[i]->fail = root;
25         } else {
26             root->go[i] = root;
27         }
28         rep(i, 1, t - 1) {
29             node *u = q[i];
30             rep(j, 0, AC_SIGMA - 1) if (u->go[j]) {
31                 u->go[j]->fail = u->fail->go[j];
32                 q[t++] = u->go[j];
33             } else {
34                 u->go[j] = u->fail->go[j];
35             }
36         }
37     }
38 } ac;
39 typedef AC_automaton::node ACnode;
40
41 const int M = 2, N = 2.1e5;
42 struct node {
43     node *son[M], *go[M], *fail;
44     int cnt, vis, ins;
45 } pool[N], *cur = pool, *q[N], *root;
46
47 node *newnode() { return cur++; }
48 int t, n;
49
50 void build() {
51     t = 0;
52     q[t++] = root;
53     for (int i = 0; i < t; i++) {
54         node *u = q[i];
55         for (int j = 0; j < M; j++) {
56             if (u->son[j]) {
57                 u->go[j] = u->son[j];
58                 if (u != root)
59                     u->go[j]->fail = u->fail->go[j];
60             } else
61                 u->go[j]->fail = root;

```

```

62             q[t++] = u->son[j];
63         } else {
64             if (u != root)
65                 u->go[j] = u->fail->go[j];
66             else
67                 u->go[j] = root;
68         }
69     }
70 }
71 }
72
73 void insert(string &s) {
74     node *cur = root;
75     for (auto c : s) {
76         int w = c - '0';
77         if (!cur->son[w]) {
78             cur->son[w] = newnode();
79         }
80         cur = cur->son[w];
81     }
82     cur->cnt = 1;
83 }

```

7.2 hash61.cpp

```

1 struct hash61 {
2     static const uint64_t md = (1LL << 61) - 1;
3     static uint64_t step;
4     static vector<uint64_t> pw;
5
6     uint64_t addmod(uint64_t a, uint64_t b) const {
7         a += b;
8         if (a >= md) a -= md;
9         return a;
10    }
11
12    uint64_t submod(uint64_t a, uint64_t b) const {
13        a += md - b;
14        if (a >= md) a -= md;
15        return a;
16    }
17
18    uint64_t mulmod(uint64_t a, uint64_t b) const {

```

```

19         uint64_t l1 = (uint32_t) a, h1 = a >> 32, l2 = (uint32_t) b,
20             h2 = b >> 32;
21         uint64_t l = l1 * l2, m = l1 * h2 + l2 * h1, h = h1 * h2;
22         uint64_t ret = (l & md) + (l >> 61) + (h << 3) + (m >> 29) +
23             (m << 35 >> 3) + 1;
24         ret = (ret & md) + (ret >> 61);
25         ret = (ret & md) + (ret >> 61);
26         return ret - 1;
27     }
28
29     void ensure_pw(int sz) {
30         int cur = (int) pw.size();
31         if (cur < sz) {
32             pw.resize(sz);
33             for (int i = cur; i < sz; i++) {
34                 pw[i] = mulmod(pw[i - 1], step);
35             }
36         }
37
38     vector<uint64_t> pref;
39     int n;
40
41     template<typename T>
42     hash61(const T& s) {
43         n = (int) s.size();
44         ensure_pw(n + 1);
45         pref.resize(n + 1);
46         pref[0] = 1;
47         for (int i = 0; i < n; i++) {
48             pref[i + 1] = addmod(mulmod(pref[i], step), s[i]);
49         }
50
51     inline uint64_t operator()(const int from, const int to) const {
52         assert(0 <= from && from <= to && to <= n - 1);
53         return submod(pref[to + 1], mulmod(pref[from], pw[to - from
54             + 1]));
55     }
56
57     uint64_t hash61::step = (md >> 2) + rng() % (md >> 1);
58     vector<uint64_t> hash61::pw = vector<uint64_t>(1, 1);

```

7.3 kmp.cpp

```

1  template <typename T>
2  vector<int> kmp_table(int n, const T &s) {
3      vector<int> p(n, 0);
4      int k = 0;
5      for (int i = 1; i < n; i++) {
6          while (k > 0 && !(s[i] == s[k])) {
7              k = p[k - 1];
8          }
9          if (s[i] == s[k]) {
10             k++;
11         }
12         p[i] = k;
13     }
14     return p;
15 }
16
17 template <typename T>
18 vector<int> kmp_table(const T &s) {
19     return kmp_table((int) s.size(), s);
20 }
21
22 template <typename T>
23 vector<int> kmp_search(int n, const T &s, int m, const T &w, const vector<
24     int> &p) {
25     assert(n >= 1 && (int) p.size() == n);
26     vector<int> res;
27     int k = 0;
28     for (int i = 0; i < m; i++) {
29         while (k > 0 && (k == n || !(w[i] == s[k]))) {
30             k = p[k - 1];
31         }
32         if (w[i] == s[k]) {
33             k++;
34         }
35         if (k == n) {
36             res.push_back(i - n + 1);
37         }
38     }
39     return res;
40     // returns 0-indexed positions of occurrences of s in w
41 }

```

```

42 template <typename T>
43 vector<int> kmp_search(const T &s, const T &w, const vector<int> &p) {
44     return kmp_search((int) s.size(), s, (int) w.size(), w, p);
45 }

```

7.4 manacherfast.cpp

```

1  template <typename T>
2  vector<int> manacher(int n, const T &s) {
3      if (n == 0) {
4          return vector<int>();
5      }
6      vector<int> res(2 * n - 1, 0);
7      int l = -1, r = -1;
8      for (int z = 0; z < 2 * n - 1; z++) {
9          int i = (z + 1) >> 1;
10         int j = z >> 1;
11         int p = (i >= r ? 0 : min(r - i, res[2 * (1 + r) - z]));
12         while (j + p + 1 < n && i - p - 1 >= 0) {
13             if (!(s[j + p + 1] == s[i - p - 1])) {
14                 break;
15             }
16             p++;
17         }
18         if (j + p > r) {
19             l = i - p;
20             r = j + p;
21         }
22         res[z] = p;
23     }
24     return res;
25     // res[2 * i] = odd radius in position i
26     // res[2 * i + 1] = even radius between positions i and i + 1
27     // s = "abaa" -> res = {0, 0, 1, 0, 0, 1, 0}
28     // in other words, for every z from 0 to 2 * n - 2:
29     // calculate i = (z + 1) >> 1 and j = z >> 1
30     // now there is a palindrome from i - res[z] to j + res[z]
31     // (watch out for i > j and res[z] = 0)
32 }
33
34 template <typename T>
35 vector<int> manacher(const T &s) {
36     return manacher((int) s.size(), s);

```

```

37 }

```

7.5 MinRotation.cpp

```

1  Description: Finds the lexicographically smallest rotation of a string.
2  Usage: rotate(v.begin(), v.begin() + minRotation(v), v.end());
3  Time: O(N)
4
5  int minRotation(string s) {
6      int a = 0, N = sz(s); s += s;
7      rep(b, 0, N) rep(k, 0, N) {
8          if (a + k == b || s[a + k] < s[b + k]) {b += max(0, k - 1); break;}
9          if (s[a + k] > s[b + k]) {a = b; break;}
10     }
11     return a;
12 }

```

7.6 PAM.cpp

```

1  struct PAM {
2      struct T {
3          array<int, 10> tr;
4          int fail, len, tag;
5          T() : fail(0), len(0), tag(0) {
6              tr.fill(0);
7          }
8      };
9      vector<T> t;
10     vector<int> stk;
11     int newnode(int len) {
12         t.emplace_back();
13         t.back().len = len;
14         return (int)t.size() - 1;
15     }
16     PAM() : t(2) {
17         t[0].fail = 1, t[0].len = 0;
18         t[1].fail = 0, t[1].len = -1;
19         stk.push_back(-1);
20     }
21     int getfail(int v) {
22         while (stk.end()[-2 - t[v].len] != stk.back()) {
23             v = t[v].fail;
24         }

```

```

25         return v;
26     }
27     int insert(int lst, int c, int td) {
28         stk.emplace_back(c);
29         int x = getfail(lst);
30         if (!t[x].tr[c]) {
31             int u = newnode(t[x].len + 2);
32             t[u].fail = t[getfail(t[x].fail)].tr[c];
33             t[x].tr[c] = u;
34         }
35         t[t[x].tr[c]].tag += td;
36         return t[x].tr[c];
37     }
38     int build(int n) {
39         int ans = 0;
40         for (int i = (int)t.size() - 1; i > 1; i--) {
41             t[t[i].fail].tag += t[i].tag;
42             if (t[i].len > n) {
43                 continue;
44             }
45             ans = (ans + 1ll * t[i].tag * t[i].tag % M * t[i].
                     len) % M;
46         }
47         return ans;
48     }
49 };

```

7.7 rollingHash.cpp

```

1  typedef pair<int,int> hashv;
2  const ll mod1=1000000007;
3  const ll mod2=1000000009;
4
5  // prefixSum trick for high dimensions
6
7  hashv operator + (hashv a,hashv b) {
8      int c1=a.fi+b.fi,c2=a.se+b.se;
9      if (c1>=mod1) c1-=mod1;
10     if (c2>=mod2) c2-=mod2;
11     return mp(c1,c2);
12 }
13
14 hashv operator - (hashv a,hashv b) {

```

```

15     int c1=a.fi-b.fi,c2=a.se-b.se;
16     if (c1<0) c1+=mod1;
17     if (c2<0) c2+=mod2;
18     return mp(c1,c2);
19 }
20
21 hashv operator * (hashv a,hashv b) {
22     return mp(1ll*a.fi*b.fi%mod1,1ll*a.se*b.se%mod2);
23 }

```

7.8 SA.cpp

```

1  #include <bits/stdc++.h>
2  using namespace std;
3
4  const int N = 101000;
5  char s[N];
6  int sa[N], rk[N], ht[N], n;
7  // 0-based sa 表示第 i 大的为哪个, rk 表示第 i 个后缀第几大
8  // ht 表示 lcp(sa[i], sa[i-1])
9  void buildSA(char *s, int *sa, int *rk, int *ht, int n, int m = 128) {
10     static int x[N], y[N], c[N];
11     s[n] = 0;
12     for (int i = 0; i < m; i++) c[i] = 0;
13     for (int i = 0; i < n; i++) c[x[i] = s[i]]++;
14     for (int i = 1; i < m; i++) c[i] += c[i - 1];
15     for (int i = n - 1; i >= 0; i--) sa[--c[x[i]]] = i;
16     for (int k = 1; k < n; k <= 1) {
17         int p=0;
18         for (int i = n - 1; i >= n - k; i--) y[p++] = i;
19         for (int i = 0; i < n; i++) if (sa[i] >= k) y[p++] = sa[i] -
                k;
20         for (int i = 0; i < m; i++) c[i] = 0;
21         for (int i = 0; i < n; i++) c[x[y[i]]]++;
22         for (int i = 1; i < m; i++) c[i] += c[i - 1];
23         for (int i = n - 1; i >= 0; i--) sa[--c[x[y[i]]]] = y[i];
24         swap(x, y);
25         p = 1; x[sa[0]] = 0; y[n] = -1;
26         for (int i = 1; i < n; i++) {
27             if (y[sa[i] - 1] == y[sa[i]] && y[sa[i] - 1] + k ==
                    y[sa[i] + k])
28                 x[sa[i]] = p - 1;
29             else

```

```

30         x[sa[i]] = p++;
31     }
32     if (p == n) break;
33     m = p;
34 }
35 for (int i = 0; i < n; i++) rk[sa[i]] = i;
36 int k = 0;
37 for (int i = 0; i < n; i++) {
38     k = max(k - 1, 0);
39     if (rk[i] == 0) continue;
40     int j = sa[rk[i] - 1];
41     while (s[i + k] == s[j + k]) k++;
42     ht[rk[i]] = k;
43 }
44 }
45
46 int LCP(int u, int v) {
47     if (u == v) return n - u;
48     if (rk[u] > rk[v]) swap(u, v);
49     // RMQ(ht, rk[u] + 1, rk[v])
50 }
51
52 int main() {
53     scanf("%s", s);
54     n = strlen(s);
55     buildSA(s, sa, rk, ht, n);
56     for (int i = 0; i < n; i++) printf("%d_", sa[i] + 1); puts("");
57     for (int i = 1; i < n; i++) printf("%d_", ht[i]); puts("");
58 }

```

7.9 SAfast.cpp

```

1  template <typename T>
2  vector<int> suffix_array(int n, const T &s, int char_bound) {
3      vector<int> a(n);
4      if (n == 0) {
5          return a;
6      }
7      if (char_bound != -1) {
8          vector<int> aux(char_bound, 0);
9          for (int i = 0; i < n; i++) {
10             aux[s[i]]++;
11         }

```

```

12     int sum = 0;
13     for (int i = 0; i < char_bound; i++) {
14         int add = aux[i];
15         aux[i] = sum;
16         sum += add;
17     }
18     for (int i = 0; i < n; i++) {
19         a[aux[s[i]]++] = i;
20     }
21 } else {
22     iota(a.begin(), a.end(), 0);
23     sort(a.begin(), a.end(), [&s](int i, int j) { return s[i] < s[j]; });
24 }
25 vector<int> sorted_by_second(n);
26 vector<int> ptr_group(n);
27 vector<int> new_group(n);
28 vector<int> group(n);
29 group[a[0]] = 0;
30 for (int i = 1; i < n; i++) {
31     group[a[i]] = group[a[i - 1]] + (s[a[i]] == s[a[i - 1]]);
32 }
33 int cnt = group[a[n - 1]] + 1;
34 int step = 1;
35 while (cnt < n) {
36     int at = 0;
37     for (int i = n - step; i < n; i++) {
38         sorted_by_second[at++] = i;
39     }
40     for (int i = 0; i < n; i++) {
41         if (a[i] - step >= 0) {
42             sorted_by_second[at++] = a[i] - step;
43         }
44     }
45     for (int i = n - 1; i >= 0; i--) {
46         ptr_group[group[a[i]]] = i;
47     }
48     for (int i = 0; i < n; i++) {
49         int x = sorted_by_second[i];
50         a[ptr_group[group[x]]++] = x;
51     }
52     new_group[a[0]] = 0;
53     for (int i = 1; i < n; i++) {
54         if (group[a[i]] != group[a[i - 1]]) {

```

```

55     new_group[a[i]] = new_group[a[i - 1]] + 1;
56 } else {
57     int pre = (a[i - 1] + step >= n ? -1 : group[a[i - 1] + step]);
58     int cur = (a[i] + step >= n ? -1 : group[a[i] + step]);
59     new_group[a[i]] = new_group[a[i - 1]] + (pre != cur);
60 }
61 }
62 swap(group, new_group);
63 cnt = group[a[n - 1]] + 1;
64 step <<= 1;
65 }
66 return a;
67 }
68
69 template <typename T>
70 vector<int> suffix_array(const T &s, int char_bound) {
71     return suffix_array((int) s.size(), s, char_bound);
72 }
73
74 template <typename T>
75 vector<int> build_lcp(int n, const T &s, const vector<int> &sa) {
76     assert((int) sa.size() == n);
77     vector<int> pos(n);
78     for (int i = 0; i < n; i++) {
79         pos[sa[i]] = i;
80     }
81     vector<int> lcp(max(n - 1, 0));
82     int k = 0;
83     for (int i = 0; i < n; i++) {
84         k = max(k - 1, 0);
85         if (pos[i] == n - 1) {
86             k = 0;
87         } else {
88             int j = sa[pos[i] + 1];
89             while (i + k < n && j + k < n && s[i + k] == s[j + k]) {
90                 k++;
91             }
92             lcp[pos[i]] = k;
93         }
94     }
95     return lcp;
96 }
97

```

```

98 template <typename T>
99 vector<int> build_lcp(const T &s, const vector<int> &sa) {
100     return build_lcp((int) s.size(), s, sa);
101 }

```

7.10 SAM.cpp

```

1  struct SAM {
2      static constexpr int ALPHABET_SIZE = 26;
3      struct Node {
4          int len;
5          int link;
6          std::array<int, ALPHABET_SIZE> next;
7          Node() : len{}, link{}, next{} {}
8      };
9      std::vector<Node> t;
10     SAM() {
11         init();
12     }
13     void init() {
14         t.assign(2, Node());
15         t[0].next.fill(1);
16         t[0].len = -1;
17     }
18     int newNode() {
19         t.emplace_back();
20         return t.size() - 1;
21     }
22     int extend(int p, int c) {
23         if (t[p].next[c]) {
24             int q = t[p].next[c];
25             if (t[q].len == t[p].len + 1) {
26                 return q;
27             }
28             int r = newNode();
29             t[r].len = t[p].len + 1;
30             t[r].link = t[q].link;
31             t[r].next = t[q].next;
32             t[q].link = r;
33             while (t[p].next[c] == q) {
34                 t[p].next[c] = r;
35                 p = t[p].link;
36             }

```



```

37         return r;
38     }
39     int cur = newNode();
40     t[cur].len = t[p].len + 1;
41     while (!t[p].next[c]) {
42         t[p].next[c] = cur;
43         p = t[p].link;
44     }
45     t[cur].link = extend(p, c);
46     return cur;
47 }
48 };

```

7.11 SA-IS.cpp

```

1  /*
2   * Time Complexity: Suffix Array:  $O(N + \text{Character\_Set\_Size})$  time and space
3   * //
4   * 128 --- ASCII
5   *
6   * LCP:  $O(N)$  time and space
7   *
8   * Usage:
9   *
10  * 1. Suffix Array (returns s.size() elements, NOT considering
11  * 0-length/empty suffix)
12  *
13  * auto sa = suffix_array(s); // s is the input string with
14  * ASCII
15  * characters
16  *
17  * auto sa_wide_char = suffix_array(s, LIM); // LIM = max(s[i])
18  * + 2,
19  * s is the string with arbitrary big characters.
20  *
21  * 2. LCP:
22  *
23  * auto lcp = LCP(s, suffix_array(s)); // returns s.size()
24  * elements,
25  * where lcp[i]=LCP(sa[i], sa[i+1])
26  *
27  * Status: Tested (DMOJ: ccc03s4, SPOJ: SARRAY (100pts), Yosupo's: Suffix
28  * Array
29  *
30  * & Number of Substrings, CodeForces EDU
31  */
32  // Based on: Rickypou, https://judge.yosupo.jp/submission/10105
33  void induced_sort(const std::vector<int>& vec, int val_range,
34                   std::vector<int>& SA, const std::vector<bool>& sl,
35                   const std::vector<int>& lms_idx) {
36     std::vector<int> l(val_range, 0), r(val_range, 0);
37     for (int c : vec) {

```

```

38         if (c + 1 < val_range) ++l[c + 1];
39         ++r[c];
40     }
41     std::partial_sum(l.begin(), l.end(), l.begin());
42     std::partial_sum(r.begin(), r.end(), r.begin());
43     std::fill(SA.begin(), SA.end(), -1);
44     for (int i = (int)lms_idx.size() - 1; i >= 0; --i)
45         SA[--r[vec[lms_idx[i]]]] = lms_idx[i];
46     for (int i : SA)
47         if (i >= 1 && sl[i - 1]) SA[l[vec[i - 1]]++] = i - 1;
48     std::fill(r.begin(), r.end(), 0);
49     for (int c : vec) ++r[c];
50     std::partial_sum(r.begin(), r.end(), r.begin());
51     for (int k = (int)SA.size() - 1, i = SA[k]; k >= 1; --k, i = SA[k])
52         if (i >= 1 && !sl[i - 1]) {
53             SA[--r[vec[i - 1]]] = i - 1;
54         }
55 }
56
57 std::vector<int> SA_IS(const std::vector<int>& vec, int val_range) {
58     const int n = vec.size();
59     std::vector<int> SA(n), lms_idx;
60     std::vector<bool> sl(n);
61     sl[n - 1] = false;
62     for (int i = n - 2; i >= 0; --i) {
63         sl[i] = (vec[i] > vec[i + 1] || (vec[i] == vec[i + 1] && sl[i + 1]));
64     }
65     if (sl[i] && !sl[i + 1]) lms_idx.push_back(i + 1);
66 }
67
68 std::reverse(lms_idx.begin(), lms_idx.end());
69 induced_sort(vec, val_range, SA, sl, lms_idx);
70 std::vector<int> new_lms_idx(lms_idx.size()), lms_vec(lms_idx.size());
71 for (int i = 0, k = 0; i < n; ++i)
72     if (!sl[SA[i]] && SA[i] >= 1 && sl[SA[i] - 1]) {
73         new_lms_idx[k++] = SA[i];
74     }
75
76 int cur = 0;
77 SA[n - 1] = cur;
78 for (size_t k = 1; k < new_lms_idx.size(); ++k) {
79     int i = new_lms_idx[k - 1], j = new_lms_idx[k];
80     if (vec[i] != vec[j]) {
81         SA[j] = ++cur;
82         continue;

```

```

66     }
67     bool flag = false;
68     for (int a = i + 1, b = j + 1;; ++a, ++b) {
69         if (vec[a] != vec[b]) {
70             flag = true;
71             break;
72         }
73         if ((!sl[a] && sl[a - 1]) || (!sl[b] && sl[b - 1])) {
74             flag = !((!sl[a] && sl[a - 1]) && (!sl[b] && sl[b - 1]));
75             break;
76         }
77     }
78     SA[j] = (flag ? ++cur : cur);
79 }
80 for (size_t i = 0; i < lms_idx.size(); ++i) lms_vec[i] = SA[lms_idx[i]];
81 if (cur + 1 < (int)lms_idx.size()) {
82     auto lms_SA = SA_IS(lms_vec, cur + 1);
83     for (size_t i = 0; i < lms_idx.size(); ++i) {
84         new_lms_idx[i] = lms_idx[lms_SA[i]];
85     }
86 }
87 induced_sort(vec, val_range, SA, sl, new_lms_idx);
88 return SA;
89 }
90
91 std::vector<int> suffix_array(const std::string& s, const char first = 'a',
92                             const char last = 'z') {
93     std::vector<int> vec(s.size() + 1);
94     std::copy(std::begin(s), std::end(s), std::begin(vec));
95     for (auto& x : vec) x -= (int)first - 1;
96     vec.back() = 0;
97     auto ret = SA_IS(vec, (int)last - (int)first + 2);
98     ret.erase(ret.begin());
99     return ret;
100 }
101 // Author: https://codeforces.com/blog/entry/12796?#comment-175287
102 // Uses kasai's algorithm linear in time and space
103 std::vector<int> LCP(const std::string& s, const std::vector<int>& sa) {
104     int n = s.size(), k = 0;
105     std::vector<int> lcp(n), rank(n);
106     for (int i = 0; i < n; i++) rank[sa[i]] = i;
107     for (int i = 0; i < n; i++, k ? k-- : 0) {
108         if (rank[i] == n - 1) {

```

```

109             k = 0;
110             continue;
111         }
112         int j = sa[rank[i] + 1];
113         while (i + k < n && j + k < n && s[i + k] == s[j + k]) k++;
114         lcp[rank[i]] = k;
115     }
116     lcp[n - 1] = 0;
117     return lcp;
118 }
119
120 template <typename T, class F = function<T(const T&, const T&)>>
121 class SparseTable {
122 public:
123     int n;
124     vector<vector<T>> mat;
125     F func;
126
127     SparseTable(const vector<T>& a, const F& f) : func(f) {
128         n = static_cast<int>(a.size());
129         int max_log = 32 - __builtin_clz(n);
130         mat.resize(max_log);
131         mat[0] = a;
132         for (int j = 1; j < max_log; j++) {
133             mat[j].resize(n - (1 << j) + 1);
134             for (int i = 0; i <= n - (1 << j); i++) {
135                 mat[j][i] = func(mat[j - 1][i], mat[j - 1][i + (1 << (j - 1))]);
136             }
137         }
138     }
139
140     T get(int from, int to) const {
141         assert(0 <= from && from <= to && to <= n - 1);
142         int lg = 32 - __builtin_clz(to - from + 1) - 1;
143         return func(mat[lg][from], mat[lg][to - (1 << lg) + 1]);
144     }
145 };

```

7.12 Z.cpp

```

1 template <typename T>
2 vector<int> z_function(int n, const T &s) {
3     vector<int> z(n, n);

```

```

4     int l = 0, r = 0;
5     for (int i = 1; i < n; i++) {
6         z[i] = (i > r ? 0 : min(r - i + 1, z[i - 1]));
7         while (i + z[i] < n && s[z[i]] == s[i + z[i]]) {
8             z[i]++;
9         }
10        if (i + z[i] - 1 > r) {
11            l = i;
12            r = i + z[i] - 1;
13        }
14    }
15    return z;
16 }
17
18 template <typename T>
19 vector<int> z_function(const T &s) {
20     return z_function((int) s.size(), s);
21 }

```

8 Basic

8.1 AST.py

```

1 class Solution:
2     def calculate(self, s: str) -> int:
3         sign = ['+', '-', '*', '/', '(', ')']
4         v = []
5         num = ''
6         for c in s:
7             if c in sign:
8                 if num:
9                     v.append(num); num = ''
10                if c == '-' and (not v or v[-1] == '('):
11                    v.append('0')
12                v.append(c)
13            elif c.isnumeric():
14                num += c
15            if num: v.append(num)
16
17        stk0 = []
18        stk1 = []
19        for e in v:

```

```

20            if e.isnumeric():
21                stk0.append(e)
22            elif e in ['+', '-']:
23                while stk1 and stk1[-1] in ['*', '/', '+', '-']:
24                    stk0.append(stk1.pop())
25                stk1.append(e)
26            elif e in ['*', '/', '(']:
27                stk1.append(e)
28            else:
29                while stk1 and stk1[-1] != '(':
30                    stk0.append(stk1.pop())
31                stk1.pop()
32        while stk1:
33            stk0.append(stk1.pop())
34
35        res = []
36        for e in stk0:
37            if e.isnumeric():
38                res.append(int(e))
39            else:
40                v = res.pop(); u = res.pop()
41                if e == '+':
42                    res.append(u + v)
43                if e == '-':
44                    res.append(u - v)
45                if e == '*':
46                    res.append(u * v)
47                if e == '/':
48                    res.append(u // v)
49        return res[0]

```

8.2 bitset.cpp

```

1 template <int len = 1>
2 void solve(int n) {
3     if (n > len) {
4         solve<std::min(len*2, MAXLEN)>(n);
5         return;
6     }
7     // solution using bitset<len>
8 }
9

```

```

10 struct Bitset {
11     vector<ull> b;
12     int n;
13     Bitset(int x = 0) {
14         n = x;
15         b.resize((n + 63) / 64, 0);
16     }
17
18     int get(int x) {
19         return (b[x >> 6] >> (x & 63)) & 1;
20     }
21
22     void set(int x, int y) {
23         b[x >> 6] |= 1ULL << (x & 63);
24         if (!y) b[x >> 6] ^= 1ULL << (x & 63);
25     }
26
27     Bitset &operator&=(const Bitset &another) {
28         rep(i, 0, min(SZ(b), SZ(another.b)) - 1) {
29             b[i] &= another.b[i];
30         }
31         return (*this);
32     }
33
34     Bitset operator&(const Bitset &another)const {
35         return (Bitset(*this) &= another);
36     }
37
38     Bitset &operator|=(const Bitset &another) {
39         rep(i, 0, min(SZ(b), SZ(another.b)) - 1) {
40             b[i] |= another.b[i];
41         }
42         return (*this);
43     }
44
45     Bitset operator|(const Bitset &another)const {
46         return (Bitset(*this) |= another);
47     }
48
49     Bitset &operator^=(const Bitset &another) {
50         rep(i, 0, min(SZ(b), SZ(another.b)) - 1) {
51             b[i] ^= another.b[i];
52         }

```

```

53         return (*this);
54     }
55
56     Bitset operator^(const Bitset &another)const {
57         return (Bitset(*this) ^= another);
58     }
59
60     Bitset &operator>>=(int x) {
61         if (x & 63) {
62             rep(i, 0, SZ(b) - 2) {
63                 b[i] >>= (x & 63);
64                 b[i] ^= (b[i + 1] << (64 - (x & 63)));
65             }
66             b.back() >>= (x & 63);
67         }
68
69         x >>= 6;
70         rep(i, 0, SZ(b) - 1) {
71             if (i + x < SZ(b)) b[i] = b[i + x];
72             else b[i] = 0;
73         }
74         return (*this);
75     }
76
77     Bitset operator>>(int x)const {
78         return (Bitset(*this) >>= x);
79     }
80
81     Bitset &operator<<=(int x) {
82         if (x & 63) {
83             for (int i = SZ(b) - 1; i >= 1; i--) {
84                 b[i] <<= (x & 63);
85                 b[i] ^= b[i - 1] >> (64 - (x & 63));
86             }
87             b[0] <<= x & 63;
88         }
89
90         x >>= 6;
91         for (int i = SZ(b) - 1; i >= 0; i--) {
92             if (i - x >= 0) b[i] = b[i - x];
93             else b[i] = 0;
94         }
95         return (*this);

```

```

96     }
97
98     Bitset operator<<(int x) const {
99         return (Bitset(*this) <<= x);
100     }
101 };

```

8.3 fastIO.cpp

```

1 static struct FastInput {
2     static constexpr int BUF_SIZE = 1 << 20;
3     char buf[BUF_SIZE];
4     size_t chars_read = 0;
5     size_t buf_pos = 0;
6     FILE *in = stdin;
7     char cur = 0;
8
9     inline char get_char() {
10         if (buf_pos >= chars_read) {
11             chars_read = fread(buf, 1, BUF_SIZE, in);
12             buf_pos = 0;
13             buf[0] = (chars_read == 0 ? -1 : buf[0]);
14         }
15         return cur = buf[buf_pos++];
16     }
17
18     template <typename T>
19     inline void tie(T) {}
20
21     inline explicit operator bool() {
22         return cur != -1;
23     }
24
25     inline static bool is_blank(char c) {
26         return c <= ' ';
27     }
28
29     inline bool skip_blanks() {
30         while (is_blank(cur) && cur != -1) {
31             get_char();
32         }
33         return cur != -1;
34     }

```

```

35
36     inline FastInput& operator>>(char& c) {
37         skip_blanks();
38         c = cur;
39         get_char();
40         return *this;
41     }
42
43     inline FastInput& operator>>(string& s) {
44         if (skip_blanks()) {
45             s.clear();
46             do {
47                 s += cur;
48             } while (!is_blank(get_char()));
49         }
50         return *this;
51     }
52
53     template <typename T>
54     inline FastInput& read_integer(T& n) {
55         // unsafe, doesn't check that characters are actually digits
56         n = 0;
57         if (skip_blanks()) {
58             int sign = +1;
59             if (cur == '-') {
60                 sign = -1;
61                 get_char();
62             }
63             do {
64                 n += n * (n << 3) + cur - '0';
65             } while (!is_blank(get_char()));
66             n *= sign;
67         }
68         return *this;
69     }
70
71     template <typename T>
72     inline typename enable_if<is_integral<T>::value, FastInput&>::type
73         operator>>(T& n) {
74         return read_integer(n);
75     }
76
77     #if !defined(_WIN32) || defined(_WIN64)

```

```

77 inline FastInput& operator>>(__int128& n) {
78     return read_integer(n);
79 }
80 #endif
81
82 template <typename T>
83 inline typename enable_if<is_floating_point<T>::value, FastInput&>::type
84     operator>>(T& n) {
85     // not sure if really fast, for compatibility only
86     n = 0;
87     if (skip_blanks()) {
88         string s;
89         (*this) >> s;
90         sscanf(s.c_str(), "%lf", &n);
91     }
92     return *this;
93 } fast_input;
94
95 #define cin fast_input
96
97 static struct FastOutput {
98     static constexpr int BUF_SIZE = 1 << 20;
99     char buf[BUF_SIZE];
100     size_t buf_pos = 0;
101     static constexpr int TMP_SIZE = 1 << 20;
102     char tmp[TMP_SIZE];
103     FILE *out = stdout;
104
105     inline void put_char(char c) {
106         buf[buf_pos++] = c;
107         if (buf_pos == BUF_SIZE) {
108             fwrite(buf, 1, buf_pos, out);
109             buf_pos = 0;
110         }
111     }
112
113     ~FastOutput() {
114         fwrite(buf, 1, buf_pos, out);
115     }
116
117     inline FastOutput& operator<<(char c) {
118         put_char(c);

```

```

119     return *this;
120 }
121
122 inline FastOutput& operator<<(const char* s) {
123     while (*s) {
124         put_char(*s++);
125     }
126     return *this;
127 }
128
129 inline FastOutput& operator<<(const string& s) {
130     for (int i = 0; i < (int) s.size(); i++) {
131         put_char(s[i]);
132     }
133     return *this;
134 }
135
136 template <typename T>
137 inline char* integer_to_string(T n) {
138     // beware of TMP_SIZE
139     char* p = tmp + TMP_SIZE - 1;
140     if (n == 0) {
141         *--p = '0';
142     } else {
143         bool is_negative = false;
144         if (n < 0) {
145             is_negative = true;
146             n = -n;
147         }
148         while (n > 0) {
149             *--p = (char) ('0' + n % 10);
150             n /= 10;
151         }
152         if (is_negative) {
153             *--p = '-';
154         }
155     }
156     return p;
157 }
158
159 template <typename T>
160 inline typename enable_if<is_integral<T>::value, char*>::type stringify(T
161     n) {

```

```

161     return integer_to_string(n);
162 }
163
164 #if !defined(_WIN32) || defined(_WIN64)
165 inline char* stringify(__int128 n) {
166     return integer_to_string(n);
167 }
168 #endif
169
170 template <typename T>
171 inline typename enable_if<is_floating_point<T>::value, char*>::type
172     stringify(T n) {
173     sprintf(tmp, "%.17f", n);
174     return tmp;
175 }
176
177 template <typename T>
178 inline FastOutput& operator<<(const T& n) {
179     auto p = stringify(n);
180     for (; *p != 0; p++) {
181         put_char(*p);
182     }
183     return *this;
184 } fast_output;
185
186 #define cout fast_output

```

8.4 FastMod.cpp

```

1 Description: Compute  $a \% b$  about 5 times faster than usual, where  $b$  is
2 constant but not known at compile time. Returns a value congruent to  $a$ 
3  $(\text{mod } b)$  in the range  $[0, 2b)$ .
4
5 typedef unsigned long long ull;
6 struct FastMod {
7     ull b, m;
8     FastMod(ull b) : b(b), m((-1ULL / b) {}
9     ull reduce(ull a) { //  $a \% b + (0 \text{ or } b)$ 
10         return a - (ull)((__uint128_t(m) * a) >> 64) * b;
11     }
12 };

```

8.5 intervalContainer.cpp

```

1 Description: Add and remove intervals from a set of disjoint intervals.
2 Will merge the added interval with any overlapping intervals in the set when
3 adding. Intervals are [inclusive, exclusive).
4 Time:  $O(\log N)$ 
5
6 set<pii>::iterator addInterval(set<pii>& is, int L, int R) {
7     if (L == R) return is.end();
8     auto it = is.lower_bound({L, R}), before = it;
9     while (it != is.end() && it->first <= R) {
10         R = max(R, it->second);
11         before = it = is.erase(it);
12     }
13     if (it != is.begin() && (--it)->second >= L) {
14         L = min(L, it->first);
15         R = max(R, it->second);
16         is.erase(it);
17     }
18     return is.insert(before, {L, R});
19 }
20 void removeInterval(set<pii>& is, int L, int R) {
21     if (L == R) return;
22     auto it = addInterval(is, L, R);
23     auto r2 = it->second;
24     if (it->first == L) is.erase(it);
25     else (int&)it->second = L;
26     if (R != r2) is.emplace(R, r2);
27 }

```

8.6 lineContainer.cpp

```

1 /**
2  * Author: Simon Lindholm
3  * Date: 2017-04-20
4  * License: CC0
5  * Source: own work
6  * Description: Container where you can add lines of the form  $kx+m$ , and
7     query maximum values at points  $x$ .
8  * Useful for dynamic programming ('`convex hull trick`').
9  * Time:  $O(\log N)$ 
10  * Status: stress-tested
11 */
12 #pragma once

```

```

12
13 struct Line {
14     mutable ll k, m, p;
15     bool operator<(const Line& o) const { return k < o.k; }
16     bool operator<(ll x) const { return p < x; }
17 };
18
19 struct LineContainer : multiset<Line, less<>> {
20     // (for doubles, use inf = 1/.0, div(a,b) = a/b)
21     static const ll inf = LLONG_MAX;
22     ll div(ll a, ll b) { // floored division
23         return a / b - ((a ^ b) < 0 && a % b); }
24     bool isect(iterator x, iterator y) {
25         if (y == end()) return x->p = inf, 0;
26         if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
27         else x->p = div(y->m - x->m, x->k - y->k);
28         return x->p >= y->p;
29     }
30     void add(ll k, ll m) {
31         auto z = insert({k, m, 0}), y = z++, x = y;
32         while (isect(y, z)) z = erase(z);
33         if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
34         while ((y = x) != begin() && (--x)->p >= y->p)
35             isect(x, erase(y));
36     }
37     ll query(ll x) {
38         assert(!empty());
39         auto l = *lower_bound(x);
40         return l.k * x + l.m;
41     }
42 };

```

8.7 mint.cpp

```

1 template<int MOD, int RT> struct mint {
2     static const int mod = MOD;
3     static constexpr mint rt() { return RT; } // primitive root for FFT
4     int v; explicit operator int() const { return v; } // explicit -> don't
        silently convert to int
5     mint():v(0) {}
6     mint(ll _v) { v = int((-MOD < _v && _v < MOD) ? _v : _v % MOD);
7         if (v < 0) v += MOD; }
8     bool operator==(const mint& o) const {

```

```

9         return v == o.v; }
10     friend bool operator!=(const mint& a, const mint& b) {
11         return !(a == b); }
12     friend bool operator<(const mint& a, const mint& b) {
13         return a.v < b.v; }
14
15     mint& operator+=(const mint& o) {
16         if ((v += o.v) >= MOD) v -= MOD;
17         return *this; }
18     mint& operator-=(const mint& o) {
19         if ((v -= o.v) < 0) v += MOD;
20         return *this; }
21     mint& operator*=(const mint& o) {
22         v = int((ll)v*o.v%MOD); return *this; }
23     mint& operator/=(const mint& o) { return (*this) *= inv(o); }
24     friend mint pow(mint a, ll p) {
25         mint ans = 1; assert(p >= 0);
26         for (; p; p /= 2, a *= a) if (p&1) ans *= a;
27         return ans; }
28     friend mint inv(const mint& a) { assert(a.v != 0);
29         return pow(a,MOD-2); }
30
31     mint operator-() const { return mint(-v); }
32     mint& operator++() { return *this += 1; }
33     mint& operator--() { return *this -= 1; }
34     friend mint operator+(mint a, const mint& b) { return a += b; }
35     friend mint operator-(mint a, const mint& b) { return a -= b; }
36     friend mint operator*(mint a, const mint& b) { return a *= b; }
37     friend mint operator/(mint a, const mint& b) { return a /= b; }
38 };
39
40 const int MOD=998244353;
41 using mi = mint<MOD,5>; // 5 is primitive root for both common mods
42
43 namespace simp {
44     vector<mi> fac,ifac,invn;
45     void check(int x) {
46         if (fac.empty()) {
47             fac={mi(1),mi(1)};
48             ifac={mi(1),mi(1)};
49             invn={mi(0),mi(1)};
50         }
51         while (SZ(fac)<=x) {

```



```

52         int n=SZ(fac),m=SZ(fac)*2;
53         fac.resize(m);
54         ifac.resize(m);
55         invn.resize(m);
56         for (int i=n;i<m;i++) {
57             fac[i]=fac[i-1]*mi(i);
58             invn[i]=mi(MOD-MOD/i)*invn[MOD%i];
59             ifac[i]=ifac[i-1]*invn[i];
60         }
61     }
62 }
63 mi gfac(int x) {
64     check(x); return fac[x];
65 }
66 mi ginv(int x) {
67     check(x); return invn[x];
68 }
69 mi gifac(int x) {
70     check(x); return ifac[x];
71 }
72 mi binom(int n,int m) {
73     if (m < 0 || m > n) return mi(0);
74     return gfac(n)*gifac(m)*gifac(n - m);
75 }
76 }

```

8.8 pbds.cpp

```

1  #include <bits/extc++.h>
2  using namespace __gnu_cxx;
3  using namespace __gnu_pbds;
4
5  #include<ext/pb_ds/assoc_container.hpp>
6  #include<ext/pb_ds/tree_policy.hpp>
7  #include<ext/pb_ds/hash_policy.hpp>
8  #include<ext/pb_ds/trie_policy.hpp>
9  #include<ext/pb_ds/priority_queue.hpp>
10
11 pairing_heap_tag: 配对堆
12 thin_heap_tag: 斐波那契堆
13 binomial_heap_tag: 二项堆
14 binary_heap_tag: 二叉堆
15

```

```

16 __gnu_pbds::priority_queue<PII, greater<PII>, pairing_heap_tag> q;
17 __gnu_pbds::priority_queue<PII, greater<PII>, pairing_heap_tag>::
    point_iterator its[N];
18
19 its[v] = q.push({dis[v], v});
20 q.modify(its[v], {dis[v], v});
21
22 可以将两个优先队列中的元素合并（无任何约束）
23 使用方法为a.join(b)
24 此时优先队列b内所有元素就被合并进优先队列a中，且优先队列b被清空
25
26 cc_hash_table<string, int> mp1拉链法
27 gp_hash_table<string, int> mp2查探法

```

8.9 simu.cpp

```

1  db rnd(db l, db r) {
2      static uniform_real_distribution<db> u(0, 1);
3      static default_random_engine e(rng());
4      return l + (r - l) * u(e); // u(rng);
5  }
6
7  db eval(pair<db, db> x) { ... }
8
9  void simulate_anneal() {
10     pair<db, db> cur(rnd(0, 10000), rnd(0, 10000));
11     for (double k = 10000; k > 1e-5; k *= 0.99) {
12         // [start, end, step]
13         pair<db, db> nxt(cur.fi + rnd(-k, k), cur.se + rnd(-k, k));
14         db delta = eval(nxt) - eval(cur);
15         if (exp(-delta / k) > rnd(0, 1)) {
16             cur = nxt;
17         }
18     }
19 }
20
21 /**
22  * https://codeforces.com/gym/104813/submission/234982955
23  * The 9th CCPC (Harbin) 2023
24  * Author: QwertyPi
25  */
26 LD Prob() {
27     static uniform_real_distribution<> dist(0.0, 1.0);

```

```

28     return dist(rng);
29 }
30 LD Sigma(LD x) { return 1 / (1 + exp(-x)); }
31
32 LD overall_max_score = 0;
33 for (int main_loop = 0; main_loop < 5; main_loop++) {
34     vector<LD> e(n, (LD)1 / n);
35     for (int tr = 0; tr < 1000; tr++) {
36         vector<LD> ne(n);
37         for (int i = 0; i < n; i++) {
38             ne[i] = Prob();
39         }
40         LD s = accumulate(all(ne), 0.0L);
41         for (int i = 0; i < n; i++) {
42             ne[i] /= s;
43         }
44         if (eval(ne) > eval(e)) e = ne;
45     }
46     LD t = (LD)0.0002;
47     LD max_score = 0;
48     const LD depr = 0.999995;
49     const int tries = 2E6;
50     const int loop = 1E5;
51
52     LD score_old = eval(e);
53     for (int tr = 0; tr < tries; tr++) {
54 #ifdef LOCAL
55         if (tr % loop == loop - 1) {
56             cout << fixed << setprecision(10) << "current_score=" << max_score
57                 << ", t=" << t << '\n';
58         }
59 #endif
60         int x = rng() % n, y = rng() % n;
61         if (e[x] < t || x == y) {
62             t *= depr;
63             continue;
64         }
65         e[x] -= t;
66         e[y] += t;
67         LD score_new = eval(e);
68         if (score_new > score_old) { // ok
69             ;
70         } else { // revert

```

```

71         e[x] += t;
72         e[y] -= t;
73     }
74     score_old = score_new;
75     max_score = max(max_score, score_new);
76     t *= depr;
77 }
78 overall_max_score = max(overall_max_score, max_score);
79 #ifdef LOCAL
80     cout << "Loop#" << main_loop << ": " << max_score << '\n';
81 #endif
82 }

```

8.10 sort.cpp

```

1 void merge_sort(int q[], int l, int r) {
2     if (l >= r) return;
3     int mid = l + r >> 1;
4     merge_sort(q, l, mid);
5     merge_sort(q, mid + 1, r);
6
7     int k = 0, i = l, j = mid + 1;
8     while (i <= mid && j <= r)
9         if (q[i] <= q[j])
10             tmp[k++] = q[i++];
11         else
12             tmp[k++] = q[j++];
13
14     while (i <= mid)
15         tmp[k++] = q[i++];
16     while (j <= r)
17         tmp[k++] = q[j++];
18
19     for (i = l, j = 0; i <= r; i++, j++) q[i] = tmp[j];
20 }
21
22 void quick_sort(int q[], int l, int r) {
23     if (l >= r) return;
24     int i = l - 1, j = r + 1, x = q[l + r >> 1];
25     while (i < j) {
26         do i ++ ; while (q[i] < x);
27         do j -- ; while (q[j] > x);
28         if (i < j) swap(q[i], q[j]);

```

```

29     }
30     quick_sort(q, l, j), quick_sort(q, j + 1, r);
31 }
32
33 template<class T>
34 void radixsort(T *a, ll n) {
35     int base = 0;
36     rep(i, 1, n) sa[i] = i;
37     rep(k, 1, 5) {
38         rep(i, 0, 255) c[i] = 0;
39         rep(i, 1, n) c[(a[i] >> base) & 255]++;
40         rep(i, 1, 255) c[i] += c[i - 1];
41         per(i, n, 1) {
42             rk[sa[i]] = c[(a[sa[i]] >> base) & 255]--;
43         }
44         rep(i, 1, n) sa[rk[i]] = i;
45         base += 7;
46     }
47 }

```

8.11 高精度.cpp

```

1 vector<int> add(vector<int> &A, vector<int> &B) {
2     if (A.size() < B.size()) return add(B, A);
3     vector<int> C;
4     int t = 0;
5     for (int i = 0; i < A.size(); i++) {
6         t += A[i];
7         if (i < B.size()) t += B[i];
8         C.push_back(t % 10);
9         t /= 10;
10    }
11    if (t) C.push_back(t);
12    return C;
13 }
14
15 vector<int> sub(vector<int> &A, vector<int> &B) {

```

```

16    vector<int> C;
17    for (int i = 0, t = 0; i < A.size(); i++) {
18        t = A[i] - t;
19        if (i < B.size()) t -= B[i];
20        C.push_back((t + 10) % 10);
21        if (t < 0) t = 1;
22        else t = 0;
23    }
24    while (C.size() > 1 && C.back() == 0) C.pop_back();
25    return C;
26 }
27
28 vector<int> mul(vector<int> &A, int b) {
29     vector<int> C;
30     int t = 0;
31     for (int i = 0; i < A.size() || t; i++) {
32         if (i < A.size()) t += A[i] * b;
33         C.push_back(t % 10);
34         t /= 10;
35     }
36     while (C.size() > 1 && C.back() == 0) C.pop_back();
37     return C;
38 }
39
40 vector<int> div(vector<int> &A, int b, int &r) {
41     vector<int> C;
42     r = 0;
43     for (int i = A.size() - 1; i >= 0; i--) {
44         r = r * 10 + A[i];
45         C.push_back(r / b);
46         r %= b;
47     }
48     reverse(C.begin(), C.end());
49     while (C.size() > 1 && C.back() == 0) C.pop_back();
50     return C;
51 }

```