

Team Reference Document

Heltion

2024 年 5 月 10 日

目录

1 Template

1.1 .clang-format

```
1 BasedOnStyle: Google
2 IndentWidth: 4
3 ColumnLimit: 160
```

1.2 debug.cpp

```
1 #include <bits/stdc++.h>
2
3 using namespace std;
4
5 template <class T, size_t size = tuple_size<T>::value>
6 string to_debug(T, string s = "") requires(not ranges::range<T>);
7
8 template<class T>
9 concept check = requires(T x, ostream &os) {
10     os << x;
11 };
12
13 template<check T>
14 string to_debug(T x) {
15     return static_cast<ostringstream>(ostringstream() << x).str();
16 }
17
18 string to_debug(ranges::range auto x, string s = "") requires(not
19     is_same_v<decltype(x), string>) {
20     for (auto xi : x) {
21         s += ",_" + to_debug(xi);
22     }
23     return "[" + s.substr(s.empty() ? 0 : 2) + "_]";
24 }
25
26 template <class T, size_t size>
27 string to_debug(T x, string s) requires(not ranges::range<T>) {
28     [&<size_t... I>(index_sequence<I...>) {
```

```
28         ((s += ",_" + to_debug(get<I>(x))), ...);
29     }(make_index_sequence<size>());
30     return "{" + s.substr(s.empty() ? 0 : 2) + "}";
31 }
32
33 #define debug(...) [](auto... $){ ((cout << to_debug($) << "_"), ...);
34     cout << endl; }("[", #__VA_ARGS__, "]:", __VA_ARGS__)
```

1.3 gen.py

```
1 from random import *
2 n=1000
3 q=10000
4 for i in range(q):
5     op=randint(0,1)
6     x=randint(0,n-1)
7     y=randint(0,n-1)
8     if op==1:print(op,x,y)
9     else:print(op,x)
```

1.4 head.cpp

```
1 #pragma GCC optimize(2,"Ofast","inline","unroll-loops")
2 #include <bits/stdc++.h>
3 using namespace std;
4 #define rep(i,a,n) for (int i=a;i<=n;i++)
5 #define per(i,a,n) for (int i=a;i>=n;i--)
6 #define pb push_back
7 #define eb emplace_back
8 #define mp make_pair
9 #define all(x) (x).begin(),(x).end()
10 #define bit(x) (1ll<<(x))
11 #define fi first
12 #define se second
13 #define SZ(x) ((int)(x).size())
14 typedef vector<int> VI;
15 typedef long long ll;
16 typedef pair<int, int> PII;
17 typedef double db;
18 mt19937_64 rng(random_device {}());
19 typedef long double ldb;
```

```

20 typedef unsigned long long ull;
21 ll powmod(ll a,ll b,const ll p) { ll res=1; while (b) { if (b&1) res=res*a
    %p; b>>=1; a=a*a%p; } return res; }
22 // head
23
24 #ifdef DEBUG
25 #include "debug.cpp"
26 #else
27 #define debug(...) 42
28 #endif
29
30 const int mod = 1e9 + 7;
31 const ll inf = 1ll << 55;
32 const double pi = acos(-1);
33 const double eps = 1e-12;
34 const int maxn = 2e5 + 105;
35 const int N = 2000005;
36
37 void solve() {}
38 int main() {
39     ios::sync_with_stdio(false);
40     cin.tie(nullptr);
41     int tt = 1;
42     // cin >> tt;
43     while (tt--) {
44         solve();
45     }
46 }

```

1.5 head apiadu.cpp

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 #define rep(i,a,n) for (int i=a;i<n;i++)
4 #define per(i,a,n) for (int i=n-1;i>=a;i--)
5 #define pb push_back
6 #define eb emplace_back
7 #define mp make_pair
8 #define all(x) (x).begin(),(x).end()
9 #define fi first
10 #define se second

```

```

11 #define SZ(x) ((int)(x).size())
12 typedef vector<int> VI;
13 typedef basic_string<int> BI;
14 typedef long long ll;
15 typedef pair<int,int> PII;
16 typedef double db;
17 mt19937 mrand(random_device{}());
18 const ll mod=1000000007;
19 int rnd(int x) { return mrand() % x;}
20 ll powmod(ll a,ll b) {ll res=1;a%=mod; assert(b>=0); for(;;b>>=1){if(b&1)
    res=res*a%mod;a=a*a%mod;}return res;}
21 ll gcd(ll a,ll b) { return b?gcd(b,a%b):a;}
22 // head

```

1.6 Makefile

```

1 %: %.cpp
2     g++-13 $< -o $@ -std=gnu++20 -g -O2 -Wall -Wextra -DDEBUG -
    D_GLIBCXX_DEBUG -D_GLIBCXX_DEBUG_PEDANTIC

```

1.7 pai.py

```

1 import os
2 tt=0
3 while True:
4     os.system('python gen.py>A.in')
5     os.system('./a<A.in>a.out')
6     os.system('./b<A.in>b.out')
7     if os.system('fc A.out b.out'):
8         print("WA")
9         exit(0)
10    else:
11        tt+=1
12        print("AC:",tt)

```

1.8 settings.json

```

1 {
2     "editor.formatOnSave": true,
3     "files.autoSave": "afterDelay",
4     "files.autoSaveDelay": 350,

```

```

5     "C_Cpp.default.cppStandard": "gnu++20"
6 }

```

1.9 template.cpp

```

1 #pragma GCC optimize(2, "Ofast", "inline", "unroll-loops")
2 #include <bits/stdc++.h>
3 using namespace std;
4 #define rep(i, a, n) for (int i = a; i <= n; i++)
5 #define per(i, a, n) for (int i = a; i >= n; i--)
6 #define pb push_back
7 #define eb emplace_back
8 #define all(x) (x).begin(), (x).end()
9 #define bit(x) (1ll << (x))
10 #define fi first
11 #define se second
12 #define SZ(x) ((int)(x).size())
13 using VI = vector<int>;
14 using PII = pair<int, int>;
15 using ll = long long;
16 using ull = unsigned long long;
17 using db = double;
18 using ldb = long double;
19 mt19937_64 rng(chrono::steady_clock::now().time_since_epoch().count());
20 // head
21
22 #ifdef DEBUG
23 #include "debug.cpp"
24 #else
25 #define debug(...) 42
26 #endif
27
28 void solve() {}
29 int main() {
30     cin.tie(nullptr)->sync_with_stdio(false);
31     cout << fixed << setprecision(16);
32     int tt = 1;
33     cin >> tt;
34     while (tt--) {
35         solve();
36     }

```

```

37 }

```

2 Data

2.1 01trie.cpp

```

1 struct node {
2     int son[2];
3     int end;
4     int sz;
5 } seg[maxn << 2];
6 int root, tot;
7 int n, m;
8
9 void insert(ll x) {
10     int cnt = root;
11     for (int i = 62; i >= 0; i--) {
12         int w = (x >> i) & 1;
13         if (seg[cnt].son[w] == 0) seg[cnt].son[w] = ++tot;
14         cnt = seg[cnt].son[w];
15         seg[cnt].sz++;
16     }
17     seg[cnt].end++;
18 }
19
20 ll query(ll x, ll k) {
21     ll res = 0;
22     int cnt = root;
23     for (int i = 62; i >= 0; i--) {
24         int w = (x >> i) & 1;
25         if (seg[seg[cnt].son[w]].sz >= k) cnt = seg[cnt].son[w];
26         else {
27             k -= seg[seg[cnt].son[w]].sz;
28             cnt = seg[cnt].son[abs(w - 1)];
29             res += bit(i);
30         }
31     }
32     return res;
33 }

```

2.2 2dtree(bqi343).cpp

```

1  const int SZ = 1.1e5;
2  template <class T>
3  struct node {
4      T val = 0;
5      node<T>* c[2];
6      node() { c[0] = c[1] = NULL; }
7      void upd(int ind, T v, int L = 0, int R = SZ - 1) { // add v
8          if (L == ind && R == ind) {
9              val += v;
10             return;
11         }
12         int M = (L + R) / 2;
13         if (ind <= M) {
14             if (!c[0]) c[0] = new node();
15             c[0]->upd(ind, v, L, M);
16         } else {
17             if (!c[1]) c[1] = new node();
18             c[1]->upd(ind, v, M + 1, R);
19         }
20         val = 0;
21         rep(i, 0, 1) if (c[i]) val += c[i]->val;
22     }
23     T query(int lo, int hi, int L = 0, int R = SZ - 1) { // query sum
        of segment
24         if (hi < L || R < lo) return 0;
25         if (lo <= L && R <= hi) return val;
26         int M = (L + R) / 2;
27         T res = 0;
28         if (c[0]) res += c[0]->query(lo, hi, L, M);
29         if (c[1]) res += c[1]->query(lo, hi, M + 1, R);
30         return res;
31     }
32     void UPD(int ind, node* c0, node* c1, int L = 0, int R = SZ - 1) {
        // for 2D segtree
33         if (L != R) {
34             int M = (L + R) / 2;
35             if (ind <= M) {
36                 if (!c[0]) c[0] = new node();
37                 c[0]->UPD(ind, c0 ? c0->c[0] : NULL, c1 ?
                    c1->c[0] : NULL, L, M);

```

```

38             } else {
39                 if (!c[1]) c[1] = new node();
40                 c[1]->UPD(ind, c0 ? c0->c[1] : NULL, c1 ?
                    c1->c[1] : NULL, M + 1, R);
41             }
42         }
43         val = (c0 ? c0->val : 0) + (c1 ? c1->val : 0);
44     }
45 };
46
47 /**
48  * Description: BIT of SegTrees. $x\in (0,SZ), y\in [0,SZ)$.
49  * Memory:  $O(N\log^2 N)$ 
50  * Source: USACO Mowing the Field
51  * Verification:
52  * USACO Mowing the Field
53  * http://www.usaco.org/index.php?page=viewproblem2&cpid=722 (13/15, 15/15
        and 1857ms with BumpAllocator)
54  */
55
56 #include "../1D_Range_Queries_(9.2)/SparseSeg_(9.2).h"
57
58 template <class T>
59 struct BITseg {
60     node<T> seg[SZ];
61     BITseg() { fill(seg, seg + SZ, node<T>()); }
62     void upd(int x, int y, int v) { // add v
63         for (; x < SZ; x += x & -x) seg[x].upd(y, v);
64     }
65     T query(int x, int yl, int yr) {
66         T res = 0;
67         for (; x; x -= x & -x) res += seg[x].query(yl, yr);
68         return res;
69     }
70     T query(int xl, int xr, int yl, int yr) { // query sum of
        rectangle
71         return query(xr, yl, yr) - query(xl - 1, yl, yr);
72     }
73 };
74
75 /**
76  * Description: SegTree of SegTrees. $x,y\in [0,SZ)$. $

```

```

77  * Memory:  $O(N \log^2 N)$ 
78  * Source: USACO Mowing the Field
79  * Verification:
80  * http://www.usaco.org/index.php?page=viewproblem2&cpid=722 (9/15 w/
    BumpAllocator)
81  * http://www.usaco.org/index.php?page=viewproblem2&cpid=601 (4238 ms,
    2907 ms w/ BumpAllocator)
82  */
83
84  #include "../1D_Range_Queries_(9.2)/SparseSeg_(9.2).h"
85
86  template <class T>
87  struct Node {
88      node<T> seg;
89      Node* c[2];
90      Node() { c[0] = c[1] = NULL; }
91      void upd(int x, int y, T v, int L = 0, int R = SZ - 1) { // add v
92          if (L == x && R == x) {
93              seg.upd(y, v);
94              return;
95          }
96          int M = (L + R) / 2;
97          if (x <= M) {
98              if (!c[0]) c[0] = new Node();
99              c[0]->upd(x, y, v, L, M);
100          } else {
101              if (!c[1]) c[1] = new Node();
102              c[1]->upd(x, y, v, M + 1, R);
103          }
104          seg.upd(y, v); // only for addition
105          // seg.UPD(y, c[0]?&c[0]->seg:NULL, c[1]?&c[1]->seg:NULL);
106      }
107      T query(int x1, int x2, int y1, int y2, int L = 0, int R = SZ - 1)
108      { // query sum of rectangle
109          if (x1 <= L && R <= x2) return seg.query(y1, y2);
110          if (x2 < L || R < x1) return 0;
111          int M = (L + R) / 2;
112          T res = 0;
113          if (c[0]) res += c[0]->query(x1, x2, y1, y2, L, M);
114          if (c[1]) res += c[1]->query(x1, x2, y1, y2, M + 1, R);
115          return res;
116      }

```

```

116  };

```

2.3 cdq.cpp

```

1  int ans[maxn], lev[maxn];
2  array<int, 5> v[maxn], tmp[maxn];
3
4  struct BIT {
5      ...
6  } c;
7
8  void solve(int l, int r) {
9      if (l >= r) return;
10     int mid = (l + r) / 2;
11     solve(l, mid), solve(mid + 1, r);
12     int i = l, j = mid + 1;
13     int piv = 1;
14     while (i <= mid || j <= r) {
15         if (i <= mid && (j > r || mp(v[i][1], v[i][2]) <= mp(v[j][1], v[j]
16             [2]))) {
17             c.modify(v[i][2], v[i][3]);
18             tmp[piv++] = v[i++];
19         } else {
20             v[j][4] += c.query(v[j][2]);
21             tmp[piv++] = v[j++];
22         }
23     }
24     rep(i, l, mid) c.modify(v[i][2], -v[i][3]);
25     rep(i, l, r) v[i] = tmp[i];
26 }
27
28 void solve() {
29     cin >> n >> k;
30     c.resize(k);
31     rep(i, 1, n) {
32         int s, c, m;
33         cin >> s >> c >> m;
34         v[i] = {s, c, m, 1, 0};
35     }
36     v[0][0] = -1;
37     sort(v + 1, v + n + 1);

```

```

37     int cnt = 0;
38     rep(i, 1, n) {
39         if (v[i][0] == v[cnt][0] && v[i][1] == v[cnt][1] && v[i][2] == v[
            cnt][2]) v[cnt][3]++;
40         else v[++cnt] = v[i];
41     }
42     solve(1, cnt);
43     rep(i, 1, cnt) {
44         ans[v[i][4] + v[i][3] - 1] += v[i][3];
45     }
46     rep(i, 0, n - 1) cout << ans[i] << '\n';
47 }

```

2.4 compact.cpp

```

1 namespace compact {
2     const int LOGN=18;
3     int l[N],r[N],tot,p[N][20],n;
4     map<int,int> cv;
5     int lca(int u,int v) {
6         if (dep[u]>dep[v]) swap(u,v);
7         per(i,LOGN-1,0) if (dep[p[v][i]]>=dep[u]) v=p[v][i];
8         if (u==v) return u;
9         per(i,LOGN-1,0) if (p[v][i]!=p[u][i]) u=p[u][i],v=p[v][i];
10        return p[u][0];
11    }
12    void dfs(int u,int f) {
13        l[u]=++tot; dep[u]=dep[f]+1; p[u][0]=f;
14        vec[dep[u]].pb(u);
15        for (auto v:vE[u]) {
16            if (v==f) continue;
17            dfs(v,u);
18        }
19        r[u]=tot;
20    }
21    void build(int _n) {
22        n=_n; tot=0;
23        dfs(1,0);
24        rep(j,1,LOGN-1) rep(i,1,n) p[i][j]=p[p[i][j-1]][j-1];
25    }
26

```

```

27 bool cmp(int u,int v) { return l[u]<l[v]; }
28 vector<PII> compact(VI v) {
29     int m=SZ(v);
30     vector<PII> E;
31     sort(all(v),cmp);
32     rep(i,0,m-2) {
33         int w=lca(v[i],v[i+1]);
34         v.pb(w);
35     }
36     v.pb(0);
37     v.pb(1);
38     sort(all(v),cmp);
39     v.erase(unique(all(v)),v.end());
40     cv.clear();
41     per(i,SZ(v)-1,1) {
42         int u=v[i];
43         while (1) {
44             auto it=cv.lower_bound(l[u]);
45             if (it==cv.end()||it->fi>r[u]) break;
46             E.pb(mp(u,v[it->se]));
47             cv.erase(it);
48         }
49         cv[l[u]]=i;
50     }
51     return E;
52 }
53 };

```

2.5 dominator.cpp

```

1 void solve(int u, int S) {
2     int best = -1, cnt = S + 1;
3     auto find_best = [&](auto &find_best, int u, int par) -> void {
4         sz[u] = 1, sdom[u] = 0;
5         for (auto v : e[u]) {
6             if (v == par || del[v]) continue;
7             find_best(find_best, v, u);
8             sz[u] += sz[v];
9             sdom[u] = max(sdom[u], sz[v]);
10        }
11        sdom[u] = max(sdom[u], S - sz[u]);

```

```

12         if (sdom[u] < cnt) {
13             cnt = sdom[u], best = u;
14         }
15     };
16     find_best(find_best, u, 0);
17     int id1 = tot++, dep1 = 0;
18     int id2, dep2;
19     auto dfs = [&](auto &dfs, int u, int par, int dep) -> void {
20         dep1 = max(dep1, dep);
21         dep2 = max(dep2, dep);
22         Q[u].pb({id1, 1, dep});
23         Q[u].pb({id2, -1, dep});
24         for (auto v : e[u]) {
25             if (v == par || del[v]) continue;
26             dfs(dfs, v, u, dep + 1);
27         }
28     };
29     Q[best].pb({id1, 1, 0});
30     for (auto v : e[best]) {
31         if (del[v]) continue;
32         id2 = tot++, dep2 = 0;
33         dfs(dfs, v, best, 1);
34         fenw[id2] = BIT<ll>(dep2 + 1);
35     }
36     fenw[id1] = BIT<ll>(dep1 + 1);
37     del[best] = 1;
38     for (auto v : e[best]) {
39         if (!del[v]) solve(v, sz[v]);
40     }
41 }

```

2.6 dsu.cpp

```

1 class dsu {
2 public:
3     vector<int> fa;
4     vector<ll> dist;
5     int n;
6
7     dsu(int _n) : n(_n) {
8         fa.resize(n);

```

```

9         dist.assign(n, 0);
10        iota(fa.begin(), fa.end(), 0);
11    }
12
13    int find(int x) {
14        if (fa[x] == x) return x;
15        int par = fa[x];
16        fa[x] = find(fa[x]);
17        dist[x] += dist[par];
18        return fa[x];
19    }
20
21    void unite(int x, int y, ll v) {
22        int px = find(x);
23        int py = find(y);
24        fa[py] = px;
25        dist[py] = dist[x] - dist[y] - v;
26    }
27 };

```

2.7 dsu on tree.cpp

```

1 void dfs(int x, int fa) {
2     hs[x] = -1, w[x] = 1;
3     l[x] = ++tot;
4     id[tot] = x;
5     for (auto y : g[x]) if (y != fa) {
6         dfs(y, x);
7         w[x] += w[y];
8         if (hs[x] == -1 || w[y] > w[hs[x]])
9             hs[x] = y;
10    }
11    r[x] = tot;
12 }
13
14 void dsu(int x, int fa, int keep) {
15     for (auto y : g[x]) {
16         if (y != hs[x] && y != fa) {
17             dsu(y, x, 0);
18         }
19     }

```



```

20     if (hs[x] != -1) dsu(hs[x], x, 1);
21
22     for (auto y : g[x]) {
23         if (y != hs[x] && y != fa) {
24             for (int i = l[y]; i <= r[y]; i++) {
25
26             }
27         }
28     }
29     // add current node
30
31     ans[x] = cnt;
32
33     if (!keep) {
34         // clear
35     }
36 }

```

2.8 fenwick.cpp

```

1  template <typename T>
2  struct BIT {
3      vector<T> fenw;
4      int n;
5
6      BIT(int _n = 0) : n(_n) {
7          fenw.assign(n + 1, 0);
8      }
9
10     T query(int x) {
11         T v{};
12         // while (x >= 0) {
13         while (x > 0) {
14             v += fenw[x];
15             x -= (x & -x);
16             // x = (x & (x + 1)) - 1;
17         }
18         return v;
19     }
20
21     void modify(int x, T v) {

```

```

22         if (x <= 0) return; // 1-base
23         // while (x < n) {
24         while (x <= n) {
25             fenw[x] += v;
26             x += (x & -x);
27             // x /= (x + 1);
28         }
29     }
30
31     int kth(T d) { // 1-base
32         int p = 0;
33         T sum{};
34         for (int i = 20; i >= 0; i--) {
35             if (p + bit(i) <= n && sum + fenw[p + bit(i)] <= d
36                 ) {
37                 sum += fenw[p + bit(i)];
38                 p += bit(i);
39             }
40         }
41         return p;
42     };

```

2.9 fenwick2d.cpp

```

1  template <typename T>
2  class fenwick2d {
3  public:
4      vector<vector<T>> fenw;
5      int n, m;
6
7      fenwick2d(int _n, int _m) : n(_n), m(_m) {
8          fenw.resize(n);
9          for (int i = 0; i < n; i++) {
10             fenw[i].resize(m);
11         }
12     }
13
14     inline void modify(int i, int j, T v) {
15         int x = i;
16         while (x < n) {

```

```

17         int y = j;
18         while (y < m) {
19             fenw[x][y] += v;
20             y |= (y + 1);
21         }
22         x |= (x + 1);
23     }
24 }
25
26 inline T get(int i, int j) {
27     T v{};
28     int x = i;
29     while (x >= 0) {
30         int y = j;
31         while (y >= 0) {
32             v += fenw[x][y];
33             y = (y & (y + 1)) - 1;
34         }
35         x = (x & (x + 1)) - 1;
36     }
37     return v;
38 }
39 };
40
41 struct node {
42     int a = ...; // don't forget to set default value
43
44     inline void operator+=(node &other) {
45         ...
46     }
47 };

```

2.10 hash table.cpp

```

1 struct Hash_table {
2     static const int V = 1000003;
3     int fst[V], nxt[V];
4     int ctm, ptm[V], T;
5     int val[V];
6     ll key[V];
7     void init() {T = 0, ctm++;}

```

```

8     void insert(ll k, int v) {
9         int s = k % V;
10        if (ptm[s] != ctm) ptm[s] = ctm, fst[s] = -1;
11        for (int i = fst[s]; i != -1; i = nxt[i]) if (key[i] == k) {
12            return;
13        }
14        nxt[T] = fst[s], fst[s] = T, key[T] = k, val[T] = v;
15        T++;
16    }
17    int query(ll k) {
18        int s = k % V;
19        if (ptm[s] != ctm) return -1;
20        for (int i = fst[s]; i != -1; i = nxt[i]) {
21            if (key[i] == k) return val[i];
22        }
23        return -1;
24    }
25 };

```

2.11 HLD.cpp

```

1 struct HLD {
2     int n;
3     std::vector<int> siz, top, dep, parent, in, out, seq;
4     std::vector<std::vector<int>> adj;
5     int cur;
6
7     HLD() {}
8     HLD(int n) {
9         init(n);
10    }
11    void init(int n) {
12        this->n = n;
13        siz.resize(n);
14        top.resize(n);
15        dep.resize(n);
16        parent.resize(n);
17        in.resize(n);
18        out.resize(n);
19        seq.resize(n);
20        cur = 0;

```

```

21     adj.assign(n, {});
22 }
23 void addEdge(int u, int v) {
24     adj[u].push_back(v);
25     adj[v].push_back(u);
26 }
27 void work(int root = 0) {
28     top[root] = root;
29     dep[root] = 0;
30     parent[root] = -1;
31     dfs1(root);
32     dfs2(root);
33 }
34 void dfs1(int u) {
35     if (parent[u] != -1) {
36         adj[u].erase(std::find(adj[u].begin(), adj[u].end(), parent[u]));
37     }
38
39     siz[u] = 1;
40     for (auto &v : adj[u]) {
41         parent[v] = u;
42         dep[v] = dep[u] + 1;
43         dfs1(v);
44         siz[u] += siz[v];
45         if (siz[v] > siz[adj[u][0]]) {
46             std::swap(v, adj[u][0]);
47         }
48     }
49 }
50 void dfs2(int u) {
51     in[u] = cur++;
52     seq[in[u]] = u;
53     for (auto v : adj[u]) {
54         top[v] = v == adj[u][0] ? top[u] : v;
55         dfs2(v);
56     }
57     out[u] = cur;
58 }
59 int lca(int u, int v) {
60     while (top[u] != top[v]) {
61         if (dep[top[u]] > dep[top[v]]) {

```

```

62         u = parent[top[u]];
63     } else {
64         v = parent[top[v]];
65     }
66 }
67 return dep[u] < dep[v] ? u : v;
68 }
69
70 int dist(int u, int v) {
71     return dep[u] + dep[v] - 2 * dep[lca(u, v)];
72 }
73
74 int jump(int u, int k) {
75     if (dep[u] < k) {
76         return -1;
77     }
78
79     int d = dep[u] - k;
80
81     while (dep[top[u]] > d) {
82         u = parent[top[u]];
83     }
84
85     return seq[in[u] - dep[u] + d];
86 }
87
88 bool isAncestor(int u, int v) {
89     return in[u] <= in[v] && in[v] < out[u];
90 }
91
92 int rootedParent(int u, int v) {
93     std::swap(u, v);
94     if (u == v) {
95         return u;
96     }
97     if (!isAncestor(u, v)) {
98         return parent[u];
99     }
100     auto it = std::upper_bound(adj[u].begin(), adj[u].end(), v, [&](
101         int x, int y) {
102             return in[x] < in[y];
103         }) - 1;

```

```

103     return *it;
104 }
105
106 int rootedSize(int u, int v) {
107     if (u == v) {
108         return n;
109     }
110     if (!isAncestor(v, u)) {
111         return siz[v];
112     }
113     return n - siz[rootedParent(u, v)];
114 }
115
116 int rootedLca(int a, int b, int c) {
117     return lca(a, b) ^ lca(b, c) ^ lca(c, a);
118 }
119 };

```

2.12 kdtree.cpp

```

1 namespace kd {
2     const int K = 2, N = 2.1e5;
3     template <typename T>
4     using P = array<T, K>;
5     template <typename T>
6     struct node {
7         P<T> pt, mx, mn;
8         ll val, sum;
9         node *l, *r, *p;
10        int id;
11        node(const P<T> &_pt = P<T>(), ll _val = 0, int _id = 0) :
12            pt(_pt), val(_val), sum(_val), id(_id) {
13            mx = mn = pt;
14            p = l = r = nullptr;
15        }
16        node<ll> *ptr[N];
17        template <typename T>
18        void pull(node<T> *u) {
19            if (not u) return;
20            u->sum = u->val;

```

```

21        rep(i, 0, K - 1) u->mx[i] = u->mn[i] = u->pt[i];
22        if (u->l) {
23            u->sum += u->l->sum;
24            u->l->p = u;
25        }
26        if (u->r) {
27            u->sum += u->r->sum;
28            u->r->p = u;
29        }
30        rep(i, 0, K - 1) {
31            if (u->l) {
32                u->mx[i] = max(u->mx[i], u->l->mx[i]);
33                u->mn[i] = min(u->mn[i], u->l->mn[i]);
34            }
35            if (u->r) {
36                u->mx[i] = max(u->mx[i], u->r->mx[i]);
37                u->mn[i] = min(u->mn[i], u->r->mn[i]);
38            }
39        }
40    }
41
42    template <typename T>
43    node<T> *build(vector<node<T>> &a, int l, int r, int d = 0) {
44        if (d == K) d = 0;
45        if (l >= r) {
46            return nullptr;
47        } else {
48            int md = (l + r) >> 1;
49            nth_element(a.begin() + l, a.begin() + md, a.begin()
50                + r, [&](node<T> &x, node<T> &y) { return x
51                    .pt[d] < y.pt[d]; });
52            node<T> *p = new node<T>(a[md]);
53            ptr[p->id] = p;
54            p->l = build(a, l, md, d + 1);
55            p->r = build(a, md + 1, r, d + 1);
56            pull(p);
57            return p;
58        }
59    }
60
61    template <typename T>
62    node<T> *search(node<T> *u, P<T> p, int d = 0) {

```

```

61         if (d == K) d = 0;
62         if (not u) return nullptr;
63         if (u->pt == p) return u;
64         if (p[d] < u->pt[d]) {
65             return search(u->l, p, d + 1);
66         } else if (p[d] > u->pt[d]) {
67             return search(u->r, p, d + 1);
68         } else {
69             auto tmp = search(u->l, p, d + 1);
70             if (tmp) return tmp;
71             return search(u->r, p, d + 1);
72         }
73     }
74
75     template <typename T>
76     void modify(node<T> *u, ll v) {
77         if (not u) return;
78         u->val = v;
79         for (auto cur = u; cur; cur = cur->p) {
80             pull(cur);
81         }
82     }
83
84     template <typename T>
85     bool inside(node<T> *nd, P<T> p, ll c) {
86         int cc = 0;
87         if (nd->mx[0] * p[0] + nd->mx[1] * p[1] >= c) cc++;
88         if (nd->mn[0] * p[0] + nd->mn[1] * p[1] >= c) cc++;
89         if (nd->mx[0] * p[0] + nd->mn[1] * p[1] >= c) cc++;
90         if (nd->mn[0] * p[0] + nd->mx[1] * p[1] >= c) cc++;
91         return cc == 0;
92     }
93
94     template <typename T>
95     bool outside(node<T> *nd, P<T> p, ll c) {
96         int cc = 0;
97         if (nd->mx[0] * p[0] + nd->mx[1] * p[1] >= c) cc++;
98         if (nd->mn[0] * p[0] + nd->mn[1] * p[1] >= c) cc++;
99         if (nd->mx[0] * p[0] + nd->mn[1] * p[1] >= c) cc++;
100        if (nd->mn[0] * p[0] + nd->mx[1] * p[1] >= c) cc++;
101        return cc == 4;
102    }

```

```

103
104    template <typename T>
105    ll query(node<T> *u, P<T> p, ll c) {
106        if (inside(u, p, c)) return u->sum;
107        if (outside(u, p, c)) return 0;
108        ll s = 0;
109        if (u->pt[0] * p[0] + u->pt[1] * p[1] < c) {
110            s += u->val;
111        }
112        if (u->l) s += query(u->l, p, c);
113        if (u->r) s += query(u->r, p, c);
114        return s;
115    }
116
117    template <typename T>
118    T eval_min(node<T> *nd, P<T> p) { // 通过估价函数进行启发式搜索，
        根据当前结果对搜索剪枝
119        if (not nd) return numeric_limits<T>::max() / 4;
120        ll s = 0;
121        rep(i, 0, K - 1) {
122            if (p[i] <= nd->mn[i]) s += nd->mn[i] - p[i];
123            if (p[i] >= nd->mx[i]) s += p[i] - nd->mx[i];
124        }
125        return s;
126    }
127
128    template <typename T>
129    ll mindist(node<T> *u, P<T> p) {
130        ll s = numeric_limits<T>::max() / 4;
131        if (u->pt != p) {
132            s = min(s, abs(u->pt[0] - p[0]) + abs(u->pt[1] - p[1]));
133        }
134        ll best1 = eval_min(u->l, p), best2 = eval_min(u->r, p);
135        if (best1 < best2) {
136            if (u->l) s = min(s, mindist(u->l, p));
137            if (u->r and best2 < s) s = min(s, mindist(u->r, p));
138            return s;
139        } else {
140            if (u->r) s = min(s, mindist(u->r, p));
141            if (u->l and best1 < s) s = min(s, mindist(u->l, p));

```

```

        ));
        return s;
    }

    template <typename T>
    T eval_max(node<T> *nd, P<T> p) { // 通过估价函数进行启发式搜索,
        根据当前结果对搜索剪枝
        if (not nd) return 0;
        ll s = 0;
        rep(i, 0, K - 1) s += max(abs(nd->mx[i] - p[i]), abs(nd->
            mn[i] - p[i]));
        return s;
    }

    template <typename T>
    ll maxdist(node<T> *u, P<T> p) {
        ll s = 0;
        if (u->pt != p) {
            s = max(s, abs(u->pt[0] - p[0]) + abs(u->pt[1] - p
                [1]));
        }
        ll best1 = eval_max(u->l, p), best2 = eval_max(u->r, p);
        if (best1 > best2) {
            if (u->l) s = max(s, maxdist(u->l, p));
            if (u->r and best2 > s) s = max(s, maxdist(u->r, p
                ));
            return s;
        } else {
            if (u->r) s = max(s, maxdist(u->r, p));
            if (u->l and best1 > s) s = max(s, maxdist(u->l, p
                ));
            return s;
        }
    }
} // namespace kd

```

2.13 LCT.cpp

```

1 namespace linkCutTree {
2

```

```

3 struct node {
4     node *child[2], *parent, *max;
5     int sum, val, sz, weight, id, rev;
6     node(int val, int weight, int id) : child {nullptr, nullptr}, parent(
            nullptr), max(this), sum(val), val(val), sz(weight), weight(weight
            ), id(id), rev(false) {}
7 };
8
9 bool isRoot(node *p) {return p->parent == nullptr || p->parent->child[0]
    != p && p->parent->child[1] != p;}
10
11 int side(node *p) {return p->parent->child[1] == p;}
12
13 int sum(node *p) {return p == nullptr ? 0 : p->sum;}
14
15 int sz(node *p) {return p == nullptr ? 0 : p->sz;}
16
17 node *max(node *p) {return p == nullptr ? nullptr : p->max;}
18
19 node *max(node *p, node *q) {
20     if (p == nullptr)
21         return q;
22     if (q == nullptr)
23         return p;
24     return p->weight > q->weight ? p : q;
25 }
26
27 void reverse(node *p) {
28     if (p == nullptr)
29         return;
30     swap(p->child[0], p->child[1]);
31     p->rev ^= 1;
32 }
33
34 void push(node *p) {
35     if (p->rev == 0)
36         return;
37     p->rev = 0;
38     reverse(p->child[0]);
39     reverse(p->child[1]);
40 }
41

```

```

42 void pull(node *p) {
43     p->sum = sum(p->child[0]) + sum(p->child[1]) + p->val;
44     p->max = max(max(max(p->child[0]), max(p->child[1])), p);
45     p->sz = p->weight + sz(p->child[0]) + sz(p->child[1]);
46 }
47
48 void connect(node *p, node *q, int side) {
49     q->child[side] = p;
50     if (p != nullptr)
51         p->parent = q;
52 }
53
54 void rotate(node *p) {
55     auto q = p->parent;
56     int dir = side(p) ^ 1;
57     connect(p->child[dir], q, dir ^ 1);
58     if (!isRoot(q))
59         connect(p, q->parent, side(q));
60     else
61         p->parent = q->parent;
62     connect(q, p, dir);
63     pull(q);
64 }
65
66 void splay(node *p) {
67     vector<node *> stk;
68     for (auto i = p; !isRoot(i); i = i->parent)
69         stk.push_back(i->parent);
70     while (!stk.empty()) {
71         push(stk.back());
72         stk.pop_back();
73     }
74     push(p);
75     while (!isRoot(p)) {
76         auto q = p->parent;
77         if (!isRoot(q))
78             rotate(side(p) == side(q) ? q : p);
79         rotate(p);
80     }
81     pull(p);
82 }
83

```

```

84 node *access(node *p) {
85     node *j = nullptr;
86     for (node *i = p; i != nullptr; j = i, i = i->parent) {
87         splay(i);
88         i->val -= sum(j);
89         i->val += sum(i->child[1]);
90         i->child[1] = j;
91         pull(i);
92     }
93     splay(p);
94     return j;
95 }
96
97 void makeRoot(node *p) {
98     access(p);
99     reverse(p);
100 }
101
102 void link(node *p, node *q) {
103     makeRoot(p);
104     access(q);
105     p->parent = q;
106     q->val += sum(p);
107 }
108
109 void cut(node *p, node *q) {
110     makeRoot(p);
111     access(q);
112     p->parent = q->child[0] = nullptr;
113 }
114
115 node *pathMax(node *p, node *q) {
116     makeRoot(p);
117     access(q);
118     return max(q);
119 }
120
121 int pathSum(node *p, node *q) {
122     makeRoot(p);
123     access(q);
124     return sz(q);
125 }

```

```

126
127 int size(node *p) {
128     makeRoot(p);
129     return sum(p);
130 }
131
132 bool connected(node *p, node *q) {
133     access(p);
134     access(q);
135     return p->parent != nullptr;
136 }
137
138 void fix(node *p, ll v) {
139     access(p);
140     // modify ...
141     pull(p);
142 }
143
144 node *lca(node *z, node *x, node *y) {
145     makeRoot(z);
146     access(x);
147     return access(y);
148 }
149
150 } // namespace linkCutTree
151
152 using namespace linkCutTree;

```

2.14 Mo.cpp

```

1 int main() {
2     std::ios::sync_with_stdio(false);
3     cin.tie(0); cout.tie(0);
4
5     for (int i = 1; i <= m; i++) {
6         int x, y;
7         cin >> x >> y;
8         q.pb({x, y, i});
9         rej[i] = (y - x + 1LL) * (y - x) / 2LL;
10    }
11    sort(q.begin(), q.end(), [&](array<int, 3> a, array<int, 3> b)->bool{

```

```

12         if (getb(a[0]) == getb(b[0]))
13             if (getb(a[0]) & 1)
14                 return a[1] < b[1];
15             else
16                 return a[1] > b[1];
17         else return getb(a[0]) < getb(b[0]);
18    });
19
20    int L = 1, R = 0;
21    for (int i = 0; i < m; i++) {
22        while (R < q[i][1]) R++, add(R);
23        while (L > q[i][0]) L--, add(L);
24        while (L < q[i][0]) del(L), L++;
25        while (R > q[i][1]) del(R), R--;
26        ans[q[i][2]] = tmp;
27    }
28 }

```

2.15 moTree.cpp

```

1 void add(int ind, int end) { ... } // add a [ ind ] (end = 0 or 1)
2 void del(int ind, int end) { ... } // remove a [ ind ]
3 int calc() { ... } // compute current answer
4 vi mo(vector<pii> Q) {
5     int L = 0, R = 0, blk = 350; // N/sqrt(Q)
6     vi s(sz(Q)), res = s;
7     #define K(x) pii(x.first/blk, x.second ^ -(x.first/blk & 1))
8     iota(all(s), 0);
9     sort(all(s), [&](int s, int t) { return K(Q[s]) < K(Q[t]); });
10    for (int qi : s) {
11        pii q = Q[qi];
12        while (L > q.first) add(--L, 0);
13        while (R < q.second) add(R++, 1);
14        while (L < q.first) del(L++, 0);
15        while (R > q.second) del(--R, 1);
16        res[qi] = calc();
17    }
18    return res;
19 }
20 vi moTree(vector<array<int, 2>> Q, vector<vi>& ed, int root = 0) {
21     int N = sz(ed), pos[2] = {}, blk = 350; // N/sqrt(Q)

```



```

22 vi s(sz(Q)), res = s, I(N), L(N), R(N), in(N), par(N);
23 add(0, 0), in[0] = 1;
24 auto dfs = [&](int x, int p, int dep, auto & f) -> void {
25     par[x] = p;
26     L[x] = N;
27     if (dep) I[x] = N++;
28     for (int y : ed[x]) if (y != p) f(y, x, !dep, f);
29     if (!dep) I[x] = N++;
30     R[x] = N;
31 };
32 dfs(root, -1, 0, dfs);
33 #define K(x) pii(I[x[0]] / blk, I[x[1]] ^ -(I[x[0]] / blk & 1))
34 iota(all(s), 0);
35 sort(all(s), [&](int s, int t) { return K(Q[s]) < K(Q[t]); });
36 for (int qi : s) rep(end, 0, 2) {
37     int &a = pos[end], b = Q[qi][end], i = 0;
38 #define step(c) { if (in[c]) { del(a, end); in[a] = 0; } \
39 else { add(c, end); in[c] = 1; } a = c; }
40     while (!(L[b] <= L[a] && R[a] <= R[b]))
41         I[i++] = b, b = par[b];
42     while (a != b) step(par[a]);
43     while (i--) step(I[i]);
44     if (end) res[qi] = calc();
45 }
46 return res;
47 }

```

2.16 MSTMo.cpp

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 #define rep(i,a,n) for (int i=a;i<n;i++)
4 #define per(i,a,n) for (int i=n-1;i>=a;i--)
5 #define pb push_back
6 #define mp make_pair
7 #define all(x) (x).begin(),(x).end()
8 #define fi first
9 #define se second
10 #define SZ(x) ((int)(x).size())
11 typedef vector<int> VI;
12 typedef long long ll;

```

```

13 typedef pair<int,int> PII;
14 typedef double db;
15 mt19937 mrand(random_device{}());
16 const ll mod=1000000007;
17 int rnd(int x) { return mrand() % x;}
18 ll powmod(ll a,ll b) {ll res=1;a%=mod; assert(b>=0); for(;;b>=>1){if(b&1)
19     res=res*a%mod;a=a%mod;}return res;}
20 ll gcd(ll a,ll b) { return b?gcd(b,a%b):a;}
21 // head
22
23 const int N=1010000;
24 int a[N];
25 namespace Mo {
26     int Q,l[N],r[N],f[N],l0,r0,ans[N],n;
27     VI ne[N];
28     struct point {
29         int x, y, o;
30         point(int a, int b, int c): x(a), y(b), o(c) {}
31     };
32     inline bool operator<(const point &a, const point &b) {
33         if (a.x != b.x) return a.x > b.x;
34         else return a.y < b.y;
35     }
36     vector<point> p;
37     struct edge {
38         int s, t, d;
39         edge(const point &a, const point &b): s(a.o), t(b.o),
40             d(abs(a.x - b.x) + abs(a.y - b.y)) {}
41     };
42     inline bool operator<(const edge &a, const edge &b) {return a.d < b.d;}
43     vector<edge> e;
44     int g[N],z[N];
45     int cc,cnt[101000];
46     void addedge() {
47         sort(all(p));
48         memset(g,0,sizeof(g));
49         z[0]=N;
50         rep(i,0,SZ(p)) z[i+1]=p[i].x-p[i].y;
51         rep(i,0,SZ(p)) {
52             int k = 0, t = p[i].x + p[i].y;
53             for (int j = t; j; j -= j & -j)

```

```

54         if (z[g[j]] < z[k]) k = g[j];
55         if (k) e.pb(edge(p[i], p[k - 1]));
56         k = z[i + 1];
57         for (int j = t; j < N; j += j & -j)
58             if (k < z[g[j]]) g[j] = i + 1;
59     }
60 }
61 void updata(int i, bool j, bool k=0) {
62     // j=1 insert j=0 delete
63     // k=0 left k=1 right
64     if (j==1) {
65         cnt[a[i]]++;
66         if (cnt[a[i]]%2==0) cc++;
67     } else {
68         if (cnt[a[i]]%2==0) cc--;
69         cnt[a[i]]--;
70     }
71 }
72 void init(int l, int r) {
73     for (int i=l; i<=r; i++) {
74         cnt[a[i]]++;
75         if (cnt[a[i]]%2==0) cc++;
76     }
77 }
78 inline int query() {
79     return cc;
80 }
81 int find(int x) { if (f[x] != x) f[x] = find(f[x]); return f[x]; }
82 void dfs(int i, int p) {
83     int l1 = l[i], r1 = r[i];
84     per(j, l1, l0) updata(j, 1, 0);
85     rep(j, r0+1, r1+1) updata(j, 1, 1);
86     rep(j, l0, l1) updata(j, 0, 0);
87     per(j, r1+1, r0+1) updata(j, 0, 1);
88     ans[i]=query(); l0=l1; r0=r1;
89     rep(j, 0, SZ(ne[i])) if (ne[i][j]!=p) dfs(ne[i][j], i);
90 }
91 void solve() {
92     p.clear(); e.clear();
93     rep(i, 1, Q+1) ans[i]=0;
94     rep(i, 1, Q+1) p.pb(point(l[i], r[i], i));
95     addedge();

```

```

96     rep(i, 0, SZ(p)) p[i].y = n-p[i].y+1;
97     addedge();
98     rep(i, 0, SZ(p)) {
99         int j = n-p[i].x+1;
100         p[i].x = p[i].y; p[i].y = j;
101     }
102     addedge();
103     rep(i, 0, SZ(p)) p[i].x = n-p[i].x+1;
104     addedge();
105     sort(all(e));
106     rep(i, 1, Q+1) ne[i].clear(), f[i]=i;
107     rep(i, 0, SZ(e)) {
108         int j=e[i].s, k=e[i].t;
109         if (find(j)!=find(k)) f[f[j]]=f[k], ne[j].pb(k), ne[k].pb(j);
110     }
111     l0=l[1]; r0=r[1];
112     init(l0, r0);
113     dfs(1, 0);
114 }
115 }
116
117 int main() {
118     scanf("%d", &Mo::n);
119     for (int i=1; i<=Mo::n; i++) scanf("%d", &a+i);
120     scanf("%d", &Mo::Q);
121     rep(i, 1, Mo::Q+1) scanf("%d%d", &Mo::l[i], &Mo::r[i]);
122     Mo::solve();
123     rep(i, 1, Mo::Q+1) printf("%d\n", Mo::ans[i]);
124 }

```

2.17 psgt.cpp

```

1 struct node {
2     node *l, *r;
3     ll val, sz, add;
4 };
5
6 void pull(node *u) {
7     u->sz = 0, u->val = 0;
8     if (u->l) u->sz += u->l->sz, u->val += u->l->val;
9     if (u->r) u->sz += u->r->sz, u->val += u->r->val;

```

```

10 }
11
12 void push(node *u) {
13     if (u->add) {
14         if (u->l) {
15             node *p = new node();
16             *p = *u->l;
17             u->l = p;
18             p->add += u->add;
19             p->val += p->sz * u->add;
20         }
21         if (u->r) {
22             node *p = new node();
23             *p = *u->r;
24             u->r = p;
25             p->add += u->add;
26             p->val += p->sz * u->add;
27         }
28         u->add = 0;
29     }
30 }
31
32 node *build(int l, int r) {
33     node *p = new node();
34     p->add = 0;
35     if (l == r) {
36         p->l = p->r = nullptr;
37         p->val = a[l];
38         p->sz = 1;
39     } else {
40         int mid = (l + r) >> 1;
41         p->l = build(l, mid);
42         p->r = build(mid + 1, r);
43         pull(p);
44     }
45     return p;
46 }
47
48 ll query(node *v, int l, int r, int ql, int qr) {
49     if (ql == l && qr == r) {
50         return v->val;
51     } else {

```

```

52         push(v);
53         int mid = (l + r) >> 1;
54         if (qr <= mid)
55             return query(v->l, l, mid, ql, qr);
56         else if (ql > mid)
57             return query(v->r, mid + 1, r, ql, qr);
58         else
59             return query(v->l, l, mid, ql, mid) + query(v->r,
60                 mid + 1, r, mid + 1, qr);
61     }
62 }
63
64 node *modify(node *v, int l, int r, int ql, int qr, ll x) {
65     if (ql == l && qr == r) {
66         node *p = new node();
67         *p = *v;
68         p->add += x;
69         p->val += p->sz * x;
70         return p;
71     } else {
72         push(v);
73         int mid = (l + r) >> 1;
74         node *p = new node();
75         *p = *v;
76         if (qr <= mid)
77             p->l = modify(v->l, l, mid, ql, qr, x);
78         else if (ql > mid)
79             p->r = modify(v->r, mid + 1, r, ql, qr, x);
80         else
81             p->l = modify(v->l, l, mid, ql, mid, x),
82                 p->r = modify(v->r, mid + 1, r,
83                     mid + 1, qr, x);
84         pull(p);
85         return p;
86     }
87 }

```

2.18 rollbackMo.cpp

```

1 int n, q, k, block;
2 int cnt[maxn], ans[maxn], a[maxn], vis[maxn];

```

```

3  vector<array<int, 4>> que;
4
5  int getb(int x) {
6      return (x - 1) / block + 1;
7  }
8
9  int main() {
10     std::ios::sync_with_stdio(false);
11     cin.tie(0); cout.tie(0);
12
13     cin >> n;
14     block = sqrt(n);
15
16     rep(i, 1, n) cin >> a[i];
17     cin >> q;
18     rep(i, 1, q) {
19         int l, r;
20         cin >> l >> r >> k;
21         que.pb({l, r, i, k});
22     }
23     sort(ALL(que), [&](array<int, 4> a, array<int, 4> b)->bool{
24         if (getb(a[0]) != getb(b[0]))
25             return getb(a[0]) < getb(b[0]);
26         else
27             return a[1] < b[1];
28     });
29
30     int len = que.size();
31     int l, r;
32     auto add = [&](int x, int t) {
33         cnt[vis[a[x]]]--;
34         vis[a[x]]++;
35         cnt[vis[a[x]]]++;
36     };
37     auto del = [&](int x) {
38         cnt[vis[a[x]]]--;
39         vis[a[x]]--;
40         cnt[vis[a[x]]]++;
41     };
42
43     for (int x = 0; x < len; x++) {
44         int y = x;

```

```

45         while (y < len && getb(que[y][0]) == getb(que[x][0])) y++;
46         //暴力块内
47         while (x < y && que[x][1] <= getb(que[x][0])*block) {
48             for (int j = que[x][0]; j <= que[x][1]; j++)
49                 add(j, que[x][3]);
50             ans[que[x][2]] = cnt[que[x][3]];
51             for (int j = que[x][0]; j <= que[x][1]; j++)
52                 del(j);
53             x++;
54         }
55         //块外
56         r = getb(que[x][0]) * block;
57         while (x < y) {
58             l = getb(que[x][0]) * block + 1;
59             while (r < que[x][1]) r++, add(r, que[x][3]);
60             while (l > que[x][0]) l--, add(l, que[x][3]);
61             ans[que[x][2]] = cnt[que[x][3]];
62             for (int j = que[x][0]; j <= getb(que[x][0])*block; j++)
63                 del(j);
64             x++;
65         }
66         for (int j = getb(que[x - 1][0]) * block + 1; j <= que[x - 1][1];
67             j++)
68             del(j);
69     }
70     rep(i, 1, q) cout << ans[i] << '\n';

```

2.19 segtree.cpp

```

1  struct info {
2      ll sum;
3      int sz;
4      friend info operator+(const info &a, const info &b) {
5          return {(a.sum + b.sum) % mod, a.sz + b.sz};
6      }
7  };
8
9  struct tag {
10     ll add, mul;
11     friend tag operator+(const tag &a, const tag &b) {

```

```

12         tag res = {(a.add * b.mul + b.add) % mod, a.mul * b.mul %
13                     mod};
14     }
15 };
16 info operator+(const info &a, const tag &b) {
17     return {(a.sum * b.mul + a.sz * b.add) % mod, a.sz};
18 }
19
20 struct node {
21     info val;
22     tag t;
23 } seg[maxn << 2];
24
25 void update(int id) {
26     seg[id].val = seg[id * 2].val + seg[id * 2 + 1].val;
27 }
28 void settag(int id, tag t) {
29     seg[id].val = seg[id].val + t;
30     seg[id].t = seg[id].t + t;
31 }
32 void pushdown(int id) {
33     if (seg[id].t.mul == 1 and seg[id].t.add == 0) return;
34     settag(id * 2, seg[id].t);
35     settag(id * 2 + 1, seg[id].t);
36     seg[id].t.mul = 1;
37     seg[id].t.add = 0;
38 }
39 void build(int l, int r, int id) {
40     seg[id].t = {0, 1};
41     if (l == r) {
42         seg[id].val = {a[l], 1};
43     } else {
44         int mid = (l + r) >> 1;
45         build(l, mid, id * 2);
46         build(mid + 1, r, id * 2 + 1);
47         update(id);
48     }
49 }
50 void change(int l, int r, int id, int ql, int qr, tag t) {
51     if (l == ql && r == qr) {
52         settag(id, t);

```

```

53     } else {
54         int mid = (l + r) >> 1;
55         pushdown(id);
56         if (qr <= mid) {
57             change(l, mid, id * 2, ql, qr, t);
58         } else if (ql > mid) {
59             change(mid + 1, r, id * 2 + 1, ql, qr, t);
60         } else {
61             change(l, mid, id * 2, ql, mid, t);
62             change(mid + 1, r, id * 2 + 1, mid + 1, qr, t);
63         }
64         update(id);
65     }
66 }
67 info query(int l, int r, int id, int ql, int qr) {
68     if (l == ql && r == qr) {
69         return seg[id].val;
70     } else {
71         int mid = (l + r) >> 1;
72         pushdown(id);
73         if (qr <= mid)
74             return query(l, mid, id * 2, ql, qr);
75         else if (ql > mid)
76             return query(mid + 1, r, id * 2 + 1, ql, qr);
77         else
78             return query(l, mid, id * 2, ql, mid) +
79                    query(mid + 1, r, id * 2 + 1, mid + 1,
80                        qr);
81     }
82 ll search(int l, int r, int id, int ql, int qr, int d) {
83     if (ql == l && qr == r) {
84         int mid = (l + r) / 2;
85         // if (l != r) pushdown(id); ...
86         if (seg[id].val < d)
87             return -1;
88         else {
89             if (l == r)
90                 return l;
91             else if (seg[id * 2].val >= d)
92                 return search(l, mid, id * 2, ql, mid, d);
93             else

```

```

94         return search(mid + 1, r, id * 2 + 1, mid
95             + 1, qr, d);
96     }
97     } else {
98         int mid = (l + r) >> 1;
99         // pushdown(id); ...
100         if (qr <= mid)
101             return search(l, mid, id * 2, ql, qr, d);
102         else if (ql > mid)
103             return search(mid + 1, r, id * 2 + 1, ql, qr, d);
104         else {
105             int tmp = search(l, mid, id * 2, ql, mid, d);
106             if (tmp != -1)
107                 return tmp;
108             else
109                 return search(mid + 1, r, id * 2 + 1, mid
110                     + 1, qr, d);
111         }
112     }
113 }

```

2.20 segtreefast.cpp

```

1  /**
2   * Author: Lucian Bicsi
3   * Description: Very fast and quick segment tree.
4   * Only useful for easy invariants. 0-indexed.
5   * Range queries are half-open.
6   */
7  #pragma once
8
9  struct SegmTree {
10     vector<int> T; int n;
11     SegmTree(int n) : T(2 * n, (int)2e9), n(n) {}
12
13     void Update(int pos, int val) {
14         for (T[pos += n] = val; pos > 1; pos /= 2)
15             T[pos / 2] = min(T[pos], T[pos ^ 1]);
16     }
17
18     int Query(int b, int e) {

```

```

19     int res = (int)2e9;
20     for (b += n, e += n; b < e; b /= 2, e /= 2) {
21         if (b % 2) res = min(res, T[b++]);
22         if (e % 2) res = min(res, T[--e]);
23     }
24     return res;
25 }
26 };

```

2.21 SparseTable.cpp

```

1  template <typename T, class F = function<T(const T&, const T&>>>
2  class SparseTable {
3  public:
4       int n;
5       vector<vector<T>> mat;
6       F func;
7
8       SparseTable(const vector<T>& a, const F& f) : func(f) {
9           n = static_cast<int>(a.size());
10          int max_log = 32 - __builtin_clz(n);
11          mat.resize(max_log);
12          mat[0] = a;
13          for (int j = 1; j < max_log; j++) {
14              mat[j].resize(n - (1 << j) + 1);
15              for (int i = 0; i <= n - (1 << j); i++) {
16                  mat[j][i] = func(mat[j - 1][i], mat[j -
17                      1][i + (1 << (j - 1))]);
18              }
19          }
20
21          T get(int from, int to) const {
22              assert(0 <= from && from <= to && to <= n - 1);
23              int lg = 32 - __builtin_clz(to - from + 1) - 1;
24              return func(mat[lg][from], mat[lg][to - (1 << lg) + 1]);
25          }
26 };

```

2.22 SparseTable2D.cpp

```

1 // lg[1] = 0;
2 // rep(i, 2, N - 1) {
3 //     lg[i] = lg[i / 2] + 1;
4 // }
5 // int k = log2(r - l + 1); very slow!!!
6 // int k = __lg(r - l + 1);
7 // int k = lg[r - l + 1];
8 // int k = 32 - __builtin_clz(r - l + 1) - 1;
9 vector<vector<int>> sparse[12];
10
11 int query(int x, int y, int d) {
12     int k = __lg(d);
13     int s = d - bit(k);
14     return min({sparse[k][x][y], sparse[k][x + s][y], sparse[k][x][y +
15         s], sparse[k][x + s][y + s]});
16 }
17 void build() {
18     rep(i, 1, n) rep(j, 1, m) sparse[0][i][j] = mat[i][j];
19     rep(k, 1, 11) rep(i, 1, n) rep(j, 1, m) {
20         int d = bit(k - 1);
21         if (i + d > n || j + d > m) continue;
22         sparse[k][i][j] = min({sparse[k - 1][i][j], sparse[k - 1][
23             i + d][j], sparse[k - 1][i][j + d], sparse[k - 1][i +
24             d][j + d]});
25     }
26 }

```

2.23 treap.cpp

```

1 /**
2  *   author:   tourist
3  *   created:  07.10.2022 20:32:03
4  */
5 #include <bits/stdc++.h>
6
7 using namespace std;
8
9 #ifdef LOCAL
10 #include "algo/debug.h"
11 #else

```

```

12 #define debug(...) 42
13 #endif
14
15 mt19937_64 rng(chrono::steady_clock::now().time_since_epoch().count());
16
17 class node {
18 public:
19     int id;
20     node* l;
21     node* r;
22     node* p;
23     bool rev;
24     int sz;
25     // declare extra variables:
26     long long P;
27     long long add;
28     long long x;
29
30     node(int _id, long long _x) {
31         id = _id;
32         l = r = p = nullptr;
33         rev = false;
34         sz = 1;
35         // init extra variables:
36         P = rng();
37         add = 0;
38         x = _x;
39     }
40
41     // push everything else:
42     void push_stuff() {
43         if (add != 0) {
44             if (l != nullptr) {
45                 l->unsafe_apply(add);
46             }
47             if (r != nullptr) {
48                 r->unsafe_apply(add);
49             }
50             add = 0;
51         }
52     }
53 }

```

```

54 void unsafe_reverse() {
55     push_stuff();
56     rev ^= 1;
57     swap(l, r);
58     pull();
59 }
60
61 // apply changes:
62 void unsafe_apply(long long delta) {
63     add += delta;
64     x += delta;
65 }
66
67 void push() {
68     if (rev) {
69         if (l != nullptr) {
70             l->unsafe_reverse();
71         }
72         if (r != nullptr) {
73             r->unsafe_reverse();
74         }
75         rev = 0;
76     }
77     push_stuff();
78 }
79
80 void pull() {
81     sz = 1;
82     if (l != nullptr) {
83         l->p = this;
84         sz += l->sz;
85     }
86     if (r != nullptr) {
87         r->p = this;
88         sz += r->sz;
89     }
90 }
91 };
92
93 void debug_node(node* v, string pref = "") {
94 #ifdef LOCAL
95     if (v != nullptr) {

```

```

96         debug_node(v->r, pref + "└");
97         cerr << pref << "-" << "└" << v->id << '\n';
98         debug_node(v->l, pref + "└");
99     } else {
100         cerr << pref << "-" << "└" << "nullptr" << '\n';
101     }
102 #endif
103 }
104
105 namespace treap {
106
107 pair<node*, int> find(node* v, const function<int(node*)> &go_to) {
108     // go_to returns: 0 -- found; -1 -- go left; 1 -- go right
109     // find returns the last vertex on the descent and its go_to
110     if (v == nullptr) {
111         return {nullptr, 0};
112     }
113     int dir;
114     while (true) {
115         v->push();
116         dir = go_to(v);
117         if (dir == 0) {
118             break;
119         }
120         node* u = (dir == -1 ? v->l : v->r);
121         if (u == nullptr) {
122             break;
123         }
124         v = u;
125     }
126     return {v, dir};
127 }
128
129 node* get_leftmost(node* v) {
130     return find(v, [&](node*) { return -1; }).first;
131 }
132
133 node* get_rightmost(node* v) {
134     return find(v, [&](node*) { return 1; }).first;
135 }
136
137 node* get_kth(node* v, int k) { // 0-indexed

```



```

138 pair<node*, int> p = find(v, [&](node * u) {
139     if (u->l != nullptr) {
140         if (u->l->sz > k) {
141             return -1;
142         }
143         k -= u->l->sz;
144     }
145     if (k == 0) {
146         return 0;
147     }
148     k--;
149     return 1;
150 });
151 return (p.second == 0 ? p.first : nullptr);
152 }
153
154 int get_pos(node* v) { // 0-indexed
155     int k = (v->l != nullptr ? v->l->sz : 0);
156     while (v->p != nullptr) {
157         if (v == v->p->r) {
158             k++;
159             if (v->p->l != nullptr) {
160                 k += v->p->l->sz;
161             }
162         }
163         v = v->p;
164     }
165     return k;
166 }
167
168 node* get_root(node* v) {
169     while (v->p != nullptr) {
170         v = v->p;
171     }
172     return v;
173 }
174
175 pair<node*, node*> split(node* v, const function<bool(node*)> &is_right) {
176     if (v == nullptr) {
177         return {nullptr, nullptr};
178     }
179     v->push();

```

```

180     if (is_right(v)) {
181         pair<node*, node*> p = split(v->l, is_right);
182         if (p.first != nullptr) {
183             p.first->p = nullptr;
184         }
185         v->l = p.second;
186         v->pull();
187         return {p.first, v};
188     } else {
189         pair<node*, node*> p = split(v->r, is_right);
190         v->r = p.first;
191         if (p.second != nullptr) {
192             p.second->p = nullptr;
193         }
194         v->pull();
195         return {v, p.second};
196     }
197 }
198
199 pair<node*, node*> split_cnt(node* v, int k) {
200     if (v == nullptr) {
201         return {nullptr, nullptr};
202     }
203     v->push();
204     int left_and_me = (v->l != nullptr ? v->l->sz : 0) + 1;
205     if (k < left_and_me) {
206         pair<node*, node*> p = split_cnt(v->l, k);
207         if (p.first != nullptr) {
208             p.first->p = nullptr;
209         }
210         v->l = p.second;
211         v->pull();
212         return {p.first, v};
213     } else {
214         pair<node*, node*> p = split_cnt(v->r, k - left_and_me);
215         v->r = p.first;
216         if (p.second != nullptr) {
217             p.second->p = nullptr;
218         }
219         v->pull();
220         return {v, p.second};
221     }

```

```

222 }
223
224 node* merge(node* v, node* u) {
225     if (v == nullptr) {
226         return u;
227     }
228     if (u == nullptr) {
229         return v;
230     }
231     if (v->P > u->P) {
232         // if (rng() % (v->sz + u->sz) < (unsigned int) v->sz) {
233         v->push();
234         v->r = merge(v->r, u);
235         v->pull();
236         return v;
237     } else {
238         u->push();
239         u->l = merge(v, u->l);
240         u->pull();
241         return u;
242     }
243 }
244
245 int count_left(node* v, const function<bool(node*)> &is_right) {
246     if (v == nullptr) {
247         return 0;
248     }
249     v->push();
250     if (is_right(v)) {
251         return count_left(v->l, is_right);
252     }
253     return (v->l != nullptr ? v->l->sz : 0) + 1 + count_left(v->r, is_right)
254         ;
255 }
256
257 int count_less(node* v, long long val) {
258     int res = 0;
259     while (v != nullptr) {
260         v->push();
261         if (v->x >= val) {
262             v = v->l;
263         } else {

```

```

263         res += (v->l != nullptr ? v->l->sz : 0) + 1;
264         v = v->r;
265     }
266 }
267 return res;
268 }
269
270 node* add(node* r, node* v, const function<bool(node*)> &go_left) {
271     pair<node*, node*> p = split(r, go_left);
272     return merge(p.first, merge(v, p.second));
273 }
274
275 node* remove(node* v) { // returns the new root
276     v->push();
277     node* x = v->l;
278     node* y = v->r;
279     node* p = v->p;
280     v->l = v->r = v->p = nullptr;
281     v->push();
282     v->pull(); // now v might be reusable...
283     node* z = merge(x, y);
284     if (p == nullptr) {
285         if (z != nullptr) {
286             z->p = nullptr;
287         }
288         return z;
289     }
290     if (p->l == v) {
291         p->l = z;
292     }
293     if (p->r == v) {
294         p->r = z;
295     }
296     while (true) {
297         p->push();
298         p->pull();
299         if (p->p == nullptr) {
300             break;
301         }
302         p = p->p;
303     }
304     return p;

```

```

305 }
306
307 node* next(node* v) {
308     if (v->r == nullptr) {
309         while (v->p != nullptr && v->p->r == v) {
310             v = v->p;
311         }
312         return v->p;
313     }
314     v->push();
315     v = v->r;
316     while (v->l != nullptr) {
317         v->push();
318         v = v->l;
319     }
320     return v;
321 }
322
323 node* prev(node* v) {
324     if (v->l == nullptr) {
325         while (v->p != nullptr && v->p->l == v) {
326             v = v->p;
327         }
328         return v->p;
329     }
330     v->push();
331     v = v->l;
332     while (v->r != nullptr) {
333         v->push();
334         v = v->r;
335     }
336     return v;
337 }
338
339 int get_size(node* v) {
340     return (v != nullptr ? v->sz : 0);
341 }
342
343 template<typename... T>
344 void Apply(node* v, T... args) {
345     v->unsafe_apply(args...);
346 }

```

```

347
348 void reverse(node* v) {
349     v->unsafe_reverse();
350 }
351
352 // extra of mine
353 long long lower(node* u, long long x) {
354     if (u == nullptr)
355         return numeric_limits<long long>::min();
356     else if (x <= u->x)
357         return lower(u->l, x);
358     else
359         return max(u->x, lower(u->r, x));
360 }
361
362 long long upper(node* u, long long x) {
363     if (u == nullptr)
364         return numeric_limits<long long>::max();
365     else if (u->x <= x)
366         return upper(u->r, x);
367     else
368         return min(u->x, upper(u->l, x));
369 }
370
371 } // namespace treap
372
373 using namespace treap;
374
375 int n;
376
377 int main() {
378     ios::sync_with_stdio(false);
379     cin.tie(0);
380     node* root = nullptr;
381     cin >> n;
382     for (int i = 1; i <= n; i++) {
383         int op;
384         long long x;
385         cin >> op >> x;
386         switch (op) {
387             case 1: {
388                 root = add(root, new node(x, x), [&](node * u) {

```

```

389     return x < u->x;
390 });
391 break;
392 }
393 case 2: {
394     auto [pt, w] = find(root, [&](node * u) {
395         if (x < u->x) return -1;
396         else if (x == u->x) return 0;
397         else return 1;
398     });
399     assert(w == 0);
400     root = remove(pt);
401     break;
402 }
403 case 3: {
404     cout << count_less(root, x) + 1 << '\n';
405     break;
406 }
407 case 4: {
408     cout << get_kth(root, x - 1)->x << '\n';
409     break;
410 }
411 case 5: {
412     cout << lower(root, x) << '\n';
413     break;
414 }
415 case 6: {
416     cout << upper(root, x) << '\n';
417     break;
418 }
419 }
420 }
421 }

```

2.24 树哈希.cpp

```

1  basic_string<int> e[maxn];
2  ull hashv[maxn];
3  ull seed1, seed2, seed3, seed4;
4
5  ull f(ull x) { return x * x * x * seed1 + x * seed2; }

```

```

6  ull h(ull x) { return f(x) ^ ((x & seed3) >> 31) ^ ((x & seed4) << 31); }
7
8  void dfs1(int u, int fa) {
9      hashv[u] = 1;
10     for (auto v : e[u]) if (v != fa) {
11         dfs1(v, u);
12         hashv[u] += h(hashv[v]);
13     }
14 }
15
16 void dfs2(int u, int fa, ull fv) {
17     // for each root
18     hashv[u] += fv;
19     for (auto v : e[u]) if (v != fa) {
20         dfs2(v, u, h(hashv[u] - h(hashv[v])));
21     }
22 }
23
24 void solve() {
25     seed1 = rng(), seed2 = rng();
26     seed3 = rng(), seed4 = rng();
27     cin >> n;
28     rep(i, 2, n) {
29         int u, v;
30         cin >> u >> v;
31         e[u].pb(v);
32         e[v].pb(u);
33     }
34     dfs1(1, 0);
35     sort(hashv + 1, hashv + n + 1);
36     n = unique(hashv + 1, hashv + n + 1) - hashv - 1;
37     cout << n << '\n';
38 }

```

2.25 树链剖分 segtree.cpp

```

1  int n, m, a[N];
2  vector<int> e[N];
3  int l[N], r[N], idx[N];
4  int sz[N], hs[N], tot, top[N], dep[N], fa[N];
5

```

```

6  struct info {
7      int maxv, sum;
8  };
9
10 info operator + (const info &l, const info &r) {
11     return (info){max(l.maxv, r.maxv), l.sum + r.sum};
12 }
13
14 struct node {
15     info val;
16 } seg[N * 4];
17
18 // [l, r]
19
20 void update(int id) {
21     seg[id].val = seg[id * 2].val + seg[id * 2 + 1].val;
22 }
23
24 void build(int id, int l, int r) {
25     if (l == r) {
26         // l号点, DFS序中第l个点
27         seg[id].val = {a[idx[l]], a[idx[l]]};
28     } else {
29         int mid = (l + r) / 2;
30         build(id * 2, l, mid);
31         build(id * 2 + 1, mid + 1, r);
32         update(id);
33     }
34 }
35
36 void change(int id, int l, int r, int pos, int val) {
37     if (l == r) {
38         seg[id].val = {val, val};
39     } else {
40         int mid = (l + r) / 2;
41         if (pos <= mid) change(id * 2, l, mid, pos, val);
42         else change(id * 2 + 1, mid + 1, r, pos, val);
43         update(id);
44     }
45 }
46
47 info query(int id, int l, int r, int ql, int qr) {

```

```

48     if (l == ql && r == qr) return seg[id].val;
49     int mid = (l + r) / 2;
50     if (qr <= mid) return query(id * 2, l, mid, ql, qr);
51     else if (ql > mid) return query(id * 2 + 1, mid + 1, r, ql, qr);
52     else {
53         return query(id * 2, l, mid, ql, mid) +
54             query(id * 2 + 1, mid + 1, r, mid + 1, qr);
55     }
56 }
57
58 // 第一遍DFS, 子树大小, 重儿子, 父亲, 深度
59 void dfs1(int u, int f) {
60     sz[u] = 1;
61     hs[u] = -1;
62     fa[u] = f;
63     dep[u] = dep[f] + 1;
64     for (auto v : e[u]) {
65         if (v == f) continue;
66         dfs1(v, u);
67         sz[u] += sz[v];
68         if (hs[u] == -1 || sz[v] > sz[hs[u]])
69             hs[u] = v;
70     }
71 }
72
73 // 第二遍DFS, 每个点DFS序, 重链上的链头的元素。
74 void dfs2(int u, int t) {
75     top[u] = t;
76     l[u] = ++tot;
77     idx[tot] = u;
78     if (hs[u] != -1) {
79         dfs2(hs[u], t);
80     }
81     for (auto v : e[u]) {
82         if (v != fa[u] && v != hs[u]) {
83             dfs2(v, v);
84         }
85     }
86     r[u] = tot;
87 }
88
89 int LCA(int u, int v) {

```

```

90     while (top[u] != top[v]) {
91         if (dep[top[u]] < dep[top[v]]) v = fa[top[v]];
92         else u = fa[top[u]];
93     }
94     if (dep[u] < dep[v]) return u;
95     else return v;
96 }
97
98 info query(int u,int v) {
99     info ans{(int)-1e9, 0};
100     while (top[u] != top[v]) {
101         if (dep[top[u]] < dep[top[v]]) {
102             ans = ans + query(1, 1, n, l[top[v]], l[v]);
103             v = fa[top[v]];
104         } else {
105             ans = ans + query(1, 1, n, l[top[u]], l[u]);
106             u = fa[top[u]];
107         }
108     }
109     if (dep[u] <= dep[v]) ans = ans + query(1, 1, n, l[u], l[v]);
110     else ans = ans + query(1, 1, n, l[v], l[u]);
111     return ans;
112 }

```

2.26 笛卡尔树.cpp

```

1 int a[maxn], l[maxn], r[maxn], root;
2 int ans[maxn], tot;
3
4 void build() {
5     stack<int> stk;
6     for (int i = 1; i <= n; i++) {
7         int last = 0;
8         while (!stk.empty() && a[stk.top()] > a[i]) {
9             last = stk.top();
10            stk.pop();
11        }
12        if (stk.empty())
13            root = i;
14        else
15            r[stk.top()] = i;

```

```

16        l[i] = last;
17        stk.push(i);
18    }
19 }
20
21 void dfs(int c, int L, int R) {
22     ans[c] = ++tot;
23     if (l[c]) dfs(l[c], L, c - 1);
24     if (r[c]) dfs(r[c], c + 1, R);
25 }

```

2.27 线段树合并.cpp

```

1 struct node {
2     int sz, sum;
3     node *l, *r;
4     node() : sz(0), sum(0), l(nullptr), r(nullptr) {}
5 } pool[N * 20], *cur = pool;
6
7 node *newnode() {
8     return cur++;
9 }
10
11 void upd(node *rt) {
12     if (not rt) return;
13     rt->sum = rt->sz > 0;
14     if (rt->l) rt->sum += rt->l->sum;
15     if (rt->r) rt->sum += rt->r->sum;
16 }
17
18 node *modify(node *rt, int l, int r, int pos, int d) {
19     if (not rt) rt = newnode();
20     if (l == r) {
21         rt->sz += d;
22         upd(rt);
23         return rt;
24     } else {
25         int md = (l + r) >> 1;
26         if (pos <= md)
27             rt->l = modify(rt->l, l, md, pos, d);
28         else

```

```

29         rt->r = modify(rt->r, md + 1, r, pos, d);
30         upd(rt);
31         return rt;
32     }
33 }
34
35 node *merge(node *u, node *v, int l, int r) {
36     if (not u) return v;
37     if (not v) return u;
38     if (l == r) {
39         u->sz += v->sz;
40         upd(u);
41         return u;
42     } else {
43         int md = (l + r) >> 1;
44         u->l = merge(u->l, v->l, l, md);
45         u->r = merge(u->r, v->r, md + 1, r);
46         upd(u);
47         return u;
48     }
49 }
50
51 ll query(node *rt, int l, int r) {
52     if (not rt) return 0;
53     return rt->sum;
54 }
55
56 pair<node *, node *> split(node *rt, int l, int r, int ql, int qr) {
57     if (not rt) return {nullptr, nullptr};
58     if (ql == l && qr == r) {
59         return {nullptr, rt};
60     } else {
61         int md = (l + r) >> 1;
62         if (qr <= md) {
63             auto [p1, p2] = split(rt->l, l, md, ql, qr);
64             rt->l = p1;
65             upd(rt);
66             if (not p2) return {rt, nullptr};
67             node *u = newnode();
68             u->l = p2;
69             upd(u);
70             return {rt, u};

```

```

71         } else if (ql > md) {
72             auto [p1, p2] = split(rt->r, md + 1, r, ql, qr);
73             rt->r = p1;
74             upd(rt);
75             if (not p2) return {rt, nullptr};
76             node *u = newnode();
77             u->r = p2;
78             upd(u);
79             return {rt, u};
80         } else {
81             auto [p1, p2] = split(rt->l, l, md, ql, md);
82             auto [p3, p4] = split(rt->r, md + 1, r, md + 1, qr);
83             rt->l = p1, rt->r = p3;
84             upd(rt);
85             if (not p2 and not p4) return {rt, nullptr};
86             node *u = newnode();
87             u->l = p2, u->r = p4;
88             upd(u);
89             return {rt, u};
90         }
91     }
92 }

```

3 DP

3.1 Convex hull optimization.cpp

```

1  array<ll, 3> a[maxn];
2  int q[maxn];
3  ll ans[maxn];
4
5  ll X(int p) {
6      return 2ll * a[p][0];
7  }
8  ll Y(int p) {
9      return a[p][0] * a[p][0] + a[p][1];
10 }
11 ldb slope(int x, int y) {
12     return (ldb)(Y(y) - Y(x)) / (X(y) - X(x));
13 }

```

```

14 void solve() {
15     cin >> n;
16     int head = 1, rear = 0;
17     rep(i, 1, n) {
18         cin >> a[i][0] >> a[i][1];
19         a[i][2] = i;
20     }
21     sort(a + 1, a + n + 1);
22
23     rep(i, 1, n) {
24         while (head < rear && slope(q[rear], i) <= slope(q[rear], q[rear -
25             1])) rear--;
26         q[++rear] = i;
27     }
28     rep(i, 1, n) {
29         ll k = -a[i][0];
30         while (head < rear && slope(q[head], q[head + 1]) <= k) head++;
31         ans[a[i][2]] = (a[i][0] + a[q[head]][0]) * (a[i][0] + a[q[head
32             1]][0]) + a[i][1] + a[q[head]][1];
33     }
34     rep(i, 1, n) cout << ans[i] << '\n';
35 }

```

3.2 DivideAndConquerDP.cpp

```

1 ll w[N][N], sum[N][N], opt[N], dp[805][N];
2
3 ll calc(int i, int j) { return sum[j][j] - sum[j][i] - sum[i][j] + sum[i][i]; }
4
5 void rec(int d, int l, int r, int optl, int optr) {
6     if (l > r) return;
7     int md = (l + r) >> 1;
8     rep(i, optl, optr) if (dp[d - 1][i] + calc(i, md) < dp[d][md]) {
9         dp[d][md] = dp[d - 1][i] + calc(i, md);
10        opt[md] = i;
11    }
12    rec(d, l, md - 1, optl, opt[md]);
13    rec(d, md + 1, r, opt[md], optr);
14 }

```

3.3 有依赖决策单调.cpp

```

1 pair<int, int> stk[N];
2 auto calc = [&](int i, int j) { ... } // dp[j] -> dp[i]
3 int h = 0, t = 0;
4 stk[t++] = {1, 0}; // {left, opt}
5
6 for (int i = 1; i <= n; i++) {
7     if (h < t && stk[h].first < i) stk[h].first++;
8     if (h + 1 < t && stk[h].first >= stk[h + 1].first) ++h;
9     dp[i] = calc(i, stk[h].second);
10    while (h < t && calc(stk[t - 1].first, stk[t - 1].second) >= calc(stk[
11        t - 1].first, i))
12        --t;
13    if (h < t) {
14        int l = stk[t - 1].first, r = n + 1;
15        while (l + 1 < r) {
16            int md = (l + r) >> 1;
17            if (calc(md, stk[t - 1].second) < calc(md, i)) l = md; else r
18                = md;
19        }
20        if (r <= n) stk[t++] = {r, i};
21    } else stk[t++] = {i, i};
22 }

```

4 Geometry

4.1 all.cpp

```

1 typedef double db;
2 const db EPS = 1e-9;
3
4 inline int sign(db a) { return a < -EPS ? -1 : a > EPS; }
5
6 inline int cmp(db a, db b) { return sign(a - b); }
7
8 struct P {
9     db x, y;
10    P() {}
11    P(db _x, db _y) : x(_x), y(_y) {}
12    P operator+(P p) { return {x + p.x, y + p.y}; }

```



```

13 P operator-(P p) { return {x - p.x, y - p.y}; }
14 P operator*(db d) { return {x * d, y * d}; }
15 P operator/(db d) { return {x / d, y / d}; }
16
17 bool operator<(P p) const {
18     int c = cmp(x, p.x);
19     if (c) return c == -1;
20     return cmp(y, p.y) == -1;
21 }
22
23 bool operator==(P o) const{
24     return cmp(x,o.x) == 0 && cmp(y,o.y) == 0;
25 }
26
27 db dot(P p) { return x * p.x + y * p.y; }
28 db det(P p) { return x * p.y - y * p.x; }
29
30 db distTo(P p) { return (*this-p).abs(); }
31 db alpha() { return atan2(y, x); }
32 void read() { cin>>x>>y; }
33 void write() {cout<<"("<<x<<","<<y<<")"<<endl;}
34 db abs() { return sqrt(abs2());}
35 db abs2() { return x * x + y * y; }
36 P rot90() { return P(-y,x);}
37 P unit() { return *this/abs(); }
38 int quad() const { return sign(y) == 1 || (sign(y) == 0 && sign(x) >=
    0); }
39 P rot(db an){ return {x*cos(an)-y*sin(an),x*sin(an) + y*cos(an)}; }
40 };
41
42 struct L{ //ps[0] -> ps[1]
43     P ps[2];
44     P& operator[](int i) { return ps[i]; }
45     P dir() { return ps[1] - ps[0]; }
46     bool include(P p) { return sign((ps[1] - ps[0]).det(p - ps[0])) > 0; }
47     L push(){ // push eps outward
48         const double eps = 1e-6;
49         P delta = (ps[1] - ps[0]).rot90().unit() * eps;
50         return {{ps[0] - delta, ps[1] - delta}};
51     }
52 };
53

```

```

54 #define cross(p1,p2,p3) ((p2.x-p1.x)*(p3.y-p1.y)-(p3.x-p1.x)*(p2.y-p1.y))
55 #define cross0p(p1,p2,p3) sign(cross(p1,p2,p3))
56
57 bool chkLL(P p1, P p2, P q1, P q2) {
58     db a1 = cross(q1, q2, p1), a2 = -cross(q1, q2, p2);
59     return sign(a1+a2) != 0;
60 }
61
62 P isLL(P p1, P p2, P q1, P q2) {
63     db a1 = cross(q1, q2, p1), a2 = -cross(q1, q2, p2);
64     return (p1 * a2 + p2 * a1) / (a1 + a2);
65 }
66
67 P isLL(L l1,L l2){ return isLL(l1[0],l1[1],l2[0],l2[1]); }
68
69 bool intersect(db l1,db r1,db l2,db r2){
70     if(l1>r1) swap(l1,r1); if(l2>r2) swap(l2,r2);
71     return !( cmp(r1,l2) == -1 || cmp(r2,l1) == -1 );
72 }
73
74 bool isSS(P p1, P p2, P q1, P q2){
75     return intersect(p1.x,p2.x,q1.x,q2.x) && intersect(p1.y,p2.y,q1.y,q2.y
    ) &&
76     cross0p(p1,p2,q1) * cross0p(p1,p2,q2) <= 0 && cross0p(q1,q2,p1)
    * cross0p(q1,q2,p2) <= 0;
77 }
78
79
80 bool isSS_strict(P p1, P p2, P q1, P q2){
81     return cross0p(p1,p2,q1) * cross0p(p1,p2,q2) < 0 && cross0p(q1,q2,p1)
    * cross0p(q1,q2,p2) < 0;
82 }
83
84
85 bool isMiddle(db a, db m, db b) {
86     return sign(a - m) == 0 || sign(b - m) == 0 || (a < m != b < m);
87 }
88
89 bool isMiddle(P a, P m, P b) {
90     return isMiddle(a.x, m.x, b.x) && isMiddle(a.y, m.y, b.y);
91 }
92
93 bool onSeg(P p1, P p2, P q){
94     return cross0p(p1,p2,q) == 0 && isMiddle(p1, q, p2);

```

```

95 }
96
97 bool onSeg_strict(P p1, P p2, P q){
98     return crossOp(p1,p2,q) == 0 && sign((q-p1).dot(p1-p2)) * sign((q-p2).
99         dot(p1-p2)) < 0;
100 }
101 P proj(P p1, P p2, P q) {
102     P dir = p2 - p1;
103     return p1 + dir * (dir.dot(q - p1) / dir.abs2());
104 }
105
106 P reflect(P p1, P p2, P q){
107     return proj(p1,p2,q) * 2 - q;
108 }
109
110 db nearest(P p1,P p2,P q){
111     P h = proj(p1,p2,q);
112     if(isMiddle(p1,h,p2))
113         return q.distTo(h);
114     return min(p1.distTo(q),p2.distTo(q));
115 }
116
117 db disSS(P p1, P p2, P q1, P q2){
118     if(isSS(p1,p2,q1,q2)) return 0;
119     return min(min(nearest(p1,p2,q1),nearest(p1,p2,q2)), min(nearest(q1,q2
120         ,p1),nearest(q1,q2,p2)));
121 }
122
123 db rad(P p1,P p2){
124     return atan2l(p1.det(p2),p1.dot(p2));
125 }
126
127 db incircle(P p1, P p2, P p3){
128     db A = p1.distTo(p2);
129     db B = p2.distTo(p3);
130     db C = p3.distTo(p1);
131     return sqrtl(A*B*C/(A+B+C));
132 }
133 //polygon
134

```

```

135 db area(vector<P> ps){
136     db ret = 0; rep(i,0,ps.size()) ret += ps[i].det(ps[(i+1)%ps.size()]);
137     return ret/2;
138 }
139
140 int contain(vector<P> ps, P p){ //2:inside,1:on_seg,0:outside
141     int n = ps.size(), ret = 0;
142     rep(i,0,n){
143         P u=ps[i],v=ps[(i+1)%n];
144         if(onSeg(u,v,p)) return 1;
145         if(cmp(u.y,v.y)<=0) swap(u,v);
146         if(cmp(p.y,u.y) >0 || cmp(p.y,v.y) <= 0) continue;
147         ret ^= crossOp(p,u,v) > 0;
148     }
149     return ret*2;
150 }
151
152 vector<P> convexHull(vector<P> ps) {
153     int n = ps.size(); if(n <= 1) return ps;
154     sort(ps.begin(), ps.end());
155     vector<P> qs(n * 2); int k = 0;
156     for (int i = 0; i < n; qs[k++] = ps[i++])
157         while (k > 1 && crossOp(qs[k - 2], qs[k - 1], ps[i]) <= 0) --k;
158     for (int i = n - 2, t = k; i >= 0; qs[k++] = ps[i--])
159         while (k > t && crossOp(qs[k - 2], qs[k - 1], ps[i]) <= 0) --k;
160     qs.resize(k - 1);
161     return qs;
162 }
163
164 vector<P> convexHullNonStrict(vector<P> ps) {
165     //caution: need to unique the Ps first
166     int n = ps.size(); if(n <= 1) return ps;
167     sort(ps.begin(), ps.end());
168     vector<P> qs(n * 2); int k = 0;
169     for (int i = 0; i < n; qs[k++] = ps[i++])
170         while (k > 1 && crossOp(qs[k - 2], qs[k - 1], ps[i]) < 0) --k;
171     for (int i = n - 2, t = k; i >= 0; qs[k++] = ps[i--])
172         while (k > t && crossOp(qs[k - 2], qs[k - 1], ps[i]) < 0) --k;
173     qs.resize(k - 1);
174     return qs;
175 }
176

```

```

177 db convexDiameter(vector<P> ps){
178     int n = ps.size(); if(n <= 1) return 0;
179     int is = 0, js = 0; rep(k,1,n) is = ps[k]<ps[is]?k:is, js = ps[js] <
        ps[k]?k:js;
180     int i = is, j = js;
181     db ret = ps[i].distTo(ps[j]);
182     do{
183         if((ps[(i+1)%n]-ps[i]).det(ps[(j+1)%n]-ps[j]) >= 0)
184             (++j)%=n;
185         else
186             (++i)%=n;
187         ret = max(ret,ps[i].distTo(ps[j]));
188     }while(i!=is || j!=js);
189     return ret;
190 }
191
192 vector<P> convexCut(const vector<P>&ps, P q1, P q2) {
193     vector<P> qs;
194     int n = ps.size();
195     rep(i,0,n){
196         P p1 = ps[i], p2 = ps[(i+1)%n];
197         int d1 = crossOp(q1,q2,p1), d2 = crossOp(q1,q2,p2);
198         if(d1 >= 0) qs.pb(p1);
199         if(d1 * d2 < 0) qs.pb(isLL(p1,p2,q1,q2));
200     }
201     return qs;
202 }
203
204 //min_dist
205
206 db min_dist(vector<P>&ps,int l,int r){
207     if(r-l<=5){
208         db ret = 1e100;
209         rep(i,l,r) rep(j,l,i) ret = min(ret,ps[i].distTo(ps[j]));
210         return ret;
211     }
212     int m = (l+r)>>1;
213     db ret = min(min_dist(ps,l,m),min_dist(ps,m,r));
214     vector<P> qs; rep(i,l,r) if(abs(ps[i].x-ps[m].x)<= ret) qs.pb(ps[i]);
215     sort(qs.begin(), qs.end(),[(P a,P b) -> bool {return a.y<b.y; }]);
216     rep(i,1,qs.size()) for(int j=i-1;j>=0&&qs[j].y>=qs[i].y-ret;--j)
217         ret = min(ret,qs[i].distTo(qs[j]));

```

```

218     return ret;
219 }
220
221 int type(P o1,db r1,P o2,db r2){
222     db d = o1.distTo(o2);
223     if(cmp(d,r1+r2) == 1) return 4;
224     if(cmp(d,r1+r2) == 0) return 3;
225     if(cmp(d,abs(r1-r2)) == 1) return 2;
226     if(cmp(d,abs(r1-r2)) == 0) return 1;
227     return 0;
228 }
229
230 vector<P> isCL(P o,db r,P p1,P p2){
231     db x = (p1-o).dot(p2-p1), y = (p2-p1).abs2(), d = x * x - y * ((p1-o).
        abs2() - r*r);
232     if(sign(d) < 0) return {};
233     d = max(d,0.0); P m = p1 - (p2-p1)*(x/y), dr = (p2-p1)*(sqrt(d)/y);
234     return {m-dr,m+dr}; //along dir: p1->p2
235 }
236
237 vector<P> isCC(P o1, db r1, P o2, db r2) { //need to check whether two
        circles are the same
238     db d = o1.distTo(o2);
239     if (cmp(d, r1 + r2) == 1) return {};
240     d = min(d, r1 + r2);
241     db y = (r1 * r1 + d * d - r2 * r2) / (2 * d), x = sqrt(r1 * r1 - y * y
        );
242     P dr = (o2 - o1).unit();
243     P q1 = o1 + dr * y, q2 = dr.rot90() * x;
244     return {q1-q2,q1+q2}; //along circle 1
245 }
246
247 vector<P> tanCP(P o, db r, P p) {
248     db x = (p - o).abs2(), d = x - r * r;
249     if (sign(d) <= 0) return {}; // on circle => no tangent
250     P q1 = o + (p - o) * (r * r / x);
251     P q2 = (p - o).rot90() * (r * sqrt(d) / x);
252     return {q1-q2,q1+q2}; //counter clock-wise
253 }
254
255
256 vector<L> extanCC(P o1, db r1, P o2, db r2) {

```

```

257     vector<L> ret;
258     if (cmp(r1, r2) == 0) {
259         P dr = (o2 - o1).unit().rot90() * r1;
260         ret.pb({{o1 + dr, o2 + dr}}), ret.pb({{o1 - dr, o2 - dr}});
261     } else {
262         P p = (o2 * r1 - o1 * r2) / (r1 - r2);
263         vector<P> ps = tanCP(o1, r1, p), qs = tanCP(o2, r2, p);
264         rep(i,0,min(ps.size(),qs.size())) ret.pb({{ps[i], qs[i]}}); //c1
            counter-clock wise
265     }
266     return ret;
267 }
268
269 vector<L> intanCC(P o1, db r1, P o2, db r2) {
270     vector<L> ret;
271     P p = (o1 * r2 + o2 * r1) / (r1 + r2);
272     vector<P> ps = tanCP(o1,r1,p), qs = tanCP(o2,r2,p);
273     rep(i,0,min(ps.size(),qs.size())) ret.pb({{ps[i], qs[i]}}); //c1
        counter-clock wise
274     return ret;
275 }
276
277 db areaCT(db r, P p1, P p2){
278     vector<P> is = isCL(P(0,0),r,p1,p2);
279     if(is.empty()) return r*r*rad(p1,p2)/2;
280     bool b1 = cmp(p1.abs2(),r*r) == 1, b2 = cmp(p2.abs2(), r*r) == 1;
281     if(b1 && b2){
282         if(sign((p1-is[0]).dot(p2-is[0])) <= 0 &&
283             sign((p1-is[0]).dot(p2-is[0])) <= 0)
284             return r*r*(rad(p1,is[0]) + rad(is[1],p2))/2 + is[0].det(is[1])/2;
285         else return r*r*rad(p1,p2)/2;
286     }
287     if(b1) return (r*r*rad(p1,is[0]) + is[0].det(p2))/2;
288     if(b2) return (p1.det(is[1]) + r*r*rad(is[1],p2))/2;
289     return p1.det(p2)/2;
290 }
291
292 bool parallel(L l0, L l1) { return sign( l0.dir().det( l1.dir() ) ) == 0;
    }
293
294 bool sameDir(L l0, L l1) { return parallel(l0, l1) && sign(l0.dir().dot(l1
    .dir() ) ) == 1; }

```

```

295
296 bool cmp (P a, P b) {
297     if (a.quad() != b.quad()) {
298         return a.quad() < b.quad();
299     } else {
300         return sign( a.det(b) ) > 0;
301     }
302 }
303
304 bool operator < (L l0, L l1) {
305     if (sameDir(l0, l1)) {
306         return l1.include(l0[0]);
307     } else {
308         return cmp( l0.dir(), l1.dir() );
309     }
310 }
311
312 bool check(L u, L v, L w) {
313     return w.include(isLL(u,v));
314 }
315
316 vector<P> halfPlaneIS(vector<L> &l) {
317     sort(l.begin(), l.end());
318     deque<L> q;
319     for (int i = 0; i < (int)l.size(); ++i) {
320         if (i && sameDir(l[i], l[i - 1])) continue;
321         while (q.size() > 1 && !check(q[q.size() - 2], q[q.size() - 1], l[
            i])) q.pop_back();
322         while (q.size() > 1 && !check(q[1], q[0], l[i])) q.pop_front();
323         q.push_back(l[i]);
324     }
325     while (q.size() > 2 && !check(q[q.size() - 2], q[q.size() - 1], q[0]))
326         q.pop_back();
327     while (q.size() > 2 && !check(q[1], q[0], q[q.size() - 1])) q.
328         pop_front();
329     vector<P> ret;
330     for (int i = 0; i < (int)q.size(); ++i) ret.push_back(isLL(q[i], q[(i
        + 1) % q.size()]));
331     return ret;
332 }
333
334 P inCenter(P A, P B, P C) {

```

```

333     double a = (B - C).abs(), b = (C - A).abs(), c = (A - B).abs();
334     return (A * a + B * b + C * c) / (a + b + c);
335 }
336
337 P circumCenter(P a, P b, P c) {
338     P bb = b - a, cc = c - a;
339     double db = bb.abs2(), dc = cc.abs2(), d = 2 * bb.det(cc);
340     return a - P(bb.y * dc - cc.y * db, cc.x * db - bb.x * dc) / d;
341 }
342
343 P othroCenter(P a, P b, P c) {
344     P ba = b - a, ca = c - a, bc = b - c;
345     double Y = ba.y * ca.y * bc.y,
346     A = ca.x * ba.y - ba.x * ca.y,
347     x0 = (Y + ca.x * ba.y * b.x - ba.x * ca.y * c.x) / A,
348     y0 = -ba.x * (x0 - c.x) / ba.y + ca.y;
349     return {x0, y0};
350 }

```

4.2 circle.cpp

```

1  int type(P o1,db r1,P o2,db r2){
2      db d = o1.distTo(o2);
3      if(cmp(d,r1+r2) == 1) return 4;
4      if(cmp(d,r1+r2) == 0) return 3;
5      if(cmp(d,abs(r1-r2)) == 1) return 2;
6      if(cmp(d,abs(r1-r2)) == 0) return 1;
7      return 0;
8  }
9
10 vector<P> isCL(P o,db r,P p1,P p2){
11     if (cmp(abs((o-p1).det(p2-p1)/p1.distTo(p2)),r)>0) return {};
12     db x = (p1-o).dot(p2-p1), y = (p2-p1).abs2(), d = x * x - y * ((p1
        -o).abs2() - r*r);
13     d = max(d,(db)0.0); P m = p1 - (p2-p1)*(x/y), dr = (p2-p1)*(sqrt(d
        )/y);
14     return {m-dr,m+dr}; //along dir: p1->p2
15 }
16
17 vector<P> isCC(P o1, db r1, P o2, db r2) { //need to check whether two
        circles are the same

```

```

18     db d = o1.distTo(o2);
19     if (cmp(d, r1 + r2) == 1) return {};
20     if (cmp(d,abs(r1-r2))==-1) return {};
21     d = min(d, r1 + r2);
22     db y = (r1 * r1 + d * d - r2 * r2) / (2 * d), x = sqrt(r1 * r1 - y
        * y);
23     P dr = (o2 - o1).unit();
24     P q1 = o1 + dr * y, q2 = dr.rot90() * x;
25     return {q1-q2,q1+q2}; //along circle 1
26 }
27
28 // extanCC, intanCC : -r2, tanCP : r2 = 0
29 vector<pair<P, P>> tanCC(P o1, db r1, P o2, db r2) {
30     P d = o2 - o1;
31     db dr = r1 - r2, d2 = d.abs2(), h2 = d2 - dr * dr;
32     if (sign(d2) == 0 || sign(h2) < 0) return {};
33     h2 = max((db)0.0, h2);
34     vector<pair<P, P>> ret;
35     for (db sign : {-1, 1}) {
36         P v = (d * dr + d.rot90() * sqrt(h2) * sign) / d2;
37         ret.push_back({o1 + v * r1, o2 + v * r2});
38     }
39     if (sign(h2) == 0) ret.pop_back();
40     return ret;
41 }
42
43 db rad(P p1,P p2){
44     return atan2l(p1.det(p2),p1.dot(p2));
45 }
46
47 db areaCT(db r, P p1, P p2){
48     vector<P> is = isCL(P(0,0),r,p1,p2);
49     if(is.empty()) return r*r*rad(p1,p2)/2;
50     bool b1 = cmp(p1.abs2(),r*r) == 1, b2 = cmp(p2.abs2(), r*r) == 1;
51     if(b1 && b2){
52         P md=(is[0]+is[1])/2;
53         if(sign((p1-md).dot(p2-md)) <= 0)
54             return r*r*(rad(p1,is[0]) + rad(is[1],p2))/2 + is
                [0].det(is[1])/2;
55         else return r*r*rad(p1,p2)/2;
56     }
57     if(b1) return (r*r*rad(p1,is[0]) + is[0].det(p2))/2;

```

```

58     if(b2) return (p1.det(is[1]) + r*r*rad(is[1],p2))/2;
59     return p1.det(p2)/2;
60 }
61
62 P inCenter(P A, P B, P C) {
63     double a = (B - C).abs(), b = (C - A).abs(), c = (A - B).abs();
64     return (A * a + B * b + C * c) / (a + b + c);
65 }
66
67 P circumCenter(P a, P b, P c) {
68     P bb = b - a, cc = c - a;
69     double db = bb.abs2(), dc = cc.abs2(), d = 2 * bb.det(cc);
70     return a - P(bb.y * dc - cc.y * db, cc.x * db - bb.x * dc) / d;
71 }
72
73 P othroCenter(P a, P b, P c) {
74     P ba = b - a, ca = c - a, bc = b - c;
75     double Y = ba.y * ca.y * bc.y,
76     A = ca.x * ba.y - ba.x * ca.y,
77     x0 = (Y + ca.x * ba.y * b.x - ba.x * ca.y * c.x) / A,
78     y0 = -ba.x * (x0 - c.x) / ba.y + ca.y;
79     return {x0, y0};
80 }
81
82 pair<P,db> min_circle(vector<P> ps){
83     random_shuffle(ps.begin(), ps.end());
84     int n = ps.size();
85     P o = ps[0]; db r = 0;
86     rep(i,1,n) if(o.distTo(ps[i]) > r + EPS){
87         o = ps[i], r = 0;
88         rep(j,0,i) if(o.distTo(ps[j]) > r + EPS){
89             o = (ps[i] + ps[j]) / 2; r = o.distTo(ps[i]);
90             rep(k,0,j) if(o.distTo(ps[k]) > r + EPS){
91                 o = circumCenter(ps[i],ps[j],ps[k]);
92                 r = o.distTo(ps[i]);
93             }
94         }
95     }
96     return {o,r};
97 }

```

4.3 point.cpp

```

1  typedef double db;
2  const db EPS = 1e-9;
3
4  inline int sign(db a) { return a < -EPS ? -1 : a > EPS; }
5
6  inline int cmp(db a, db b) { return sign(a - b); }
7
8  struct P {
9      db x, y;
10     P() {}
11     P(db _x, db _y) : x(_x), y(_y) {}
12     P operator+(P p) { return {x + p.x, y + p.y}; }
13     P operator-(P p) { return {x - p.x, y - p.y}; }
14     P operator*(db d) { return {x * d, y * d}; }
15     P operator/(db d) { return {x / d, y / d}; }
16
17     bool operator<(P p) const {
18         int c = cmp(x, p.x);
19         if (c) return c == -1;
20         return cmp(y, p.y) == -1;
21     }
22
23     bool operator==(P o) const {
24         return cmp(x, o.x) == 0 && cmp(y, o.y) == 0;
25     }
26
27     db dot(P p) { return x * p.x + y * p.y; }
28     db det(P p) { return x * p.y - y * p.x; }
29
30     db distTo(P p) { return (*this - p).abs(); }
31     db alpha() { return atan2(y, x); }
32     void read() { cin >> x >> y; }
33     void write() { cout << "(" << x << ", " << y << ")" << endl; }
34     db abs() { return sqrt(abs2()); }
35     db abs2() { return x * x + y * y; }
36     P rot90() { return P(-y, x); }
37     P unit() { return *this / abs(); }
38     int quad() const { return sign(y) == 1 || (sign(y) == 0 && sign(x)
39         >= 0); }
40     P rot(db an) { return {x * cos(an) - y * sin(an), x * sin(an) + y

```

```

        * cos(an)); }
40 };
41
42 #define cross(p1,p2,p3) ((p2.x-p1.x)*(p3.y-p1.y)-(p3.x-p1.x)*(p2.y-p1.y))
43 #define crossOp(p1,p2,p3) sign(cross(p1,p2,p3))
44
45 // 直线  $p1p2$ ,  $q1q2$  是否恰有一个交点
46 bool chkLL(P p1, P p2, P q1, P q2) {
47     db a1 = cross(q1, q2, p1), a2 = -cross(q1, q2, p2);
48     return sign(a1 + a2) != 0;
49 }
50
51 // 求直线  $p1p2$ ,  $q1q2$  的交点
52 P isLL(P p1, P p2, P q1, P q2) {
53     db a1 = cross(q1, q2, p1), a2 = -cross(q1, q2, p2);
54     return (p1 * a2 + p2 * a1) / (a1 + a2);
55 }
56
57 // 判断区间  $[l1, r1]$ ,  $[l2, r2]$  是否相交
58 bool intersect(db l1, db r1, db l2, db r2) {
59     if (l1 > r1) swap(l1, r1); if (l2 > r2) swap(l2, r2);
60     return !(cmp(r1, l2) == -1 || cmp(r2, l1) == -1);
61 }
62
63 // 线段  $p1p2$ ,  $q1q2$  相交
64 bool isSS(P p1, P p2, P q1, P q2) {
65     return intersect(p1.x, p2.x, q1.x, q2.x) && intersect(p1.y, p2.y,
66         q1.y, q2.y) &&
67         crossOp(p1, p2, q1) * crossOp(p1, p2, q2) <= 0 && crossOp(
68             q1, q2, p1)
69             * crossOp(q1, q2, p2) <= 0;
70 }
71
72 // 线段  $p1p2$ ,  $q1q2$  严格相交
73 bool isSS_strict(P p1, P p2, P q1, P q2) {
74     return crossOp(p1, p2, q1) * crossOp(p1, p2, q2) < 0 && crossOp(q1
75         , q2, p1)
76         * crossOp(q1, q2, p2) < 0;
77 }
78
79 //  $m$  在  $a$  和  $b$  之间
80 bool isMiddle(db a, db m, db b) {

```

```

81     /*if (a > b) swap(a, b);
82     return cmp(a, m) <= 0 && cmp(m, b) <= 0;*/
83     return sign(a - m) == 0 || sign(b - m) == 0 || (a < m != b < m);
84 }
85
86 bool isMiddle(P a, P m, P b) {
87     return isMiddle(a.x, m.x, b.x) && isMiddle(a.y, m.y, b.y);
88 }
89
90 // 点  $p$  在线段  $p1p2$  上
91 bool onSeg(P p1, P p2, P q) {
92     return crossOp(p1, p2, q) == 0 && isMiddle(p1, q, p2);
93 }
94
95 //  $q1q2$  和  $p1p2$  的交点 在  $p1p2$  上?
96 // 点  $p$  严格在  $p1p2$  上
97 bool onSeg_strict(P p1, P p2, P q) {
98     return crossOp(p1, p2, q) == 0 && sign((q - p1).dot(p1 - p2)) *
99         sign((q - p2).dot(p1 - p2)) < 0;
100 }
101
102 // 求  $q$  到 直线 $p1p2$  的投影 (垂足) :  $p1 \neq p2$ 
103 P proj(P p1, P p2, P q) {
104     P dir = p2 - p1;
105     return p1 + dir * (dir.dot(q - p1) / dir.abs2());
106 }
107
108 // 求  $q$  以 直线 $p1p2$  为轴的反射
109 P reflect(P p1, P p2, P q) {
110     return proj(p1, p2, q) * 2 - q;
111 }
112
113 // 求  $q$  到 线段 $p1p2$  的最小距离
114 db nearest(P p1, P p2, P q) {
115     if (p1 == p2) return p1.distTo(q);
116     P h = proj(p1, p2, q);
117     if (isMiddle(p1, h, p2))
118         return q.distTo(h);
119     return min(p1.distTo(q), p2.distTo(q));
120 }
121
122 // 求 线段 $p1p2$  与 线段 $q1q2$  的距离

```

```

119 db disSS(P p1, P p2, P q1, P q2) {
120     if (isSS(p1, p2, q1, q2)) return 0;
121     return min(min(nearest(p1, p2, q1), nearest(p1, p2, q2)), min(
        nearest(q1, q2, p1), nearest(q1, q2, p2)));
122 }
123
124 // 极角排序
125 sort(p, p + n, [&](P a, P b) {
126     int qa = a.quad(), qb = b.quad();
127     if (qa != qb) return qa < qb;
128     else return sign(a.det(b)) > 0;
129 });

```

4.4 polygon.cpp

```

1 db area(vector<P> ps){
2     db ret = 0; rep(i,0,ps.size()) ret += ps[i].det(ps[(i+1)%ps.size()
        ]]);
3     return ret/2;
4 }
5
6 int contain(vector<P> ps, P p){ //2:inside,1:on_seg,0:outside
7     int n = ps.size(), ret = 0;
8     rep(i,0,n){
9         P u=ps[i],v=ps[(i+1)%n];
10        if(onSeg(u,v,p)) return 1;
11        if(cmp(u.y,v.y)<=0) swap(u,v);
12        if(cmp(p.y,u.y) > 0 || cmp(p.y,v.y) <= 0) continue;
13        ret ^= crossOp(p,u,v) > 0;
14    }
15    return ret*2;
16 }
17
18 vector<P> convexHull(vector<P> ps) {
19     int n = ps.size(); if(n <= 1) return ps;
20     sort(ps.begin(), ps.end());
21     vector<P> qs(n * 2); int k = 0;
22     for (int i = 0; i < n; qs[k++] = ps[i++])
23         while (k > 1 && crossOp(qs[k - 2], qs[k - 1], ps[i]) <= 0)
24             --k;
25     for (int i = n - 2, t = k; i >= 0; qs[k++] = ps[i--])

```

```

25         while (k > t && crossOp(qs[k - 2], qs[k - 1], ps[i]) <= 0)
26             --k;
27     qs.resize(k - 1);
28     return qs;
29 }
30 vector<P> convexHullNonStrict(vector<P> ps) {
31     //caution: need to unique the Ps first
32     int n = ps.size(); if(n <= 1) return ps;
33     sort(ps.begin(), ps.end());
34     vector<P> qs(n * 2); int k = 0;
35     for (int i = 0; i < n; qs[k++] = ps[i++])
36         while (k > 1 && crossOp(qs[k - 2], qs[k - 1], ps[i]) < 0)
37             --k;
38     for (int i = n - 2, t = k; i >= 0; qs[k++] = ps[i--])
39         while (k > t && crossOp(qs[k - 2], qs[k - 1], ps[i]) < 0)
40             --k;
41     qs.resize(k - 1);
42     return qs;
43 }
44
45 db convexDiameter(vector<P> ps){
46     int n = ps.size(); if(n <= 1) return 0;
47     int is = 0, js = 0; rep(k,1,n) is = ps[k]<ps[is]?k:is, js = ps[js]
48         < ps[k]?k:js;
49     int i = is, j = js;
50     db ret = ps[i].distTo(ps[j]);
51     do{
52         if((ps[(i+1)%n]-ps[i]).det(ps[(j+1)%n]-ps[j]) >= 0)
53             (++j)%=n;
54         else
55             (++i)%=n;
56         ret = max(ret,ps[i].distTo(ps[j]));
57     }while(i!=is || j!=js);
58     return ret;
59 }
60
61 vector<P> convexCut(const vector<P>&ps, P q1, P q2) {
62     vector<P> qs;
63     int n = ps.size();
64     rep(i,0,n){
65         P p1 = ps[i], p2 = ps[(i+1)%n];

```



```

63         int d1 = crossOp(q1,q2,p1), d2 = crossOp(q1,q2,p2);
64         if(d1 >= 0) qs.push_back(p1);
65         if(d1 * d2 < 0) qs.push_back(isLL(p1,p2,q1,q2));
66     }
67     return qs;
68 }
69
70 void reorderPolygon(vector<P> &ps) {
71     size_t pos = 0;
72     for(size_t i = 1; i < ps.size(); i++){
73         if(ps[i].y < ps[pos].y || (ps[i].y == ps[pos].y && ps[i].x < ps[
74             pos].x))
75             pos = i;
76     }
77     rotate(ps.begin(), ps.begin() + pos, ps.end());
78
79     vector<P> minkowski(vector<P> p, vector<P> q){
80         if(p.empty()) return q;
81         // the first vertex must be the lowest
82         reorderPolygon(p);
83         reorderPolygon(q);
84         // must ensure cyclic indexing
85         p.push_back(p[0]);
86         p.push_back(p[1]);
87         q.push_back(q[0]);
88         q.push_back(q[1]);
89         // main part
90         vector<P> result;
91         size_t i = 0, j = 0;
92         while(i < p.size() - 2 || j < q.size() - 2){
93             result.push_back(p[i] + q[j]);
94             auto cross = (p[i + 1] - p[i]).det(q[j + 1] - q[j]);
95             if(cross >= 0 && i < SZ(p) - 2)
96                 ++i;
97             if(cross <= 0 && j < SZ(q) - 2)
98                 ++j;
99         }
100         return result;
101     }
102
103     bool convexContain(const vector<P> &l, P p, bool strict = true) {

```

```

104         int a = 1, b = l.size() - 1, r = !strict;
105         if (l.size() < 3) return r && onSeg(l[0], l.back(), p);
106         if (crossOp(l[0], l[a], l[b]) > 0) swap(a, b);
107         if (crossOp(l[0], l[a], p) >= r || crossOp(l[0], l[b], p) <= -r)
108             return false;
109         while (abs(a - b) > 1) {
110             int c = (a + b) / 2;
111             (crossOp(l[0], l[c], p) > 0 ? b : a) = c;
112         }
113         return sign(cross(l[a], l[b], p)) < r;
114     }

```

4.5 圆面积并.cpp

```

1 db intergal(db x,db y,db r,db L,db R){
2     return r*r*(R-L) + x*r*(sinl(R) - sinl(L)) + y*r*(-cosl(R) + cosl(L));
3 }
4
5 db calc_area_circle(P c,db r,db L,db R){
6     return intergal(c.x,c.y,r,L,R) / 2;
7 }
8
9 db norm(db x){
10     while(x < 0) x += 2 * PI;
11     while(x > 2 * PI) x -= 2 * PI;
12     return x;
13 }
14
15 P cs[N]; db rs[N];
16
17 void work(){
18     vector<int> cand = {};
19     rep(i,0,m){
20         bool ok = 1;
21         rep(j,0,m) if(i!=j){
22             if(rs[j] > rs[i] + EPS && rs[i] + cs[i].distTo(cs[
23                 j]) <= rs[j] + EPS){
24                 ok = 0; break;
25             }
26             if(cs[i] == cs[j] && cmp(rs[i],rs[j]) == 0 && j <
27                 i){

```

```

26         ok = 0; break;
27     }
28 }
29     if(ok) cand.pb(i);
30 }
31
32 rep(i,0,cand.size()) cs[i] = cs[cand[i]], rs[i] = rs[cand[i]];
33 m = cand.size();
34
35 db area = 0;
36
37 //work
38 rep(i,0,m){
39     vector<pair<db,int>> ev = {{0,0},{2*PI,0}};
40
41     int cur = 0;
42
43     rep(j,0,m) if(j!=i){
44         auto ret = isCC(cs[i],rs[i],cs[j],rs[j]);
45         if(!ret.empty()){
46             db l = (ret[0] - cs[i]).alpha();
47             db r = (ret[1] - cs[i]).alpha();
48             l = norm(l); r = norm(r);
49             ev.pb({l,1});ev.pb({r,-1});
50             if(l > r) ++cur;
51         }
52     }
53
54     sort(ev.begin(), ev.end());
55     rep(j,0,ev.size() - 1){
56         cur += ev[j].se;
57         if(cur == 0){
58             area += calc_area_circle(cs[i],rs[i],ev[j]
59                                     ].fi,ev[j+1].fi);
60         }
61     }
62 }

```

5 Graph

5.1 bellmanford.cpp

```

1 vector<PII> e[N];
2
3 template <typename T>
4 void add(int u, int v, T w) {
5     e[u].eb(v, w);
6 }
7
8 template <typename T>
9 vector<T> bellmanford(vector<pair<int, T>> *g, int start) {
10     // assert(0 <= start && start < g.n);
11     // maybe use inf = numeric_limits<T>::max() / 4
12     const T inf = numeric_limits<T>::max() / 4;
13     vector<T> dist(n, inf);
14     dist[start] = 0;
15     int cnt = 0;
16     while (true) {
17         bool upd = 0;
18         cnt++;
19         for (int i = 0; i < n; i++) {
20             for (auto [to, cost] : e[i]) {
21                 if (dist[to] > dist[i] + cost) {
22                     upd = 1;
23                     dist[to] = dist[i] + cost;
24                 }
25             }
26         }
27         if (!upd || cnt == n) {
28             break;
29         }
30     }
31     return dist;
32     // returns inf if there's no path
33 }

```

5.2 BlockCutTree.cpp

```

1 struct BlockCutTree {
2     int n;

```

```

3     std::vector<std::vector<int>> adj;
4     std::vector<int> dfn, low, stk;
5     int cnt, cur;
6     std::vector<std::pair<int, int>> edges;
7
8     BlockCutTree() {}
9     BlockCutTree(int n) {
10         init(n);
11     }
12
13     void init(int n) {
14         this->n = n;
15         adj.assign(n, {});
16         dfn.assign(n, -1);
17         low.resize(n);
18         stk.clear();
19         cnt = cur = 0;
20         edges.clear();
21     }
22
23     void addEdge(int u, int v) {
24         adj[u].push_back(v);
25         adj[v].push_back(u);
26     }
27
28     void dfs(int x) {
29         stk.push_back(x);
30         dfn[x] = low[x] = cur++;
31
32         for (auto y : adj[x]) {
33             if (dfn[y] == -1) {
34                 dfs(y);
35                 low[x] = std::min(low[x], low[y]);
36                 if (low[y] == dfn[x]) {
37                     int v;
38                     do {
39                         v = stk.back();
40                         stk.pop_back();
41                         edges.emplace_back(n + cnt, v);
42                     } while (v != y);
43                     edges.emplace_back(x, n + cnt);
44                     cnt++;

```

```

45         }
46     } else {
47         low[x] = std::min(low[x], dfn[y]);
48     }
49 }
50 }
51
52     std::pair<int, std::vector<std::pair<int, int>>> work() {
53         for (int i = 0; i < n; i++) {
54             if (dfn[i] == -1) {
55                 stk.clear();
56                 dfs(i);
57             }
58         }
59         return {cnt, edges};
60     }
61 };

```

5.3 dijfast.cpp

```

1     vector<PII> e[N];
2
3     template <typename T>
4     void add(int u, int v, T w) {
5         e[u].eb(v, w);
6     }
7
8     template <typename T>
9     vector<T> dijkstra(vector<pair<int, T>> *g, int start) {
10         // assert(0 <= start && start < g.n);
11         // maybe use inf = numeric_limits<T>::max() / 4
12         vector<T> dist(n, numeric_limits<T>::max());
13         priority_queue<pair<T, int>, vector<pair<T, int>>, greater<pair<T,
14             int>>> s;
15         dist[start] = 0;
16         s.emplace(dist[start], start);
17         while (!s.empty()) {
18             T expected = s.top().first;
19             int i = s.top().second;
20             s.pop();
21             if (dist[i] != expected) {

```

```

21         continue;
22     }
23     for (auto [to, cost] : g[i]) {
24         if (dist[i] + cost < dist[to]) {
25             dist[to] = dist[i] + cost;
26             s.emplace(dist[to], to);
27         }
28     }
29 }
30 return dist;
31 // returns numeric_limits<T>::max() if there's no path
32 }

```

5.4 dijkstra.cpp

```

1 vector<PII> e[N];
2
3 template <typename T>
4 void add(int u, int v, T w) {
5     e[u].eb(v, w);
6 }
7
8 template <typename T>
9 vector<T> dijkstra(vector<pair<int, T>> *g, int start) {
10     // assert(0 <= start < g->n);
11     // maybe use inf = numeric_limits<T>::max() / 4
12     const T inf = numeric_limits<T>::max();
13     vector<T> dist(n, inf);
14     vector<int> was(n, 0);
15     dist[start] = 0;
16     while (true) {
17         int cur = -1;
18         for (int i = 0; i < n; i++) {
19             if (was[i] || dist[i] == inf) continue;
20             if (cur == -1 || dist[i] < dist[cur]) {
21                 cur = i;
22             }
23         }
24         if (cur == -1 || dist[cur] == inf) {
25             break;
26         }
27     }
28 }

```

```

27         was[cur] = 1;
28         for (auto [to, cost] : g[cur]) {
29             dist[to] = min(dist[to], dist[cur] + cost);
30         }
31     }
32     return dist;
33     // returns inf if there's no path
34 }

```

5.5 dinic.cpp

```

1 template<typename T>
2 struct FlowGraph {
3     static const int V = 1015;
4     static const int E = 100015;
5     int s, t, vtot;
6     int head[V], etot;
7     int dis[V], cur[V];
8     struct edge {
9         int v, nxt;
10        T f;
11    } e[E * 2];
12    void addedge(int u, int v, T f) {
13        e[etot] = {v, head[u], f};
14        head[u] = etot++;
15        e[etot] = {u, head[v], 0};
16        head[v] = etot++;
17    }
18    bool bfs() {
19        for (int i = 1; i <= vtot; i++) {
20            dis[i] = 0;
21            cur[i] = head[i];
22        }
23        queue<int> q;
24        q.push(s); dis[s] = 1;
25        while (!q.empty()) {
26            int u = q.front(); q.pop();
27            for (int i = head[u]; i != -1; i = e[i].nxt) {
28                if (e[i].f && !dis[e[i].v]) {
29                    int v = e[i].v;
30                    dis[v] = dis[u] + 1;

```

```

31         if (v == t) return true;
32         q.push(v);
33     }
34 }
35 }
36 return false;
37 }
38 T dfs(int u, T m) {
39     if (u == t) return m;
40     T flow = 0;
41     for (int i = cur[u]; i != -1; cur[u] = i = e[i].nxt) {
42         if (e[i].f && dis[e[i].v] == dis[u] + 1) {
43             T f = dfs(e[i].v, min(m, e[i].f));
44             e[i].f -= f;
45             e[i ^ 1].f += f;
46             m -= f;
47             flow += f;
48             if (!m) break;
49         }
50     }
51     if (!flow) dis[u] = -1;
52     return flow;
53 }
54 T dinic() {
55     T flow = 0;
56     while (bfs()) flow += dfs(s, numeric_limits<T>::max());
57     return flow;
58 }
59 void init(int _s, int _t, int _vtot) {
60     s = _s;
61     t = _t;
62     vtot = _vtot;
63     etot = 0;
64     for (int i = 1; i <= vtot; i++) head[i] = -1;
65 }
66 };

```

5.6 dinic tourist.cpp

```

1 template <typename T>
2 class flow_graph {

```

```

3 public:
4     static constexpr T eps = (T) 1e-9;
5
6     struct edge {
7         int from;
8         int to;
9         T c;
10        T f;
11    };
12
13    vector<vector<int>>> g;
14    vector<edge> edges;
15    int n;
16    int st;
17    int fin;
18    T flow;
19
20    flow_graph(int _n, int _st, int _fin) : n(_n), st(_st), fin(_fin) {
21        assert(0 <= st && st < n && 0 <= fin && fin < n && st != fin);
22        g.resize(n);
23        flow = 0;
24    }
25
26    void clear_flow() {
27        for (const edge &e : edges) {
28            e.f = 0;
29        }
30        flow = 0;
31    }
32
33    int add(int from, int to, T forward_cap, T backward_cap) {
34        assert(0 <= from && from < n && 0 <= to && to < n);
35        int id = (int) edges.size();
36        g[from].push_back(id);
37        edges.push_back({from, to, forward_cap, 0});
38        g[to].push_back(id + 1);
39        edges.push_back({to, from, backward_cap, 0});
40        return id;
41    }
42 };
43
44 template <typename T>

```

```

45 class dinic {
46 public:
47     flow_graph<T> &g;
48
49     vector<int> ptr;
50     vector<int> d;
51     vector<int> q;
52
53     dinic(flow_graph<T> &_g) : g(_g) {
54         ptr.resize(g.n);
55         d.resize(g.n);
56         q.resize(g.n);
57     }
58
59     bool expath() {
60         fill(d.begin(), d.end(), -1);
61         q[0] = g.fin;
62         d[g.fin] = 0;
63         int beg = 0, end = 1;
64         while (beg < end) {
65             int i = q[beg++];
66             for (int id : g.g[i]) {
67                 const auto &e = g.edges[id];
68                 const auto &back = g.edges[id ^ 1];
69                 if (back.c - back.f > g.eps && d[e.to] == -1) {
70                     d[e.to] = d[i] + 1;
71                     if (e.to == g.st) {
72                         return true;
73                     }
74                     q[end++] = e.to;
75                 }
76             }
77         }
78         return false;
79     }
80
81     T dfs(int v, T w) {
82         if (v == g.fin) {
83             return w;
84         }
85         int &j = ptr[v];
86         while (j >= 0) {

```

```

87             int id = g.g[v][j];
88             const auto &e = g.edges[id];
89             if (e.c - e.f > g.eps && d[e.to] == d[v] - 1) {
90                 T t = dfs(e.to, min(e.c - e.f, w));
91                 if (t > g.eps) {
92                     g.edges[id].f += t;
93                     g.edges[id ^ 1].f -= t;
94                     return t;
95                 }
96             }
97             j--;
98         }
99         return 0;
100     }
101
102     T max_flow() {
103         while (expath()) {
104             for (int i = 0; i < g.n; i++) {
105                 ptr[i] = (int) g.g[i].size() - 1;
106             }
107             T big_add = 0;
108             while (true) {
109                 T add = dfs(g.st, numeric_limits<T>::max());
110                 if (add <= g.eps) {
111                     break;
112                 }
113                 big_add += add;
114             }
115             if (big_add <= g.eps) {
116                 break;
117             }
118             g.flow += big_add;
119         }
120         return g.flow;
121     }
122
123     vector<bool> min_cut() {
124         max_flow();
125         vector<bool> ret(g.n);
126         for (int i = 0; i < g.n; i++) {
127             ret[i] = (d[i] != -1);
128         }

```

```

129         return ret;
130     }
131 };

```

5.7 eulerian digraph.cpp

```

1 // http://oj.daimayuan.top/course/14/problem/765 单词接龙
2 vector<int> g[N];
3 int in[N], out[N], f[N], vis[N];
4 string s;
5 vector<int> path;
6
7 void dfs(int x) {
8     while (f[x] < SZ(g[x])) {
9         int y = g[x][f[x]];
10        f[x]++;
11        dfs(y);
12        path.pb(x);
13    }
14 }
15
16 bool euler() {
17     int start = -1, diff = 0, num = 0;
18     rep(i, 0, n - 1) {
19         if (in[i] + 1 == out[i]) num++, start = i;
20         if (in[i] != out[i]) diff++;
21     }
22     // 恰好都balance或者恰好一个in = out + 1, 一个in + 1 = out
23     if (!(diff == 0 || (diff == 2 && num == 1))) return false;
24     if (start == -1) {
25         rep(i, 0, n - 1) {
26             if (in[i]) {
27                 start = i;
28                 break;
29             }
30         }
31     }
32     dfs(start);
33     path.pb(start);
34     reverse(all(path));
35     if (SZ(path) != m + 1) return false;

```

```

36         return true;
37     }
38
39 void solve() {
40     cin >> m;
41     n = 26;
42     rep(i, 1, m) {
43         cin >> s;
44         int u = s[0] - 'a', v = s[SZ(s) - 1] - 'a';
45         g[u].pb(v);
46         in[v]++, out[u]++;
47     }
48     cout << (euler() ? "Yes" : "No") << '\n';
49 }

```

5.8 eulerian undigraph.cpp

```

1 // http://oj.daimayuan.top/course/14/problem/763 欧拉路判断
2 vector<PII> g[N];
3 int d[N], f[N], vis[N], edge_idx;
4 vector<int> path;
5
6 void dfs(int x) {
7     while (f[x] < SZ(g[x])) {
8         auto [v, id] = g[x][f[x]];
9         f[x]++;
10        if (vis[id]) continue;
11        vis[id] = 1;
12        dfs(v);
13        path.pb(x);
14    }
15 }
16
17 bool euler() {
18     int start = -1, num = 0;
19     rep(i, 1, n) {
20         if (d[i] & 1) num++, start = i;
21     }
22     if (!(num == 0 || (num == 2 && start != -1))) return false;
23     if (start == -1) {
24         rep(i, 1, n) {

```

```

25         if (d[i]) {
26             start = i;
27             break;
28         }
29     }
30 }
31 dfs(start);
32 path.pb(start);
33 reverse(all(path));
34 if (SZ(path) != m + 1) return false;
35 return true;
36 }
37
38 void solve() {
39     cin >> n >> m;
40     rep(i, 1, m) {
41         int u, v;
42         cin >> u >> v;
43         edge_idx++;
44         g[u].pb({v, edge_idx});
45         g[v].pb({u, edge_idx});
46         d[u]++, d[v]++;
47     }
48     cout << (euler() ? "Yes" : "No") << '\n';
49 }

```

5.9 hungarian.cpp

```

1 vector<int> g[maxn];
2 int idx;
3 int a[N][N], use[N][N], p[maxn], vis[maxn];
4
5 bool find(int x) {
6     vis[x] = 1;
7     for (auto y : g[x]) {
8         if (!p[y] || (!vis[p[y]] && find(p[y]))) {
9             p[y] = x;
10            return true;
11        }
12    }
13    return false;

```

```

14 }
15
16 int match() {
17     int res = 0;
18     fill(p + 1, p + idx + 1, 0);
19     for (int i = 1; i <= idx; i++) {
20         fill(vis + 1, vis + idx + 1, 0);
21         if (find(i)) res++;
22     }
23     return res;
24 }

```

5.10 KM.cpp

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 using ll = long long;
4
5 //  $L \leq R$ , 左边完全匹配
6 // 最小权完备匹配
7
8 // 带权匹配: 使得该二分图的权值和最大 (或最小) 的匹配。
9 // 最大匹配: 使得该二分图边数最多的匹配。
10 // 完备匹配: 使得点数较小的点集中每个点都被匹配的匹配。
11 // 完美匹配: 所有点都被匹配的匹配。
12 // 定理1: 最大匹配数 = 最小点覆盖数 (König 定理)
13 // 定理2: 最大匹配数 = 最大独立数
14 // 定理3: 最小路径覆盖数 = 顶点数 - 最大匹配数
15
16 // 二分图的最小点覆盖
17 // 定义: 在二分图中, 求最少的点集, 使得每一条边至少都有端点在这个点集中。
18 // 二分图的最小点覆盖 = 二分图的最大匹配
19
20 // 二分图的最少边覆盖
21 // 定义: 在二分图中, 求最少的边, 使得他们覆盖所有的点, 并且每一个点只被一条边覆盖。
22 // 二分图的最少边覆盖 = 点数 - 二分图的最大匹配
23
24 // 二分图的最大独立集
25 // 定义: 在二分图中, 选最多的点, 使得任意两个点之间没有直接边连接。
26 // 二分图的最大独立集 = 点数 - 二分图的最大匹配

```



```

27
28 template<class T>
29 pair<T, vector<int>>> hungarian(const vector<vector<T>>> &a) {
30     if (a.empty()) return {0, {}};
31     int n = a.size() + 1, m = a[0].size() + 1;
32     vector<T> u(n), v(m); // 顶标
33     vector<int> p(m), ans(n - 1);
34     for (int i = 1; i < n; i++) {
35         p[0] = i;
36         int j0 = 0;
37         vector<T> dist(m, numeric_limits<T>::max());
38         vector<int> pre(m, -1);
39         vector<bool> done(m + 1);
40         do { // dijkstra
41             done[j0] = true;
42             int i0 = p[j0], j1;
43             T delta = numeric_limits<T>::max();
44             for (int j = 1; j < m; j++) if (!done[j]) {
45                 auto cur = a[i0 - 1][j - 1] - u[i0] - v[j];
46                 if (cur < dist[j]) dist[j] = cur, pre[j] = j0;
47                 if (dist[j] < delta) delta = dist[j], j1 = j;
48             }
49             for (int j = 0; j < m; j++) {
50                 if (done[j]) u[p[j]] += delta, v[j] -= delta;
51                 else dist[j] -= delta;
52             }
53             j0 = j1;
54         } while (p[j0]);
55         while (j0) { // update alternating path
56             int j1 = pre[j0];
57             p[j0] = p[j1], j0 = j1;
58         }
59     }
60     for (int j = 1; j < m; j++) {
61         if (p[j]) ans[p[j] - 1] = j - 1;
62     }
63     return {-v[0], ans}; // min cost
64 }

```

```

65
66 int L, R, m;
67 int main() {
68     scanf("%d%d%d", &L, &R, &m);
69     R = max(L, R);
70     auto a = vector<vector<ll>>>(L, vector<ll>(R, 0));
71     for (int i = 0; i < m; i++) {
72         int u, v, w;
73         scanf("%d%d%d", &u, &v, &w);
74         --u; --v;
75         a[u][v] = -w;
76     }
77     auto [val, ans] = hungarian(a);
78     printf("%lld\n", -val);
79     for (int i = 0; i < L; i++) {
80         if (a[i][ans[i]] >= 0) ans[i] = -1;
81         printf("%d%c", ans[i] + 1, "\n"[i == L - 1]);
82     }
83 }

```

5.11 kosaraju.cpp

```

1 vector<int> e[maxn], erev[maxn];
2 vector<int> c, out;
3 vector<vector<int>>> scc;
4 int vis[maxn];
5 void dfs(int u) {
6     vis[u] = 1;
7     for (auto v : e[u]) if (!vis[v]) dfs(v);
8     out.pb(u);
9 }
10 void dfs_rev(int u) {
11     vis[u] = 1;
12     for (auto v : erev[u]) if (!vis[v]) dfs_rev(v);
13     c.pb(u);
14 }
15 void solve() {
16     cin >> n >> m;
17     rep(i, 1, m) {
18         int u, v;
19         cin >> u >> v;

```

```

20     e[u].pb(v);
21     erev[v].pb(u);
22 }
23 rep(i, 1, n) if (!vis[i]) dfs(i);
24 fill(vis + 1, vis + n + 1, 0);
25 reverse(all(out));
26 for (auto v : out) if (!vis[v]) {
27     c.clear();
28     dfs_rev(v);
29     scc.pb(c);
30 }
31 }

```

5.12 MCMF.cpp

```

1  template<typename T>
2  struct MinCostGraph {
3      static const int V = 20100;
4      static const int E = 201000;
5      int s, t, vtot;
6      int head[V], etot;
7      T dis[V], flow, cost;
8      int pre[V];
9      bool vis[V];
10
11     struct edge {
12         int v, nxt;
13         T f, c;
14     } e[E * 2];
15     void addedge(int u, int v, T f, T c, T f2 = 0) {
16         e[etot] = {v, head[u], f, c}; head[u] = etot++;
17         e[etot] = {u, head[v], f2, -c}; head[v] = etot++;
18     }
19
20     bool spfa() {
21         T inf = numeric_limits<T>::max() / 2;
22         for (int i = 1; i <= vtot; i++) {
23             dis[i] = inf;
24             vis[i] = false;
25             pre[i] = -1;
26         }

```

```

27         dis[s] = 0;
28         vis[s] = true;
29         queue<int> q;
30         q.push(s);
31         while (!q.empty()) {
32             int u = q.front();
33             for (int i = head[u]; ~i; i = e[i].nxt) {
34                 int v = e[i].v;
35                 if (e[i].f && dis[v] > dis[u] + e[i].c) {
36                     dis[v] = dis[u] + e[i].c;
37                     pre[v] = i;
38                     if (!vis[v]) {
39                         vis[v] = 1;
40                         q.push(v);
41                     }
42                 }
43             }
44             q.pop();
45             vis[u] = false;
46         }
47         return dis[t] != inf;
48     }
49
50     void augment() {
51         int u = t;
52         T f = numeric_limits<T>::max();
53         while (~pre[u]) {
54             f = min(f, e[pre[u]].f);
55             u = e[pre[u] ^ 1].v;
56         }
57         flow += f;
58         cost += f * dis[t];
59         u = t;
60         while (~pre[u]) {
61             e[pre[u]].f -= f;
62             e[pre[u] ^ 1].f += f;
63             u = e[pre[u] ^ 1].v;
64         }
65     }
66
67     pair<T, T> solve() {
68         flow = 0;

```

```

69     cost = 0;
70     while (spfa()) augment();
71     return {flow, cost};
72 }
73 void init(int s_, int t_, int vtot_) {
74     s = s_;
75     t = t_;
76     vtot = vtot_;
77     etot = 0;
78     for (int i = 1; i <= vtot; i++) head[i] = -1;
79 }
80 };

```

5.13 MCMFfast.cpp

```

1  template <typename flow_t = int, typename cost_t = long long>
2  struct MCMF_SSPA {
3      int N;
4      vector<vector<int>>> adj;
5      struct edge_t {
6          int dest;
7          flow_t cap;
8          cost_t cost;
9      };
10     vector<edge_t> edges;
11
12     vector<char> seen;
13     vector<cost_t> pi;
14     vector<int> prv;
15
16     explicit MCMF_SSPA(int N_) : N(N_), adj(N), pi(N, 0), prv(N) {}
17
18     void addEdge(int from, int to, flow_t cap, cost_t cost) {
19         assert(cap >= 0);
20         int e = int(edges.size());
21         edges.emplace_back(edge_t{to, cap, cost});
22         edges.emplace_back(edge_t{from, 0, -cost});
23         adj[from].push_back(e);
24         adj[to].push_back(e+1);
25     }
26

```

```

27     const cost_t INF_COST = numeric_limits<cost_t>::max() / 4;
28     const flow_t INF_FLOW = numeric_limits<flow_t>::max() / 4;
29     vector<cost_t> dist;
30     __gnu_pbds::priority_queue<pair<cost_t, int>> q;
31     vector<typename decltype(q)::point_iterator> its;
32     void path(int s) {
33         dist.assign(N, INF_COST);
34         dist[s] = 0;
35
36         its.assign(N, q.end());
37         its[s] = q.push({0, s});
38
39         while (!q.empty()) {
40             int i = q.top().second; q.pop();
41             cost_t d = dist[i];
42             for (int e : adj[i]) {
43                 if (edges[e].cap) {
44                     int j = edges[e].dest;
45                     cost_t nd = d + edges[e].cost;
46                     if (nd < dist[j]) {
47                         dist[j] = nd;
48                         prv[j] = e;
49                         if (its[j] == q.end()) {
50                             its[j] = q.push({-(dist[j] - pi[j]), j});
51                         } else {
52                             q.modify(its[j], {-(dist[j] - pi[j]), j});
53                         }
54                     }
55                 }
56             }
57         }
58
59         swap(pi, dist);
60     }
61
62     vector<pair<flow_t, cost_t>> maxflow(int s, int t) {
63         assert(s != t);
64         flow_t totFlow = 0; cost_t totCost = 0;
65         vector<pair<flow_t, cost_t>> res;
66         while (path(s), pi[t] < INF_COST) {
67             flow_t curFlow = numeric_limits<flow_t>::max();
68             for (int cur = t; cur != s; ) {

```

```

69         int e = prv[cur];
70         int nxt = edges[e^1].dest;
71         curFlow = min(curFlow, edges[e].cap);
72         cur = nxt;
73     }
74     totFlow += curFlow;
75     totCost += pi[t] * curFlow;
76     for (int cur = t; cur != s; ) {
77         int e = prv[cur];
78         int nxt = edges[e^1].dest;
79         edges[e].cap -= curFlow;
80         edges[e^1].cap += curFlow;
81         cur = nxt;
82     }
83
84     res.emplace_back(totFlow, totCost);
85 }
86 return res;
87 }
88 };

```

5.14 MCMFfull.cpp

```

1  template <typename T, typename C>
2  class MCMF {
3  public:
4      static constexpr T eps = (T) 1e-9;
5
6      struct edge {
7          int from;
8          int to;
9          T c;
10         T f;
11         C cost;
12     };
13
14     int n;
15     vector<vector<int>>> g;
16     vector<edge> edges;
17     vector<C> d;
18     vector<C> pot;

```

```

19     __gnu_pbds::priority_queue<pair<C, int>>> q;
20     vector<typename decltype(q)::point_iterator> its;
21     vector<int> pe;
22     const C INF_C = numeric_limits<C>::max() / 2;
23
24     explicit MCMF(int n_) : n(n_), g(n), d(n), pot(n, 0), its(n), pe(n) {}
25
26     int add(int from, int to, T forward_cap, T backward_cap, C edge_cost) {
27         assert(0 <= from && from < n && 0 <= to && to < n);
28         assert(forward_cap >= 0 && backward_cap >= 0);
29         int id = static_cast<int>(edges.size());
30         g[from].push_back(id);
31         edges.push_back({from, to, forward_cap, 0, edge_cost});
32         g[to].push_back(id + 1);
33         edges.push_back({to, from, backward_cap, 0, -edge_cost});
34         return id;
35     }
36
37     void expath(int st) {
38         fill(d.begin(), d.end(), INF_C);
39         q.clear();
40         fill(its.begin(), its.end(), q.end());
41         its[st] = q.push({pot[st], st});
42         d[st] = 0;
43         while (!q.empty()) {
44             int i = q.top().second;
45             q.pop();
46             its[i] = q.end();
47             for (int id : g[i]) {
48                 const edge &e = edges[id];
49                 int j = e.to;
50                 if (e.c - e.f > eps && d[i] + e.cost < d[j]) {
51                     d[j] = d[i] + e.cost;
52                     pe[j] = id;
53                     if (its[j] == q.end()) {
54                         its[j] = q.push({pot[j] - d[j], j});
55                     } else {
56                         q.modify(its[j], {pot[j] - d[j], j});
57                     }
58                 }
59             }
60         }

```

```

61     swap(d, pot);
62 }
63
64 pair<T, C> calc(int st, int fin) { // max_flow_min_cost
65     T flow = 0;
66     C cost = 0;
67     bool ok = true;
68     for (auto& e : edges) {
69         if (e.c - e.f > eps && e.cost + pot[e.from] - pot[e.to] < 0) {
70             ok = false;
71             break;
72         }
73     }
74     if (ok) {
75         expath(st);
76     } else {
77         vector<int> deg(n, 0);
78         for (int i = 0; i < n; i++) {
79             for (int eid : g[i]) {
80                 auto& e = edges[eid];
81                 if (e.c - e.f > eps) {
82                     deg[e.to] += 1;
83                 }
84             }
85         }
86         vector<int> que;
87         for (int i = 0; i < n; i++) {
88             if (deg[i] == 0) {
89                 que.push_back(i);
90             }
91         }
92         for (int b = 0; b < (int) que.size(); b++) {
93             for (int eid : g[que[b]]) {
94                 auto& e = edges[eid];
95                 if (e.c - e.f > eps) {
96                     deg[e.to] -= 1;
97                     if (deg[e.to] == 0) {
98                         que.push_back(e.to);
99                     }
100                 }
101             }
102         }

```

```

103     fill(pot.begin(), pot.end(), INF_C);
104     pot[st] = 0;
105     if (static_cast<int>(que.size()) == n) {
106         for (int v : que) {
107             if (pot[v] < INF_C) {
108                 for (int eid : g[v]) {
109                     auto& e = edges[eid];
110                     if (e.c - e.f > eps) {
111                         if (pot[v] + e.cost < pot[e.to]) {
112                             pot[e.to] = pot[v] + e.cost;
113                             pe[e.to] = eid;
114                         }
115                     }
116                 }
117             }
118         }
119     } else {
120         que.assign(1, st);
121         vector<bool> in_queue(n, false);
122         in_queue[st] = true;
123         for (int b = 0; b < (int) que.size(); b++) {
124             int i = que[b];
125             in_queue[i] = false;
126             for (int id : g[i]) {
127                 const edge &e = edges[id];
128                 if (e.c - e.f > eps && pot[i] + e.cost < pot[e.to]) {
129                     pot[e.to] = pot[i] + e.cost;
130                     pe[e.to] = id;
131                     if (!in_queue[e.to]) {
132                         que.push_back(e.to);
133                         in_queue[e.to] = true;
134                     }
135                 }
136             }
137         }
138     }
139 }
140 // debug(pot[fin]);
141 while (pot[fin] < INF_C) { // < 0
142     T push = numeric_limits<T>::max();
143     int v = fin;
144     while (v != st) {

```

```

145     const edge &e = edges[pe[v]];
146     push = min(push, e.c - e.f);
147     v = e.from;
148 }
149 v = fin;
150 while (v != st) {
151     edge &e = edges[pe[v]];
152     e.f += push;
153     edge &back = edges[pe[v] ^ 1];
154     back.f -= push;
155     v = e.from;
156 }
157 flow += push;
158 cost += push * pot[fin];
159 expath(st);
160 }
161 return {flow, cost};
162 }
163 };

```

5.15 prim.cpp

```

1 vector<PII> e[N];
2
3 template <typename T>
4 void add(int u, int v, T w) {
5     e[u].eb(v, w);
6 }
7
8 template <typename T>
9 T prim(vector<pair<int, T>> *g, int start) {
10     const T inf = numeric_limits<T>::max() / 4;
11     T res = 0;
12     vector<T> dist(n, inf);
13     dist[start] = 0;
14     priority_queue<pair<T, int>, vector<pair<T, int>>, greater<pair<T,
        int>>> s;
15     s.emplace(dist[start], start);
16     vector<int> was(n, 0);
17     while (!s.empty()) {
18         T expected = s.top().first;

```

```

19         int i = s.top().second;
20         s.pop();
21         if (dist[i] != expected || was[i]) {
22             continue;
23         }
24         was[i] = 1;
25         res += expected;
26         for (auto [to, cost] : g[i]) {
27             if (cost < dist[to]) {
28                 dist[to] = cost;
29                 s.emplace(dist[to], to);
30             }
31         }
32     }
33     return res;
34 }

```

5.16 PushRelabel.cpp

```

1 /**
2  * Author: Simon Lindholm
3  * Date: 2015-02-24
4  * License: CC0
5  * Source: Wikipedia, tinyKACTL
6  * Description: Push-relabel using the highest label selection rule and
        the gap heuristic. Quite fast in practice.
7  * To obtain the actual flow, look at positive values only.
8  * Time:  $O(V^2\sqrt{E})$ 
9  * Status: Tested on Kattis and SPOJ, and stress-tested
10 */
11 #pragma once
12
13 struct PushRelabel {
14     typedef vector<int> vi;
15     struct Edge {
16         int dest, back;
17         ll f, c;
18     };
19     vector<vector<Edge>> g;
20     vector<ll> ec;
21     vector<Edge*> cur;

```

```

22     vector<vi> hs; vi H;
23     PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}
24
25     void addEdge(int s, int t, ll cap, ll rcap=0) {
26         if (s == t) return;
27         g[s].push_back({t, SZ(g[t]), 0, cap});
28         g[t].push_back({s, SZ(g[s])-1, 0, rcap});
29     }
30
31     void addFlow(Edge& e, ll f) {
32         Edge &back = g[e.dest][e.back];
33         if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
34         e.f += f; e.c -= f; ec[e.dest] += f;
35         back.f -= f; back.c += f; ec[back.dest] -= f;
36     }
37     ll calc(int s, int t) {
38         int v = SZ(g); H[s] = v; ec[t] = 1;
39         vi co(2*v); co[0] = v-1;
40         rep(i,0,v-1) cur[i] = g[i].data();
41         for (Edge& e : g[s]) addFlow(e, e.c);
42
43         for (int hi = 0;;) {
44             while (hs[hi].empty()) if (!hi--) return -ec[s];
45             int u = hs[hi].back(); hs[hi].pop_back();
46             while (ec[u] > 0) // discharge u
47                 if (cur[u] == g[u].data() + SZ(g[u])) {
48                     H[u] = 1e9;
49                     for (Edge& e : g[u]) if (e.c && H[
50                         u] > H[e.dest]+1)
51                         H[u] = H[e.dest]+1, cur[u]
52                             = &e;
53                     if (++co[H[u]], !--co[hi] && hi <
54                         v)
55                         rep(i,0,v-1) if (hi < H[i]
56                             && H[i] < v)
57                             --co[H[i]], H[i] =
58                                 v + 1;
59                     hi = H[u];
60                 } else if (cur[u]->c && H[u] == H[cur[u]->
61                     dest]+1)
62                     addFlow(*cur[u], min(ec[u], cur[u]
63                         ]->c));

```

```

57         else ++cur[u];
58     }
59 }
60 bool leftOfMinCut(int a) { return H[a] >= SZ(g); }
61 };

```

5.17 tarjan 割点.cpp

```

1     vector<int> g[maxn], ans;
2     stack<int> stk;
3     int dfn[maxn], cut[maxn], low[maxn], idx;
4
5     void dfs(int x, int f) {
6         low[x] = dfn[x] = ++idx;
7         stk.push(x);
8         int ch = 0;
9         for (auto y : g[x]) {
10             if (!dfn[y]) {
11                 ch++;
12                 dfs(y, x);
13                 low[x] = min(low[x], low[y]);
14                 if (low[y] >= dfn[x]) cut[x] = 1;
15             } else {
16                 if (y != f) low[x] = min(low[x], dfn[y]);
17             }
18         }
19         if (x == 1 && ch <= 1) cut[x] = 0;
20         if (cut[x]) ans.pb(x);
21     }

```

5.18 tarjan 割边.cpp

```

1     vector<PII> g[maxn];
2     stack<int> stk;
3     int dfn[maxn], ins[maxn], low[maxn];
4     int idx, tot;
5     VI ans;
6     void dfs(int x, int f) {
7         low[x] = dfn[x] = ++idx;
8         stk.push(x);
9         ins[x] = 1;

```

```

10     for (auto [y, id] : g[x]) {
11         if (!dfn[y]) {
12             dfs(y, id);
13             low[x] = min(low[x], low[y]);
14         } else {
15             if (ins[y] && id != f) low[x] = min(low[x], dfn[y]);
16         }
17     }
18     if (low[x] >= dfn[x]) {
19         ++tot;
20         while (true) {
21             int cur = stk.top();
22             stk.pop();
23             ins[cur] = 0;
24             if (cur == x) break;
25         }
26         if (f != 0) ans.pb(f);
27     }
28 }

```

5.19 tarjan 强连通分量.cpp

```

1 vector<int> g[maxn];
2 stack<int> stk;
3 int dfn[maxn], ins[maxn], low[maxn], belong[maxn];
4 int idx, tot;
5
6 void dfs(int x) {
7     low[x] = dfn[x] = ++idx;
8     ins[x] = 1;
9     stk.push(x);
10    for (auto y : g[x]) {
11        if (!dfn[y]) {
12            dfs(y);
13            low[x] = min(low[x], low[y]);
14        } else {
15            if (ins[y]) low[x] = min(low[x], dfn[y]);
16        }
17    }
18    if (low[x] >= dfn[x]) {
19        ++tot;

```

```

20        while (true) {
21            int cur = stk.top(); stk.pop();
22            ins[cur] = 0;
23            belong[cur] = tot;
24            if (cur == x) break;
25        }
26    }
27 }

```

5.20 tarjan 点双.cpp

```

1 vector<int> g[maxn];
2 stack<int> stk;
3 int dfn[maxn], low[maxn], idx, tot, cut[maxn];
4 vector<int> bcc[maxn];
5
6 void dfs(int x, int f) {
7     low[x] = dfn[x] = ++idx;
8     stk.push(x);
9     int ch = 0;
10    for (auto y : g[x]) {
11        if (!dfn[y]) {
12            ch++;
13            dfs(y, x);
14            low[x] = min(low[x], low[y]);
15            if (low[y] >= dfn[x]) {
16                cut[x] = 1;
17                ++tot;
18                bcc[tot].pb(x);
19                while (true) {
20                    int cur = stk.top();
21                    stk.pop();
22                    bcc[tot].pb(cur);
23                    if (cur == y) break;
24                }
25            }
26        } else {
27            if (y != f) low[x] = min(low[x], dfn[y]);
28        }
29    }
30    if (x == 1 && ch <= 1) cut[x] = 0;

```



```
31 }
```

5.21 tarjan 边双.cpp

```
1 vector<PII> g[maxn];
2 stack<int> stk;
3 int dfn[maxn], low[maxn], idx, tot, belong[maxn];
4 vector<int> bcc[maxn];
5
6 void dfs(int x, int f) {
7     low[x] = dfn[x] = ++idx;
8     stk.push(x);
9     for (auto [y, id] : g[x]) {
10         if (!dfn[y]) {
11             dfs(y, id);
12             low[x] = min(low[x], low[y]);
13         } else {
14             if (id != f) low[x] = min(low[x], dfn[y]);
15         }
16     }
17     if (low[x] >= dfn[x]) {
18         ++tot;
19         while (true) {
20             int cur = stk.top();
21             stk.pop();
22             belong[cur] = tot;
23             bcc[tot].pb(cur);
24             if (cur == x) break;
25         }
26     }
27 }
```

5.22 twosat.cpp

```
1 class twosat {
2 public:
3     digraph<int> g;
4     int n;
5
6     twosat(int _n) : g(digraph<int>(2 * _n)), n(_n) {
7     }
```

```
8
```

```
9
```

```
// (v[x] == value_x)
```

```
10
```

```
inline void add(int x, int value_x) {
```

```
11
```

```
    assert(0 <= x && x < n);
```

```
12
```

```
    assert(0 <= value_x && value_x <= 1);
```

```
13
```

```
    g.add(2 * x + (value_x ^ 1), 2 * x + value_x);
```

```
14
```

```
}
```

```
15
```

```
// (v[x] == value_x || v[y] == value_y)
```

```
16
```

```
inline void add(int x, int value_x, int y, int value_y) {
```

```
17
```

```
    assert(0 <= x && x < n && 0 <= y && y < n);
```

```
18
```

```
    assert(0 <= value_x && value_x <= 1 && 0 <= value_y &&
```

```
19
```

```
        value_y <= 1);
```

```
20
```

```
    g.add(2 * x + (value_x ^ 1), 2 * y + value_y);
```

```
21
```

```
    g.add(2 * y + (value_y ^ 1), 2 * x + value_x);
```

```
22
```

```
}
```

```
23
```

```
inline vector<int> solve() {
```

```
24
```

```
    int cnt;
```

```
25
```

```
    vector<int> c = find_scc(g, cnt);
```

```
26
```

```
    vector<int> res(n);
```

```
27
```

```
    for (int i = 0; i < n; i++) {
```

```
28
```

```
        if (c[2 * i] == c[2 * i + 1]) {
```

```
29
```

```
            return vector<int>();
```

```
30
```

```
        }
```

```
31
```

```
        res[i] = (c[2 * i] < c[2 * i + 1]);
```

```
32
```

```
    }
```

```
33
```

```
    return res;
```

```
34
```

```
}
```

```
35
```

```
36 };
```

5.23 差分约束系统.cpp

```
1 /**
```

```
2
```

```
Description:
```

```
3
```

```
求解方程组  $x_u - x_v \leq w_i$ , 求出的  $x_i$  为满足条件的最大值
```

```
4
```

```
转化为  $x_u \leq x_v + w_i$ 
```

```
5
```

```
问题等价于求最短路 (bellmanford或Floyd)
```

```
6
```

```
即加一条有向边  $add(u, v, w)$ ,  $dist[v] = \min(dist[v], dist[u] + w)$ 
```

```
7
```

```
求最小值 (满足条件情况下尽量小) 等价于求  $(-x_i)$  最大 (或者转化为求最  
长路)
```

```

8      求非负解只需要添加超级节点 $S$ ,  $S$ 向各个点连边 ( $S + 0 \leq x_i$ ), 再设
       $dist[S] = 0$ 
9      */
10     void solve() {
11         cin >> n >> m;
12         vector<int> dist(n, 0);
13         vector<vector<PII>> g(n);
14         rep(i, 0, m - 1) {
15             int u, v, w;
16             cin >> u >> v >> w;
17             u--, v--;
18             g[u].eb(v, -w);
19         }
20         bool ok = 1;
21         rep(i, 1, n) {
22             bool upd = 0;
23             rep(u, 0, n - 1) {
24                 for (auto [v, w] : g[u]) {
25                     if (dist[v] < dist[u] + w) {
26                         dist[v] = dist[u] + w;
27                         upd = 1;
28                     }
29                 }
30             }
31             if (!upd) break;
32             // 仍然有约束未满足
33             if (i == n && upd) ok = 0;
34         }
35         if (!ok) {
36             return cout << -1 << '\n', void();
37         }
38         rep(i, 0, n - 1) {
39             cout << dist[i] << "□\n"[i == n - 1];
40         }
41     }

```

6 Math

6.1 binom.cpp

```

1 vector<Mint> fact(1, 1);

```

```

2 vector<Mint> inv_fact(1, 1);
3
4 Mint C(int n, int k) {
5     if (k < 0 || k > n) {
6         return 0;
7     }
8     while ((int)fact.size() < n + 1) {
9         fact.push_back(fact.back() * (int)fact.size());
10        inv_fact.push_back(1 / fact.back());
11    }
12    return fact[n] * inv_fact[k] * inv_fact[n - k];
13 }
14
15 const int mod = 1000000007;
16 const int T = 1000000;
17 ll fact[] = {};
18 ll powmod(ll a, ll b) {
19     ll ret = 1;
20     for (; b; b >>= 1) {
21         if (b & 1) ret = ret * a % mod;
22         a = a * a % mod;
23     }
24     return ret;
25 }
26 ll fac(int n) {
27     ll v = fact[n / T];
28     for (int i = n / T * T + 1; i <= n; i++)
29         v = v * i % mod;
30     return v;
31 }
32 ll binom(int n, int m) {
33     if (m < 0 || m > n) return 0;
34     return fac(n) * powmod(fac(m) * fac(n - m) % mod, mod - 2) % mod;
35 }

```

6.2 bsgs.cpp

```

1 int bsgs(int a, int b, int m) { //  $a^x \equiv b \pmod m$ 
2     int res = m + 1;
3     int t = sqrt(m) + 2;
4     ll d = powmod(a, t, m);

```

```

5     ll cnt = 1;
6     //map<int,int> p;
7     hs.init();
8     for (int i = 1; i <= t; i++) {
9         cnt = cnt * d % m;
10        //if (!p.count(cnt)) p[cnt] = i;
11        if (hs.query(cnt) == -1) hs.insert(cnt, i);
12    }
13    cnt = b;
14    for (int i = 1; i <= t; i++) {
15        cnt = cnt * a % m;
16        //if (p.count(cnt)) res = min(res, p[cnt] * t - i);
17        int tmp = hs.query(cnt);
18        if (tmp != -1) res = min(res, tmp * t - i);
19    }
20    if (res >= m) res = -1;
21    return res;
22 }

```

6.3 cantor.cpp

```

1  ll fac[maxn], A[maxn], w[maxn];
2  void init(int n) {
3      fac[0] = 1;
4      rep(i, 1, n) fac[i] = fac[i - 1] * i % mod;
5  }
6  ll cantor(int w[], int n) {
7      ll ans = 1;
8      for (int i = 1; i <= n; i++) { // can optimize by BIT
9          for (int j = i + 1; j <= n; j++) {
10             if (w[i] > w[j]) A[i]++;
11          }
12      }
13      for (int i = 1; i < n; i++) {
14          ans += A[i] * fac[n - i];
15      }
16      return ans;
17  }
18
19  void decanter(ll x, int n) { // x->rank n->length
20      x--;

```

```

21     vector<int> rest(n, 0);
22     iota(rest.begin(), rest.end(), 1); // rest->1,2,3,4...
23     for (int i = 1; i <= n; i++) {
24         A[i] = x / fac[n - i];
25         x %= fac[n - i];
26     }
27     for (int i = 1; i <= n; i++) {
28         w[i] = rest[A[i]];
29         rest.erase(lower_bound(rest.begin(), rest.end(), w[i]));
30     }
31 }

```

6.4 EXCRT modequ exgcd.cpp

```

1  ll exgcd(ll a, ll b, ll &x, ll &y) {
2      if (b == 0) {
3          x = 1, y = 0;
4          return a;
5      }
6      ll d = exgcd(b, a % b, y, x);
7      y -= (a / b) * x;
8      return d;
9  }
10
11 // 求  $a * x = b \pmod m$  的解
12 ll modequ(ll a, ll b, ll m) {
13     ll x, y;
14     ll d = exgcd(a, m, x, y);
15     if (b % d != 0) return -1;
16     m /= d; a /= d; b /= d;
17     x = x * b % m;
18     if (x < 0) x += m;
19     return x;
20 }
21
22 void merge(ll &a, ll &b, ll c, ll d) {
23     if (a == -1 || b == -1) return;
24     ll x, y;
25     ll g = exgcd(b, d, x, y);
26     if ((c - a) % g != 0) {
27         a = -1, b = -1;

```

```

28     return;
29 }
30 d /= g;
31 ll t = ((c - a) / g) % d * x % d;
32 if (t < 0) t += d;
33 a = b * t + a;
34 b = b * d;
35 }

```

6.5 factor.cpp

```

1 namespace Factor {
2     const int N=1010000;
3     ll C,fac[10010],n,mul,a[1001000];
4     int T,cnt,i,l,prime[N],p[N],psize,_cnt;
5     ll _e[100],_pr[100];
6     vector<ll> d;
7     inline ll mul(ll a,ll b,ll p) {
8         if (p<=10000000000) return a*b%p;
9         else if (p<=100000000000011) return (((a*(b>>20)%p)<<20)+(a*(b
10             &((1<<20)-1))))%p;
11         else {
12             ll d=(ll)floor(a*(long double)b/p+0.5);
13             ll ret=(a*b-d*p)%p;
14             if (ret<0) ret+=p;
15             return ret;
16         }
17     }
18     void prime_table(){
19         int i,j,tot,t1;
20         for (i=1;i<=psize;i++) p[i]=i;
21         for (i=2,tot=0;i<=psize;i++){
22             if (p[i]==i) prime[++tot]=i;
23             for (j=1;j<=tot && (t1=prime[j]*i)<=psize;j++){
24                 p[t1]=prime[j];
25                 if (i%prime[j]==0) break;
26             }
27         }
28     void init(int ps) {
29         psize=ps;

```

```

30     prime_table();
31 }
32 ll powl(ll a,ll n,ll p) {
33     ll ans=1;
34     for (;n;n>>=1) {
35         if (n&1) ans=mul(ans,a,p);
36         a=mul(a,a,p);
37     }
38     return ans;
39 }
40 bool witness(ll a,ll n) {
41     int t=0;
42     ll u=n-1;
43     for (;~u&1;u>>=1) t++;
44     ll x=powl(a,u,n),_x=0;
45     for (;t;t--) {
46         _x=mul(x,x,n);
47         if (_x==1 && x!=1 && x!=n-1) return 1;
48         x=_x;
49     }
50     return _x!=1;
51 }
52 bool miller(ll n) {
53     if (n<2) return 0;
54     if (n<=psize) return p[n]==n;
55     if (~n&1) return 0;
56     for (int j=0;j<=7;j++) if (witness(rng()%(n-1)+1,n)) return 0;
57     return 1;
58 }
59 ll gcd(ll a,ll b) {
60     ll ret=1;
61     while (a!=0) {
62         if ((~a&1) && (~b&1)) ret<=<=1,a>>=1,b>>=1;
63         else if (~a&1) a>>=1; else if (~b&1) b>>=1;
64         else {
65             if (a<b) swap(a,b);
66             a-=b;
67         }
68     }
69     return ret*b;
70 }
71 ll rho(ll n) {

```

```

72     while (1) {
73         ll X=rng()%n,Y,Z,T=1,*lY=a,*lX=lY;
74         int tmp=20;
75         C=rng()%10+3;
76         X=mul(X,X,n)+C;*(lY++)=X;lX++;
77         Y=mul(X,X,n)+C;*(lY++)=Y;
78         for(;X!=Y;) {
79             ll t=X-Y+n;
80             Z=mul(T,t,n);
81             if(Z==0) return gcd(T,n);
82             tmp--;
83             if (tmp==0) {
84                 tmp=20;
85                 Z=gcd(Z,n);
86                 if (Z!=1 && Z!=n) return Z;
87             }
88             T=Z;
89             Y=*(lY++)=mul(Y,Y,n)+C;
90             Y=*(lY++)=mul(Y,Y,n)+C;
91             X=*(lX++);
92         }
93     }
94 }
95 void _factor(ll n) {
96     for (int i=0;i<cnt;i++) {
97         if (n%fac[i]==0) n/=fac[i],fac[cnt++]=fac[i];}
98     if (n<=psize) {
99         for (;n!=1;n/=p[n]) fac[cnt++]=p[n];
100        return;
101    }
102    if (miller(n)) fac[cnt++]=n;
103    else {
104        ll x=rho(n);
105        _factor(x);_factor(n/x);
106    }
107 }
108 void dfs(ll x,int dep) {
109     if (dep==_cnt) d.pb(x);
110     else {
111         dfs(x,dep+1);
112         for (int i=1;i<=_e[dep];i++) dfs(x*_pr[dep],dep+1);
113     }

```

```

114 }
115 void norm() {
116     sort(fac,fac+cnt);
117     _cnt=0;
118     rep(i,0,cnt-1) if (i==0||fac[i]!=fac[i-1]) _pr[_cnt]=fac[i],_e[
119         _cnt++]=1;
120         else _e[_cnt-1]++;
121 }
122 vector<ll> getd() {
123     d.clear();
124     dfs(1,0);
125     return d;
126 }
127 vector<ll> factor(ll n) {
128     cnt=0;
129     _factor(n);
130     norm();
131     return getd();
132 }
133 vector<PLL> factorG(ll n) {
134     cnt=0;
135     _factor(n);
136     norm();
137     vector<PLL> d;
138     rep(i,0,_cnt-1) d.pb(mp(_pr[i],_e[i]));
139     return d;
140 }
141 bool is_primitive(ll a,ll p) {
142     assert(miller(p));
143     vector<PLL> D=factorG(p-1);
144     rep(i,0,SZ(D)-1) if (powl(a,(p-1)/D[i].fi,p)==1) return 0;
145     return 1;
146 }
147 ll phi(ll n) {
148     auto d=factorG(n);
149     for (auto p:d) n=n/p.fi*(p.fi-1);
150     return n;
151 }

```

6.6 fft.cpp

```
1 namespace fft {
2     typedef double dbl;
3
4     struct num {
5         dbl x, y;
6         num() { x = y = 0; }
7         num(dbl x, dbl y) : x(x), y(y) { }
8     };
9
10    inline num operator+(num a, num b) { return num(a.x + b.x, a.y + b.y); }
11    inline num operator-(num a, num b) { return num(a.x - b.x, a.y - b.y); }
12    inline num operator*(num a, num b) { return num(a.x * b.x - a.y * b.y, a
        .x * b.y + a.y * b.x); }
13    inline num conj(num a) { return num(a.x, -a.y); }
14
15    int base = 1;
16    vector<num> roots = {{0, 0}, {1, 0}};
17    vector<int> rev = {0, 1};
18
19    const dbl PI = acos(-1.0);
20
21    void ensure_base(int nbase) {
22        if (nbase <= base) {
23            return;
24        }
25        rev.resize(1 << nbase);
26        for (int i = 0; i < (1 << nbase); i++) {
27            rev[i] = (rev[i >> 1] >> 1) + ((i & 1) << (nbase - 1));
28        }
29        roots.resize(1 << nbase);
30        while (base < nbase) {
31            dbl angle = 2 * PI / (1 << (base + 1));
32            // num z(cos(angle), sin(angle));
33            for (int i = 1 << (base - 1); i < (1 << base); i++) {
34                roots[i << 1] = roots[i];
35                // roots[(i << 1) + 1] = roots[i] * z;
36                dbl angle_i = angle * (2 * i + 1 - (1 << base));
37                roots[(i << 1) + 1] = num(cos(angle_i), sin(angle_i));
38            }
39            base++;
```

```
40        }
41    }
42
43    void fft(vector<num> &a, int n = -1) {
44        if (n == -1) {
45            n = a.size();
46        }
47        assert((n & (n - 1)) == 0);
48        int zeros = __builtin_ctz(n);
49        ensure_base(zeros);
50        int shift = base - zeros;
51        for (int i = 0; i < n; i++) {
52            if (i < (rev[i] >> shift)) {
53                swap(a[i], a[rev[i] >> shift]);
54            }
55        }
56        /* for (int k = 1; k < n; k <= 1) {
57            for (int i = 0; i < n; i += 2 * k) {
58                for (int j = 0; j < k; j++) {
59                    num z = a[i + j + k] * roots[j + k];
60                    a[i + j + k] = a[i + j] - z;
61                    a[i + j] = a[i + j] + z;
62                }
63            }
64        }*/
65        for (int len = 1; len < n; len <= 1) {
66            for (int i = 0; i < n; i += 2 * len) {
67                for (int j = i, k = i + len; j < i + len; j++, k++) {
68                    num z = a[k] * roots[k - i];
69                    a[k] = a[j] - z;
70                    a[j] = a[j] + z;
71                }
72            }
73        }
74    }
75
76    vector<num> fa, fb;
77
78    vector<long long> multiply(vector<int> &a, vector<int> &b) {
79        int need = a.size() + b.size() - 1;
80        int nbase = 0;
81        while ((1 << nbase) < need) nbase++;
```

```

82     ensure_base(nbase);
83     int sz = 1 << nbase;
84     if (sz > (int) fa.size()) {
85         fa.resize(sz);
86     }
87     for (int i = 0; i < sz; i++) {
88         int x = (i < (int) a.size() ? a[i] : 0);
89         int y = (i < (int) b.size() ? b[i] : 0);
90         fa[i] = num(x, y);
91     }
92     fft(fa, sz);
93     num r(0, -0.25 / sz);
94     for (int i = 0; i <= (sz >> 1); i++) {
95         int j = (sz - i) & (sz - 1);
96         num z = (fa[j] * fa[j] - conj(fa[i] * fa[i])) * r;
97         if (i != j) {
98             fa[j] = (fa[i] * fa[i] - conj(fa[j] * fa[j])) * r;
99         }
100        fa[i] = z;
101    }
102    fft(fa, sz);
103    vector<long long> res(need);
104    for (int i = 0; i < need; i++) {
105        res[i] = fa[i].x + 0.5;
106    }
107    return res;
108 }
109
110 vector<int> multiply_mod(vector<int> &a, vector<int> &b, int m, int eq =
111     0) {
112     int need = a.size() + b.size() - 1;
113     int nbase = 0;
114     while ((1 << nbase) < need) nbase++;
115     ensure_base(nbase);
116     int sz = 1 << nbase;
117     if (sz > (int) fa.size()) {
118         fa.resize(sz);
119     }
120     for (int i = 0; i < (int) a.size(); i++) {
121         int x = (a[i] % m + m) % m;
122         fa[i] = num(x & ((1 << 15) - 1), x >> 15);
123     }

```

```

123     fill(fa.begin() + a.size(), fa.begin() + sz, num {0, 0});
124     fft(fa, sz);
125     if (eq) {
126         copy(fa.begin(), fa.begin() + sz, fb.begin());
127     } else {
128         if (sz > (int) fb.size()) {
129             fb.resize(sz);
130         }
131         for (int i = 0; i < (int) b.size(); i++) {
132             int x = (b[i] % m + m) % m;
133             fb[i] = num(x & ((1 << 15) - 1), x >> 15);
134         }
135         fill(fb.begin() + b.size(), fb.begin() + sz, num {0, 0});
136         fft(fb, sz);
137     }
138     dbl ratio = 0.25 / sz;
139     num r2(0, -1);
140     num r3(ratio, 0);
141     num r4(0, -ratio);
142     num r5(0, 1);
143     for (int i = 0; i <= (sz >> 1); i++) {
144         int j = (sz - i) & (sz - 1);
145         num a1 = (fa[i] + conj(fa[j]));
146         num a2 = (fa[i] - conj(fa[j])) * r2;
147         num b1 = (fb[i] + conj(fb[j])) * r3;
148         num b2 = (fb[i] - conj(fb[j])) * r4;
149         if (i != j) {
150             num c1 = (fa[j] + conj(fa[i]));
151             num c2 = (fa[j] - conj(fa[i])) * r2;
152             num d1 = (fb[j] + conj(fb[i])) * r3;
153             num d2 = (fb[j] - conj(fb[i])) * r4;
154             fa[i] = c1 * d1 + c2 * d2 * r5;
155             fb[i] = c1 * d2 + c2 * d1;
156         }
157         fa[j] = a1 * b1 + a2 * b2 * r5;
158         fb[j] = a1 * b2 + a2 * b1;
159     }
160     fft(fa, sz);
161     fft(fb, sz);
162     vector<int> res(need);
163     for (int i = 0; i < need; i++) {
164         long long aa = fa[i].x + 0.5;

```

```

165     long long bb = fb[i].x + 0.5;
166     long long cc = fa[i].y + 0.5;
167     res[i] = (aa + ((bb % m) << 15) + ((cc % m) << 30)) % m;
168 }
169 return res;
170 }
171
172 vector<int> square_mod(vector<int> &a, int m) {
173     return multiply_mod(a, a, m, 1);
174 }
175 // fft::multiply uses dbl, outputs vector<long long> of rounded values
176 // fft::multiply_mod might work for res.size() up to 2^21
177 // typedef long double dbl;          =>          up to 2^25 (but takes a
        lot of memory)
178 };

```

6.7 fftfast.cpp

```

1 // FFT_MAXN = 2^k
2 // fft_init() to precalc FFT_MAXN-th roots
3
4 typedef long double db;
5 const int FFT_MAXN = 262144;
6 const int N = 3.1e5;
7 const db pi = acosl(-1.);
8 struct cp {
9     db a, b;
10     cp operator+(const cp &y) const { return (cp){a + y.a, b + y.b}; }
11     cp operator-(const cp &y) const { return (cp){a - y.a, b - y.b}; }
12     cp operator*(const cp &y) const { return (cp){a * y.a - b * y.b, a
        * y.b + b * y.a}; }
13     cp operator!() const { return (cp){a, -b}; };
14 } nw[FFT_MAXN + 1];
15 int bitrev[FFT_MAXN];
16 void dft(cp *a, int n, int flag = 1) {
17     int d = 0;
18     while ((1 << d) * n != FFT_MAXN) d++;
19     rep(i, 0, n - 1) if (i < (bitrev[i] >> d)) swap(a[i], a[bitrev[i]
        >> d]);
20     for (int l = 2; l <= n; l <= 1) {
21         int del = FFT_MAXN / l * flag;

```

```

22         for (int i = 0; i < n; i += 1) {
23             cp *le = a + i, *ri = a + i + (l >> 1), *w = flag
                == 1 ? nw : nw + FFT_MAXN;
24             rep(k, 0, l / 2 - 1) {
25                 cp ne = *ri * *w;
26                 *ri = *le - ne, *le = *le + ne;
27                 le++, ri++, w += del;
28             }
29         }
30     }
31     if (flag != 1) rep(i, 0, n - 1) a[i].a /= n, a[i].b /= n;
32 }
33 void fft_init() {
34     int L = 0;
35     while ((1 << L) != FFT_MAXN) L++;
36     bitrev[0] = 0;
37     rep(i, 1, FFT_MAXN - 1) bitrev[i] = bitrev[i >> 1] >> 1 | ((i & 1)
        << (L - 1));
38     nw[0] = nw[FFT_MAXN] = (cp){1, 0};
39     rep(i, 0, FFT_MAXN)
40     nw[i] = (cp){cosl(2 * pi / FFT_MAXN * i), sinl(2 * pi / FFT_MAXN *
        i)}; // very slow
41 }
42
43 void convo(db *a, int n, db *b, int m, db *c) {
44     static cp f[FFT_MAXN >> 1], g[FFT_MAXN >> 1], t[FFT_MAXN >> 1];
45     int N = 2;
46     while (N <= n + m) N <= 1;
47     rep(i, 0, N - 1) if (i & 1) {
48         f[i >> 1].b = (i <= n) ? a[i] : 0.0;
49         g[i >> 1].b = (i <= m) ? b[i] : 0.0;
50     }
51     else {
52         f[i >> 1].a = (i <= n) ? a[i] : 0.0;
53         g[i >> 1].a = (i <= m) ? b[i] : 0.0;
54     }
55     dft(f, N >> 1);
56     dft(g, N >> 1);
57     int del = FFT_MAXN / (N >> 1);
58     cp qua = (cp){0, 0.25}, one = (cp){1, 0}, four = (cp){4, 0}, *w =
        nw;
59     rep(i, 0, N / 2 - 1) {

```



```

60         int j = i ? (N >> 1) - i : 0;
61         t[i] = (four * !(f[j] * g[j]) - (!f[j] - f[i]) * (!g[j] -
           g[i]) * (one + *w)) * qua;
62         w += del;
63     }
64     dft(t, N >> 1, -1);
65     rep(i, 0, n + m) c[i] = (i & 1) ? t[i >> 1].a : t[i >> 1].b;
66 }
67
68 int mo;
69 void mul(int *a, int *b, int n) { // n<=N, 0<=a[i],b[i]<mo
70     static cp f[N], g[N], t[N], r[N];
71     int nn = 2;
72     while (nn <= n + n) nn <= 1;
73     rep(i, 0, nn - 1) {
74         f[i] = (i <= n) ? (cp){(db)(a[i] >> 15), (db)(a[i] &
           32767)} : (cp){0, 0};
75         g[i] = (i <= n) ? (cp){(db)(b[i] >> 15), (db)(b[i] &
           32767)} : (cp){0, 0};
76     }
77     swap(n, nn);
78     dft(f, n, 1);
79     dft(g, n, 1);
80     rep(i, 0, n - 1) {
81         int j = i ? n - i : 0;
82         t[i] = ((f[i] + !f[j]) * (!g[j] - g[i]) + (!f[j] - f[i]) *
           (g[i] + !g[j])) * (cp){0, 0.25};
83         r[i] = (!f[j] - f[i]) * (!g[j] - g[i]) * (cp){-0.25, 0} +
           (cp){0, 0.25} * (f[i] + !f[j]) * (g[i] + !g[j]);
84     }
85     dft(t, n, -1);
86     dft(r, n, -1);
87     rep(i, 0, n - 1)
88         a[i] = ((ll(t[i].a + 0.5) % mo << 15) + ll(r[i].a + 0.5) + (ll(r[i]
           ].b + 0.5) % mo << 30)) % mo;
89 }

```

6.8 FST.cpp

```

1 void fst(VI &a, bool inv) {
2     for (int n=SZ(a), step=1; step<n; step*=2) {

```

```

3         for (int i=0; i<n; i+=2*step) rep(j, i, i+step-1) {
4             int &u=a[j], &v=a[j+step];
5             tie(u, v)=
6                 inv?PII(v-u, u):PII(v, u+v); // AND
7                 inv?PII(v, u-v):PII(u+v, u); // OR
8                 PII(u+v, u-v); // XOR
9         }
10    }
11    if (inv) for (auto &x : a) x/=SZ(a); // XOR only
12 }
13 VI conv(VI a, VI b) {
14     fst(a, 0), fst(b, 0);
15     rep(i, 0, SZ(a)-1) a[i]=a[i]*b[i];
16     fst(a, 1); return a;
17 }

```

6.9 FWT.cpp

```

1 ll f[maxn], g[maxn], h[maxn];
2 int main() {
3     for (int i = 0; i < n; i++) {
4         for (int j = 0; j < bit(n); j++) {
5             if ((j & bit(i)) == 0) {
6                 f[j] += f[j + bit(i)];
7                 g[j] += g[j + bit(i)];
8             }
9         }
10    }
11    for (int i = 0; i < bit(n); i++) {
12        f[i] %= mod;
13        g[i] %= mod;
14        h[i] = f[i] * g[i] % mod;
15    }
16    for (int i = 0; i < n; i++) {
17        for (int j = 0; j < bit(n); j++) {
18            if ((j & bit(i)) == 0)
19                h[j] -= h[j + bit(i)];
20        }
21    }
22    for (int i = 0; i < bit(n); i++) {
23        h[i] %= mod;

```

```

24         if (h[i] < 0) h[i] += mod;
25     }
26
27     ll ans = 0;
28     rep(i, 0, bit(n) - 1) ans ^= h[i];
29     cout << ans << '\n';
30 }

```

6.10 gauss(合数).cpp

```

1 void gauss(int n) {
2     int ans = 1;
3     //rep(i, 1, n) rep(j, 1, n) p[i][j] %= mod;
4     for (int i = 1; i <= n; i++) {
5         for (int j = i + 1; j <= n; j++) {
6             int x = i, y = j;
7             while (p[x][i]) {
8                 int t = p[y][i] / p[x][i];
9                 for (int k = i; k <= n; k++)
10                     p[y][k] = (p[y][k] - p[x][k] * t) % mod;
11                 swap(x, y);
12             }
13             if (x == i) {
14                 for (int k = i; k <= n; k++) swap(p[i][k], p[j][k]);
15                 ans = -ans;
16             }
17         }
18     }
19 }

```

6.11 gauss.cpp

```

1 ll f[N][N];
2 ll v[N], a[N];
3 void gauss() {
4     for (int i = 1; i <= n; i++) {
5         for (int j = i; j <= n; j++) {
6             if (f[j][i] > f[i][i]) {
7                 swap(v[i], v[j]);
8                 for (int k = 1; k <= n; k++)
9                     swap(f[j][k], f[i][k]);

```

```

10         }
11     }
12     for (int j = i + 1; j <= n; j++) {
13         if (f[j][i]) {
14             int delta = f[j][i] * fpow(f[i][i], mod - 2) % mod;
15             for (int k = i; k <= n; k++) {
16                 f[j][k] -= f[i][k] * delta % mod;
17                 if (f[j][k] < 0)
18                     f[j][k] += mod;
19             }
20             v[j] -= v[i] * delta % mod;
21             if (v[j] < mod)
22                 v[j] += mod;
23         }
24     }
25 }
26 for (int j = n; j > 0; j--) {
27     for (int k = j + 1; k <= n; k++) {
28         v[j] -= f[j][k] * a[k] % mod;
29         if (v[j] < 0)
30             v[j] += mod;
31     }
32     a[j] = v[j] * fpow(f[j][j], mod - 2) % mod;
33 }
34 }

```

6.12 linearbasis.cpp

```

1 struct linear_base {
2     ll w[64];
3     ll zero = 0;
4     ll tot = -1;
5     void clear() {
6         rep(i, 0, 63) w[i] = 0;
7         zero = 0;
8         tot = -1;
9     }
10    void insert(ll x) {
11        for (int i = 62; i >= 0; i--) {
12            if (x & bit(i))
13                if (!w[i]) {w[i] = x; return;}

```

```

14         else x ^= w[i];
15     }
16     zero++;
17 }
18 void build() {
19     rep(i, 0, 63) rep(j, 0, i - 1) {
20         if (w[i]&bit(j)) w[i] ^= w[j];
21     }
22     for (int i = 0; i <= 62; i++) {
23         if (w[i] != 0) w[++tot] = w[i];
24     }
25 }
26 ll qmax() {
27     ll res = 0;
28     for (int i = 62; i >= 0; i--) {
29         res = max(res, res ^ w[i]);
30     }
31     return res;
32 }
33 bool check(ll x) {
34     for (int i = 62; i >= 0; i--) {
35         if (x & bit(i))
36             if (!w[i]) return false;
37         else x ^= w[i];
38     }
39     return true;
40 }
41 ll query(ll k) {
42     ll res = 0;
43     // if (zero) k-=1;
44     // if (k >= bit(tot)) return -1;
45     for (int i = tot; i >= 0; i--) {
46         if (k & bit(i)) {
47             res = max(res, res ^ w[i]);
48         } else {
49             res = min(res, res ^ w[i]);
50         }
51     }
52     return res;
53 }
54 };

```

6.13 lucas.cpp

```

1 ll fac[maxn], fnv[maxn];
2
3 ll binom(ll a, ll b) {
4     if (b > a || b < 0) return 0;
5     return fac[a] * fnv[a - b] % p * fnv[b] % p;
6 }
7
8 ll lucas(ll a, ll b, ll p) {
9     ll ans = 1;
10    while (a > 0 || b > 0) {
11        ans = (ans * binom(a % p, b % p)) % p;
12        a /= p, b /= p;
13    }
14    return ans;
15 }
16
17 int main() {
18     cin >> p >> T;
19     fac[0] = 1;
20     rep(i, 1, p - 1) fac[i] = fac[i - 1] * i % p;
21     fnv[p - 1] = powmod(fac[p - 1], p - 2, p);
22     per(i, p - 2, 0) fnv[i] = fnv[i + 1] * (i + 1) % p;
23     assert(fnv[0] == 1);
24 }

```

6.14 mathdiv.cpp

```

1 ll floor_div(ll x, ll y) {
2     assert(y != 0);
3     if (y < 0) {
4         y = -y;
5         x = -x;
6     }
7     if (x >= 0) return x / y;
8     return (x + 1) / y - 1;
9 }
10 ll ceil_div(ll x, ll y) {
11     assert(y != 0);
12     if (y < 0) {
13         y = -y;

```

```

14         x = -x;
15     }
16     if (x <= 0) return x / y;
17     return (x - 1) / y + 1;
18 }

```

6.15 matrix.cpp

```

1  template <typename T>
2  vector<vector<T>> operator*(const vector<vector<T>>& a, const vector<
    vector<T>>& b) {
3      if (a.empty() || b.empty()) {
4          return {};
5      }
6      vector<vector<T>> c(a.size(), vector<T>(b[0].size()));
7      for (int i = 0; i < static_cast<int>(c.size()); i++) {
8          for (int j = 0; j < static_cast<int>(c[0].size()); j++) {
9              c[i][j] = 0;
10             for (int k = 0; k < static_cast<int>(b.size()); k
                ++){
11                 c[i][j] += a[i][k] * b[k][j];
12             }
13         }
14     }
15     return c;
16 }
17
18 template <typename T>
19 vector<vector<T>>& operator*=(vector<vector<T>>& a, const vector<vector<T
    >>& b) {
20     return a = a * b;
21 }
22
23 template <typename T, typename U>
24 vector<vector<T>> power(const vector<vector<T>>& a, const U& b) {
25     assert(b >= 0);
26     vector<U> binary;
27     U bb = b;
28     while (bb > 0) {
29         binary.push_back(bb & 1);
30         bb >>= 1;

```

```

31     }
32     vector<vector<T>> res(a.size(), vector<T>(a.size()));
33     for (int i = 0; i < static_cast<int>(a.size()); i++) {
34         res[i][i] = 1;
35     }
36     for (int j = (int)binary.size() - 1; j >= 0; j--) {
37         res *= res;
38         if (binary[j] == 1) {
39             res *= a;
40         }
41     }
42     return res;
43 }

```

6.16 matrixfast.cpp

```

1  Description: Basic operations on square matrices.
2  Usage: Matrix<int, 3> A;
3  A.d = {{{{1, 2, 3}}, {{4, 5, 6}}, {{7, 8, 9}}}};
4  vector<int> vec = {1, 2, 3};
5  vec = (A^N) * vec;
6
7  template<class T, int N> struct Matrix {
8      typedef Matrix M;
9      array<array<T, N>, N> d{};
10     M operator*(const M& m) const {
11         M a;
12         rep(i, 0, N) rep(j, 0, N)
13             rep(k, 0, N) a.d[i][j] += d[i][k] * m.d[k][j];
14         return a;
15     }
16     vector<T> operator*(const vector<T>& vec) const {
17         vector<T> ret(N);
18         rep(i, 0, N) rep(j, 0, N) ret[i] += d[i][j] * vec[j];
19         return ret;
20     }
21     M operator^(ll p) const {
22         assert(p >= 0);
23         M a, b(*this);
24         rep(i, 0, N) a.d[i][i] = 1;
25         while (p) {

```

```

26         if (p & 1) a = a * b;
27         b = b * b;
28         p >>= 1;
29     }
30     return a;
31 }
32 };

```

6.17 MillerRabbin pollard modmul.cpp

```

1  /*ModMulLL.h
2  Description: Calculate  $a \cdot b \bmod c$  (or  $a$ 
3   $b \bmod c$ ) for  $0 \leq a, b < c \leq 7.2 \cdot 10^{18}$ 
4  Time:  $O(1)$  for modmul,  $O(\log b)$  for modpow*/
5  /*ull modmul(ull a, ull b, ull M) {
6      ll ret = a * b - M * ull(1.L / M * a * b);
7      return ret + M * (ret < 0) - M * (ret >= (ll)M);
8  }
9  ull modpow(ull b, ull e, ull mod) {
10     ull ans = 1;
11     for (; e; b = modmul(b, b, mod), e /= 2)
12         if (e & 1) ans = modmul(ans, b, mod);
13     return ans;
14 }*/
15 ll modmul(ll a, ll b, ll m) {
16     a %= m, b %= m;
17     ll d = ((ldb)a * b / m);
18     d = a * b - d * m;
19     if (d >= m) d -= m;
20     if (d < 0) d += m;
21     return d;
22 }
23 ll modpow(ll a, ll b, ll p) {
24     ll ans = 1;
25     while (b) {
26         if (b & 1) ans = modmul(ans, a, p);
27         a = modmul(a, a, p); b >>= 1;
28     } return ans;
29 }
30 /*MillerRabin.h
31 Description: Deterministic Miller-Rabin primality test. Guaranteed to

```

```

32 work for numbers up to  $7 \cdot 10^{18}$ ; for larger numbers, use Python and extend
33   A randomly.
34 Time: 7 times the complexity of  $a^b \bmod c$  */
35 bool isPrime(ll n) {
36     if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
37     ll A[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022},
38         s = __builtin_ctzll(n - 1), d = n >> s;
39     for (ll a : A) { // ^ count trailing zeroes
40         ll p = modpow(a % n, d, n), i = s;
41         while (p != 1 && p != n - 1 && a % n && i--)
42             p = modmul(p, p, n);
43         if (p != n - 1 && i != s) return 0;
44     }
45     return 1;
46 }
47 /*Factor.h
48 Description: Pollard-rho randomized factorization algorithm. Returns
49 prime factors of a number, in arbitrary order (e.g. 2299 -> {11, 19, 11}).
50 Time:  $O(n^{1/4})$ , less for numbers with small factors.*/
51 ll pollard(ll n) {
52     auto f = [n](ll x) { return modmul(x, x, n) + 1; };
53     ll x = 0, y = 0, t = 30, prd = 2, i = 1, q;
54     while (t++ % 40 || __gcd(prd, n) == 1) {
55         if (x == y) x = ++i, y = f(x);
56         if ((q = modmul(prd, max(x, y) - min(x, y), n))) prd = q;
57         x = f(x), y = f(f(y));
58     }
59     return __gcd(prd, n);
60 }
61 vector<ll> factor(ll n) {
62     if (n == 1) return {};
63     if (isPrime(n)) return {n};
64     ll x = pollard(n);
65     auto l = factor(x), r = factor(n / x);
66     l.insert(l.end(), all(r));
67     return l;
68 }

```

6.18 ntt(polynomial).cpp

```

1  #include<bits/stdc++.h>

```

```

2  using namespace std;
3
4  const int mod = 998244353;
5
6  inline void add(int &x, int y) {
7      x += y;
8      if (x >= mod) {
9          x -= mod;
10     }
11 }
12
13 inline void sub(int &x, int y) {
14     x -= y;
15     if (x < 0) {
16         x += mod;
17     }
18 }
19
20 inline int mul(int x, int y) {
21     return (long long) x * y % mod;
22 }
23
24 inline int power(int x, int y) {
25     int res = 1;
26     for (; y; y >>= 1, x = mul(x, x)) {
27         if (y & 1) {
28             res = mul(res, x);
29         }
30     }
31     return res;
32 }
33
34 inline int inv(int a) {
35     a %= mod;
36     if (a < 0) {
37         a += mod;
38     }
39     int b = mod, u = 0, v = 1;
40     while (a) {
41         int t = b / a;
42         b -= t * a;
43         swap(a, b);

```

```

44         u -= t * v;
45         swap(u, v);
46     }
47     if (u < 0) {
48         u += mod;
49     }
50     return u;
51 }
52
53 namespace ntt {
54     int base = 1, root = -1, max_base = -1;
55     vector<int> rev = {0, 1}, roots = {0, 1};
56
57     void init() {
58         int temp = mod - 1;
59         max_base = 0;
60         while (temp % 2 == 0) {
61             temp >>= 1;
62             ++max_base;
63         }
64         root = 2;
65         while (true) {
66             if (power(root, 1 << max_base) == 1 && power(root, 1 << (max_base - 1)
67                 ) != 1) {
68                 break;
69             }
69             ++root;
70         }
71     }
72
73     void ensure_base(int nbase) {
74         if (max_base == -1) {
75             init();
76         }
77         if (nbase <= base) {
78             return;
79         }
80         assert(nbase <= max_base);
81         rev.resize(1 << nbase);
82         for (int i = 0; i < 1 << nbase; ++i) {
83             rev[i] = (rev[i >> 1] >> 1) | ((i & 1) << (nbase - 1));
84         }

```

```

85     roots.resize(1 << nbase);
86     while (base < nbase) {
87         int z = power(root, 1 << (max_base - 1 - base));
88         for (int i = 1 << (base - 1); i < 1 << base; ++i) {
89             roots[i << 1] = roots[i];
90             roots[i << 1 | 1] = mul(roots[i], z);
91         }
92         ++base;
93     }
94 }
95
96 void dft(vector<int> &a) {
97     int n = a.size(), zeros = __builtin_ctz(n);
98     ensure_base(zeros);
99     int shift = base - zeros;
100    for (int i = 0; i < n; ++i) {
101        if (i < rev[i] >> shift) {
102            swap(a[i], a[rev[i] >> shift]);
103        }
104    }
105    for (int i = 1; i < n; i <= 1) {
106        for (int j = 0; j < n; j += i << 1) {
107            for (int k = 0; k < i; ++k) {
108                int x = a[j + k], y = mul(a[j + k + i], roots[i + k]);
109                a[j + k] = (x + y) % mod;
110                a[j + k + i] = (x + mod - y) % mod;
111            }
112        }
113    }
114 }
115
116 vector<int> multiply(vector<int> a, vector<int> b) {
117     int need = a.size() + b.size() - 1, nbase = 0;
118     while (1 << nbase < need) {
119         ++nbase;
120     }
121     ensure_base(nbase);
122     int sz = 1 << nbase;
123     a.resize(sz);
124     b.resize(sz);
125     bool equal = a == b;
126     dft(a);

```

```

127     if (equal) {
128         b = a;
129     } else {
130         dft(b);
131     }
132     int inv_sz = inv(sz);
133     for (int i = 0; i < sz; ++i) {
134         a[i] = mul(mul(a[i], b[i]), inv_sz);
135     }
136     reverse(a.begin() + 1, a.end());
137     dft(a);
138     a.resize(need);
139     return a;
140 }
141
142 vector<int> inverse_new(const vector<int> &a) {
143     assert(!a.empty());
144     int n = (int) a.size();
145     vector<int> b = {inv(a[0])};
146     while ((int) b.size() < n) {
147         vector<int> x(a.begin(), a.begin() + min(a.size(), b.size() << 1));
148         x.resize(b.size() << 1);
149         b.resize(b.size() << 1);
150         vector<int> c = b;
151         // NTT<T>::fft(c);
152         // NTT<T>::fft(x);
153         dft(c);
154         dft(x);
155         // Modular<T> inv = 1 / static_cast<Modular<T>>((int) x.size());
156         int inv_sz = inv((int)x.size());
157         for (int i = 0; i < (int) x.size(); i++) {
158             // x[i] *= c[i] * inv;
159             x[i] = mul(x[i], mul(c[i], inv_sz));
160         }
161         reverse(x.begin() + 1, x.end());
162         // NTT<T>::fft(x);
163         dft(x);
164         rotate(x.begin(), x.begin() + (x.size() >> 1), x.end());
165         fill(x.begin() + (x.size() >> 1), x.end(), 0);
166         // NTT<T>::fft(x);
167         dft(x);
168         for (int i = 0; i < (int) x.size(); i++) {

```

```

169     // x[i] *= c[i] * inv;
170     x[i] = mul(x[i], mul(c[i], inv_sz));
171 }
172 reverse(x.begin() + 1, x.end());
173 // NTT<T>::fft(x);
174 dft(x);
175 for (int i = 0; i < ((int) x.size() >> 1); i++) {
176     // b[i + ((int) x.size() >> 1)] = -x[i];
177     int t = 0; sub(t, x[i]);
178     b[i + ((int) x.size() >> 1)] = t;
179 }
180 }
181 b.resize(n);
182 return b;
183 }
184
185 vector<int> inverse(vector<int> a) {
186     int n = a.size(), m = (n + 1) >> 1;
187     if (n == 1) {
188         return vector<int>(1, inv(a[0]));
189     } else {
190         vector<int> b = inverse(vector<int>(a.begin(), a.begin() + m));
191         int need = n << 1, nbase = 0;
192         while (1 << nbase < need) {
193             ++nbase;
194         }
195         ensure_base(nbase);
196         int sz = 1 << nbase;
197         a.resize(sz);
198         b.resize(sz);
199         dft(a);
200         dft(b);
201         int inv_sz = inv(sz);
202         for (int i = 0; i < sz; ++i) {
203             a[i] = mul(mul(mod + 2 - mul(a[i], b[i]), b[i]), inv_sz);
204         }
205         reverse(a.begin() + 1, a.end());
206         dft(a);
207         a.resize(n);
208         return a;
209     }
210 }

```

```

211 }
212
213 using ntt::multiply;
214 using ntt::inverse;
215
216 vector<int>& operator += (vector<int> &a, const vector<int> &b) {
217     if (a.size() < b.size()) {
218         a.resize(b.size());
219     }
220     for (int i = 0; i < b.size(); ++i) {
221         add(a[i], b[i]);
222     }
223     return a;
224 }
225
226 vector<int> operator + (const vector<int> &a, const vector<int> &b) {
227     vector<int> c = a;
228     return c += b;
229 }
230
231 vector<int>& operator -= (vector<int> &a, const vector<int> &b) {
232     if (a.size() < b.size()) {
233         a.resize(b.size());
234     }
235     for (int i = 0; i < b.size(); ++i) {
236         sub(a[i], b[i]);
237     }
238     return a;
239 }
240
241 vector<int> operator - (const vector<int> &a, const vector<int> &b) {
242     vector<int> c = a;
243     return c -= b;
244 }
245
246 vector<int>& operator *= (vector<int> &a, const vector<int> &b) {
247     if (min(a.size(), b.size()) < 128) {
248         vector<int> c = a;
249         a.assign(a.size() + b.size() - 1, 0);
250         for (int i = 0; i < c.size(); ++i) {
251             for (int j = 0; j < b.size(); ++j) {
252                 add(a[i + j], mul(c[i], b[j]));

```



```

253     }
254 }
255 } else {
256     a = multiply(a, b);
257 }
258 return a;
259 }
260
261 vector<int> operator * (const vector<int> &a, const vector<int> &b) {
262     vector<int> c = a;
263     return c *= b;
264 }
265
266 vector<int>& operator /= (vector<int> &a, const vector<int> &b) {
267     int n = a.size(), m = b.size();
268     if (n < m) {
269         a.clear();
270     } else {
271         vector<int> c = b;
272         reverse(a.begin(), a.end());
273         reverse(c.begin(), c.end());
274         c.resize(n - m + 1);
275         a *= inverse(c);
276         a.erase(a.begin() + n - m + 1, a.end());
277         reverse(a.begin(), a.end());
278     }
279     return a;
280 }
281
282 vector<int> operator / (const vector<int> &a, const vector<int> &b) {
283     vector<int> c = a;
284     return c /= b;
285 }
286
287 vector<int>& operator %=(vector<int> &a, const vector<int> &b) {
288     int n = a.size(), m = b.size();
289     if (n >= m) {
290         vector<int> c = (a / b) * b;
291         a.resize(m - 1);
292         for (int i = 0; i < m - 1; ++i) {
293             sub(a[i], c[i]);
294         }

```

```

295     }
296     return a;
297 }
298
299 vector<int> operator % (const vector<int> &a, const vector<int> &b) {
300     vector<int> c = a;
301     return c %= b;
302 }
303
304 vector<int> derivative(const vector<int> &a) {
305     int n = a.size();
306     vector<int> b(n - 1);
307     for (int i = 1; i < n; ++i) {
308         b[i - 1] = mul(a[i], i);
309     }
310     return b;
311 }
312
313 vector<int> primitive(const vector<int> &a) {
314     int n = a.size();
315     vector<int> b(n + 1), invs(n + 1);
316     for (int i = 1; i <= n; ++i) {
317         invs[i] = i == 1 ? 1 : mul(mod - mod / i, invs[mod % i]);
318         b[i] = mul(a[i - 1], invs[i]);
319     }
320     return b;
321 }
322
323 vector<int> logarithm(const vector<int> &a) {
324     vector<int> b = primitive(derivative(a) * inverse(a));
325     b.resize(a.size());
326     return b;
327 }
328
329 vector<int> exponent(const vector<int> &a) {
330     vector<int> b(1, 1);
331     while (b.size() < a.size()) {
332         vector<int> c(a.begin(), a.begin() + min(a.size(), b.size() << 1));
333         add(c[0], 1);
334         vector<int> old_b = b;
335         b.resize(b.size() << 1);
336         c -= logarithm(b);

```

```

337     c *= old_b;
338     for (int i = b.size() >> 1; i < b.size(); ++i) {
339         b[i] = c[i];
340     }
341 }
342 b.resize(a.size());
343 return b;
344 }
345
346 vector<int> power(vector<int> a, int m) {
347     int n = a.size(), p = -1;
348     vector<int> b(n);
349     for (int i = 0; i < n; ++i) {
350         if (a[i]) {
351             p = i;
352             break;
353         }
354     }
355     if (p == -1) {
356         b[0] = !m;
357         return b;
358     }
359     if ((long long) m * p >= n) {
360         return b;
361     }
362     int mu = power(a[p], m), di = inv(a[p]);
363     vector<int> c(n - m * p);
364     for (int i = 0; i < n - m * p; ++i) {
365         c[i] = mul(a[i + p], di);
366     }
367     c = logarithm(c);
368     for (int i = 0; i < n - m * p; ++i) {
369         c[i] = mul(c[i], m);
370     }
371     c = exponent(c);
372     for (int i = 0; i < n - m * p; ++i) {
373         b[i + m * p] = mul(c[i], mu);
374     }
375     return b;
376 }
377
378 vector<int> sqrt(const vector<int> &a) {

```

```

379     vector<int> b(1, 1);
380     while (b.size() < a.size()) {
381         vector<int> c(a.begin(), a.begin() + min(a.size(), b.size() << 1));
382         vector<int> old_b = b;
383         b.resize(b.size() << 1);
384         c *= inverse(b);
385         for (int i = b.size() >> 1; i < b.size(); ++i) {
386             b[i] = mul(c[i], (mod + 1) >> 1);
387         }
388     }
389     b.resize(a.size());
390     return b;
391 }
392
393 vector<int> multiply_all(int l, int r, vector<vector<int>> &all) {
394     if (l > r) {
395         return vector<int>();
396     } else if (l == r) {
397         return all[l];
398     } else {
399         int y = (l + r) >> 1;
400         return multiply_all(l, y, all) * multiply_all(y + 1, r, all);
401     }
402 }
403
404 vector<int> evaluate(const vector<int> &f, const vector<int> &x) {
405     int n = x.size();
406     if (!n) {
407         return vector<int>();
408     }
409     vector<vector<int>> up(n * 2);
410     for (int i = 0; i < n; ++i) {
411         up[i + n] = vector<int> {(mod - x[i]) % mod, 1};
412     }
413     for (int i = n - 1; i; --i) {
414         up[i] = up[i << 1] * up[i << 1 | 1];
415     }
416     vector<vector<int>> down(n * 2);
417     down[1] = f % up[1];
418     for (int i = 2; i < n * 2; ++i) {
419         down[i] = down[i >> 1] % up[i];
420     }

```

```

421     vector<int> y(n);
422     for (int i = 0; i < n; ++i) {
423         y[i] = down[i + n][0];
424     }
425     return y;
426 }
427
428 vector<int> interpolate(const vector<int> &x, const vector<int> &y) {
429     int n = x.size();
430     vector<vector<int>> up(n * 2);
431     for (int i = 0; i < n; ++i) {
432         up[i + n] = vector<int> {(mod - x[i]) % mod, 1};
433     }
434     for (int i = n - 1; i; --i) {
435         up[i] = up[i << 1] * up[i << 1 | 1];
436     }
437     vector<int> a = evaluate(derivative(up[1]), x);
438     for (int i = 0; i < n; ++i) {
439         a[i] = mul(y[i], inv(a[i]));
440     }
441     vector<vector<int>> down(n * 2);
442     for (int i = 0; i < n; ++i) {
443         down[i + n] = vector<int>(1, a[i]);
444     }
445     for (int i = n - 1; i; --i) {
446         down[i] = down[i << 1] * up[i << 1 | 1] + down[i << 1 | 1] * up[i <<
            1];
447     }
448     return down[1];
449 }
450
451 int main() {
452
453 }

```

6.19 区间互质.cpp

```

1 int p[N / 5], num;
2 void prime(int n) {
3     num = 0;
4     for (int i = 2; i * i <= n; i++) {

```

```

5         if ((n % i) == 0) {
6             p[++num] = i;
7             while ((n % i) == 0) n /= i;
8         }
9     }
10    if (n > 1) p[++num] = n;
11 }
12 ll solve(ll r, int k) {
13     prime(k);
14     ll res = 0;
15     for (int i = 1; i < (1 << num); i++) {
16         int k = 0;
17         ll div = 1;
18         for (int j = 1; j <= num; j++) {
19             if (i & (1 << (j - 1))) {
20                 k++;
21                 div *= p[j];
22             }
23         }
24         if (k % 2)
25             res += r / div;
26         else
27             res -= r / div;
28     }
29     return r - res;
30 }
31 ll que(ll L, ll R, ll k) {
32     return solve(R, k) - solve(L - 1, k);
33 }

```

6.20 幂转下降幂 (求幂和).cpp

```

1 ll comb[N][N];
2 ll s[maxn], inv[maxn], p;
3 //  $1^k + 2^k + \dots + n^k$ 
4 void solve() {
5     cin >> k >> n >> p;
6     rep(i, 0, k + 1) {
7         comb[i][0] = comb[i][i] = 1;
8         rep(j, 1, i - 1) {
9             comb[i][j] = (comb[i - 1][j - 1] + comb[i - 1][j])

```

```

                                % p;
10     }
11 }
12 inv[1] = 1;
13 rep(i, 2, k + 1) inv[i] = (p - p / i) * inv[p % i] % p;
14 assert(inv[k] * k % p == 1);
15
16 ll pw = 1;
17 // (k+1)*S[k]=(n+1)^(k+1)-[0-k-1](k+1,j)*S[j]-1
18 rep(i, 0, k) {
19     pw = pw * (n + 1) % p;
20     s[i] = (pw - 1 + p) % p;
21     rep(j, 0, i - 1) {
22         s[i] = (s[i] - comb[i + 1][j] * s[j] % p + p) % p;
23     }
24     s[i] = s[i] * inv[i + 1] % p;
25 }
26 cout << s[k] << '\n';
27 }

```

6.21 扩展欧拉定理.cpp

```

1 // mod {min(b, b % phi + phi)}
2 ll calc(ll p) {
3     if (p == 1) return 0;
4     int phi = p, q = p;
5     for (int i = 2; i * i <= p; i++) {
6         if (q % i == 0) {
7             phi = phi / i * (i - 1);
8             while (q % i == 0) q /= i;
9         }
10    }
11    if (q != 1) phi = phi / q * (q - 1);
12    return powmod(2, calc(phi) + phi, p);
13 }

```

6.22 拉格朗日插值.cpp

```

1 // k阶多项式(需要k+1个点)
2 // 求在点n上的值
3 // O(k)

```

```

4 ll lagrange(ll n, int k) {
5     vector<ll> x(k + 5), y(k + 5);
6     rep(i, 1, k + 1) {
7         x[i] = i;
8         // y[i]=(y[i-1]+powmod(i,k-1,mod))%mod;
9     }
10    if (n <= k + 1) return y[n];
11
12    vector<ll> fac(k + 5);
13    fac[0] = 1;
14    ll coe = 1;
15    rep(i, 1, k + 4) fac[i] = fac[i - 1] * i % mod;
16    rep(i, 1, k + 1) coe = coe * (n - i + mod) % mod;
17    ll ans = 0;
18    rep(i, 1, k + 1) {
19        ll sgn = (((k + 1 - i) % 2) ? -1 : 1);
20        ll f1 = powmod(fac[i - 1] * fac[k + 1 - i] % mod, mod - 2,
21                        mod);
22        ll f2 = powmod(n - i, mod - 2, mod);
23        ans += sgn * coe * f1 % mod * f2 % mod * y[i] % mod;
24        ans = (ans + mod) % mod;
25    }
26    return ans;
27 }

```

6.23 整除分块.cpp

```

1 void solve() {
2     u64 ans = 0;
3     cin >> n;
4     for (ll l = 1; l <= n; l++) {
5         ll d = n / l, r = n / d;
6         ans += (l + r) * (r - l + 1) / 2 * d;
7         l = r;
8     }
9 }

```

6.24 枚举子集.cpp

```

1 void solve() {
2     f[0] = 1;

```

```

3     for (int i = 1; i < (1ll << n); i++) {
4         int t = i;
5         ll res = 0;
6         while (true) {
7             if (t == 0) break;
8             t = (t - 1) & i;
9             res = (res + f[t]) % mod;
10        }
11        f[i] = res * i;
12    }
13 }

```

6.25 枚举超集.cpp

```

1 void solve() {
2     for (int i = 1; i < (1ll << n); i++) {
3         int t = i;
4         while (true) {
5             t = (t + 1) | i;
6             if (t == bit(n) - 1) break;
7         }
8     }
9 }

```

6.26 狄利克雷卷积.cpp

```

1 const int N = 1010000;
2 int p[N], pr[N / 5], n, tot;
3 unsigned int A, B, C, mu[N], f[N], g[N];
4
5 inline unsigned int rng61() {
6     A ^= A << 16;
7     A ^= A >> 5;
8     A ^= A << 1;
9     unsigned int t = A;
10    A = B;
11    B = C;
12    C ^= t ^ A;
13    return C;
14 }
15

```

```

16 int main() {
17     scanf("%d%u%u%u", &n, &A, &B, &C);
18     for (int i = 1; i <= n; i++)
19         f[i] = rng61();
20
21     p[1] = 1; mu[1] = 1;
22     for (int i = 2; i <= n; i++) {
23         if (!p[i]) p[i] = i, mu[i] = (uint)-1, pr[++tot] = i;
24         for (int j = 1; j <= tot && pr[j] * i <= n; j++) {
25             p[i * pr[j]] = pr[j];
26             if (p[i] == pr[j]) {
27                 mu[i * pr[j]] = 0;
28                 break;
29             } else {
30                 mu[i * pr[j]] = (uint)-mu[i];
31             }
32         }
33     }
34     for (int d1 = 1; d1 <= n; d1++)
35         for (int d2 = 1; d1 * d2 <= n; d2++)
36             g[d1 * d2] += f[d1] * mu[d2];
37     uint ans = 0;
38     for (int i = 1; i <= n; i++) ans ^= g[i];
39     printf("%u\n", ans);
40 }

```

6.27 线性筛常见积性函数.cpp

```

1 const int N = 20010000;
2 int p[N], pr[N / 5], n, pe[N], tot;
3 uint f[N], a, b, ans;
4
5 void compute(int n, function<void(int)> calcpe) {
6     ans = 0;
7     f[1] = 1;
8     for (int i = 2; i <= n; i++) {
9         if (i == pe[i])
10            calcpe(i);
11        else
12            f[i] = f[pe[i]] * f[i / pe[i]];
13    }

```

```

14     for (uint i = 1; i <= n; i++) {
15         ans ^= (a * i * f[i] + b);
16     }
17     printf("%u\n", ans);
18 }
19
20 int main() {
21     scanf("%d%u%u", &n, &a, &b);
22     p[1] = 1;
23     for (int i = 2; i <= n; i++) {
24         if (!p[i]) p[i] = i, pe[i] = i, pr[++tot] = i;
25         for (int j = 1; j <= tot && pr[j] * i <= n; j++) {
26             p[i * pr[j]] = pr[j];
27             if (p[i] == pr[j]) {
28                 pe[i * pr[j]] = pe[i] * pr[j];
29                 break;
30             } else {
31                 pe[i * pr[j]] = pr[j];
32             }
33         }
34     }
35     // 因子个数, 因子和, 欧拉函数, 莫比乌斯函数
36     compute(n, [&](int x) {
37         f[x] = f[x / p[x]] + 1;
38     });
39
40     compute(n, [&](int x) {
41         f[x] = f[x / p[x]] + x;
42     });
43
44     compute(n, [&](int x) {
45         f[x] = x / p[x] * (p[x] - 1);
46     });
47
48     compute(n, [&](int x) {
49         f[x] = x == p[x] ? -1 : 0;
50     });
51 }

```

6.28 莫比乌斯反演 gcd 常见结论.cpp

```

1  // u * 1 = e, phi * 1 = id, phi = id * u
2  const int N = 10100000, M = 10000000;
3  int p[N], pr[N / 5], n, tot;
4  int mu[N], smu[N];
5
6  int main() {
7      p[1] = 1; mu[1] = 1;
8      for (int i = 2; i <= M; i++) {
9          if (!p[i]) p[i] = i, mu[i] = -1, pr[++tot] = i;
10         for (int j = 1; j <= tot && pr[j] * i <= M; j++) {
11             p[i * pr[j]] = pr[j];
12             if (p[i] == pr[j]) {
13                 mu[i * pr[j]] = 0;
14                 break;
15             } else {
16                 mu[i * pr[j]] = -mu[i];
17             }
18         }
19     }
20     for (int i = 1; i <= M; i++)
21         smu[i] = smu[i - 1] + mu[i];
22
23     int T;
24     scanf("%d", &T);
25     for (int tc = 0; tc < T; tc++) {
26         int n, m;
27         scanf("%d%d", &n, &m);
28         if (n > m) swap(n, m);
29         ll ans = 0;
30         for (int l = 1; l <= n; l++) {
31             int n1 = n / l, m1 = m / l;
32             int r = min(n / n1, m / m1);
33             // l ... r
34             ans += 1ll * (smu[r] - smu[l - 1]) * n1 * m1;
35             l = r;
36         }
37         printf("%lld\n", ans);
38     }
39 }

```

7 String

7.1 ACAM.cpp

```
1  const int M = 2, N = 2.1e5;
2  struct node {
3      node *son[M], *go[M], *fail;
4      int cnt, vis, ins;
5  } pool[N], *cur = pool, *q[N], *root;
6
7  node *newnode() { return cur++; }
8  int t, n;
9
10 void build() {
11     t = 0;
12     q[t++] = root;
13     for (int i = 0; i < t; i++) {
14         node *u = q[i];
15         for (int j = 0; j < M; j++) {
16             if (u->son[j]) {
17                 u->go[j] = u->son[j];
18                 if (u != root)
19                     u->go[j]->fail = u->fail->go[j];
20                 else
21                     u->go[j]->fail = root;
22                 q[t++] = u->son[j];
23             } else {
24                 if (u != root)
25                     u->go[j] = u->fail->go[j];
26                 else
27                     u->go[j] = root;
28             }
29         }
30     }
31 }
32
33 void insert(string &s) {
34     node *cur = root;
35     for (auto c : s) {
36         int w = c - '0';
37         if (!cur->son[w]) {
38             cur->son[w] = newnode();
```

```
39         }
40         cur = cur->son[w];
41     }
42     cur->cnt = 1;
43 }
```

7.2 hash61.cpp

```
1  struct hash61 {
2      static const uint64_t md = (1LL << 61) - 1;
3      static uint64_t step;
4      static vector<uint64_t> pw;
5
6      uint64_t addmod(uint64_t a, uint64_t b) const {
7          a += b;
8          if (a >= md) a -= md;
9          return a;
10     }
11
12     uint64_t submod(uint64_t a, uint64_t b) const {
13         a += md - b;
14         if (a >= md) a -= md;
15         return a;
16     }
17
18     uint64_t mulmod(uint64_t a, uint64_t b) const {
19         uint64_t l1 = (uint32_t) a, h1 = a >> 32, l2 = (uint32_t)
20             b, h2 = b >> 32;
21         uint64_t l = l1 * l2, m = l1 * h2 + l2 * h1, h = h1 * h2;
22         uint64_t ret = (l & md) + (l >> 61) + (h << 3) + (m >> 29)
23             + (m << 35 >> 3) + 1;
24         ret = (ret & md) + (ret >> 61);
25         return ret - 1;
26     }
27
28     void ensure_pw(int sz) {
29         int cur = (int) pw.size();
30         if (cur < sz) {
31             pw.resize(sz);
32             for (int i = cur; i < sz; i++) {
```

```

32         pw[i] = mulmod(pw[i - 1], step);
33     }
34 }
35
36
37 vector<uint64_t> pref;
38 int n;
39
40 template<typename T>
41 hash61(const T& s) {
42     n = (int) s.size();
43     ensure_pw(n + 1);
44     pref.resize(n + 1);
45     pref[0] = 1;
46     for (int i = 0; i < n; i++) {
47         pref[i + 1] = addmod(mulmod(pref[i], step), s[i]);
48     }
49 }
50
51 inline uint64_t operator()(const int from, const int to) const {
52     assert(0 <= from && from <= to && to <= n - 1);
53     return submod(pref[to + 1], mulmod(pref[from], pw[to -
54         from + 1]));
55 }
56
57 uint64_t hash61::step = (md >> 2) + rng() % (md >> 1);
58 vector<uint64_t> hash61::pw = vector<uint64_t>(1, 1);

```

7.3 kmp.cpp

```

1 template <typename T>
2 vector<int> kmp_table(int n, const T &s) {
3     vector<int> p(n, 0);
4     int k = 0;
5     for (int i = 1; i < n; i++) {
6         while (k > 0 && !(s[i] == s[k])) {
7             k = p[k - 1];
8         }
9         if (s[i] == s[k]) {
10             k++;

```

```

11     }
12     p[i] = k;
13 }
14 return p;
15 }
16
17 template <typename T>
18 vector<int> kmp_table(const T &s) {
19     return kmp_table((int) s.size(), s);
20 }
21
22 template <typename T>
23 vector<int> kmp_search(int n, const T &s, int m, const T &w, const vector<
24     int> &p) {
25     assert(n >= 1 && (int) p.size() == n);
26     vector<int> res;
27     int k = 0;
28     for (int i = 0; i < m; i++) {
29         while (k > 0 && (k == n || !(w[i] == s[k]))) {
30             k = p[k - 1];
31         }
32         if (w[i] == s[k]) {
33             k++;
34         }
35         if (k == n) {
36             res.push_back(i - n + 1);
37         }
38     }
39     return res;
40     // returns 0-indexed positions of occurrences of s in w
41 }
42
43 template <typename T>
44 vector<int> kmp_search(const T &s, const T &w, const vector<int> &p) {
45     return kmp_search((int) s.size(), s, (int) w.size(), w, p);

```

7.4 manacherfast.cpp

```

1 template <typename T>
2 vector<int> manacher(int n, const T &s) {

```



```

3     if (n == 0) {
4         return vector<int>();
5     }
6     vector<int> res(2 * n - 1, 0);
7     int l = -1, r = -1;
8     for (int z = 0; z < 2 * n - 1; z++) {
9         int i = (z + 1) >> 1;
10        int j = z >> 1;
11        int p = (i >= r ? 0 : min(r - i, res[2 * (1 + r) - z]));
12        while (j + p + 1 < n && i - p - 1 >= 0) {
13            if (!(s[j + p + 1] == s[i - p - 1])) {
14                break;
15            }
16            p++;
17        }
18        if (j + p > r) {
19            l = i - p;
20            r = j + p;
21        }
22        res[z] = p;
23    }
24    return res;
25    // res[2 * i] = odd radius in position i
26    // res[2 * i + 1] = even radius between positions i and i + 1
27    // s = "abaa" -> res = {0, 0, 1, 0, 0, 1, 0}
28    // in other words, for every z from 0 to 2 * n - 2:
29    // calculate i = (z + 1) >> 1 and j = z >> 1
30    // now there is a palindrome from i - res[z] to j + res[z]
31    // (watch out for i > j and res[z] = 0)
32 }
33
34 template <typename T>
35 vector<int> manacher(const T &s) {
36     return manacher((int) s.size(), s);
37 }

```

7.5 MinRotation.cpp

```

1 Description: Finds the lexicographically smallest rotation of a string.
2 Usage: rotate(v.begin(), v.begin() + minRotation(v), v.end());
3 Time: O (N)

```

```

4
5 int minRotation(string s) {
6     int a = 0, N = sz(s); s += s;
7     rep(b, 0, N) rep(k, 0, N) {
8         if (a + k == b || s[a + k] < s[b + k]) {b += max(0, k - 1); break
9         };}
10        if (s[a + k] > s[b + k]) { a = b; break; }
11    }
12    return a;
13 }

```

7.6 rollingHash.cpp

```

1 typedef pair<int,int> hashv;
2 const ll mod1=1000000007;
3 const ll mod2=1000000009;
4
5 // prefixSum trick for high dimensions
6
7 hashv operator + (hashv a,hashv b) {
8     int c1=a.fi+b.fi,c2=a.se+b.se;
9     if (c1>=mod1) c1-=mod1;
10    if (c2>=mod2) c2-=mod2;
11    return mp(c1,c2);
12 }
13
14 hashv operator - (hashv a,hashv b) {
15     int c1=a.fi-b.fi,c2=a.se-b.se;
16     if (c1<0) c1+=mod1;
17     if (c2<0) c2+=mod2;
18     return mp(c1,c2);
19 }
20
21 hashv operator * (hashv a,hashv b) {
22     return mp(1ll*a.fi*b.fi%mod1,1ll*a.se*b.se%mod2);
23 }

```

7.7 SA.cpp

```

1 #include <bits/stdc++.h>
2 using namespace std;

```

```

3
4 const int N = 101000;
5 char s[N];
6 int sa[N], rk[N], ht[N], n;
7 // 0-based sa 表示第i大的为哪个, rk 表示第i个后缀第几大
8 // ht表示 lcp(sa[i], sa[i-1])
9 void buildSA(char *s, int *sa, int *rk, int *ht, int n, int m = 128) {
10     static int x[N], y[N], c[N];
11     s[n] = 0;
12     for (int i = 0; i < m; i++) c[i] = 0;
13     for (int i = 0; i < n; i++) c[x[i]]++;
14     for (int i = 1; i < m; i++) c[i] += c[i - 1];
15     for (int i = n - 1; i >= 0; i--) sa[--c[x[i]]] = i;
16     for (int k = 1; k < n; k <= 1) {
17         int p = 0;
18         for (int i = n - 1; i >= n - k; i--) y[p++] = i;
19         for (int i = 0; i < n; i++) if (sa[i] >= k) y[p++] = sa[i]
20             - k;
21         for (int i = 0; i < m; i++) c[i] = 0;
22         for (int i = 0; i < n; i++) c[x[y[i]]]++;
23         for (int i = 1; i < m; i++) c[i] += c[i - 1];
24         for (int i = n - 1; i >= 0; i--) sa[--c[x[y[i]]]] = y[i];
25         swap(x, y);
26         p = 1; x[sa[0]] = 0; y[n] = -1;
27         for (int i = 1; i < n; i++) {
28             if (y[sa[i - 1]] == y[sa[i]] && y[sa[i - 1] + k]
29                 == y[sa[i] + k])
30                 x[sa[i]] = p - 1;
31             else
32                 x[sa[i]] = p++;
33         }
34         if (p == n) break;
35         m = p;
36     }
37     for (int i = 0; i < n; i++) rk[sa[i]] = i;
38     int k = 0;
39     for (int i = 0; i < n; i++) {
40         k = max(k - 1, 0);
41         if (rk[i] == 0) continue;
42         int j = sa[rk[i] - 1];
43         while (s[i + k] == s[j + k]) k++;
44         ht[rk[i]] = k;

```

```

45     }
46     int LCP(int u, int v) {
47         if (u == v) return n - u;
48         if (rk[u] > rk[v]) swap(u, v);
49         // RMQ(ht, rk[u] + 1, rk[v])
50     }
51
52     int main() {
53         scanf("%s", s);
54         n = strlen(s);
55         buildSA(s, sa, rk, ht, n);
56         for (int i = 0; i < n; i++) printf("%d", sa[i] + 1); puts("");
57         for (int i = 1; i < n; i++) printf("%d", ht[i]); puts("");
58     }

```

7.8 SAfast.cpp

```

1 template <typename T>
2 vector<int> suffix_array(int n, const T &s, int char_bound) {
3     vector<int> a(n);
4     if (n == 0) {
5         return a;
6     }
7     if (char_bound != -1) {
8         vector<int> aux(char_bound, 0);
9         for (int i = 0; i < n; i++) {
10             aux[s[i]]++;
11         }
12         int sum = 0;
13         for (int i = 0; i < char_bound; i++) {
14             int add = aux[i];
15             aux[i] = sum;
16             sum += add;
17         }
18         for (int i = 0; i < n; i++) {
19             a[aux[s[i]]++] = i;
20         }
21     } else {
22         iota(a.begin(), a.end(), 0);

```

```

23     sort(a.begin(), a.end(), [&s](int i, int j) { return s[i] < s[j]; });
24 }
25 vector<int> sorted_by_second(n);
26 vector<int> ptr_group(n);
27 vector<int> new_group(n);
28 vector<int> group(n);
29 group[a[0]] = 0;
30 for (int i = 1; i < n; i++) {
31     group[a[i]] = group[a[i - 1]] + (!(s[a[i]] == s[a[i - 1]]));
32 }
33 int cnt = group[a[n - 1]] + 1;
34 int step = 1;
35 while (cnt < n) {
36     int at = 0;
37     for (int i = n - step; i < n; i++) {
38         sorted_by_second[at++] = i;
39     }
40     for (int i = 0; i < n; i++) {
41         if (a[i] - step >= 0) {
42             sorted_by_second[at++] = a[i] - step;
43         }
44     }
45     for (int i = n - 1; i >= 0; i--) {
46         ptr_group[group[a[i]]] = i;
47     }
48     for (int i = 0; i < n; i++) {
49         int x = sorted_by_second[i];
50         a[ptr_group[group[x]]++] = x;
51     }
52     new_group[a[0]] = 0;
53     for (int i = 1; i < n; i++) {
54         if (group[a[i]] != group[a[i - 1]]) {
55             new_group[a[i]] = new_group[a[i - 1]] + 1;
56         } else {
57             int pre = (a[i - 1] + step >= n ? -1 : group[a[i - 1] + step]);
58             int cur = (a[i] + step >= n ? -1 : group[a[i] + step]);
59             new_group[a[i]] = new_group[a[i - 1]] + (pre != cur);
60         }
61     }
62     swap(group, new_group);
63     cnt = group[a[n - 1]] + 1;
64     step <<= 1;

```

```

65     }
66     return a;
67 }
68
69 template <typename T>
70 vector<int> suffix_array(const T &s, int char_bound) {
71     return suffix_array((int) s.size(), s, char_bound);
72 }
73
74 template <typename T>
75 vector<int> build_lcp(int n, const T &s, const vector<int> &sa) {
76     assert((int) sa.size() == n);
77     vector<int> pos(n);
78     for (int i = 0; i < n; i++) {
79         pos[sa[i]] = i;
80     }
81     vector<int> lcp(max(n - 1, 0));
82     int k = 0;
83     for (int i = 0; i < n; i++) {
84         k = max(k - 1, 0);
85         if (pos[i] == n - 1) {
86             k = 0;
87         } else {
88             int j = sa[pos[i] + 1];
89             while (i + k < n && j + k < n && s[i + k] == s[j + k]) {
90                 k++;
91             }
92             lcp[pos[i]] = k;
93         }
94     }
95     return lcp;
96 }
97
98 template <typename T>
99 vector<int> build_lcp(const T &s, const vector<int> &sa) {
100     return build_lcp((int) s.size(), s, sa);
101 }

```

7.9 SAM.cpp

```

1 struct SAM {

```

```

2 static constexpr int ALPHABET_SIZE = 26;
3 struct Node {
4     int len;
5     int link;
6     std::array<int, ALPHABET_SIZE> next;
7     Node() : len{}, link{}, next{} {}
8 };
9 std::vector<Node> t;
10 SAM() {
11     init();
12 }
13 void init() {
14     t.assign(2, Node());
15     t[0].next.fill(1);
16     t[0].len = -1;
17 }
18 int newNode() {
19     t.emplace_back();
20     return t.size() - 1;
21 }
22 int extend(int p, int c) {
23     if (t[p].next[c]) {
24         int q = t[p].next[c];
25         if (t[q].len == t[p].len + 1) {
26             return q;
27         }
28         int r = newNode();
29         t[r].len = t[p].len + 1;
30         t[r].link = t[q].link;
31         t[r].next = t[q].next;
32         t[q].link = r;
33         while (t[p].next[c] == q) {
34             t[p].next[c] = r;
35             p = t[p].link;
36         }
37         return r;
38     }
39     int cur = newNode();
40     t[cur].len = t[p].len + 1;
41     while (!t[p].next[c]) {
42         t[p].next[c] = cur;
43         p = t[p].link;

```

```

44     }
45     t[cur].link = extend(p, c);
46     return cur;
47 }
48 };

```

7.10 SA-IS.cpp

```

1  /*
2   * Time Complexity: Suffix Array:  $O(N + \text{Character\_Set\_Size})$  time and space
3   * //
4   * 128 --- ASCII
5   * LCP:  $O(N)$  time and space
6   * Usage:
7   * 1. Suffix Array (returns s.size() elements, NOT considering
8   * 0-length/empty suffix)
9   * auto sa = suffix_array(s); // s is the input string with
10  ASCII
11  characters
12  * auto sa_wide_char = suffix_array(s, LIM); // LIM = max(s[i
13  ]) + 2,
14  s is the string with arbitrary big characters.
15  * 2. LCP:
16  * auto lcp = LCP(s, suffix_array(s)); // returns s.size()
17  elements,
18  where lcp[i]=LCP(sa[i], sa[i+1])
19  * Status: Tested (DMOJ: ccc03s4, SPOJ: SARRAY (100pts), Yosupo's: Suffix
20  Array
21  & Number of Substrings, CodeForces EDU
22  */
23  // Based on: Rickypon, https://judge.yosupo.jp/submission/10105
24  void induced_sort(const std::vector<int>& vec, int val_range,
25                  std::vector<int>& SA, const std::vector<bool>& sl,
26                  const std::vector<int>& lms_idx) {
27      std::vector<int> l(val_range, 0), r(val_range, 0);
28      for (int c : vec) {
29          if (c + 1 < val_range) ++l[c + 1];
30          ++r[c];
31      }
32      std::partial_sum(l.begin(), l.end(), l.begin());
33      std::partial_sum(r.begin(), r.end(), r.begin());

```

```

29     std::fill(SA.begin(), SA.end(), -1);
30     for (int i = (int)lms_idx.size() - 1; i >= 0; --i)
31         SA[--r[vec[lms_idx[i]]]] = lms_idx[i];
32     for (int i : SA)
33         if (i >= 1 && sl[i - 1]) SA[l[vec[i - 1]]++] = i - 1;
34     std::fill(r.begin(), r.end(), 0);
35     for (int c : vec) ++r[c];
36     std::partial_sum(r.begin(), r.end(), r.begin());
37     for (int k = (int)SA.size() - 1, i = SA[k]; k >= 1; --k, i = SA[k])
38         if (i >= 1 && !sl[i - 1]) {
39             SA[--r[vec[i - 1]]] = i - 1;
40         }
41 }
42
43 std::vector<int> SA_IS(const std::vector<int>& vec, int val_range) {
44     const int n = vec.size();
45     std::vector<int> SA(n), lms_idx;
46     std::vector<bool> sl(n);
47     sl[n - 1] = false;
48     for (int i = n - 2; i >= 0; --i) {
49         sl[i] = (vec[i] > vec[i + 1] || (vec[i] == vec[i + 1] && sl[i +
50             1]));
51         if (sl[i] && !sl[i + 1]) lms_idx.push_back(i + 1);
52     }
53     std::reverse(lms_idx.begin(), lms_idx.end());
54     induced_sort(vec, val_range, SA, sl, lms_idx);
55     std::vector<int> new_lms_idx(lms_idx.size()), lms_vec(lms_idx.size());
56     for (int i = 0, k = 0; i < n; ++i)
57         if (!sl[SA[i]] && SA[i] >= 1 && sl[SA[i] - 1]) {
58             new_lms_idx[k++] = SA[i];
59         }
60     int cur = 0;
61     SA[n - 1] = cur;
62     for (size_t k = 1; k < new_lms_idx.size(); ++k) {
63         int i = new_lms_idx[k - 1], j = new_lms_idx[k];
64         if (vec[i] != vec[j]) {
65             SA[j] = ++cur;
66             continue;
67         }
68         bool flag = false;
69         for (int a = i + 1, b = j + 1;; ++a, ++b) {
70             if (vec[a] != vec[b]) {

```

```

70                 flag = true;
71                 break;
72             }
73             if ((!sl[a] && sl[a - 1]) || (!sl[b] && sl[b - 1])) {
74                 flag = !((!sl[a] && sl[a - 1]) && (!sl[b] && sl[b - 1]));
75                 break;
76             }
77         }
78         SA[j] = (flag ? ++cur : cur);
79     }
80     for (size_t i = 0; i < lms_idx.size(); ++i) lms_vec[i] = SA[lms_idx[i
81         ]];
82     if (cur + 1 < (int)lms_idx.size()) {
83         auto lms_SA = SA_IS(lms_vec, cur + 1);
84         for (size_t i = 0; i < lms_idx.size(); ++i) {
85             new_lms_idx[i] = lms_idx[lms_SA[i]];
86         }
87     }
88     induced_sort(vec, val_range, SA, sl, new_lms_idx);
89     return SA;
90 }
91 std::vector<int> suffix_array(const std::string& s, const char first = 'a'
92     ,
93     const char last = 'z') {
94     std::vector<int> vec(s.size() + 1);
95     std::copy(std::begin(s), std::end(s), std::begin(vec));
96     for (auto& x : vec) x -= (int)first - 1;
97     vec.back() = 0;
98     auto ret = SA_IS(vec, (int)last - (int)first + 2);
99     ret.erase(ret.begin());
100     return ret;
101 }
102 // Author: https://codeforces.com/blog/entry/12796?#comment-175287
103 // Uses kasai's algorithm linear in time and space
104 std::vector<int> LCP(const std::string& s, const std::vector<int>& sa) {
105     int n = s.size(), k = 0;
106     std::vector<int> lcp(n), rank(n);
107     for (int i = 0; i < n; i++) rank[sa[i]] = i;
108     for (int i = 0; i < n; i++, k ? k-- : 0) {
109         if (rank[i] == n - 1) {

```

```

110         continue;
111     }
112     int j = sa[rank[i] + 1];
113     while (i + k < n && j + k < n && s[i + k] == s[j + k]) k++;
114     lcp[rank[i]] = k;
115 }
116 lcp[n - 1] = 0;
117 return lcp;
118 }
119
120 template <typename T, class F = function<T(const T&, const T&)>>
121 class SparseTable {
122 public:
123     int n;
124     vector<vector<T>> mat;
125     F func;
126
127     SparseTable(const vector<T>& a, const F& f) : func(f) {
128         n = static_cast<int>(a.size());
129         int max_log = 32 - __builtin_clz(n);
130         mat.resize(max_log);
131         mat[0] = a;
132         for (int j = 1; j < max_log; j++) {
133             mat[j].resize(n - (1 << j) + 1);
134             for (int i = 0; i <= n - (1 << j); i++) {
135                 mat[j][i] = func(mat[j - 1][i], mat[j - 1][i + (1 << (j - 1))]);
136             }
137         }
138     }
139
140     T get(int from, int to) const {
141         assert(0 <= from && from <= to && to <= n - 1);
142         int lg = 32 - __builtin_clz(to - from + 1) - 1;
143         return func(mat[lg][from], mat[lg][to - (1 << lg) + 1]);
144     }
145 };

```

7.11 Z.cpp

```

1 template <typename T>
2 vector<int> z_function(int n, const T &s) {

```

```

3     vector<int> z(n, n);
4     int l = 0, r = 0;
5     for (int i = 1; i < n; i++) {
6         z[i] = (i > r ? 0 : min(r - i + 1, z[i - l]));
7         while (i + z[i] < n && s[z[i]] == s[i + z[i]]) {
8             z[i]++;
9         }
10        if (i + z[i] - 1 > r) {
11            l = i;
12            r = i + z[i] - 1;
13        }
14    }
15    return z;
16 }
17
18 template <typename T>
19 vector<int> z_function(const T &s) {
20     return z_function((int) s.size(), s);
21 }

```

8 Basic

8.1 AST.py

```

1 class Solution:
2     def calculate(self, s: str) -> int:
3         sign = ['+', '-', '*', '/'], '(', ')'
4         v = []; num = ''
5         for c in s:
6             if c in sign:
7                 if num:
8                     v.append(num); num = ''
9                 if c == '-' and (not v or v[-1] == '('):
10                    v.append('0')
11                v.append(c)
12            elif c.isnumeric():
13                num += c
14            if num: v.append(num)
15
16        stk0 = []; stk1 = []
17        for e in v:

```

```

18         if e.isnumeric():
19             stk0.append(e)
20         elif e in ['+', '-']:
21             while stk1 and stk1[-1] in ['*', '/', '+',
22                 '-']:
23                 stk0.append(stk1.pop())
24                 stk1.append(e)
25         elif e in ['*', '/', '(']:
26             stk1.append(e)
27         else:
28             while stk1 and stk1[-1] != '(':
29                 stk0.append(stk1.pop())
30             stk1.pop()
31     while stk1:
32         stk0.append(stk1.pop())
33
34     res = []
35     for e in stk0:
36         if e.isnumeric():
37             res.append(int(e))
38         else:
39             v = res.pop(); u = res.pop()
40             if e == '+':
41                 res.append(u + v)
42             elif e == '-':
43                 res.append(u - v)
44             elif e == '*':
45                 res.append(u * v)
46             elif e == '/':
47                 res.append(u // v)
48
49     return res[0]

```

8.2 bitset.cpp

```

1  template <int len = 1>
2  void solve(int n) {
3      if (n > len) {
4          solve<std::min(len*2, MAXLEN)>(n);
5          return;
6      }
7      // solution using bitset<len>

```

```

8  }
9
10 struct Bitset {
11     vector<ull> b;
12     int n;
13     Bitset(int x = 0) {
14         n = x;
15         b.resize((n + 63) / 64, 0);
16     }
17
18     int get(int x) {
19         return (b[x >> 6] >> (x & 63)) & 1;
20     }
21
22     void set(int x, int y) {
23         b[x >> 6] |= 1ULL << (x & 63);
24         if (!y) b[x >> 6] ^= 1ULL << (x & 63);
25     }
26
27     Bitset &operator&=(const Bitset &another) {
28         rep(i, 0, min(SZ(b), SZ(another.b)) - 1) {
29             b[i] &= another.b[i];
30         }
31         return (*this);
32     }
33
34     Bitset operator&(const Bitset &another) const {
35         return (Bitset(*this) &= another);
36     }
37
38     Bitset &operator|=(const Bitset &another) {
39         rep(i, 0, min(SZ(b), SZ(another.b)) - 1) {
40             b[i] |= another.b[i];
41         }
42         return (*this);
43     }
44
45     Bitset operator|(const Bitset &another) const {
46         return (Bitset(*this) |= another);
47     }
48
49     Bitset &operator^=(const Bitset &another) {

```

```

50     rep(i, 0, min(SZ(b), SZ(another.b)) - 1) {
51         b[i] ^= another.b[i];
52     }
53     return (*this);
54 }
55
56 Bitset operator^(const Bitset &another) const {
57     return (Bitset(*this) ^= another);
58 }
59
60 Bitset &operator>>=(int x) {
61     if (x & 63) {
62         rep(i, 0, SZ(b) - 2) {
63             b[i] >>= (x & 63);
64             b[i] ^= (b[i + 1] << (64 - (x & 63)));
65         }
66         b.back() >>= (x & 63);
67     }
68
69     x >>= 6;
70     rep(i, 0, SZ(b) - 1) {
71         if (i + x < SZ(b)) b[i] = b[i + x];
72         else b[i] = 0;
73     }
74     return (*this);
75 }
76
77 Bitset operator>>(int x) const {
78     return (Bitset(*this) >>= x);
79 }
80
81 Bitset &operator<<=(int x) {
82     if (x & 63) {
83         for (int i = SZ(b) - 1; i >= 1; i--) {
84             b[i] <<= (x & 63);
85             b[i] ^= b[i - 1] >> (64 - (x & 63));
86         }
87         b[0] <<= x & 63;
88     }
89
90     x >>= 6;
91     for (int i = SZ(b) - 1; i >= 0; i--) {

```

```

92         if (i - x >= 0) b[i] = b[i - x];
93         else b[i] = 0;
94     }
95     return (*this);
96 }
97
98 Bitset operator<<(int x) const {
99     return (Bitset(*this) <<= x);
100 }
101 };

```

8.3 fastIO.cpp

```

1 static struct FastInput {
2     static constexpr int BUF_SIZE = 1 << 20;
3     char buf[BUF_SIZE];
4     size_t chars_read = 0;
5     size_t buf_pos = 0;
6     FILE *in = stdin;
7     char cur = 0;
8
9     inline char get_char() {
10         if (buf_pos >= chars_read) {
11             chars_read = fread(buf, 1, BUF_SIZE, in);
12             buf_pos = 0;
13             buf[0] = (chars_read == 0 ? -1 : buf[0]);
14         }
15         return cur = buf[buf_pos++];
16     }
17
18     template <typename T>
19     inline void tie(T) {}
20
21     inline explicit operator bool() {
22         return cur != -1;
23     }
24
25     inline static bool is_blank(char c) {
26         return c <= ' ';
27     }
28

```



```

29 inline bool skip_blanks() {
30     while (is_blank(cur) && cur != -1) {
31         get_char();
32     }
33     return cur != -1;
34 }
35
36 inline FastInput& operator>>(char& c) {
37     skip_blanks();
38     c = cur;
39     get_char();
40     return *this;
41 }
42
43 inline FastInput& operator>>(string& s) {
44     if (skip_blanks()) {
45         s.clear();
46         do {
47             s += cur;
48         } while (!is_blank(get_char()));
49     }
50     return *this;
51 }
52
53 template <typename T>
54 inline FastInput& read_integer(T& n) {
55     // unsafe, doesn't check that characters are actually digits
56     n = 0;
57     if (skip_blanks()) {
58         int sign = +1;
59         if (cur == '-') {
60             sign = -1;
61             get_char();
62         }
63         do {
64             n += n * (n << 3) + cur - '0';
65         } while (!is_blank(get_char()));
66         n *= sign;
67     }
68     return *this;
69 }
70

```

```

71 template <typename T>
72 inline typename enable_if<is_integral<T>::value, FastInput&>::type
73     operator>>(T& n) {
74     return read_integer(n);
75 }
76
77 #if !defined(_WIN32) || defined(_WIN64)
78 inline FastInput& operator>>(__int128& n) {
79     return read_integer(n);
80 }
81 #endif
82
83 template <typename T>
84 inline typename enable_if<is_floating_point<T>::value, FastInput&>::type
85     operator>>(T& n) {
86     // not sure if really fast, for compatibility only
87     n = 0;
88     if (skip_blanks()) {
89         string s;
90         (*this) >> s;
91         sscanf(s.c_str(), "%lf", &n);
92     }
93     return *this;
94 }
95 } fast_input;
96
97 #define cin fast_input
98
99 static struct FastOutput {
100     static constexpr int BUF_SIZE = 1 << 20;
101     char buf[BUF_SIZE];
102     size_t buf_pos = 0;
103     static constexpr int TMP_SIZE = 1 << 20;
104     char tmp[TMP_SIZE];
105     FILE *out = stdout;
106
107     inline void put_char(char c) {
108         buf[buf_pos++] = c;
109         if (buf_pos == BUF_SIZE) {
110             fwrite(buf, 1, buf_pos, out);
111             buf_pos = 0;
112         }
113     }
114 }

```

```

111     }
112
113     ~FastOutput() {
114         fwrite(buf, 1, buf_pos, out);
115     }
116
117     inline FastOutput& operator<<(char c) {
118         put_char(c);
119         return *this;
120     }
121
122     inline FastOutput& operator<<(const char* s) {
123         while (*s) {
124             put_char(*s++);
125         }
126         return *this;
127     }
128
129     inline FastOutput& operator<<(const string& s) {
130         for (int i = 0; i < (int) s.size(); i++) {
131             put_char(s[i]);
132         }
133         return *this;
134     }
135
136     template <typename T>
137     inline char* integer_to_string(T n) {
138         // beware of TMP_SIZE
139         char* p = tmp + TMP_SIZE - 1;
140         if (n == 0) {
141             *--p = '0';
142         } else {
143             bool is_negative = false;
144             if (n < 0) {
145                 is_negative = true;
146                 n = -n;
147             }
148             while (n > 0) {
149                 *--p = (char) ('0' + n % 10);
150                 n /= 10;
151             }
152             if (is_negative) {

```

```

153                 *--p = '-';
154             }
155         }
156         return p;
157     }
158
159     template <typename T>
160     inline typename enable_if<is_integral<T>::value, char*>::type stringify(
161         T n) {
162         return integer_to_string(n);
163     }
164
165     #if !defined(_WIN32) || defined(_WIN64)
166     inline char* stringify(__int128 n) {
167         return integer_to_string(n);
168     }
169     #endif
170
171     template <typename T>
172     inline typename enable_if<is_floating_point<T>::value, char*>::type
173         stringify(T n) {
174         sprintf(tmp, "%.17f", n);
175         return tmp;
176     }
177
178     template <typename T>
179     inline FastOutput& operator<<(const T& n) {
180         auto p = stringify(n);
181         for (; *p != 0; p++) {
182             put_char(*p);
183         }
184         return *this;
185     }
186     } fast_output;
187
188     #define cout fast_output

```

8.4 FastMod.cpp

```

1 Description: Compute a % b about 5 times faster than usual, where b is
2 constant but not known at compile time. Returns a value congruent to a

```

```

3 (mod b) in the range [0, 2b).
4
5 typedef unsigned long long ull;
6 struct FastMod {
7     ull b, m;
8     FastMod(ull b) : b(b), m(-1ULL / b) {}
9     ull reduce(ull a) { // a % b + (0 or b)
10         return a - (ull)((__uint128_t(m) * a) >> 64) * b;
11     }
12 };

```

8.5 intervalContainer.cpp

```

1 Description: Add and remove intervals from a set of disjoint intervals.
2 Will merge the added interval with any overlapping intervals in the set
  when
3 adding. Intervals are [inclusive, exclusive).
4 Time: O (log N)
5
6 set<pii>::iterator addInterval(set<pii>& is, int L, int R) {
7     if (L == R) return is.end();
8     auto it = is.lower_bound({L, R}), before = it;
9     while (it != is.end() && it->first <= R) {
10         R = max(R, it->second);
11         before = it = is.erase(it);
12     }
13     if (it != is.begin() && (--it)->second >= L) {
14         L = min(L, it->first);
15         R = max(R, it->second);
16         is.erase(it);
17     }
18     return is.insert(before, {L, R});
19 }
20 void removeInterval(set<pii>& is, int L, int R) {
21     if (L == R) return;
22     auto it = addInterval(is, L, R);
23     auto r2 = it->second;
24     if (it->first == L) is.erase(it);
25     else (int&)it->second = L;
26     if (R != r2) is.emplace(R, r2);
27 }

```

8.6 lineContainer.cpp

```

1 /**
2  * Author: Simon Lindholm
3  * Date: 2017-04-20
4  * License: CC0
5  * Source: own work
6  * Description: Container where you can add lines of the form  $kx+m$ , and
   query maximum values at points  $x$ .
7  * Useful for dynamic programming ('`convex hull trick'').
8  * Time: O(\log N)
9  * Status: stress-tested
10 */
11 #pragma once
12
13 struct Line {
14     mutable ll k, m, p;
15     bool operator<(const Line& o) const { return k < o.k; }
16     bool operator<(ll x) const { return p < x; }
17 };
18
19 struct LineContainer : multiset<Line, less<>> {
20     // (for doubles, use inf = 1/.0, div(a,b) = a/b)
21     static const ll inf = LLONG_MAX;
22     ll div(ll a, ll b) { // floored division
23         return a / b - ((a ^ b) < 0 && a % b); }
24     bool isect(iterator x, iterator y) {
25         if (y == end()) return x->p = inf, 0;
26         if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
27         else x->p = div(y->m - x->m, x->k - y->k);
28         return x->p >= y->p;
29     }
30     void add(ll k, ll m) {
31         auto z = insert({k, m, 0}), y = z++, x = y;
32         while (isect(y, z)) z = erase(z);
33         if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
34         while ((y = x) != begin() && (--x)->p >= y->p)
35             isect(x, erase(y));
36     }
37     ll query(ll x) {
38         assert(!empty());
39         auto l = *lower_bound(x);

```

```

40     return l.k * x + l.m;
41 }
42 };

```

8.7 mint.cpp

```

1  template<int MOD, int RT> struct mint {
2      static const int mod = MOD;
3      static constexpr mint rt() { return RT; } // primitive root for FFT
4      int v; explicit operator int() const { return v; } // explicit -> don'
          t silently convert to int
5      mint():v(0) {}
6      mint(ll _v) { v = int((-MOD < _v && _v < MOD) ? _v : _v % MOD);
7          if (v < 0) v += MOD; }
8      bool operator==(const mint& o) const {
9          return v == o.v; }
10     friend bool operator!=(const mint& a, const mint& b) {
11         return !(a == b); }
12     friend bool operator<(const mint& a, const mint& b) {
13         return a.v < b.v; }
14
15     mint& operator+=(const mint& o) {
16         if ((v += o.v) >= MOD) v -= MOD;
17         return *this; }
18     mint& operator-=(const mint& o) {
19         if ((v -= o.v) < 0) v += MOD;
20         return *this; }
21     mint& operator*=(const mint& o) {
22         v = int((ll)v*o.v%MOD); return *this; }
23     mint& operator/=(const mint& o) { return (*this) *= inv(o); }
24     friend mint pow(mint a, ll p) {
25         mint ans = 1; assert(p >= 0);
26         for (; p; p /= 2, a *= a) if (p&1) ans *= a;
27         return ans; }
28     friend mint inv(const mint& a) { assert(a.v != 0);
29         return pow(a,MOD-2); }
30
31     mint operator-() const { return mint(-v); }
32     mint& operator++() { return *this += 1; }
33     mint& operator--() { return *this -= 1; }
34     friend mint operator+(mint a, const mint& b) { return a += b; }

```

```

35     friend mint operator-(mint a, const mint& b) { return a -= b; }
36     friend mint operator*(mint a, const mint& b) { return a *= b; }
37     friend mint operator/(mint a, const mint& b) { return a /= b; }
38 };
39
40 const int MOD=998244353;
41 using mi = mint<MOD,5>; // 5 is primitive root for both common mods
42
43 namespace simp {
44     vector<mi> fac,ifac,invn;
45     void check(int x) {
46         if (fac.empty()) {
47             fac={mi(1),mi(1)};
48             ifac={mi(1),mi(1)};
49             invn={mi(0),mi(1)};
50         }
51         while (SZ(fac)<=x) {
52             int n=SZ(fac),m=SZ(fac)*2;
53             fac.resize(m);
54             ifac.resize(m);
55             invn.resize(m);
56             for (int i=n;i<m;i++) {
57                 fac[i]=fac[i-1]*mi(i);
58                 invn[i]=mi(MOD-MOD/i)*invn[MOD%i];
59                 ifac[i]=ifac[i-1]*invn[i];
60             }
61         }
62     }
63     mi gfac(int x) {
64         check(x); return fac[x];
65     }
66     mi ginv(int x) {
67         check(x); return invn[x];
68     }
69     mi gifac(int x) {
70         check(x); return ifac[x];
71     }
72     mi binom(int n,int m) {
73         if (m < 0 || m > n) return mi(0);
74         return gfac(n)*gifac(m)*gifac(n - m);
75     }
76 }

```

8.8 pbds.cpp

```
1 #include <bits/extc++.h>
2 using namespace __gnu_cxx;
3 using namespace __gnu_pbds;
4
5 #include<ext/pb_ds/assoc_container.hpp>
6 #include<ext/pb_ds/tree_policy.hpp>
7 #include<ext/pb_ds/hash_policy.hpp>
8 #include<ext/pb_ds/trie_policy.hpp>
9 #include<ext/pb_ds/priority_queue.hpp>
10
11 pairing_heap_tag: 配对堆
12 thin_heap_tag: 斐波那契堆
13 binomial_heap_tag: 二项堆
14 binary_heap_tag: 二叉堆
15
16 __gnu_pbds::priority_queue<PII, greater<PII>, pairing_heap_tag> q;
17 __gnu_pbds::priority_queue<PII, greater<PII>, pairing_heap_tag>::
    point_iterator its[N];
18
19 its[v] = q.push({dis[v], v});
20 q.modify(its[v], {dis[v], v});
21
22 可以将两个优先队列中的元素合并（无任何约束）
23 使用方法为a.join(b)
24 此时优先队列b内所有元素就被合并进优先队列a中，且优先队列b被清空
25
26 cc_hash_table<string, int> mp1拉链表
27 gp_hash_table<string, int> mp2查探法
```

8.9 simu.cpp

```
1 pair<db,db> p[N];
2 db ans = 1e10;
3 db rd(db l, db r) {
4     uniform_real_distribution<db> u(l,r);
5     // uniform_int_distribution<ll> u(l,r);
6     default_random_engine e(rng());
7     return u(e); // e(rng)
8 }
9
```

```
10 db dist(pair<db,db> a, pair<db,db> b) {
11     db dx = a.fi - b.fi;
12     db dy = a.se - b.se;
13     // sqrtl() for long double
14     return sqrt(dx * dx + dy * dy);
15 }
16
17 db eval(pair<db,db> x) {
18     db res = 0;
19     rep(i, 1, n) res += dist(p[i], x);
20     ans = min(ans, res);
21     return res;
22 }
23
24 void simulate_anneal() {
25     pair<db,db> cnt(rd(0, 10000), rd(0, 10000));
26     for (double k = 10000; k > 1e-5; k *= 0.99) {
27         // [start, end, step]
28         pair<db,db> np(cnt.fi + rd(-k, k), cnt.se + rd(-k, k));
29         db delta = eval(np) - eval(cnt);
30         if (exp(-delta / k) > rd(0, 1)) cnt = np;
31     }
32 }
```

8.10 sort.cpp

```
1 void merge_sort(int q[], int l, int r) {
2     if (l >= r) return;
3     int mid = l + r >> 1;
4     merge_sort(q, l, mid);
5     merge_sort(q, mid + 1, r);
6
7     int k = 0, i = l, j = mid + 1;
8     while (i <= mid && j <= r)
9         if (q[i] <= q[j])
10             tmp[k++] = q[i++];
11         else
12             tmp[k++] = q[j++];
13
14     while (i <= mid)
15         tmp[k++] = q[i++];
```

```

16     while (j <= r)
17         tmp[k++] = q[j++];
18
19     for (i = l, j = 0; i <= r; i++, j++) q[i] = tmp[j];
20 }
21
22 void quick_sort(int q[], int l, int r) {
23     if (l >= r) return;
24     int i = l - 1, j = r + 1, x = q[l + r >> 1];
25     while (i < j) {
26         do i ++ ; while (q[i] < x);
27         do j -- ; while (q[j] > x);
28         if (i < j) swap(q[i], q[j]);
29     }
30     quick_sort(q, l, j), quick_sort(q, j + 1, r);
31 }
32
33 template<class T>
34 void radixsort(T *a, ll n) {
35     int base = 0;
36     rep(i, 1, n) sa[i] = i;
37     rep(k, 1, 5) {
38         rep(i, 0, 255) c[i] = 0;
39         rep(i, 1, n) c[(a[i] >> base) & 255]++;
40         rep(i, 1, 255) c[i] += c[i - 1];
41         per(i, n, 1) {
42             rk[sa[i]] = c[(a[sa[i]] >> base) & 255]--;
43         }
44         rep(i, 1, n) sa[rk[i]] = i;
45         base += 7;
46     }
47 }

```

8.11 高精度.cpp

```

1 vector<int> add(vector<int> &A, vector<int> &B) {
2     if (A.size() < B.size()) return add(B, A);
3     vector<int> C;
4     int t = 0;
5     for (int i = 0; i < A.size(); i ++ ) {
6         t += A[i];

```

```

7         if (i < B.size()) t += B[i];
8         C.push_back(t % 10);
9         t /= 10;
10    }
11    if (t) C.push_back(t);
12    return C;
13 }
14
15 vector<int> sub(vector<int> &A, vector<int> &B) {
16     vector<int> C;
17     for (int i = 0, t = 0; i < A.size(); i ++ ) {
18         t = A[i] - t;
19         if (i < B.size()) t -= B[i];
20         C.push_back((t + 10) % 10);
21         if (t < 0) t = 1;
22         else t = 0;
23     }
24     while (C.size() > 1 && C.back() == 0) C.pop_back();
25     return C;
26 }
27
28 vector<int> mul(vector<int> &A, int b) {
29     vector<int> C;
30     int t = 0;
31     for (int i = 0; i < A.size() || t; i ++ ) {
32         if (i < A.size()) t += A[i] * b;
33         C.push_back(t % 10);
34         t /= 10;
35     }
36     while (C.size() > 1 && C.back() == 0) C.pop_back();
37     return C;
38 }
39
40 vector<int> div(vector<int> &A, int b, int &r) {
41     vector<int> C;
42     r = 0;
43     for (int i = A.size() - 1; i >= 0; i -- ) {
44         r = r * 10 + A[i];
45         C.push_back(r / b);
46         r %= b;
47     }
48     reverse(C.begin(), C.end());

```

```
49     while (C.size() > 1 && C.back() == 0) C.pop_back();  
50     return C;
```

```
51 }
```