PeerEval: Learning Whose AI Judgments to Trust

Xinya Du, The University of Texas at Dallas

Arena Academic Partnerships Program, Fall 2026 12 months $50,000

Research objective

AI judges compare answers and decide which is better, but they can favor their own model family. Arena found a 37-percentage-point gap between three same-provider judges' preferences for their family and human votes [3]. We will extend our **Peer Rank and Discussion (PRD)** framework so that a panel learns judge weights from repeated peer-agreement calculations. The aim is to make collective evaluation reliable using the models' own reviews, with human votes used to test the results.

How PRD works, and what we will change

PRD gives each model two roles: answer writer and reviewer [1]. Models answer the same prompts and review anonymous pairs of answers. We start with equal reviewer weights, combine the reviews into answer scores, rescale and normalize each model's score, and use it as that model's reviewer weight in the next iteration. This repeats until the scores stabilize. PRD also lets reviewers discuss their disagreements. Its ranking rule assumes that a model that writes good answers is also a good judge; **we will instead test weights updated directly from agreement among judges**.

Our PeerEval leaderboard and tool implement this foundation [2]. A pilot covers 1,179 human-labeled battles with four judges. On 794 crowd battles, agreement weighting matched 67.8% of votes, versus 65.7% for equal weighting. These exploratory results motivate studying when agreement is useful evidence and when it repeats a shared bias.




Figure 1: Peer evaluation as an iterative weighting loop. Original PRD feeds answer-quality scores back into reviewer weights. Our proposed extension uses agreement with other model families. Each iteration reuses the collected reviews; it does not require a new round of model calls. Icons illustrate model families.

Project scope and requested support. Months 1–3 will reproduce PRD and establish data; months 4–8 will develop the agreement loop; months 9–12 will complete transfer tests and release a paper, code, and evaluation reports. The $50,000 gift allocates $36,000 to graduate research, including fringe and tuition; $10,000 to APIs and computing; and $4,000 to evaluation annotations. At maximum scale, 10,000 pairs $\times$ eight judges $\times$ two orders require 160,000 judging calls; pilot costs will set the affordable scale. Results will complement Arena's voting and AutoEval [4].

Research approach

1. Update judge weights from mutual agreement. Six to eight judges from different families will review anonymous answer pairs in both display orders, choosing A, B, tie, or both bad. We will align the orders and average each judge's votes. At iteration t, judge i receives an agreement score $a_i^{(t)}$: its mean agreement with the weighted votes of judges *outside its own model family*. This comparison excludes the judge's own vote and family. Starting from equal weights, we update

$$w_i^{(t+1)} = (1-\eta)w_i^{(t)} + \eta \frac{\varepsilon + a_i^{(t)}}{\sum_j (\varepsilon + a_j^{(t)})},$$

where $0 < \eta \leq 1$ controls how quickly weights change and $\varepsilon > 0$ keeps every judge eligible. We stop when weights stabilize or reach a fixed iteration limit. The final weighted votes determine answer preferences and model rankings. No human labels enter these updates.

2. Determine when the weighting loop is reliable. Agreement can reward a shared mistake, so we will study what prevents a group of similar judges from reinforcing itself. We will compare ordinary agreement, agreement excluding a judge's own family, and a version that limits any one family's total influence. We will analyze convergence, sensitivity to initialization, and how many correlated judges it takes to change a decision. Original PRD's answer-quality weights and a fixed combination of answer quality and agreement will serve as comparisons. These tests separate the benefit of the new update rule from simply adding more judges.

3. Test whether peer weights transfer to new questions and models. We will construct weights on development prompts, freeze them for unseen prompts, and compare this with recomputing weights on new unlabeled prompts. Later time windows and new answer-model families will test transfer. We will bootstrap questions and remove one judge family at a time to measure how stable the resulting rankings are. Instability will flag a result for additional review; we will test whether this flag predicts disagreement with people. For the proposed method, human votes are used only for evaluation.

Evaluation, outputs, and feasibility

We will use up to 10,000 public and, subject to agreement, recent Arena battles. Baselines include the strongest single judge, equal weighting, original PRD, static agreement weights, and weights fitted to limited human votes. We will measure preference accuracy, log loss, ranking agreement, stability, and cost, with paired bootstrap intervals that rerun the weighting loop. Length-matched tests, balanced longer/shorter-answer cases, and a length heuristic will check whether apparent gains come from verbosity. Repeated human votes and display-order metadata will help interpret disagreements. Shared biases may still limit gains; we will report those failure cases.

References

[1] Li R, Patel T, Du X. PRD: Peer Rank and Discussion Improve Large Language Model based Evaluations. TMLR, 2024. Paper.

[2] PeerEval. https://peereval-ai.github.io/; pilot results. 2026.

[3] Arena Team. Self-Preference of AI Judges. September 30, 2026. Article.

[4] Arena Team. Introducing AutoEval to the Arena leaderboards. July 30, 2026. Article.