



**POLYTECHNIQUE
MONTRÉAL**

UNIVERSITÉ
D'INGÉNIERIE




Matrix and Tensor Models for Spatiotemporal Traffic Data Imputation and Forecasting

Ph.D. Defense

Xinyu Chen

Polytechnique Montreal, Canada

December 11, 2023



Ph.D. Candidate
Xinyu Chen



Supervisor
Prof. Nicolas Saunier



Co-supervisor
Prof. Lijun Sun (McGill)


Outline

- **Background**
- **Literature Review**
 - Tensor Factorization
 - Tensor Factorization (TF)
- **Nonstationary Temporal Matrix Factorization**
- **Low-Rank Autoregressive Tensor Completion**
- **Laplacian Convolutional Representation**
 - Motivation
 - Reformulate Laplacian Regularization
 - Traffic Time Series Imputation
- **Hankel Tensor Factorization**
 - Motivation
 - Hankel Structure
- **Experiments**
- **Conclusion**

Multivariate Traffic Time Series

Many spatiotemporal traffic time series data are in the form of **matrix**.

- Example: Portland highway traffic data¹.



- $X \in \mathbb{R}^{N \times T}$ with N spatial locations \times T time steps
- Traffic volume/speed shows strong spatial/temporal dependencies

¹<https://portal.its.pdx.edu/home>

Multiple Data Behaviors

Spatiotemporal traffic data are time series, but they involve multiple data behaviors.

- Incompleteness & sparsity
- High-dimensionality
- Multidimensionality
- Noises & outliers
- Time-varying behavior
- Nonstationarity
-

In addition, spatiotemporal correlations are also very important.

Multiple Data Behaviors

Sparsity & high-dimensionality

- Uber (hourly) movement speed data²



NYC movement



Seattle movement


- The average speed on a given road segment for each hour of each day.
- Hourly speeds are computed when road segments have 5+ unique trips.
- **Issue:** insufficient sampling of ridesharing vehicles on the road network.

²<https://movement.uber.com/>


Multiple Data Behaviors

Sparsity & high-dimensionality

- **NYC** movement speed data (2019)
 - 98,210 road segments & 8,760 time steps (hours)
 - Overall missing rate: 64.43%





- **Seattle** movement speed data (2019)
 - 63,490 road segments & 8,760 time steps (hours)
 - Overall missing rate: 84.95%



Problem Formulation

- **Objective A:** Given a multivariate time series data like $\mathbf{Y} \in \mathbb{R}^{N \times T}$ or a multidimensional time series data like $\mathcal{Y} \in \mathbb{R}^{M \times N \times T}$, impute the missing values of the data.




[Q]

- How to reconstruct missing values from observed data?
- How to make use of spatiotemporal correlations?
- How to make use of traffic time series dynamics?

Problem Formulation

- **Objective C-1:** Given a partially observed data $\mathbf{Y} \in \mathbb{R}^{N \times T}$ consisting of time series $\mathbf{y}_1, \dots, \mathbf{y}_T \in \mathbb{R}^N$, forecast data points $\hat{\mathbf{y}}_{T+\delta}, \delta \in \mathbb{N}^+$.




[Q]


- How to learn from *high-dimensional* and *sparse* data?
- How to model *nonstationarity* in time series?
- How to perform forecasting on these time series?

Whole Picture


We are working on **spatiotemporal traffic data modeling**.



Spatiotemporal Traffic Data Imputation



Spatiotemporal Traffic Forecasting



Low-Rank Tensor Models

- Low-rank matrix/tensor completion



Candès & Recht'09: Convex nuclear norm minimization for matrix completion.

$$\begin{aligned} \min_{\mathbf{X}} \quad & \|\mathbf{X}\|_* \\ \text{s.t. } & \mathcal{P}_\Omega(\mathbf{X}) = \mathcal{P}_\Omega(\mathbf{Y}) \end{aligned}$$

Cai, Candès & Shen'10: Singular value thresholding algorithm.

$$\begin{cases} \mathbf{X}^\ell = \mathcal{D}_\tau(\mathbf{Z}^{\ell-1}) \\ \mathbf{Z}^\ell = \mathbf{Z}^{\ell-1} + \delta_\ell \mathcal{P}_\Omega(\mathbf{Y} - \mathbf{X}^\ell) \end{cases}$$

Zhang et al.'12: Nonconvex truncated nuclear norm minimization.


Liu et al.'13: Convex nuclear norm minimization for tensor completion.

$$\begin{aligned} \min_{\boldsymbol{\mathcal{X}}} \quad & \|\boldsymbol{\mathcal{X}}\|_* \\ \text{s.t. } & \mathcal{P}_\Omega(\boldsymbol{\mathcal{X}}) = \mathcal{P}_\Omega(\mathbf{Y}) \end{aligned}$$

Lu, Peng & Wei'19: Tensor nuclear norm induced by linear transform.

Tensor Factorization

- Revisit tensor factorization (TF)




Frank Lauren Hitchcock

Tamara G. Kolda

Ivan Oseledets

- **CP tensor factorization:** Factorize \mathcal{Y} into the combination of three rank- R factor matrices (i.e., low-dimensional latent factors).




Matrix Factorization

Low-Rank Matrix Factorization (Koren et al.'09)

Given any partially observed data matrix $\mathbf{Y} \in \mathbb{R}^{N \times T}$ with observed index set Ω , then the optimization problem of matrix factorization with rank R can be formulated as

$$\min_{\mathbf{W}, \mathbf{X}} \frac{1}{2} \|\mathcal{P}_\Omega(\mathbf{Y} - \mathbf{W}^\top \mathbf{X})\|_F^2 + \frac{\rho}{2} (\|\mathbf{W}\|_F^2 + \|\mathbf{X}\|_F^2)$$




- ✗ Cannot capture temporal correlations.
- ✗ Cannot perform time series forecasting.

Temporal Matrix Factorization

Temporal Matrix Factorization (Yu et al.'16; Chen & Sun'21)

Given any partially observed time series data $\mathbf{Y} \in \mathbb{R}^{N \times T}$ with observed index set Ω , then temporal matrix factorization assumes a d th-order vector autoregressive (VAR) process on the temporal factor matrix:

$$\begin{aligned} \min_{\mathbf{W}, \mathbf{X}, \{\mathbf{A}_k\}_{k=1}^d} \quad & \frac{1}{2} \|\mathcal{P}_\Omega(\mathbf{Y} - \mathbf{W}^\top \mathbf{X})\|_F^2 + \frac{\rho}{2} (\|\mathbf{W}\|_F^2 + \|\mathbf{X}\|_F^2) \\ & + \frac{\lambda}{2} \sum_{t=d+1}^T \left\| \mathbf{x}_t - \sum_{k=1}^d \mathbf{A}_k \mathbf{x}_{t-k} \right\|_2^2 \end{aligned}$$



\times VAR is usually built on stationary time series (temporal factors).

Nonstationary Temporal Matrix Factorization

Rewrite VAR in the form of matrix

Temporal operators

For any multivariate time series $\mathbf{X} \in \mathbb{R}^{R \times T}$ with $m, d \in \mathbb{N}^+$, if we define temporal operators as

$$\begin{aligned}\Psi_k &\triangleq \begin{bmatrix} \mathbf{0}_{(T-d-m) \times (d-k)} & -\mathbf{I}_{T-d-m} & \mathbf{0}_{(T-d-m) \times (k+m)} \end{bmatrix} \\ &+ \begin{bmatrix} \mathbf{0}_{(T-d-m) \times (d+m-k)} & \mathbf{I}_{T-d-m} & \mathbf{0}_{(T-d-m) \times k} \end{bmatrix} \\ &\in \mathbb{R}^{(T-d-m) \times T}, \quad k = 0, 1, \dots, d\end{aligned}$$

then

$$\begin{aligned}&\sum_{t=d+m+1}^T \|(\mathbf{x}_t - \mathbf{x}_{t-m}) - \sum_{k=1}^d \mathbf{A}_k (\mathbf{x}_{t-k} - \mathbf{x}_{t-m-k})\|_2^2 \\ &\equiv \|\mathbf{X}\Psi_0^\top - \sum_{k=1}^d \mathbf{A}_k \mathbf{X}\Psi_k^\top\|_F^2 \triangleq \|\mathbf{X}\Psi_0^\top - \mathbf{A}(\mathbf{I}_d \otimes \mathbf{X})\Psi^\top\|_F^2\end{aligned}$$

where $\mathbf{A} \triangleq [\mathbf{A}_1 \quad \cdots \quad \mathbf{A}_d]$ and $\Psi \triangleq [\Psi_1 \quad \cdots \quad \Psi_d]$.

Nonstationary Temporal Matrix Factorization

Nonstationary temporal matrix factorization (NoTMF)

Given any partially observed time series data $\mathbf{Y} \in \mathbb{R}^{N \times T}$ with observed index set Ω , then we assume a season- m differencing on the latent temporal factors:

$$\begin{aligned} \min_{\mathbf{W}, \mathbf{X}, \{\mathbf{A}_k\}_{k=1}^d} \quad & \frac{1}{2} \|\mathcal{P}_\Omega(\mathbf{Y} - \mathbf{W}^\top \mathbf{X})\|_F^2 + \frac{\rho}{2} (\|\mathbf{W}\|_F^2 + \|\mathbf{X}\|_F^2) \\ & + \frac{\lambda}{2} \sum_{t=d+m+1}^T \left\| (\mathbf{x}_t - \mathbf{x}_{t-m}) - \sum_{k=1}^d \mathbf{A}_k (\mathbf{x}_{t-k} - \mathbf{x}_{t-m-k}) \right\|_2^2 \end{aligned}$$

- First-order differencing $\mathbf{x}'_t = \mathbf{x}_t - \mathbf{x}_{t-1}$.
 - Second-order differencing $\mathbf{x}''_t = (\mathbf{x}_t - \mathbf{x}_{t-1}) - (\mathbf{x}_{t-1} - \mathbf{x}_{t-2})$.
 - Twice-differenced series $\mathbf{x}'''_t = (\mathbf{x}_t - \mathbf{x}_{t-m}) - (\mathbf{x}_{t-1} - \mathbf{x}_{t-m-1})$.
- ✓ Stationarizing a time series with differencing can improve the prediction.³

³Stationarity and differencing: <https://otexts.com/fpp2/stationarity.html>

Nonstationary Temporal Matrix Factorization

Rewrite NoTMF:

$$\begin{aligned} \min_{\mathbf{W}, \mathbf{X}, \mathbf{A}} \quad & \frac{1}{2} \|\mathcal{P}_\Omega(\mathbf{Y} - \mathbf{W}^\top \mathbf{X})\|_F^2 + \frac{\rho}{2} (\|\mathbf{W}\|_F^2 + \|\mathbf{X}\|_F^2) \\ & + \frac{\lambda}{2} \|\mathbf{X} \Psi_0^\top - \mathbf{A} (\mathbf{I}_d \otimes \mathbf{X}) \Psi^\top\|_F^2 \end{aligned}$$

Alternating minimization method:

- w.r.t. \mathbf{W} :

$$\frac{\partial f}{\partial \mathbf{W}} = -\mathbf{X} \mathcal{P}_\Omega^\top (\mathbf{Y} - \mathbf{W}^\top \mathbf{X}) + \rho \mathbf{W} = \mathbf{0}$$

- w.r.t. \mathbf{X} :

$$\frac{\partial f}{\partial \mathbf{X}} = -\mathbf{W} \mathcal{P}_\Omega (\mathbf{Y} - \mathbf{W}^\top \mathbf{X}) + \rho \mathbf{X} + \lambda \sum_{k=0}^d \mathbf{A}_k^\top \left(\sum_{h=0}^d \mathbf{A}_h \mathbf{X} \Psi_h^\top \right) \Psi_k = \mathbf{0}$$

- w.r.t. \mathbf{A} :

$$\mathbf{A} = \mathbf{X} \Psi_0^\top [(\mathbf{I}_d \otimes \mathbf{X}) \Psi^\top]^\dagger$$

Nonstationary Temporal Matrix Factorization

NoTMF forecasting on streaming data?

- NoTMF: Use \mathbf{Y}_t to estimate $\{\mathbf{W}, \mathbf{X}, \mathbf{A}\}$.

$$\underbrace{\mathbf{Y}_t}_{\in \mathbb{R}^{N \times t}} = \begin{matrix} ? & & & ? \\ & ? & & ? \\ ? & & ? & \end{matrix}$$


$$R \left(\begin{matrix} \mathbf{x}_{t-3} & \mathbf{x}_{t-2} & \mathbf{x}_{t-1} & \mathbf{x}_t & \mathbf{x}_{t+1} \\ t-3 & t-2 & t-1 & t & t+1 \end{matrix} \right) \hat{\mathbf{x}}_{t+1} = \mathbf{x}_{t+1-m} + \text{VAR}(d, m)$$

time step


Nonstationary Temporal Matrix Factorization

NoTMF forecasting on streaming data?

- NoTMF: Use \mathbf{Y}_t to estimate $\{\mathbf{W}, \mathbf{X}, \mathbf{A}\}$.



- Online forecasting (Gultekin & Paisley'18): Fix \mathbf{W} and use \mathbf{Y}_{t+1} to update $\{\mathbf{X}, \mathbf{A}\}$.



Low-Rank Autoregressive Tensor Completion

Low-rank matrix completion (Candès & Recht'09)

For any partially observed data matrix $\mathbf{Y} \in \mathbb{R}^{N \times T}$ with observed index set Ω , then low-rank matrix completion takes the form of

$$\begin{aligned} & \min_{\mathbf{X}} \|\mathbf{X}\|_* \\ & \text{s.t. } \mathcal{P}_\Omega(\mathbf{X}) = \mathcal{P}_\Omega(\mathbf{Y}). \end{aligned}$$

Low-rank tensor completion (Liu et al.'13)

For any partially observed data matrix $\mathbf{Y} \in \mathbb{R}^{M \times N \times T}$ with observed index set Ω , then low-rank matrix completion takes the form of

$$\begin{aligned} & \min_{\boldsymbol{\mathcal{X}}} \|\boldsymbol{\mathcal{X}}\|_* \\ & \text{s.t. } \mathcal{P}_\Omega(\boldsymbol{\mathcal{X}}) = \mathcal{P}_\Omega(\mathbf{Y}). \end{aligned}$$


- **Limitation:** Only cover the global consistency.
- **Comment:** For modeling spatiotemporal traffic data, local consistency (e.g., temporal correlations) is also important.

Low-Rank Autoregressive Tensor Completion

Optimization problem:

$$\begin{aligned} \min_{\mathcal{X}} \quad & \|\mathcal{X}\|_* + \frac{\lambda}{2} \sum_{n=1}^N \sum_{t=d+1}^T (z_{n,t} - \sum_{k=1}^d a_{n,k} z_{n,t-k})^2 \\ \text{s.t. } & \begin{cases} \mathcal{X} = \mathcal{Q}(Z), \\ \mathcal{P}_{\Omega}(Z) = \mathcal{P}_{\Omega}(Y). \end{cases} \end{aligned}$$


- **Advantage:** Global consistency + local consistency.




Laplacian Convolutional Representation

Motivation: Time series imputation

- Global trends (e.g., long-term quasi-seasonality & daily/weekly rhythm):



- Local trends (e.g., short-term time series trends):




- [Question] How to characterize both global and local trends in sparse time series data?

Laplacian Convolutional Representation

[Local trend modeling] Reformulate temporal regularization with circular convolution.

- Intuition of (circulant) Laplacian matrix.



- Define Laplacian kernel:

$$\boldsymbol{\ell} \triangleq (2, -1, 0, 0, -1)^\top$$

\Downarrow

$$\boldsymbol{\ell} \triangleq (\underbrace{2\tau}_{\text{degree}}, \underbrace{-1, \dots, -1}_\tau, 0, \dots, 0, \underbrace{-1, \dots, -1}_\tau)^\top \in \mathbb{R}^T$$

for any time series $\mathbf{x} = (x_1, \dots, x_T)^\top \in \mathbb{R}^T$.

- (Laplacian) Temporal regularization:

$$\mathcal{R}_\tau(\mathbf{x}) = \frac{1}{2} \|\mathbf{L}\mathbf{x}\|_2^2 = \frac{1}{2} \|\boldsymbol{\ell} * \mathbf{x}\|_2^2$$


Laplacian Convolutional Representation

Laplacian Convolutional Representation (LCR)

For any partially observed time series $\mathbf{y} \in \mathbb{R}^T$ with observed index set Ω , LCR utilizes circulant matrix and Laplacian kernel to characterize **global and local trends** in time series, respectively, i.e.,

$$\begin{aligned} & \min_{\mathbf{x}} \|\mathcal{C}(\mathbf{x})\|_* + \frac{\gamma}{2} \|\ell * \mathbf{x}\|_2^2 \\ & \text{s.t. } \|\mathcal{P}_\Omega(\mathbf{x} - \mathbf{y})\|_2 \leq \epsilon \end{aligned}$$

where $\mathcal{C} : \mathbb{R}^T \rightarrow \mathbb{R}^{T \times T}$ denotes the circulant operator. $\|\cdot\|_*$ denotes the nuclear norm of matrix, namely, the sum of singular values.



Laplacian Convolutional Representation

- Augmented Lagrangian function:

$$\mathcal{L}(\mathbf{x}, \mathbf{z}, \mathbf{w}) = \|\mathcal{C}(\mathbf{x})\|_* + \frac{\gamma}{2} \|\ell \star \mathbf{x}\|_2^2 + \frac{\lambda}{2} \|\mathbf{x} - \mathbf{z}\|_2^2 + \langle \mathbf{w}, \mathbf{x} - \mathbf{z} \rangle + \frac{\eta}{2} \|\mathcal{P}_\Omega(\mathbf{z} - \mathbf{y})\|_2^2$$

where $\mathbf{w} \in \mathbb{R}^T$ is the Lagrange multiplier, and $\langle \cdot, \cdot \rangle$ denotes the inner product.

- The ADMM scheme:

$$\begin{cases} \mathbf{x} := \arg \min_{\mathbf{x}} \mathcal{L}(\mathbf{x}, \mathbf{z}, \mathbf{w}) & \text{(Nuclear norm minimization)} \\ \mathbf{z} := \arg \min_{\mathbf{z}} \mathcal{L}(\mathbf{x}, \mathbf{z}, \mathbf{w}) & \text{(Closed-form solution)} \\ = \frac{1}{\lambda + \eta} \mathcal{P}_\Omega(\lambda \mathbf{x} + \mathbf{w} + \eta \mathbf{y}) + \frac{1}{\lambda} \mathcal{P}_\Omega^\perp(\lambda \mathbf{x} + \mathbf{w}) \\ \mathbf{w} := \mathbf{w} + \lambda(\mathbf{x} - \mathbf{z}) & \text{(Standard update)} \end{cases}$$

- Optimize \mathbf{x} ?

$$\|\mathcal{C}(\mathbf{x})\|_* = \|\mathcal{F}(\mathbf{x})\|_1 \quad \& \quad \frac{1}{2} \|\ell \star \mathbf{x}\|_2^2 = \frac{1}{2T} \|\mathcal{F}(\ell) \circ \mathcal{F}(\mathbf{x})\|_2^2$$

Nuclear norm minimization \Rightarrow **ℓ_1 -norm minimization with FFT** (in $\mathcal{O}(T \log T)$ time).

Laplacian Convolutional Representation

- Optimize \mathbf{x} via FFT (in $\mathcal{O}(T \log T)$ time):

$$\begin{aligned}\mathbf{x} &:= \arg \min_{\mathbf{x}} \|\mathcal{C}(\mathbf{x})\|_* + \frac{\gamma}{2} \|\ell * \mathbf{x}\|_2^2 + \frac{\lambda}{2} \|\mathbf{x} - \mathbf{z} + \mathbf{w}/\lambda\|_2^2 \\ \implies \hat{\mathbf{x}} &:= \arg \min_{\hat{\mathbf{x}}} \|\hat{\mathbf{x}}\|_1 + \frac{\gamma}{2T} \|\hat{\ell} \circ \hat{\mathbf{x}}\|_2^2 + \frac{\lambda}{2T} \|\hat{\mathbf{x}} - \hat{\mathbf{z}} + \hat{\mathbf{w}}/\lambda\|_2^2\end{aligned}$$

where we introduce $\{\hat{\ell}, \hat{\mathbf{x}}, \hat{\mathbf{z}}, \hat{\mathbf{w}}\} \triangleq \mathcal{F}\{\ell, \mathbf{x}, \mathbf{z}, \mathbf{w}\}$ (i.e., FFT).

ℓ_1 -norm Minimization in Complex Space (Liu & Zhang'23)

For any optimization problem in the form of ℓ_1 -norm minimization in complex space:

$$\min_{\hat{\mathbf{x}}} \|\hat{\mathbf{x}}\|_1 + \frac{\omega}{2} \|\hat{\mathbf{x}} - \hat{\mathbf{h}}\|_2^2$$

with complex-valued vectors $\hat{\mathbf{x}}, \hat{\mathbf{h}} \in \mathbb{C}^T$ and weight parameter ω , element-wise, the solution is given by


$$\hat{x}_t := \frac{\hat{h}_t}{|\hat{h}_t|} \cdot \max\{0, |\hat{h}_t| - 1/\omega\}, t = 1, \dots, T.$$

Laplacian Convolutional Representation


Empirical time complexity

On the synthetic data $\mathbf{y} \in \mathbb{R}^T$ with $T \in \{2^{10}, 2^{11}, \dots, 2^{20}\}$

- Ours: **LCR**
 - An FFT implementation in $\mathcal{O}(T \log T)$
 - The logarithmic factor $\log T$ makes the FFT highly efficient
- Baseline: **ConvNNM** (Convolution nuclear norm minimization, Liu & Zhang'23)
 - Convolution matrix $\mathcal{C}_{\tilde{\tau}}(\mathbf{y}) \in \mathbb{R}^{T \times \tilde{\tau}}$ with kernel size $\tilde{\tau} \in \mathbb{N}^+$
 - Singular value thresholding in $\mathcal{O}(\tilde{\tau}^2 T)$




ConvNNM vs. LCR




LCR

Motivation: Spatiotemporal data reconstruction

- Speed field reconstruction problem in vehicular traffic flow.



200-by-500 matrix
(NGSIM) \Downarrow Reconstruct speed field from
5% sparse trajectories?




- How to learn from sparse spatiotemporal data?
- How to characterize spatial/temporal dependencies?

Hankel Tensor Factorization

- Hankel matrix
 - Given $\mathbf{x} = (1, 2, 3, 4, 5)^\top$ and window length $\tau = 2$, we have

$$\mathcal{H}_\tau(\mathbf{x}) = \begin{bmatrix} 1 & 2 \\ 2 & 3 \\ 3 & 4 \\ 4 & 5 \end{bmatrix} \in \mathbb{R}^{4 \times 2}$$



Hankel matrix (Source: Twitter)

Hankel Tensor Factorization

- Hankel matrix

- On time series $\mathbf{y} = (y_1, y_2, \dots, y_5)^\top$ with $\tau = 2$:

$$\mathcal{H}_\tau(\mathbf{y}) = \begin{bmatrix} y_1 & y_2 \\ y_2 & y_3 \\ y_3 & y_4 \\ y_4 & y_5 \end{bmatrix} \approx \begin{bmatrix} v_1 \\ v_2 \\ v_3 \\ v_4 \end{bmatrix} \otimes \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$$

$$\implies \hat{\mathbf{y}} = \begin{bmatrix} \hat{y}_1 \\ \hat{y}_2 \\ \hat{y}_3 \\ \hat{y}_4 \\ \hat{y}_5 \end{bmatrix} = \mathcal{H}_\tau^{-1} \left(\begin{bmatrix} v_1 x_1 & v_1 x_2 \\ v_2 x_1 & v_2 x_2 \\ v_3 x_1 & v_3 x_2 \\ v_4 x_1 & v_4 x_2 \end{bmatrix} \right) = \begin{bmatrix} v_1 x_1 \\ (v_1 x_2 + v_2 x_1)/2 \\ (v_2 x_2 + v_3 x_1)/2 \\ (v_3 x_2 + v_4 x_1)/2 \\ v_4 x_2 \end{bmatrix}$$


- Automatic temporal modeling.

Hankel Tensor Factorization

- Hankel tensor: Given any matrix $\mathbf{X} \in \mathbb{R}^{N \times T}$, we have

$$\mathcal{X} \triangleq \mathcal{H}_{\tau_1, \tau_2}(\mathbf{X})$$

- Window lengths: $\tau_1, \tau_2 \in \mathbb{N}^+$;
- Tensor size: $(N - \tau_1 + 1) \times \tau_1 \times (T - \tau_2 + 1) \times \tau_2$;



(Figure) 4th order Hankel tensor: A sequence of third-order tensors.

- Slice: $\mathcal{X}_{:,k_1,:,k_2}$, $\forall k_1, k_2$;
- Slice size: $(N - \tau_1 + 1) \times (T - \tau_2 + 1)$.

Hankel Tensor Factorization


Hankel indexing:

- Sampling function for the Hankelization:

$$\theta_{k_1, k_2}(\mathbf{X}) \triangleq [\mathcal{H}_{\tau_1, \tau_2}(\mathbf{X})]_{:, k_1, :, k_2},$$

referring to the tensor slice with $k_1 \in \{1, \dots, \tau_1\}$, $k_2 \in \{1, \dots, \tau_2\}$.

- [Importance] Developing memory-efficient algorithms.



- Tensor slices $\theta_{k_1, k_2}(\mathbf{X})$ vs. data matrix \mathbf{X}

Hankel Tensor Factorization

Ours:

- Convolutional tensor decomposition (circular convolution \star_{row}):

$$\theta_{k_1, k_2}(\mathbf{Y}) \approx (\mathbf{Q} \star_{\text{row}} \mathbf{s}_{k_1}^{\top})(\mathbf{U} \star_{\text{row}} \mathbf{v}_{k_2}^{\top})^{\top}$$

Baselines:


- CP tensor decomposition (Khatri-Rao product \odot):

$$\theta_{k_1, k_2}(\mathbf{Y}) \approx (\mathbf{Q} \odot \mathbf{s}_{k_1}^{\top})(\mathbf{U} \odot \mathbf{v}_{k_2}^{\top})^{\top}$$

- Tensor-train decomposition:

$$\theta_{k_1, k_2}(\mathbf{Y}) \approx (\mathbf{Q} \mathbf{S}_{k_1})(\mathbf{U} \mathbf{V}_{k_2})^{\top}$$

- $\{\mathbf{S}_{k_1}, \mathbf{V}_{k_2}\}$ are **circulant matrices** \Rightarrow convolutional decomposition
- $\{\mathbf{S}_{k_1}, \mathbf{V}_{k_2}\}$ are **diagonal matrices** \Rightarrow CP decomposition



Hankel Tensor Factorization

HTF (convolutional decomposition)

- Optimization problem:


$$\begin{aligned} \min_{\mathbf{Q}, \mathbf{S}, \mathbf{U}, \mathbf{V}} \quad & \frac{1}{2} \sum_{k_1, k_2} \left\| \mathcal{P}_{\Omega_{k_1, k_2}} (\theta_{k_1, k_2}(\mathbf{Y}) - (\mathbf{Q} \star_{\text{row}} \mathbf{s}_{k_1})(\mathbf{U} \star_{\text{row}} \mathbf{v}_{k_2})^\top) \right\|_F^2 \\ & + \frac{\rho}{2} (\|\mathbf{Q}\|_F^2 + \|\mathbf{S}\|_F^2 + \|\mathbf{U}\|_F^2 + \|\mathbf{V}\|_F^2) \end{aligned}$$

- Alternating minimization:


$$\left\{ \begin{array}{l} \mathbf{Q} := \{ \mathbf{Q} \mid \frac{\partial f}{\partial \mathbf{Q}} = \mathbf{0} \} \\ \mathbf{s}_{k_1} := \{ \mathbf{s}_{k_1} \mid \frac{\partial f}{\partial \mathbf{s}_{k_1}} = \mathbf{0} \}, \quad k_1 \in \{1, 2, \dots, \tau_1\} \\ \mathbf{U} := \{ \mathbf{U} \mid \frac{\partial f}{\partial \mathbf{U}} = \mathbf{0} \} \\ \mathbf{v}_{k_2} := \{ \mathbf{v}_{k_2} \mid \frac{\partial f}{\partial \mathbf{v}_{k_2}} = \mathbf{0} \}, \quad k_2 \in \{1, 2, \dots, \tau_2\} \end{array} \right.$$

Whole Picture

We are working on **spatiotemporal traffic data modeling**.




Univariate Traffic Time Series Imputation



CircNNM:

$$\begin{aligned} & \min_{\mathbf{x}} \|\mathcal{C}(\mathbf{x})\|_* \\ \text{s. t. } & \|\mathcal{P}_\Omega(\mathbf{x} - \mathbf{y})\|_2 \leq \epsilon \end{aligned}$$


↓ Plus temporal regularization (TR)




LCR:

$$\begin{aligned} & \min_{\mathbf{x}} \|\mathcal{C}(\mathbf{x})\|_* + \frac{\gamma}{2} \|\ell \star \mathbf{x}\|_2^2 \\ \text{s. t. } & \|\mathcal{P}_\Omega(\mathbf{x} - \mathbf{y})\|_2 \leq \epsilon \end{aligned}$$


Univariate Traffic Time Series Imputation









↓ Mask 90% observations



↓ Reconstruct time series




Univariate Traffic Time Series Imputation




Spatiotemporal Traffic Data Imputation

LATC imputation

- Seattle freeway traffic speed data



- Portland highway traffic volume data



Background
oooooooo

Literature Review
oooo

NoTMF
oooooo

LATC
oo

LCR
oooooooo

HTF
ooooooooo


Experiments
oooo●ooo

Conclusion
ooo


Large-Scale Traffic Data Imputation

LCR


Extreme Missing Traffic Data Imputation




Sparse speed field




Ground truth speed field



MAPE = 51.92%



MAPE = 53.93%



Background
oooooooo

Literature Review
oooo

NoTMF
ooooooo

LATC
oo

LCR
oooooooo

HTF
oooooooooooo

Experiments
ooooooo●

Conclusion
ooo

Sparse Urban Traffic State Forecasting

NoTMF

Conclusion

Time-Varying Autoregression:

- (Highlight) Interpretable model with tensor factorization.
 - ✓ Parameter compression ✓ Pattern discovery

Laplacian Convolutional Representation:

- (Solution) Time series trend modeling in the low-rank framework?
 - Global time series trend modeling (low-rank model):

$$\begin{aligned} & \min_{\mathbf{x}} \|\mathcal{C}(\mathbf{x})\|_* \\ & \text{ s. t. } \|\mathcal{P}_\Omega(\mathbf{x} - \mathbf{y})\|_2 \leq \epsilon \end{aligned}$$

- Local time series trend modeling (temporal regularization):

$$\mathcal{R}_\tau(\mathbf{x}) = \frac{1}{2} \|\boldsymbol{\ell} * \mathbf{x}\|_2^2$$

- (Highlight) A unified framework with the **FFT** implementation.

Hankel Tensor Factorization:

- (Highlight) Memory-efficient **Hankel indexing** & convolutional parameterization.

Our studies:

- ② X. Chen, Z. Cheng, N. Saunier, L. Sun (2022). Laplacian convolutional representation for traffic time series imputation. arXiv preprint arXiv:2212.01529.
- ③ X. Chen, L. Sun (2022). Bayesian temporal factorization for multidimensional time series prediction. IEEE Transactions on Pattern Analysis and Machine Intelligence. 44 (9): 4659-4673.

GitHub repository:

- **transdim**: Machine learning for spatiotemporal traffic data imputation and forecasting. (1,000 stars & 270 forks on GitHub)
<https://github.com/xinychen/transdim>



POLYTECHNIQUE
MONTRÉAL

UNIVERSITÉ
D'INGÉNIERIE



Thank you for your attention!


Any Questions?

About me:

- Homepage: <https://xinychen.github.io>
- GitHub: <https://github.com/xinychen>
- How to reach me: chenxy346@gmail.com

What Is Tensors?


- What is tensor? $\mathbf{X} \in \mathbb{R}^{m \times n}$ vs. $\mathcal{X} \in \mathbb{R}^{m \times n \times t}$



- Tensors are everywhere!



Color image with
RGB channels



Dynamical system (fluid flow)

Appendix