



**POLYTECHNIQUE
MONTRÉAL**

UNIVERSITÉ
D'INGÉNIERIE




Matrix and Tensor Models for Spatiotemporal Traffic Data Modeling

Xinyu Chen

Polytechnique Montreal, Canada

August 23, 2023



Ph.D. Candidate
Xinyu Chen



Supervisor
Prof. Nicolas Saunier



Co-supervisor
Prof. Lijun Sun (McGill)

Outline

- **Motivation**

- Data-Driven ITS

- Traffic Time Series Imputation

- Speed Field Reconstruction

- **Laplacian Convolutional Representation**

- Motivation

- Reformulate Temporal Regularization

- LCR & Solution Algorithm

- Traffic Time Series Imputation

- **Hankel Tensor Factorization**

- Hankel Matrix/Tensor

- Hankel Indexing


- Hankel Tensor Factorization Formulas

- Reconstruction Results

- **Conclusion**

Motivation

- Portland highway traffic flow data¹




Traffic speed field

Highway network & sensor locations



- Speed field $\mathbf{Y} \in \mathbb{R}^{N \times T}$ (N locations & T time steps)
- Speed field shows strong spatial/temporal dependencies

¹<https://portal.its.pdx.edu/home>


Motivation



↓
Reconstruct
traffic volume?




↓
Reconstruct
traffic speed?



- How to utilize the global trends of traffic time series?
- How to produce local consistency of traffic data?


Motivation



200-by-500 matrix
(NGSIM)



Reconstruct speed field from
20% sparse trajectories?




- How to learn from sparse spatiotemporal data?
- How to characterize spatial/temporal local dependencies?


Laplacian Convolutional Representation

Time series imputation

- Global trends (e.g., long-term quasi-seasonality & daily/weekly rhythm):




- Local trends (e.g., short-term time series trends):



- [Question] How to characterize both global and local trends in sparse time series data?

Laplacian Convolutional Representation

- Intuition of (circulant) Laplacian matrix.



Undirected and circulant graph


Modeling

$$\mathbf{L} = \begin{bmatrix} 2 & -1 & 0 & 0 & -1 \\ -1 & 2 & -1 & 0 & 0 \\ 0 & -1 & 2 & -1 & 0 \\ 0 & 0 & -1 & 2 & -1 \\ -1 & 0 & 0 & -1 & 2 \end{bmatrix}$$

(Circulant) Laplacian matrix

Laplacian Convolutional Representation

- Intuition of (circulant) Laplacian matrix.



Modeling

$$\mathbf{L} = \begin{bmatrix} 2 & -1 & 0 & 0 & -1 \\ -1 & 2 & -1 & 0 & 0 \\ 0 & -1 & 2 & -1 & 0 \\ 0 & 0 & -1 & 2 & -1 \\ -1 & 0 & 0 & -1 & 2 \end{bmatrix}$$

(Circulant) Laplacian matrix

Laplacian Convolutional Representation

[Local trend modeling] Reformulate temporal regularization with circular convolution.

- Intuition of (circulant) Laplacian matrix.

The diagram illustrates the mapping between a graph structure and its corresponding Laplacian matrix. On the left, five nodes labeled x_1 , x_2 , x_3 , x_4 , and x_5 are arranged horizontally. Edges connect x_1 to x_2 and x_4 , x_2 to x_3 and x_5 , x_3 to x_4 , and x_4 to x_5 . Below this graph, the text "Undirected and circulant graph" is written. An arrow labeled "Modeling" points to the right, where the matrix \mathbf{L} is defined. The matrix \mathbf{L} is given as:

$$\mathbf{L} = \begin{bmatrix} 2 & -1 & 0 & 0 & -1 \\ -1 & 2 & -1 & 0 & 0 \\ 0 & -1 & 2 & -1 & 0 \\ 0 & 0 & -1 & 2 & -1 \\ -1 & 0 & 0 & -1 & 2 \end{bmatrix}$$

(Circulant) Laplacian matrix

- Define Laplacian kernel:

$$\boldsymbol{\ell} \triangleq (2, -1, 0, 0, -1)^\top$$

\Downarrow

$$\boldsymbol{\ell} \triangleq (\underbrace{2\tau}_{\text{degree}}, \underbrace{-1, \dots, -1}_\tau, 0, \dots, 0, \underbrace{-1, \dots, -1}_\tau)^\top \in \mathbb{R}^T$$

for any time series $\mathbf{x} = (x_1, \dots, x_T)^\top \in \mathbb{R}^T$.

- (Laplacian) Temporal regularization:

$$\mathcal{R}_\tau(\mathbf{x}) = \frac{1}{2} \|\mathbf{L}\mathbf{x}\|_2^2 = \frac{1}{2} \|\boldsymbol{\ell} \star \mathbf{x}\|_2^2$$


Laplacian Convolutional Representation

Laplacian Convolutional Representation (LCR)

For any partially observed time series $\mathbf{y} \in \mathbb{R}^T$ with observed index set Ω , LCR utilizes circulant matrix and Laplacian kernel to characterize **global and local trends** in time series, respectively, i.e.,

$$\begin{aligned} & \min_{\mathbf{x}} \|\mathcal{C}(\mathbf{x})\|_* + \frac{\gamma}{2} \|\ell * \mathbf{x}\|_2^2 \\ \text{s.t. } & \|\mathcal{P}_\Omega(\mathbf{x} - \mathbf{y})\|_2 \leq \epsilon \end{aligned}$$

where $\mathcal{C} : \mathbb{R}^T \rightarrow \mathbb{R}^{T \times T}$ denotes the circulant operator. $\|\cdot\|_*$ denotes the nuclear norm of matrix, namely, the sum of singular values.



Laplacian Convolutional Representation

- Augmented Lagrangian function:

$$\mathcal{L}(\mathbf{x}, \mathbf{z}, \mathbf{w}) = \|\mathcal{C}(\mathbf{x})\|_* + \frac{\gamma}{2} \|\ell \star \mathbf{x}\|_2^2 + \frac{\lambda}{2} \|\mathbf{x} - \mathbf{z}\|_2^2 + \langle \mathbf{w}, \mathbf{x} - \mathbf{z} \rangle + \frac{\eta}{2} \|\mathcal{P}_\Omega(\mathbf{z} - \mathbf{y})\|_2^2$$

where $\mathbf{w} \in \mathbb{R}^T$ is the Lagrange multiplier, and $\langle \cdot, \cdot \rangle$ denotes the inner product.


- The ADMM scheme:

$$\begin{cases} \mathbf{x} := \arg \min_{\mathbf{x}} \mathcal{L}(\mathbf{x}, \mathbf{z}, \mathbf{w}) & \text{(Nuclear norm minimization)} \\ \mathbf{z} := \arg \min_{\mathbf{z}} \mathcal{L}(\mathbf{x}, \mathbf{z}, \mathbf{w}) & \text{(Closed-form solution)} \\ = \frac{1}{\lambda + \eta} \mathcal{P}_\Omega(\lambda \mathbf{x} + \mathbf{w} + \eta \mathbf{y}) + \frac{1}{\lambda} \mathcal{P}_\Omega^\perp(\lambda \mathbf{x} + \mathbf{w}) \\ \mathbf{w} := \mathbf{w} + \lambda(\mathbf{x} - \mathbf{z}) & \text{(Standard update)} \end{cases}$$

- Optimize \mathbf{x} ?

$$\|\mathcal{C}(\mathbf{x})\|_* = \|\mathcal{F}(\mathbf{x})\|_1 \quad \& \quad \frac{1}{2} \|\ell \star \mathbf{x}\|_2^2 = \frac{1}{2T} \|\mathcal{F}(\ell) \circ \mathcal{F}(\mathbf{x})\|_2^2$$


Nuclear norm minimization $\Rightarrow \ell_1$ -norm minimization with FFT.



CircNNM:

$$\begin{aligned} & \min_{\boldsymbol{x}} \|\mathcal{C}(\boldsymbol{x})\|_* \\ \text{s. t. } & \|\mathcal{P}_\Omega(\boldsymbol{x} - \boldsymbol{y})\|_2 \leq \epsilon \end{aligned}$$

↓ Plus temporal regularization (TR)




LCR:

$$\begin{aligned} & \min_{\boldsymbol{x}} \|\mathcal{C}(\boldsymbol{x})\|_* + \frac{\gamma}{2} \|\boldsymbol{\ell} * \boldsymbol{x}\|_2^2 \\ \text{s. t. } & \|\mathcal{P}_\Omega(\boldsymbol{x} - \boldsymbol{y})\|_2 \leq \epsilon \end{aligned}$$


Hankel Tensor Factorization

Motivation: Spatiotemporal data reconstruction

- Speed field reconstruction problem in vehicular traffic flow.



200-by-500 matrix \downarrow Reconstruct speed field from
(NGSIM) 5% sparse trajectories?



- How to learn from sparse spatiotemporal data?
- How to characterize spatial/temporal dependencies?

Hankel Tensor Factorization

- Hankel matrix

- Given $\mathbf{x} = (1, 2, 3, 4, 5)^\top$ and window length $\tau = 2$, we have

$$\mathcal{H}_\tau(\mathbf{x}) = \begin{bmatrix} 1 & 2 \\ 2 & 3 \\ 3 & 4 \\ 4 & 5 \end{bmatrix} \in \mathbb{R}^{4 \times 2}$$




Hankel matrix (Source: Twitter)

Hankel Tensor Factorization

- Hankel tensor: Given any matrix $\mathbf{X} \in \mathbb{R}^{N \times T}$, we have

$$\mathcal{X} \triangleq \mathcal{H}_{\tau_1, \tau_2}(\mathbf{X})$$

- Window lengths: $\tau_1, \tau_2 \in \mathbb{N}^+$;
- Tensor size: $(N - \tau_1 + 1) \times \tau_1 \times (T - \tau_2 + 1) \times \tau_2$;



(Figure) 4th order Hankel tensor: A sequence of third-order tensors.

- Slice: $\mathcal{X}_{:,k_1,:,k_2}, \forall k_1, k_2$;
- Slice size: $(N - \tau_1 + 1) \times (T - \tau_2 + 1)$.

Hankel Tensor Factorization


Hankel indexing:

- Sampling function for the Hankelization:

$$\theta_{k_1, k_2}(\mathbf{X}) \triangleq [\mathcal{H}_{\tau_1, \tau_2}(\mathbf{X})]_{:, k_1, :, k_2},$$

referring to the tensor slice with $k_1 \in \{1, \dots, \tau_1\}$, $k_2 \in \{1, \dots, \tau_2\}$.

- [Importance]** Developing memory-efficient algorithms.



- Tensor slices $\theta_{k_1, k_2}(\mathbf{X})$ vs. data matrix \mathbf{X}

Hankel Tensor Factorization

Our model:

- Convolutional tensor decomposition (circular convolution \star_{row}):

$$\theta_{k_1, k_2}(\mathbf{Y}) \approx (\mathbf{Q} \star_{\text{row}} \mathbf{s}_{k_1}^{\top})(\mathbf{U} \star_{\text{row}} \mathbf{v}_{k_2}^{\top})^{\top}$$

Baselines:


- CP tensor decomposition (Khatri-Rao product \odot):


$$\theta_{k_1, k_2}(\mathbf{Y}) \approx (\mathbf{Q} \odot \mathbf{s}_{k_1}^{\top})(\mathbf{U} \odot \mathbf{v}_{k_2}^{\top})^{\top}$$

- Tensor-train decomposition:


$$\theta_{k_1, k_2}(\mathbf{Y}) \approx (\mathbf{Q} \mathbf{S}_{k_1})(\mathbf{U} \mathbf{V}_{k_2})^{\top}$$

- $\{\mathbf{S}_{k_1}, \mathbf{V}_{k_2}\}$ are **circulant matrices** \Rightarrow convolutional decomposition
- $\{\mathbf{S}_{k_1}, \mathbf{V}_{k_2}\}$ are **diagonal matrices** \Rightarrow CP decomposition







Sparse speed field




Ground truth speed field



MAPE = 51.92%



MAPE = 53.93%



MAPE = 56.48%

Conclusion

Laplacian Convolutional Representation:

- **(Starting point)** How to impute traffic time series?
 - ✓ Low-rank models ✓ Temporal regularization
- **(Solution)** Time series trend modeling in the low-rank framework?

- Global time series trend modeling (low-rank model):

$$\begin{aligned} \min_{\boldsymbol{x}} \quad & \|\mathcal{C}(\boldsymbol{x})\|_* \\ \text{s. t. } & \|\mathcal{P}_\Omega(\boldsymbol{x} - \boldsymbol{y})\|_2 \leq \epsilon \end{aligned}$$

- Local time series trend modeling (temporal regularization):

$$\mathcal{R}_\tau(\boldsymbol{x}) = \frac{1}{2} \|\boldsymbol{\ell} \star \boldsymbol{x}\|_2^2$$

- **(Highlight)** A unified framework with the **FFT** implementation.

Hankel Tensor Factorization:

- **(Highlight)** Memory-efficient **Hankel indexing** & **convolutional parameterization**.



Thanks for your attention!

Any Questions?


About me:

- 🏠 Homepage: <https://xinychen.github.io>
- 👤 GitHub: <https://github.com/xinychen>
- 💻 Blog: <https://medium.com/@xinyu.chen>
- ✉️ How to reach me: chenxy346@gmail.com

Appendix

Tensors


- What is tensor? $\mathbf{X} \in \mathbb{R}^{m \times n}$ vs. $\mathcal{X} \in \mathbb{R}^{m \times n \times t}$



- Tensors are everywhere!




Color image with
RGB channels




Dynamical system (fluid flow)

Appendix

- Revisit tensor factorization (TF)



- **CP tensor factorization:** Factorize \mathcal{Y} into the combination of three rank- R factor matrices (i.e., low-dimensional latent factors).



Appendix

LCR:

- Optimize \mathbf{x} via FFT (in $\mathcal{O}(T \log T)$ time):

$$\begin{aligned}\mathbf{x} &:= \arg \min_{\mathbf{x}} \|\mathcal{C}(\mathbf{x})\|_* + \frac{\gamma}{2} \|\hat{\ell} \star \mathbf{x}\|_2^2 + \frac{\lambda}{2} \|\mathbf{x} - \mathbf{z} + \mathbf{w}/\lambda\|_2^2 \\ \implies \hat{\mathbf{x}} &:= \arg \min_{\hat{\mathbf{x}}} \|\hat{\mathbf{x}}\|_1 + \frac{\gamma}{2T} \|\hat{\ell} \circ \hat{\mathbf{x}}\|_2^2 + \frac{\lambda}{2T} \|\hat{\mathbf{x}} - \hat{\mathbf{z}} + \hat{\mathbf{w}}/\lambda\|_2^2 \\ &= \arg \min_{\hat{\mathbf{x}}} \|\hat{\mathbf{x}}\|_1 + \frac{\lambda}{2T} \|\hat{\mathbf{x}} - (\lambda \hat{\mathbf{z}} - \hat{\mathbf{w}}) \oslash (\gamma \hat{\ell}^* \circ \hat{\ell} + \lambda \mathbb{1}_T)\|_2^2\end{aligned}$$

where we introduce $\{\hat{\ell}, \hat{\mathbf{x}}, \hat{\mathbf{z}}, \hat{\mathbf{w}}\} \triangleq \mathcal{F}\{\ell, \mathbf{x}, \mathbf{z}, \mathbf{w}\}$ (i.e., FFT).

ℓ_1 -norm Minimization in Complex Space (Liu & Zhang'23)

For any optimization problem in the form of ℓ_1 -norm minimization in complex space:

$$\min_{\hat{\mathbf{x}}} \|\hat{\mathbf{x}}\|_1 + \frac{\lambda}{2T} \|\hat{\mathbf{x}} - \hat{\mathbf{h}}\|_2^2$$

with complex-valued $\hat{\mathbf{x}}, \hat{\mathbf{h}} \in \mathbb{C}^T$, element-wise, the solution is given by

$$\hat{x}_t := \frac{\hat{h}_t}{|\hat{h}_t|} \cdot \max\{0, |\hat{h}_t| - T/\lambda\}, t = 1, \dots, T.$$

Appendix

- Hankel matrix

- On time series $\mathbf{y} = (y_1, y_2, \dots, y_5)^\top$ with $\tau = 2$:

$$\mathcal{H}_\tau(\mathbf{y}) = \begin{bmatrix} y_1 & y_2 \\ y_2 & y_3 \\ y_3 & y_4 \\ y_4 & y_5 \end{bmatrix} \approx \begin{bmatrix} \mathbf{v}_1 \\ \mathbf{v}_2 \\ \mathbf{v}_3 \\ \mathbf{v}_4 \end{bmatrix} \otimes \begin{bmatrix} \mathbf{x}_1 \\ \mathbf{x}_2 \end{bmatrix}$$

$$\implies \hat{\mathbf{y}} = \begin{bmatrix} \hat{y}_1 \\ \hat{y}_2 \\ \hat{y}_3 \\ \hat{y}_4 \\ \hat{y}_5 \end{bmatrix} = \mathcal{H}_\tau^{-1} \left(\begin{bmatrix} v_1 x_1 & v_1 x_2 \\ v_2 x_1 & v_2 x_2 \\ v_3 x_1 & v_3 x_2 \\ v_4 x_1 & v_4 x_2 \end{bmatrix} \right) = \begin{bmatrix} v_1 x_1 \\ (\mathbf{v}_1 \mathbf{x}_2 + \mathbf{v}_2 \mathbf{x}_1)/2 \\ (\mathbf{v}_2 \mathbf{x}_2 + \mathbf{v}_3 \mathbf{x}_1)/2 \\ (\mathbf{v}_3 \mathbf{x}_2 + \mathbf{v}_4 \mathbf{x}_1)/2 \\ \mathbf{v}_4 \mathbf{x}_2 \end{bmatrix}$$

- Automatic temporal modeling.

Appendix

HTF (convolutional decomposition)

- Optimization problem:

$$\begin{aligned} \min_{\mathbf{Q}, \mathbf{S}, \mathbf{U}, \mathbf{V}} \quad & \frac{1}{2} \sum_{k_1, k_2} \left\| \mathcal{P}_{\Omega_{k_1, k_2}} (\theta_{k_1, k_2}(\mathbf{Y}) - (\mathbf{Q} \star_{\text{row}} \mathbf{s}_{k_1})(\mathbf{U} \star_{\text{row}} \mathbf{v}_{k_2})^\top) \right\|_F^2 \\ & + \frac{\rho}{2} (\|\mathbf{Q}\|_F^2 + \|\mathbf{S}\|_F^2 + \|\mathbf{U}\|_F^2 + \|\mathbf{V}\|_F^2) \end{aligned}$$

- Alternating minimization:

$$\left\{ \begin{array}{l} \mathbf{Q} := \{ \mathbf{Q} \mid \frac{\partial f}{\partial \mathbf{Q}} = \mathbf{0} \} \\ \mathbf{s}_{k_1} := \{ \mathbf{s}_{k_1} \mid \frac{\partial f}{\partial \mathbf{s}_{k_1}} = \mathbf{0} \}, \quad k_1 \in \{1, 2, \dots, \tau_1\} \\ \mathbf{U} := \{ \mathbf{U} \mid \frac{\partial f}{\partial \mathbf{U}} = \mathbf{0} \} \\ \mathbf{v}_{k_2} := \{ \mathbf{v}_{k_2} \mid \frac{\partial f}{\partial \mathbf{v}_{k_2}} = \mathbf{0} \}, \quad k_2 \in \{1, 2, \dots, \tau_2\} \end{array} \right.$$