



**POLYTECHNIQUE
MONTRÉAL**


UNIVERSITÉ
D'INGÉNIERIE



Laplacian Convolutional Representation for Traffic Time Series Imputation


Xinyu Chen

July 19, 2023



Ph.D. Candidate

Xinyu Chen
Polytechnique Montréal



Postdoc

Dr. Zhanhong Cheng
McGill University



Supervisor

Prof. Nicolas Saunier
Polytechnique Montréal



Co-supervisor

Prof. Lijun Sun
McGill University

Current work:

- X. Chen, Z. Cheng, N. Saunier, L. Sun (2022). Laplacian convolutional representation for traffic time series imputation. arXiv preprint arXiv:2212.01529.

GitHub repository:

- **transdim**: Machine learning for spatiotemporal traffic data imputation and forecasting. (1,000+ stars & 270+ forks on GitHub)
<https://github.com/xinychen/transdim>

Slides:

- <https://xinychen.github.io/slides/LCR.pdf>

Outline

- **Motivation**

- Data-Driven ITS

- Time Series Imputation

- Speed Field Reconstruction

- **Revisit Laplacian Matrix & Circular Convolution**

- Laplacian Matrix

- Laplacian Regularization

- **Circulant Matrix Nuclear Norm Minimization**

- **Laplacian Convolutional Representation**

- Model Description

- Solution Algorithm

- **Experiments**


- Univariate Traffic Time Series Imputation

- Multivariate Model for Speed Field Reconstruction

- **Conclusion**

Motivation

- Portland highway traffic flow data¹



Traffic speed field

Highway network & sensor locations


- Speed field $\mathbf{Y} \in \mathbb{R}^{N \times T}$ (N locations & T time steps)
- Speed field shows strong spatial/temporal dependencies

¹<https://portal.its.pdx.edu/home>


Motivation

- How to reconstruct missing values from partial observations?

Motivation




200-by-500 matrix
(NGSIM) \Downarrow Reconstruct speed field from
20% sparse trajectories?



- How to learn from sparse spatiotemporal data?
- How to characterize spatial/temporal local dependencies?

Revisit Laplacian Matrix & Circular Convolution

- Intuition of (circulant) Laplacian matrix.



Undirected and circulant graph


Modeling

$$\mathbf{L} = \begin{bmatrix} 2 & -1 & 0 & 0 & -1 \\ -1 & 2 & -1 & 0 & 0 \\ 0 & -1 & 2 & -1 & 0 \\ 0 & 0 & -1 & 2 & -1 \\ -1 & 0 & 0 & -1 & 2 \end{bmatrix}$$

(Circulant) Laplacian matrix

Revisit Laplacian Matrix & Circular Convolution

- Intuition of (circulant) Laplacian matrix.



Undirected and circulant graph

Modeling

$$\mathbf{L} = \begin{bmatrix} 2 & -1 & 0 & 0 & -1 \\ -1 & 2 & -1 & 0 & 0 \\ 0 & -1 & 2 & -1 & 0 \\ 0 & 0 & -1 & 2 & -1 \\ -1 & 0 & 0 & -1 & 2 \end{bmatrix}$$

(Circulant) Laplacian matrix

Revisit Laplacian Matrix & Circular Convolution

Reformulate Laplacian regularization with circular convolution.

- Intuition of (circulant) Laplacian matrix.

Undirected and circulant graph

$$\xrightarrow{\text{Modeling}} \mathbf{L} = \begin{bmatrix} 2 & -1 & 0 & 0 & -1 \\ -1 & 2 & -1 & 0 & 0 \\ 0 & -1 & 2 & -1 & 0 \\ 0 & 0 & -1 & 2 & -1 \\ -1 & 0 & 0 & -1 & 2 \end{bmatrix}$$

(Circulant) Laplacian matrix

- Laplacian kernel: $\ell = (2, -1, 0, 0, -1)^\top$.

$$\mathbf{L}\mathbf{x} = \begin{bmatrix} 2 & -1 & 0 & 0 & -1 \\ -1 & 2 & -1 & 0 & 0 \\ 0 & -1 & 2 & -1 & 0 \\ 0 & 0 & -1 & 2 & -1 \\ -1 & 0 & 0 & -1 & 2 \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \\ x_3 \\ x_4 \\ x_5 \end{bmatrix} = \begin{bmatrix} 2 \\ -1 \\ 0 \\ 0 \\ -1 \end{bmatrix} \star \begin{bmatrix} x_1 \\ x_2 \\ x_3 \\ x_4 \\ x_5 \end{bmatrix} = \ell \star \mathbf{x}$$

where \star denotes the circular convolution.

- Local trend modeling via (Laplacian) temporal regularization:

$$\mathcal{R}(\mathbf{x}) = \frac{1}{2} \|\mathbf{L}\mathbf{x}\|_2^2 = \frac{1}{2} \|\ell \star \mathbf{x}\|_2^2$$

Revisit Laplacian Matrix & Circular Convolution

Reformulate Laplacian regularization with circular convolution.

- Define Laplacian kernel:

$$\boldsymbol{\ell} \triangleq (\underbrace{2\tau}_{\text{degree}}, \underbrace{-1, \dots, -1}_{\tau}, 0, \dots, 0, \underbrace{-1, \dots, -1}_{\tau})^\top \in \mathbb{R}^T$$

for any time series $\mathbf{x} = (x_1, \dots, x_T)^\top \in \mathbb{R}^T$.

- Local trend modeling via (Laplacian) temporal regularization:

$$\mathcal{R}_\tau(\mathbf{x}) = \frac{1}{2} \|\mathbf{L}\mathbf{x}\|_2^2 = \frac{1}{2} \|\boldsymbol{\ell} \star \mathbf{x}\|_2^2$$

- Property with discrete Fourier transform (denoted by $\mathcal{F}(\cdot)$):

$$\mathcal{R}_\tau(\mathbf{x}) = \frac{1}{2} \|\boldsymbol{\ell} \star \mathbf{x}\|_2^2 = \frac{1}{2} \|\mathcal{F}(\boldsymbol{\ell}) \circ \mathcal{F}(\mathbf{x})\|_2^2$$

Circulant Matrix Nuclear Norm Minimization

Circulant Matrix Nuclear Norm Minimization (CircNNM)

For any partially observed time series $\mathbf{y} \in \mathbb{R}^T$ with observed index set Ω , the optimization problem of CircNNM for reconstructing time series is given by

$$\begin{aligned} \min_{\mathbf{x}} \quad & \|\mathcal{C}(\mathbf{x})\|_* \\ \text{s.t. } & \|\mathcal{P}_\Omega(\mathbf{x} - \mathbf{y})\|_2 \leq \epsilon \end{aligned}$$

where $\mathcal{C} : \mathbb{R}^T \rightarrow \mathbb{R}^{T \times T}$ denotes the circulant operator. $\|\cdot\|_*$ denotes the nuclear norm of matrix, namely, the sum of singular values.

- An important property:

$$\|\mathcal{C}(\mathbf{x})\|_* = \|\mathcal{F}(\mathbf{x})\|_1$$

- CircNNM shows an efficient FFT implementation (Liu'22).


Laplacian Convolutional Representation

Laplacian Convolutional Representation (LCR)

For any partially observed time series $\mathbf{y} \in \mathbb{R}^T$ with observed index set Ω , LCR utilizes circulant matrix and Laplacian kernel to characterize **global and local trends** in time series, respectively, i.e.,

$$\min_{\mathbf{x}} \|\mathcal{C}(\mathbf{x})\|_* + \gamma \cdot \mathcal{R}_\tau(\mathbf{x})$$

$$\text{s.t. } \|\mathcal{P}_\Omega(\mathbf{x} - \mathbf{y})\|_2 \leq \epsilon$$



Laplacian Convolutional Representation

- LCR model:

$$\begin{aligned} \min_{\boldsymbol{x}} \quad & \|\mathcal{C}(\boldsymbol{x})\|_* + \gamma \cdot \mathcal{R}_\tau(\boldsymbol{x}) \\ \text{s.t.} \quad & \|\mathcal{P}_\Omega(\boldsymbol{x} - \boldsymbol{y})\|_2 \leq \epsilon \end{aligned}$$

- Augmented Lagrangian function:

$$\mathcal{L}(\boldsymbol{x}, \boldsymbol{z}, \boldsymbol{w}) = \|\mathcal{C}(\boldsymbol{x})\|_* + \frac{\gamma}{2} \|\boldsymbol{\ell} * \boldsymbol{x}\|_2^2 + \frac{\lambda}{2} \|\boldsymbol{x} - \boldsymbol{z}\|_2^2 + \langle \boldsymbol{w}, \boldsymbol{x} - \boldsymbol{z} \rangle + \frac{\eta}{2} \|\mathcal{P}_\Omega(\boldsymbol{z} - \boldsymbol{y})\|_2^2$$

where $\boldsymbol{w} \in \mathbb{R}^T$ is the Lagrange multiplier, and $\langle \cdot, \cdot \rangle$ denotes the inner product.

- The ADMM scheme:

$$\left\{ \begin{array}{l} \boldsymbol{x} := \arg \min_{\boldsymbol{x}} \mathcal{L}(\boldsymbol{x}, \boldsymbol{z}, \boldsymbol{w}) \\ \boldsymbol{z} := \arg \min_{\boldsymbol{z}} \mathcal{L}(\boldsymbol{x}, \boldsymbol{z}, \boldsymbol{w}) \\ = \frac{1}{\lambda + \eta} \mathcal{P}_\Omega(\lambda \boldsymbol{x} + \boldsymbol{w} + \eta \boldsymbol{y}) + \frac{1}{\lambda} \mathcal{P}_\Omega^\perp(\lambda \boldsymbol{x} + \boldsymbol{w}) \\ \boldsymbol{w} := \boldsymbol{w} + \lambda(\boldsymbol{x} - \boldsymbol{z}) \end{array} \right.$$

Laplacian Convolutional Representation

- Optimize \mathbf{x} via fast Fourier transform (in $\mathcal{O}(T \log T)$ time):

$$\begin{aligned}\mathbf{x} &:= \arg \min_{\mathbf{x}} \|\mathcal{C}(\mathbf{x})\|_* + \frac{\gamma}{2} \|\ell * \mathbf{x}\|_2^2 + \frac{\lambda}{2} \|\mathbf{x} - \mathbf{z} + \mathbf{w}/\lambda\|_2^2 \\ \implies \hat{\mathbf{x}} &:= \arg \min_{\hat{\mathbf{x}}} \|\hat{\mathbf{x}}\|_1 + \frac{\gamma}{2T} \|\hat{\ell} \circ \hat{\mathbf{x}}\|_2^2 + \frac{\lambda}{2T} \|\hat{\mathbf{x}} - \hat{\mathbf{z}} + \hat{\mathbf{w}}/\lambda\|_2^2 \\ &= \arg \min_{\hat{\mathbf{x}}} \|\hat{\mathbf{x}}\|_1 + \frac{\lambda}{2T} \|\hat{\mathbf{x}} - (\lambda \hat{\mathbf{z}} - \hat{\mathbf{w}}) \oslash (\lambda \hat{\ell}^* \circ \hat{\ell} + \lambda \mathbb{1}_T)\|_2^2\end{aligned}$$

where we introduce $\{\hat{\ell}, \hat{\mathbf{x}}, \hat{\mathbf{z}}, \hat{\mathbf{w}}\}$ referring to $\{\ell, \mathbf{x}, \mathbf{z}, \mathbf{w}\}$ in the frequency domain.

ℓ_1 -norm Minimization in Complex Space (Liu & Zhang'22)

For any optimization problem in the form of ℓ_1 -norm minimization in complex space:


$$\min_{\hat{\mathbf{x}}} \|\hat{\mathbf{x}}\|_1 + \frac{\lambda}{2T} \|\hat{\mathbf{x}} - \hat{\mathbf{h}}\|_2^2$$

with complex-valued $\hat{\mathbf{x}}, \hat{\mathbf{h}} \in \mathbb{C}^T$, element-wise, the solution is given by

$$\hat{x}_t := \frac{\hat{h}_t}{|\hat{h}_t|} \cdot \max\{0, |\hat{h}_t| - T/\lambda\}, t = 1, \dots, T.$$

Laplacian Convolutional Representation

- What is tensor? $\mathbf{X} \in \mathbb{R}^{m \times n}$ vs. $\mathbf{X} \in \mathbb{R}^{m \times n \times t}$




Two-Dimensional LCR (LCR-2D)

For any partially observed time series $\mathbf{Y} \in \mathbb{R}^{N \times T}$ with observed index set Ω , LCR can be formulated as follows,

$$\begin{aligned} \min_{\mathbf{X}} \quad & \|\mathcal{C}(\mathbf{X})\|_* + \frac{\gamma}{2} \|(\ell_s \ell^\top) \star \mathbf{X}\|_F^2 \\ \text{s.t. } & \|\mathcal{P}_\Omega(\mathbf{X} - \mathbf{Y})\|_F \leq \epsilon \end{aligned}$$

where $\mathcal{C} : \mathbb{R}^{N \times T} \rightarrow \mathbb{R}^{N \times N \times T \times T}$ denotes the circulant operator.


Experiments



CircNNM:

$$\begin{aligned} \min_{\boldsymbol{x}} \quad & \| \mathcal{C}(\boldsymbol{x}) \|_* \\ \text{s. t. } \quad & \| \mathcal{P}_\Omega(\boldsymbol{x} - \boldsymbol{y}) \|_2 \leq \epsilon \end{aligned}$$







↓ Plus temporal regularization




LCR:


$$\begin{aligned} \min_{\boldsymbol{x}} \quad & \| \mathcal{C}(\boldsymbol{x}) \|_* + \gamma \cdot \mathcal{R}_\tau(\boldsymbol{x}) \\ \text{s. t. } \quad & \| \mathcal{P}_\Omega(\boldsymbol{x} - \boldsymbol{y}) \|_2 \leq \epsilon \end{aligned}$$

Experiments







MAPE = 51.50% & RMSE = 4.86mph



MAPE = 46.94% & RMSE = 4.34mph



MAPE = 43.51% & RMSE = 1.65mph



MAPE = 41.29% & RMSE = 1.55mph

- QVC & LKC:

$$\begin{aligned} \min_{\mathbf{X}} \quad & \frac{\gamma}{2} \|(\ell_s \ell^\top) \star \mathbf{X}\|_F \\ \text{s.t. } & \|\mathcal{P}_\Omega(\mathbf{X} - \mathbf{Y})\|_F \leq \epsilon \end{aligned}$$

- CTNNM:

$$\begin{aligned} \min_{\mathbf{X}} \quad & \|\mathcal{C}(\mathbf{X})\|_* \\ \text{s.t. } & \|\mathcal{P}_\Omega(\mathbf{X} - \mathbf{Y})\|_F \leq \epsilon \end{aligned}$$

Conclusion

- **(Starting point)** How to reconstruct sparse speed field?
 - ✓ Matrix factorization (**MF**) ✓ Tensor factorization (**TF**)
- **(Highlight)** The importance of spatiotemporal modeling in low-rank methods?
 - Spatial/temporal **smoothing** regularization:

$$\begin{aligned} \min_{\mathbf{W}, \mathbf{X}} \quad & \frac{1}{2} \left\| \mathcal{P}_{\Omega}(\mathbf{Y} - \mathbf{W}^{\top} \mathbf{X}) \right\|_F^2 + \frac{\rho}{2} (\|\mathbf{W}\|_F^2 + \|\mathbf{X}\|_F^2) \\ & + \frac{\lambda}{2} (\|\mathbf{W} \Psi_1^{\top}\|_F^2 + \|\mathbf{X} \Psi_2^{\top}\|_F^2) \end{aligned}$$

- Automatic temporal modeling via **Hankelization**:

$$\min_{\mathbf{U}, \mathbf{V}, \mathbf{X}} \quad \frac{1}{2} \left\| \mathcal{P}_{\tilde{\Omega}} \left(\mathcal{H}_{\tau}(\mathbf{Y}) - \sum_{r=1}^R \mathbf{u}_r \otimes \mathbf{v}_r \otimes \mathbf{x}_r \right) \right\|_F^2$$

vs.

$$\min_{\mathbf{Q}, \mathbf{S}, \mathbf{U}, \mathbf{V}} \quad \frac{1}{2} \left\| \mathcal{P}_{\dot{\Omega}} \left(\mathcal{H}_{\tau_1, \tau_2}(\mathbf{Y}) - \sum_{r=1}^R \mathbf{q}_r \otimes \mathbf{s}_r \otimes \mathbf{u}_r \otimes \mathbf{v}_r \right) \right\|_F^2$$

- **(Challenge)** How to solve the **high memory consumption** issue in the Hankelization process?

References

A short list:

- [Liu'22] ×
- [Liu & Zhang'22] ×



POLYTECHNIQUE
MONTRÉAL

UNIVERSITÉ
D'INGÉNIERIE



Thanks for your attention!

Any Questions?

About me:

- 🏠 Homepage: <https://xinychen.github.io>
- 👤 GitHub: <https://github.com/xinychen> (3.4k+ stars)
- 💻 Blog: <https://medium.com/@xinyu.chen> (70k+ views)
- ✉️ How to reach me: chenxy346@gmail.com