



SCM International (US) Co., Ltd.



产品性能单 TYPICAL DATA SHEET

第一部分：基本信息 Basic Information

版本 Edition (201911)

产品名称 Product name	聚醚醚酮树脂 Polyetheretherketone resin
产品型号 Product grade	8200G
品牌 Brand	PFLUON

第二部分：性能指标 Specifications

材料性能 Properties	测试标准 Test standard	测试条件 Test conditions	单位 Unit	典型值 Typical Value
机械性能 Mechanical properties				
拉伸强度 Tensile strength	ISO527	23°C	MPa	98
断裂拉伸应变 Tensile Stress at Break	ISO527	23°C	%	25
拉伸模量 Tensile modulus	ISO527	23°C	GPa	3.7
弯曲强度 Bending strength	ISO178	23°C	MPa	165
弯曲模量 Bending modulus	ISO178	23°C	GPa	3.8
简支梁冲击强度 Charpy impact strength	ISO 179/1eA	23°C	KJ/m²	7
热性能 Thermal properties				
熔点 Melting point	ISO11357	DSC	°C	343
热变形温度 HDT	ISO 75	1.8Mpa	°C	152
玻璃化转变温度 Glass transition temp.	ISO11357	DSC	°C	150
流动特性 Fluidity				
熔融指数 MVR	ISO1133	380°C/5kg	cm³/10min	20
其他性能 Other properties				
密度 Density	ISO1183	23°C	g/cm³	1.3
易燃等级 Flammable grade	IEC60695	1.6mm	-	V-0

声明:本证书由本公司严格依照其检测标准检验出具,此证书并不免除客户收货时检验产品的义务。同时此证书不具有任何形式的对第三者的承诺,且仅适用于产品的常规基本性能信息参考。此为电子版检验证书,无需签字生效。 Statement: This certificate has been prepared with care and the best of our knowledge as part of the testing system of ZHEJIANG PFLUON TECHNOLOGY CO., LTD. However, it does not relieve our customers of their obligation to inspect the goods upon receipt or establish any warranties to third parties, and it is only a reference to the general basic performance information of the product. The document issued electronically, valid without signature.