SonicShine

Single-tank F / FH / F+ reference

2026 catalogue reference / 2026 目录参考

This reference organizes equipment information from the supplied SONIC SHINE 2026 catalogue. The source is a recovered candidate edition; its historical version has not been confirmed. Confirm current values and configuration in the order specification.

本资料整理所提供 SONIC SHINE 2026 目录中的设备信息。来源为候选补存版本，历史版本未证实。当前型号数值及配置应以订货技术规格确认为准。

Source catalogue spreads: 12

Tank capacity is not a usable basket rating. Confirm capacity convention, basket dimensions and load, frequency mode, electrical supply and ultrasonic-power definition. Stage power values are not automatically whole-line electrical demand.

槽体容量不等于有效篮筐或载荷能力。需确认容量口径、篮筐尺寸及载重、频率模式、电源和超声功率定义。工位功率不能自动当作整线接入负荷。

Catalogue photographs do not establish every feature supplied for your order. No customer-project result or certification status is established by this extract.

目录图片不代表订购设备包含图片中的全部功能。本摘录不用于证明客户项目效果或当前认证状态。

Current specification and matching operation manual: postmaster@gzsonicshine.com

Single-tank F-series / 单槽 F 系列

Catalogue reference; current configuration requires confirmation. / 目录参考，当前配置需另行确认。



Reference model / 型号	Capacity L; tank mm; ultrasonic W; heating W / 容量、槽体、超声与加热功率
SN-1012F	38 L · 500 × 300 × 250 mm · 720 W · 1500 W
SN-1018F	61 L · 500 × 350 × 350 mm · 1080 W · 1500 W
SN-1024F	88 L · 550 × 400 × 400 mm · 1440 W · 3000 W
SN-1030F	108 L · 600 × 450 × 400 mm · 1800 W · 3000 W
SN-1060F	264 L · 800 × 600 × 550 mm · 3600 W · 6000 W
SN-10120F	640 L · 1000 × 800 × 800 mm · 7200 W · 12000 W

Source: supplied 2026 catalogue spread 12. Listed frequency 28/40 kHz; bath temperature room temperature to 80 ° C. Frequency mode and ultrasonic-power convention are not defined in the source. Basket dimensions and load must be confirmed separately. / 来源：所提供 2026 目录第 12 跨页。列示频率 28/40 kHz，槽温室温至 80 ° C。原表未解释频率模式及超声功率口径；篮筐尺寸和载重另行确认。