

IDMA 2026

Problem set 1

Abdulkareem Al-Rifai, kbt185

16-02-26

Contents

1	Different representations of integers	2
1.a	Write the binary number $(110)_2$ in decimal notation	2
1.b	Write the decimal number 110 in binary notation	2
1.c	Write the octal number $(110)_8$ in decimal notation	2
2	Find the greatest common divisor using the algorithm we learned, show the steps then express d as linear combination of m and n	3
2.a	m=38, n=14	3
2.b	m=117, n=69	3
3	Consider the following algorithm	3
3.a	Explain what the algorithm does, and what are the number stored and computed in A	3
3.b	4
3.c	4
4		4
4.a	4
4.b	4
4.c	4

1 Different representations of integers

1.a Write the binary number $(110)_2$ in decimal notation

Binary notation refers to the number system of base 2, where as the decimal notation refers to base 10. I will start by expanding $(110)_2 = 1 * 2^2 + 1 * 2^1 + 0 * 2^0 = 6$, now I will try to write the number 6 in decimal notation. To do that I will use the equation

$$m = q_0 \cdot b + r_0 \dots$$

$$\dots m = q_n \cdot b + r_n$$

where : m : is the number we are trying to rewrite, b : the base, we continue running the recursion process until $q_n = 0$

$$6 = 0 \cdot 10 + 6$$

since $q_0 = 0$ we stop and now we have

$$(110)_2 = (6)_{10}$$

1.b Write the decimal number 110 in binary notation

Following the steps of the previous question, we have

$$(110)_{10} = 1 \cdot 10^2 + 1 \cdot 10^1 + 0 \cdot 10^0 = 110$$

to convert the number 110 to base 2 we use the equation :

$$110 = 55 \cdot 2 + 0$$

$$55 = 27 \cdot 2 + 1$$

$$27 = 13 \cdot 2 + 1$$

$$13 = 6 \cdot 2 + 1$$

$$6 = 3 \cdot 2 + 0$$

$$3 = 1 \cdot 2 + 1$$

$$1 = 0 \cdot 2 + 1$$

Then we have that

$$(110)_{10} = (1101110)_2$$

1.c Write the octal number $(110)_8$ in decimal notation

$$(110)_8 = 1 \cdot 8^2 + 1 \cdot 8^1 + 0 \cdot 8^0 = 64 + 8 + 0 = 72$$

$$72 = 7 \cdot 10 + 2$$

$$7 = 0 \cdot 10 + 7$$

hence

$$(110)_8 = (72)_{10}$$

2 Find the greatest common divisor using the algorithm we learned, show the steps then express d as linear combination of m and n

2.a m=38, n=14

2.b m=117, n=69

3 Consider the following algorithm

```
j := 1
while (j <= n) {
    A[j] := 0
    for i := j downto 1 {
        A[j] := A[j] + i * i
    }
    j := j + 1
}
```

3.a Explain what the algorithm does, and what are the numbers stored and computed in A

Let's start with the easier part, what are the values stored in array A, from j to n. The values stored in A are the sum of squares of j down to 1, meaning that for A[2], A[2] is equal to $2^2 + 1^2 = 5$.

j is an index variable showing our position in the array. This algorithm has 2 loops, the outer while-loop runs n times, going through every element in the array. The inner for-loop, that also runs n times, is used to update the values of the array from j to n. Initially $A[j:n] = 0$, a condition/command specified at the beginning of the outer-loop. The inner for-loop takes A[j] and iterates through it i times, until i hits 1. At each iteration in the for loop, the value of A[j] is updated, then the updated value is used for the next iteration, once i hits 1, the for-loop terminates, and j is updated to j+1. To reduce abstraction, suppose that n=3 and execute the algorithm at j=3 manually. j=3

$$A[3] = 0 \rightarrow j \leq n(\text{true}, \text{continue}) \quad (1)$$

we enter for-loop

$$A[3] = 0 + 3 * 3 = 9 \rightarrow A[3'] = A[3] + 2 * 2 = 13 \rightarrow A[3''] = A[3'] + 1 * 1 = 13 + 1 = 14 \quad (2)$$

$$i = 1(\text{for-loop terminates}) \rightarrow j = 3 + 1 = 4 \rightarrow 4 \leq 3(j \text{ larger than, outer-loop terminates}) \quad (3)$$

3.b

3.c

4

4.a

4.b

4.c