



中国数据库联盟
All China Database Union



墨天轮

2023 JUN 30

ACDU China Tour

数据库前沿技术揭秘及应用

中国·深圳





中国数据库联盟
All China Database Union



墨天轮

2023 ACDU China Tour

中国数据库联盟·深圳站

Oracle 23c创新特性与SQL增强

演讲人：杨廷琨



介绍

杨廷琨 (yangtingkun)

- ACOUG副总裁
- 前Oracle ACED
- ITPUB数据库管理区版主
- 参与编写《Oracle数据库性能优化》、《Oracle DBA手记》、《Oracle DBA手记3》和《Oracle性能优化与诊断案例精选》
- 二十三年的一线DBA经验
- 个人BLOG中积累了2500篇原创技术文章
- 云和恩墨联合创始人兼CTO

ACOUG
All China Oracle User Group
中国 Oracle 用户组



目录

CONTENTS

01

Oracle 23c创新特性

02

Oracle 23c SQL新特性

03

Oracle 23c升级策略



Oracle23c 概述

- 23c的主要目标：应用简化

NEW in Oracle Database 23c

Accelerating our mission to make developing and running all data-driven apps simple

23c
App Simple

JSON Relational Duality

Operational Property Graph

In-Database Sagas

Lock-free Reservations

OKafka

True Cache

JavaScript stored procedures

SQL Domains


Real-time SQL Plan Management

Read-only Per-PDB Standby

In-Database SQL Firewall

Schema Level Privileges

Oracle23c创新特性：JSON RELATIONAL DUALITY



Oracle23c创新特性：JSON RELATIONAL DUALITY

```
SQL> CREATE TABLE GUEST
  2   (G_ID NUMBER GENERATED BY DEFAULT ON NULL AS IDENTITY ,
  3   NAME VARCHAR2(30),
  4   CONSTRAINT PK_STUDENT PRIMARY KEY (G_ID));
```

Table created.

```
SQL> CREATE TABLE COURSE
  2   (C_ID NUMBER GENERATED BY DEFAULT ON NULL AS IDENTITY,
  3   NAME VARCHAR2(90),
  4   TIME VARCHAR2(30),
  5   TEACHER_NAME VARCHAR2(30),
  6   CONSTRAINT PK_COURSE PRIMARY KEY (C_ID));
```

Table created.

```
SQL> CREATE TABLE GUEST_SCHEDULE
  2   (SCHED_ID NUMBER GENERATED BY DEFAULT ON NULL AS IDENTITY,
  3   G_ID NUMBER,
  4   C_ID NUMBER,
  5   CONSTRAINT PK_STUD_SCHED PRIMARY KEY (SCHED_ID),
  6   CONSTRAINT FK_GUEST FOREIGN KEY (G_ID) REFERENCES GUEST(G_ID),
  7   CONSTRAINT FK_COURSE FOREIGN KEY (C_ID) REFERENCES COURSE(C_ID));
```

Table created.

Oracle23c创新特性：JSON RELATIONAL DUALITY

```
SQL> CREATE OR REPLACE JSON DUALITY VIEW GUEST_DV AS
  2  SELECT JSON {
  3      'GUEST_ID'    : G.G_ID,
  4      'GUEST_NAME': G.NAME,
  5      'COURSE'      :
  6          [SELECT JSON {
  7              'SCHEDULE_ID': GS.SCHED_ID,
  8              'COURSE_INFO': (
  9                  SELECT JSON{
 10                      'COURSE_ID'    : C.C_ID,
 11                      'TIME'         : C.TIME,
 12                      'COURSE_NAME'  : C.NAME,
 13                      'TEACHER_NAME': C.TEACHER_NAME WITH NOCHECK}
 14                  FROM COURSE C WITH NOINSERT NOUPDATE NODELETE
 15                  WHERE C.C_ID = GS.C_ID)}
 16          FROM GUEST_SCHEDULE GS WITH INSERT UPDATE DELETE
 17          WHERE GS.G_ID = G.G_ID]}
 18  FROM GUEST G WITH INSERT UPDATE DELETE;
```

View created.

Oracle23c创新特性：JSON RELATIONAL DUALITY

```
SQL> CREATE OR REPLACE JSON DUALITY VIEW COURSE_DV AS
  2  SELECT JSON {
  3      'COURSE_ID'      : C.C_ID,
  4      'TIME'           : C.TIME,
  5      'COURSE_NAME'    : C.NAME,
  6      'TEACHER_NAME'   : C.TEACHER_NAME}
  7  FROM COURSE C WITH INSERT UPDATE DELETE;
```

View created.

```
SQL> INSERT INTO COURSE_DV
  2  VALUES (' { "COURSE_ID"      : 20001,
  3              "TIME"           : "2023-06-30 14:00:00",
  4              "COURSE_NAME"    : "新时代下数据库运维和DBA面临的挑战和机遇",
  5              "TEACHER_NAME"   : "徐戟" } ');
```

1 row created.

```
SQL> INSERT INTO COURSE_DV
  2  VALUES (' { "COURSE_ID"      : 20002,
  3              "TIME"           : "2023-06-30 14:30:00",
  4              "COURSE_NAME"    : "Greenplum Database 7 性能提升的秘密武器",
  5              "TEACHER_NAME"   : "汤韬" } ');
```

1 row created.

Oracle23c创新特性：JSON RELATIONAL DUALITY

```
SQL> INSERT INTO COURSE_DV
  2  VALUES (' { "COURSE_ID"      : 20003,
  3              "TIME"           : "2023-06-30 15:00:00",
  4              "COURSE_NAME"    : "MySQL 8.0 新特性解读",
  5              "TEACHER_NAME"   : "姜承尧" } ');
```

1 row created.

```
SQL> INSERT INTO COURSE_DV
  2  VALUES (' { "COURSE_ID"      : 20004,
  3              "TIME"           : "2023-06-30 15:30:00",
  4              "COURSE_NAME"    : "基于PostgreSQL内核增强和扩展的产品设计哲学",
  5              "TEACHER_NAME"   : "赵伟" } ');
```

1 row created.

```
SQL> INSERT INTO COURSE_DV
  2  VALUES (' { "COURSE_ID"      : 20005,
  3              "TIME"           : "2023-06-30 16:00:00",
  4              "COURSE_NAME"    : "深算院全自研数据库系统的设计与实践",
  5              "TEACHER_NAME"   : "王海峰" } ');
```

1 row created.

Oracle23c创新特性：JSON RELATIONAL DUALITY

```
SQL> INSERT INTO COURSE_DV
  2  VALUES (' { "COURSE_ID"      : 20006,
  3              "TIME"           : "2023-06-30 16:30:00",
  4              "COURSE_NAME"    : "openGauss 5.0.0的新特性解读",
  5              "TEACHER_NAME"   : "熊小军" } ');
```

1 row created.

```
SQL> INSERT INTO COURSE_DV
  2  VALUES (' { "COURSE_ID"      : 20007,
  3              "TIME"           : "2023-06-30 17:00:00",
  4              "COURSE_NAME"    : "Oracle 23c创新技术与SQL增强",
  5              "TEACHER_NAME"   : "杨廷琨" } ');
```

1 row created.

Oracle23c创新特性：JSON RELATIONAL DUALITY

```
SQL> INSERT INTO GUEST_DV VALUES ('
 2  {"GUEST_ID"      : 100000,
 3  "GUEST_NAME"    : "墨天轮",
 4  "COURSE"        :
 5  [ {"SCHEDULE_ID" : 101,
 6    "COURSE_INFO"  : {"COURSE_ID"    : 20001,
 7                      "TIME"         : "2023-06-30 14:00:00",
 8                      "COURSE_NAME"   : "新时代下数据库运维和DBA面临的挑战和机遇",
 9                      "TEACHER_NAME"  : "徐戟" } }],
10  {"SCHEDULE_ID"   : 102,
11  "COURSE_INFO"    : {"COURSE_ID"    : 20005,
12                      "TIME"         : "2023-06-30 16:00:00",
13                      "COURSE_NAME"   : "深算院全自研数据库系统的设计与实践",
14                      "TEACHER_NAME"  : "王海峰" } } ] } ' );
```

1 row created.

Oracle23c创新特性：JSON RELATIONAL DUALITY

```
SQL> SELECT * FROM GUEST;
```

G_ID	NAME
100000	墨天轮

```
SQL> SELECT NAME, TEACHER_NAME TEACHER, SUBSTR(TIME, 1, 16) TIME FROM COURSE;
```

NAME	TEACHER	TIME
新时代下数据库运维和DBA面临的挑战和机遇	徐戟	2023-06-30 14:00
Greenplum Database 7 性能提升的秘密武器	汤韬	2023-06-30 14:30
MySQL 8.0 新特性解读	姜承尧	2023-06-30 15:00
基于PostgreSQL内核增强和扩展的产品设计哲学	赵伟	2023-06-30 15:30
深算院全自研数据库系统的设计与实践	王海峰	2023-06-30 16:00
openGauss 5.0.0的新特性解读	熊小军	2023-06-30 16:30
Oracle 23c创新技术与SQL增强	杨廷琨	2023-06-30 17:00

```
SQL> SELECT * FROM GUEST_SCHEDULE;
```

SCHED_ID	G_ID	C_ID
101	100000	20001
102	100000	20005

Oracle23c创新特性：JSON RELATIONAL DUALITY

```
SQL> SELECT REPLACE(JSON_QUERY(DATA, '$.COURSE'), ',', ' ' || CHR(10)) FROM GUEST_DV;
```

```
REPLACE(JSON_QUERY(DATA, '$.COURSE'), ',', ' ' || CHR(10))
```

```
-----  
[{"SCHEDULE_ID":101,  
"COURSE_INFO":{"COURSE_ID":20001,  
"TIME":"2023-06-30 14:00:00",  
"COURSE_NAME":"新时代下数据库运维和DBA面临的挑战和机遇",  
"TEACHER_NAME":"徐戟"}},  
{"SCHEDULE_ID":102,  
"COURSE_INFO":{"COURSE_ID":20005,  
"TIME":"2023-06-30 16:00:00",  
"COURSE_NAME":"深算院全自研数据库系统的设计与实践",  
"TEACHER_NAME":"王海峰"}}]
```

```
SQL> INSERT INTO GUEST_SCHEDULE VALUES (103, 100000, 20007);
```

```
1 row created.
```

```
SQL> COMMIT;
```

```
Commit complete.
```

Oracle23c创新特性：JSON RELATIONAL DUALITY

```
SQL> SELECT REPLACE(JSON_QUERY(DATA, '$.COURSE'), ',', ' ' || CHR(10)) FROM GUEST_DV;
```

```
REPLACE(JSON_QUERY(DATA, '$.COURSE'), ',', ' ' || CHR(10))
```

```
[{"SCHEDULE_ID":101,  
"COURSE_INFO":{"COURSE_ID":20001,  
"TIME":"2023-06-30 14:00:00",  
"COURSE_NAME":"新时代下数据库运维和DBA面临的挑战和机遇",  
"TEACHER_NAME":"徐戟"}},  
{"SCHEDULE_ID":102,  
"COURSE_INFO":{"COURSE_ID":20005,  
"TIME":"2023-06-30 16:00:00",  
"COURSE_NAME":"深算院全自研数据库系统的设计与实践",  
"TEACHER_NAME":"王海峰"}},  
{"SCHEDULE_ID":103,  
"COURSE_INFO":{"COURSE_ID":20007,  
"TIME":"2023-06-30 17:00:00",  
"COURSE_NAME":"Oracle 23c创新技术与SQL增强",  
"TEACHER_NAME":"杨廷琨"}}]
```

目录

CONTENTS

01

Oracle 23c创新特性

02

Oracle 23c SQL新特性

03

Oracle 23c升级策略



Oracle23c新特性

- 查询省略FROM
- 表支持4096列
- Boolean类型
- GROUP BY别名
- SCHEMA级授权
- DDL支持EXISTS
- 构建多行记录
- 更新JOIN结果
- RETURN支持OLD
- SQL DOMAINS
- 无锁列值托管
- 自动事务终止

Oracle23c新特性：查询省略FROM

```
SQL> select banner_full from v$version;
```

BANNER_FULL

Oracle Database 23c Free, Release 23.0.0.0.0 - Developer-Release
Version 23.2.0.0.0

```
SQL> select 100;
```

100

100

```
SQL> select to_char(sysdate, 'yyyy-mm-dd');
```

TO CHAR(SY

2023-02-02

Id	Operation	Name	Rows	Cost (%CPU)	Time
0	SELECT STATEMENT		1	2 (0)	00:00:01
1	FAST DUAL		1	2 (0)	00:00:01

Oracle23c新特性：表支持4096列

```
SQL> CREATE TABLE T_1001_COLUMNS (  
    2  C0001 NUMBER,  
    3  C0002 NUMBER,  
  
    .  
    .  
    .  
    999 C0998 NUMBER,  
    1000 C0999 NUMBER,  
    1001 C1000 NUMBER,  
    1002 C1001 NUMBER);  
C1001 NUMBER)  
*  
ERROR at line 1002:  
ORA-01792: maximum number of columns in a table or view is 1000
```

```
SQL> SHOW PARAMETER MAX_COLUMNS
```

NAME	TYPE	VALUE
max_columns	string	STANDARD

Oracle23c新特性：表支持4096列

```
SQL> ALTER SYSTEM SET MAX_COLUMNS = EXTENDED;
```

```
System altered.
```

```
SQL> CREATE TABLE T_1001_COLUMNS (  
    2  C0001 NUMBER,  
    3  C0002 NUMBER,  
    4  C0003 NUMBER,  
    .  
    .  
    .  
    999 C0998 NUMBER,  
    1000 C0999 NUMBER,  
    1001 C1000 NUMBER,  
    1002 C1001 NUMBER);
```

```
Table created.
```

```
SQL> SELECT COUNT(*) FROM USER_TAB_COLUMNS WHERE TABLE_NAME = 'T_1001_COLUMNS';
```

```
    COUNT(*)  
-----  
         1001
```


Oracle23c新特性： Boolean类型

```
SQL> CREATE TABLE T_BOOL (ID NUMBER, BOOL BOOLEAN);
```

```
Table created.
```

```
SQL> INSERT INTO T_BOOL VALUES (1, TRUE);
```

```
1 row created.
```

```
SQL> INSERT INTO T_BOOL VALUES (2, FALSE);
```

```
1 row created.
```

```
SQL> INSERT INTO T_BOOL VALUES (3, NULL);
```

```
1 row created.
```

```
SQL> INSERT INTO T_BOOL VALUES (4, 'T');
```

```
1 row created.
```

```
SQL> INSERT INTO T_BOOL VALUES (5, 0);
```

```
1 row created.
```

Oracle23c新特性： Boolean类型

```
SQL> SELECT ID FROM T_BOOL WHERE BOOL;
```

ID
1
4

```
SQL> SELECT * FROM T_BOOL;
```

ID	BOOL
1	TRUE
2	FALSE
3	
4	TRUE
5	FALSE

Oracle23c新特性： GROUP BY别名

```
SQL> create table t as select rownum id, a.* from dba_objects a;
```

Table created.

```
SQL> SELECT TRUNC(CREATED, 'MM') MON, COUNT(*) FROM T
      2  GROUP BY TRUNC(CREATED, 'MM');
```

MON	COUNT(*)
01-OCT-22	76378
01-DEC-22	5289
01-JAN-23	10164
01-FEB-23	683

```
SQL> SELECT TRUNC(CREATED, 'MM') MON, COUNT(*) FROM T
      2  GROUP BY MON;
```

MON	COUNT(*)
01-OCT-22	76378
01-DEC-22	5289
01-JAN-23	10164
01-FEB-23	683

Oracle23c新特性：SCHEMA级授权

```
SQL> CREATE USER YANGTK_SELE IDENTIFIED BY SELECTONLY DEFAULT TABLESPACE USERS;
```

```
User created.
```

```
SQL> GRANT CREATE SESSION TO YANGTK_SELE;
```

```
Grant succeeded.
```

```
SQL> GRANT SELECT ANY TABLE ON SCHEMA YANGTK TO YANGTK_SELE;
```

```
Grant succeeded.
```

```
SQL> CONN YANGTK_SELE/SELECTONLY@pdb1
```

```
Connected.
```

```
SQL> SELECT * FROM SESSION_PRIVS;
```

```
PRIVILEGE
```

```
-----
```

```
CREATE SESSION
```

```
SQL> SELECT * FROM SESSION_ROLES;
```

```
no rows selected
```


Oracle23c新特性：SCHEMA级授权

```
SQL> SELECT OWNER, TABLE_NAME FROM ALL_TABLES WHERE OWNER NOT IN ('SYS', 'SYSTEM', 'XDB', 'MDSYS', 'CTXSYS');
```

OWNER	TABLE_NAME
-----	-----
YANGTK	STUDENT_SCHEDULER
YANGTK	T
YANGTK	T_1001_COLUMNS

```
SQL> SELECT TABLE_NAME, PRIVILEGE FROM USER_TAB_PRIVS;
```

TABLE_NAME	PRIVILEGE
-----	-----
YANGTK_SELE	INHERIT PRIVILEGES

```
SQL> SELECT COUNT(*) FROM YANGTK.T;
```

COUNT(*)

92514

Oracle23c新特性：SCHEMA级授权

```
SQL> CONN YANGTK/yangtk@pdb1
```

```
Connected.
```

```
SQL> CREATE TABLE T_NEW (ID NUMBER);
```

```
Table created.
```

```
SQL> CONN YANGTK_SELE/SELECTONLY@pdb1
```

```
Connected.
```

```
SQL> SELECT OWNER, TABLE_NAME FROM ALL_TABLES WHERE OWNER NOT IN ('SYS', 'SYSTEM', 'XDB',  
'MDSYS', 'CTXSYS');
```

OWNER	TABLE_NAME
-----	-----
YANGTK	STUDENT_SCHEDULER
YANGTK	T
YANGTK	T_1001_COLUMNS
YANGTK	T_NEW

Oracle23c新特性：DDL支持EXISTS

```
SQL> SELECT * FROM TAB;
```

TNAME	TABTYPE	CLUSTERID
STUDENT_SCHEDULER	TABLE	
T	TABLE	
T_1001_COLUMNS	TABLE	
T_NEW	TABLE	
T_BOOL	TABLE	

```
SQL> DROP TABLE T_NOTEXIST;
DROP TABLE T_NOTEXIST
      *
ERROR at line 1:
ORA-00942: table or view does not exist
```

```
SQL> DROP TABLE IF EXISTS T_NOTEXIST;
```

Table dropped.

```
SQL> DROP TABLE IF EXISTS T_NEW;
```

Table dropped.

Oracle23c新特性：DDL支持EXISTS

```
SQL> SELECT * FROM TAB;
```

TNAME	TABTYPE	CLUSTERID
STUDENT_SCHEDULER	TABLE	
T	TABLE	
T_1001_COLUMNS	TABLE	
T_BOOL	TABLE	
BIN\$87V21hTqU+jgU6YWFKyjjyQ==\$0	TABLE	

```
SQL> CREATE TABLE T (ID NUMBER);
CREATE TABLE T (ID NUMBER)
      *
ERROR at line 1:
ORA-00955: name is already used by an existing object
```

```
SQL> CREATE TABLE IF NOT EXISTS T (ID NUMBER);

Table created.
```

Oracle23c新特性：构建多行记录

```
SQL> WITH S (A, B, C) AS (  
2  VALUES (1, 'A', SYSDATE),  
3  (2, 'B', TO_DATE('20230202', 'YYYYMMDD')),  
4  (3, 'ABCD', SYSDATE - 1))  
5  SELECT A, B, TO_CHAR(C, 'YYYYMMDD') FROM S;
```

A	B	TO_CHAR(
1	A	20230202
2	B	20230202
3	ABCD	20230201

Id	Operation	Name	Rows	Bytes	Cost (%CPU)	Time
0	SELECT STATEMENT		18E	15E	6 (0)	00:00:01
1	VIEW		18E	15E	6 (0)	00:00:01
2	VALUES SCAN					

Oracle23c新特性： 构建多行记录

```
SQL> CREATE TABLE T_MULROW (ID NUMBER, NAME VARCHAR2(30));
```

Table created.

```
SQL> INSERT INTO T_MULROW VALUES (1, 'A'), (2, 'B'), (3, 'ABC');
```

3 rows created.

Id	Operation	Name	Rows	Cost (%CPU)	Time
0	INSERT STATEMENT		18E	6 (0)	00:00:01
1	LOAD TABLE CONVENTIONAL	T_MULROW			
2	VALUES SCAN				

Oracle23c新特性：更新JOIN结果

```
SQL> SELECT * FROM T_BOOL;
```

ID	BOOL
1	TRUE
2	FALSE
3	
4	TRUE
5	FALSE

```
SQL> SELECT * FROM T_MULROW;
```

ID	NAME
1	A
2	B
3	ABC

Oracle23c新特性：更新JOIN结果

```
SQL> UPDATE T_MULROW SET NAME = LOWER(NAME)
      2 FROM T_BOOL
      3 WHERE T_MULROW.ID = T_BOOL.ID
      4 AND BOOL;
```

1 row updated.

	Id	Operation	Name	Rows	Bytes	Cost (%CPU)		Time

	0	UPDATE STATEMENT		3	30	6	(0)	00:00:01
	1	UPDATE	T_MULROW					
*	2	HASH JOIN		3	30	6	(0)	00:00:01
*	3	TABLE ACCESS FULL	T_BOOL	3	12	3	(0)	00:00:01
	4	TABLE ACCESS FULL	T_MULROW	3	18	3	(0)	00:00:01

```
SQL> SELECT * FROM T_MULROW;
```

ID NAME		-----						
	1	a						
	2	B						
	3	ABC						

Oracle23c新特性：更新JOIN结果

```
SQL> ALTER TABLE T_BOOL ADD PRIMARY KEY (ID);
```

Table altered.

```
SQL> ALTER TABLE T_MULROW ADD CONSTRAINT FK_ID FOREIGN KEY (ID) REFERENCES T_BOOL;
```

Table altered.

```
SQL> UPDATE
  2  (SELECT M.NAME, M.ID MID, B.ID BID FROM T_MULROW M, T_BOOL B WHERE M.ID = B.ID)
  3  SET NAME = LOWER(NAME)
  4  WHERE MID = BID;
```

3 rows updated.

	Id		Operation		Name		Rows		Bytes		Cost (%CPU)		Time	

	0		UPDATE STATEMENT				3		18		3 (0)		00:00:01	
	1		UPDATE		T_MULROW									
	* 2		TABLE ACCESS FULL		T_MULROW		3		18		3 (0)		00:00:01	

Oracle23c新特性：RETURN支持OLD

```
SQL> SET SERVEROUT ON SIZE 100000
SQL> DECLARE
  2     V_NAME_O VARCHAR2(30);
  3     V_NAME_N VARCHAR2(30);
  4 BEGIN
  5     UPDATE T_MULROW SET NAME = UPPER(NAME) WHERE ID = 1
  6     RETURN OLD NAME, NEW NAME
  7     INTO V_NAME_O, V_NAME_N;
  8     DBMS_OUTPUT.PUT_LINE('OLD NAME: ' || V_NAME_O);
  9     DBMS_OUTPUT.PUT_LINE('NEW NAME: ' || V_NAME_N);
 10 COMMIT;
 11 END;
 12 /
OLD NAME: a
NEW NAME: A
```

PL/SQL procedure successfully completed.

Oracle23c新特性：SQL DOMAINS

```
SQL> CREATE DOMAIN ID_NUMBER AS VARCHAR2(18)
2  CONSTRAINT C_LEN CHECK (LENGTH(ID_NUMBER) = 18
3  AND LTRIM(SUBSTR(ID_NUMBER, 1, 17), '0123456789') IS NULL
4  AND SUBSTR(ID_NUMBER, 18) IN ('X', '0', '1', '2', '3', '4', '5', '6', '7', '8', '9'))
5  AND MOD(SUBSTR(ID_NUMBER,1,1)*7 + SUBSTR(ID_NUMBER,2,1)*9 + SUBSTR(ID_NUMBER,3,1)*10
6  + SUBSTR(ID_NUMBER,4,1)*5 + SUBSTR(ID_NUMBER,5,1)*8 + SUBSTR(ID_NUMBER,6,1)*4
7  + SUBSTR(ID_NUMBER,7,1)*2 + SUBSTR(ID_NUMBER,8,1) + SUBSTR(ID_NUMBER,9,1)*6
8  + SUBSTR(ID_NUMBER,10,1)*3 + SUBSTR(ID_NUMBER,11,1)*7 + SUBSTR(ID_NUMBER,12,1)*9
9  + SUBSTR(ID_NUMBER,13,1)*10 + SUBSTR(ID_NUMBER,14,1)*5 + SUBSTR(ID_NUMBER,15,1)*8
10 + SUBSTR(ID_NUMBER,16,1)*4 + SUBSTR(ID_NUMBER,17,1)*2, 11) =
11 MOD(12 - CASE (SUBSTR(ID_NUMBER, 18)) WHEN 'X' THEN 10 ELSE TO_NUMBER(SUBSTR(ID_NUMBER,
18)) END, 11))
12  DISPLAY SUBSTR(ID_NUMBER, 1, 10) || '****' || SUBSTR(ID_NUMBER, 15)
13  ORDER TO_NUMBER(SUBSTR(ID_NUMBER, 7, 11));
```

Domain created.

```
SQL> CREATE TABLE T_IDEN (ID NUMBER, NAME VARCHAR2(30), IDEN VARCHAR2(18) DOMAIN ID_NUMBER);
```

Table created.

Oracle23c新特性：SQL DOMAINS

```
SQL> INSERT INTO T_IDEN VALUES (1, 'A', '110101198001010010');
```

```
1 row created.
```

```
SQL> INSERT INTO T_IDEN VALUES (2, 'B', '220381197001010014');
```

```
1 row created.
```

```
SQL> INSERT INTO T_IDEN VALUES (3, 'C', '33010519900101002X');
```

```
1 row created.
```

```
SQL> INSERT INTO T_IDEN VALUES (4, 'D', '330105199001010021');
```

```
INSERT INTO T_IDEN VALUES (4, 'D', '330105199001010021')
```

```
*
```

```
ERROR at line 1:
```

```
ORA-02290: check constraint (YANGTK.SYS_C008298) violated
```

```
SQL> COMMIT;
```

```
Commit complete.
```

Oracle23c新特性： SQL DOMAINS

```
SQL> SELECT ID, NAME, IDEN, DOMAIN_DISPLAY(IDEN) D_ID
2 FROM T_IDEN ORDER BY IDEN;
```

ID	NAME	IDEN	D_ID
1	A	110101198001010010	1101011980****0010
2	B	220381197001010014	2203811970****0014
3	C	33010519900101002X	3301051990****002X

```
SQL> SELECT ID, NAME, IDEN, DOMAIN_DISPLAY(IDEN) D_ID
2 FROM T_IDEN ORDER BY DOMAIN_ORDER(IDEN);
```

ID	NAME	IDEN	D_ID
2	B	220381197001010014	2203811970****0014
1	A	110101198001010010	1101011980****0010
3	C	33010519900101002X	3301051990****002X

Oracle23c新特性：无锁列值托管

```
SQL> CREATE TABLE T_ESCROW (ID NUMBER PRIMARY KEY, ESC_LOCK NUMBER ESCROW, NORMAL_LOCK NUMBER);
```

Table created.

```
SQL> INSERT INTO T_ESCROW VALUES (1, 1, 1), (2, 2, 2), (3, 3, 3);
```

3 rows created.

```
SQL> COMMIT;
```

Commit complete.

```
SQL> SELECT * FROM T_ESCROW;
```

ID	ESC_LOCK	NORMAL_LOCK
1	1	1
2	2	2
3	3	3

Oracle23c新特性：无锁列值托管

```
SQL> UPDATE T_ESCROW SET ESC_LOCK = ESC_LOCK + 1 WHERE ID = 1;
```

```
1 row updated.
```

--sqlplus登陆新的会话，用SQL标识符SQL2>来表示第二个会话进行的操作

```
SQL> SET SQLP 'SQL2> '
```

```
SQL2> UPDATE T_ESCROW SET ESC_LOCK = ESC_LOCK - 1 WHERE ID = 1;
```

```
1 row updated.
```

```
SQL2> COMMIT;
```

```
Commit complete.
```

```
SQL> COMMIT;
```

```
Commit complete.
```

Oracle23c新特性：无锁列值托管

```
SQL> UPDATE T_ESCROW SET NORMAL_LOCK = NORMAL_LOCK + 1 WHERE ID = 1;
```

1 row updated.

```
SQL> SELECT L.SID, L.TYPE, ID1, LMODE, CTIME, BLOCK FROM V$LOCK L, V$SESSION S
2 WHERE L.SID = S.SID AND S.USERNAME = USER AND L.TYPE IN ('TX', 'TM');
```

SID	TY	ID1	LMODE	CTIME	BLOCK
506	TM	119484	3	13	2
506	TX	1376279	6	13	2

```
SQL> SELECT * FROM T_ESCROW;
```

ID	ESC_LOCK	NORMAL_LOCK
1	1	2
2	2	2
3	3	3

```
SQL> COMMIT;
```

Commit complete.

Oracle23c新特性：无锁列值托管

```
SQL> UPDATE T_ESCROW SET ESC_LOCK = ESC_LOCK + 1 WHERE ID = 1;
```

```
1 row updated.
```

```
SQL> SELECT L.SID, L.TYPE, ID1, LMODE, CTIME, BLOCK FROM V$LOCK L, V$SESSION S
2 WHERE L.SID = S.SID AND S.USERNAME = USER AND L.TYPE IN ('TX', 'TM');
```

SID	TY	ID1	LMODE	CTIME	BLOCK
506	TX	1376285	6	19	2
506	TM	119485	3	19	2
506	TM	119484	3	19	2

```
SQL> SELECT OWNER, OBJECT_NAME FROM DBA_OBJECTS WHERE OBJECT_ID IN (119484, 119485);
```

OWNER	OBJECT_NAME
YANGTK	T_ESCROW
YANGTK	SYS_ESCROWJRNL_119484

Oracle23c新特性：无锁列值托管

```
SQL> SELECT * FROM T_ESCROW;
```

ID	ESC_LOCK	NORMAL_LOCK
1	1	2
2	2	2
3	3	3

```
SQL> COMMIT;
```

Commit complete.

```
SQL> SELECT * FROM T_ESCROW;
```

ID	ESC_LOCK	NORMAL_LOCK
1	2	2
2	2	2
3	3	3

Oracle23c新特性：无锁列值托管

```
SQL> UPDATE T_ESCROW SET ESC_LOCK = ESC_LOCK - 1 WHERE ID = 1;
```

1 row updated.

```
SQL> SELECT * FROM T_ESCROW;
```

ID	ESC_LOCK	NORMAL_LOCK
1	2	2
2	2	2
3	3	3

```
SQL> ROLLBACK;
```

Rollback complete.

```
SQL> SELECT * FROM T_ESCROW;
```

ID	ESC_LOCK	NORMAL_LOCK
1	2	2
2	2	2
3	3	3

Oracle23c新特性：无锁列值托管

```
SQL> select * from t_escrow;
```

ID	ESC_LOCK	NORMAL_LOCK
1	2	2
2	2	2
3	3	3

```
SQL> select * from SYS_ESCROWJRNL_119484;
```

no rows selected

```
SQL> update t_escrow set esc_lock = esc_lock - 1 where id = 1;
```

1 row updated.

```
SQL> select * from SYS_ESCROWJRNL_119484;
```

ORA_SAGA_I	ORA_TXN_ID\$	ORA_STATUS\$	ORA_STMT_TYPE\$	ID	ESC_LOC	ESC_LOCK_RESERVED
	1500130070AA0100	ACTIVE	UPDATE	1	-	1

Oracle23c新特性：无锁列值托管

```
SQL> update t_escrow set esc_lock = esc_lock + 3 where id = 1;
```

1 row updated.

```
SQL> select * from SYS_ESCROWJRNL_119484;
```

ORA_SAGA_I	ORA_TXN_ID\$	ORA_STATUS\$	ORA_STMT_TYPE\$	ID	ESC_LOC	ESC_LOCK_RESERVED
	1500130070AA0100	ACTIVE	UPDATE	1	-	1
	1500130070AA0100	ACTIVE	UPDATE	1	+	3

```
SQL> commit;
```

Commit complete.

```
SQL> select * from SYS_ESCROWJRNL_119484;
```

no rows selected

Oracle23c新特性：无锁列值托管

```
SQL> CREATE TABLE T_ESCROW (ID NUMBER, ESC_LOCK VARCHAR2(30) ESCROW, NORMAL_LOCK NUMBER);
CREATE TABLE T_ESCROW (ID NUMBER, ESC_LOCK VARCHAR2(30) ESCROW, NORMAL_LOCK NUMBER)
*
```

ERROR at line 1:

ORA-55748: Escrow column is supported only on columns of types Oracle NUMBER, INTEGER, and FLOAT.

```
SQL> CREATE TABLE T_ESCROW (ID NUMBER, ESC_LOCK NUMBER ESCROW, NORMAL_LOCK NUMBER);
CREATE TABLE T_ESCROW (ID NUMBER, ESC_LOCK NUMBER ESCROW, NORMAL_LOCK NUMBER)
*
```

ERROR at line 1:

ORA-55728: Escrow columns can only be specified on tables with a primary key.

```
SQL> UPDATE T_ESCROW SET ESC_LOCK = 0 WHERE ID = 1;
UPDATE T_ESCROW SET ESC_LOCK = 0 WHERE ID = 1
*
```

ERROR at line 1:

ORA-55782: Operation is not supported on escrow columns.

```
SQL> UPDATE T_ESCROW SET ESC_LOCK = ESC_LOCK + 1 WHERE NORMAL_LOCK = 3;
UPDATE T_ESCROW SET ESC_LOCK = ESC_LOCK + 1 WHERE NORMAL_LOCK = 3
*
```

ERROR at line 1:

ORA-55732: Escrow update should specify all the primary key columns

Oracle23c新特性：无锁列值托管

```
SQL> DROP TABLE T_ESCROW PURGE;  
DROP TABLE T_ESCROW PURGE
```

*

```
ERROR at line 1:
```

```
ORA-55764: Cannot drop/move an escrow table. First run alter table <table_name> modify  
(<escrow_column_name> NOT ESCROW) and then drop/move the escrow table
```

```
SQL> ALTER TABLE T_ESCROW MODIFY (ESC_LOCK NOT ESCROW);
```

```
Table altered.
```

```
SQL> DROP TABLE T_ESCROW PURGE;
```

```
Table dropped.
```

Oracle23c新特性：自动事务终止

```
SQL> SHOW PARAMETER TXN
```

NAME	TYPE	VALUE
global_txn_processes	integer	1
txn_high_priority_wait_target	integer	2147483647
txn_medium_priority_wait_target	integer	2147483647
txn_priority	string	HIGH

```
SQL> ALTER SESSION SET TXN_PRIORITY = MEDIUM;
```

Session altered.

```
SQL> UPDATE T_BOOL SET BOOL = FALSE WHERE ID = 3;
```

1 row updated.

```
SQL> SELECT XID, STATUS, USED_UREC, START_TIME, TXN_PRIORITY, TXN_PRIORITY_WAIT_TARGET FROM V$TRANSACTION;
```

XID	STATUS	USED_UREC	START_TIME	TXN_PRI	TXN_PRIORITY_WAIT_TARGET
0C0010004E0C0000	ACTIVE	1	02/14/23 16:44:07	MEDIUM	0

Oracle23c新特性：自动事务终止

```
SQL2> ALTER SYSTEM SET TXN_HIGH_PRIORITY_WAIT_TARGET = 10;
```

System altered.

```
SQL2> SHOW PARAMETER TXN
```

NAME	TYPE	VALUE
txn_high_priority_wait_target	integer	10
txn_medium_priority_wait_target	integer	2147483647
txn_priority	string	HIGH

```
SQL2> SET TIMING ON TIME ON
```

```
16:44:18 SQL2> UPDATE T_BOOL SET BOOL = TRUE WHERE ID = 3;
```

1 row updated.

Elapsed: 00:00:10.68

```
16:44:36 SQL2> SELECT XID, STATUS, USED_UREC, START_TIME, TXN_PRIORITY,  
TXN_PRIORITY_WAIT_TARGET FROM V$TRANSACTION;
```

XID	STATUS	USED_UREC	START_TIME	TXN_PRI	TXN_PRIORITY_WAIT_TARGET
15000B00311C0000	ACTIVE	1	02/14/23 16:44:25	HIGH	10

Oracle23c新特性：自动事务终止

```
SQL> SELECT XID, STATUS, USED_UREC, START_TIME, TXN_PRIORITY, TXN_PRIORITY_WAIT_TARGET FROM  
V$TRANSACTION;  
SELECT XID, STATUS, USED_UREC, START_TIME, TXN_PRIORITY, TXN_PRIORITY_WAIT_TARGET FROM  
V$TRANSACTION
```

*

```
ERROR at line 1:
```

```
ORA-03113: end-of-file on communication channel
```

```
Process ID: 2684285
```

```
Session ID: 1229 Serial number: 33384
```

目录

CONTENTS

01

Oracle 23c创新特性

02

Oracle 23c SQL新特性


03

Oracle 23c升级策略




Oracle23c升级策略

- 23c是长期版本



Oracle23c升级策略

- 23c升级路径



谢谢观看

THANKS FOR WATCHING



中国数据库联盟
All China Database Union



墨天轮





中国数据库联盟
All China Database Union



墨天轮

点击查看合辑免费获取更多PPT: <https://www.modb.pro/topic/655627>

扫码关注更多ACDU大会活动

<https://www.modb.pro/meetup>



添加墨天轮小助手微信: modb666

备注常用数据库名称, 入群获取更多技术干货

