

Laboratory work 5

Author: Dávid Kromka

Part 1:

For **Task 1**, the code finds prime roots modulo n and prints a table of reflections for each value of n in the `n_values` list. The algorithm works as follows:

1. Find Prime Roots Modulo n :
 - Loop through all integers a from 1 to $n - 1$.
 - For each a , calculate residues for values of x from 1 to $n - 1$ using the formula $(a ** x) \% n$.
 - Store the residues in a list `residues`.
 - If the number of residues equals $n - 1$, add the list of residues to the `prime_roots` list.
 - Return the list of prime roots.
2. Print Table of Reflections:
 - Iterate through the `prime_roots` list for each n in `n_values`.
 - Print the prime roots for the current n .
 - Print a table header with indices from 1 to the length of prime roots.
 - For each x from 1 to $n - 1$, print the corresponding residues in the table.

For **Task 2**, the code finds possible values of x for given (a, y) combinations where $(a ** x) \% 7 = y$. It then prints the combinations of a , possible x values, and y in a table. The algorithm works as follows:

1. Find Possible x Values:
 - Loop through integers x from 0 to 6.
 - For each x , calculate $(a ** x) \% 7$ and check if it equals y .
 - If it matches, add x to the `possible_x` list.
2. Find (a, x, y) Combinations:
 - Iterate through predefined combinations of (a, y) in the `combinations` list.
 - For each combination, find possible values of x using the `find_x` function.
 - If there are possible x values, store the combination of (a, x_values) as the key and y as the value in the `results` dictionary.
3. Print Results in a Table:
 - Print the header for the table.

- For each key-value pair in the results dictionary, print a, possible x values, and y in the table.

Part 2:

1. Define a function called `hex_to_decimal` that takes a single argument `hex_string`, which represents a hexadecimal number. The function returns the decimal equivalent of the input hexadecimal number. This is achieved by using the built-in `int()` function with base 16, which converts the hexadecimal string to a decimal integer.
2. Create two lists: `direct_replacement_table` and `reverse_swap_table`, which store hexadecimal strings representing elements in two different tables.
3. Create two empty lists: `direct_replacement_decimal` and `reverse_swap_decimal` to store the decimal equivalents of the elements in the `direct_replacement_table` and `reverse_swap_table`, respectively.
4. Iterate over each element in the `direct_replacement_table` and `reverse_swap_table` using list comprehensions. For each element, call the `hex_to_decimal` function to convert the hexadecimal string to its decimal equivalent, and add the result to the respective list (`direct_replacement_decimal` or `reverse_swap_decimal`).
5. Print the results of the conversion for both tables in decimal notation.