

**A8.15. UN3541, Articles containing flammable solid N.O.S.** are authorized when classified per paragraph A4.2.3., maximum net quantity per package 50 kg, when packaged, or unpackaged as follows:

A8.15.1. When packaged, packagings meeting Packing Group II performance is required.

A8.15.1.1. Pack articles to prevent movement and inadvertent operation during normal conditions of transport.

A8.15.1.2. Where there is no receptacle within the article, ensure the article fully encloses the dangerous goods and prevent their release under normal conditions of transport.

Inner packaging	Outer packaging
<b>Receptacles:</b> constructed of suitable materials and secured in the article in such a way that, under normal conditions of transport, they cannot break, be punctured or leak their contents into the article itself or the outer packaging.	<b>Drums:</b> removable head steel (1A2), removable head aluminum (1B2), removable head metal other than steel or aluminum (1N2), plywood (1D), fiber (1G), or removable head plastic (1H2) <i>or</i> <b>Boxes:</b> steel (4A), aluminum (4B), ordinary natural wood (4C1), sift-proof natural wood (4C2), plywood (4D), reconstituted wood (4F), fiberboard (4G), expanded plastic (4H1), or solid plastic (4H2), other metal (4N) <i>or</i> <b>Jerricans:</b> removable head steel (3A2), plastic removable head (3H2), or aluminum removable head (3B2)

A8.15.2. Robust articles.

A8.15.2.1. Robust articles may be transported in strong outer packagings constructed of suitable material and of adequate strength and design in relation to the packaging capacity and its intended use; or,

A8.15.2.2. Robust articles may be transported unpackaged or on pallets when the dangerous goods are afforded equivalent protection by the article in which they are contained.