

**Supplementary Material for Manuscript ID IEEE
TCNS 23-0126**

Structural Controllability of Multiplex Networks with the Minimum
Number of Driver Nodes

Xiang Li, Guoqi Li, Leitao Gao, Lock Yue Chew and Gaoxi Xiao

August 20, 2023

This Supplementary Material is organized as follows. In Section I, the proposed “Minimum-cost Flow based Driver-node Identification” (MFDI) method is compared with the existing methods in terms of the driver nodes required to ensure the structural controllability of two-layer multiplex networks. In Section II, we demonstrate how using the method for single layer networks on two-layer networks might lead to driver nodes that violate the location constraint.

1 Comparative Analysis of MFDI with Existing Techniques

To the best of our knowledge, our work is the first to study the problem of finding the minimum number of driver nodes to ensure the structural controllability of multiplex networks. Our work shares a common interest in the structural controllability of multiplex networks with several other significant studies but features some distinct characteristics [14, 18, 19]. In [14], the authors examined finding the minimum number of controllers on multiplex multi-time-scale networks within discrete dynamics, providing a solution using the max flow method. However, this work may not be directly comparable to our work and existing works on continuous dynamics [18, 19] due to the significant difference in the dynamics framework. In the following, we shall conduct the comparisons between the MFDI algorithm and the algorithms proposed in [18, 19] from problem formulation and numerical results perspectives.

In [18, 19], the authors delved into the problem of finding the minimum number of controllers required to ensure target controllability on two-layer multiplex networks. These two studies respectively employed a maximum flow algorithm and a minimum-cost maximum flow algorithm, respectively. When their methods are applied to the problem of structural controllability, the target set is considered as the whole network’s node sets. Specifically, their formulation of the problem is as follows. In a two-layer multiplex network with

n nodes in each layer, of which the wiring diagram is $\bar{A} = \begin{bmatrix} \bar{A}_{11} & \mathbf{0} \\ \bar{A}_{21} & \bar{A}_{22} \end{bmatrix} \in \{0, \star\}^{2n \times 2n}$, the problem can be formulated as

$$\begin{aligned}
& \min_{\bar{B}_1 \in \{0, \star\}^{n \times m}} m, \\
& \text{s. t. } \bar{B} = \begin{bmatrix} \bar{B}_1 \\ \mathbf{0} \end{bmatrix} \in \{0, \star\}^{2n \times m}, \\
& \dot{\mathbf{x}}(t) = \bar{A}\mathbf{x}(t) + \bar{B}\mathbf{u}(t), \\
& (\bar{A}, \bar{B}) \text{ is structurally controllable.}
\end{aligned} \tag{S1}$$

where m represents the number of external controllers.

In our paper, we study the problem of finding the minimum number of driver nodes necessary to ensure the structural controllability of multiplex networks. On a two-layer multiplex network, of which the wiring diagram is denoted as $\bar{A} = \begin{bmatrix} \bar{A}_{11} & \mathbf{0} \\ \bar{A}_{21} & \bar{A}_{22} \end{bmatrix} \in \{0, \star\}^{2n \times 2n}$, we tackle the optimization problem

$$\begin{aligned}
& \min_{\bar{B}_1 \in \{0, \star\}^{n \times n}} \|\bar{B}\|_0, \\
& \text{s. t. } \bar{B} = \begin{bmatrix} \bar{B}_1 \\ \mathbf{0} \end{bmatrix} \in \{0, \star\}^{2n \times n}, \\
& \dot{\mathbf{x}}(t) = \bar{A}\mathbf{x}(t) + \bar{B}\mathbf{u}(t), \\
& (\bar{A}, \bar{B}) \text{ is structurally controllable.}
\end{aligned} \tag{S2}$$

The main distinction between formulations (S1) and (S2) is that while (S1) focuses on finding the minimum number of controllers, (S2) is concerned with identifying the minimum number of driver nodes required to ensure the structural controllability of multiplex networks. Both equations (S1) and (S2) impose a constraint that controllers can only be connected to nodes in the first layer.

The proposed “Minimum-cost Flow based Driver-node Identification” (MFDI) method is compared with the methods described in [18, 19] in terms of the driver nodes required to ensure the structural controllability of two-layer multiplex networks. The results of comparisons on synthetic multiplex networks are presented in Table S1, where each layer consists of n nodes and μ_i denotes the average nodal degree in the i^{th} layer. In Table S1, each value is represented as the mean \pm standard deviation calculated from 100 independent simulations. Moreover, Table S2 showcases the comparisons made on real-life multiplex networks where each layer consists of n nodes and $|E_i|$ denotes the number of edges in the i^{th} layer. The real-life network datasets are accessible on the website of CoMuNe Laboratory ¹, the Research Unit of Bruno Kessler Foundations Center for Information and Communication Technologies. For those networks with more than two layers, we only use the data of the first two layers in the simulations. In Table S2, each real-life multiplex network is represented where n marks the number of nodes in each layer, and $|E_i|$ denotes the number of edges in the i^{th} layer.

¹<https://manliodedomenico.com/data.php>

Table S1: Comparisons between the number of driver nodes obtained by different methods on two-layer synthetic multiplex networks ($n = 1000$)

	maximum flow algorithm [18]	minimum-cost maximum flow algorithm [19]	proposed MFDI algorithm
ER-ER, $\mu_1 = 2, \mu_2 = 2$	330.99 ± 10.48	330.99 ± 10.48	330.62 ± 10.11
ER-ER, $\mu_1 = 3, \mu_2 = 3$	131.44 ± 9.10	131.44 ± 9.10	127.95 ± 8.87
ER-ER, $\mu_1 = 4, \mu_2 = 4$	44.04 ± 5.52	44.04 ± 5.52	41.88 ± 5.40
ER-ER, $\mu_1 = 5, \mu_2 = 5$	18.10 ± 4.33	18.10 ± 4.33	14.28 ± 3.55
ER-ER, $\mu_1 = 8, \mu_2 = 8$	6.64 ± 2.17	6.64 ± 2.17	1.36 ± 0.66
SF-SF, $\mu_1 = 2, \mu_2 = 2$	776.58 ± 7.89	776.58 ± 7.89	775.16 ± 7.37
SF-SF, $\mu_1 = 3, \mu_2 = 3$	693.82 ± 8.92	693.82 ± 8.92	692.28 ± 8.21
SF-SF, $\mu_1 = 10, \mu_2 = 10$	301.46 ± 9.85	301.46 ± 9.85	300.66 ± 9.88
SF-SF, $\mu_1 = 15, \mu_2 = 15$	129.81 ± 8.07	129.81 ± 8.07	128.64 ± 8.16
SF-SF, $\mu_1 = 20, \mu_2 = 20$	26.41 ± 7.07	26.41 ± 7.07	23.22 ± 6.93
SF-SF, $\mu_1 = 30, \mu_2 = 30$	6.28 ± 1.71	6.28 ± 1.71	1.00 ± 0.00

Table S2: Comparisons between the Number of Driver Nodes Obtained by Different Methods on Two-layer Real-life Multiplex Networks

	maximum flow algorithm [18]	minimum-cost maximum flow algorithm [19]	proposed MFDI algorithm
CKM physicians' innovation [43] $n = 246, E _1 = 480, E _2 = 565$	133	133	127
Lazega law firm [44] $n = 71, E _1 = 892, E _2 = 575$	9	9	6
C. Elegans connectome [47] $n = 279, E _1 = 1031, E _2 = 1639$	135	135	60
C. Elegans GPI [48] $n = 3879, E _1 = 5557, E _2 = 313$	3817	3817	3810
Arabidopsis GPI [48] $n = 6980, E _1 = 13857, E _2 = 4411$	6597	6597	6564

From Tables S1 and S2, it can be observed that the proposed MFDI consistently finds the smallest number of driver nodes on either synthetic or real-life networks. However, it's important to note that we should not claim our algorithm "outperforms" the algorithms in [18, 19] because their optimization targets are different from ours.

2 Applying Single-Layer Methods to Two-Layer Networks

The fundamental distinction between identifying the minimum number of driver nodes required to ensure structural controllability in single-layer and two-layer multiplex networks lies in the location constraints of driver nodes in the latter; they must be situated in the first layer. Casting a two-layer network into a single-layer network and using the method from [27] on two-layer networks may result in driver nodes that violate this location constraint. We further elucidate this with mathematical formulations and supportive

empirical data.

Specifically, in [27], the authors studied the problem of finding the minimum number of driver nodes on single-layer networks, which could be formulated as

$$\begin{aligned}
& \min_{\bar{B} \in \{0, \star\}^{n \times n}} \|\bar{B}\|_0, \\
& \text{s. t. } \dot{\mathbf{x}}(t) = \bar{A}\mathbf{x}(t) + \bar{B}\mathbf{u}(t), \\
& (\bar{A}, \bar{B}) \text{ is structurally controllable,}
\end{aligned} \tag{S3}$$

where $\bar{A} \in \{0, \star\}^{n \times n}$ denotes the wiring diagram of the network, and $\|\bar{B}\|_0$ denotes the number of non-zero entries in B , i.e., the number of driver nodes. This problem was solved by a minimum-weighted maximum matching method.

In our paper, we study the problem of finding the minimum number of driver nodes needed to ensure the structural controllability of multiplex networks, where the driver nodes can only be situated on the first layer of the network. On a two-layer multiplex network, of which the wiring diagram is denoted as $\bar{A} = \begin{bmatrix} \bar{A}_{11} & \mathbf{0} \\ \bar{A}_{21} & \bar{A}_{22} \end{bmatrix} \in \{0, \star\}^{2n \times 2n}$, the problem is formulated as

$$\begin{aligned}
& \min_{\bar{B}_1 \in \{0, \star\}^{n \times n}} \|\bar{B}\|_0, \\
& \text{s. t. } \bar{B} = \begin{bmatrix} \bar{B}_1 \\ \mathbf{0} \end{bmatrix} \in \{0, \star\}^{2n \times n}, \\
& \dot{\mathbf{x}}(t) = \bar{A}\mathbf{x}(t) + \bar{B}\mathbf{u}(t), \\
& (\bar{A}, \bar{B}) \text{ is structurally controllable.}
\end{aligned} \tag{S4}$$

We shall then illustrate that the minimum-weighted maximum matching method in [27] may violate the constraints in our problem (S4). In order to keep the dimensions consistent,

we rewrite the formulation (S3) as

$$\begin{aligned}
& \min_{\bar{B} \in \{0, \star\}^{2n \times n}} \|\bar{B}\|_0, \\
& \text{s. t. } \dot{\mathbf{x}}(t) = \bar{A}\mathbf{x}(t) + \bar{B}\mathbf{u}(t), \\
& (\bar{A}, \bar{B}) \text{ is structurally controllable,}
\end{aligned} \tag{S5}$$

where $\bar{A} \in \{0, \star\}^{2n \times 2n}$. The distinction between (S4) and (S5) is that (S5) does not confine the locations of driver nodes. As such, the lower half of $\bar{B} \in \{0, \star\}^{2n \times n}$, obtained by using minimum-weighted maximum matching method [27], may contain non-zero entries, violating the restriction set in (S4). Table S3 records the proportion of instances where the method proposed in [27] fails to meet the constraints of our problem (S4) on synthetic networks. This implies the scenarios where the lower half of the obtained $\bar{B} \in \{0, \star\}^{2n \times n}$ has non-zero entries. In Table S3, μ_i represents the mean degree of the i^{th} layer. For each network configuration, the result is generated from simulations run on 100 independent networks. Table S4 illustrates cases from real-life multiplex networks, assessing whether the calculated $\bar{B} \in \{0, \star\}^{2n \times n}$, which was obtained using the minimum-weighted maximum matching method [27], violates the constraints outlined in (S4). The real-life network datasets are accessible on the website of CoMuNe Laboratory ², the Research Unit of Bruno Kessler Foundations Center for Information and Communication Technologies. For those networks with more than two layers, we only use the data of the first two layers in the simulations. In Table S4, each real-life multiplex network is represented with n marking the number of nodes in each layer, while $|E_i|$ corresponds to the number of edges in the i^{th} layer. The symbol \checkmark denotes that \bar{B} , calculated using the minimum-weighted maximum matching method, complies with the constraints specified in (S4). Conversely, \times indicates that the calculated \bar{B} violates the constraints.

²<https://manliodedomenico.com/data.php>

Table S3: The proportion of instances where the calculated B using the minimum-weighted maximum matching method [27] on synthetic networks fails to comply with the constraints specified in problem (S4)

two-layer ER-ER multiplex networks, $n = 1000$	$\mu_1 = 2$	$\mu_1 = 3$	$\mu_1 = 4$	$\mu_1 = 5$
$\mu_2 = 2$	100%	100%	100%	100%
$\mu_2 = 3$	100%	100%	100%	100%
$\mu_2 = 4$	84%	83%	94%	100%
$\mu_2 = 5$	46%	42%	43%	67%
two-layer SF-SF multiplex networks, $n = 1000$	$\mu_1 = 2$	$\mu_1 = 3$	$\mu_1 = 4$	$\mu_1 = 5$
$\mu_2 = 2$	100%	100%	100%	100%
$\mu_2 = 3$	100%	100%	100%	100%
$\mu_2 = 4$	92%	100%	100%	100%
$\mu_2 = 5$	86%	95%	100%	100%

Table S4: Assessment of constraint violations in (S4) by the minimum-weighted maximum matching method [27] on real-life multiplex networks

CKM physicians' innovation [43], $n = 246$, $ E _1 = 480$, $ E _2 = 565$	✗
Lazega law firm [44], $n = 71$, $ E _1 = 892$, $ E _2 = 575$	✓
C. Elegans connectome [47], $n = 279$, $ E _1 = 1031$, $ E _2 = 1639$	✗
C. Elegans GPI [48], $n = 3879$, $ E _1 = 5557$, $ E _2 = 313$	✗
Arabidopsis GPI [48], $n = 6980$, $ E _1 = 13857$, $ E _2 = 4411$	✗

From Tables S3 and S4, it can be seen that on either synthetic or real-life networks, the minimum-weighted maximum matching method [27] may violate the constraints in (S4) and is thus not applicable to our problem.

References (in sequence as they appear in this Response)

- [14] M. Pósfai, J. Gao, S. P. Cornelius, A.-L. Barabási, and R. M. D’Souza, “Controllability of multiplex, multi-time-scale networks,” *Phys. Rev. E*, vol. 94, p. 032316, Sep 2016.
- [18] K. Song *et al.*, “Target controllability of two-layer multiplex networks based on network flow theory,” vol. 51, no. 5, pp. 2699–2711, 2021.
- [19] J. Ding *et al.*, “Target controllability in multilayer networks via minimum-cost maximum-flow method,” vol. 32, no. 5, pp. 1949–1962, 2021.
- [43] J. Coleman, E. Katz, and H. Menzel, “The diffusion of an innovation among physicians,” *Sociometry*, vol. 20, no. 4, pp. 253–270, 1957.
- [44] T. A. Snijders, P. E. Pattison, G. L. Robins, and M. S. Handcock, “New specifications for exponential random graph models,” *Sociol. Methodol.*, vol. 36, no. 1, pp. 99–153, 2006.
- [47] B. L. Chen, D. H. Hall, and D. B. Chklovskii, “Wiring optimization can relate neuronal structure and function,” *Proc. Natl. Acad. Sci.*, vol. 103, no. 12, pp. 4723–4728, 2006.
- [48] C. Stark, B. J. Breitkreutz, T. Regul, L. Boucher, A. Breitkreutz, and M. Tyers, “Biogrid: a general repository for interaction datasets,” *Nucleic Acids Res.*, vol. 34, no. suppl_1, pp. D535–D539, 2006.
- [27] S. Pequito, S. Kar, and A. P. Aguiar, “A framework for structural input/output and control configuration selection in large-scale systems,” vol. 61, no. 2, pp. 303–318, 2016.