

Package ‘pqr’

January 16, 2020

Type Package

Title Regularized projection score estimation of treatment effects in high-dimensional quantile regression

Version 1.0.1

Date 2019-12-11

Author Chao Cheng [aut],
Xingdong Feng [aut],
Jian Huang [aut],
Xu Liu [aut,cre]

Maintainer Xu Liu <liu.xu@shufe.edu> and Chao Cheng

Depends R (>= 3.1.0), SparseM, quantreg

Imports glmnet, gprreg

Description A regularized projection score method is proposed for estimating treatment effects in quantile regression in the presence of high-dimensional confounding covariates. This method is based on an estimated projection score function of the low-dimensional treatment parameters in the presence of high-dimensional confounding covariates. We propose one-step algorithm and a refitted wild bootstrapping approach for variance estimation. This enables us to construct confidence intervals for the treatment effects in the high-dimensional circumstances.

License GPL-2

LazyData true

NeedsCompilation yes

Repository GitHub

URL <https://github.com/xliusufe/pqr>

Encoding UTF-8

R topics documented:

pqr-package	2
infern	2

Index	5
--------------	----------

pqr-package	<i>Regularized projection score estimation of treatment effects in high-dimensional quantile regression</i>
-------------	---

Description

A regularized projection score method is proposed for estimating treatment effects in quantile regression in the presence of high-dimensional confounding covariates. This method is based on an estimated projection score function of the low-dimensional treatment parameters in the presence of high-dimensional confounding covariates. We propose one-step algorithm and a refitted wild bootstrapping approach for variance estimation. This enables us to construct confidence intervals for the treatment effects in the high-dimensional circumstances.

Details

Package: pqr
 Type: Package
 Version: 1.0.1
 Date: 2019-12-12
 License: GPL-2

References

Cheng, C., Feng, X., Huang, J. and Liu, X. (2020). Regularized projection score estimation of treatment effects in high-dimensional quantile regression. Manuscript.

infern	<i>Provide CI of individual coefficient of high-dimensional quantile regression.</i>
--------	--

Description

This function provides the confidence intervals of individual coefficient of high-dimensional quantile regression by a regularized projection score method for estimating treatment effects. One-step estimation procedure can speed up computation, and the Bootstrap method can narrow the length of CI.

Usage

```
infern(y,x,z,tau,method="OneStep",pen="lasso",eps=1e-6,
      level=0.85,iter.num=100,RCV=F,K=1,weights=NULL,B=1000)
```

Arguments

<code>y</code>	The response, a vector of size n
<code>x</code>	The treatment effects, a matrix with dimension $n \times p$
<code>z</code>	The confounders a matrix with dimension $n \times q$
<code>tau</code>	The given quantile, a scale in the unit interval
<code>method</code>	The method including "OneStep", "Iterative". "OneStep" denotes one-step method (Feng et al. 2019); "Iterative" denotes that the iteration stops when algorithm converges. Default is "OneStep".
<code>pen</code>	The penalty including "glasso" and "lasso". "glasso" denotes the grouped lasso that is used in the regression of treatment effect on confounders; "lasso" denotes the lasso. Default is "glasso".
<code>eps</code>	The perturbation when the proposed algorithm is used. Default is $\epsilon=1e-6$.
<code>level</code>	The length of tuning parameter α which is selected automatically. Default is 50.
<code>iter.num</code>	The number of iteration if <code>method="Iterative"</code> is used. Default is 100.
<code>RCV</code>	Use refitted cross validation method and wild bootstrap to estimate the asymptotic covariance matrix. Default is False.
<code>K</code>	The number of repeated RCV. Default is 1.
<code>weights</code>	The weights used for wild bootstrap; if not specified (=NULL). Default is NULL.
<code>B</code>	The size for bootstrap. Default is 1000.

Value

<code>ests</code>	Estimator of β . It is a list.
<code>covs</code>	Covariance matrix of β . It is a $d \times d$ -matrix.

Author(s)

Chao Cheng, Xingdong Feng, Jian Huang and Xu Liu (liu.xu@sufe.edu.cn)

References

Cheng, C., Feng, X., Huang, J. and Liu, X. (2020). Regularized projection score estimation of treatment effects in high-dimensional quantile regression. Manuscript.

Examples

```
library(pqr)
library(SparseM)
library(quantreg)
n <- 50
d <- 3
s <- 3
p <- 20
alpha <- 0.95
beta <- rep(3,d)
eta <- c(rep(3,s),numeric(p-s))
x <- matrix(rnorm(n*d),n,d)
z <- matrix(rnorm(n*(p-1)),n,p-1)
y <- x%*%beta + cbind(1,z)%*%eta + rnorm(n)
fit <- infern(y,x,z,tau=0.5)
```

```
ests <- fit$ests
est.coef <- ests$coef
boot.var <- diag(fit$cov)
lbounds <- ests$coef - qnorm((1+alpha)/2)*sqrt(boot.var)
ubounds <- ests$coef + qnorm((1+alpha)/2)*sqrt(boot.var)
counts <- ifelse(lbounds<beta&beta<ubounds,1,0)
```

Index

*Topic **Projection score**

inferen, [2](#)

*Topic **Quantile regression**

inferen, [2](#)

*Topic **package**

pqr-package, [2](#)

inferen, [2](#)

pqr (pqr-package), [2](#)

pqr-package, [2](#)