

Package ‘limai’

August 27, 2025

Title Linear modeling and AI decision making

Version 0.0.1

Author Xu Liu [aut,cre]

Maintainer Xu Liu <liu.xu@sufe.edu.cn>

Description Datasets used in the book ``Linear modeling and AI decision making"

License GPL (>=2)

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Depends R (>= 3.5.0)

Imports Matrix, glmnet

LazyData true

Contents

boston	2
breastcancer	3
CHARLS	4
game	6
GTEEx_apoe	7
happiness	8
insurance	9
lungcapacity	10
MBI	11
personality	11
pollution	12
skcm	14
socialmedia	15
Index	17

boston	<i>Boston housing data</i>
--------	----------------------------

Description

The dataset contains information on housing values in suburbs of Boston, including various attributes such as crime rate, property tax, and average number of rooms.

Usage

```
data(boston)
```

Arguments

crim	Per capita crime rate by town.
zn	Proportion of residential land zoned for large lots (over 25,000 square feet).
indus	Proportion of non-retail business acres per town.
chas	Charles River dummy variable (1 if tract bounds river; 0 otherwise).
nox	Nitrogen oxide concentration (parts per 10 million).
rm	Average number of rooms per dwelling.
age	Proportion of owner-occupied units built before 1940.
dis	Weighted distance to employment centers in Boston.
rad	Index of accessibility to radial highways.
tax	Full-value property tax rate per \$10,000.
ptratio	Pupil-teacher ratio by town.
b	Proportion of residents of African American descent.
lstat	Percentage of lower status population.
medv	Median value of owner-occupied homes in \$1000s.

Details

The dataset is derived from the Boston Housing dataset, originally from the UCI Machine Learning Repository. It contains data collected from 506 census tracts in Boston, providing a snapshot of various housing-related features, which can be used for regression and classification tasks in machine learning.

Source

<https://lib.stat.cmu.edu/datasets/boston> or R package MASS

References

Harrison, D., & Rubinfeld, D. L. (1978). Hedonic housing prices and the demand for clean air. *Journal of Environmental Economics and Management*, 5(1), 81-102.

Examples

```
data(boston)
model = lm(medv ~ ., data = boston)
summary(model)
```

breastcancer	<i>Breast cancer data</i>
--------------	---------------------------

Description

The dataset contains gene expression and gene copy number information from 89 subjects.

Usage

```
data(breastcancer)
```

Arguments

dna	Copy number variation (CNV) data representing genomic DNA amplification or deletion events in tumor samples.
rna	Gene expression profiles measured via RNA transcript levels (e.g., microarray or RNA-seq data).
chrom	Chromosome numbers (1-22, X, Y) corresponding to the genomic location of the measured genes.
nuc	Nucleotide positions (start/end coordinates) of genes or probes on the chromosome (e.g., hg18/hg19 reference).
gene	Unique gene identifiers (e.g., Entrez Gene IDs or probe IDs) linked to genomic features.
genenames	Official gene symbols or names (e.g., BRCA1, ERBB2) standardized by HUGO Gene Nomenclature Committee (HGNC).
genechr	Chromosomal mapping information for each gene (e.g., "chr17" for TP53).
genedesc	Brief functional descriptions of genes (e.g., "tumor protein p53" or "estrogen receptor 1").
genepos	Genomic coordinates of genes (e.g., cytoband or base-pair positions like "17q21.31").

Details

The dataset is derived from molecular bioinformatics data obtained from breast cancer tissue samples treated according to the standard of care between 1989 and 1997. It primarily consists of gene expression profiles and copy number variation data across 22 chromosomal pairs in tumor tissue samples from 89 breast cancer patients. For a detailed explanation of this dataset, please refer to Chin et al. (2006).

Source

<http://icbp.lbl.gov/breastcancer/> or R package PMA

References

Chin, K., DeVries, S., et al. (2006). Genomic and transcriptional aberrations linked to breast cancer pathophysiologies. *Cancer cell*, **10**(6), 529-541.

Examples

```
library(glmnet)
data(breastcancer)
dna = breastcancer$dna[breastcancer$chrom==21,]
rna = breastcancer$rna[which(breastcancer$genechr==21),]
y = dna[1,]
x = t(rna)
set.seed(100)
fit_ridge = cv.glmnet(x,y,alpha = 0)
coef(fit_ridge, s = "lambda.min")
fit_lasso = cv.glmnet(x,y,alpha = 1)
coef(fit_lasso, s = "lambda.min")
```

CHARLS	<i>China Health and Retirement Longitudinal Study (CHARLS) data of Hebei, Shandong, and Fujian provinces.</i>
--------	---

Description

The dataset contains the CHARLS data collected in Hebei, Shandong, and Fujian provinces.

Usage

```
data(CHARLS)
```

Format

A list object containing the following 3 variables:

Name	Type	Description
hebei	matrix	The CHARLS data of Hebei province. A matrix with 257 rows and 50 columns including y and 49 covariates v1,...,v49.
shandong	matrix	The CHARLS data of Shandong province. A matrix with 413 rows and 50 columns including y and 49 covariates v1,...,v49.
fujian	matrix	The CHARLS data of Fujian province. A matrix with 167 rows and 50 columns including y and 49 covariates v1,...,v49.

Details

Each matrix containing y, v1-v49 variables:

Name	Description
y	Annual support income of elderly people.
v1	Gender: 1 = male, 0 = female.
v2	Age.
v3	Education level: 1 = primary, 2 = junior high, 3 = high school, 4 = other.
v4	Marital status: 1 = married, 0 = unmarried.
v5	Live alone: 1 = yes, 0 = no.
v6	Live with a spouse: 1 = yes, 0 = no.
v7	Live with children: 1 = yes, 0 = no.

- v8 Live with other members (e.g., parents): 1 = yes, 0 = no.
- v9 Health status: 1 = disability/chronic illness, 0 = healthy.
- v10 Pension income.
- v11 Whether to receive a pension: 1 = yes, 0 = no.
- v12 Number of surviving children: 0 = none, 1 = one, 2 = two or more.
- v13 Wage income per household.
- v14 Net operating income per household.
- v15 Net transfer income per household.
- v16 Number of children with a college degree or above.
- v17 Number of children earning over 10,000 CNY annually.
- v18 Emotional comfort: 1 = contact children $\geq$ every half month, 0 = otherwise.
- v19 Number of household members.
- v20 Number of deceased biological children.
- v21 Number of surviving adopted children.
- v22 Number of surviving sons.
- v23 Financial support for parents.
- v24 Financial support for other relatives.
- v25 Net financial support received from other relatives.
- v26 Number of types of disability.
- v27 Chronic illness: 0 = no, 1 = yes, 2 = other.
- v28 Whether to receive a retirement pension: 1 = yes, 0 = no.
- v29 Retirement pension income.
- v30 New rural pension income.
- v31 All other pension income.
- v32 Pension income of elderly households.
- v33 Total financial assets of elderly and spouses.
- v34 Wage income of main household members.
- v35 Government subsidies for individual families.
- v36 Government subsidies for main household members.
- v37 Wage income of other family members.
- v38 Government subsidies for other family members.
- v39 Total government subsidies for families.
- v40 Government transfer income for households.
- v41 Net household income excluding private transfers.
- v42 Net household income.
- v43 Net household income per capita.
- v44 Other net private transfer income of elderly.
- v45 Family shared income received by elderly.
- v46 Whether to complete junior high school education: 1 = yes, 0 = no.
- v47 Whether to complete high school education: 1 = yes, 0 = no.
- v48 Annual net income from other sources.
- v49 Financial support provided for children.

Source

The CHARLS data from <https://charls.charlsdata.com/pages/Data/2015-charls-wave4/zh-cn.html>

References

Ren, P., Liu, X., Zhang, X., Zhan, P., & Qiu, T. (2024). Integrative analysis of high-dimensional quantile regression with contrasted penalization. *Journal of Applied Statistics*, 1-17.

Examples

```
library(glmnet)
data(CHARLS)
data_hebei = CHARLS$hebei
y = data_hebei$y
x = data_hebei[, -1]
x = matrix(unlist(x), nrow = nrow(x))
fit_lasso = cv.glmnet(x, y, alpha = 1)
coef(fit_lasso, s = "lambda.min")
```

game

Online Gaming Behavior Dataset

Description

This dataset captures comprehensive metrics and demographics related to player behavior in online gaming environments. It includes variables such as player demographics, game-specific details, engagement metrics, and a target variable reflecting player retention.

Usage

```
data(game)
```

Arguments

A data frame object containing 200 player entries with the following 13 variables:

Name	Type	Description
ID	integer	Unique identifier for each player
age	integer	Age of the player
gender	character	Gender of the player
location	character	Geographic location of the player
genre	character	Genre of the game the player is engaged in
time	numeric	Average hours spent playing per session
inbuy	integer	Indicates whether the player makes in-game purchases (0 = No, 1 = Yes)
difficulty	character	Difficulty level of the game
session	integer	Number of gaming sessions per week
sesslong	integer	Average duration of each gaming session in minutes
level	integer	Current level of the player in the game
achievement	integer	Number of achievements unlocked by the player
engagement	character	Categorized engagement level reflecting player retention ('High', 'Medium', 'Low')

Details

The data provides information on various aspects of online gaming behavior for 200 players, including player identifiers, demographic details, gaming - related metrics.

Source

The dataset from Kaggle website <https://www.kaggle.com/datasets/rabieelkharoua/predict-online-gaming-behavior-dataset/data>

Examples

```
data(game)

# Check the relationship between in - game purchases and session length
cor(game$inbuy, game$sessionlong, use = "complete.obs")

# Count the number of players in each game genre
genre_counts <- table(game$genre)
barplot(genre_counts,
        main = "Number of Players in Each Game Genre",
        xlab = "Game Genre",
        ylab = "Number of Players")
```

GTEx_apoe

GTEx data associated with APOE gene

Description

The dataset contains APOE gene and other related genes from 111 subjects.

Usage

```
data(GTEx_apoe)
```

Details

This dataset contains gene expression profiles and genomic data derived from the Genotype-Tissue Expression (GTEx) project. It is a list with 111 rows and 119 columns, and the last column is the APOE gene, the other 118 columns is the related genes.

Source

Genotype-Tissue Expression (GTEx) project, available at: <https://www.gtexportal.org/home/>

Examples

```
library(glmnet)
data(GTEx_apoe)
y = GTEx_apoe$APOE
x = GTEx_apoe[,-1]
x = matrix(unlist(x), nrow = nrow(x))
fit_lasso = cv.glmnet(x,y,alpha = 1)
coef(fit_lasso,s = "lambda.min")
```

`happiness`*World Happiness Report Dataset (2016)*

Description

This dataset provides country-level measures of happiness from the World Happiness Report 2016. It includes overall happiness scores, rankings, and contributing factors such as GDP, family support, life expectancy, freedom, generosity, and corruption perception. The dataset enables quantitative analysis of global well-being and policy-related research.

Usage

```
data(happiness)
```

Arguments

A data frame object containing country-level records with the following 13 variables:

Variable Name	Variable Description
Country	Country name
Region	Region where the country is located
Rank	Ranking based on overall happiness score
Score	Happiness score in 2016 (0-10)
Economy (GDP per Capita)	Contribution of GDP per capita to happiness score
Family	Contribution of social support to happiness score
Health (Life Expectancy)	Contribution of life expectancy to happiness score
Freedom	Contribution of personal freedom to happiness score
Generosity	Contribution of generosity to happiness score
Trust (Government Corruption)	Contribution of distrust in government corruption to happiness score
Dystopia Residual	Residual compared to the "dystopia" benchmark

Details

The World Happiness Report dataset is based on Gallup World Poll survey results, evaluating happiness scores across countries. The dataset allows exploration of how economic, social, and political factors contribute to happiness.

Source

Data from Kaggle: <https://www.kaggle.com/datasets/unsdsn/world-happiness>

Examples

```
data(happiness)

hist(happiness$happ_score,
     main = "Distribution of Happiness Scores (2016)",
     xlab = "Happiness Score",
     ylab = "Frequency")
```

insurance

Medical Insurance Expenditure Dataset

Description

This dataset contains annual medical charges for insured individuals in the United States, along with demographic and lifestyle-related predictors. It is commonly used for building predictive models (e.g., regression) to estimate future medical costs, which supports actuarial pricing and risk stratification.

Usage

```
data(insurance)
```

Arguments

A data frame with 1,338 observations of insured individuals (aged 18–64), with the following 7 variables:

Name	Type	Description
age	integer	Age of the primary beneficiary (18–64 years)
sex	character	Gender of the insured (female/male)
bmi	numeric	Body mass index (kg/m ²)
children	integer	Number of children/dependents covered by insurance
smoker	character	Smoking status (yes/no)
region	character	Residential region (northeast/southeast/southwest/northwest)
charges	numeric	Annual medical expenditure (in USD)

Details

The dataset was simulated based on U.S. Census Bureau data and introduced in Chapter 6 of *Machine Learning with R*. It is widely used for regression modeling to estimate healthcare costs and to demonstrate how demographic and lifestyle variables influence expenditures.

Source

Original dataset from GitHub: <https://github.com/stedy/Machine-Learning-with-R-datasets>

Examples

```
data(insurance)

# Display first rows
head(insurance)

# Fit a linear regression model: charges ~ age + bmi + children + smoker + region
model <- lm(charges ~ age + bmi + children + smoker + region,
            data = insurance)

summary(model)
```

lungcapacity	<i>Children's Lung Capacity Dataset</i>
--------------	---

Description

This dataset contains measurements of lung capacity in children and adolescents aged 3 to 19 years. It includes physiological measurements, demographic information, and health-related factors that may influence respiratory development.

Usage

```
data(lungcapacity)
```

Arguments

A data frame with 725 observations and the following 6 variables:

Variable	Type	Description
LungCap	numeric	Lung capacity measurement (liters)
Age	integer	Age of child in years (3-19)
Height	numeric	Height in inches (45.3-81.8)
Smoke	character	Smoking habit (no/yes)
Gender	character	Gender (male/female)
Caesarean	character	Born by Caesarean section (no/yes)

Source

The dataset from Kaggle website <https://www.kaggle.com/datasets/jacopoferretti/lung-capacity-of-kids>

Examples

```
data(lungcapacity)

# Basic summary statistics
summary(lungcapacity)

# Compare lung capacity between smokers and non-smokers
boxplot(LungCap ~ Smoke, data = lungcapacity,
        main = "Lung Capacity by Smoking Status",
        xlab = "Smoker", ylab = "Lung Capacity (liters)")
```

MBI*MBI Dataset*

Description

A dataset containing gender, height and weight measurements for individuals.

Usage

```
data(MBI)
```

Arguments

A data frame object containing 10000 samples entries with the following 3 variables: "Gender", "Height", "Weight"

Name	Type
Weight	integer
Height	integer
Gender	character

Details

The dataset contains 10000 samples with three variables. We can use this dataset to explore the relationship between height and weight. And calculate MBI (Mass Body Index) = weight/height.

Source

Data from Kaggle: <https://www.kaggle.com/datasets/mustafaali96/weight-height/data>

Examples

```
data(MBI)

cor(MBI$Weight, MBI$Height, use = "complete.obs")
```

personality*Extrovert vs. Introvert Personality Traits Dataset*

Description

Dive into the Extrovert vs. Introvert Personality Traits Dataset, a rich collection of behavioral and social data designed to explore the spectrum of human personality. This dataset captures key indicators of extroversion and introversion, making it a valuable resource for psychologists, data scientists, and researchers studying social behavior, personality prediction, or data preprocessing techniques.

Usage

```
data(personality)
```

Arguments

A data frame with 2,900 observations and the following 8 variables:

Variable	Type	Description
AloneTime	numeric	Daily hours spent alone (0-11 hours)
StageFear	character	Presence of stage fright (Yes/No)
SocialEvents	numeric	Frequency of social events attended (0-10 scale)
GoOut	numeric	Frequency of going outside (0-7 days/week)
Drained	character	Feeling drained after socializing (Yes/No)
Friends	numeric	Number of close friends (0-15 people)
PostFreq	numeric	Social media post frequency (0-10 scale)
Personality	character	Target personality classification (Extrovert/Introvert)

Source

The dataset is taken from an open source on Kaggle website <https://www.kaggle.com/datasets/example/personality-traits>

Examples

```
data(personality)

# Examine relationship between social events and friends count
cor(personality$SocialEvents, personality$Friends, use = "complete.obs")

# Plot distribution of social engagement
barplot(table(personality$SocialEvents),
        main = "Distribution of Social Event Attendance",
        xlab = "Attendance Frequency",
        ylab = "Number of Individuals")
```

pollution	<i>Air Quality Index (AQI) for Chinese Cities (2022)</i>
-----------	--

Description

A multidimensional dataset containing weekly Air Quality Index (AQI), meteorological parameters, and socioeconomic indicators for 173 Chinese cities in 2022.

Usage

```
data(pollution)
```

Arguments

A list object containing 173 city entries with the following 10 variables:

Name	Type	Description
AQI	matrix	Air Quality Index, a matrix with 173 rows (cities) and 51 columns (weekly AQI values). Higher values indicate poorer air quality.
city	character	City names vector (length 173).
temp	numeric	Annual mean air temperature in °C.
dew	numeric	Annual mean dew point temperature in °C.
windD	numeric	Wind direction in degrees (0-360).
windS	numeric	Annual mean wind speed in m/s.
pres	numeric	Annual mean atmospheric pressure in hPa.
pop	numeric	Household resident population (unit: 10,000).
green	numeric	Green Covered Area as percentage of Completed Area (0-100).
second	numeric	Secondary Industry as Percentage to GRP (0-100).

Details

The data provides AQI data for 173 Chinese cities for the 51 weeks of 2022 and economic and meteorological related annual average data.

Source

- Air Quality Index form China National Environmental Monitoring Center(<https://air.cnemc.cn:18007/>)
- Meteorological Data from NOAA National Centers for Environmental Information (<https://www.ncei.noaa.gov/>)
- Socioeconomic data from China City Statistical Yearbook (<https://www.stats.gov.cn/>)

References

Guan, X., Li, Y., Liu, X., & You, J. (2025). Subgroup learning in functional regression models under the RKHS framework. *arXiv preprint arXiv:2503.01515*.

Examples

```
data(pollution)

# Explore AQI distribution for Beijing
bj_aqi <- as.numeric(pollution$AQI[pollution$city == "Beijing", ])
plot(bj_aqi,
     type = "l",
     main = "Weekly AQI in Beijing (2022)",
     xlab = "Week",
     ylab = "AQI")

# Correlation analysis
cor(pollution$temp, rowMeans(pollution$AQI, na.rm = TRUE))
```

skcm

*Skin Cutaneous Melanoma (SKCM) data***Description**

The dataset contains clinical outcome measurements and high-dimensional gene expression profiles from 361 subjects with skin cutaneous melanoma.

Usage

```
data(skcm)
```

Arguments

- | | |
|------------|--|
| y | A numeric vector of length 361 representing Breslow's thickness, a clinico-pathologic feature of cutaneous melanoma. |
| gexp | A data frame with 361 rows and 2000 columns, where each column represents expression values of a gene. Gene names are provided as column names (e.g., SLC8A1, DPYD). |
| adj_matrix | <p>A 2000 x 2000 adjacency matrix representing gene-gene interaction relationships in gexp. Entries are defined as:</p> <ul style="list-style-type: none"> • 1: If two genes are directly interacting in the KEGG melanoma pathway (hsa05218) • 0: Otherwise (no interaction or gene not in the pathway) |

We obtain melanoma-related pathway data through KEGG portal:

1. Access <https://www.kegg.jp/> and search "melanoma"
2. Identify pathway ID: hsa05218 (Skin Cutaneous Melanoma)
3. Contains 73 genes with curated regulatory relationships

Key construction steps see Details.

Details

The dataset includes 361 samples with outcomes (Breslow's thickness measurements) and expression levels of the top 2000 most variable genes. It is derived from The Cancer Genome Atlas (TCGA) for Skin Cutaneous Melanoma (SKCM), one of the most aggressive cancer types.

adj_matrix construction follows these key steps:

1. **Pathway Data Retrieval:** Download KGML file from KEGG via:

```
download.file("https://rest.kegg.jp/get/hsa05218/kgml", "melanoma_kgml.xml")
```

2. **Graph Parsing:** Convert KGML to adjacency matrix:

```
if (!require("BiocManager", quietly = TRUE))
  install.packages("BiocManager")
BiocManager::install("KEGGgraph")

library(KEGGgraph)
melanoma_kgml <- "melanoma_kgml.xml"
kegg_graph <- parseKGML2Graph(melanoma_kgml, genesOnly = TRUE)
adjacent <- as(kegg_graph, "matrix")
adj_matrix_KEGG <- adjacent + t(adjacent)
```

3. **Gene ID Conversion:** Map KEGG IDs to Gene Symbols:

```
BiocManager::install("KEGGREST")
BiocManager::install("org.Hs.eg.db")

library(KEGGREST)
library(org.Hs.eg.db)
kegg_genes <- keggLink("hsa", "hsa05218")
kegg_ids <- gsub("hsa:", "", kegg_genes)
gene_symbols <- mapIds(org.Hs.eg.db,
  keys = kegg_ids,
  column = "SYMBOL",
  keytype = "ENTREZID") # Get Symbol mapping
rownames(adj_matrix_KEGG) <- gene_symbols[match(rownames(adj_matrix_KEGG), kegg_genes)]
colnames(adj_matrix_KEGG) <- rownames(adj_matrix_KEGG)
```

4. **Matrix Embedding:** Create final adjacency matrix:

```
gene_skcm <- colnames(skcm$gexp)
p <- length(gene_skcm)
adj_matrix_skcm <- matrix(0, nrow = p, ncol = p, dimnames = list(gene_skcm, gene_skcm))
common_genes <- intersect(gene_skcm, gene_symbols)
adj_matrix_skcm[common_genes, common_genes] <- adj_matrix_KEGG[common_genes, common_genes]
```

Source

The Cancer Genome Atlas (TCGA) portal: <https://tcga-data.nci.nih.gov>

References

- The Cancer Genome Atlas Consortium. (2015). Genomic classification of cutaneous melanoma. *Cell*, **161**(7), 1681-1696.
- Tan, X., Zhang, X., Cui, Y., & Liu, X. (2024). Uncertainty quantification in high-dimensional linear models incorporating graphical structures with applications to gene set analysis. *Bioinformatics*, **40**(9), btae541.

Examples

```
data(skcm)
hist(skcm$y, main = "Distribution of Clinical Outcomes", xlab = "Outcome Value")
pca_result <- prcomp(skcm$gexp[, 1:100], scale = TRUE) # Run PCA on the top 100 genes
plot(pca_result$x[, 1:2], main = "PCA of Gene Expression Data")
```

Description

This dataset contains anonymized records of students' social media behaviors and related life outcomes. Spanning multiple countries and academic levels, it captures key dimensions including usage intensity, platform preferences, and relationship dynamics.

Usage

```
data(socialmedia)
```

Arguments

A data frame with configurable observations (typically 100-1000) and the following 13 variables:

Variable & Type & Description

id & integer & Unique student identifier
age & integer & Age in years (16-25)
gender & character & Gender identity (Male/Female)
academic & character & Academic level (High School/Undergraduate/Graduate)
country & character & Country of residence (Bangladesh, India, USA, UK, etc.)
usage & numeric & Average daily social media usage in hours
platform & character & Most frequently used platform (Instagram, Facebook, TikTok, etc.)
affects_academic & character & Self-reported academic impact (Yes/No)
sleep & numeric & Average nightly sleep duration in hours
health & integer & Self-rated mental health score (1 = poor to 10 = excellent)
relationship & character & Relationship status (Single/In Relationship/Complicated)
conflicts & integer & Number of relationship conflicts attributed to social media
addiction & integer & Social media addiction score (1 = low to 10 = high)

Source

The dataset is taken from an open source on Kaggle website <https://www.kaggle.com/datasets/adilshamim8/social-media-addiction-vs-relationships>

Examples

```
data(socialmedia)

# Visualize addiction scores by platform
boxplot(addiction ~ platform, data = socialmedia,
        main = "Addiction Scores by Social Media Platform",
        xlab = "Platform", ylab = "Addiction Score")
```


Index

* datasets

- game, [6](#)
- happiness, [8](#)
- insurance, [9](#)
- lungcapacity, [10](#)
- MBI, [11](#)
- personality, [11](#)
- pollution, [12](#)
- socialmedia, [15](#)

boston, [2](#)

breastcancer, [3](#)

CHARLS, [4](#)

game, [6](#)

GTEEx_apoe, [7](#)

happiness, [8](#)

insurance, [9](#)

lungcapacity, [10](#)

MBI, [11](#)

personality, [11](#)

pollution, [12](#)

skcm, [14](#)

socialmedia, [15](#)