

# Package ‘tensorApp’

February 12, 2020

**Type** Package

**Title** tensorApp

**Version** 0.1.0

**Author** Xu Liu [aut,cre].

**Maintainer** Xu Liu <liu.xu@sufe.edu.cn>

**Description**

High-order SVD approximation of a tensor by Tucker or CP decomposition and rank selection.

**License** GPL (>= 2)

**Imports** Rcpp (>= 0.11.15), RcppEigen (>= 0.3.2.3.0)

**LinkingTo** Rcpp, RcppEigen

**RoxygenNote** 6.0.1

**NeedsCompilation** yes

**Repository** github

**URL** <https://github.com/xliusufe/tensorApp>

**Encoding** UTF-8

## R topics documented:

tensorApp-package . . . . .	1
HOsvd . . . . .	2
HOsvd_dr . . . . .	3
TransUnfoldingsT . . . . .	5
<b>Index</b>	<b>6</b>

---

tensorApp-package	<i>High-order SVD approximation of a tensor <math>\mathcal{Y}</math> by Tucker or CP decomposition and selection of ranks</i>
-------------------	---

---

## Description

High-order SVD approximation of a tensor  $\mathcal{Y}$  by Tucker decomposition or CANDECOMP/PARAFAC (CP) decomposition and selection of ranks.

### Details

High-order SVD approximation of a tensor  $\mathbf{Y}$  by Tucker decomposition or CANDECOMP/PARAFAC (CP) decomposition and selection of ranks.

### Author(s)

Xu Liu

Maintainer: Xu Liu <liu.xu@sufe.edu.cn>

---

HOsvd	<i>High-order SVD approximation of a tensor <math>\mathbf{Y}</math> by Tucker or CP decomposition</i>
-------	---

---

### Description

High-order SVD approximation of a tensor  $\mathbf{Y}$  by Tucker decomposition or CANDECOMP/PARAFAC (CP) decomposition with preset rank.

### Usage

```
HOsvd(Y, d0=NULL, dims=NULL, isCP=TRUE, ranks=NULL, dr=20,
      D0=NULL, eps=1e-6, max_step=100)
```

### Arguments

$\mathbf{Y}$	An array with dimension $\mathbf{dims}$ , or a $n_{d0} \times N/n_{d0}$ numeric matrix of responses that is the mode $d0$ -unfolding of tensor in $\mathcal{R}^{n_1 \times \dots \times n_d}$ , where $N = n_1 \times \dots \times n_d$ .
$d0$	$d0$ is the mode which unfoldings $\mathbf{Y}$ is. $d0$ can be NULL (the default) if $\mathbf{Y}$ is an array with dimension $\mathbf{dims}$ .
$\mathbf{dims}$	The size of tensor $\mathbf{Y}$ , which is a $d$ -vector $(n_1, \dots, n_d)$ . $\mathbf{dims}$ can be NULL (the default) if $\mathbf{Y}$ is an array with dimension $\mathbf{dims}$ . If the length of $\mathbf{dims}$ is 2, it is the ordinary SVD decomposition of a matrix.
$isCP$	A logical value indicating whether CP decomposition will be used. Default is TRUE.
$\mathbf{ranks}$	The user-specified ranks. It is a vector with length $d$ . Default is $(2, \dots, 2)$ .
$dr$	The user-specified rank for CP decomposition. It is useless if Tucker decomposition is used. Default is 20.
$D0$	A user-specified list of initial matrices of $U_1, U_2, \dots, U_d$ and core tensor $S$ , $D0 = \text{list}(U_1 = U_1, \dots, U_d = U_d, S = S)$ . By default, initial matrices are provided by random.
$eps$	Convergence threshold. The algorithm iterates until the relative change in any coefficient is less than $eps$ . Default is $1e-6$ .
$max\_step$	Maximum number of iterations. Default is 100.

### Details

This function gives a  $n_{d0} \times N/n_{d0}$  matrix, which is the mode- $d0$  unfolding, and approximates  $\mathbf{Y}$ .

**Value**

Tnew	Approximation of $\mathbf{Y}$ .
Tn	A list of estimated matrices of $U_1, U_2, \dots, U_d$ and core tensor $S$ , $Tn = list(U_1 = U_1, \dots, U_d = U_d, S = S)$ .
ranks	The ranks of estimated tensor Tnew. It is a vector with the same length as dims if Tucker decomposition is used, or an integer if CP decomposition is used.

**See Also**

HOSvd\_dr

**Examples**

```

dims <- c(8,8,10,10,6)
N <- length(dims)
ranks <- rep(2,N)
S0 = matrix(runif(prod(ranks),3,7),ranks[N])
T1 <- matrix(rnorm(dims[1]*ranks[1]),nrow = dims[1])
tmp <- qr.Q(qr(T1))
for(k in 2:(N-1)){
  T1 <- matrix(rnorm(dims[k]*ranks[k]),nrow = dims[k])
  tmp <- kronecker(qr.Q(qr(T1)),tmp)
}
T1 <- matrix(rnorm(dims[N]*ranks[N]),nrow = dims[N])
U = qr.Q(qr(T1))
Y <- U%*%S0%*%t(tmp)

fit <- HOSvd(Y,N,dims,isCP=TRUE)
Tnew <- fit$Tnew
ranks1 <- fit$ranks
lambda <- fit$Tn[[N+1]]
U1 <- fit$Tn[[1]]
TNew1 <- TransUnfoldingsT(Tnew,N,1,dims)

```

HOSvd\_dr

*High-order SVD approximation of a tensor  $\mathbf{Y}$  by Tucker or CP decomposition and selection of ranks*

**Description**

High-order SVD approximation of a tensor  $\mathbf{Y}$  by Tucker decomposition or CANDECOMP/PARAFAC (CP) decomposition and selection of ranks.

**Usage**

```

HOSvd_dr(Y, d0=NULL, dims=NULL, isCP=TRUE, ranks=NULL, dr=100,
          D0=NULL, eps=1e-6, max_step=100, thresh=1e-6)

```

**Arguments**

Y	An array with dimension <code>dims</code> , or a $n_{d0} \times N/n_{d0}$ numeric matrix of responses that is the mode <code>d0</code> -unfolding of tensor in $\mathcal{R}^{n_1 \times \dots \times n_d}$ , where $N = n_1 \times \dots \times n_d$ .
d0	<code>d0</code> is the mode which unfoldings <code>Y</code> is. <code>d0</code> can be <code>NULL</code> (the default) if <code>Y</code> is an array with dimension <code>dims</code> .
dims	The size of tensor <code>Y</code> , which is a $d$ -vector $(n_1, \dots, n_d)$ . <code>dims</code> can be <code>NULL</code> (the default) if <code>Y</code> is an array with dimension <code>dims</code> . If the length of <code>dims</code> is 2, it is the ordinary SVD decomposition of a matrix.
isCP	A logical value indicating whether CP decomposition will be used. Default is <code>TRUE</code> .
ranks	The user-specified ranks. It is a vector with length <code>d</code> . Default is $(2, \dots, 2)$ .
dr	The user-specified rank for CP decomposition. It is useless if Tucker decomposition is used. Default is 100.
D0	A user-specified list of initial matrices of $U_1, U_2, \dots, U_d$ and core tensor $S$ , <code>D0=list(<math>U_1 = U_1, \dots, U_d = U_d, S = S</math>)</code> . By default, initial matrices are provided by random.
eps	Convergence threshold in the inner loop. The algorithm iterates until the relative change in any coefficient is less than <code>eps</code> . Default is $1e-6$ .
max_step	Maximum number of iterations. Default is 100.
thresh	Convergence threshold in the outer loop. The algorithm iterates until the relative change in any coefficient is less than <code>eps</code> . Default is $1e-6$ .

**Details**

This function gives a  $n_{d0} \times N/n_{d0}$  matrix, which is the mode-`d0` unfolding, and approximates `Y`.

**Value**

Tnew	Approximation of <code>Y</code> .
Tn	A list of estimated matrices of $U_1, U_2, \dots, U_d$ and core tensor $S$ , <code>Tn=list(<math>U_1 = U_1, \dots, U_d = U_d, S = S</math>)</code> .
ranks	The ranks of estimated tensor <code>Tnew</code> . It is a vector with the same length as <code>dims</code> if Tucker decomposition is used, or an integer if CP decomposition is used.

**See Also**

HOsvd

**Examples**

```

dims <- c(8,8,10,10,6)
N <- length(dims)
ranks <- rep(2,N)
S0 = matrix(runif(prod(ranks),3,7),ranks[N])
T1 <- matrix(rnorm(dims[1]*ranks[1]),nrow = dims[1])
tmp <- qr.Q(qr(T1))
for(k in 2:(N-1)){
  T1 <- matrix(rnorm(dims[k]*ranks[k]),nrow = dims[k])

```

```

    tmp <- kronecker(qr.Q(qr(T1)),tmp)
  }
  T1 <- matrix(rnorm(dims[N]*ranks[N]),nrow = dims[N])
  U = qr.Q(qr(T1))
  Y <- U%*%S0%*%t(tmp)

  fit_dr <- HOSvd_dr(Y,N,dims,isCP=TRUE)
  Tnew <- fit_dr$Tnew
  ranks1 <- fit_dr$ranks
  lambda <- fit_dr$Tn[[N+1]]
  U1 <- fit_dr$Tn[[1]]
  TNew1 <- TransUnfoldingsT(Tnew,N,1,dims)

```

---

TransUnfoldingsT	<i>Transfer a tensor's modal unfoldings to another.</i>
------------------	---

---

### Description

Transfer a tensor's modal unfoldings to another.

### Usage

```
TransUnfoldingsT(S, d1=NULL, d2=0 , dims=NULL)
```

### Arguments

S	An array with dimension dims, or a mode-d1-unfolding of a tensor with size $n_1 \times \dots \times n_d$ .
d1	An integer, the mode of unfolding $S_{(d_1)}$ . d1 can be NULL (the default) if S is an array with dimension dims.
d2	An integer, the mode of output unfolding $S_{(d_2)}$ . It transfers S to an array with dimension dims if d2=0. The default is 0.
dims	The size of tensor $S$ , which is a vector $(n_1, \dots, n_d)$ . dims can be NULL (the default) if S is an array with dimension dims.

### Details

This function transfers an input mode-d1-unfolding  $S_{(d_1)}$  to mode-d2-unfolding  $S_{(d_2)}$

### Value

Td2                      the output mode-d2-unfolding,  $S_{(d_2)}$ .

### Examples

```

T1 <- matrix(1:24,nrow = 4) # A tensor unfolding with size 4*6
T2 <- TransUnfoldingsT(T1,1,2,c(4,3,2))

T0 <- TransUnfoldingsT(T2,2,dims=c(4,3,2))

```

# Index

\*Topic **CP decomposition; HOSVD;  
Tucker decomposition.**

H0svd, [2](#)

\*Topic **CP decomposition; HOSVD;  
Tucker decomposition**

H0svd\_dr, [3](#)

tensorApp-package, [1](#)

TransUnfoldingsT, [5](#)

H0svd, [2](#)

H0svd-function (H0svd), [2](#)

H0svd\_dr, [3](#)

H0svd\_dr-function (H0svd\_dr), [3](#)

tensorApp (tensorApp-package), [1](#)

tensorApp-package, [1](#)

TransUnfoldingsT, [5](#)

TransUnfoldingsT-function  
(TransUnfoldingsT), [5](#)