

Package ‘tensorMQR1’

January 5, 2020

Type Package

Title tensorMQR1

Version 0.1.0

Date 2019-09-01

Author Xu Liu [aut,cre],
Jian Huang [aut],
Heng Lian [aut],
Xinyuan Song [aut],
Yuling Jiao [aut]

Maintainer Xu Liu <liu.xu@sufe.edu.cn>

Description Symmetric tensor estimation for multiresponse quadratic regression. The number of predictors can be diverged as sample size increases, in which the penalty LASSO, MCP or SCAD can be used.

License GPL (>= 2)

Imports Rcpp (>= 0.11.15), RcppEigen (>= 0.3.2.3.0)

LinkingTo Rcpp, RcppEigen

RoxygenNote 6.0.1

NeedsCompilation yes

Repository github

URL <https://github.com/xliusufe/tensorMQR1>

Encoding UTF-8

R topics documented:

tensorMQR1-package	2
generateData	2
mqr	3
mqr_dr	5
mqr_sparse	6
mqr_sparse_dr	8
TransferModalUnfoldings	11
TransferP2T	12
TransferT2P	13
Index	14

tensorMQR1-package	<i>Symmetric Tensor Estimation for Quadratic Regression.</i>
--------------------	--

Description

For a high-dimensional multiresponse quadratic regression (MQR) with or without aparsity assumptions, treating the coefficients as a third-order tensor and borrowing Tucker decomposition to reduce the number of parameters. The multivariate sparse group lasso (mcp or scad) and the steepest gradient descent algorithm are used to estimate tensor for sparsity situation.

Details

This section should provide a more detailed overview of how to use the package, including the most important functions.

Author(s)

Xu Liu

Maintainer: Xu Liu <liu.xu@sufe.edu.cn>

References

Symmetric Tensor Estimation for Quadratic Regression.

generateData	<i>Generate data from MQR model.</i>
--------------	--------------------------------------

Description

Generate data for a high-dimensional multiresponse quadratic regression, with or without aparsity assumptions.

Usage

```
generateData(n, q, s, p, D3, SigmaX=diag(p-1), sigma2=0.2, seed_id, t=0.0, rho=0.0)
```

Arguments

n	Sample size.
q	The number of responses, $q \geq 1$.
s	The true covariates associating to response, $s \geq 1$.
p	The number of covariates, $p \geq 1$.
D3	The mode of unfolding $D_{(3)}$.
SigmaX	Covariance of X . Default is identity matrix.
sigma2	err variance. Default is 0.1.
seed_id	Seed of generator.
rho	The correlation of ϵ_j and ϵ_k , where $j, k \in \{1, \dots, q\}$.

Details

This function gives $qp(p+1)/2$ coefficients' estimators of MQR. The core tensor is a $r_1 \times r_2 \times r_3$ -tensor. We choose r_1, r_2 and r_3 by BIC or CV.

Value

Y	Response, a $n \times q$ -matrix.
X	Design matrix, a $n \times p$ -matrix.

References

Symmetric Tensor Estimation for Quadratic Regression.

See Also

mam_sparse

Examples

```
# Example 1

D3 <- matrix(runif(72, 0.7, 1), 2, 36)
mydata <- generateData(200, 2, 6, 6, D3)

Y <- mydata$Y
X <- mydata$X

# Example 2
n <- 500
p <- 10
q <- 10
s <- 7
s0 <- s
r10=r20=r30=2
S3 <- matrix(runif(r10*r20*r30,3,7),nrow = r30)
T1 <- matrix(rnorm(s0*r10),nrow = s0)
U1 <- qr.Q(qr(T1))
T1 <- matrix(rnorm(q*r30),nrow = q)
U3 <- qr.Q(qr(T1))
D3 <- U3%*%S3%*%t(kronecker(U1,U1))
mydata <- generateData(n,q,s0,p,D3)
```

mqr

Fit MQR without sparsity assumption and with fixed ranks.

Description

Fit a low-dimensional multiresponse quadratic regression without aparsity assumptions and with given r_1, r_2, r_3 . The steepest gradient descent algorithm is used to estimate tensor.

Usage

```
mqr(Y, X, r1 = NULL, r3 = NULL, SUV = NULL, isSym = TRUE, eps = 1e-6, max_step = 20)
```

Arguments

<code>Y</code>	A $n \times q$ numeric matrix of responses.
<code>X</code>	A $n \times p$ numeric design matrix for the model.
<code>r1</code>	The first dimension of single value matrix of the tensor. Default is 2.
<code>r3</code>	The third dimension of single value matrix of the tensor. Default is 2.
<code>SUV</code>	A user-specified list of initial coefficient matrix of S , U , V . By default, initial matrices are provided randomly.
<code>isSym</code>	A logical value indicating whether restrict tensor to be symmetric. If <code>isSym</code> is TRUE (the default), the core tensor is symmetric, and both U and V belong to Stiefel manifold. If <code>isSym</code> is FALSE, we decompose tensor to S , A , B , C , where we treat the tensor as an asymmetric tensor.
<code>eps</code>	Convergence threshold. The algorithm iterates until the loss function change in any coefficient is less than <code>eps</code> . Default is $1e-6$.
<code>max_step</code>	Maximum number of iterations. Default is 20.
<code>maxstep1</code>	The maximum iterates number of the steepest gradient descent method. Default is 20.

Details

This function gives $qp(p+1)/2$ coefficients' estimators of MQR. The core tensor is a $r_1 \times r_2 \times r_3$ -tensor. We fixed r_1 , r_2 and r_3 in the function `mqr`, but one can choose r_1 , r_2 and r_3 by BIC or CV. See details in function `mqr_bic` or `mqr_cv`.

Value

<code>Dnew</code>	Estimator of $D_{(3)}$.
<code>rss</code>	Residual sum of squares (RSS).
<code>Y</code>	Response Y .
<code>X</code>	Design matrix X .

References

Symmetric Tensor Estimation for Quadratic Regression.

See Also

`mqr_sparse`, `mqr_bic`, `mqr_cv`

Examples

```
D3 <- matrix(runif(72, 0.7, 1), 2, 36) # tensor with size 6*6*2
mydata <- generateData(200, 2, 6, 6, D3)

fit <- mqr(mydata$Y, mydata$X, r1=4, r3= 2)
D3hat <- fit$Dnew
```

mqr_dr	<i>Fit MQR without sparsity assumption, and with ranks selected by BIC or CV.</i>
--------	---

Description

Fit a low-dimensional multiresponse quadratic regression without sparsity assumptions and with ranks r_1, r_3 selected by BIC or CV.

Usage

```
mqr_dr(Y, X, r1_index = NULL, r3_index = NULL, method = "BIC",
       ncv = 10, SUV = NULL, isSym = TRUE, eps = 1e-6, max_step = 20)
```

Arguments

Y	A $n \times q$ numeric matrix of responses.
X	A $n \times p$ numeric design matrix for the model.
r1_index	A user-specified sequence of r_1 values, where r_1 is the first dimension of single value matrix of the tensor. Default is $r1_index = 1, \dots, \min(\log(n), p)$.
r3_index	A user-specified sequence of r_3 values, where r_3 is the third dimension of single value matrix of the tensor. Default is $r3_index = 1, \dots, \min(\log(n), q)$.
method	The method to be applied to select parameters. Either BIC (the default), AIC, EBIC, CV, or GCV.
ncv	The number of cross-validation folds. Default is 10. If method is not "CV", ncv is useless.
SUV	A user-specified list of initial coefficient matrix of S, U, V , which is a list with values S, U, V . By default, initial matrices are provided randomly.
isSym	A logical value indicating whether restrict tensor to be symmetric. If isSym is TRUE (the default), the core tensor is symmetric, and both U and V belong to Stiefel manifold. If isSym is FALSE, we decompose tensor to S, A, B, C , where we treat the tensor as an asymmetric tensor.
eps	Convergence threshold. The algorithm iterates until the relative change in any coefficient is less than eps. Default is $1e-6$.
max_step	Maximum number of iterations. Default is 20.
maxstep1	The maximum iterates number of the steepest gradient descent method. Default is 20.

Details

This function gives $qp(p+1)/2$ coefficients' estimators of MQR. The core tensor is a $r_1 \times r_2 \times r_3$ -tensor. We choose r_1, r_2 and r_3 by BIC or CV.

Value

Dnew	Estimator of $D_{(3)}$.
rss	Residual sum of squares (RSS).
rk_opt	The optimal parametres that slected by BIC or CV. It is a vector with length 4, which are selected r_1 and r_3 .
selected	Which λ is selection.
Y	Response Y .
X	Design matrix X .

References

Symmetric Tensor Estimation for Quadratic Regression.

See Also

mqr, mqr_sparse_dr

Examples

```
D3 <- matrix(runif(72, 0.7, 1), 2, 36) # tensor with size 6*6*2
mydata <- generateData(200, 2, 6, 6, D3)

fit <- mqr_dr(mydata$Y, mydata$X)
D3hat <- fit$Dnew
opt <- fit$rk_opt
```

mqr_sparse

Fit MQR with sparsity assumption and fixed ranks.

Description

Fit a high-dimensional multiresponse quadratic regression with or without aparsity assumptions, and given ranks given ranks r_1, r_2, r_3 . The multivariate sparse group lasso (mcp or scad) and the steepest gradient descent algorithm are used to estimate tensor for sparsity situation.

Usage

```
mqr_sparse(Y, X, r1 = NULL, r3 = NULL, method = "BIC", ncv = 10, isPenU = 0,
            isPenColumn = 1, penalty = "LASSO", lambda = NULL, SUV = NULL,
            nlam = 50, lam_min = 1e-4, ftol = 1e-6, maxstep = 20, maxstep1 = 20,
            eps = 1e-4, thresh=1e-4, gamma_pen = 2, dfmax = NULL, alpha = 1)
```

Arguments

Y	A $n \times q$ numeric matrix of responses.
X	A $n \times q$ numeric design matrix for the model.
r1	The first dimension of single value matrix of the tensor. Default is 2.
r3	The third dimension of single value matrix of the tensor. Default is 2.

method	The method to be applied to select parameters. Either BIC (the default), AIC, EBIC, CV, or GCV.
ncv	The number of cross-validation folds. Default is 10. If method is not CV, ncv is useless.
isPenU	A logical value indicating whether the rows of U is penalized. Default is FALSE. If isPenU is FALSE, the coefficients associating with X_j is penalized for each $j \in \{1, \dots, p\}$.
isPenColumn	A logical value indicating whether the coefficients associating with X_j that affects whole response y is penalized. Default is TRUE. If isPenU is TRUE, the coefficients associating with X_j that affects whole response y is penalized for each $j \in \{1, \dots, p\}$. If isPenU is FALSE, the coefficients associating with X_j that affects single response y_l is penalized for each $j \in \{1, \dots, p\}$, where $l \in \{1, \dots, q\}$.
penalty	The penalty to be applied to the model. Either "LASSO" (the default), "SCAD", or "MCP".
lambda	A user-specified sequence of lambda values. By default, a sequence of values of length nlam is computed, equally spaced on the log scale.
SUV	A user-specified list of initial coefficient matrix of S , U , V . By default, initial matrices are provided randomly.
nlam	The number of lambda values. Default is 20.
lam_min	The smallest value for lambda, as a fraction of lambda.max. Default is 1e-3.
ftol	Convergence threshold for the Curvilinear search. The algorithm iterates until the relative change in any coefficient is less than eps1. Default is 1e-6.
maxstep	Maximum number of iterations. Default is 20.
maxstep1	The maximum iterates number of the steepest gradient descent method. Default is 20.
thresh	The threshold to numerically determine which coefficients are zeros. Since the steepest projected gradient descent method with the approximated penalty can not shrink the estimated row of true zero row of U to exactly zero, we need to determine a numerical threshold. Default is 1e-6.
eps	Convergence threshold for the outer loop. The algorithm iterates until the relative change in any coefficient is less than eps1. Default is 1e-4.
gamma_pen	The tuning parameter of the MCP/SCAD penalty (see details).
dfmax	Upper bound for the number of nonzero coefficients. Default is no upper bound. However, for large data sets, computational burden may be heavy for models with a large number of nonzero coefficients.
alpha	Tuning parameter for the Mnet estimator which controls the relative contributions from the LASSO, MCP/SCAD penalty and the ridge, or L2 penalty. alpha=1 is equivalent to LASSO, MCP/SCAD penalty, while alpha=0 would be equivalent to ridge regression. However, alpha=0 is not supported; alpha may be arbitrarily small, but not exactly 0.

Details

This function gives $qp(p+1)/2$ coefficients' estimators of MQR. The core tensor is a $r_1 \times r_1 \times r_3$ -tensor. r_1 and r_3 are fixed.

Value

betapath	Solution path of β .
rss	Residual sum of squares (RSS).
df	Degrees of freedom.
lambda	The sequence of regularization parameter values in the path.
lambda_opt	The value of lambda with the minimum BIC value.
selectedID	The index of lambda corresponding to lambda_opt.
activeF	The active set of U . If isPenColumn is TRUE, activeF is same as activeX
activeX	The active set of coefficients associating with X . If isPenColumn is TRUE, activeX is same as activeF
Snew	Estimator of S_3 .
Unew	Estimator of U .
Vnew	Estimator of V .
Y	Response Y .
X	Design matrix X .

References

Symmetric Tensor Estimation for Quadratic Regression.

See Also

mqr, mqr_sparse_dr

Examples

```
D3 <- matrix(runif(72, 0.7, 1), 2, 36) # tensor with size 6*6*2
mydata <- generateData(200, 2, 6, 6, D3)

fit <- mqr_sparse(mydata$Y, mydata$X)
activeX <- fit$activeX
```

mqr_sparse_dr

Fit MQR with sparsity assumption and ranks selected by BIC or CV.

Description

Fit a high-dimensional multiresponse quadratic regression with or with sparsity assumptions and ranks selected by BIC or CV. The multivariate sparse group lasso (mcp or scad) and the steepest gradient descent algorithm are used to estimate tensor for sparsity situation. The tuning parameter is selected by BIC or CV, which matches the method of rank selection.

Usage

```
mqr_sparse_dr(Y, X, r1_index = NULL, r3_index = NULL, method = "BIC", ncv = 10,
  penalty = "LASSO", isPenU = 0, isPenColumn = 1, lambda = NULL, SUV = NULL,
  nlam = 50, lam_min = 0.001, ftol = 1e-6, maxstep = 20, maxstep1 = 20,
  eps = 1e-4, thresh = 1e-4, gamma_pen = 2, dfmax = NULL, alpha = 1)
```


Arguments

Y	A $n \times q$ numeric matrix of responses.
X	A $n \times q$ numeric design matrix for the model.
r1_index	A user-specified sequence of r_1 values, where r_1 is the first dimension of single value matrix of the tensor. Default is <code>r1_index= 1, ..., min($\lceil \log(n) \rceil, p$)</code> .
r3_index	A user-specified sequence of r_3 values, where r_3 is the third dimension of single value matrix of the tensor. Default is <code>r3_index= 1, ..., min($\lceil \log(n) \rceil, q$)</code> .
method	The method to be applied to select parameters. Either BIC (the default), AIC, EBIC, CV, or GCV.
ncv	The number of cross-validation folds. Default is 10. If method is not CV, ncv is useless.
penalty	The penalty to be applied to the model. Either "LASSO" (the default), "SCAD", or "MCP".
isPenU	A logical value indicating whether the rows of U is penalized. Default is FALSE. If isPenU is FALSE, the coefficients associating with X_j is penalized for each $j \in \{1, \dots, p\}$.
isPenColumn	A logical value indicating whether the coefficients associating with X_j that affects whole response y is penalized. Default is TRUE. If isPenU is TRUE, the coefficients associating with X_j that affects whole response y is penalized for each $j \in \{1, \dots, p\}$. If isPenU is FALSE, the coefficients associating with X_j that affects single response y_l is penalized for each $j \in \{1, \dots, p\}$, where $l \in \{1, \dots, q\}$.
lambda	A user-specified sequence of lambda values. By default, a sequence of values of length <code>nlam</code> is computed, equally spaced on the log scale.
SUV	A user-specified list of initial coefficient matrix of S , U , V . By default, initial matrices are provided randomly.
nlam	The number of lambda values. Default is 50.
lam_min	The smallest value for lambda, as a fraction of <code>lambda.max</code> . Default is 1e-2.
ftol	Convergence threshold for the Curvilinear search. The algorithm iterates until the relative change in any coefficient is less than <code>eps1</code> . Default is 1e-6.
maxstep	Maximum number of iterations. Default is 20.
maxstep1	The maximum iterates number of the steepest gradient descent method. Default is 20.
eps	Convergence threshold for the outer loop. The algorithm iterates until the relative change in any coefficient is less than <code>eps1</code> . Default is 1e-4.
thresh	The threshold to numerically determine which coefficients are zeros. Since the steepest projected gradient descent method with the approximated penalty can not shrink the estimated row of true zero row of U to exactly zero, we need to determine a numerical threshold. Default is 1e-6.
gamma_pen	The tuning parameter of the MCP/SCAD penalty (see details).
dfmax	Upper bound for the number of nonzero coefficients. Default is no upper bound. However, for large data sets, computational burden may be heavy for models with a large number of nonzero coefficients.
alpha	Tuning parameter for the Mnet estimator which controls the relative contributions from the LASSO, MCP/SCAD penalty and the ridge, or L2 penalty. <code>alpha=1</code> is equivalent to LASSO, MCP/SCAD penalty, while <code>alpha=0</code> would be equivalent to ridge regression. However, <code>alpha=0</code> is not supported; alpha may be arbitrarily small, but not exactly 0.

Details

This function gives $qp(p+1)/2$ coefficients' estimators of MAM. The core tensor is a $r_1 \times r_1 \times r_3$ -tensor. We choose r_1 and r_3 by BIC or CV.

Value

rss	Residual sum of squares (RSS).
df	Degrees of freedom.
activeF	The active set of U . If isPenColumn is TRUE, activeF is same as activeX
activeX	The active set of coefficients associating with X . If isPenColumn is TRUE, activeX is same as activeF
Snew	Estimator of S_3 .
Unew	Estimator of U .
Vnew	Estimator of V .
lambda	The sequence of regularization parameter values in the path.
selectedID	The index of lambda corresponding to lambda_opt.
lambda_opt	The value of lambda with the minimum BIC or CV value.
RSS	The values of BIC or CV, which is a vector.
rk_opt	The optimal parametres that slected by BIC or CV. It is a vector with length 2, which are selected r_1 and r_3 .
Y	Response Y .
X	Design matrix X .

References

Symmetric Tensor Estimation for Quadratic Regression.

See Also

mqr_dr, mqr_sparse

Examples

```
#Example 1

D3 <- matrix(runif(72, 0.7, 1), 2, 36) # tensor with size 6*6*2
mydata <- generateData(200, 2, 6, 6, D3)

fit <- mqr_sparse_dr(mydata$Y, mydata$X)
S3hat <- fit$Snew
opt <- fit$rk_opt
```

TransferModalUnfoldings

Transfer a tensor's modal unfoldings to another.

Description

Transfer a tensor's modal unfoldings to another.

Usage

```
TransferModalUnfoldings(S, d1, d2, r1, r2, r3)
```

Arguments

S	A mode-d1-unfolding of a tensor with size $r_1 \times r_2 \times r_3$, input unfolding
d1	An integer, the mode of unfolding $S_{(d_1)}$
d2	An integer, the mode of output unfolding $S_{(d_2)}$
r1	The first dimension of tensor
r2	The second dimension of tensor
r3	The third dimension of tensor

Details

This function transfers an input mode-d1-unfolding $S_{(d_1)}$ to mode-d2-unfolding $S_{(d_2)}$

Value

D	The output mode-d2-unfolding, $S_{(d_2)}$
---	---

References

Symmetric Tensor Estimation for Quadratic Regression.

Examples

```
D1 <- matrix(1:24,nrow = 4) # A tensor unfolding with size 4*6
D2 <- TransferModalUnfoldings(D1,1,2,4,3,2)
```

TransferP2T	<i>Transfer coefficients of the multivariate quadratic model to a tensor's modal unfoldings.</i>
-------------	--

Description

Transfer coefficients of the multivariate quadratic model to a tensor's modal unfoldings.

Usage

```
TransferP2T(coef, d , p, q)
```

Arguments

coef	The coefficients of the multivariate quadratic model, which is a vector with length $qp(p+1)/2$
d	An integer, the mode of unfolding $S_{(d)}$
p	The first dimension of tensor
q	The third dimension of tensor

Details

This function transfers coefficients of the multivariate quadratic model coef to a mode- d -unfolding $D_{(d)}$ of a tensor.

Value

Dd A mode- d -unfolding of a tensor with size $p \times pq$, input unfolding.

References

Symmetric Tensor Estimation for Quadratic Regression.

Examples

```
p <- 4
q <- 3
D1 <- NULL
for(j in 1:q){
  D0 <- matrix(runif(p^2,1,3),p)
  D1 <- cbind(D1,(D0+t(D0))/2)
}
coef <- TransferP2T(D1, 1 , p, q)
D1 <- TransferP2T(coef, 1 , p, q)
D2 <- TransferP2T(coef, 2 , p, q)
```

TransferT2P	<i>Transfer a tensor's modal unfoldings to coefficients of the multivariate quadratic model.</i>
-------------	--

Description

Transfer a tensor's modal unfoldings to coefficients of the multivariate quadratic model.

Usage

```
TransferT2P(S, d , p, q)
```

Arguments

S	A mode- d -unfolding of a tensor with size $p \times pq$, input unfolding
d	An integer, the mode of unfolding $S_{(d)}$
p	The first dimension of tensor
q	The third dimension of tensor

Details

This function transfers an input mode- d -unfolding $S_{(d)}$ to coefficients of the multivariate quadratic model `coef`.

Value

<code>coef</code>	The coefficients of the multivariate quadratic model. <code>coef</code> is a vector with length $qp(p+1)/2$.
-------------------	---

References

Symmetric Tensor Estimation for Quadratic Regression.

Examples

```
p <- 4
q <- 3
D1 <- NULL
for(j in 1:q){
  D0 <- matrix(runif(p^2,1,3),p)
  D1 <- cbind(D1,(D0+t(D0))/2)
}
coef <- TransferT2P(D1, 1 , p, q)
```

Index

*Topic **High-dimensional; Gradient descent; Stiefel manifold; Tensor estimation; Tucker decomposition.**

- generateData, [2](#)
- mqr, [3](#)
- mqr_dr, [5](#)
- mqr_sparse, [6](#)
- mqr_sparse_dr, [8](#)
- tensorMQR1-package, [2](#)
- TransferModalUnfoldings, [11](#)
- TransferP2T, [12](#)
- TransferT2P, [13](#)

generateData, [2](#)

- mqr, [3](#)
- mqr-function (mqr), [3](#)
- mqr_dr, [5](#)
- mqr_dr-function (mqr_dr), [5](#)
- mqr_sparse, [6](#)
- mqr_sparse-function (mqr_sparse), [6](#)
- mqr_sparse_dr, [8](#)
- mqr_sparse_dr-function (mqr_sparse_dr),
[8](#)

- tensorMQR1 (tensorMQR1-package), [2](#)
- tensorMQR1-package, [2](#)
- TransferModalUnfoldings, [11](#)
- TransferModalUnfoldings-function
(TransferModalUnfoldings), [11](#)
- TransferP2T, [12](#)
- TransferP2T-function (TransferP2T), [12](#)
- TransferT2P, [13](#)
- TransferT2P-function (TransferT2P), [13](#)