CH10 Control Hardware Driver

Application and Hardware



User Space and Kernel Space



SysFS

- Allows kernel code to export information to user processes
- SysFS is an in-memory file system
- It provides two components
  - A kernel programming interface for exporting these items via sysfs
  - User interface to view and manipulate these items that maps back to the kernel objects which they represent

LED and SysFS



Sys File System

# tree -L 1 /sys/



```
/sys/
├── block
├── bus
├── class
├── dev
├── devices
├── firmware
├── fs
├── hypervisor
├── kernel
├── module
└── power
```

# tree -L 1 /sys/class/i2c-dev/i2c-0/



```
/sys/class/i2c-dev/i2c-0/
├── dev
├── device -> ../../../i2c-0
├── name
├── power
├── subsystem -> ../../../../../../class/i2c-dev
└── uevent
```

# tree -L 1 /sys/class/i2c-dev



```
/sys/class/i2c-dev/
├── i2c-0 -> ../../devices/pci0000:00/0000:00:02.0/i2c-0/i2c-dev/i2c-0
├── i2c-1 -> ../../devices/pci0000:00/0000:00:02.0/i2c-1/i2c-dev/i2c-1
├── i2c-2 -> ../../devices/pci0000:00/0000:00:02.0/i2c-2/i2c-dev/i2c-2
├── i2c-3 -> ../../devices/pci0000:00/0000:00:02.0/i2c-3/i2c-dev/i2c-3
├── i2c-4 -> ../../devices/pci0000:00/0000:00:02.0/i2c-4/i2c-dev/i2c-4
├── i2c-5 -> ../../devices/pci0000:00/0000:00:02.0/i2c-5/i2c-dev/i2c-5
├── i2c-6 -> ../../devices/pci0000:00/0000:00:02.0/drm/card0/card0-DP-1/i2c-6/i2c-dev/i2c-6
├── i2c-7 -> ../../devices/pci0000:00/0000:00:02.0/drm/card0/card0-DP-2/i2c-7/i2c-dev/i2c-7
└── i2c-8 -> ../../devices/pci0000:00/0000:00:02.0/drm/card0/card0-DP-3/i2c-8/i2c-dev/i2c-8
```

LED Drivers

LED Schematic



GPIO3_D4/I2S0_SDI1SDO3_d → LED1

GPIO3_D5/I2S0_SDI2SDO2_d → LED2

LED Subsystem

- Control LED convenient with SysFS
  - For example
    - echo 1 > /sys/class/leds/user-led2/shot
- Switch different LED trigger type in SysFS
  - For example
    - echo "gpio" > /sys/class/leds/user-led2/trigger
    - echo "1" > /sys/class/leds/user-led2/brightness
      - echo "0" > /sys/class/leds/user-led2/brightness

LED SysFS



```
root@rockpi4b:/sys/class/leds/user-led2# ls -l

brightness
device -> ../../../gpio-leds
max_brightness
power
subsystem -> ../../../../../class/leds
trigger
uevent

root@rockpi4b:/sys/class/leds/user-led2# cat trigger
none rc-feedback kbd-scrolllock kbd-numlock kbd-capslock
kbd-kanalock kbd-shiftlock kbd-altgrlock kbd-ctrllock kbd-altlock
kbd-shiftllock kbd-shiftrlock kbd-ctrlllock kbd-ctrlrlock m
timer oneshot heartbeat backlight [gpio] cpu0 cpu1 cpu2 cpu


root@rockpi4b:/sys/class/leds/user-led2# echo heartbeat > trigger

root@rockpi4b:/sys/class/leds/user-led2# cat trigger
none rc-feedback kbd-scrolllock kbd-numlock kbd-capslock
kbd-kanalock kbd-shiftlock kbd-altgrlock kbd-ctrllock kbd-altlock
kbd-shiftllock kbd-shiftrlock kbd-ctrlllock kbd-ctrlrlock mmc0 mmc1
timer oneshot [heartbeat] backlight gpio cpu0 cpu1 cpu2 cpu3 cpu4 cpu5
```

Check trigger type

Switch trigger type

GPIO Control

Driver LED in User Space

- Paths in Sysfs
- /sys/class/gpio:
  - Control interfaces used to get userspace control over GPIOs;
  - GPIOs themselves
  - GPIO controllers("gpio_chip" instances)
- /sys/class/gpio/
  - "export" : ask the kernel to export GPIO to userspace by writing
    - "echo 19 > export"
    - create a "gpio19" node in /sys/class/gpio
  - "unexport" : Reverses the effect of exporting to userspace
    - "echo 19 > unexport"
    - remove "gpio19" node from /sys/class/gpio

Cadtc Ext Board LED



RockPi4B HEAD



Rock Pi 4 A/B/C general purpose input-output (GPIO) connector

ROCK Pi 4 has a 40-pin expansion header. Each pin is distinguished by color.

GPIO number	Function2	Function1	GPIO	Pin#	Pin#	GPIO	Function1	Function2	GPIO number
		+3.3V		1	2		+5.0V		
71		I2C7_SDA	GPIO2_A7	3	4		+5.0V		
72		I2C7_SCL	GPIO2_B0	5	6		GND		
75		SPI2_CLK	GPIO2_B3	7	8	GPIO4_C4	UART2_TXD		148
		GND		9	10	GPIO4_C3	UART2_RXD		147
146		PWM0	GPIO4_C2	11	12	GPIO4_A3	I2S1_SCLK		131
150		PWM1	GPIO4_C6	13	14		GND		
149		SPDIF_TX	GPIO4_C5	15	16	GPIO4_D2			154
		+3.3V		17	18	GPIO4_D4			156
40	UART4_TXD	SPI1_TXD	GPIO1_B0	19	20		GND		
39	UART4_RXD	SPI1_RXD	GPIO1_A7	21	22	GPIO4_D5			157
41		SPI1_CLK	GPIO1_B1	23	24	GPIO1_B2	SPI1_CSn		42
		GND		25	26		ADC_IN0		
64		I2C2_SDA	GPIO2_A0	27	28	GPIO2_A1	I2C2_CLK		65
74	I2C6_SCL	SPI2_TXD	GPIO2_B2	29	30		GND		
73	I2C6_SDA	SPI2_RXD	GPIO2_B1	31	32	GPIO3_C0	SPDIF_TX	UART3_CTSn	112
76		SPI2_CSn	GPIO2_B4	33	34		GND		
133		I2S1_LRCK_TX	GPIO4_A5	35	36	GPIO4_A4	I2S1_LRCK_RX		132
158			GPIO4_D6	37	38	GPIO4_A6	I2S1_SDI		134
		GND		39	40	GPIO4_A7	I2S1_SDO		135

PWM Sub System

PWM

- PWM : Pulse Width Modulation



https://circuitdigest.com/tutorial/what-is-pwm-pulse-width-modulation

PWM



```
          _      _      _      _      _      _      _      _
         | |    | |    | |    | |    | |    | |    | |    | |
Clock    | |    | |    | |    | |    | |    | |    | |    | |
       __| |____| |____| |____| |____| |____| |____| |____| |____

                 _      __     ____          ____   _
PWM signal      | |    |  |   |    |        |    | | |
                | |    |  |   |    |        |    | | |
       _________| |____|  |___|    |________|    |_| |___________

Data       0     1       2      4      0      4     1      0
```

https://en.wikipedia.org/wiki/Pulse-width_modulation

PWM Parameter in Linux

- Period
  - The total period of the PWM signal
  - Value is in nanoseconds
  - sum of the active and inactive time of the PWM
- duty_cycle
  - The active time of the PWM signal
  - Value is in nanoseconds
  - must be less than the period.

PWM Parameter in Linux

- Polarity
  - → The polarity of the PWM signal
- Enable
  - → Enable PWM Signal

PWM Driver

- $(KERNEL_SRC)/Documentation/pwm.txt
- Platform Driver
  - drivers/pwm/
  - drivers/pwm/core.c
  - drivers/pwm/pwm-rockchip.c

PWM Subsystem



RockPi4B HEAD



Rock Pi 4 A/B/C general purpose input-output (GPIO) connector

ROCK Pi 4 has a 40-pin expansion header. Each pin is distinguished by color.

GPIO number	Function2	Function1	GPIO	Pin#	Pin#	GPIO	Function1	Function2	GPIO number
		+3.3V		1	2		+5.0V		
71		I2C7_SDA	GPIO2_A7	3	4		+5.0V		
72		I2C7_SCL	GPIO2_B0	5	6		GND		
75		SPI2_CLK	GPIO2_B3	7	8	GPIO4_C4	UART2_TXD		148
		GND		9	10	GPIO4_C3	UART2_RXD		147
146		PWM0	GPIO4_C2	11	12	GPIO4_A3	I2S1_SCLK		131
150		PWM1	GPIO4_C6	13	14		GND		
149		SPDIF_TX	GPIO4_C5	15	16	GPIO4_D2			154
		+3.3V		17	18	GPIO4_D4			156
40	UART4_TXD	SPI1_TXD	GPIO1_B0	19	20		GND		
39	UART4_RXD	SPI1_RXD	GPIO1_A7	21	22	GPIO4_D5			157
41		SPI1_CLK	GPIO1_B1	23	24	GPIO1_B2	SPI1_CSn		42
		GND		25	26		ADC_IN0		
64		I2C2_SDA	GPIO2_A0	27	28	GPIO2_A1	I2C2_CLK		65
74	I2C6_SCL	SPI2_TXD	GPIO2_B2	29	30		GND		
73	I2C6_SDA	SPI2_RXD	GPIO2_B1	31	32	GPIO3_C0	SPDIF_TX	UART3_CTSn	112
76		SPI2_CSn	GPIO2_B4	33	34		GND		
133		I2S1_LRCK_TX	GPIO4_A5	35	36	GPIO4_A4	I2S1_LRCK_RX		132
158			GPIO4_D6	37	38	GPIO4_A6	I2S1_SDI		134
		GND		39	40	GPIO4_A7	I2S1_SDO		135

PWM SYSFS

```
/sys/class/pwm/pwmchip0

device    export    npwm    power    subsystem  uevent    unexport
```

```
echo 0 > export
capture    enable    polarity    uevent    duty_cycle  period    power
```

```
echo “20000000” > period          //20ms, 50 Hz

echo "2000000" > duty_cycle       //2ms

echo 1 > enable                   //Enable
```

Hwmon Subsystem

Hwmon Subsystem



SHT21

- Simple interface
- Bus interface
  - I2C, GPIO, SPI
- Sensors
  - Temperature
  - Voltage
  - Humidity
  - Fan speed
  - PWM control

SHT21





Pin	Name	Comment
1	SDA	Serial Data, bidirectional
2	VSS	Ground
5	VDD	Supply Voltage
6	SCL	Serial Clock, bidirectional
3,4	NC	Not Connected



Command	Comment	Code
Trigger T measurement	hold master	1110’0011
Trigger RH measurement	hold master	1110’0101
Trigger T measurement	no hold master	1111’0011
Trigger RH measurement	no hold master	1111’0101
Write user register		1110’0110
Read user register		1110’0111
Soft reset		1111’1110

SHT21

Hold master communication sequence



	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
S	1	0	0	0	0	0	0	0	ACK	1	1	1	0	0	1	0	1	ACK
	I^2C address + write									Command (see Table 6)								

	19	20	21	22	23	24	25	26	27	
S	1	0	0	0	0	0	0	1	ACK	Measurement
	I^2C address + read									Hold during measurement

28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45
0	1	1	0	0	0	1	1	ACK	0	1	0	1	0	0	1	0	ACK
Data (MSB)									Data (LSB)						Stat.		

46	47	48	49	50	51	52	53	54	
0	1	1	0	0	1	0	0	NACK	P
Checksum									

No Hold master communication sequence



	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
S	1	0	0	0	0	0	0	0	ACK	1	1	1	1	0	1	0	1	ACK
	I^2C address + write									Command (see Table 6)								

		19	20	21	22	23	24	25	26	27
Measurement	S	1	0	0	0	0	0	0	1	NACK
measuring		I^2C address + read								

		19	20	21	22	23	24	25	26	27
Measurement	S	1	0	0	0	0	0	0	1	ACK
continue measuring		I^2C address + read								

28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45
0	1	1	0	0	0	1	1	ACK	0	1	0	1	0	0	1	0	ACK
Data (MSB)									Data (LSB)						Stat.		

46	47	48	49	50	51	52	53	54	
0	1	1	0	0	1	0	0	NACK	P
Checksum									

SHT21



I2C



I2C

SHT21

Hwmon Sysfs

```
# ls /sys/class/hwmon/hwmon0
device           name   subsystem    uevent
humidity1_input  power  temp1_input
```

temperature

```
# cat /sys/class/hwmon/hwmon0/temp1_input
32279
```

humidity

```
# cat /sys/class/hwmon/hwmon0/humidity1_input
34512
```