

BoilerBridge: Sprint 1 Retrospective Grading Rubric

Team 26 - BoilerBridge: Xavion Marable, Logan Wilkinson, Emilio Guzman,

Shashank Mukkera

1. What went well? (0.5 point)

- a. You may write this section in sentences and/or list successful user stories and tasks with detailed discussions.
- The backend API for the shared costs and cost splits turned out to be well designed. After fixing a couple of routing issues, all of the CRUD operations were implemented for `/api/groups/:groupId/shared-costs` and `/api/groups/:groupId/cost-splits`. All relevant fields were enforced to be present, all amounts were enforced to be positive, and group participants were correctly validated. For create, the creator of the group or the group admins could make changes. For edit/deletes, only the creator of the group or the group admins could make changes. The ledger functionality was updated to correctly update the group balances when a new shared cost was created. (**User Stories #9 and #10**)

2. What did not go well? (0.5 point)

- a. Include general retrospective review for this sprint.
- b. Ensure to list ALL unsuccessful user stories and tasks with detailed discussions. (They should be in line with the Sprint Planning Document for the next sprint.)
- Fixed issue where shared costs and cost splits endpoints were not routing correctly which

meant the application would fail. The group ID in the URL path is a custom UUID field (groupId) on the TravelGroup document, not the MongoDB _id. Initially all routes had been set up using TravelGroup.findById(groupId) which caused a CastError for every request until the root cause had been found and all routes updated to use TravelGroup.findOne({ groupId: groupId }). **(User stories #9 and #10)**

- When I first set up the test suite it was set up to test against the production database instead of the test database. In a couple of the test files I had not set process.env.MONGODB_URI and therefore it was not being defaulted to process.env.TEST_MONGODB_URI which meant that User.deleteMany({}) and TravelGroup.deleteMany({}) were running against the real database during test runs because dbConnect remembers the URI that it connects with when the module loads it. **(User Stories #9 and #10)**

3. How should you improve? (1.0 point)

- a. Mention at least two ways to improve your work in the next sprint and be as detailed as you can.
- We should establish a routing convention at the start of the next sprint. As a matter of principle, since the app uses custom UUID fields for groups, trips, etc and these are never equal to the MongoDB _id, all developers should know to use `findOne({ fieldName: param })` instead of `findById`. We should write a shared utility function to look up a trip and then reuse that function in the endpoints that hit this bug.
 - I think the pre-run safety check in jest.setup.js should also assert that MONGODB_URI is set to point to the test database. This would mean that no test file can accidentally wipe the production database even if they are trying to use the override incorrectly (and it would error before that incorrectly overridden code could even run)

4. Notes

- a. For section 1 and 2, only listing out some user stories and tasks without any discussion will not get you full credits.
- b. Please make sure to include your project name, team number and the names of all your team members.

Total: 2 points (2% of your project grade)