

# Graph algorithms library

PV264 project

Vojtěch Kaňa, Matej Hulín

The main goal of the proposed project is, as its name suggests, to create C++ library, which should provide various graph traversal and shortest-paths algorithms. For implementation, we have chosen following algorithm categories:

## Graph traversal

- Depth-first search (DFS) with function prototype:  

```
template<typename Graph>
std::enable_if_t<Graph::traversableTag>
void dfs(Graph& graph);
```
- Breadth-first search (BFS) with function prototype:  

```
template<typename Graph>
std::enable_if_t<Graph::traversableTag>
bfs(Graph& graph,
    const typename graph_traits<Graph>::node_handle &source);
```
- Iterative deepening depth-first search (IDDFS) with function prototype:  

```
template<typename Graph>
std::enable_if_t<Graph::traversableTag, bool>
iddfs(Graph& graph,
    const typename graph_traits<Graph>::node_handle &root_nh,
    const typename graph_traits<Graph>::node_handle &goal_nh,
    std::size_t max_depth);
```
- A\* with function prototype:  

```
template<typename Graph,
        typename Heuristic,
        typename PriorityQueue = BinHeap<typename Graph::node_handle,
        CustomComparator<Graph>>>
void AStar(Graph& graph,
    const typename graph_traits<Graph>::node_handle &source,
    const typename graph_traits<Graph>::node_handle &target,
    const Heuristic& heuristic);
```

A\* algorithm traverses `graph` from `source` using `heuristic` until it finds node `target`.

## Single source shortest-paths

- Dijkstra algorithm (using Heap and Fibonacci heap) with function prototype:

```
template<typename Graph,
        typename PriorityQueue = BinHeap<Graph>>
std::enable_if_t<Graph::weightedTag &&
                Graph::pathTag, bool>
dijkstra(Graph& graph,
         const typename graph_traits<Graph>::node_handle &source);
```
- Bellman-Ford algorithm with function prototypes:

```
template<typename Graph>
std::enable_if_t<Graph::directedTag &&
                Graph::weightedTag &&
                Graph::pathTag, bool>
bellmanFord(Graph& graph,
            const typename graph_traits<Graph>::node_handle &source);

template<typename Graph>
std::enable_if_t<Graph::directedTag &&
                Graph::weightedTag &&
                Graph::pathTag, bool>
bellmanFord(Graph& graph,
            const typename graph_traits<Graph>::node_handle &source);
```
- DAG shortest-paths (Topological sort and DFS) with function prototype:

```
template<typename Graph>
std::enable_if_t<Graph::directedTag &&
                Graph::weightedTag &&
                Graph::pathTag, bool>
dag(Graph& graph,
    const typename graph_traits<Graph>::node_handle &source);
```

## All-pairs shortest-paths

- Floyd-Warshall algorithm with function prototype:

```
template<typename Graph>
std::enable_if_t<Graph::directedTag &&
                Graph::weightedTag &&
                Graph::pathTag,
                Matrix<typename graph_traits<Graph>::distance_type>>
floydWarshall(const Graph& graph);
```
- Johnson's algorithm with function prototype:

```
template<typename Graph>
std::enable_if_t<Graph::directedTag &&
                Graph::weightedTag &&
                Graph::pathTag,
                Matrix<typename graph_traits<Graph>::distance_type>>
johnson(Graph& graph);
```