

TECHNICAL CHARACTERISTICS

MATERIAL
INSULATOR: PA 66
FLAMMABILITY RATING: UL94-V0
COLOR: WHITE
PITCH: 1.00 MM

ENVIRONMENTAL
OPERATING TEMPERATURE: -25 UP TO 85°C
COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL
INSULATOR RESISTANCE: >100 MΩ
DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC/MN

STANDARD
 CERTIFIED: E323964

PACKAGING
BAG

DIMENSION
A = NB. POLE - 1
B = NB. POLE + 3

RoHS Compliant

PROJECTION:



GENERAL TOLERANCE

.X = ± 0.2

.XX = ± 0.15



APPROVAL: BBu

UNIT: MM

SCALE:

SHEET: 1/3

DRAW: AS

DESCRIPTION: WR-WTB 1.00 MM FEMALE TERMINAL HOUSING

WERI PART NO: 665 0xx 113 322

SIZE

A4


1		2		3		4		5		A	
											B
										D	

Note:


1.Dimension:


Carton Size:40*28*28(cm)


Pin.	Pcs/Bag	Pcs/Carton	Pin.	Pcs/Bag	Pcs/Carton
2	1000	60000	9	1000	28000
3	1000	54000	10	1000	26000
4	1000	48000	11	1000	26000
5	1000	42000	12	1000	22000
6	1000	36000	13	1000	20000
7	1000	30000	14	1000	18000
8	1000	28000	15	1000	18000





PE BAG







Carton

RoHS Compliant				PROJECTION: 	GENERAL TOLERANCE .X = ± 0.2 .XX = ± 0.15		DESCRIPTION: WR-WTB 1.00 MM FEMALE TERMINAL HOUSING WERI PART NO: 665 0xx 113 322	SIZE A4
G								
F								
E								
D								
C				APPROVAL: BBu	UNIT: MM			
B					SCALE:			
A	23-AVR-15	NBR PIECES/BAG	QP		SHEET: 2/3			
REV	DATE	FILE	BY		DRAW: AS			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Wurth Elektronik:](#)

[665003113322](#)