

Disjoint Polymorphism

João Alpuim, Bruno C. d. S. Oliveira, and Zhiyuan Shi

The University of Hong Kong
{zyshi,bruno}@cs.hku.hk

Abstract. The combination of *intersection types*, a *merge operator* and *parametric polymorphism* enables important applications for programming. However such combination makes it hard to achieve the desirable property of a *coherent semantics*: all valid reductions for the same expression should have the same value. Recent work proposed *disjoint intersections types* as a means to ensure coherence in a simply typed setting. However, the addition of parametric polymorphism was not studied. This paper presents F_i : a calculus with *disjoint intersection types*, a variant of *parametric polymorphism* and a *merge operator*. F_i is both type-safe and coherent. The key difficulty in adding polymorphism is that, when a type variable occurs in an intersection type, it is not statically known whether the instantiated type will be disjoint to other components of the intersection. To address this problem we propose *disjoint polymorphism*: a constrained form of parametric polymorphism, which allows programmers to specify disjointness constraints for type variables. With disjoint polymorphism the calculus remains very flexible in terms of programs that can be written, while retaining coherence.

1 Introduction

Intersection types [19,40] are a popular language feature for modern languages, such as Microsoft’s TypeScript [4], Redhat’s Ceylon [1], Facebook’s Flow [3] and Scala [35]. In those languages a typical use of intersection types, which has been known for a long time [17], is to model the subtyping aspects of OO-style multiple inheritance. For example, the following Scala declaration:

```
class A extends B with C
```

says that the class `A` implements *both* `B` and `C`. The fact that `A` implements two interfaces/traits is captured by an intersection type between `B` and `C` (denoted in Scala by `B with C`). Unlike a language like Java, where `implements` (which plays a similar role to `with`) would be a mere keyword, in Scala intersection types are first class. For example, it is possible to define functions such as:

```
def narrow(x : B with C) : B = x
```

taking an argument with an intersection type `B with C`.

The existence of first-class intersections has lead to the discovery of other interesting applications of intersection types. For example, TypeScript’s documentation motivates intersection types¹ as follows:

¹ <https://www.typescriptlang.org/docs/handbook/advanced-types.html>

You will mostly see intersection types used for mixins and other concepts that don't fit in the classic object-oriented mold. (There are a lot of these in JavaScript!)

Two points are worth emphasizing. Firstly, intersection types are being used to model concepts that are not like the classical (class-based) object-oriented programming. Indeed, being a prototype-based language, JavaScript has a much more dynamic notion of object composition compared to class-based languages: objects are composed at run-time, and their types are not necessarily statically known. Secondly, the use of intersection types in TypeScript is inspired by common programming patterns in the (dynamically typed) JavaScript. This hints that intersection types are useful to capture certain programming patterns that are out-of-reach for more conventional type systems without intersection types.

Central to TypeScript's use of intersection types for modelling such a dynamic form of mixins is the function:

```
function extend<T, U>(first: T, second: U) : T & U {...}
```

The name *extend* is given as an analogy to the *extends* keyword commonly used in OO languages like Java. The function takes two objects (**first** and **second**) and produces an object with the intersection of the types of the original objects. The implementation of *extend* relies on low-level (and type-unsafe) features of JavaScript. When a method is invoked on the new object resulting from the application of **extend**, the new object tries to use the **first** object to answer the method call and, if the method invocation fails, it then uses the **second** object to answer the method call.

The *extend* function is essentially an encoding of the *merge operator*. The merge operator is used on some calculi [45,44,14,23,46] as an introduction form for intersection types. Similar encodings to those in TypeScript have been proposed for Scala to enable applications where the merge operator also plays a fundamental role [36,43]. Unfortunately, the merge operator is not directly supported by TypeScript, Scala, Ceylon or Flow. There are two possible reasons for such lack of support. One reason is simply that merge operator is not well-known: many calculi with intersection types in the literature do not have explicit introduction forms for intersection types. The other reason is that, while powerful, the merge operator is known to introduce *(in)coherence* problems [44,23]. If care is not taken, certain programs using the merge operator do not have a unique semantics, which significantly complicates reasoning about programs.

Solutions to the problem of coherence in the presence of a merge operator exist for simply typed calculi [45,44,14,46], but no prior work addresses polymorphism. Most recently Oliveira et al. [46] proposed using *disjoint intersection types* to guarantee coherence in a calculus with intersection types and a merge operator. The key idea is to allow only disjoint types in intersections. If two types are disjoint then there is no ambiguity in selecting a value of the appropriate type from an intersection, guaranteeing coherence.

Combining parametric polymorphism with disjoint intersection types, while retaining enough flexibility for practical applications, is non-trivial. The key issue

is that when a type variable occurs in an intersection type it is not statically known whether the instantiated type will be disjoint to other components of the intersection. A naive way to add polymorphism is to forbid type variables in intersections, since they may be instantiated with a type which is not disjoint to other types in an intersection. Unfortunately this is too conservative and prevents many useful programs, including the `extend` function, which uses an intersection of two type variables T and U .

This paper presents F_i : a core calculus with *disjoint intersection types*, a variant of *parametric polymorphism* and a *merge operator*. The key innovation in the calculus is *disjoint polymorphism*: a constrained form of parametric polymorphism, which allows programmers to specify disjointness constraints for type variables. With disjoint polymorphism the calculus remains very flexible in terms of programs that can be written with intersection types, while retaining coherence. In F_i the `extend` function is implemented as follows:

```
let extend T (U * T) (first : T, second : U) : T & U = first , , second
```

From the typing point of view, the difference between `extend` in TypeScript and F_i is that the type variable U now has a *disjointness constraint*. The notation $U * T$ means that the type variable U can be instantiated to any types which are disjoint to the type T . Unlike TypeScript, the definition of `extend` is trivial, type-safe and guarantees coherence by using the built-in merge operator $(, ,)$.

The applicability of F_i is illustrated with examples using `extend` ported from TypeScript, and various operations on polymorphic extensible records [32,28,30]. The operations on polymorphic extensible records show that F_i can encode various operations of row types [48]. However, in contrast to various existing proposals for row types and extensible records, F_i supports general intersections and not just record operations.

F_i and the proofs of coherence and type-safety are formalized in the Coq theorem prover [2]. The proofs are complete except for a minor (and trivially true) variable renaming lemma used to prove the soundness between two subtyping relations used in the formalization. The problem arises from the combination of the locally nameless representation of binding [7] and existential quantification, which prevents a Coq proof for that lemma.

In summary, the contributions of this paper are:

- **Disjoint Polymorphism:** A novel form of universal quantification where type variables can have disjointness constraints. Disjoint polymorphism enables a flexible combination of intersection types, the merge operator and parametric polymorphism.
- **Coq Formalization of F_i and Proof of Coherence:** An elaboration semantics of System F_i into System F is given. Type-soundness and coherence are proved in Coq².
- **Applications:** We show how F_i provides basic support for dynamic mixins and various operations on polymorphic extensible records.

² **Note to reviewers:** Due to the anonymous submission process, the Coq formalization is submitted as supplementary material.

2 Overview

This section introduces F_i and its support for intersection types, parametric polymorphism and the merge operator. It then discusses the issue of coherence and shows how the notion of disjoint intersection types and disjoint quantification achieves a coherent semantics. This section uses some syntactic sugar, as well as standard programming language features, to illustrate the various concepts in F_i . Although the minimal core language that we formalize in Section 4 does not present all such features, such syntactic sugar is trivial to add.

2.1 Intersection Types and the Merge Operator

Intersection types. The intersection of type A and B (denoted as $A \& B$ in F_i) contains exactly those values which can be used as both values of type A and of type B . For instance, consider the following program in F_i :

```
let x : Int & Bool = ... in -- definition omitted
let succ (y : Int) : Int = y+1 in
let not (y : Bool) : Bool = if y then False else True in (succ x, not x)
```

If a value x has type $\text{Int} \& \text{Bool}$ then x can be used anywhere where either a value of type Int or a value of type Bool is expected. This means that, in the program above the functions `succ` and `not` – simple functions on integers and booleans, respectively – both accept x as an argument.

Merge operator. The previous program deliberately omitted the introduction of values of an intersection type. There are many variants of intersection types in the literature. Our work follows a particular formulation, where intersection types are introduced by a *merge operator* [45,44,14,23,46]. As Dunfield [23] has argued a merge operator adds considerable expressiveness to a calculus. The merge operator allows two values to be merged in a single intersection type. For example, an implementation of x in F_i is $1, \text{True}$. Following Dunfield’s notation the merge of v_1 and v_2 is denoted as v_1, v_2 .

2.2 Coherence and Disjointness

Coherence is a desirable property for a semantics. A semantics is coherent if any *valid program* has exactly one meaning [44] (that is, the semantics is not ambiguous). Unfortunately the implicit nature of elimination for intersection types built with a merge operator can lead to incoherence. This is due to intersections with overlapping types, as in $\text{Int} \& \text{Int}$. The result of the program $((1, 2) : \text{Int})$ can be either 1 or 2, depending on the implementation of the language.

Disjoint intersection types One option to restore coherence is to reject programs which may have multiple meanings. The λ_i calculus [46] – a simply-typed calculus with intersection types and a merge operator – solves this problem by using the concept of disjoint intersections. The incoherence problem with the expression

1,,2 happens because there are two overlapping integers in the merge. Generally speaking, if both terms can be assigned some type C then both of them can be chosen as the meaning of the merge, which in its turn leads to multiple meanings of a term. Thus a natural option is to forbid such overlapping values of the same type in a merge. In λ_i intersections such as $\text{Int}\&\text{Int}$ are forbidden, since the types in the intersection overlap (i.e. they are not disjoint). However an intersection such as $\text{Char}\&\text{Int}$ is ok because the set of characters and integers are disjoint to each other.

2.3 Parametric Polymorphism

Unfortunately, combining parametric polymorphism with disjoint intersection types is non-trivial. Consider the following program (uppercase Latin letters to denote type variables):

```
let merge3 A (x : A) : A & Int = x,,3 in
```

The `merge3` function takes an argument x of some type (A) and merges x with 3. Thus the return type of the program is $A \& \text{Int}$. `merge3` is unproblematic for many possible instantiations of A . However, if `merge3` instantiates A with a type that overlaps (i.e. is not disjoint) with Int , then incoherence may happen. For example:

```
merge3 Int 2
```

can evaluate to both 2 or 3.

Forbidding type variables in intersections A naive way to ensure that only programs with disjoint types are accepted is simply to forbid type variables in intersections. That is, an intersection type such as $\text{Char}\&\text{Int}$ would be accepted, but an intersection such as $A\&\text{Int}$ (where A is some type variable) would be rejected. The reasoning behind this design is that type variables can be instantiated to any types, including those already in the intersection. Thus forbidding type variables in the intersection will prevent invalid intersections arising from instantiations with overlapping types.

Such design does guarantee coherence and would prevent `merge3` from type-checking. Unfortunately the big drawback is that the design is too conservative and many other (useful) programs would be rejected. In particular, the `extend` function from Section 1 would also be rejected.

Other approaches Another option to mitigate the issues of incoherence, without using disjoint intersection types is to allow for a biased choice: that is multiple values of the same type may exist in an intersection, but an implementation gives preference to one of them. The encodings of merge operators in TypeScript and Scala [36] use such an approach. A first problem with this approach, which has already been pointed out by Dunfield [23], is that the choice of the corresponding value is tied up to a particular choice in the implementation. In other words incoherence still exists at the semantic level, but the implementation makes it

predictable which overlapping value will be chosen. From the theoretical point-of-view it would be much better to have a clear, coherent semantics, which is independent from concrete implementations. Another problem is that the interaction between biased choice and polymorphism can lead to counter-intuitive programs, since instantiation of type-variables affects the type-directed lookup of a value in an intersection.

2.4 Disjoint Polymorphism

To avoid being overly conservative, while still retaining coherence in the presence of parametric polymorphism and intersection types, F_i uses *disjoint polymorphism*. Inspired by bounded quantification [12], where a type variable is constrained by a type bound, disjoint polymorphism allows type variables to be constrained so that they are disjoint to some given types.

With disjoint quantification a variant of the program `merge3`, which is accepted by F_i , is written as:

```
let merge3 (A * Int) (x : A) : A & Int = x, 3 in
```

In this variant the type `A` can be instantiated to any types disjoint to `Int`. Such restriction is expressed by the notation `A * Int`, where the left-side of `*` denotes the type variable being declared (`A`), and the right-side denotes the disjointness constraint (`Int`). For example,

```
merge3 Bool True
```

is accepted. However, instantiating `A` with `Int` fails to type-check.

Multiple constraints Disjoint quantifications allows for multiple constraints. For example, in the following variant of the `merge3` there is an additional boolean in the merge:

```
let merge3b (A * Int & Bool) (x : A) : A & Int & Bool = x, 3, True in
```

In this case the type variable `A` needs to be disjoint to both `Int` and `Bool`. In F_i such constraint is specified using an intersection type `Int & Bool`. In general, multiple constraints are specified by creating an intersection of all required constraints.

Type variable constraints Disjoint quantification also allows type variables to be disjoint to previously defined type variables. For example, the following program is accepted by F_i :

```
let fst A (B * A) (x : A & B) : A = x
in ...
```

The program has two type variables `A` and `B`. `A` is unconstrained and can be instantiated with any type. However, the type variable `B` can only be instantiated with types that are disjoint to `A`. The constraint on `B` ensures that the intersection type `A & B` is disjoint for all valid instantiations of `A` and `B`. In other words, only coherent uses of `fst` will be accepted. For example, the following use of `fst`:

```
fst Int Char (1,, 'c')
```

is accepted since `Int` and `Char` are disjoint, thus satisfying the constraint on the second type parameter of `fst`. Furthermore, problematic uses of `fst`, such as:

```
fst Int Int (1,, 2)
```

are rejected because `Int` is not disjoint with `Int`, thus failing to satisfy the disjointness constraint on the second type parameter of `fst`.

Empty constraint The type variable A in the `fst` function has no constraint. In F_i this actually means that A should be associated with the empty constraint, which raises the question: which type should be used to represent such empty constraint? Or, in other words, which type is disjoint to every other type? It is obvious that this type should be one of the bounds of the subtyping lattice: either \perp or \top . The essential intuition here is that the more specific a type in the subtyping relation is, the less types exist that are disjoint to it. For example, `Int` is disjoint to all types except the intersections that contain `Int`, `Int` itself, and \perp ; while `Int&Char` is disjoint to all types that `Int` is, plus the types disjoint to `Char`. Thus, the more specific a type variable constraint is, the less options we have to instantiate it with. This reasoning implies that \top should be treated as the empty constraint. Indeed, in F_i , a single type variable A is only syntactic sugar for $A * \top$.

2.5 Stability of Substitutions

From the technical point of view, the main challenge in the design of F_i is that, *in general, types are not stable under substitution*. This contrasts, for example, with System F where types are stable under substitution. That is in System F the following property (among others) holds:

Lemma 1 (Stability of Substitution). *For any well-formed types A and B , and a type variable α , the result of substituting α for A in B is also a well-formed type.*

In F_i if a type variable A is substituted in a type T_1 , for a type T_2 (written $[A := T_2] T_1$), where T_1 and T_2 are well-formed, the resulting type might be ill-formed. To understand why, recall the previous example:

```
fst Int Int (1,, 2)
```

The type signature of `fst` may be read as $\forall A (B * A). (A \& B) \rightarrow A$. An application to the type `Int` will lead to instantiation of the variable A , leading to the type $\forall (B * \text{Int}). (\text{Int} \& B) \rightarrow \text{Int}$. Now, the second `Int` application is problematic, since instantiating B with `Int` will lead to the ill-formed type $(\text{Int} \& \text{Int}) \rightarrow \text{Int}$. However, from this example it is easy to see that all types which are not problematic are exactly the ones disjoint with A . This paper shows how a weaker version of the usual type substitution stability still holds, namely by requiring that the type variable's disjointness constraint is compatible with the type as target of the instantiation.

3 Applications

F_i is illustrated with two applications. The first application shows how to mimic some of TypeScript’s examples of dynamic mixins in F_i . The second application shows how F_i enables a powerful form of polymorphic extensible records.

3.1 Dynamic Mixins

TypeScript is a language that adds static type checking to JavaScript. Amongst numerous static typing constructs, *TypeScript supports a form of intersection types, without a merge operator*. However, it is possible to define a function `extend` that mimics the merge operator:

```
function extend<T, U>(first: T, second: U): T & U {
  let result = <T & U>{};
  for (let id in first) {
    (<any>result)[id] = (<any>first)[id];
  }
  for (let id in second) {
    if (!result.hasOwnProperty(id)) {
      (<any>result)[id] = (<any>second)[id];
    }
  }
  return result;
}

class Person { constructor(public name : string, public male : boolean)
  { } }
interface Loggable { log() : void; }
class ConsoleLogger implements Loggable { log() {...} }
var jim = extend(new Person("Jim",true), new ConsoleLogger());
var n = jim.name;
jim.log();
```

In this example, taken from TypeScript’s documentation³, an `extend` function is defined for mixin composition. Two classes `Person` and `ConsoleLogger` are also defined. Two instances of those classes are then composed in a variable `jim` with the type of the intersection of both using `extend`. It is type-safe to access both the properties from `Person` and `ConsoleLogger` in the object `jim`.

TypeScript’s implementation of `extend` relies on a biased choice. The function starts by creating a variable `result` with the type of the intersection. It then iterates through the `first`’s properties and copies them to the `result`. Next, it iterates through the `second`’s properties but it only copies the properties that `result` does not possess yet (i.e. the ones present in `first`). This means that the implementation is left-biased, as the properties of left type of the intersection are chosen in favor of the ones present in the right. However, in TypeScript this may be a cause of severe problems since that, at the time of writing, intersections at type-level are actually right-biased! For example, the following code is well-typed:

³ We have added the field `male` to the class `Person`.


```

class Dog { constructor(public name : string, public male : string) { } }
var fool : Dog & Person = extend(new Dog("Pluto","yes"),new
    Person("Arnold",true))
boolean b = fool.male

```

Note how `fool.male` is statically bound to a variable of type `boolean` but, at run-time, it will contain a value of type `String`!

Other problematic issues regarding the semantics of intersection types can include the order of the types in an intersection, or even intersections including repeated types. This motivates the need to define a clear meaning for the practical application of intersection types.

Dynamic mixins in F_i In F_i , the merge combinator is directly embedded in the semantics of the language, and thus `extend` is simply defined as follows:

```

let extend T (U * T) (first : T, second : U) : T & U = first ,, second

```

The disjointness constraint on `U` ensures that no conflicts (such as duplicated fields of the same type) exists when merging the two objects. In practice this approach is quite similar to trait-based OO approaches [1]. If conflicts exist when two objects are composed, then fields have to be explicitly dropped from at least one object. Moreover if no existing implementation can be directly reused, a new one must be provided via record extension, analogously to standard method overriding in OO languages.

For the previous TypeScript examples, assuming a straightforward translation from objects to (polymorphic) records, then the composition of `person` and `consoleLogger` is well-typed in F_i :

```

type Person = {name : String} & {male : Bool};
type Loggable = {log : T → T};

let person (n : String) (s : Bool) : Person = {name = n} ,, {male = s} in
let consoleLogger : Loggable = {log = ...} in
let jim = extend Person Loggable (person "Jim" true) consoleLogger in
let n = jim.name in
jim.log T

```

However, the intersection `Person & Dog` is not accepted. This is due to both types sharing a field with the same name (`name`) and the same type (`String`). Note that the name clash between `male` fields does not impose any problem in this example. This will be further illustrated in the next section.

3.2 Extensible Records

F_i can encode polymorphic extensible records. Describing and implementing records within programming languages is certainly not novel and has been extensively studied in the past, including systems with row types [48,49]; predicates [29,28,27]; flags [42]; conditional constraints [39]; cases [9]; amongst others. However, while most systems have non-trivial built-in constructs to model various aspects of records, F_i specializes the more general notion of intersection types to encode complex records.

Records and record operations in F_i Systems with records usually rely on 3 basic operations: selection, restriction and extension/concatenation. Selection and concatenation (via the merge operator) are built-in in the semantics of F_i . Merges in F_i can be viewed as a generalization of record concatenation. In F_i , following well-known encodings of records in systems with intersection types and a merge operator \llbracket , there are only three rather simple constructs for records: 1) single field record types; 2) single field records; 3) field accessors. Multi-field records in F_i are encoded with intersections and merges of single field records. An example is already illustrated in Section 3.1. The record type `Person` is the intersection of two single field record types. The record `person "Jim" true` is built with a merge of two single field records. Finally, `jim.name` and `jim.log` illustrates the use of field accessors. Note how, through the use of subtyping, accessors will accept any intersection type that contains the single record with the corresponding field. This resembles systems with record subtyping [13,38].

Restriction via subtyping In contrast with most record systems, restriction is not directly embedded in F_i . Instead, F_i uses subtyping for restriction:

```
let remove (x : { age : Int } & {name : String}) : {name : String} = x in
  ...
```

The function `remove` drops the field `age` from the record `x`.

Polymorphic extensible records Records in F_i can have polymorphic fields, and disjointness enables encoding various operations expressible in systems with polymorphic records. For example, the following variant of `remove`

```
let remove A (B * {l : A}) (x : { l : A } & B) : B = x in ...
```

takes a value `x` which contains a record of type `l : A`, as well as some extra information of type `B`. The disjointness constraint on `B` ensures that values of type `B` do not contain a record with type `l : A`. This example shows that one can use disjoint quantification to express negative field information, which is very close to the system described by Harper and Pierce [28]. Note, however, that F_i requires explicitly stating the type of field in the constraint, whereas systems with a *lacks* (field) predicate only require the name of the field. The generality of disjoint intersection types, which allows one to encode record types, is exactly what forces us to add this extra type in the constraint. However, there is a slight gain with F_i 's approach: `remove` allows `B` to contain fields with label `l`, as long as the field types are *disjoint* to `Int`. Such fine-grained constraint is not possible to express only with a *lacks* predicate.

Expressibility As noted by Leijen [32], systems typically can be categorized into two distinct groups in what concerns extension: strict; and free. The former does not allow field overriding when extending a record (i.e. one can only extend a record with a field that is not present in it); while the latter does account for field overriding. Our system can be seen as hybrid of these two kinds of systems.

With lightweight extensible records [30] – a system with strict extension – an example of a function that uses record types is the following:

```
let avg1 (R\y, R\y) => (r : {R | x:Int, y:Int}) = (r.x+r.y)/2
```

The type signature says that for any record r , containing fields x and y and some more information R (which lacks both fields x and y), can be accepted returning an integer. Note how the bounded polymorphism is essential to ensure that R does not contain x nor y .

On the other hand, in Leijen’s [32] system with free extension the more general program would be accepted:

```
let avg2 R (r : {x:Int, y:Int | R}) = (r.x+r.y)/2
```

BRUNO: any reason why the position of R in the record type for the 3 examples is not consistent? If not, please make sure they are all consistent. In this case, if R contains either field x or field y , they would be shadowed by the labels present in the type signature. In other words, in a record with multiple x fields, the most recent (i.e. left-most) is used in any function which accesses x .

In F_i the following program can be written instead:

```
let avg3 (R*{x:Int}&{y:Int}) (r : {x:Int}&{y:Int}&R) = (r.x+r.y)/2
```

Since F_i accepts duplicated fields as long as the types of the overlapping fields are disjoint, more inputs are accepted by this function than in the first system. However, since Leijen’s system accepts duplicated fields even when types are overlapping, avg_3 accepts less types than avg_2 . Another major difference between F_i and the two other mentioned systems, is the ability to combine records with arbitrary types. Our system does not account for well-formedness of record types as the other two systems do (i.e. using a special *row* kind), since our encoding of records piggybacks on the more general notion of disjoint intersection types.

4 The F_i Calculus

This section presents the syntax, subtyping, and typing of F_i : a calculus with intersection types, parametric polymorphism, records and a merge operator. This calculus is an extension of λ_i and Dunfield’s calculus [23], which are simply typed calculus with intersection types and a merge operator. The novelty of F_i is the addition of *disjoint polymorphism*: a form of parametric polymorphism with disjointness constraints, which allows flexibility while at the same time retaining coherence. Section 5 introduces the necessary changes to the definition of disjointness presented by Oliveira et al. [46] in order to add disjoint polymorphism.

All the meta-theory of F_i has been mechanized in Coq, which is available in the supplementary materials submitted with the paper.

4.1 Syntax

The syntax of F_i (with the differences to λ_i highlighted in gray) is:

Types	$A, B ::= \top \mid \text{Int} \mid A \rightarrow B \mid A \& B \mid \alpha \mid \forall(\alpha * A). B \mid \{l : A\}$
Terms	$e ::= \top \mid i \mid x \mid \lambda x. e \mid e_1 \ e_2 \mid e_1, e_2 \mid \Lambda(\alpha * A). e \mid e \ A \mid \{l = e\}$ $\mid e.l$
Contexts Γ	$::= \cdot \mid \Gamma, \alpha * A \mid \Gamma, x : A$

Types. Metavariables A, B range over types. Types include all constructs in λ_i : a top type \top ; the type of integers Int ; function types $A \rightarrow B$; and intersection types $A \& B$. The main novelty are two standard constructs of System F used to support polymorphism: type variables α and disjoint (universal) quantification $\forall(\alpha * A). B$. Unlike traditional universal quantification, the disjoint quantification includes a disjointness constraint associated to a type variable α . Finally, F_i also includes singleton record types, which consist of a label l and an associated type A . We will use $[\alpha := A] B$ to denote the capture-avoiding substitution of A for α inside B and $\text{ftv}(\cdot)$ for sets of free type variables.

Terms. Metavariables e range over terms. Terms include all constructs in λ_i : a canonical top value \top ; integer literals i ; variables x , lambda abstractions $(\lambda x. e)$; applications $(e_1 \ e_2)$; and the *merge* of terms e_1 and e_2 denoted as e_1, e_2 . Terms are extended with two standard constructs in System F: abstraction of type variables over terms $\Lambda(\alpha * A). e$; and application of terms to types $e \ A$. The former also includes an extra disjointness constraint tied to the type variable α , due to disjoint quantification. Singleton records consists of a label l and an associated term e . Finally, the accessor for a label l in term e is denoted as $e.l$.

Contexts. Typing contexts Γ track bound type variables α with disjointness constraints A ; and variables x with their type A . We will use $[\alpha := A] \Gamma$ to denote the capture-avoiding substitution of A for α in the co-domain of Γ where the domain is a type variable (i.e all disjointness constraints). Throughout this paper, we will assume that all contexts are well-formed. Importantly, besides usual well-formedness conditions, in well-formed contexts type variables must not appear free within its own disjointness constraint.

Syntactic sugar In F_i we may quantify a type variables and omit its constraint. This means that its constraint is \top . For example, the function type $\forall \alpha. \alpha \rightarrow \alpha$ is syntactic sugar for $\forall(\alpha * \top). \alpha \rightarrow \alpha$. This is discussed in more detail in Section 6.

4.2 Subtyping

The subtyping rules of the form $A <: B$ are shown in Figure 1. At the moment, the reader is advised to ignore the gray-shaded parts, which will be explained later. Some rules are ported from λ_i : ST , SZ , $\text{S}\rightarrow$, $\text{S}\&\text{R}$, $\text{S}\&\text{L}_1$ and $\text{S}\&\text{L}_2$.

Polymorphism and Records. The subtyping rules introduced by F_i refer to polymorphic constructs and records. $\text{S}\alpha$ defines subtyping as a reflexive relation on type variables. In $\text{S}\forall$ a universal quantifier (\forall) is covariant in its body, and contravariant in its disjointness constraints. The SREC rule says that records are covariant within their fields' types. Also, since the **ordinary** conditions on two of the intersection rules are necessary to produce unique coercions [46], the **ordinary** relation needed to be extended. As shown at the top of Figure 1, the new types it contains are type variables, universal quantifiers and record types.

$$\begin{array}{c}
\boxed{A \text{ ordinary}} \\
\text{Int ordinary} \quad A \rightarrow B \text{ ordinary} \quad \alpha \text{ ordinary} \quad \forall(\alpha * B). A \text{ ordinary} \\
\{l : A\} \text{ ordinary} \\
\boxed{A <: B \hookrightarrow E} \\
\\
\frac{}{A <: \top \hookrightarrow \lambda x. ()} \text{ST} \quad \frac{A_1 <: A_2 \hookrightarrow E_1 \quad A_1 <: A_3 \hookrightarrow E_2}{A_1 <: A_2 \& A_3 \hookrightarrow \lambda x. (E_1 \ x, E_2 \ x)} \text{S\&R} \\
\\
\frac{}{\text{Int} <: \text{Int} \hookrightarrow \lambda x. x} \text{SZ} \quad \frac{A_1 <: A_3 \hookrightarrow E \quad A_3 \text{ ordinary}}{A_1 \& A_2 <: A_3 \hookrightarrow \lambda x. \llbracket A_3 \rrbracket_{(E \ (\text{proj}_1 \ x))}} \text{S\&L}_1 \\
\\
\frac{A <: B \hookrightarrow E}{\{l : A\} <: \{l : B\} \hookrightarrow E} \text{SREC} \quad \frac{A_2 <: A_3 \hookrightarrow E \quad A_3 \text{ ordinary}}{A_1 \& A_2 <: A_3 \hookrightarrow \lambda x. \llbracket A_3 \rrbracket_{(E \ (\text{proj}_2 \ x))}} \text{S\&L}_2 \\
\\
\frac{}{\alpha <: \alpha \hookrightarrow \lambda x. x} \text{S}\alpha \quad \frac{B_1 <: A_1 \hookrightarrow E_1 \quad A_2 <: B_2 \hookrightarrow E_2}{A_1 \rightarrow A_2 <: B_1 \rightarrow B_2 \hookrightarrow \lambda f. \lambda x. E_2 \ (f \ (E_1 \ x))} \text{S}\rightarrow \\
\\
\frac{B_1 <: B_2 \hookrightarrow E_1 \quad A_2 <: A_1 \hookrightarrow E_2}{\forall(\alpha * A_1). B_1 <: \forall(\alpha * A_2). B_2 \hookrightarrow \lambda f. \forall \alpha. E_1 \ (f \ \alpha)} \text{S}\forall
\end{array}$$

Fig. 1. Subtyping rules of F_i .

Properties of Subtyping. The subtyping relation is reflexive and transitive.

Lemma 2 (Subtyping reflexivity). *For any type A , $A <: A$.*

Proof. By induction on A .

Lemma 3 (Subtyping transitivity). *If $A <: B$ and $B <: C$, then $A <: C$.*

Proof. By double induction on both derivations.

4.3 Typing

Well-formedness. The well-formedness rules are shown in the top part of Figure 2. The new rules over λ_i are $\text{WF}\alpha$ and $\text{WF}\forall$. Their definition is quite straightforward, but note that the constraint in the latter must be well-formed.

$$\boxed{\Gamma \vdash A}$$

$$\begin{array}{c}
\frac{}{\Gamma \vdash \text{Int}} \text{WF}\mathbb{Z} \quad \frac{\alpha * A \in \Gamma}{\Gamma \vdash \alpha} \text{WF}\alpha \quad \frac{\Gamma \vdash A}{\Gamma \vdash \{l : A\}} \text{WFR} \quad \frac{\Gamma \vdash A \quad \Gamma \vdash B}{\Gamma \vdash A \rightarrow B} \text{WF}\rightarrow \\
\frac{}{\Gamma \vdash \top} \text{WF}\top \quad \frac{\Gamma \vdash A \quad \Gamma, \alpha * A \vdash B}{\Gamma \vdash \forall(\alpha * A). B} \text{WF}\forall \quad \frac{\Gamma \vdash A \quad \Gamma \vdash B \quad \Gamma \vdash A * B}{\Gamma \vdash A \& B} \text{WF}\& \\
\boxed{\Gamma \vdash e \Rightarrow A \hookrightarrow E \quad e \text{ synthesizes type } A} \\
\frac{}{\Gamma \vdash \top \Rightarrow \top \hookrightarrow ()} \text{T-TOP} \quad \frac{}{\Gamma \vdash i \Rightarrow \text{Int} \hookrightarrow i} \text{T-INT} \\
\frac{x:A \in \Gamma}{\Gamma \vdash x \Rightarrow A \hookrightarrow x} \text{T-VAR} \quad \frac{\Gamma \vdash e \Leftarrow A \hookrightarrow E}{\Gamma \vdash e : A \Rightarrow A \hookrightarrow E} \text{T-ANN} \\
\frac{\Gamma \vdash e_1 \Rightarrow A_1 \rightarrow A_2 \hookrightarrow E_1 \quad \Gamma \vdash e_2 \Leftarrow A_1 \hookrightarrow E_2}{\Gamma \vdash e_1 \ e_2 \Rightarrow A_2 \hookrightarrow E_1 \ E_2} \text{T-APP} \\
\frac{\Gamma \vdash e \Rightarrow \forall(\alpha * B). C \hookrightarrow E \quad \Gamma \vdash A \quad \boxed{\Gamma \vdash A * B}}{\Gamma \vdash e \ A \Rightarrow [\alpha := A] \ C \hookrightarrow E \ |A|} \text{T-TAPP} \\
\frac{\Gamma \vdash e_1 \Rightarrow A \hookrightarrow E_1 \quad \Gamma \vdash e_2 \Rightarrow B \hookrightarrow E_2 \quad \Gamma \vdash A * B}{\Gamma \vdash e_1, e_2 \Rightarrow A \& B \hookrightarrow (E_1, E_2)} \text{T-MERGE} \\
\frac{\Gamma \vdash e \Rightarrow A \hookrightarrow E}{\Gamma \vdash \{l = e\} \Rightarrow \{l : A\} \hookrightarrow E} \text{T-REC} \quad \frac{\Gamma \vdash e \Rightarrow \{l : A\} \hookrightarrow E}{\Gamma \vdash e.l \Rightarrow A \hookrightarrow E} \text{T-PROJR} \\
\frac{\Gamma \vdash A \quad \Gamma, \alpha * A \vdash e \Rightarrow B \hookrightarrow E \quad \alpha \notin \text{ftv}(\Gamma)}{\Gamma \vdash \Lambda(\alpha * A). e \Rightarrow \forall(\alpha * A). B \hookrightarrow \Lambda\alpha. E} \text{T-BLAM} \\
\boxed{\Gamma \vdash e \Leftarrow A \hookrightarrow E \quad e \text{ checks against given type } A} \\
\frac{\Gamma \vdash A \quad \Gamma, x:A \vdash e \Leftarrow B \hookrightarrow E}{\Gamma \vdash \lambda x. e \Leftarrow A \rightarrow B \hookrightarrow \lambda x. E} \text{T-LAM} \\
\frac{\Gamma \vdash e \Rightarrow A \hookrightarrow E \quad A <: B \hookrightarrow E_{\text{sub}}}{\Gamma \vdash e \Leftarrow B \hookrightarrow E_{\text{sub}} \ E} \text{T-SUB}
\end{array}$$

Fig. 2. Wellformedness and type system of F_i .

Typing rules. Our typing rules are formulated as a bi-directional type-system. Just as in λ_i , this ensures the type-system is not only syntax-directed, but also that there is no type ambiguity: that is, inferred types are unique. The typing rules are shown in the bottom part of Figure 2. Again, the reader is advised to ignore the gray-shaded parts, as these will be explained later. The typing judgements are of the form: $\Gamma \vdash e \Leftarrow A$ and $\Gamma \vdash e \Rightarrow A$. They read: “in the typing context Γ , the term e can be checked or inferred to type A ”, respectively. The rules ported from λ_i are the check rules for \top (T-TOP), integers (T-INT), variables (T-VAR), application (T-APP), merge operator (T-MERGE), annotations (T-ANN); and infer rules for lambda abstractions (T-LAM), and the subsumption rule (T-SUB).

Disjoint quantification. The new rules, inspired by System F, are the infer rules for type application T-TAPP, and for type abstraction T-BLAM. Type abstraction is introduced by the big lambda $\Lambda(\alpha * A).e$, eliminated by the usual type application $e A$ (T-TAPP). The disjointness constraint is added to the context in T-BLAM. During a type application, the type system makes sure that the type argument satisfies the disjointness constraint. Type application performs an extra check ensuring that the type to be instantiated is compatible (i.e. disjoint) with the constraint associated with the abstracted variable. This is important, as it will retain the desired coherence of our type-system. For ease of discussion, also in T-BLAM, we require the type variable introduced by the quantifier to be fresh. For programs with type variable shadowing, this requirement can be met straightforwardly by variable renaming.

Records. Finally, T-REC and T-PROJR deal with record types. The former infers a type for a record with label l if it can infer a type for the inner expression; the latter says if one can infer a record type $\{l : A\}$ from an expression e , then it is safe to access the field l , and inferring type A .

5 Disjointness

Section 4 presented a type system with disjoint intersection types and disjoint quantification. In order to prove both type-safe and coherence (in Section 6), it is necessary to first introduce a notion of disjointness, considering polymorphism and disjointness quantification. This section presents an algorithmic set of rules for determining whether two types are disjoint. After, it will show a few important properties regarding substitution, which will turn out to be crucial to ensure type-safety. Finally, it will discuss the bounds of disjoint quantification and what implications they have on F_i , with a special focus on the \top type.

5.1 Algorithmic Rules for Disjointness

The rules for the disjointness judgement are shown in Figure 3, which consists of two judgements.

$$\boxed{\Gamma \vdash A * B}$$

$$\begin{array}{c}
\frac{}{\Gamma \vdash \top * A} \text{D}\top \quad \frac{}{\Gamma \vdash A * \top} \text{D}\top\text{Sym} \quad \frac{\alpha * A \in \Gamma \quad A <: B}{\Gamma \vdash \alpha * B} \text{D}\alpha \\
\\
\frac{\alpha * A \in \Gamma \quad A <: B}{\Gamma \vdash B * \alpha} \text{D}\alpha\text{Sym} \quad \frac{\Gamma, \alpha * A_1 \& A_2 \vdash B * C}{\Gamma \vdash \forall(\alpha * A_1). B * \forall(\alpha * A_2). C} \text{D}\forall \\
\\
\frac{\Gamma \vdash A_2 * B_2}{\Gamma \vdash A_1 \rightarrow A_2 * B_1 \rightarrow B_2} \text{D}\rightarrow \quad \frac{\Gamma \vdash A_1 * B \quad \Gamma \vdash A_2 * B}{\Gamma \vdash A_1 \& A_2 * B} \text{D}\&\text{L} \\
\\
\frac{\Gamma \vdash A * B_1 \quad \Gamma \vdash A * B_2}{\Gamma \vdash A * B_1 \& B_2} \text{D}\&\text{R} \quad \frac{A *_{\text{ax}} B}{\Gamma \vdash A * B} \text{D}\text{Ax} \\
\\
\boxed{A *_{\text{ax}} B}
\end{array}$$

$$\begin{array}{c}
\frac{}{\text{Int } *_{\text{ax}} A_1 \rightarrow A_2} \text{D-Ax}(\mathbb{Z} \rightarrow) \quad \frac{}{\text{Int } *_{\text{ax}} \forall(\alpha * B_1). B_2} \text{D-Ax}(\mathbb{Z}\forall) \\
\\
\frac{}{A_1 \rightarrow A_2 *_{\text{ax}} \forall(\alpha * B_1). B_2} \text{D-Ax}(\rightarrow \forall) \quad \frac{B *_{\text{ax}} A}{A *_{\text{ax}} B} \text{D-AxSym}
\end{array}$$

Fig. 3. Algorithmic Disjointness.

Main judgement. The judgement $\Gamma \vdash A * B$ says two types A and B are disjoint in a context Γ . The top five rules are novel in relation to the algorithm described in λ_i . $\text{D}\top$ and $\text{D}\top\text{Sym}$ say that any type is disjoint to \top . This is a major difference with λ_i , where the notion of disjointness explicitly forbids the presence of \top types in intersections. It turns out that even though \top overlaps with every other type, it does not affect coherence in any way. We will come back to this in Section 6.

Type variables are dealt with two rules: $\text{D}\alpha$ is the base rule; and $\text{D}\alpha\text{Sym}$ is its twin symmetrical rule. Both rules state that a type variable is disjoint to some type A , if Γ contains any subtype of the corresponding disjointness constraint. This rule is a specialization of the more general lemma:

Lemma 4 (Covariance of disjointness).

*If $\Gamma \vdash A * B$ and $B <: C$, then $\Gamma \vdash A * C$.*

Proof. By double induction, first on the disjointness derivation and then on the subtyping derivation. The first induction case for $\text{D}\alpha$ does not need the second induction as it is a straightforward application of subtyping transitivity.

The lemma states that if a type A is disjoint to B under Γ , then it is also disjoint to any supertype of B . Note how these two variable rules would allow one to prove $x * x$, for a given type variable x . However, since we are assuming that all contexts are well-formed, it is not possible to make such derivation as x cannot occur free in A . The rule for disjoint quantification $D\forall$ is the last novel rule. It adds a constraint composed of the intersection both constraints into Γ and checks for disjointness in the bodies under that environment. To illustrate this rule, consider the following two types:

$$(\forall(\alpha * \text{Int}). \text{Int} \& \alpha) \quad (\forall(\alpha * \text{Char}). \text{Char} \& \alpha)$$

When are these two types disjoint? In the first type α cannot be instantiated with Int and in the second case α cannot be instantiated with Char . Therefore for both bodies to be disjoint, α cannot be instantiated with either Int or Char . The reader might notice how this intersection does not necessarily need to be well-formed, in the sense that the types that compose it might not be disjoint. This means that disjointness is only necessary to guarantee the coherence of elaboration. Introducing arbitrary intersection types in the environment is not problematic, as the disjointness relation does not contribute directly to the coercions generated by the type-system. The remaining rules are identical to the original rules. We emphasize that the rule $D\text{Ax}$ says two different type constructs are disjoint if the axiom rules (explained below) apply.

Axioms. Axiom rules take care of two types with different language constructs. These rules capture the set of rules is that $A *_{\text{ax}} B$ holds for all two types of different constructs unless any of them is an intersection type, a type variable, or \top . Note that disjointness with type variables is already captured by $D\alpha$ and $D\alpha\text{Sym}$, and disjointness with the \top type is captured by $D\top$ and $D\top\text{Sym}$.

5.2 Stability under Substitution

The combination of polymorphism and disjoint intersection types invalidates various conventional substitution lemmas related to well-formedness and typing. For example, as shown in Section 2, in the type $\forall(A * \text{Int}). (\text{Int} \& A) \rightarrow \text{Int}$, the type A cannot be substituted by any type. However, under certain conditions, weaker versions of substitution lemmas do hold. The conditions are guaranteed by the type-system by only allowing instantiations of a type variable with types disjoint to the variable's disjointness constraints.

Problematic substitutions. One rule of thumb in disjoint intersection types is that, if a type A is disjoint to a type B , then the intersection $A \& B$ is well-typed. However, during type instantiation (i.e. when type substitution should be stable), both types A and B can change. It should follow naturally that this instantiation will not produce an ill-formed type $A \& B$, or, more generally, disjointness should be stable under substitution. Let us illustrate with an example, showing why disjointness judgements are not invariant with respect to free variable substitution. In other words, why a careless substitution can violate the

disjoint constraint in the context. Consider the following judgement, where in the context $\alpha * \text{Int}$, α and Int are disjoint:

$$\alpha * \text{Int} \vdash \alpha * \text{Int}$$

After the substitution of Int for α on the two types, the sentence

$$\alpha * \text{Int} \vdash \text{Int} * \text{Int}$$

is no longer true since Int is clearly not disjoint with itself. This explains the need to ensure that during type-instantiation the target of the substitution is compatible with the disjointness constraint associated with the variable.

Disjoint substitutions. While disjointness cannot be preserved for general substitutions, if appropriate disjointness pre-conditions are met then disjointness can be preserved. More formally, the following lemma holds:

Lemma 5 (Disjointness is stable under substitution).

*If $(x * C) \in \Gamma$ and $\Gamma \vdash C * D$, then $[x := C] \Gamma \vdash [x := C] A * [x := C] B$,*

Proof. By induction on the disjointness derivation of C and D . Special attention is needed for the variable case, where it is necessary to prove stability of substitution for the subtyping relation. It is also needed to show that, if C and D do not contain any variable x , then it is safe to make a substitution in the co-domain of the environment.

Well-formedness substitution stability. Typically polymorphic systems with explicit instantiation are required to show that their types are stable under substitution, in order to avoid ill-formed types. In the presence of disjoint quantification, we cannot prove such property. However, a weaker version of that property – but strong enough for our type-system’s metatheory – can be proven, namely:

Lemma 6 (Types are stable under substitution).

*If $\Gamma \vdash A$ and $\Gamma \vdash B$ and $(\alpha * C) \in \Gamma$ and $\Gamma \vdash B * C$, then $[\alpha := B] \Gamma \vdash [\alpha := B] A$.*

Proof. By induction on the well-formedness derivation of A . The intersection case requires the use of Lemma 5. Also, the variable case required proving that if α does not occur free in A , and it is safe to substitute it in the co-domain of Γ , then it is safe to perform the substitution.

This lemma enables us to show that all types produced by the type-system are well-typed. More formally, we have that:

Lemma 7 (Well-formed typing).

If $\Gamma \vdash e \Leftarrow A$, then $\Gamma \vdash A$.

If $\Gamma \vdash e \Rightarrow A$, then $\Gamma \vdash A$.

Proof. By induction on the derivation and applying Lemma 6 in the case of T-TAPP.

Even though the meta-theory is consistent with the expected results, we might still ask: what exactly are the bounds of disjoint quantification? In other words, which type(s) might be used to allow unrestricted instantiation, and which one(s) might be used to completely restrict instantiation? As the reader might expect, the answer is tightly related to subtyping, as we will show next.

5.3 Bounds of Disjoint Quantification

Substitution raises the question of what range of types can be instantiated for a given variable, under a given context. To get a feeling about this, we ask the reader to recall Lemma 4, used to justify the rule for disjointness of variables. If one takes A as some variable α , then the lemma should read as:

$$\frac{\Gamma \vdash \alpha * B \quad B <: C}{\Gamma \vdash \alpha * C}$$

Now we may ask: how many suitable types are there to instantiate α with, depending on B ? Before we answer this, let us ask first how many options are there for C , depending on the shape of B ? Given that the cardinality of F_i 's types is infinite, for the sake of this example we will restrict the type universe to a finite number of primitive types (i.e. **Int**, **String**, etc), disjoint intersections of these types, \top and \perp . Having this in mind, we can answer the second question: the number of choices for C is directly proportional to the number of intersections present in B . For example, taking B as **Int** leads C to be either \top or **Int**; whereas B as **Int&String** leaves C as either \top , **Int** or **String**. However, as the choices for C grows, the less choices we are left to instantiate the variable α , since α must be disjoint to all possible C 's. Thus, to answer the first question, the options for instantiating α are inversely proportional to the number of intersections present in B . By analogy, one may think of a disjointness constraint as a set of (forbidden) types, where primitive types are the singleton set and each $\&$ is the set union.

We can now turn our attention to the two extreme cases, namely \top (i.e. the 0-ary intersection) and \perp (i.e. the infinite intersection) ⁴. Following the same logic, we may conclude that having \top as constraint leaves α with the most options for instantiation; whereas \perp will deliver the least options. This implies that \top is the empty constraint, meaning that a variable associated to it can be instantiated to any well-formed type. It is a subtle but very important property, since F_i is a generalization of System F. Any type variable present in a type signature of System F, can be represented in F_i equivalently by assigning it a \top disjointness constraint (as seen in Section 2.4).

6 Semantics, Coherence and Type-Safety

This section discusses the elaboration semantics of F_i and proves type-safety and coherence. It will first show how the semantics is described by an elaboration

⁴ \perp would not add anything to the hypothetical finite type system, however it can be seen as the infinite intersection in F_i .

$ A = T$	$ \Gamma = G$
$ \alpha = \alpha$	$ \cdot = \cdot$
$ \top = ()$	$ \Gamma, \alpha * A = \Gamma , \alpha$
$ A_1 \rightarrow A_2 = A_1 \rightarrow A_2 $	$ \Gamma, \alpha : A = \Gamma , \alpha : A $
$ \forall(\alpha * A). B = \forall \alpha. B $	
$ A_1 \& A_2 = (A_1 , A_2)$	

Fig. 4. Type and context translation.

to System F. Then, it will discuss the necessary extensions to retain coherence, namely in the coercions of top-like types; coercive subtyping, and bidirectional type-system's elaboration.

6.1 Semantics

The dynamic semantics of the call-by-value F_i is defined by means of a type-directed translation to an extension of System F with pairs.

Target language. The syntax and typing of our target language is unsurprising:

Types $T ::= \alpha \mid \text{Int} \mid T_1 \rightarrow T_2 \mid \forall \alpha. T \mid () \mid (T_1, T_2)$
Terms $E ::= x \mid i \mid \lambda x. E \mid E_1 E_2 \mid \Lambda \alpha. E \mid E T \mid () \mid (E_1, E_2) \mid \text{proj}_1 E \mid \text{proj}_2 E$
Contexts $G ::= \cdot \mid G, \alpha \mid G, x : T$

The highlighted part shows its difference with the standard System F. The interested reader can find the formalization of the target language syntax and typing rules (which are standard) in our Coq development.

Type and context translation. Figure 4 defines the type translation function $|\cdot|$ from F_i types A to target language types T . The notation $|\cdot|$ is also overloaded for context translation from F_i contexts Γ to target language contexts G .

6.2 Top-like types and their coercions

Top-like types. An important set of types are the so-called top-like types. This classification is crucial in order to prove coherence. Top-like types are types that relate to \top , in the sense that they only having one inhabitant each. Therefore, their (unique) coercions can be generated structurally from their types. For example, the term $\lambda x. ()$ represents the only inhabitant of the type $\text{Int} \rightarrow \top$.

$$\begin{array}{c}
\boxed{\lceil A \rceil} \\
\\
\frac{}{\lceil \top \rceil} \text{TL}\top \quad \frac{\lceil A \rceil \quad \lceil B \rceil}{\lceil A \& B \rceil} \text{TL}\& \quad \frac{\lceil B \rceil}{\lceil A \rightarrow B \rceil} \text{TL} \rightarrow \quad \frac{\lceil A \rceil}{\lceil \forall(\alpha * B). A \rceil} \text{TL}\forall \\
\\
\boxed{\llbracket A \rrbracket_{\text{C}} = \top} \quad \boxed{\llbracket A \rrbracket = \top} \\
\\
\llbracket A \rrbracket_{\text{C}} = \begin{cases} \lceil A \rceil & \llbracket A \rrbracket \\ \text{otherwise} & \text{C} \end{cases} \quad \llbracket A \rrbracket = \begin{cases} A = \top & () \\ A = A_1 \rightarrow A_2 & \lambda x. \llbracket A_2 \rrbracket \\ A = A_1 \& A_2 & (\llbracket A_1 \rrbracket, \llbracket A_2 \rrbracket) \\ A = \forall(\alpha * B). A & \lambda \alpha. \llbracket A \rrbracket \end{cases}
\end{array}$$

Fig. 5. Top-like types and their coercions.

However, according to [46], some top-like types might be problematic. For instance, a top-like type can be an intersection composed of \top types, as in $\top \& \top$. This type is a super-type of every other type, including \top itself. Also, there might be a coherence problem with this type, since both components of the intersection overlap. However, taking a closer look at this type clarifies that there is no issues with such types. To see this, let us first consider the ill-type $\text{Int} \& \text{Int}$. This type is a potential source for incoherence, as both components of the merge overlap. For example, the term $(3, 4) : \text{Int}$ is incoherent, since the terms 3 and 4 can both be typed Int . There is one case though, where coherence is not compromised: if the inhabitants of both types are the same, as in $2, 2$. In this case, both values can be chosen interchangeably, without affecting the coherence of the program. It is important realizing that this is always the case with top-like intersections. Moreover, top-like types can also be safely intersected with other types, as their inhabitants do not overlap. Generally speaking, top-like types should never be a source of incoherence. This explains why \top is disjoint to every other type, as mentioned in Section 5.

Rules. Our definition of top-like types is naturally extended from λ_i . The rules that compose this unary relation, denoted as $\lceil \cdot \rceil$, are presented at the top of Figure 5. The only new rule is $\text{TL}\forall$, which extends the notion of top-like types for the (disjoint) universal quantifier.

Furthermore, the notion of disjointness has changed, leading to a larger set of well-formed top-like types. In order to retain coherence, we adjusted the meta-function $\llbracket A \rrbracket$, as shown in the bottom of Figure 5. Note how not only the \forall case is now defined, but also the $\&$ case (covering types such as $\top \& \top$).

6.3 Coercive Subtyping and Coherence

Coercive subtyping. The judgement

$$A_1 <: A_2 \hookrightarrow E$$

extends the subtyping judgement in Figure 1 with a coercion on the right hand side of \hookrightarrow . A coercion E is just a term in the target language and is ensured to have type $|A_1| \rightarrow |A_2|$ (by Lemma 8). For example,

$$\text{Int}\&\alpha <: \alpha \hookrightarrow \lambda x. \text{proj}_2 x$$

generates a target coercion function with type: $(\text{Int}, \alpha) \rightarrow \alpha$.

Rules ST , $\text{S}\alpha$, SZ , $\text{S}\rightarrow$, $\text{S}\&\text{L}_1$, $\text{S}\&\text{L}_2$, and $\text{S}\&\text{R}$ are taken directly from λ_i . In rule $\text{S}\alpha$, the coercion is simply the identity function. Rule $\text{S}\forall$ elaborates disjoint quantification, reusing only the coercion of subtyping between the bodies of both types. Rule SREC elaborates records by simply reusing the coercion generated between the inner types. Finally, all rules produce type-correct coercions:

Lemma 8 (Subtyping rules produce type-correct coercions). *If $A_1 <: A_2 \hookrightarrow E$, then $\cdot \vdash E : |A_1| \rightarrow |A_2|$.*

Proof. By a straightforward induction on the derivation.

Unique coercions In order to ensure a coherent type-system, the subtyping relation also needs to be coherent. With disjoint polymorphism the following theorem holds:

Lemma 9 (Unique subtype contributor).

If $A_1 \& A_2 <: B$, where $A_1 \& A_2$ and B are well-formed types, and B is not top-like, then it is not possible that the following holds at the same time:

1. $A_1 <: B$
2. $A_2 <: B$

Proof. By double induction: the first on the disjointness derivation (which follows from $A_1 \& A_2$ being well-formed); the second on type B . The variable cases $\text{D}\alpha$ and $\text{D}\alpha\text{Sym}$ needed to show that, for any two well-formed and disjoint types A and B , and B is not top-like, then A cannot be a subtype of B .

Using the unique subtype contributor, we can show that the coercion of a subtyping relation $A <: B$ is uniquely determined. This fact is captured by the following lemma:

Lemma 10 (Unique coercion).

If $A <: B \hookrightarrow E_1$ and $A <: B \hookrightarrow E_2$, where A and B are well-formed types, then $E_1 \equiv E_2$.

Proof. By induction on the first derivation and case analysis on the shape of the second.

6.4 Elaboration of type-system and coherence

In order to prove the coherence result, we refer to the bidirectional type-system introduced in Section 4. The bidirectional type-system is elaborating, producing a term in the target language while performing the typing derivation.

Key idea of the translation. This translation turns merges into usual pairs, similar to Dunfield’s elaboration approach [23]. It also translates the form of disjoint quantification and disjoint type application into regular (polymorphic) quantification and type application. For example,

$$\Lambda(\alpha * \text{Int}). \lambda x. (x, 1)$$

in F_i will be translated into System F’s:

$$\Lambda \alpha. \lambda x. (x, 1)$$

The translation judgement. The translation judgement $\Gamma \vdash e : A \hookrightarrow E$ extends the typing judgement with an elaborated term on the right hand side of \hookrightarrow . The translation ensures that E has type $|A|$. The two rules for type abstraction (T-BLAM) and type application (T-TAPP) generate the expected corresponding coercions in System F. The coercions generated for T-REC and T-PROJR simply erase the labels and translate the corresponding underlying term. All the remaining rules are ported from λ_i . However, it may be noteworthy pointing out that, as usual, the rule T-MERGE translates merges into pairs.

Type-safety The type-directed translation is type-safe. This property is captured by the following two theorems.

Theorem 1 (Type preservation). *We have that:*

- If $\Gamma \vdash e \Rightarrow A \hookrightarrow E$, then $|\Gamma| \vdash E : |A|$.
- If $\Gamma \vdash e \Leftarrow A \hookrightarrow E$, then $|\Gamma| \vdash E : |A|$.

Proof. By structural induction on the term and the corresponding inference rule.

Theorem 2 (Type safety). *If e is a well-typed F_i term, then e evaluates to some System F value v .*

Proof. Since we define the dynamic semantics of F_i in terms of the composition of the type-directed translation and the dynamic semantics of System F, type safety follows immediately.

Uniqueness of type-inference An important property of the bidirectional type-checking is that, given an expression e , if it is possible to infer a type for it, then e has a unique type.

Theorem 3 (Uniqueness of type-inference). *We have that:*

- If $\Gamma \vdash e \Rightarrow A_1 \hookrightarrow E_1$ and $\Gamma \vdash e \Rightarrow A_2 \hookrightarrow E_2$, then $A_1 = A_2$.

Proof. By structural induction on the term and the corresponding inference rule.

Coherency of Elaboration Combining the previous results, we are finally able to show the central theorem:

Theorem 4 (Unique elaboration). *We have that:*

- If $\Gamma \vdash e \Rightarrow A \hookrightarrow E_1$ and $\Gamma \vdash e \Rightarrow A \hookrightarrow E_2$, then $E_1 \equiv E_2$.
- If $\Gamma \vdash e \Leftarrow A \hookrightarrow E_1$ and $\Gamma \vdash e \Leftarrow A \hookrightarrow E_2$, then $E_1 \equiv E_2$.

(“ \equiv ” means syntactical equality, up to α -equality.)

Proof. By induction on the first derivation. The most important case is the subsumption rule:

$$\frac{\Gamma \vdash e \Rightarrow A \hookrightarrow E \quad A <: B \hookrightarrow E_{\text{sub}}}{\Gamma \vdash e \Leftarrow B \hookrightarrow E_{\text{sub}} E} \text{ T-SUB}$$

We need to show that E_{sub} is unique (by Lemma 10), and thus to show that A is well-formed (by Lemma 7). Note that this is the place where stability of substitutions (used by Lemma 7) plays a crucial role in guaranteeing coherence. We also need to show that A is unique (by Theorem 3). Uniqueness of A is needed to apply the induction hypothesis.

7 Related Work

Intersection types, polymorphism and the merge operator. To our knowledge no previous work has been done in a calculus which includes parametric polymorphism, intersection types and a merge operator.

JOAO: maybe these 3 paragraphs can go, as they aren't referring polymorphic systems? Concerning simply-typed systems, the oldest work dates back to the 1980s, when Reynolds invented Forsythe [45], with his merge-like operator being noted as p_1, p_2 . Even though his calculus was proven to be coherent [44], it uses a form of biased choice by having precedence in typing rules for intersections. His system is also arguably more restrictive than ours since it forbids, for instance, the merge of two functions.

Pierce [37] made a comprehensive review of coherence, but he was unable to prove it for his F_{\wedge} calculus. He introduced a primitive **glue** function as a language extension which corresponds to our merge operator. However, users can “glue” two arbitrary values, which may lead to incoherence.

Castagna et al. [14] proposed $\lambda\&$ to study the overloading problem for functions. They have a special merge for functions and also a special function application for these merges. Their calculus is coherent and they also employ well-formedness conditions on their (functional) merges. These conditions are incompatible with systems like ours – which allow arbitrary intersections – and thus are hard to compare in terms of expressiveness. This means that $\lambda\&$ accepts different functional merges than F_i and vice-versa.

More recently, Dunfield [23] formalised a system with intersection types and a merge operator with a type-directed translation to the simply-typed lambda calculus with pairs. The major differences to our calculus (besides being simply-typed), is that on one hand his system includes union types, but on the other it lacks coherence.

Our work is an extension of the recent λ_i calculus [46]. λ_i solves the coherence problem present in Dunfield’s calculus, by requiring that intersection types can only be composed of *disjoint* types. For simplicity purposes, λ_i uses a specification for disjointness, which says that two types are disjoint as long as they do not share a common supertype. F_i does not use such definition as its adaptation to polymorphic types would require using some form of unification. We opted to omit the specification from F_i , on grounds that unification would defeat the purpose of having such specification. In fact, F_i ’s notion of disjointness is based on λ_i ’s definition of the more general notion of disjointness concerning \top types, called \top -disjointness, which states that two types A and B are disjoint if two conditions are satisfied:

1. (not $\top A$) and (not $\top B$)
2. $\forall C$. if $A <: C$ and $B <: C$ then $\top C$

A major difference between the two calculus, is that \top -disjointness does not allow \top in intersections, while our calculus allows it. In other words, condition (1) is not imposed by F_i . As a consequence, the set of well-formed *top-like* types is a superset of λ_i ’s. This is covered in greater detail in Section 6.

Intersection types and polymorphism, without the merge operator. Recently, Castagna *et al.* [16] studied a very interesting and coherent calculus that has polymorphism and set-theoretic type connectives (such as intersections, unions, and negations). However, their calculus is based on a semantic subtyping relation due to their interpretation of intersection types. The difference to our calculus, is that their intersections are used between function types, allowing overloading (i.e. branching) of types. For example, they can express a function whose domain is defined on any type, but executes different code depending on that type:

$$\lambda^{(\text{Int} \rightarrow \text{Bool}) \wedge (\alpha \setminus \text{Int} \rightarrow \alpha \setminus \text{Int})} x. (x \in \text{Int}) ? (x \bmod 2) = 0 : x$$

In our system we cannot express some of these intersections, namely the ones that do not have disjoint co-domains. However, F_i accepts other kind of intersections which are not possible to express in their calculus, as in merges of type $(\text{Int} \rightarrow \text{Bool}) \& (\text{Int} \rightarrow \text{Int})$. Just as [14], their work is focused on combining intersections with functions, whereas F_i is concerned with merges between arbitrary types.

[JOAO: elaborate more on this paragraph?](#) Going in the direction of higher kinds, Compagnoni and Pierce [18] added intersection types to System F_ω and used a new calculus, F_ω^\wedge , to model multiple inheritance. In their system, types include the construct of intersection of types of the same kind K . Davies and Pfenning [21] studied the interactions between intersection types and effects

in call-by-value languages. They proposed a “value restriction” for intersection types, similar to value restriction on parametric polymorphism.

Intersection types have also been adopted in object-oriented languages such as Scala, Ceylon, Grace, Flow or TypeScript. Generally speaking, the main difference between these languages and F_i is the lack of explicit instantiation through the merge operator. This leads to several ad-hoc solutions at defining such operator in those languages, as it has been discussed in Section 1 and Section 3.1.

Extensible records. Encoding records using intersection types appeared in Reynolds [45] and Castagna et al. [15]. Although Dunfield also discussed this idea in his paper [23], he only provided an implementation but not a formalization. Very similar to our treatment of elaborating records is Cardelli’s work [11] on translating a calculus, named $F_{<:\rho}$, with extensible records to a simpler calculus without records primitives ($F_{<:}$). However, he does not encode multi-field records as intersections; hence his translation is more heavyweight. Crary [20] used intersection types and existential types to address the problem that arises when interpreting method dispatch as self-application. But in his paper, intersection types are not used to encode multi-field records.

Wand [48] started the work on extensible records and proposed row types [49] for records, together with a *concatenation* operator, which is standard in many calculi with extensible records [28,41,49,47,33,39]. Cardelli and Mitchell [13] defined three primitive operations on records that are standard in type-systems with record types: *selection*, *restriction*, and *extension*. Most calculi are based on these three primitive operators (especially extension), such as [42,27,30,31,32,9]. The merge operator in F_i plays the same role as the concatenation operator, as its components may contain any (well-formed and disjoint) types. One problem with concatenation is that typically systems are hard to use in practise, due to the complicated set of constraints/filters which might arise from combining several, possibly polymorphic, records [32]. However, in F_i , the implementation of records instead piggybacks on the disjointness and intersection types features of the type-system. The constraints on labels are encoded using disjoint quantification, and the coherent type-system will statically ensure that records and their operations are safe. This means that technical concerns, i.e type inference, efficiency, etc.; are to be dealt with the compilation of disjoint intersection types as opposed to compiling extensible records directly. Thus, what is expressed in other systems by means of row types, predicates, flags, qualified types, etc; in F_i it is expressed by the use of disjoint intersection types.

Traits and mixins. Traits [22,25,34] and mixins [10,6,26,24,5,8] have become very popular in object-oriented languages. They allow a kind of object composition which is not allowed in object-oriented type-systems with support for single inheritance. One of the main differences between traits and mixins are the way in which ambiguity of names is dealt. The former usually rejects programs which compose classes with conflicting methods, whereas the latter assumes a resolution strategy, usually language dependent. Our example demonstrated in Section 3 suggests that F_i can be used in place of traits, due to the semantics of

the merge operator. However there is a subtle difference between traits and F_i : equal names/labels are always rejected in the former, whereas in the latter only rejects when their types are disjoint. [JOAO](#): should we reference [CZ](#), where they have a similar spec to our notion of disjointness?

8 Conclusion and Future Work

This paper described F_i : a System F-based language that combines intersection types, parametric polymorphism and a merge operator. The language is proved to be type-safe and coherent. To ensure coherence the type system accepts only disjoint intersections. To provide flexibility in the presence of parametric polymorphism, universal quantification is extended with disjointness constraints. We believe that disjoint intersection types and disjoint quantification are intuitive, and at the same time expressive.

For the future, we intend to improve our source language and show the power of disjoint intersection types and disjoint quantification in large case studies. We are also interested in extending our work to systems with union types and/or a \perp type. While introducing the former should not be a major problem, introducing the latter imposes a serious issue in our system. Had F_i include the \perp type, non-sensical constructs such as $\Gamma \vdash \alpha * \alpha$ could be derived. It turns out the well-formedness conditions imposed on environments are not strong enough for this purpose. However, since introducing \perp was not strictly necessary to the system's formalization; adds substantial complexity in our system; and its practical application is not clear; we leave it as an open problem.

References

1. Ceylon, <https://ceylon-lang.org/>
2. The Coq Proof Assistant, <https://coq.inria.fr/>
3. Flow, <https://flowtype.org/>
4. TypeScript, <https://www.typescriptlang.org/>
5. Ancona, D., Lagorio, G., Zucca, E.: Jam—designing a java extension with mixins. *ACM Trans. Program. Lang. Syst.* 25(5), 641–712 (Sep 2003), <http://doi.acm.org/10.1145/937563.937567>
6. Ancona, D., Zucca, E.: An algebraic approach to mixins and modularity. In: *ALP '96 - 5th Intl. Conf. on Algebraic and Logic Programming*, number 1139 in *Lecture Notes in Computer Science*. pp. 179–193. Springer Verlag (1996)
7. Aydemir, B.E., Charguéraud, A., Pierce, B.C., Pollack, R., Weirich, S.: Engineering formal metatheory. In: Necula, G.C., Wadler, P. (eds.) *Proceeding of the 35th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL)*. pp. 3–15. ACM (2008)
8. Bettini, L., Bono, V., Likavec, S.: A Core Calculus of Higher-Order Mixins and Classes, pp. 83–98. Springer Berlin Heidelberg, Berlin, Heidelberg (2004)
9. Blume, M., Acar, U.A., Chae, W.: Extensible programming with first-class cases. In: *Proceedings of the 11th ACM SIGPLAN International Conference on Functional Programming, ICFP 2006, Portland, Oregon, USA, September 16-21, 2006*. pp. 239–250 (2006)
10. Bracha, G., Cook, W.: Mixin-based inheritance. In: *Proc. OOPSLA'90* (1990)
11. Cardelli, L.: Extensible records in a pure calculus of subtyping. *Digital. Systems Research Center* (1992)
12. Cardelli, L., Martini, S., Mitchell, J.C., Scedrov, A.: An extension of system f with subtyping. *Inf. Comput.* 109(1-2) (Feb 1994)
13. Cardelli, L., Mitchell, J.C.: Operations on records. In: *Mathematical foundations of programming semantics* (1990)
14. Castagna, G., Ghelli, G., Longo, G.: A calculus for overloaded functions with subtyping. In: *Proceedings of the 1992 ACM Conference on LISP and Functional Programming. LFP '92* (1992)
15. Castagna, G., Ghelli, G., Longo, G.: A calculus for overloaded functions with subtyping. *Information and Computation* (1995)
16. Castagna, G., Nguyen, K., Xu, Z., Im, H., Lenglet, S., Padovani, L.: Polymorphic functions with set-theoretic types: Part 1: Syntax, semantics, and evaluation. In: *Proceedings of the 41st ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages. POPL '14* (2014)
17. Compagnoni, A.B., Pierce, B.C.: Higher-order intersection types and multiple inheritance. *Math. Structures Comput. Sci.* 6(5), 469–501 (1996)
18. Compagnoni, A.B., Pierce, B.C.: Higher-order intersection types and multiple inheritance. *Mathematical Structures in Computer Science* (1996)
19. Coppo, M., Dezani-Ciancaglini, M., Venneri, B.: Functional characters of solvable terms. *Mathematical Logic Quarterly* 27(2–6), 45–58 (1981)
20. Crary, K.: Simple, efficient object encoding using intersection types. Tech. rep., Cornell University (1998)
21. Davies, R., Pfenning, F.: Intersection types and computational effects. In: *Proceedings of the Fifth ACM SIGPLAN International Conference on Functional Programming (ICFP'00)* (2000)

22. Ducasse, S., Nierstrasz, O., Schärli, N., Wuyts, R., Black, A.P.: Traits: A mechanism for fine-grained reuse. *ACM Trans. Program. Lang. Syst.* 28(2), 331–388 (Mar 2006), <http://doi.acm.org/10.1145/1119479.1119483>
23. Dunfield, J.: Elaborating intersection and union types. *Journal of Functional Programming* (2014)
24. Findler, R.B., Flatt, M.: Modular object-oriented programming with units and mixins. *SIGPLAN Not.* 34(1), 94–104 (Sep 1998)
25. Fisher, K.: A typed calculus of traits. In: In FOOL11 (2004)
26. Flatt, M., Krishnamurthi, S., Felleisen, M.: Classes and mixins. In: *Proceedings of the 25th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*. pp. 171–183. POPL ’98, ACM, New York, NY, USA (1998)
27. Gaster, B.R., Jones, M.P.: A polymorphic type system for extensible records and variants. Tech. rep., University of Nottingham (1996)
28. Harper, R., Pierce, B.: A record calculus based on symmetric concatenation. In: *Proceedings of the 18th ACM SIGPLAN-SIGACT symposium on Principles of programming languages*. ACM (1991)
29. Harper, R.W., Pierce, B.C.: Extensible records without subsumption (1990)
30. Jones, M., Jones, S.: Lightweight extensible records for haskell (1999)
31. Leijen, D.: First-class labels for extensible rows. UU-CS (2004-051) (2004)
32. Leijen, D.: Extensible records with scoped labels. *Trends in Functional Programming* (2005)
33. Makhholm, H., Wells, J.B.: Type inference, principal typings, and let-polymorphism for first-class mixin modules. In: *Proceedings of the 10th ACM SIGPLAN International Conference on Functional Programming, ICFP 2005, Tallinn, Estonia, September 26-28, 2005*. pp. 156–167 (2005)
34. Odersky, M., Zenger, M.: Scalable component abstractions. In: *Proceedings of the 20th Annual ACM SIGPLAN Conference on Object-oriented Programming, Systems, Languages, and Applications*. pp. 41–57. OOPSLA ’05, ACM, New York, NY, USA (2005), <http://doi.acm.org/10.1145/1094811.1094815>
35. Odersky, M., et al.: An overview of the Scala programming language. Tech. Rep. IC/2004/64, EPFL Lausanne, Switzerland (2004)
36. Oliveira, B.C.d.S., Van Der Storm, T., Loh, A., Cook, W.R.: Feature-oriented programming with object algebras. In: *ECOOP 2013–Object-Oriented Programming* (2013)
37. Pierce, B.C.: Programming with Intersection Types and Bounded Polymorphism. Ph.D. thesis, Carnegie Mellon University (December 1991)
38. Pierce, B.C., Turner, D.N.: Simple type-theoretic foundations for object-oriented programming. *J. Funct. Program.* 4(2), 207–247 (1994)
39. Pottier, F.: A constraint-based presentation and generalization of rows. In: *Proceedings of the Eighteenth Annual IEEE Symposium on Logic in Computer Science (LICS 2003)*. pp. 331–340. IEEE Computer Society Press (June 2003)
40. Pottinger, G.: A type assignment for the strongly normalizable λ -terms. In: To H. B. Curry: essays on combinatory logic, lambda calculus and formalism. pp. 561–577. Academic Press, London (1980)
41. Rémy, D.: Typing record concatenation for free. In: *Conference Record of the Nineteenth Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, Albuquerque, New Mexico, USA, January 19-22, 1992*. pp. 166–176 (1992)
42. Rémy, D.: Type inference for records in a natural extension of ML. *Theoretical Aspects Of Object-Oriented Programming. Types, Semantics and Language Design*. MIT Press (1993)

- 43. Rendel, T., Brachthäuser, J.I., Ostermann, K.: From object algebras to attribute grammars. In: Proceedings of the 2014 ACM International Conference on Object Oriented Programming Systems Languages & Applications. pp. 377–395. OOPSLA '14 (2014)
- 44. Reynolds, J.C.: The coherence of languages with intersection types. In: Proceedings of the International Conference on Theoretical Aspects of Computer Software. TACS '91 (1991)
- 45. Reynolds, J.C.: Design of the Programming Language Forsythe, pp. 173–233. Birkhäuser Boston, Boston, MA (1997)
- 46. d. S. Oliveira, B.C., Shi, Z., Alpuim, J.: Disjoint intersection types. In: Proceedings of the 21st ACM SIGPLAN International Conference on Functional Programming, ICFP 2016, Nara, Japan, September 18–22, 2016. pp. 364–377 (2016)
- 47. Sulzmann, M.: Designing record systems. Tech. rep., Yale University (1997)
- 48. Wand, M.: Complete type inference for simple objects. In: LICS (1987)
- 49. Wand, M.: Type inference for record concatenation and multiple inheritance. In: Logic in Computer Science, 1989. LICS'89, Proceedings., Fourth Annual Symposium on. IEEE (1989)