



# Novel Classifier for Smart Traffic Network

Submitted June 2020, in partial fulfillment of  
the conditions for the award of the degree **Bachelor of Computer  
Engineering/Computer Science.**

**Thomas Courtney**

**3175353**

**Supervised by Assoc. Prof. Kaushik Mahata**

School of Engineering

University of Newcastle

I hereby declare that this dissertation is all my own work, except as indicated in the  
text:

Signature \_\_\_\_\_

Date \_\_\_\_ / \_\_\_\_ / \_\_\_\_



# Contents

<b>1</b>	<b>Literature Review</b>	<b>1</b>
1.1	Digital Images . . . . .	1
1.2	Linear Filtering . . . . .	3
1.2.1	Correlation . . . . .	4
1.2.2	Convolution . . . . .	6
1.3	The Gaussian . . . . .	7
1.4	Clustering . . . . .	9
1.4.1	K-Means . . . . .	10
1.4.2	Mixtures of Gaussians . . . . .	11
1.4.3	Background Subtraction . . . . .	15
1.4.4	Expectation Maximization . . . . .	16
<b>2</b>	<b>Design</b>	<b>17</b>
	<b>Bibliography</b>	<b>17</b>



# List of Tables



# List of Figures

1.1	(a) A Simple 8-bit Image (b) Array Representation of Image. . . . .	2
1.2	Surface Plot of Figure 1.1a . . . . .	2
1.3	General Form of a Linear Filter . . . . .	3
1.4	Visualization of a Filter Kernel Application . . . . .	3
1.5	Box Filter application and kernel. . . . .	4
1.6	Sobel Filters . . . . .	5
1.7	Application of Sobel filters to exaggerate lines. . . . .	5
1.8	Correlation of a filter and an image. . . . .	6
1.9	Convolution of a filter and an image. . . . .	7
1.10	The Gaussian Function in 2D with $\mu=0$ , $\sigma=0.2$ and $A = 2$ . . . . .	8
1.11	The Gaussian Function in 1D with $\mu=0$ , $\sigma=0.2$ and $A = 2$ . . . . .	8
1.12	Segmentation of toy cars using K-Means Clustering. . . . .	9
1.13	K-Means clustering performed on random data. . . . .	11
1.14	Formulation of Mixture of Gaussians. . . . .	12

1.15 Clustering using GMM. . . . .	13
1.16 Individual Gaussians with scaled weightings. . . . .	14



# Chapter 1

## Literature Review

This section of the report expands upon the theory behind the design of the system. Digital image processing and computer vision are broad fields and so only concepts relevant to the system are explored.

### 1.1 Digital Images

Digital images consists of a discrete number of discrete valued data points called pixels. It is the value of these pixels that determine their color. A pixel's value is also called its *intensity* and will lie within a range of values determined by the image's encoding. For example an 8-bit image has pixel values in the range  $[0, 255]$ .

Digital images are often represented as a 2D array of values where each cell corresponds to an intensity. In software in particular, digital images are stored and manipulated as arrays. An image's array is  $M \times N$  pixels in size, which is also its resolution. Notice that in Figure 1.1 the lowest value is 0 (black) and the highest value is 255 (white). All other colors that can be represented by 8-bits are between these two values.




Figure 1.1: (a) A Simple 8-bit Image (b) Array Representation of Image.

2D array representation allows pixels to be referenced by their relative position in the  $M$  and  $N$  directions. Furthermore,  $M$  and  $N$  may be substituted for the  $x$  and  $y$  axes of the Cartesian plane. In fact, a digital image is just a two dimensional function where each pixel is described by a coordinate  $(x,y)$  and an intensity  $(z)$  at that point.

$$z = f(x, y) \quad (1.1)$$

This means that two dimensional operations may be applied to a digital image and images may be modelled as 3D surfaces. Modelling images as a surface is useful when trying to visualize rates of change in an image. In Figure 1.1 you can see that there is a rapid change in value between different coloured squares, shown as steep cliff edges.




Figure 1.2: Surface Plot of Figure 1.1a

## 1.2 Linear Filtering

Filtering an image is a way to augment or extract information from it. Linear filters are a subset of operations that operate on a neighbourhood of pixels in an image. All linear filters operate on the same principal, that is, they output a weighted average of their input. Filters take pixels in the neighbourhood covered by the filter as input. It is the weightings of a filter, known as filter coefficients, that determine the effect of the filter. These weights are stored in a matrix called a mask or kernel (see Figure 1.3) that's then convolved or correlated with an image (see sections 1.2.1 & 1.2.2).

$$Kernel = \frac{1}{\sum_{i=0}^M \sum_{j=0}^N c_{i,j}} \begin{bmatrix} c_{0,0} & c_{0,1} & \dots & c_{0,n} \\ c_{1,0} & c_{1,1} & \dots & c_{1,n} \\ \vdots & \vdots & \ddots & \vdots \\ c_{m,0} & c_{m,1} & \dots & c_{m,n} \end{bmatrix}$$

Figure 1.3: General Form of a Linear Filter

A filter kernel is nearly always square so as to have a center cell which sits atop a reference pixel. The result of the filter's application at that reference pixel will be stored in the output image at the location of the reference pixel. Notice in Figure 1.4 how the mask sits over the reference pixel.




Figure 1.4: Visualization of a Filter Kernel Application

A 'box filter', for example, outputs the average of its inputs because the filter weights are evenly distributed. By passing this filter over an image its sharpness is reduced giving a smoothing or blurring effect. This can be observed in Figure 1.5a.



(a) Left: Photo by Charles Deluvio. Right: Application of  $16 \times 16$  box filter.

$$\frac{1}{9} \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix}$$

(b) Box Filter Kernel.

Figure 1.5: Box Filter application and kernel.

### 1.2.1 Correlation

The application of a linear filter  $h(u, v)$  to an image  $f(i, j)$  may be described as follows

$$g(i, j) = \sum_{u=-k}^k \sum_{v=-l}^l f(i+u, j+v)h(u, v) \quad (1.2)$$

$g(i, j)$  is the output image. Performing correlation with a filter may be notated more concisely by the correlation operator.

$$g = f \otimes h$$

Correlation measures the similarity between two signals. Both digital images and linear filters are two dimensional signals. Performing correlation between them will yield an output image where the highest values correspond to where the image and filter were most similar [1]. This is useful because if you wish to emphasise a feature in an image it can be done by correlating it with a filter that describes that feature. For example, if you wished to exaggerate vertical and horizontal lines you could use Sobel filters as in 1.6.

$$\begin{bmatrix} -1 & -1 & -1 \\ 2 & 2 & 2 \\ -1 & -1 & -1 \end{bmatrix}$$


(a) Horizontal Sobel Filter Mask

$$\begin{bmatrix} -1 & 2 & -1 \\ -1 & 2 & -1 \\ -1 & 2 & -1 \end{bmatrix}$$

(b) Vertical Sobel Filter Mask

Figure 1.6: Sobel Filters

The use of negative weightings means that values next to an edge are diminished and the positively weighted line sections (the 2s) strengthen line features. Notice in figure 1.7 how the lines have a high values (white) and regions that aren't lines are low valued (black).



(a) Image by Simone Hutsch

(b) Vertical Sobel Filter

(c) Horizontal Sobel Filter

Figure 1.7: Application of Sobel filters to exaggerate lines.

Correlation is *shift invariant*, which means that it does the same thing no matter where in an image it is applied. To satisfy this property correlation may be superpositioned

$$a(f_1 + f_2) = af_1 + af_2$$

and abides by the shift invariance principle

$$g(i, j) = f(i + k, j + l) \Leftrightarrow (h \circ g)(i, j) = (h \circ f)(i + k, j + l)$$

Correlation has the side effect of flipping both horizontally and vertically the location of output points relative to location the center point (*reference point*) in the original image which may be undesirable.

0	0	0	0	0	$\otimes$	a	b	c	$=$	0	0	0	0	0
0	0	0	0	0		d	e	f		0	<b>i</b>	<b>h</b>	<b>g</b>	0
0	0	1	0	0		g	h	i		0	<b>f</b>	<b>e</b>	<b>d</b>	0
0	0	0	0	0						0	<b>c</b>	<b>b</b>	<b>a</b>	0
0	0	0	0	0						0	0	0	0	0
$F(x, y)$						$H(u, v)$				$G(x, y)$				

Figure 1.8: Correlation of a filter and an image.

### 1.2.2 Convolution

Convolution is also a linear operation that is shift invariant. It is very similar to correlation except that where correlation measure similarity between signals convolution measures the effect of one signal on another. It is described mathematically by the expression,

$$g(i, j) = \sum_{u=-k}^k \sum_{v=-l}^l f(u, v) h(i - u, j - v)$$

Notice that the filter  $h(i, j)$  is rotated 180 degrees. This causes the output's orientation to match the original image. Convolution may be notated as follows,

$$g = f * h$$

0	0	0	0	0	*	a	b	c	=	0	0	0	0	0
0	0	0	0	0		0	<b>a</b>	<b>b</b>		<b>c</b>	0			
0	0	1	0	0		d	e	f		0	<b>d</b>	<b>e</b>	<b>f</b>	0
0	0	0	0	0		g	h	i		0	<b>g</b>	<b>h</b>	<b>i</b>	0
0	0	0	0	0		0	0	0		0	0			
$F(x, y)$						$H(u, v)$				$G(x, y)$				

Figure 1.9: Convolution of a filter and an image.

## 1.3 The Gaussian

The Gaussian provides a consistent model for normal distributions, aka the bell curve, as in Figure 1.10 & 1.11. Normal distributions follow the *central limit theorem* where in if a histogram is taken of a sufficiently large number of independent random variables they will distribute with a central most probable value and symmetrically fall away either side of this value. Many datasets follow this trend closely enough that the Gaussian can be used to approximate a probability distribution for them.

The Gaussian function is defined by three parameters, its mean  $\mu$ , standard deviation  $\sigma$  and amplitude  $A$ .




Figure 1.10: The Gaussian Function in 2D with  $\mu=0$ ,  $\sigma=0.2$  and  $A = 2$ .




Figure 1.11: The Gaussian Function in 1D with  $\mu=0$ ,  $\sigma=0.2$  and  $A = 2$ .

The general one dimensional Gaussian is described:

$$f(x) = \frac{A}{\sigma\sqrt{2\pi}} e^{-\frac{1}{2}\left(\frac{x-\mu}{\sigma}\right)^2} \quad (1.3)$$

The mean value, the central limit, of the sample distribution is the value that has the greatest likelihood<sup>1</sup> in the distribution. The standard deviation is how much the distribution is spread out, the greater the standard deviation the fatter the distribution. The

---

<sup>1</sup>Likelihood is the value of the distribution given a fixed sample. Probability is the value of a sample given a fixed distribution.



amplitude is the likelihood at the mean of the distribution. In Figure 1.10, for example, the likelihood of a value being 0 is 2. Generally, the curve is used to determine a sample's probability density within a value range. This is the area under the distribution given an interval and is calculated using integration, as shown in 1.4.

$$P(x) = \int_a^b \frac{A}{\sigma\sqrt{2\pi}} e^{-\frac{1}{2}\left(\frac{x-\mu}{\sigma}\right)^2} dx \quad (1.4)$$

Data sets can have many dimensions and distributions need to be able to express all of them. The notation for a multi-variate Gaussian distribution, for a k-dimensional random vector  $\mathbf{X} = (X_1, \dots, X_k)^T$ , is

$$\mathbf{X} \sim \mathcal{N}_k(\mu, \sigma^2) \quad (1.5)$$

## 1.4 Clustering

Clustering is a method of segmenting an image into disjoint sets known as classes. This is useful for separating types of features or objects in an image. For example in Figure 1.12 the toy car has been segmented from the background.



(a) Image by Gustavo, Upsplash.

(b) Segmentation of car from background.

Figure 1.12: Segmentation of toy cars using K-Means Clustering.

In an image every pixel can be individually classified or groups of pixels known as super-pixels may be treated as single entities. Entities are sorted based on their similarity. For example, a pixel's intensity is a feature that could be used to cluster it with other pixels of similar intensity. As seen in (1.6) an entity's comparable traits may be represented by a feature vector. An entity may have any number of features which as also regarded as dimensions,  $d$ .

$$\vec{v} = \begin{bmatrix} d_1 \\ d_2 \\ \vdots \\ d_n \end{bmatrix} \quad (1.6)$$

### 1.4.1 K-Means

There are many methods by which to cluster, K-Means is a popular method due to its speed and simplicity. Data points are sorted into one of K clusters where the average value of the cluster is stored in a central data point known as the cluster centroid. Centroids may initially be randomly generated or selected from the given data set.

Data points or samples are placed in the class of the centroid that is closest to them. The distance between them is the Euclidean Distance between their feature vectors as in 1.7.

$$D(\vec{p}, \vec{q}) = \sqrt{(p_1 - q_1)^2 + (p_2 - q_2)^2 + \dots + (p_n - q_n)^2} \quad (1.7)$$

K-Mean's algorithm proceeds as follows:

1. Place the initial K centroids.
2. Assign all data points to their nearest centroid.
3. Update the centroids' values to be the mean of all data points in their cluster.

4. Repeat steps 2 and 3 until a criteria is met, for example until cluster centroids no longer move (converge).

K-means benefits greatly from its low computational cost such that it is often performed a number of times with different initial centroids and the instance best result is used. The best result is defined as having the smallest intracluster variance. K-Means is disadvantaged by the implicit trait that it formulates clusters of similar sizes. This happens because the algorithm seeks to minimize variance (spread) in each cluster hence the ‘ideal’ centroid placement will form distributions spherically about centroids. This method cannot disentangle overlapping samples that belong in different classes. In Figure 1.13 clear edges between clusters and spherical distributions can be observed. The algorithm can only implement *hard assignments*, as opposed to a *soft assignment* that consider the probability of a sample’s class membership.




Figure 1.13: K-Means clustering performed on random data.

### 1.4.2 Mixtures of Gaussians

Mixtures of Gaussian or the Gaussian Mixture Model (GMM) is a method of clustering data that’s able to disentangle ambiguous samples by considering a sample’s probability

of belonging to a class, known as a soft assignment.

Initially,  $K$  Gaussian functions are randomly generated corresponding to  $K$  clusters. If a dataset has low dimensionality, by taking a histogram of its values the Gaussian's initial conditions can be approximated, as in Figure 1.14. By superpositioning all of the Gaussians a sample's complete probabilistic model is created, i.e. a model for *all* clusters.




Figure 1.14: Formulation of Mixture of Gaussians.

With each iteration of the GMM algorithm the parameters of the model's component Gaussians are tuned according to the covariance (1.8) between samples in each cluster.  $X$  and  $Y$  are the variables being compared,  $\bar{X}$  and  $\bar{Y}$  are variable means and  $n$  is the number of samples. For a multidimensional dataset this results in a covariance matrix  $\Sigma_k$  for each Gaussian, furthermore a multidimensional Gaussian requires also a mean vector  $\mu_k$  as opposed to scalar.

$$Cov(X, Y) = \frac{\sum (X_i - \bar{X})(Y_j - \bar{Y})}{n} \quad (1.8)$$

The algorithm seeks the highest covariance possible in each of its clusters. It is by considering the covariance of samples that the GMM is able to best classify ambiguous samples. The higher the covariance (aka correlation) between sample dimensions the more likely it is they belong in the same cluster. This can be observed in Figure 1.15, the data being

clustered is the same as in Figure 1.13 but notice the elliptical shape of the Gaussian cluster distributions as opposed to the spherical shape of K-Means clustering.




Figure 1.15: Clustering using GMM.

Within the complete mixture model the probability a sample belongs in one of them is 100%. In Figure 1.16 the Gaussians from Figure 1.14b have been scaled to have the amplitudes  $\pi_1 = 0.3$ ,  $\pi_2 = 0.5$  and  $\pi_3 = 0.2$ . These are weightings that give the mixing ratio of the model and represent a cluster's proportion of the total samples. The more samples a cluster contains the more likely it is a sample belongs to it. The sum of ratios must add to one because the probability a sample belongs to at least one cluster is one, as defined in 1.9 and 1.10.

$$0 \leq \pi_k \leq 1 \quad (1.9)$$

$$\sum_{k=1}^K \pi_k = 1 \quad (1.10)$$




Figure 1.16: Individual Gaussians with scaled weightings.

Each Gaussian's three parameters, mean  $\mu_k$ , amplitude  $\pi_k$  and covariance matrix  $\Sigma_k$  are updated following each iteration of the algorithm. These augmentations are performed according to 'Expectation Maximization'.

## Expectation Maximization

Expectation Maximization (EM) is a method by which to update the parameters of the Gaussian distributions that seeks to maximize a sample's likelihood of belonging to a cluster.

EM will compute the a sample's probability of being in a cluster. This value will be used to reestimate the Gaussian probability to better fit the data that is presented by trying to maximizing all sample's probabilities of belonging in a cluster.

The reajustment of the mean of each Gaussian receives weighting from all points proportional to their probability of belonging to that Gaussian's cluster.

The algorithm is comprised of two steps

1. The *expectation* step estimates the probability the sample  $x_i$  belongs to Gaussian cluster  $k$ .

$$z_{ik} = \frac{1}{Z_i} \pi_k \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k) \quad (1.11)$$

2. The *maximization* step aguments the Gaussian parameter values.

$$\boldsymbol{\mu}_k = \frac{1}{N_k} \sum_i z_i \mathbf{x}_i \quad (\text{eqn1})$$

$$\boldsymbol{\Sigma}_k = \frac{1}{N_k} \sum_i z_{ik} (\mathbf{x}_i - \boldsymbol{\mu}_k)(\mathbf{x}_i - \boldsymbol{\mu}_k)^T \quad (\text{eqn2})$$

$$\pi_k = \frac{N_k}{N} \quad (\text{eqn3})$$

where

$$N_k = \sum_i z_{ik}$$

A cluster indicator  $z_i$  exists for every sample, it is the *probability* that the  $i$ th sample is associated with the  $k$ th cluster. It is completely specified by the mixture weight  $\pi_k$ . I.e.

$$p(z_i = k) = \pi_k$$

If we know that a sample  $x_i$  is from cluster  $k$  the *likelihood* of seeing it in Gaussian associated with that cluster is

$$p(x_i | z_i = k, \mu_k, \Sigma_k) = \mathcal{N}(x_i | \mu_k, \Sigma_k)$$

for each cluster such that a sample's likelihood of belonging to each cluster is maximized.

### 1.4.3 Background Subtraction

This is performed by identifying a background image and then subtracting this image from subsequent frames of video to determine what has changed and hence what is a

foreground image.

#### **1.4.4 Expectation Maximization**

This is an optimization scheme used to fit a Gaussian Mixture Model. It is an iterative method that guarantees convergence to a local maximum in a search space.



# Chapter 2

## Design

The design of the system is compromised of a number of submodules.

[ Insert Block Diagram of Submodules Comprising Whole System ]

[ Then Breakdown Each Submodule ]

[ Why was a CNN not used? ]

# Bibliography

- [1] Sabyasachi Sahoo. Deciding optimal kernel size for cnn.