

# SIMULTANEOUS ELICITATION OF COMMITTEE AND VOTERS PREFERENCES

B. Napolitano<sup>1</sup>, O. Cailloux<sup>1</sup> and P. Viappiani<sup>2</sup>

<sup>1</sup> LAMSADE, Université Paris-Dauphine, Paris, France

<sup>2</sup> LIP6, Sorbonne Université, Paris, France

## Setting


### Incomplete profile and uncertain positional scoring rule

(Head of the)  
**Committee**

$w_1 > w_2 \geq w_3$   
 $\parallel$   
1                      0

**Voters**

Alice Bob Carl



### Goals

- Development of query strategies interleaving questions to the chair and to the voters in order to simultaneously elicit preferences and voting rule
- Robust winner determination

## Motivation and approach

### • Who?

- Imagine to be an *external observer* helping with the voting procedure

### • Why?

- Requiring voters to express *full preference* orderings can be prohibitively *costly*, especially for decisions with lots of alternatives
- *Difficult* for non-expert users *to formalize* a voting rule on the basis of some generic preferences over a desired aggregation method

### • How?

- *Minimax regret*: given the current knowledge, the alternatives with the lowest worst-case regret are selected as tied winners

### • Assumptions:

- Voters and committee have true preferences in mind
- The voting rule is a Positional Scoring Rule where the scoring vector  $(w_1, \dots, w_m)$  is a convex sequence of weights and  $w_1 = 1, w_m = 0$

## Minimax Regret

$$\begin{aligned} \text{Regret}^{v,w}(x) &= \max_{y \in A} s^{v,w}(y) - s^{v,w}(x) \\ \text{PMR}^{p,W}(x, y) &= \max_{w \in W} \max_{v \in C(p)} s^{v,w}(y) - s^{v,w}(x) \\ \text{MR}^{p,W}(x) &= \max_{y \in A} \text{PMR}^{p,W}(x, y) \\ \text{MMR}(p, W) &= \min_{x \in A} \text{MR}^{p,W}(x) \\ x_{p,W}^* \in A_{p,W}^* &= \arg \min_{x \in A} \text{MR}^{p,W}(x) \end{aligned}$$

## Pairwise Max Regret Computation


The computation of  $\text{PMR}^{p,W}(x, y)$  can be seen as a game in which an adversary can both extend the partial profile into a complete one and instantiate the weights choosing among any feasible weight vector

### • Profile Completion

For any other alternative  $a$

$$\begin{aligned} a \succ_j x &\Leftrightarrow \neg(x \succeq_j^p a) \\ y \succ_j a &\Leftrightarrow \neg(a \succeq_j^p y) \wedge \neg((x \succeq_j^p y) \wedge \neg(x \succeq_j^p a)). \end{aligned}$$

Considering the example



### • Weights Choice

The vector that satisfies the constraints specified by the chair so far and maximize the PMR is chosen.

In the previous example the vector  $(1, 0, 0)$  is chosen.

## Question Types

### • Questions to the voters

- Comparison queries that ask a particular agent to compare two alternatives

$$a \succ_j b \quad ?$$

### • Questions to the chair

- Queries relating the difference between the importance of consecutive ranks  $r$  and  $r+1$

$$w_r - w_{r+1} \geq \lambda(w_{r+1} - w_{r+2}) \quad ?$$

## Elicitation strategies

A function that, given our partial knowledge so far, returns a question that should be asked.

- **Random**: it decides, with a probability of  $1/2$ , whether to ask a question to the voters or to the chair, then it equiprobably draws a question among the set of the possible ones;
- **Extreme completions**: it asks a question to the chair or to the agents depending on which uncertainty contributes the most to the regret;
- **Pessimistic**: it selects the question that leads to minimal regret in the worst case considering, and aggregating, both possible answers to each question;
- **Two phase**: it asks a predefined, non adaptive sequence of  $m - 2$  questions to the chair and then it only asks questions about the agents.

## References

### References

- [1] Olivier Cailloux and Ulle Endriss. Eliciting a suitable voting rule via examples. In *ECAI 2014 - 21st European Conference on Artificial Intelligence, 18-22 August 2014, Prague, Czech Republic - Including Prestigious Applications of Intelligent Systems (PAIS 2014)*, pages 183–188, 2014.
- [2] Meir Kalech, Sarit Kraus, Gal A. Kaminka, and Claudia V. Goldman. Practical voting rules with partial information. *Autonomous Agents and Multi-Agent Systems*, 22(1):151–182, 2011.
- [3] Kathrin Konczak and Jerome Lang. Voting procedures with incomplete preferences. In *IJCAI Workshop on Advances in Preference Handling*, pages 124–129, 2005.
- [4] Tyler Lu and Craig Boutilier. Robust approximation and incremental elicitation in voting protocols. In *Proceedings of IJCAI 2011*, pages 287–293, 2011.
- [5] Paolo Viappiani. Positional scoring rules with uncertain weights. In *Scalable Uncertainty Management - 12th International Conference, SUM 2018, Milan, Italy, October 3-5, 2018, Proceedings*, pages 306–320, 2018.
- [6] Lirong Xia and Vincent Conitzer. Determining possible and necessary winners under common voting rules given partial orders. In *Proceedings of the Twenty-Third AAAI Conference on Artificial Intelligence, AAAI 2008, Chicago, Illinois, USA, July 13-17, 2008*, pages 196–201, 2008.