



Simultaneous Elicitation of Committee and Voters' Preferences

B. Napolitano¹, O. Cailloux¹ and P. Viappiani²


¹ LAMSADE, Université Paris-Dauphine, Paris, France ² LIP6, Sorbonne Université, Paris, France

International Summer School on Preferences, Decisions and Games 28 June 2019



Scenario

Setting: Incompletely specified profile and positional scoring rule



Goal: Development of an incremental elicitation protocol based on minimax regret

Motivation and approach

Who?

• Imagine to be an external observer helping with the voting procedure

Why?

- Voters: difficult or costly to order all alternatives
- Committee: difficult to specify a voting rule precisely and abstractly

How?

 Minimax regret: given the current knowledge, the alternatives with the lowest worst-case regret are selected as tied winners

Related Works

Incomplete profile

 and known weights: Minimax regret to produce a robust winner approximation (Lu and Boutilier 2011, [2]; Boutilier et al. 2006, [1])

Uncertain weights

- and complete profile: dominance relations derived to eliminate alternatives always less preferred than others (Stein et al. 1994, [3])
- in positional scoring rules (Viappiani 2018, [4])

Framework

|N|=n, |A|=m voters, alternatives $\succ_j^{\rm p}$ partial preference order of the voter $j\in N$ \mathcal{C}_W set of linear constraints given by the committee about $m{w}$

Given complete voters preferences v, a specific positional scoring rule, defined by a scoring vector w, attributes a score $s^{v,w}$ to each alternative

Framework

Assumptions

- Voters and committee have true preferences in mind
- The voting rule is a Positional Scoring Rule where the scoring vector $\mathbf{w} = (w_1, \dots, w_m)$ is a convex sequence of weights and $w_1 = 1$, $w_m = 0$

Minimax Regret

- $PMR^{p,W}(x, y)$ is the maximum difference of score between x and y under all possible realizations of the full profile and weights
 - $MR^{p,W}(x)$ represents the worst case loss: the *maximal regret* between a chosen alternative x and best real alternative y

We select the alternative which minimizes the maximal regret

Pairwise Max Regret Computation

The computation of $PMR^{p,W}(x,y)$ can be seen as a game in which an adversary can both

complete the partial profile



choose a feasible weight vector

(1, 0, 0)

in order to maximize the difference of scores

Question Types

Questions to the voters

Comparison queries that ask a particular voter to compare two alternatives

$$x \succ_j y$$
 ?

Questions to the committee

Queries relating the difference between the importance of consecutive ranks r and r+1

$$w_r - w_{r+1} \ge \lambda (w_{r+1} - w_{r+2})$$
 ?

Elicitation strategies

- Random: equiprobably draws a question among the set of the possible ones;
- Extreme completions: choses the question that reduces the most the uncertainty;
- Pessimistic: selects the question that leads to minimal regret in the worst case;
- **Two phase**: it asks a predefined sequence of questions to the committee and then it only asks questions about the voters.

Thank You!



C. Boutilier, R. Patrascu, P. Poupart, and D. Schuurmans. Constraint-based Optimization and Utility Elicitation using the Minimax Decision Criterion.

Artifical Intelligence, 170(8–9):686–713, 2006.



Tyler Lu and Craig Boutilier.

Robust approximation and incremental elicitation in voting protocols. In *Proceedings of IJCAI 2011*, pages 287–293, 2011.



William E. Stein, Philip J. Mizzi, and Roger C. Pfaffenberger. A stochastic dominance analysis of ranked voting systems with scoring.

European Journal of Operational Research, 74(1):78 – 85, 1994.



Paolo Viappiani.

Positional scoring rules with uncertain weights.

In Scalable Uncertainty Management - 12th International Conference, SUM 2018, Milan, Italy, October 3-5, 2018, Proceedings, pages 306-320, 2018,