

Simultaneous Elicitation of Committee and Voters' Preferences

B. Napolitano¹, O. Cailloux¹ and P. Viappiani²

¹ LAMSADE, Université Paris-Dauphine, Paris, France

² LIP6, Sorbonne Université, Paris, France

Advances in Economic Design : Games, voting, information and measurement

28 November 2019

LAMSADE

UMR CNRS 7243

laboratoire d'analyse et modélisation de systèmes pour l'aide à la décision

Classical Scenario

Setting: Voters specify preferences over alternatives and a committee defines the social choice rule to aggregate them

(Head of the)

Committee





$$w_1 > w_2 \geq w_3$$

$$\begin{matrix} \parallel \\ 1 \end{matrix} \qquad \begin{matrix} \parallel \\ 0 \end{matrix}$$

Voters


Mickey Donald Goofy



Classical Scenario



Setting: Voters specify preferences over alternatives and a committee defines the social choice rule to aggregate them

(Head of the)
Committee



Voters

Mickey Donald Goofy



Goal: Find a consensus choice

Our Scenario

Setting: Incompletely specified preferences and social choice rule

(Head of the)
Committee





$$w_1 > w_2 \geq w_3$$

$$\begin{array}{c} \parallel \\ 1 \end{array} \qquad \begin{array}{c} \parallel \\ 0 \end{array}$$

Voters

Mickey Donald Goofy



Our Scenario

Setting: Incompletely specified preferences and social choice rule

(Head of the)
Committee





$$w_1 > w_2 \geq w_3$$

$$\begin{array}{c} \parallel \\ 1 \end{array} \qquad \begin{array}{c} \parallel \\ 0 \end{array}$$

Voters

Mickey Donald Goofy



Goal: Develop an incremental elicitation strategy to acquire the most relevant information

Motivation and approach

Who?

- Imagine to be an *external observer* helping with the voting procedure

Motivation and approach

Who?

- Imagine to be an *external observer* helping with the voting procedure

Why?

- Voters: difficult or costly to order *all* alternatives
- Committee: difficult to *specify* a voting rule precisely and abstractly

Motivation and approach

Who?

- Imagine to be an *external observer* helping with the voting procedure

Why?

- Voters: difficult or costly to order *all* alternatives
- Committee: difficult to *specify* a voting rule precisely and abstractly

What?

- We want to reduce uncertainty, inferring (*eliciting*) the true preferences of voters and committee, in order to quickly converge to an optimal or a near-optimal alternative

Motivation and approach

Approach

- Develop query strategies that interleave questions to the committee and questions to the voters
- Use *Minimax regret* to measure the quality of those strategies

Motivation and approach

Approach

- Develop query strategies that interleave questions to the committee and questions to the voters
- Use *Minimax regret* to measure the quality of those strategies

Assumptions

- We consider *positional scoring rules*, which attach weights to positions according to a scoring vector w
- We assume w to be *convex*

$$w_i - w_{i+1} \geq w_{i+1} - w_{i+2} \quad \forall i$$

Related Works

Incomplete profile

- and known weights: Minimax regret to produce a robust winner approximation (*Lu and Boutilier 2011*, [2]; *Boutilier et al. 2006*, [1])

Uncertain weights

- and complete profile: dominance relations derived to eliminate alternatives always less preferred than others (*Stein et al. 1994*, [3])
- in positional scoring rules (*Viappiani 2018*, [4])

Context

A alternatives, $|A| = m$

N voters

$P = (\succsim_j, j \in N)$, $P \in \mathcal{P}$ complete preferences profile

$W = (\mathbf{w}_r, 1 \leq r \leq m)$, $W \in \mathcal{W}$ (convex) scoring vector that the committee has in mind

Context

A alternatives, $|A| = m$

N voters

$P = (\succ_j, j \in N)$, $P \in \mathcal{P}$ complete preferences profile

$W = (\mathbf{w}_r, 1 \leq r \leq m)$, $W \in \mathcal{W}$ (convex) scoring vector that the committee has in mind

W defines a Positional Scoring Rule $f_W(P) \subseteq A$ using scores $s^{W,P}(a)$, $\forall a \in A$

Context

A alternatives, $|A| = m$

N voters

$P = (\succ_j, j \in N)$, $P \in \mathcal{P}$ complete preferences profile

$W = (\mathbf{w}_r, 1 \leq r \leq m)$, $W \in \mathcal{W}$ (convex) scoring vector that the committee has in mind

W defines a Positional Scoring Rule $f_W(P) \subseteq A$ using scores $s^{W,P}(a)$, $\forall a \in A$

P and W exist in the minds of voters and committee but unknown to us

Questions

Questions

Questions to the voters

Comparison queries that ask a particular voter to compare two alternatives $a, b \in A$

$$a \succ_j b \quad ?$$

Questions

Questions to the voters

Comparison queries that ask a particular voter to compare two alternatives $a, b \in A$

$$a \succ_j b \quad ?$$

Questions to the committee

Queries relating the difference between the importance of consecutive ranks from r to $r + 2$

$$w_r - w_{r+1} \geq \lambda(w_{r+1} - w_{r+2}) \quad ?$$

Our Knowledge

The answers to these questions define C_P and C_W that is our knowledge about P and W

Our Knowledge

The answers to these questions define C_P and C_W that is our knowledge about P and W

- $C_P \subseteq \mathcal{P}$ constraints on the profile given by the voters

Our Knowledge

The answers to these questions define C_P and C_W that is our knowledge about P and W

- $C_P \subseteq \mathcal{P}$ constraints on the profile given by the voters
- $C_W \subseteq \mathcal{W}$ constraints on the voting rule given by the committee

Minimax Regret

Given $C_P \subseteq \mathcal{P}$ and $C_W \subseteq \mathcal{W}$:

$$\text{PMR}^{C_P, C_W}(a, b) = \max_{P \in C_P, W \in C_W} s^{P, W}(b) - s^{P, W}(a)$$

is the maximum difference of score between a and b under all possible realizations of the full profile *and* weights

Minimax Regret

Given $C_P \subseteq \mathcal{P}$ and $C_W \subseteq \mathcal{W}$:

$$\text{PMR}^{C_P, C_W}(a, b) = \max_{P \in C_P, W \in C_W} s^{P, W}(b) - s^{P, W}(a)$$

is the maximum difference of score between a and b under all possible realizations of the full profile *and* weights

We care about the worst case loss: *maximal regret* between a chosen alternative a and best real alternative b

Minimax Regret

Given $C_P \subseteq \mathcal{P}$ and $C_W \subseteq \mathcal{W}$:

$$\text{PMR}^{C_P, C_W}(a, b) = \max_{P \in C_P, W \in C_W} s^{P, W}(b) - s^{P, W}(a)$$

is the maximum difference of score between a and b under all possible realizations of the full profile *and* weights

We care about the worst case loss: *maximal regret* between a chosen alternative a and best real alternative b

We select the alternative which minimizes the maximal regret

Pairwise Max Regret Computation


The computation of $\text{PMR}^{C_P, C_W}(\text{broccoli}, \text{eggplant})$ can be seen as a game in which an adversary both:

Pairwise Max Regret Computation

The computation of $\text{PMR}^{C_P, C_W}(\text{broccoli}, \text{eggplant})$ can be seen as a game in which an adversary both:

- chooses a complete profile $\mathbf{P} \in \mathcal{P}$

Mickey Donald Goofy



Mickey Donald Goofy




Pairwise Max Regret Computation

The computation of $\text{PMR}^{C_P, C_W}(\text{broccoli}, \text{eggplant})$ can be seen as a game in which an adversary both:

- chooses a complete profile $\mathbf{P} \in \mathcal{P}$

Mickey Donald Goofy



Mickey Donald Goofy



- chooses a feasible weight vector $\mathbf{W} \in \mathcal{W}$


$$(1, ?, 0) \longrightarrow (1, 0, 0)$$

in order to maximize the difference of scores

Computing Minimax Regret: Example

Profile completion

Consider the following partial profile



Computing Minimax Regret: Example

Weight selection

Consider the following constraint on the scoring vector given by the committee

$$w_1 \geq 2 \cdot w_2$$

and the convex assumption

$$w_1 - w_2 \geq w_2 - w_3$$

Computing Minimax Regret: Example

Minimax computing

$$\text{MR}(\text{carrot}) = \max \left\{ \begin{array}{l} \text{PMR}(\text{carrot, broccoli}) = 19 \rightarrow v = \textcircled{3} \quad w = \{10, 1, 0\} \\ \text{PMR}(\text{carrot, eggplant}) = 9 \rightarrow v = \textcircled{2} \quad w = \{10, 1, 0\} \end{array} \right.$$

$$\text{MR}(\text{broccoli}) = \boxed{-1}$$

$$\text{MR}(\text{eggplant}) = 20$$

$$\boxed{\text{MMR}} = -1 \rightarrow \text{winner } \text{broccoli}$$

Elicitation strategies

At each step, the strategy selects a question to ask either to one of the voters about her preferences or to the committee about the voting rule

Elicitation strategies

At each step, the strategy selects a question to ask either to one of the voters about her preferences or to the committee about the voting rule

The termination condition could be:

Elicitation strategies

At each step, the strategy selects a question to ask either to one of the voters about her preferences or to the committee about the voting rule

The termination condition could be:

- when the minimax regret is lower than a threshold

Elicitation strategies

At each step, the strategy selects a question to ask either to one of the voters about her preferences or to the committee about the voting rule

The termination condition could be:

- when the minimax regret is lower than a threshold
- when the minimax regret is zero

Elicitation strategies

Random Strategy

Elicitation strategies

Random Strategy

Decides with a probability of $\frac{1}{2}$ each whether to ask a question about

Elicitation strategies

Random Strategy

Decides with a probability of $\frac{1}{2}$ each whether to ask a question about

- **weights:** it draws a rank $2 \leq r \leq m - 2$ equiprobably, takes λ as the middle of the interval of values we are still uncertain about, and asks whether $w_r - w_{r+1} \geq \lambda(w_{r+1} - w_{r+2})$

Elicitation strategies

Random Strategy

Decides with a probability of $\frac{1}{2}$ each whether to ask a question about

- **weights:** it draws a rank $2 \leq r \leq m - 2$ equiprobably, takes λ as the middle of the interval of values we are still uncertain about, and asks whether $w_r - w_{r+1} \geq \lambda(w_{r+1} - w_{r+2})$
- **a preference ordering:** it draws equiprobably a voter whose preference is not known entirely and two alternatives that are incomparable in our current knowledge

Elicitation strategies

Pessimistic Strategy

Elicitation strategies

Pessimistic Strategy

Assume that a question leads to the possible new knowledge states (C_P^1, C_W^1) and (C_P^2, C_W^2) depending on the answer, then the badness of the question in the worst case is:

$$\max_{i=1,2} \text{MMR}(C_P^i, C_W^i)$$

Elicitation strategies

Pessimistic Strategy

Assume that a question leads to the possible new knowledge states (C_P^1, C_W^1) and (C_P^2, C_W^2) depending on the answer, then the badness of the question in the worst case is:

$$\max_{i=1,2} \text{MMR}(C_P^i, C_W^i)$$

The pessimistic strategy selects the question that leads to minimal regret in the worst case

Elicitation strategies

Pessimistic Strategy

Assume that a question leads to the possible new knowledge states (C_P^1, C_W^1) and (C_P^2, C_W^2) depending on the answer, then the badness of the question in the worst case is:

$$\max_{i=1,2} \text{MMR}(C_P^i, C_W^i)$$

The pessimistic strategy selects the question that leads to minimal regret in the worst case

Note:

if the maximal MMR of two questions are equal, then prefers the one with the lowest MMR values associated to the opposite answer

Elicitation strategies

Two Phase Strategy

Elicitation strategies

Two Phase Strategy

- **phase one:** asks a predefined sequence of $m - 2$ questions to the committee in order to gather informations about the weights (one per rank except the extremes)

Elicitation strategies

Two Phase Strategy

- **phase one:** asks a predefined sequence of $m - 2$ questions to the committee in order to gather informations about the weights (one per rank except the extremes)
- **phase two:** asks only questions to the voters, using the mechanism defined in the Pessimistic strategy

Elicitation strategies

Extreme completions Strategy

Elicitation strategies

Extreme completions Strategy

Let x^* be the minimax regret optimal alternative, and \bar{y} , \bar{P} and \bar{W} the instantiations that, given the choice of x^* , maximize the regret. Define:

Elicitation strategies

Extreme completions Strategy

Let x^* be the minimax regret optimal alternative, and \bar{y} , \bar{P} and \bar{W} the instantiations that, given the choice of x^* , maximize the regret. Define:

$$\tau_W = \min_{W \in C_W} s^{\bar{P}, W}(\bar{y}) - s^{\bar{P}, W}(x^*)$$

$$\tau_{P_i} = \min_{\hat{P}_i \in C_P} s^{\hat{P}_i, \bar{W}}(\bar{y}) - s^{\hat{P}_i, \bar{W}}(x^*)$$

where \hat{P}_i is defined as \bar{P} except for i

Elicitation strategies

Extreme completions Strategy

Let x^* be the minimax regret optimal alternative, and \bar{y} , \bar{P} and \bar{W} the instantiations that, given the choice of x^* , maximize the regret. Define:

$$\tau_W = \min_{W \in C_W} s^{\bar{P}, W}(\bar{y}) - s^{\bar{P}, W}(x^*)$$

$$\tau_{P_i} = \min_{\hat{P}_i \in C_P} s^{\hat{P}_i, \bar{W}}(\bar{y}) - s^{\hat{P}_i, \bar{W}}(x^*)$$

where \hat{P}_i is defined as \bar{P} except for i

$\text{MMR} - \tau_W$ estimates the contribution to the regret of our uncertainty about the weights; $\text{MMR} - \tau_{P_i}$ estimates the uncertainty about the profile

Elicitation strategies

Extreme completions Strategy

Let x^* be the minimax regret optimal alternative, and \bar{y} , \bar{P} and \bar{W} the instantiations that, given the choice of x^* , maximize the regret. Define:

$$\tau_W = \min_{W \in C_W} s^{\bar{P}, W}(\bar{y}) - s^{\bar{P}, W}(x^*)$$

$$\tau_{P_i} = \min_{\hat{P}_i \in C_P} s^{\hat{P}_i, \bar{W}}(\bar{y}) - s^{\hat{P}_i, \bar{W}}(x^*)$$

where \hat{P}_i is defined as \bar{P} except for i

$\text{MMR} - \tau_W$ estimates the contribution to the regret of our uncertainty about the weights; $\text{MMR} - \tau_{P_i}$ estimates the uncertainty about the profile

The extreme completions strategy asks a question to whoever minimizes τ

Preliminary Results

k	Rnd \pm sd	T. ph. \pm sd	Pes. \pm sd
0	5.0 \pm 0	5.0 \pm 0	5.0 \pm 0
5	4.9 \pm 0.2	5.0 \pm 0.0	4.2 \pm 0.3
10	4.8 \pm 0.2	4.4 \pm 0.3	3.4 \pm 0.5
15	4.3 \pm 0.6	3.7 \pm 0.3	2.7 \pm 0.5
20	3.9 \pm 0.3	2.7 \pm 0.5	1.6 \pm 0.8
25	3.5 \pm 0.8	2.2 \pm 0.7	0.8 \pm 0.6
30	3.0 \pm 0.8	1.5 \pm 1.1	0.5 \pm 0.7

Table: Minimax regret in problems of size (5, 5) after k questions.

Thank You!



C. Boutilier, R. Patrascu, P. Poupart, and D. Schuurmans.
Constraint-based Optimization and Utility Elicitation using the
Minimax Decision Criterion.
Artificial Intelligence, 170(8–9):686–713, 2006.



Tyler Lu and Craig Boutilier.
Robust approximation and incremental elicitation in voting protocols.
In *Proceedings of IJCAI 2011*, pages 287–293, 2011.



William E. Stein, Philip J. Mizzi, and Roger C. Pfaffenberger.
A stochastic dominance analysis of ranked voting systems with
scoring.
European Journal of Operational Research, 74(1):78 – 85, 1994.



Paolo Viappiani.
Positional scoring rules with uncertain weights.
In *Scalable Uncertainty Management - 12th International Conference, SUM 2018, Milan, Italy, October 3-5, 2018, Proceedings*, pages 306–320, 2018.